

Product Data Sheet

No. **2937** - 08/19

TEF-LUBE™

VOC ≤ 25%, MIR <0.4 (Multi-Purpose Lubricant)

PRODUCT NUMBERS: 937 - 11 OZ. NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: Tef-Lube™ is a superior lubricant which combines the advantages of high-grade petroleum oils and solvents with micron-sized PTFE. This formula provides the finest multi-component penetrating lubricant system available.

Benefits: Tef-Lube's superior performance lubricates at high friction and load, breaks up corrosion, cleans and shields against dirt and contaminants. PTFE coating provides long-lasting protection against moisture.

Application: Sporting equipment, recreational sports vehicles, aircraft maintenance, automotive assemblies, office machines and home appliances. Use on chains, gears, bearings, sprockets, conveyors, electric motors and switches, locks, air tools, firearms, fishing reels, pipes, hinges, bolts, dies and any heavy duty metal-to-metal lubrication requirement.

Directions: Shake well before use. Hold can 5 to 10 inches from surface, spraying liberally and uniformly. The 937 has the Spray-Any-Way valve which allows product to be applied either in an upright or upside down position. Use the extension tube for hard-to-reach areas and pinpoint accuracy. For best results use at temperatures between 35° and 120° F (2° and 49° C). For heavily corroded parts, scrape and allow short time to penetrate. For use in the manufacturing process only. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc. Check surface compatibility by testing small area first, product may affect certain rubber, plastic and painted surfaces.

Packaging:

Aerosol:	Cans - (16 oz.)	12 oz. net wt. (340 g)	13.5 fl. oz. (400 mL)
	Case - 12 cans/case	14 lbs. (6.4 kg)	0.47 CF (0.013 CM)



AerVOE Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aerVOE.com • mailbox@aerVOE.com

II. CHARACTERISTICS & PROPERTIES

Specifications:

Mil-C372B (Small arms bore cleaner), Mil-C-81309 (Corrosion preventive compound), VV-P-216B (Penetrating oil), VV-L-820C (Lubricating oil), VV-L-751C (Chain, wire rope lubricating oil).

Appearance:

Thin, non-foaming, wet film

Color:

Transparent and slightly amber

Odor:

Mild, sweet

Dry Schedule:

N/A

Performance and Chemical Properties:

Aerosol

Weight per gallon	6.65 lbs.
Specific gravity	0.88
Viscosity in centipoise @ 104° F (40°)	17
Viscosity in centipoise @ 212° F (100°)	6
Flammability: Label marking	Extremely Flammable
Flash point	<0°F (-18°C)
Operating temperature range	40°F to 110°F (5° to 43°C)
Active ingredients by weight	48%
Volatile Organic Compound Level	24.5%
EPA VOC% limit	Not Regulated
CARB VOC% limit (multi-purpose lubricant)	<25% with MIR <0.4
Pour point	N/A
Dielectric strength	19 kV/mm
Lubricity (FALEX FLC Test)	>100 ft. lbs.
Penetrating ability	Excellent
Corrosion protection	Excellent
Food contact rating	N/A

Base Materials: Petroleum Oil, PTFE

Propellant: Hydrocarbon Propellant

III. SHIPPING, STORAGE AND HEALTH

UN number	UN1950
Proper Shipping Description	Aerosols
Hazard Class	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 2
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 3 years

HMIS ratings

Health	2
Fire	4
Reactivity	1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year performance warranty on all products from date of purchase. Report to home office or local Aerove representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.