

## Commercial Air Circulators - 115V

### Pedestal & Wall / Vertical Mount Unit Packs

Non-Oscillating



Adjustable Floor Model  
Solid Base



Vertical Mount



Wall Mount

#### 2 Year Warranty

#### Features

- 115V, 1/4 HP, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.
- Unit Pack ships with Motor, Specified Style Mounting, Propeller & Guard In One Carton
- Pedestal Models Adjust 43" - 63" ; 26" Base Diameter
- Wall / Vertical Mount Models Include Safety Cable
- 15' Supply Cord and Three Prong Plug Included
- Models are UPS Shippable in One Carton
- Guard Meets OSHA Standards
- Galvanized Steel Propeller
- All Stocked



Type	Tilt (In Degrees) Non-Oscillating	
	Up	Down
Floor	30°	15°
Wall	30°	50°
Vertical	0°	90°

0° = Horizontal Plane

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	CFM			RPM			F.L. Amps	Ship Wt.
					High	Med	Low	High	Med	Low		
71584	CA24APE	24"	Adjustable Floor (S.B.)	1/4								
71572	CA24WC	24"	Wall / Vertical Mount	1/4	4400	3460	2460	1100	800	600	3.5	82
71586	CA30APE	30"	Adjustable Floor (S.B.)	1/4								42
71573	CA30WC	30"	Wall / Vertical Mount	1/4	6100	4400	2700	1100	800	600	3.5	87
												49

### Non-Oscillating Assembled Fan Heads



#### Features

- Motor, Guard, and Propeller are Pre-Assembled
- 30" Head Assembly is UPS OverSize 2


EDP No.	Catalog No.	Prop Dia.	HP	Ship Wt.
71590	CA24	24"	1/4	39
71591	CA30	30"	1/4	48



## Commercial Air Circulators

### Component Parts / Accessories

#### Motors



EDP No.	Catalog No.	Ship Wt.	Description
78018	C-1A	19	Commercial Non-Oscillating motor, 1/4 HP, 3.5 Amp, 1 Phase, 3 Speed, TEAO, ball bearing 5/8" diameter shaft, 15' power cord.
37430	0-3B	23	Commercial Oscillating motor, 1/4 HP, 1 Phase, 3 Speed, 115V, 2.8 Amps, TEAO ball bearing, 5/8" diameter shaft. <b>NOTE:</b> Oscillating motor <b>not</b> to be used in <b>UPSIDE-DOWN</b> position.

#### Capacitors


EDP No.	Catalog No.	Ship Wt.	Description
01683	Capacitor	1	Capacitor - 8 MFD (for 78018 motors)
01430	Capacitor	1	Capacitor - 20 MFD (for 37430 motors)

#### Pedestals



EDP No.	Catalog No.	Ship Wt.	Description
73103	C-2030NP	7	5' high floor model. Top section provides 33 1/2" counter model. Use only with I-2030B Base. (1)
73101	I-2030AP	12	5' to 8' adjustable floor model. (2)

#### Bases



EDP No.	Catalog No.	Ship Wt.	Description
21153	I-2030B	24	Open base. (1)
21165	A-786B-1	17	Solid base, 26" diameter. (2)
21166	A786B-2	34	Solid base, 32" diameter. (2)

#### Wall / Vertical Mount Bracket




EDP No.	Catalog No.	Ship Wt.	Description
75002	C-2030W	5	Use with non-oscillating commercial air circulators. Safety Cable Kit Included. <b>NOT FOR USE WITH OSCILLATING MOTORS.</b>

#### Wall Mount Bracket



EDP No.	Catalog No.	Ship Wt.	Description
37772	IAC-WB	7	Recommended for use with oscillating and non-oscillating motors. Includes Safety Cable Kit.

#### Vertical Mount Bracket



EDP No.	Catalog No.	Ship Wt.	Description
11456	DJ-CM	7	Vertical mount for use with industrial 20", 24", and 30" non-oscillating fans. Safety Cable Kit Included <b>NOT FOR USE WITH OSCILLATING MOTORS</b>



### Component Parts / Accessories

#### Suspension Mount Bracket



EDP No.	Catalog No.	Ship Wt.	Description
75003	C-2030S	3	Use with commercial & industrial non-oscillating air circulators. Includes Safety Cable Kit.

#### I-Beam Mount Bracket



EDP No.	Catalog No.	Ship Wt.	Description
37784	IAC-BM-1	13	For use with I-Beam mounting. Includes Safety Cable Kit. <b>NOT FOR USE WITH OSCILLATING MOTORS</b>

#### Safety Cable



EDP No.	Catalog No.	Ship Wt.	Description
21204	Safety Kit	3	12' of 1/16" diameter cable, two (2) cable clamps and instructions.

#### Accessories



EDP No.	Catalog No.	Ship Wt.	Description
70601	AMFW30K	5	Snap-on wheel kit with set screw lock for 18" to 30" pedestal fans, except I-2030B.
01723	Switch	2	2 Speed / 3 Speed Pull Chain Switch

#### Guards



EDP No.	Catalog No.	Ship Wt.	Description
21070	AC24-G	14	24" guard.
21080	AC30-G	20	30" guard.

#### Propellers



EDP No.	Catalog No.	Ship Wt.	Description
72458	C-24B2	5	24" Propeller with 5/8" bore, includes bushing to adapt propeller to fit motors with 1/2" shaft
73058	C-30B	7	30" Propeller with 5/8" bore, includes bushing to adapt propeller to fit motors with 1/2" shaft

## Pedestal & Wall / Vertical Mounts

Non-Oscillating



### 1 Year Warranty

#### Features

- 120V, 1 Phase, 2 Speed, 1/4 HP, Open Ventilated, Ball Bearing Motor
- Permanently lubricated permanent split capacitor
- Pull Chain, SJT type 3 conductor, 9½' long cord
- Pedestal adjusts center of fan from 44" to 62"
- Epoxy coated steel guard with retaining clips
- Wall / Vertical mount includes safety cable
- Meets OSHA Standards
- Aluminum blades



EDP No.	Catalog No.	Prop Dia.	Fan Style	CFM		RPM		F.L. Amps	Ship Wt.
				High	Low	High	Low		
71531	LC30AP	30"	Pedestal Mount	6000	5500	1100	800	2.1	62
71533	LC30WC	30"	Wall / Vertical Mount						37

Because these circulators do not have totally enclosed motors, they should be used in clean and dry commercial applications, such as schools, offices or warehouses.

## Belt Drive Portable Mancooler®



### 1 Year Warranty

#### Features

- 115V, 1 HP, 1 Phase, 2 Speed, 630 Watts, ODP, Ball Bearing Motor
- Epoxy Coated Steel Guards and Housing
- Aluminum Four Bladed Propeller
- Grounded Plug and 10' Cord
- Full Width Easy Grip Handle
- Two Speed Rocker Switch
- Velocity: 159 fpm @ 90 ft.
- Fully Assembled
- 8" Steel Wheels



EDP No.	Catalog No.	Prop Dia.	HP	CFM		RPM		dBA		Ship Wt.
				High	Low	High	Low	High	Low	
78933	LC42BD	42"	1	13036	11850	582	517	70	66	103



**Warning: Cancer and Reproductive Harm** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)  
This warning is applicable to all products on this page, see page i2 for more information