

Supreno® SE SU-690

Durable Nitrile Exam Glove with Advanced Barrier Protection



Sturdy protection for demanding jobs

- Durable nitrile formulation for demanding jobs
- Sturdy design for longer wear times
- Exceptional barrier integrity with 0.65 AQL for allowable pinholes
- Textured fingertips provide secure grip



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare
- Agriculture
- Emergency Medical Services
- Utilities
- Warehousing

Recommended For

- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Assembly of parts
- Sample taking and processing
- Raw material sample collection
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients





TECHNICAL DATA SHEET

| | Product Information |
|-----------------------------|--|
| External Glove Surface | Textured Fingers |
| Audit Standards | EN ISO 13485:2012 |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Robust |
| Antistatic | Yes |

PHYSICAL PROPERTIES

| | Typical | Testing Method | |
|---|---------------------|-----------------------|---------------------|
| Length (mm/inches) | 245 / | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 0.65 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils) | 0.11 / 4.3 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.18 / 7.1 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 32 | 27 | ASTM D412 & D573 |
| Elongation at Break (%) | 550 | 500 | ASTM D412 |
| Force at break (N) | 12 | 9 | EN 455-2 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | SU-690-XS | SU-690-S | SU-690-M | SU-690-L | SU-690-XL |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Ansell