



COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.975	24.77	72366S	4.00	101.6	.827	21.0	5.3	.92	2.6	65	13	60	.85	21.6	0.074	1.9	11.5	SST	CG	N
0.975	24.77	72378	4.00	101.6	.813	20.7	9.7	1.7	2.7	69	26	117	.89	22.6	0.081	2.1	11.0	MW	CG	N
0.975	24.77	72378S	4.00	101.6	.813	20.7	8.2	1.4	2.1	54	18	78	.89	22.6	0.081	2.1	11.0	SST	CG	N
0.975	24.77	72393	4.00	101.6	.805	20.4	12	2.2	2.4	62	30	134	.89	22.7	0.085	2.2	10.5	MW	CG	N
0.975	24.77	72393S	4.00	101.6	.805	20.4	11	1.9	1.9	49	20	90	.89	22.7	0.085	2.2	10.5	SST	CG	N
0.975	24.77	72402	4.00	101.6	.791	20.1	13	2.3	2.8	70	36	159	1.24	31.5	0.092	2.3	13.5	MW	CG	N
0.975	24.77	72402S	4.00	101.6	.791	20.1	11	1.9	2.2	56	24	108	1.24	31.5	0.092	2.3	13.5	SST	CG	N
0.975	24.77	72414	4.00	101.6	.783	19.9	16	2.8	2.6	65	42	185	1.26	32.0	0.096	2.4	13.1	MW	CG	N
0.975	24.77	72414S	4.00	101.6	.783	19.9	14	2.4	2.0	51	28	123	1.26	32.0	0.096	2.4	13.1	SST	CG	N
0.975	24.77	72426	4.00	101.6	.765	19.4	22	3.9	2.4	62	54	241	1.46	37.0	0.105	2.7	13.9	MW	CG	N
0.975	24.77	72426S	4.00	101.6	.765	19.4	19	3.3	1.9	48	36	160	1.46	37.0	0.105	2.7	13.9	SST	CG	N
0.975	24.77	72439	4.00	101.6	.751	19.1	29	5.0	2.2	56	63	281	1.60	40.5	0.112	2.8	14.3	MW	CG	N
0.975	24.77	72439S	4.00	101.6	.751	19.1	24	4.3	1.7	43	41	184	1.60	40.5	0.112	2.8	14.3	SST	CG	N
0.975	24.77	72446	4.00	101.6	.745	18.9	32	5.6	2.1	54	68	304	1.65	42.0	0.115	2.9	14.4	MW	CG	N
0.975	24.77	72446S	4.00	101.6	.745	18.9	27	4.8	1.6	42	45	199	1.65	42.0	0.115	2.9	14.4	SST	CG	N
0.975	24.77	72454	4.00	101.6	.735	18.7	38	6.7	2.0	52	77	344	1.74	44.2	0.120	3.0	14.5	MW	CG	N
0.975	24.77	72454S	4.00	101.6	.735	18.7	32	5.7	1.6	40	51	225	1.74	44.2	0.120	3.0	14.5	SST	CG	N
0.975	24.77	72466	4.00	101.6	.725	18.4	44	7.7	2.0	51	87	388	1.89	48.0	0.125	3.2	15.1	MW	CG	N
0.975	24.77	72466S	4.00	101.6	.725	18.4	37	6.5	1.5	39	57	253	1.89	48.0	0.125	3.2	15.1	SST	CG	N
0.975	24.77	72474	4.00	101.6	.705	17.9	58	10	1.8	46	106	473	2.14	54.4	0.135	3.4	15.9	MW	CG	N
0.975	24.77	72474S	4.00	101.6	.705	17.9	50	8.7	1.4	35	68	304	2.14	54.4	0.135	3.4	15.9	SST	CG	N
0.975	24.77	72481	4.00	101.6	.679	17.2	87	15	1.6	40	139	617	2.37	60.1	0.148	3.8	16.0	MW	CG	N
0.975	24.77	72481S	4.00	101.6	.679	17.2	74	13	1.2	31	89	397	2.37	60.1	0.148	3.8	16.0	SST	CG	N
0.975	24.77	72487	4.00	101.6	.651	16.5	133	23	1.3	34	176	782	2.57	65.3	0.162	4.1	15.9	MW	CG	N
0.975	24.77	72487S	4.00	101.6	.651	16.5	113	20	.99	25	111	496	2.57	65.3	0.162	4.1	15.9	SST	CG	N
0.984	24.99	3336	.72	18.2	.794	20.2	111	19	.26	6.5	29	127	.33	8.4	0.095	2.4	3.50	SPR	CG	Z
0.984	24.99	2832	.81	20.6	.800	20.3	97	17	.38	9.5	36	162	.41	10.5	0.092	2.3	3.50	MW	C	Z
0.984	24.99	12579	.81	20.6	.794	20.2	111	19	.26	6.5	29	127	.33	8.5	0.095	2.4	3.50	SPR	CG	Z
0.984	24.99	S-3104	.88	22.2	.904	23.0	1.3	.22	.64	16	.81	3.6	.24	6.1	0.040	1.0	5.00	SST	C	N
0.984	24.99	10652	.94	23.8	.824	20.9	29	5.1	.48	12	14	62	.46	11.7	0.080	2.0	4.75	SPR	C	GI
0.984	24.99	1659	1.00	25.4	.860	21.8	11	1.9	.66	17	7.1	32	.34	8.7	0.062	1.6	4.50	SPR	C	Z
0.984	24.99	11942	1.00	25.4	.792	20.1	44	7.6	.42	11	18	82	.58	14.6	0.096	2.4	6.00	SPR	CG	Z
0.984	24.99	2635	1.00	25.4	.690	17.5	763	134	.18	4.5	135	600	.51	13.1	0.147	3.7	3.50	MW	CG	Z
0.984	24.99	3146	1.03	26.2	.894	22.7	2.5	.43	.81	21	2.0	8.9	.22	5.6	0.045	1.1	5.00	SPR	CG	Z
0.984	24.99	1513	1.06	27.0	.914	23.2	1.0	.18	.87	22	.88	3.9	.19	4.9	0.035	0.9	4.50	HD	C	Z
0.984	24.99	B12-24	1.06	27.0	.890	22.6	2.8	.50	.83	21	2.4	10	.24	6.0	0.047	1.2	5.00	SPR	CG	N
0.984	24.99	S-1048	1.19	30.2	.840	21.3	15	2.6	.83	21	12	54	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.984	24.99	322	1.19	30.2	.824	20.9	30	5.2	.60	15	18	80	.45	11.5	0.080	2.0	4.67	SPR	C	GI
0.984	24.99	S-3087	1.25	31.8	.894	22.7	3.1	.54	1.0	26	3.2	14	.23	5.7	0.045	1.1	4.00	SST	C	N
0.984	24.99	3402	1.25	31.8	.656	16.7	539	94	.24	6.1	129	574	.90	22.9	0.164	4.2	5.50	SPR	CG	Z
0.984	24.99	11866	1.31	33.3	.862	21.9	13	2.2	.67	17	8.4	38	.31	7.7	0.061	1.5	4.00	SPR	C	N
0.984	24.99	12041	1.34	34.1	.674	17.1	485	85	.23	5.7	110	488	.78	19.7	0.155	3.9	5.00	SPR	CG	Z
0.984	24.99	S-183	1.41	35.7	.784	19.9	53	9.2	.58	15	31	137	.55	14.0	0.100	2.5	5.50	SST	CG	N
0.984	24.99	S-3084	1.47	37.3	.814	20.7	26	4.5	.78	20	20	89	.47	11.9	0.085	2.2	5.50	SST	CG	N
0.984	24.99	12205	1.50	38.1	.800	20.3	32	5.6	.81	20	26	116	.60	15.2	0.092	2.3	6.50	SPR	CG	Z
0.984	24.99	2599	1.50	38.1	.774	19.7	57	10	.67	17	38	171	.68	17.3	0.105	2.7	6.50	SPR	CG	Z
0.984	24.99	12704	1.63	41.3	.796	20.2	40	7.0	.97	25	38	171	.66	16.7	0.094	2.4	6.00	MW	C	N
0.984	24.99	S-1570	1.72	43.6	.916	23.3	.53	.09	1.5	38	.79	3.5	.23	5.8	0.034	0.9	5.75	SST	C	N
0.984	24.99	10861	1.75	44.5	.914	23.2	.60	.10	1.5	38	.90	4.0	.24	6.0	0.035	0.9	5.75	SST	C	N
0.984	24.99	II-78	1.75	44.5	.704	17.9	153	27	.55	14	84	372	1.12	28.4	0.140	3.6	8.00	SPR	CG	Z
0.984	24.99	S-470	1.78	45.2	.688	17.5	209	37	.42	11	89	394	1.04	26.3	0.148	3.8	7.00	SST	CG	N
0.984	24.99	S-1201	1.81	46.0	.814	20.7	9.0	1.6	.79	20	7.1	32	1.02	25.9	0.085	2.2	12.0	SST	CG	N
0.984	24.99	3862	1.88	47.6	.774	19.7	37	6.4	.93	24	34	152	.95	24.0	0.105	2.7	9.00	HD	CG	Z
0.984	24.99	B18-199	2.09	53.2	.784	19.9	31	5.4	1.0	25	31	137	.90	22.9	0.100	2.5	8.00	SST	C	N
0.984	24.99	12427	2.16	54.8	.884	22.5	3.3	.57	1.3	34	4.4	20	.30	7.6	0.050	1.3	5.00	SST	C	N
0.984	24.99	S-1590	2.25	57.2	.906	23.0	.58	.10	1.9	48	1.1	4.9	.35	8.9	0.039	1.0	8.00	SST	C	N
0.984	24.99	10395	2.25	57.2	.834	21.2	15	2.7	.98	25	15	66	.53	13.3	0.075	1.9	6.00	SPR	C	Z
0.984	24.99	11673	2.38	60.3	.686	17.4	187	33	.54	14	100	446	1.27	32.2	0.149	3.8	8.50	SPR	CG	Z
0.984	24.99	M-141	2.47	62.7	.484	12.3	2367	414	.16	4.1	385	1714	2.00	50.8	0.250	6.4	8.00	SPR	CG	Z
0.984	24.99	11752	2.50	63.5	.824	20.9	10	1.7	1.7	43	17	75	.80	20.3	0.080	2.0	10.0	SPR	CG	Z
0.984	24.99	2622	2.72	69.0	.600	15.2	562	98	.34	8.7	193	859	1.73	43.9	0.192	4.9	9.00	SPR	CG	Z
0.984	24.99	4371	3.00	76.2	.814	20.7	12	2.1	1.8	46	21	95	.91	23.2	0.085	2.2	10.8	SPR	CG	Z
0.984	24.99	1807	3.00	76.2	.774	19.7	22	3.9	1.6	40	35	157	1.42	36.0	0.105	2.7	13.5	HD	CG	Z
0.984	24.99	10429	3.50	88.9	.758	19.3	31	5.4	1.5	38	46	205	1.53	38.7	0.113	2.9	13.5	SPR	CG	Z
0.984	24.99	3188	3.63	92.1	.890	22.6	1.1	.19	3.1	79	3.3	15	.52	13.1	0.047	1.2	10.0	SPR	C	Z
0.984	24.99	10586	3.75	95.3	.820	20.8	6.0	1.1	2.5	64	15	68	1.23	31.2	0.082	2.1	15.0	SST	CG	N
0.984	24.99	11623	4.00	101.6	.626	15.9	189	33	.88	22	166	737	3.04	77.3	0.179	4.5	17.0	SPR	CG	Z
0.984	24.99	11630	4.00	101.6	.624	15.8	194	34	.83	21	161	715	3.06	77.7	0.180	4.6	17.0	SPR	CG	Z




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH	
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
1.000	25.40	S-1360	1.00	25.4	.880	22.4	9.8	1.7	.70	18	6.8	30	.30	7.6	0.060	1.5	4.00	SST	C	N	
1.000	25.40	11763	1.00	25.4	.876	22.3	8.6	1.5	.63	16	5.4	24	.37	9.4	0.062	1.6	5.00	SPR	C	Z	
1.000	25.40	12402	1.00	25.4	.852	21.6	22	3.8	.00	.00	.00	.00	.41	10.3	0.074	1.9	4.50	DD	C	N	
1.000	25.40	11534	1.00	25.4	.840	21.3	23	4.1	.50	13	12	52	.50	12.7	0.080	2.0	5.25	SPR	CG	Z	
1.000	25.40	11548	1.00	25.4	.808	20.5	66	12	.44	11	29	129	.53	13.4	0.096	2.4	4.50	SPR	CG	Z	
1.000	25.40	11805	1.00	25.4	.790	20.1	216	38	.16	4.1	35	156	.32	8.0	0.105	2.7	3.00	SST	CG	N	
1.000	25.40	27	1.00	25.4	.730	18.5	268	47	.28	7.0	74	330	.64	16.3	0.135	3.4	4.75	HD	CG	Z	
1.000	25.40	4341	1.13	28.6	.804	20.4	52	9.0	.59	15	30	135	.54	13.7	0.098	2.5	5.50	SPR	CG	Z	
1.000	25.40	S-1599	1.16	29.4	.852	21.6	19	3.4	.68	17	13	58	.41	10.3	0.074	1.9	4.50	SST	C	N	
1.000	25.40	3854	1.19	30.2	.750	19.1	140	24	.44	11	61	271	.72	18.3	0.125	3.2	5.75	SPR	CG	Z	
1.000	25.40	10164	1.25	31.8	.750	19.1	175	31	.35	8.9	61	271	.63	15.9	0.125	3.2	5.00	SPR	CG	Z	
1.000	25.40	10251	1.25	31.8	.750	19.1	190	33	.32	8.1	61	271	.59	15.1	0.125	3.2	4.75	SPR	CG	Z	
1.000	25.40	Q-82	1.34	34.1	.814	20.7	29	5.0	.69	18	20	89	.65	16.5	0.093	2.4	7.00	SPR	CG	N	
1.000	25.40	S-899	1.38	34.9	.930	23.6		.52	.09	1.1	29	.59	2.6	.25	6.2	0.035	0.9	6.00	SST	C	N
1.000	25.40	OO-90	1.38	34.9	.892	22.7	6.3	1.1	.87	22	5.4	24	.27	6.9	0.054	1.4	4.00	SST	CG	N	
1.000	25.40	S-53	1.38	34.9	.840	21.3	17	3.0	.91	23	15	68	.47	11.9	0.080	2.0	6.00	SST	CG	N	
1.000	25.40	S-1573	1.50	38.1	.892	22.7	3.7	.64	1.2	31	4.4	20	.30	7.5	0.054	1.4	5.50	SST	CG	N	
1.000	25.40	2864	1.50	38.1	.790	20.1	54	9.5	.70	18	38	168	.68	17.3	0.105	2.7	6.50	HD	CG	Z	
1.000	25.40	10969	1.50	38.1	.646	16.4	595	104	.27	6.8	158	704	1.11	28.2	0.177	4.5	6.25	HD	CG	BO	
1.000	25.40	S-75	1.72	43.6	.790	20.1	41	7.2	.85	22	35	156	.76	19.3	0.105	2.7	7.25	SST	CG	N	
1.000	25.40	10791	1.75	44.5	.930	23.6		.57	.10	1.5	38	.86	3.8	.24	6.0	0.035	0.9	5.75	SST	C	N
1.000	25.40	12523	1.75	44.5	.884	22.5	4.9	.85	1.4	36	6.8	30	.35	8.8	0.058	1.5	6.00	SPR	CG	Z	
1.000	25.40	912	1.75	44.5	.876	22.3	5.7	1.0	1.3	33	7.3	33	.47	11.8	0.062	1.6	6.50	MW	C	Z	
1.000	25.40	11812	1.75	44.5	.868	22.0	7.4	1.3	1.3	34	9.8	44	.43	10.9	0.066	1.7	6.50	SPR	CG	Z	
1.000	25.40	11751	1.75	44.5	.840	21.3	22	3.8	.82	21	18	78	.44	11.2	0.080	2.0	5.50	SPR	CG	Z	
1.000	25.40	11832	1.75	44.5	.790	20.1	41	7.2	.85	22	35	156	.76	19.3	0.105	2.7	7.25	SST	CG	N	
1.000	25.40	3935	1.75	44.5	.760	19.3	87	15	.62	16	54	241	.84	21.3	0.120	3.0	7.00	SPR	CG	Z	
1.000	25.40	S-3033	1.75	44.5	.704	17.9	194	34	.45	11	87	388	1.04	26.3	0.148	3.8	7.00	SST	CG	N	
1.000	25.40	12260	1.78	45.2	.840	21.3	15	2.6	1.1	29	17	77	.64	16.3	0.080	2.0	7.00	SPR	C	Z	
1.000	25.40	S-3195	1.88	47.6	.798	20.3	52	9.1	.60	15	31	139	.56	14.1	0.101	2.6	5.50	SST	CG	N	
1.000	25.40	10561	1.94	49.2	.818	20.8	22	3.8	1.1	27	23	102	.67	16.9	0.091	2.3	7.33	SST	CG	N	
1.000	25.40	S-1485	2.00	50.8	.918	23.3	1.3	.23	1.8	45	2.3	10	.25	6.2	0.041	1.0	5.00	SST	C	N	
1.000	25.40	S-3021	2.00	50.8	.876	22.3	3.7	.65	1.5	38	5.6	25	.50	12.6	0.062	1.6	8.00	SST	CG	N	
1.000	25.40	2767	2.00	50.8	.840	21.3	14	2.5	1.2	32	18	78	.59	14.9	0.080	2.0	7.33	HD	CG	Z	
1.000	25.40	10091	2.00	50.8	.818	20.8	26	4.6	.94	24	25	110	.73	18.5	0.091	2.3	7.00	SPR	C	Z	
1.000	25.40	1771	2.00	50.8	.760	19.3	109	19	.69	18	76	336	.84	21.3	0.120	3.0	6.00	MW	C	Z	
1.000	25.40	10321	2.03	51.6	.774	19.7	75	13	.61	15	45	202	.73	18.7	0.113	2.9	6.50	SPR	CG	Z	
1.000	25.40	10006	2.09	53.2	.676	17.2	240	42	.51	13	123	546	1.46	37.0	0.162	4.1	9.00	SPR	CG	Z	
1.000	25.40	S-3226	2.13	54.0	.816	20.7	17	3.1	1.2	31	21	93	.92	23.4	0.092	2.3	9.00	SST	C	N	
1.000	25.40	B17-189	2.13	54.0	.540	13.7	1469	257	.29	7.2	419	1862	1.84	46.7	0.230	5.8	8.00	MW	CG	Z	
1.000	25.40	2662	2.16	54.8	.730	18.5	148	26	.50	13	74	330	.95	24.0	0.135	3.4	7.00	SPR	CG	Z	
1.000	25.40	S-395	2.19	55.6	.898	22.8	3.3	.58	1.4	35	4.6	20	.31	7.8	0.051	1.3	5.00	SST	C	N	
1.000	25.40	S-1386	2.19	55.6	.892	22.7	3.1	.55	1.7	44	5.4	24	.38	9.6	0.054	1.4	6.00	SST	C	N	
1.000	25.40	S-3056	2.25	57.2	.910	23.1	1.2	.21	1.9	48	2.2	9.9	.36	9.1	0.045	1.1	7.00	SST	C	N	
1.000	25.40	S-1147	2.25	57.2	.876	22.3	4.7	.83	1.7	44	8.2	36	.42	10.6	0.062	1.6	6.75	SST	CG	N	
1.000	25.40	11391	2.25	57.2	.860	21.8	6.1	1.1	1.6	39	9.5	42	.70	17.8	0.070	1.8	9.00	SPR	C	Z	
1.000	25.40	FF-79	2.25	57.2	.820	20.8	16	2.7	1.4	34	21	94	.90	22.9	0.090	2.3	10.0	SPR	CG	N	
1.000	25.40	S-106	2.25	57.2	.706	17.9	171	30	.50	13	86	381	1.10	28.0	0.147	3.7	7.50	SST	CG	N	
1.000	25.40	11912	2.28	57.9	.878	22.3	4.3	.75	1.8	47	7.8	35	.43	10.8	0.061	1.5	7.00	SST	CG	N	
1.000	25.40	10697	2.31	58.7	.814	20.7	18	3.1	1.3	32	22	99	1.04	26.5	0.093	2.4	10.5	SPR	C	N	
1.000	25.40	S-293	2.38	60.3	.790	20.1	30	5.3	1.2	29	35	156	.95	24.0	0.105	2.7	9.00	SST	CG	N	
1.000	25.40	4141	2.38	60.3	.760	19.3	58	10	.93	24	54	241	1.26	32.0	0.120	3.0	9.50	SPR	C	Z	
1.000	25.40	DD-67	2.50	63.5	.860	21.8	5.4	.94	1.8	46	9.7	43	.70	17.8	0.070	1.8	10.0	SPR	CG	Z	
1.000	25.40	B17-184	2.50	63.5	.800	20.3	28	4.9	1.6	41	45	200	.90	22.9	0.100	2.5	9.00	MW	CG	GI	
1.000	25.40	375	2.50	63.5	.790	20.1	35	6.1	1.1	28	38	168	1.05	26.7	0.105	2.7	9.00	HD	C	Z	
1.000	25.40	71	2.50	63.5	.760	19.3	55	9.6	.99	25	54	241	1.20	30.5	0.120	3.0	10.0	HD	CG	Z	
1.000	25.40	S-408	2.59	65.9	.676	17.2	260	45	.42	11	109	485	1.26	31.9	0.162	4.1	7.75	SST	CG	N	
1.000	25.40	4311	2.63	66.7	.704	17.9	131	23	.74	19	97	431	1.55	39.5	0.148	3.8	10.5	SPR	CG	Z	
1.000	25.40	10964	2.72	69.0	.750	19.1	62	11	.87	22	53	238	1.85	47.0	0.125	3.2	10.5	HD	CG	Z	
1.000	25.40	2587	2.75	69.9	.866	22.0	5.9	1.0	1.8	47	11	49	.54	13.6	0.067	1.7	8.00	HD	CG	Z	
1.000	25.40	12477	2.75	69.9	.840	21.3	9.5	1.7	1.9	47	18	78	.80	20.3	0.080	2.0	10.0	SPR	CG	Z	
1.000	25.40	4207	2.88	73.0	.816	20.7	15	2.7	1.7	43	26	114	1.01	25.7	0.092	2.3	11.0	SPR	CG	Z	
1.000	25.40	10358	2.94	74.6	.750	19.1	58	10	1.0	27	61	271	1.38	34.9	0.125	3.2	11.0	SPR	CG	Z	
1.000	25.40	EE-56	3.00	76.2	.880	22.4	2.7	.46	2.4	60	6.3	28	.63	16.0	0.060	1.5	9.50	SST	C	N	
1.000	25.40	10741	3.00	76.2	.876	22.3	2.0	.35	2.1	53	4.1	18	.93	23.6	0.062	1.6	15.0	SPR	CG	N	
1.000	25.40	11135	3.00	76.2	.816	20.7	11	1.9	1.7	44	19	84	1.27	32.4	0.092	2.3	14.0	HD	CG	Z	
1.000	25.40	3357	3.00	76.2	.782	19.9	29	5.0	1.5	37	42	188	1.31	33.2	0.109	2.8	12.0	SPR	CG	Z	
1.000	25.40	57	3.00	76.2	.760	19.3	45	7.9	1.2	31	54	241	1.41	35.8	0.120	3.0	11.8	HD	CG	Z	
1.000	25.40	7052	3.00	76.2	.744	18.9															

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.000	25.40	3111	3.63	92.1	.914	23.2	.93	.16	3.3	83	3.1	14	.34	8.7	0.043	1.1	8.00	SPR	CG	Z
1.000	25.40	2716	3.75	95.3	.856	21.7	3.9	.68	2.6	67	10	45	1.12	28.3	0.072	1.8	14.5	SPR	C	Z
1.000	25.40	2968	3.75	95.3	.790	20.1	27	4.7	1.4	35	38	168	1.26	32.0	0.105	2.7	11.0	SPR	C	Z
1.000	25.40	4228	3.75	95.3	.712	18.1	90	16	1.0	25	89	398	2.02	51.2	0.144	3.7	13.0	SPR	C	Z
1.000	25.40	4356	3.94	100.0	.830	21.1	6.5	1.1	2.5	63	16	72	1.45	36.7	0.085	2.2	17.0	SPR	CG	Z
1.000	25.40	10548	4.00	101.6	.838	21.3	12	2.1	1.5	38	18	81	.69	17.5	0.081	2.1	8.50	SPR	CG	Z
1.000	25.40	10777	4.00	101.6	.820	20.8	9.8	1.7	2.4	62	24	107	1.33	33.7	0.090	2.3	14.8	SPR	CG	N
1.000	25.40	11615	4.19	106.4	.820	20.8	9.6	1.7	2.5	63	24	107	1.44	36.6	0.090	2.3	15.0	SPR	CG	Z
1.000	25.40	10248	4.25	108.0	.812	20.6	16	2.8	1.7	44	27	121	1.18	29.8	0.094	2.4	11.5	SPR	C	Z
1.000	25.40	12556	4.45	113.0	.734	18.6	53	9.3	1.2	30	64	285	1.90	48.1	0.133	3.4	13.3	SST	C	N
1.000	25.40	7001	4.50	114.3	.760	19.3	25	4.4	2.1	53	53	234	2.40	61.0	0.120	3.0	19.5	HD	C	Z
1.000	25.40	656	4.50	114.3	.646	16.4	153	27	1.0	26	158	704	3.27	83.2	0.177	4.5	18.5	HD	CG	Z
1.000	25.40	1949	4.69	119.0	.704	17.9	74	13	1.3	33	97	431	2.52	63.9	0.148	3.8	17.0	SPR	CG	Z
1.000	25.40	4365	4.75	120.7	.840	21.3	6.0	1.1	2.9	74	18	78	1.16	29.5	0.080	2.0	14.5	SPR	CG	Z
1.000	25.40	3062	4.81	122.2	.818	20.8	12	2.1	2.1	52	25	110	1.17	29.8	0.091	2.3	13.0	SPR	CG	Z
1.000	25.40	10115	4.88	123.8	.676	17.2	120	21	1.0	26	123	546	2.59	65.8	0.162	4.1	16.0	SPR	CG	N
1.000	25.40	333	5.00	127.0	.646	16.4	137	24	1.2	29	158	704	3.63	92.2	0.177	4.5	20.5	HD	CG	Z
1.000	25.40	S-3106	5.13	130.2	.840	21.3	4.7	.82	3.5	89	17	73	1.28	32.5	0.080	2.0	16.0	SST	CG	N
1.000	25.40	S-270	5.13	130.2	.820	20.8	7.8	1.4	2.9	73	22	99	1.44	36.6	0.090	2.3	16.0	SST	CG	N
1.000	25.40	2605	5.25	133.4	.790	20.1	15	2.7	2.5	63	38	168	2.00	50.7	0.105	2.7	18.0	SPR	C	Z
1.000	25.40	12150	5.50	139.7	.700	17.8	54	9.4	1.8	46	98	437	3.60	91.4	0.150	3.8	24.0	SPR	CG	Z
1.000	25.40	848	6.00	152.4	.676	17.2	74	13	1.7	42	123	546	4.00	101.5	0.162	4.1	24.7	HD	CG	Z
1.000	25.40	11617	6.50	165.1	.814	20.7	8.0	1.4	3.3	84	26	118	1.95	49.6	0.093	2.4	20.0	SPR	CG	Z
1.000	25.40	2880	6.88	174.6	.706	17.9	49	8.6	1.9	49	95	423	3.53	89.6	0.147	3.7	24.0	SPR	CG	Z
1.000	25.40	S-1251	7.25	184.2	.818	20.8	8.2	1.4	2.8	72	23	102	1.46	37.0	0.091	2.3	16.0	SST	CG	N
1.000	25.40	12115	7.50	190.5	.660	16.8	66	11	1.7	44	113	502	5.78	146.8	0.170	4.3	34.0	SPR	CG	Z
1.000	25.40	S-121	8.00	203.2	.930	23.6	.15	.03	7.4	188	1.1	4.9	.60	15.1	0.035	0.9	16.0	SST	C	N
1.000	25.40	884	8.00	203.2	.818	20.8	5.6	.98	4.4	113	25	110	2.41	61.3	0.091	2.3	25.5	HD	C	Z
1.000	25.40	873	8.00	203.2	.790	20.1	9.3	1.6	4.1	103	38	168	2.97	75.3	0.105	2.7	28.3	HD	CG	Z
1.000	25.40	866	8.00	203.2	.760	19.3	15	2.7	3.5	90	54	241	3.78	96.0	0.120	3.0	30.5	HD	C	Z
1.000	25.40	856	8.00	203.2	.730	18.5	25	4.3	3.0	77	74	330	4.32	109.7	0.135	3.4	32.0	HD	CG	Z
1.000	25.40	S-464	8.00	203.2	.730	18.5	21	3.7	3.1	79	67	297	4.32	109.7	0.135	3.4	32.0	SST	CG	N
1.000	25.40	819	8.00	203.2	.704	17.9	37	6.4	2.7	67	97	431	4.81	122.2	0.148	3.8	32.5	HD	CG	Z
1.000	25.40	360	8.00	203.2	.586	14.9	183	32	1.3	33	235	1047	6.42	163.0	0.207	5.3	31.0	HD	CG	Z
1.000	25.40	10175	8.50	215.9	.646	16.4	114	20	1.4	35	158	704	4.29	109.0	0.177	4.5	24.3	SPR	CG	Z
1.000	25.40	2962	9.00	228.6	.790	20.1	8.3	1.5	4.5	115	38	168	3.39	86.0	0.105	2.7	31.3	SPR	C	Z
1.000	25.40	910	10.0	254.0	.790	20.1	7.0	1.2	5.4	138	38	168	3.99	101.3	0.105	2.7	37.0	HD	C	Z
1.000	25.40	11576	11.0	279.4	.828	21.0	3.5	.61	6.3	160	22	97	2.82	71.5	0.086	2.2	31.8	SPR	C	N
1.000	25.40	901	12.0	304.8	.856	21.7	1.8	.32	7.1	181	13	57	2.14	54.4	0.072	1.8	28.8	HD	C	Z
1.000	25.40	298	12.0	304.8	.840	21.3	2.4	.41	7.5	190	18	78	2.80	71.1	0.080	2.0	34.0	HD	C	Z
1.000	25.40	341	12.0	304.8	.616	15.6	99	17	1.9	49	190	847	7.58	192.6	0.192	4.9	39.5	HD	CG	Z
1.000	25.40	3069	16.8	425.5	.704	17.9	20	3.5	4.8	123	97	431	8.55	217.1	0.148	3.8	57.8	SPR	CG	GI
1.010	25.65	72489	1.00	25.4	.786	20.0	105	18	.44	11	46	206	.56	14.2	0.112	2.8	5.00	MW	CG	N
1.010	25.65	72489S	1.00	25.4	.786	20.0	90	16	.44	11	39	175	.56	14.2	0.112	2.8	5.00	SST	CG	N
1.010	25.65	72491	1.50	38.1	.786	20.0	64	11	.73	19	47	208	.77	19.6	0.112	2.8	6.88	MW	CG	N
1.010	25.65	72491S	1.50	38.1	.786	20.0	54	9.5	.73	19	40	177	.77	19.6	0.112	2.8	6.88	SST	CG	N
1.010	25.65	72493	2.00	50.8	.786	20.0	46	8.1	1.0	26	47	209	.98	24.9	0.112	2.8	8.75	MW	CG	N
1.010	25.65	72493S	2.00	50.8	.786	20.0	39	6.8	1.0	26	40	177	.98	24.9	0.112	2.8	8.75	SST	CG	N
1.010	25.65	72495	2.50	63.5	.786	20.0	36	6.3	1.3	33	47	207	1.20	30.6	0.112	2.8	10.8	MW	CG	N
1.010	25.65	72495S	2.50	63.5	.786	20.0	31	5.3	1.3	33	40	176	1.20	30.6	0.112	2.8	10.8	SST	CG	N
1.010	25.65	72497	3.00	76.2	.786	20.0	29	5.1	1.6	40	47	207	1.41	35.9	0.112	2.8	12.6	MW	CG	N
1.010	25.65	72497S	3.00	76.2	.786	20.0	25	4.4	1.6	40	40	176	1.41	35.9	0.112	2.8	12.6	SST	CG	N
1.010	25.65	72499	3.50	88.9	.786	20.0	25	4.4	1.9	48	47	208	1.62	41.2	0.112	2.8	14.5	MW	CG	N
1.010	25.65	72499S	3.50	88.9	.786	20.0	21	3.7	1.9	48	40	177	1.62	41.2	0.112	2.8	14.5	SST	CG	N
1.010	25.65	72501	4.00	101.6	.786	20.0	22	3.8	2.2	55	46	207	1.85	46.9	0.112	2.8	16.5	MW	CG	N
1.010	25.65	72501S	4.00	101.6	.786	20.0	18	3.2	2.2	55	40	176	1.85	46.9	0.112	2.8	16.5	SST	CG	N
1.010	25.65	72503	4.50	114.3	.786	20.0	19	3.3	2.4	62	47	207	2.06	52.3	0.112	2.8	18.4	MW	CG	N
1.010	25.65	72503S	4.50	114.3	.786	20.0	16	2.8	2.4	62	40	176	2.06	52.3	0.112	2.8	18.4	SST	CG	N
1.015	25.78	3882	.69	17.4	.775	19.7	416	73	.13	3.3	53	237	.36	9.1	0.120	3.0	3.00	HD	CG	Z
1.015	25.78	S-896	.88	22.2	.829	21.1	40	7.0	.41	10	16	73	.47	11.8	0.093	2.4	5.00	SST	CG	N
1.015	25.78	12136	1.28	32.5	.889	22.6	10	1.8	.86	22	9.0	40	.35	8.8	0.063	1.6	4.50	SPR	C	Z
1.015	25.78	S-1626	1.38	34.9	.909	23.1	5.7	.99	.90	23	5.1	23	.21	5.4	0.053	1.3	4.00	SST	CG	N
1.015	25.78	11694	1.50	38.1	.891	22.6	4.9	.86	1.1	27	5.2	23	.43	11.0	0.062	1.6	7.00	SPR	CG	Z
1.015	25.78	3390	1.50	38.1	.825	21.0	30	5.3	.84	21	25	112	.67	16.9	0.095	2.4	7.00	SPR	CG	Z
1.015	25.78	S-1021	1.63	41.3	.907	23.0	3.0	.52	1.3	33	3.9	17	.32	8.2	0.054	1.4	6.00	SST	CG	N
1.015	25.78	12059	1.69	42.8	.591	15.0	1869	327	.13	3.4	249	1106	1.06	26.9	0.212	5.4	5.00	SPR	CG	Z
1.015	25.78	11846	1.72	43.6	.767	19.5	142	25	.38	9.6	54	238	.74	18.9	0.124	3.1	5.00	SST	C	N
1.015	25.78	A13-62	1.78	45.2	.717	18.2	194	34	.45	12										




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.015	25.78	S-962	3.50	88.9	.825	21.0	15	2.7	1.7	42	26	114	1.00	25.3	0.095	2.4	10.5	SST	CG	N
1.015	25.78	B17-201	3.59	91.3	.935	23.7	.43	.07	3.1	80	1.3	6.0	.45	11.4	0.040	1.0	10.3	SST	C	N
1.015	25.78	2810	3.88	98.4	.887	22.5	5.6	.98	2.3	59	13	58	.45	11.4	0.064	1.6	7.00	MW	CG	Z
1.015	25.78	S-1222	4.88	123.8	.895	22.7	1.2	.22	3.8	96	4.7	21	1.08	27.4	0.060	1.5	17.0	SST	C	N
1.015	25.78	1823	4.88	123.8	.691	17.6	106	19	1.1	29	121	539	2.75	70.0	0.162	4.1	17.0	HD	CG	Z
1.015	25.78	12456	5.38	136.5	.763	19.4	37	6.5	1.7	42	62	274	2.14	54.4	0.126	3.2	16.0	SPR	C	N
1.015	25.78	2647	7.50	190.5	.833	21.2	7.2	1.3	4.7	120	34	152	1.75	44.5	0.091	2.3	19.3	MW	CG	Z
1.031	26.19	S-1084	.63	15.9	.871	22.1	60	10	.27	6.8	16	71	.24	6.1	0.080	2.0	3.00	SST	CG	N
1.031	26.19	MM-98	.69	17.4	.731	18.6	710	124	.13	3.4	96	425	.53	13.3	0.150	3.8	3.50	SPR	CG	Z
1.031	26.19	BB-40	.75	19.1	.931	23.6	2.1	.37	.45	11	.95	4.2	.30	7.6	0.050	1.3	6.00	SST	CG	N
1.031	26.19	10107	.81	20.7	.907	23.0	12	2.0	.57	14	6.6	29	.25	6.3	0.062	1.6	4.00	SPR	CG	Z
1.031	26.19	S-3054	.88	22.2	.915	23.2	15	2.7	.43	11	6.5	29	.23	5.9	0.058	1.5	3.00	SST	C	N
1.031	26.19	A10-65	1.03	26.2	.869	22.1	21	3.7	.63	16	13	59	.41	10.3	0.081	2.1	5.00	SST	CG	N
1.031	26.19	2678	1.13	28.6	.849	21.6	40	6.9	.58	15	23	102	.55	13.9	0.091	2.3	5.00	HD	C	Z
1.031	26.19	10852	1.38	34.9	.875	22.2	18	3.2	.82	21	15	66	.39	9.9	0.078	2.0	5.00	SST	CG	N
1.031	26.19	3339	1.44	36.5	.907	23.0	4.9	.86	1.0	26	5.0	22	.42	10.6	0.062	1.6	6.75	HD	CG	GI
1.031	26.19	10740	1.50	38.1	.929	23.6	5.2	.90	.92	23	4.7	21	.20	5.2	0.051	1.3	4.00	SPR	CG	Z
1.031	26.19	S-1417	1.50	38.1	.857	21.8	17	3.0	.80	20	14	61	.70	17.7	0.087	2.2	7.00	SST	C	N
1.031	26.19	10659	1.53	38.9	.741	18.8	244	43	.36	9.3	89	395	.83	21.2	0.145	3.7	5.75	SPR	CG	Z
1.031	26.19	12447	1.56	39.7	.791	20.1	53	9.2	.42	11	22	99	1.14	29.0	0.120	3.0	9.50	SPR	CG	N
1.031	26.19	10409	1.94	49.2	.657	16.7	487	85	.35	9.0	172	766	1.50	38.0	0.187	4.7	8.00	SPR	CG	Z
1.031	26.19	10676	1.97	50.0	.807	20.5	36	6.4	.74	19	27	119	1.23	31.3	0.112	2.8	10.0	SPR	C	Z
1.031	26.19	S-1532	2.00	50.8	.923	23.4	2.8	.50	1.7	43	4.8	21	.32	8.2	0.054	1.4	6.00	SST	CG	N
1.031	26.19	10457	2.19	55.6	.707	18.0	224	39	.53	14	119	531	1.42	36.0	0.162	4.1	8.75	SPR	CG	Z
1.031	26.19	NN-20	2.19	55.6	.571	14.5	1305	228	.23	5.8	297	1321	1.84	46.7	0.230	5.8	8.00	SPR	CG	Z
1.031	26.19	10722	2.28	57.9	.747	19.0	145	25	.58	15	84	372	1.10	28.0	0.142	3.6	7.75	SPR	CG	Z
1.031	26.19	2730	2.34	59.5	.911	23.1	5.1	.89	1.9	49	9.8	44	.42	10.7	0.060	1.5	6.00	MW	C	Z
1.031	26.19	2702	2.47	62.7	.761	19.3	111	19	.91	23	101	449	1.08	27.4	0.135	3.4	8.00	MW	CG	Z
1.031	26.19	2677	2.63	66.7	.871	22.1	12	2.1	1.4	37	17	76	.62	15.7	0.080	2.0	7.75	HD	CG	Z
1.031	26.19	10988	2.81	71.4	.657	16.7	325	57	.53	13	172	766	2.06	52.2	0.187	4.7	11.0	HD	CG	Z
1.031	26.19	S-1473	3.00	76.2	.871	22.1	4.8	.83	1.8	47	8.8	39	1.16	29.5	0.080	2.0	14.5	SST	CG	N
1.031	26.19	3401	3.63	92.1	.917	23.3	1.5	.26	2.8	72	4.2	19	.80	20.3	0.057	1.4	13.0	SPR	C	Z
1.031	26.19	B18-197	3.75	95.3	.959	24.4	.49	.09	3.5	88	1.7	7.5	.29	7.3	0.036	0.9	7.00	SPR	C	Z
1.031	26.19	1631	3.75	95.3	.851	21.6	10	1.7	2.3	59	23	104	1.29	32.8	0.090	2.3	13.3	SPR	C	Z
1.031	26.19	B9-48	3.88	98.4	.637	16.2	325	57	.62	16	200	888	2.66	67.6	0.197	5.0	13.5	SPR	CG	N
1.031	26.19	12004	9.88	250.8	.837	21.3	4.9	.85	6.0	151	29	129	3.30	83.8	0.097	2.5	34.0	SPR	CG	Z
1.046	26.57	1895	.75	19.1	.944	24.0	9.9	1.7	.47	12	4.7	21	.20	5.2	0.051	1.3	3.00	HD	C	Z
1.046	26.57	S-1035	.81	20.6	.806	20.5	154	27	.31	7.8	47	211	.50	12.6	0.120	3.0	4.00	SST	CG	N
1.046	26.57	S-3004	.81	20.6	.806	20.5	163	29	.29	7.4	47	211	.48	12.2	0.120	3.0	4.00	SST	CG	N
1.046	26.57	10973	.94	23.8	.934	23.7	13	2.3	.45	11	5.8	26	.22	5.7	0.056	1.4	3.00	SST	C	N
1.046	26.57	B18-193	1.03	26.2	.866	22.0	36	6.3	.49	12	18	79	.54	13.7	0.090	2.3	5.00	SPR	CG	Z
1.046	26.57	A14-56	1.19	30.2	.916	23.3	7.8	1.4	.83	21	6.4	29	.36	9.1	0.065	1.7	5.50	SPR	CG	Z
1.046	26.57	S-1444	1.31	33.3	.864	21.9	33	5.7	.67	17	22	98	.46	11.6	0.091	2.3	5.00	SST	CG	N
1.046	26.57	3338	1.44	36.5	.916	23.3	5.4	.95	.98	25	5.3	24	.46	11.6	0.065	1.7	7.00	SPR	CG	Z
1.046	26.57	2985	1.47	37.3	.806	20.5	94	16	.55	14	52	231	.72	18.3	0.120	3.0	6.00	SPR	CG	Z
1.046	26.57	S-1199	1.50	38.1	.930	23.6	2.9	.51	1.0	26	3.0	14	.46	11.8	0.058	1.5	7.00	SST	C	N
1.046	26.57	3826	1.50	38.1	.918	23.3	5.1	.89	1.1	27	5.4	24	.45	11.4	0.064	1.6	7.00	SPR	CG	Z
1.046	26.57	12066	1.50	38.1	.808	20.5	90	16	.56	14	51	225	.71	18.1	0.119	3.0	6.00	SPR	CG	Z
1.046	26.57	11561	1.69	42.8	.924	23.5	10	1.8	.76	19	8.0	35	.31	7.7	0.061	1.5	4.00	SPR	C	Z
1.046	26.57	12245	1.72	43.6	.884	22.5	14	2.4	1.2	29	16	71	.57	14.4	0.081	2.1	7.00	SPR	CG	GI
1.046	26.57	S-1496	1.81	46.0	.902	22.9	12	2.1	.96	24	12	52	.36	9.1	0.072	1.8	5.00	SST	CG	N
1.046	26.57	11231	1.91	48.4	.896	22.8	13	2.3	1.1	27	14	62	.51	12.9	0.075	1.9	5.75	SPR	C	Z
1.046	26.57	3213	2.00	50.8	.934	23.7	3.8	.66	1.6	42	6.2	27	.33	8.4	0.056	1.4	6.00	SPR	CG	Z
1.046	26.57	S-350	2.00	50.8	.836	21.2	52	9.1	.64	16	34	149	.58	14.7	0.105	2.7	5.50	SST	CG	N
1.046	26.57	3067	2.00	50.8	.750	19.1	159	28	.59	15	93	414	1.18	30.1	0.148	3.8	8.00	SPR	CG	Z
1.046	26.57	3757	2.25	57.2	.836	21.2	47	8.2	.78	20	36	161	.68	17.3	0.105	2.7	6.50	SPR	CG	Z
1.046	26.57	3009	2.25	57.2	.722	18.3	205	36	.58	15	118	525	1.46	37.0	0.162	4.1	9.00	SPR	CG	Z
1.046	26.57	S-1425	2.63	66.7	.896	22.8	6.9	1.2	1.9	48	13	58	.62	15.7	0.075	1.9	8.25	SST	C	N
1.046	26.57	S-3244	2.66	67.5	.898	22.8	6.6	1.2	1.9	49	13	56	.62	15.7	0.074	1.9	8.33	SST	CG	N
1.046	26.57	2744	3.88	98.4	.922	23.4	1.7	.29	2.9	73	4.8	21	1.01	25.6	0.062	1.6	15.3	HD	C	Z
1.046	26.57	11992	4.88	123.8	.822	20.9	21	3.7	2.0	50	42	189	1.68	42.7	0.112	2.8	15.0	SPR	CG	Z
1.046	26.57	3329	4.88	123.8	.722	18.3	96	17	1.2	31	118	525	2.75	70.0	0.162	4.1	17.0	SPR	CG	Z
1.046	26.57	11684	7.50	190.5	.790	20.1	28	4.8	2.3	58	63	279	2.88	73.2	0.128	3.3	22.0	SPR	CG	Z
1.046	26.57	3427	8.50	215.9	.846	21.5	8.9	1.6	3.5	89	31	140	2.10	53.3	0.100	2.5	21.0	SPR	CG	Z
1.062	26.97	AA-80	.88	22.2	.942	23.9	6.0	1.0	.59	15	3.5	16	.29	7.2	0.060	1.5	4.75	SST	CG	N
1.062	26.97	S-1394	.88	22.2	.938	23.8	7.4	1.3	.60	15	4.4	20	.28	7.1	0.062	1.6	4.50	SST	CG	N
1.062	26.97	S-311	.88	22.2	.914	23.2	26	4.5	.48	12	12	55	.26	6.6	0.074	1.9	3.50	SST	CG	N
1.062	26.97	4192	1.00	25.4	.938	23.8	11	1.9	.69	18	7.3	33	.31	7.9	0.062	1.6	4.00	HD	C	Z
1.062	26.97	S-1221	1.00	25.4	.872	22.														

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.062	26.97	S-83	1.63	41.3	.902	22.9	22	3.8	.72	18	16	69	.36	9.1	0.080	2.0	4.50	SST	CG	N
1.062	26.97	10207	1.63	41.3	.612	15.5	1571	275	.17	4.4	273	1214	1.35	34.3	0.225	5.7	6.00	SPR	CG	Z
1.062	26.97	10796	1.75	44.5	.826	21.0	133	23	.37	9.3	49	217	.53	13.5	0.118	3.0	4.50	SPR	CG	BO
1.062	26.97	3007	1.84	46.8	.954	24.2	4.0	.70	1.4	35	5.5	24	.32	8.2	0.054	1.4	5.00	SPR	C	Z
1.062	26.97	S-3125	1.88	47.6	.918	23.3	5.8	1.0	1.2	31	7.1	31	.65	16.5	0.072	1.8	8.00	SST	C	N
1.062	26.97	4388	1.88	47.6	.910	23.1	13	2.3	1.1	27	14	64	.51	13.0	0.076	1.9	5.75	SPR	C	Z
1.062	26.97	MM-44	1.88	47.6	.882	22.4	21	3.6	1.1	28	23	101	.63	16.0	0.090	2.3	7.00	SPR	CG	Z
1.062	26.97	12311	1.94	49.2	.862	21.9	29	5.1	1.1	27	31	138	.75	19.1	0.100	2.5	7.50	SPR	CG	Z
1.062	26.97	S-1385	2.00	50.8	.880	22.4	17	3.0	1.3	32	22	97	.68	17.3	0.091	2.3	7.50	SST	CG	N
1.062	26.97	4352	2.19	55.6	.892	22.7	16	2.8	1.2	31	20	89	.60	15.1	0.085	2.2	7.00	SPR	CG	Z
1.062	26.97	11636	2.25	57.2	.842	21.4	35	6.1	1.1	29	40	176	.99	25.1	0.110	2.8	9.00	SPR	CG	Z
1.062	26.97	CC-44	2.25	57.2	.742	18.8	190	33	.53	13	100	443	1.28	32.5	0.160	4.1	8.00	SST	CG	N
1.062	26.97	12520	2.31	58.7	.812	20.6	71	12	.81	21	58	257	1.13	28.6	0.125	3.2	8.00	SPR	C	N
1.062	26.97	3133	2.38	60.3	.922	23.4	9.4	1.7	1.2	30	11	50	.47	12.0	0.070	1.8	5.75	SPR	C	Z
1.062	26.97	3942	2.50	63.5	.766	19.5	113	20	.81	21	92	408	1.48	37.6	0.148	3.8	10.0	SPR	CG	Z
1.062	26.97	A13-56	2.69	68.2	.916	23.3	4.4	.77	1.9	49	8.5	38	.77	19.5	0.073	1.9	10.5	SST	CG	N
1.062	26.97	S-437	3.38	85.7	.904	23.0	4.7	.83	2.4	60	11	49	1.02	25.8	0.079	2.0	13.0	SST	CG	N
1.062	26.97	S-1326	3.50	88.9	.918	23.3	3.5	.61	2.6	67	9.1	41	.86	21.9	0.072	1.8	12.0	SST	CG	N
1.062	26.97	3272	3.63	92.1	.848	21.5	22	3.8	1.7	44	38	168	1.28	32.6	0.107	2.7	12.0	SPR	CG	Z
1.062	26.97	12436	3.88	98.4	.938	23.8	2.2	.39	3.1	79	6.9	31	.78	19.7	0.062	1.6	11.5	SPR	C	Z
1.062	26.97	S-444	4.63	117.5	.862	21.9	12	2.0	2.5	62	29	128	1.40	35.6	0.100	2.5	14.0	SST	CG	N
1.062	26.97	S-3217	5.00	127.0	.992	25.2	.15	.03	4.5	114	.69	3.1	.51	12.9	0.035	0.9	13.5	SST	C	N
1.062	26.97	4108	5.00	127.0	.822	20.9	27	4.8	1.9	47	51	228	1.92	48.8	0.120	3.0	15.0	SPR	C	Z
1.062	26.97	334	6.00	152.4	.708	18.0	96	17	1.6	40	150	668	4.12	104.5	0.177	4.5	23.3	HD	CG	Z
1.062	26.97	2755	7.25	184.2	.738	18.7	61	11	1.9	49	116	518	3.94	100.1	0.162	4.1	24.3	SPR	CG	Z
1.062	26.97	1936	7.63	193.7	.880	22.4	6.3	1.1	3.7	94	23	104	1.73	43.9	0.091	2.3	19.0	SPR	CG	Z
1.062	26.97	1703	7.63	193.7	.738	18.7	60	10	1.9	49	116	518	4.16	105.6	0.162	4.1	24.7	SPR	C	Z
1.062	26.97	385	11.5	292.1	.852	21.6	12	2.2	2.9	73	36	159	2.00	50.7	0.105	2.7	18.0	HD	C	Z
1.062	26.97	4170	11.5	292.1	.852	21.6	5.7	1.0	6.3	159	36	159	3.99	101.3	0.105	2.7	37.0	SPR	C	Z
1.070	27.18	12804	4.00	101.6	.656	16.7	315	55	.71	18	223	991	3.10	78.7	0.207	5.3	15.0	HD	CG	Z
1.078	27.38	11507	.78	19.8	.934	23.7	19	3.3	.42	11	8.0	36	.36	9.1	0.072	1.8	4.00	SPR	CG	Z
1.078	27.38	12074	1.00	25.4	.918	23.3	30	5.2	.55	14	16	73	.32	8.1	0.080	2.0	4.00	SPR	CG	Z
1.078	27.38	10525	1.00	25.4	.868	22.0	47	8.3	.37	9.4	18	78	.63	16.0	0.105	2.7	6.00	SPR	CG	Z
1.078	27.38	11702	1.13	28.6	.992	25.2	1.3	.22	.89	23	1.1	5.0	.24	6.0	0.043	1.1	5.50	SPR	CG	Z
1.078	27.38	10685	1.13	28.6	.908	23.1	27	4.8	.66	17	18	79	.47	11.9	0.085	2.2	4.50	SST	C	N
1.078	27.38	11728	1.13	28.6	.828	21.0	135	24	.42	11	57	253	.63	15.9	0.125	3.2	5.00	SPR	CG	Z
1.078	27.38	12318	1.19	30.2	.992	25.2	1.3	.22	.91	23	1.2	5.1	.28	7.1	0.043	1.1	5.50	SPR	C	Z
1.078	27.38	11850	1.34	34.1	.922	23.4	12	2.1	.88	22	10	46	.47	11.9	0.078	2.0	6.00	SST	CG	N
1.078	27.38	12307	1.47	37.3	.958	24.3	3.5	.62	.99	25	3.5	16	.48	12.2	0.060	1.5	7.00	SPR	C	Z
1.078	27.38	A13-69	1.47	37.3	.894	22.7	23	4.0	.90	23	21	93	.56	14.3	0.092	2.3	6.13	SST	CG	N
1.078	27.38	12268	1.50	38.1	.966	24.5	3.8	.66	1.2	30	4.5	20	.31	7.8	0.056	1.4	5.50	SPR	CG	Z
1.078	27.38	1908	1.50	38.1	.852	21.6	65	11	.65	16	42	188	.68	17.2	0.113	2.9	6.00	SPR	CG	Z
1.078	27.38	1739	1.63	41.3	.782	19.9	229	40	.55	14	127	564	.85	21.6	0.148	3.8	5.75	MW	CG	Z
1.078	27.38	1741	1.75	44.5	.896	22.8	34	6.0	.68	17	23	103	.55	13.9	0.091	2.3	5.00	HD	C	Z
1.078	27.38	11564	1.81	46.0	.960	24.4	4.7	.82	1.4	36	6.7	30	.38	9.7	0.059	1.5	5.50	SPR	CG	Z
1.078	27.38	S-844	1.88	47.6	.908	23.1	14	2.4	1.3	33	18	78	.58	14.8	0.085	2.2	6.88	SST	CG	N
1.078	27.38	S-356	2.00	50.8	.988	25.1	1.6	.27	1.7	44	2.7	12	.27	6.9	0.045	1.1	5.00	SST	C	N
1.078	27.38	11586	2.00	50.8	.896	22.8	21	3.6	1.1	29	23	103	.73	18.5	0.091	2.3	7.00	SPR	CG	N
1.078	27.38	12156	2.00	50.8	.808	20.5	104	18	.67	17	69	308	1.01	25.7	0.135	3.4	7.50	SPR	CG	Z
1.078	27.38	B11-29	2.00	50.8	.808	20.5	127	22	.55	14	69	308	.88	22.3	0.135	3.4	6.50	SPR	CG	N
1.078	27.38	10992	2.00	50.8	.754	19.2	224	39	.51	13	115	511	1.42	36.0	0.162	4.1	7.75	HD	CG	Z
1.078	27.38	10939	2.06	52.4	.934	23.7	6.3	1.1	1.5	38	9.4	42	.58	14.6	0.072	1.8	8.00	SPR	CG	Z
1.078	27.38	3121	2.13	54.0	.934	23.7	9.5	1.7	1.3	32	12	53	.43	11.0	0.072	1.8	6.00	SPR	CG	Z
1.078	27.38	11870	2.13	54.0	.894	22.7	20	3.4	1.2	31	24	106	.69	17.5	0.092	2.3	7.50	SPR	CG	N
1.078	27.38	11165	2.13	54.0	.782	19.9	202	35	.45	11	91	403	.93	23.5	0.148	3.8	6.25	SPR	CG	Z
1.078	27.38	S-129	2.19	55.6	.932	23.7	8.2	1.4	1.4	36	12	52	.46	11.6	0.073	1.9	6.25	SST	CG	N
1.078	27.38	S-3166	2.25	57.2	.954	24.2	4.1	.73	1.8	47	7.6	34	.39	9.8	0.062	1.6	6.25	SST	CG	N
1.078	27.38	S-1672	2.25	57.2	.898	22.8	14	2.5	1.4	36	21	92	.72	18.3	0.090	2.3	8.00	SST	CG	N
1.078	27.38	B17-132	2.50	63.5	1.026	26.1	.08	.01	2.3	58	.19	.84	.23	5.9	0.026	0.7	8.00	SST	C	N
1.078	27.38	S-422	2.50	63.5	.894	22.7	18	3.1	1.2	32	22	98	.67	16.9	0.092	2.3	7.25	SST	CG	N
1.078	27.38	11827	2.50	63.5	.808	20.5	70	12	.90	23	62	277	1.25	31.7	0.135	3.4	9.25	SST	CG	N
1.078	27.38	10369	2.50	63.5	.796	20.2	138	24	.57	14	79	350	.99	25.1	0.141	3.6	7.00	SPR	CG	Z
1.078	27.38	2649	2.50	63.5	.784	19.9	104	18	.85	22	89	395	1.47	37.3	0.147	3.7	10.0	HD	CG	Z
1.078	27.38	RR-58	2.75	69.9	.998	25.3	.41	.07	2.3	59	.95	4.2	.44	11.2	0.040	1.0	10.0	SPR	C	Z
1.078	27.38	11759	2.84	72.2	.954	24.2	1.6	.27	1.9	47	2.9	13	.99	25.2	0.062	1.6	15.0	SPR	C	Z
1.078	27.38	S-95	3.00	76.2	.578	14.7	1075	188	.28	7.2	304	1352	2.50	63.5	0.250	6.4	10.0	SST	CG	N
1.078	27.38	2698	3.75	95.3	.748	19.0	127	22	.95	24	121	539	2.15	54.5	0.165	4.2	13.0	SPR	CG	Z
1.078	27.38	11674	4.00	101.6	.996	25.3	.28	.05	3.4	86	.95	4.2	.62	15.6	0.041	1.0	15.0	SPR	CG	Z
1.078	27.38	10386																		




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	F NCH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.094	27.79	A15-59	.97	24.6	.910	23.1	45	7.9	.48	12	22	97	.37	9.3	0.092	2.3	4.00	SST	CG	N
1.094	27.79	S-130	1.00	25.4	.884	22.5	79	14	.41	10	32	143	.42	10.7	0.105	2.7	4.00	SST	CG	N
1.094	27.79	KK-44	1.06	27.0	.954	24.2	16	2.8	.68	17	11	48	.28	7.1	0.070	1.8	4.00	SPR	CG	GI
1.094	27.79	3910	1.25	31.8	.912	23.2	33	5.7	.70	18	23	101	.46	11.6	0.091	2.3	5.00	SPR	CG	GI
1.094	27.79	11741	1.25	31.8	.904	23.0	39	6.9	.66	17	26	115	.48	12.1	0.095	2.4	5.00	SPR	CG	Z
1.094	27.79	2814	1.38	34.9	.950	24.1	14	2.5	.82	21	12	53	.32	8.2	0.072	1.8	4.50	HD	CG	Z
1.094	27.79	3034	1.38	34.9	.944	24.0	16	2.8	.83	21	13	59	.42	10.8	0.075	1.9	4.67	SPR	C	Z
1.094	27.79	10223	1.50	38.1	.902	22.9	38	6.6	.71	18	27	119	.50	12.8	0.096	2.4	5.25	SPR	CG	Z
1.094	27.79	HH-98	1.50	38.1	.894	22.7	42	7.3	.72	18	30	134	.55	14.0	0.100	2.5	5.50	SPR	CG	Z
1.094	27.79	12555	1.50	38.1	.884	22.5	45	7.9	.72	18	32	143	.58	14.7	0.105	2.7	5.50	SST	CG	N
1.094	27.79	12111	1.53	38.9	.934	23.7	11	1.9	.93	24	10	46	.60	15.2	0.080	2.0	6.50	SST	C	N
1.094	27.79	3132	1.59	40.5	.894	22.7	33	5.7	.92	23	30	134	.65	16.5	0.100	2.5	6.50	SPR	CG	N
1.094	27.79	12006	1.59	40.5	.782	19.9	295	52	.34	8.8	102	452	.86	21.8	0.156	4.0	5.50	SPR	CG	Z
1.094	27.79	1671	1.63	41.3	.798	20.3	217	38	.41	10	89	397	.85	21.6	0.148	3.8	5.75	SPR	CG	Z
1.094	27.79	11278	1.69	42.8	.782	19.9	258	45	.39	10	102	452	.94	23.8	0.156	4.0	6.00	SPR	CG	Z
1.094	27.79	10332	1.88	47.6	.810	20.6	159	28	.50	13	79	352	.89	22.6	0.142	3.6	6.25	SPR	CG	Z
1.094	27.79	945	2.00	50.8	.974	24.7	3.7	.66	1.6	39	5.8	26	.45	11.4	0.060	1.5	6.50	MW	C	Z
1.094	27.79	1577	2.00	50.8	.884	22.5	34	5.9	1.0	26	35	154	.77	19.6	0.105	2.7	7.33	SPR	CG	Z
1.094	27.79	3262	2.00	50.8	.824	20.9	98	17	.69	18	68	304	1.01	25.7	0.135	3.4	7.50	HD	CG	Z
1.094	27.79	10325	2.13	54.0	.810	20.6	135	24	.58	15	79	352	.99	25.2	0.142	3.6	7.00	SPR	CG	Z
1.094	27.79	S-1246	2.19	55.6	.950	24.1	7.9	1.4	1.4	36	11	49	.43	11.0	0.072	1.8	6.00	SST	C	N
1.094	27.79	11284	2.19	55.6	.798	20.3	172	30	.52	13	89	397	1.00	25.4	0.148	3.8	6.75	SPR	CG	Z
1.094	27.79	3697	2.25	57.2	1.006	25.6	1.2	.20	1.9	49	2.3	10	.31	7.8	0.044	1.1	6.00	SPR	C	Z
1.094	27.79	11971	2.38	60.3	.914	23.2	14	2.5	1.4	36	20	91	.70	17.7	0.090	2.3	7.75	SST	CG	N
1.094	27.79	11381	2.50	63.5	.944	24.0	7.6	1.3	1.6	42	13	56	.53	13.3	0.075	1.9	7.00	SST	CG	N
1.094	27.79	3309	2.50	63.5	.814	20.7	91	16	.84	21	76	338	1.26	32.0	0.140	3.6	9.00	SPR	CG	Z
1.094	27.79	S-448	2.63	66.7	.872	22.1	32	5.6	1.1	29	36	161	.92	23.3	0.111	2.8	8.25	SST	CG	N
1.094	27.79	10381	2.63	66.7	.868	22.0	31	5.4	1.3	34	42	186	1.13	28.7	0.113	2.9	10.0	SPR	CG	Z
1.094	27.79	3913	2.75	69.9	1.012	25.7	.43	.08	2.3	58	1.0	4.4	.45	11.5	0.041	1.0	10.0	SPR	C	Z
1.094	27.79	S-1439	2.75	69.9	.992	25.2	1.4	.24	2.3	59	3.1	14	.43	11.0	0.051	1.3	7.50	SST	C	N
1.094	27.79	3163	2.75	69.9	.782	19.9	163	29	.62	16	102	452	1.33	33.9	0.156	4.0	8.50	SPR	CG	Z
1.094	27.79	11388	3.41	86.5	.844	21.4	38	6.7	1.3	34	51	228	1.38	34.9	0.125	3.2	11.0	SST	CG	N
1.094	27.79	S-279	3.63	92.1	.912	23.2	6.3	1.1	2.2	56	14	62	1.41	35.8	0.091	2.3	15.5	SST	CG	N
1.094	27.79	3711	4.00	101.6	.984	25.0	1.2	.21	3.3	83	3.9	17	.72	18.2	0.055	1.4	12.0	SPR	C	Z
1.094	27.79	3374	4.00	101.6	.814	20.7	55	9.7	1.4	35	76	338	1.89	48.0	0.140	3.6	13.5	SPR	CG	GI
1.094	27.79	12169	4.06	103.2	.778	19.8	121	21	.87	22	105	469	1.74	44.1	0.158	4.0	11.0	SPR	CG	GI
1.094	27.79	10948	4.19	106.4	.854	21.7	26	4.6	1.7	44	45	202	1.56	39.6	0.120	3.0	13.0	SST	CG	N
1.094	27.79	2713	4.75	120.7	.894	22.7	11	1.9	2.8	70	30	134	1.55	39.4	0.100	2.5	15.5	SPR	CG	Z
1.094	27.79	11775	4.91	124.6	.900	22.9	9.7	1.7	2.6	67	25	113	1.33	33.9	0.097	2.5	13.8	SST	CG	N
1.094	27.79	12312	5.00	127.0	.884	22.5	15	2.6	2.3	59	35	154	1.58	40.0	0.105	2.7	14.0	HD	C	Z
1.094	27.79	S-3046	5.13	130.2	.844	21.4	24	4.2	2.1	54	51	228	2.00	50.8	0.125	3.2	16.0	SST	CG	N
1.094	27.79	4130	5.38	136.5	.914	23.2	9.3	1.6	2.4	60	22	98	1.08	27.4	0.090	2.3	12.0	SPR	CG	Z
1.094	27.79	11709	6.00	152.4	.910	23.1	7.9	1.4	3.0	76	24	105	1.38	35.1	0.092	2.3	15.0	SPR	CG	Z
1.094	27.79	3471	7.50	190.5	.766	19.5	57	10	2.0	52	117	522	4.18	106.2	0.164	4.2	24.5	SPR	C	Z
1.094	27.79	1643	7.88	200.0	.884	22.5	7.5	1.3	4.6	117	35	154	2.73	69.3	0.105	2.7	26.0	SPR	CG	Z
1.094	27.79	12180	8.19	207.9	.888	22.6	6.9	1.2	4.7	120	33	146	2.68	68.0	0.103	2.6	26.0	SPR	CG	Z
1.094	27.79	361	11.3	285.8	.740	18.8	46	8.0	3.2	81	146	651	7.43	188.8	0.177	4.5	42.0	HD	CG	Z
1.100	27.94	72504	.88	22.4	.936	23.8	43	7.5	.57	14	24	108	.29	7.3	0.082	2.1	3.50	MW	CG	N
1.100	27.94	72504S	.88	22.4	.936	23.8	36	6.3	.45	11	16	72	.29	7.3	0.082	2.1	3.50	SST	CG	N
1.100	27.94	72514	.88	22.4	.930	23.6	45	7.9	.57	15	26	115	.31	7.8	0.085	2.2	3.63	MW	CG	N
1.100	27.94	72514S	.88	22.4	.930	23.6	38	6.7	.47	12	18	80	.31	7.8	0.085	2.2	3.63	SST	CG	N
1.100	27.94	72527	.88	22.4	.914	23.2	65	11	.52	13	34	150	.34	8.6	0.093	2.4	3.63	MW	CG	N
1.100	27.94	72527S	.88	22.4	.914	23.2	55	9.6	.41	10	22	100	.34	8.6	0.093	2.4	3.63	SST	CG	N
1.100	27.94	72537	.88	22.4	.908	23.1	70	12	.52	13	36	161	.36	9.1	0.096	2.4	3.75	MW	CG	N
1.100	27.94	72537S	.88	22.4	.908	23.1	59	10	.41	11	25	109	.36	9.1	0.096	2.4	3.75	SST	CG	N
1.100	27.94	72549	.88	22.4	.890	22.6	98	17	.47	12	46	206	.41	10.3	0.105	2.7	3.88	MW	CG	N
1.100	27.94	72549S	.88	22.4	.890	22.6	83	15	.39	9.8	32	142	.41	10.3	0.105	2.7	3.88	SST	CG	N
1.100	27.94	72560	.88	22.4	.876	22.3	126	22	.45	11	56	249	.43	11.0	0.112	2.8	3.88	MW	CG	N
1.100	27.94	72560S	.88	22.4	.876	22.3	107	19	.35	8.8	37	164	.43	11.0	0.112	2.8	3.88	SST	CG	N
1.100	27.94	72582	.88	22.4	.850	21.6	194	34	.38	9.7	74	328	.50	12.7	0.125	3.2	4.00	MW	CG	N
1.100	27.94	72582S	.88	22.4	.850	21.6	165	29	.31	7.8	51	227	.50	12.7	0.125	3.2	4.00	SST	CG	N
1.100	27.94	72505	1.00	25.4	.936	23.8	36	6.3	.67	17	24	108	.31	7.8	0.082	2.1	3.75	MW	CG	N
1.100	27.94	72505S	1.00	25.4	.936	23.8	31	5.4	.53	13	16	72	.31	7.8	0.082	2.1	3.75	SST	CG	N
1.100	27.94	72515	1.00	25.4	.930	23.6	38	6.7	.67	17	26	114	.33	8.4	0.085	2.2	3.88	MW	CG	N
1.100	27.94	72515S	1.00	25.4	.930	23.6	33	5.7	.55	14	18	80	.33	8.4	0.085	2.2	3.88	SST	CG	N
1.100	27.94	72528	1.00	25.4	.914	23.2	55	9.6	.62	16	34	150	.36	9.2	0.093	2.4	3.88	MW	CG	N
1.100	27.94	72528S	1.00	25.4	.914	23.2	46	8.1	.48	12	22	100	.36	9.2	0.093	2.4	3.88	SST	CG	N
1.100	27.94	72538	1.00	25.4	.908	23.1	59	10	.62	16	36	162	.38	9.8	0.096	2.4	4.00	MW	CG	N
1.100	27.94	72538S	1.00	25.4	.908	23.1</														

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.100	27.94	72516S	1.25	31.8	.930	23.6	25	4.4	.72	18	18	80	.37	9.4	0.085	2.2	4.38	SST	CG	N
1.100	27.94	72529	1.25	31.8	.914	23.2	43	7.4	.79	20	34	150	.42	10.6	0.093	2.4	4.50	MW	CG	N
1.100	27.94	72529S	1.25	31.8	.914	23.2	36	6.3	.62	16	22	100	.42	10.6	0.093	2.4	4.50	SST	CG	N
1.100	27.94	72539	1.25	31.8	.908	23.1	45	7.9	.81	20	36	162	.44	11.3	0.096	2.4	4.63	MW	CG	N
1.100	27.94	72539S	1.25	31.8	.908	23.1	38	6.7	.64	16	25	109	.44	11.3	0.096	2.4	4.63	SST	CG	N
1.100	27.94	72551	1.25	31.8	.890	22.6	62	11	.74	19	46	205	.51	13.0	0.105	2.7	4.88	MW	CG	N
1.100	27.94	72551S	1.25	31.8	.890	22.6	53	9.3	.60	15	32	142	.51	13.0	0.105	2.7	4.88	SST	CG	N
1.100	27.94	72562	1.25	31.8	.876	22.3	80	14	.69	18	55	244	.56	14.2	0.112	2.8	5.00	MW	CG	N
1.100	27.94	72562S	1.25	31.8	.876	22.3	68	12	.55	14	37	164	.56	14.2	0.112	2.8	5.00	SST	CG	N
1.100	27.94	72584	1.25	31.8	.850	21.6	122	21	.61	15	75	332	.64	16.3	0.125	3.2	5.13	MW	CG	N
1.100	27.94	72584S	1.25	31.8	.850	21.6	104	18	.49	12	51	227	.64	16.3	0.125	3.2	5.13	SST	CG	N
1.100	27.94	72507	1.50	38.1	.936	23.8	23	4.0	1.1	27	24	108	.39	9.9	0.082	2.1	4.75	MW	CG	N
1.100	27.94	72507S	1.50	38.1	.936	23.8	19	3.4	.84	21	16	72	.39	9.9	0.082	2.1	4.75	SST	CG	N
1.100	27.94	72517	1.50	38.1	.930	23.6	24	4.2	1.1	27	26	114	.43	10.8	0.085	2.2	5.00	MW	CG	N
1.100	27.94	72517S	1.50	38.1	.930	23.6	20	3.6	.89	23	18	80	.43	10.8	0.085	2.2	5.00	SST	CG	N
1.100	27.94	72530	1.50	38.1	.914	23.2	34	6.0	.98	25	34	150	.48	12.1	0.093	2.4	5.13	MW	CG	N
1.100	27.94	72530S	1.50	38.1	.914	23.2	29	5.1	.77	19	22	100	.48	12.1	0.093	2.4	5.13	SST	CG	N
1.100	27.94	72540	1.50	38.1	.908	23.1	37	6.4	1.0	25	36	162	.50	12.8	0.096	2.4	5.25	MW	CG	N
1.100	27.94	72540S	1.50	38.1	.908	23.1	31	5.4	.79	20	25	109	.50	12.8	0.096	2.4	5.25	SST	CG	N
1.100	27.94	72552	1.50	38.1	.890	22.6	50	8.8	.92	23	46	206	.58	14.7	0.105	2.7	5.50	MW	CG	N
1.100	27.94	72552S	1.50	38.1	.890	22.6	43	7.5	.75	19	32	142	.58	14.7	0.105	2.7	5.50	SST	CG	N
1.100	27.94	72563	1.50	38.1	.876	22.3	68	12	.84	21	56	251	.62	15.6	0.112	2.8	5.50	MW	CG	N
1.100	27.94	72563S	1.50	38.1	.876	22.3	57	10	.64	16	37	164	.62	15.6	0.112	2.8	5.50	SST	CG	N
1.100	27.94	72573	1.50	38.1	.860	21.8	93	16	.75	19	69	308	.65	16.4	0.120	3.0	5.38	MW	CG	N
1.100	27.94	72573S	1.50	38.1	.860	21.8	79	14	.57	15	45	201	.65	16.4	0.120	3.0	5.38	SST	CG	N
1.100	27.94	72585	1.50	38.1	.850	21.6	105	18	.74	19	78	347	.70	17.9	0.125	3.2	5.63	MW	CG	N
1.100	27.94	72585S	1.50	38.1	.850	21.6	89	16	.57	15	51	227	.70	17.9	0.125	3.2	5.63	SST	CG	N
1.100	27.94	72594	1.50	38.1	.830	21.1	137	24	.69	18	95	423	.79	20.1	0.135	3.4	5.88	MW	CG	N
1.100	27.94	72594S	1.50	38.1	.830	21.1	116	20	.53	13	61	272	.79	20.1	0.135	3.4	5.88	SST	CG	N
1.100	27.94	72508	1.75	44.5	.936	23.8	19	3.3	1.3	32	24	108	.43	10.9	0.082	2.1	5.25	MW	CG	N
1.100	27.94	72508S	1.75	44.5	.936	23.8	16	2.8	1.0	25	16	72	.43	10.9	0.082	2.1	5.25	SST	CG	N
1.100	27.94	72519	1.75	44.5	.930	23.6	21	3.6	1.3	33	27	119	.47	11.9	0.085	2.2	5.50	MW	CG	N
1.100	27.94	72519S	1.75	44.5	.930	23.6	18	3.1	1.0	26	18	80	.47	11.9	0.085	2.2	5.50	SST	CG	N
1.100	27.94	72531	1.75	44.5	.914	23.2	29	5.1	1.2	30	34	150	.52	13.3	0.093	2.4	5.63	MW	CG	N
1.100	27.94	72531S	1.75	44.5	.914	23.2	25	4.3	.91	23	22	100	.52	13.3	0.093	2.4	5.63	SST	CG	N
1.100	27.94	72542	1.75	44.5	.908	23.1	31	5.3	1.2	30	36	159	.58	14.6	0.096	2.4	6.00	MW	CG	N
1.100	27.94	72542S	1.75	44.5	.908	23.1	26	4.5	.95	24	25	109	.58	14.6	0.096	2.4	6.00	SST	CG	N
1.100	27.94	72553	1.75	44.5	.890	22.6	42	7.4	1.1	28	46	204	.66	16.7	0.105	2.7	6.25	MW	CG	N
1.100	27.94	72553S	1.75	44.5	.890	22.6	36	6.3	.90	23	32	142	.66	16.7	0.105	2.7	6.25	SST	CG	N
1.100	27.94	72564	1.75	44.5	.876	22.3	56	9.9	1.0	25	56	251	.69	17.4	0.112	2.8	6.13	MW	CG	N
1.100	27.94	72564S	1.75	44.5	.876	22.3	48	8.4	.77	20	37	164	.69	17.4	0.112	2.8	6.13	SST	CG	N
1.100	27.94	72574	1.75	44.5	.860	21.8	77	14	.90	23	69	308	.74	18.7	0.120	3.0	6.13	MW	CG	N
1.100	27.94	72574S	1.75	44.5	.860	21.8	66	11	.69	17	45	201	.74	18.7	0.120	3.0	6.13	SST	CG	N
1.100	27.94	72586	1.75	44.5	.850	21.6	86	15	.90	23	78	347	.80	20.2	0.125	3.2	6.38	MW	CG	N
1.100	27.94	72586S	1.75	44.5	.850	21.6	73	13	.69	18	51	227	.80	20.2	0.125	3.2	6.38	SST	CG	N
1.100	27.94	72596	1.75	44.5	.830	21.1	113	20	.84	21	95	423	.89	22.7	0.135	3.4	6.63	MW	CG	N
1.100	27.94	72596S	1.75	44.5	.830	21.1	96	17	.63	16	61	272	.89	22.7	0.135	3.4	6.63	SST	CG	N
1.100	27.94	72605	1.75	44.5	.816	20.7	150	26	.73	19	110	490	.91	23.0	0.142	3.6	6.38	MW	CG	N
1.100	27.94	72605S	1.75	44.5	.816	20.7	128	22	.56	14	71	316	.91	23.0	0.142	3.6	6.38	SST	CG	N
1.100	27.94	72617	1.75	44.5	.804	20.4	175	31	.71	18	124	553	.98	24.9	0.148	3.8	6.63	MW	CG	N
1.100	27.94	72617S	1.75	44.5	.804	20.4	149	26	.54	14	80	356	.98	24.9	0.148	3.8	6.63	SST	CG	N
1.100	27.94	72509	2.00	50.8	.936	23.8	17	2.9	1.5	37	24	108	.47	12.0	0.082	2.1	5.75	MW	CG	N
1.100	27.94	72509S	2.00	50.8	.936	23.8	14	2.5	1.2	29	16	72	.47	12.0	0.082	2.1	5.75	SST	CG	N
1.100	27.94	72520	2.00	50.8	.930	23.6	17	3.0	1.5	38	26	114	.52	13.2	0.085	2.2	6.13	MW	CG	N
1.100	27.94	72520S	2.00	50.8	.930	23.6	15	2.6	1.2	31	18	80	.52	13.2	0.085	2.2	6.13	SST	CG	N
1.100	27.94	72532	2.00	50.8	.914	23.2	25	4.4	1.4	34	34	150	.58	14.8	0.093	2.4	6.25	MW	CG	N
1.100	27.94	72532S	2.00	50.8	.914	23.2	21	3.7	1.1	27	22	100	.58	14.8	0.093	2.4	6.25	SST	CG	N
1.100	27.94	72543	2.00	50.8	.908	23.1	26	4.6	1.4	35	36	160	.64	16.2	0.096	2.4	6.63	MW	CG	N
1.100	27.94	72543S	2.00	50.8	.908	23.1	22	3.9	1.1	28	25	109	.64	16.2	0.096	2.4	6.63	SST	CG	N
1.100	27.94	72554	2.00	50.8	.890	22.6	36	6.3	1.3	32	46	206	.72	18.3	0.105	2.7	6.88	MW	CG	N
1.100	27.94	72554S	2.00	50.8	.890	22.6	31	5.4	1.0	26	32	142	.72	18.3	0.105	2.7	6.88	SST	CG	N
1.100	27.94	72565	2.00	50.8	.876	22.3	49	8.5	1.2	30	56	251	.77	19.6	0.112	2.8	6.88	MW	CG	N
1.100	27.94	72565S	2.00	50.8	.876	22.3	41	7.2	.89	23	37	164	.77	19.6	0.112	2.8	6.88	SST	CG	N
1.100	27.94	72575	2.00	50.8	.860	21.8	66	12	1.0	27	69	308	.81	20.6	0.120	3.0	6.75	MW	CG	N
1.100	27.94	72575S	2.00	50.8	.860	21.8	56	9.9	.80	20	45	201	.81	20.6	0.120	3.0	6.75	SST	CG	N
1.100	27.94	72587	2.00	50.8	.850	21.6	74	13	1.0	27	78	347	.89	22.6	0.125	3.2	7.13	MW	CG	N
1.100	27.94	72587S	2.00	50.8	.850	21.6	63	11	.80	20	51	227	.89	22.6	0.125	3.2	7.13	SST	CG	N
1.100	27.94	72597	2.00	50.8	.830	21.1	98	17	.97	25	95	423	1.01	25.7	0.135	3.4	7.50	MW	CG	N
1.100	27.94	72597S	2.00	50.8	.830	21.1	83	15</												




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.100	27.94	72588S	2.25	57.2	.850	21.6	55	9.7	.92	23	51	227	.98	25.0	0.125	3.2	7.88	SST	CG	N
1.100	27.94	72598	2.25	57.2	.830	21.1	88	15	1.1	27	95	423	1.08	27.4	0.135	3.4	8.00	MW	CG	N
1.100	27.94	72598S	2.25	57.2	.830	21.1	75	13	.82	21	61	272	1.08	27.4	0.135	3.4	8.00	SST	CG	N
1.100	27.94	72608	2.25	57.2	.816	20.7	111	19	.99	25	110	490	1.14	28.9	0.142	3.6	8.00	MW	CG	N
1.100	27.94	72608S	2.25	57.2	.816	20.7	94	17	.75	19	71	316	1.14	28.9	0.142	3.6	8.00	SST	CG	N
1.100	27.94	72619	2.25	57.2	.804	20.4	130	23	.96	24	124	553	1.20	30.5	0.148	3.8	8.13	MW	CG	N
1.100	27.94	72619S	2.25	57.2	.804	20.4	111	19	.72	18	80	356	1.20	30.5	0.148	3.8	8.13	SST	CG	N
1.100	27.94	72510	2.50	63.5	.936	23.8	13	2.3	1.9	47	24	108	.55	14.1	0.082	2.1	6.75	MW	CG	N
1.100	27.94	72510S	2.50	63.5	.936	23.8	11	1.9	1.5	37	16	72	.55	14.1	0.082	2.1	6.75	SST	CG	N
1.100	27.94	72521	2.50	63.5	.930	23.6	14	2.4	1.9	48	26	115	.62	15.7	0.085	2.2	7.25	MW	CG	N
1.100	27.94	72521S	2.50	63.5	.930	23.6	12	2.0	1.5	39	18	80	.62	15.7	0.085	2.2	7.25	SST	CG	N
1.100	27.94	72533	2.50	63.5	.914	23.2	20	3.4	1.7	44	34	150	.69	17.4	0.093	2.4	7.38	MW	CG	N
1.100	27.94	72533S	2.50	63.5	.914	23.2	17	2.9	1.4	34	22	100	.69	17.4	0.093	2.4	7.38	SST	CG	N
1.100	27.94	72544	2.50	63.5	.908	23.1	21	3.6	1.7	44	36	161	.76	19.2	0.096	2.4	7.88	MW	CG	N
1.100	27.94	72544S	2.50	63.5	.908	23.1	18	3.1	1.4	35	25	109	.76	19.2	0.096	2.4	7.88	SST	CG	N
1.100	27.94	72555	2.50	63.5	.890	22.6	28	5.0	1.6	41	46	206	.87	22.0	0.105	2.7	8.25	MW	CG	N
1.100	27.94	72555S	2.50	63.5	.890	22.6	24	4.2	1.3	34	32	142	.87	22.0	0.105	2.7	8.25	SST	CG	N
1.100	27.94	72567	2.50	63.5	.876	22.3	38	6.6	1.5	38	56	251	.92	23.5	0.112	2.8	8.25	MW	CG	N
1.100	27.94	72567S	2.50	63.5	.876	22.3	32	5.6	1.1	29	37	164	.92	23.5	0.112	2.8	8.25	SST	CG	N
1.100	27.94	72577	2.50	63.5	.860	21.8	52	9.0	1.3	34	69	308	.98	24.8	0.120	3.0	8.13	MW	CG	N
1.100	27.94	72577S	2.50	63.5	.860	21.8	44	7.7	1.0	26	45	201	.98	24.8	0.120	3.0	8.13	SST	CG	N
1.100	27.94	72589	2.50	63.5	.850	21.6	58	10	1.4	34	78	347	1.08	27.4	0.125	3.2	8.63	MW	CG	N
1.100	27.94	72589S	2.50	63.5	.850	21.6	49	8.6	1.0	26	51	227	1.08	27.4	0.125	3.2	8.63	SST	CG	N
1.100	27.94	72599	2.50	63.5	.830	21.1	76	13	1.3	32	95	423	1.22	30.9	0.135	3.4	9.00	MW	CG	N
1.100	27.94	72599S	2.50	63.5	.830	21.1	65	11	.95	24	61	272	1.22	30.9	0.135	3.4	9.00	SST	CG	N
1.100	27.94	72609	2.50	63.5	.816	20.7	98	17	1.1	29	110	490	1.24	31.6	0.142	3.6	8.75	MW	CG	N
1.100	27.94	72609S	2.50	63.5	.816	20.7	83	15	.85	22	71	316	1.24	31.6	0.142	3.6	8.75	SST	CG	N
1.100	27.94	72620	2.50	63.5	.804	20.4	115	20	1.1	27	124	553	1.31	33.4	0.148	3.8	8.88	MW	CG	N
1.100	27.94	72620S	2.50	63.5	.804	20.4	98	17	.82	21	80	356	1.31	33.4	0.148	3.8	8.88	SST	CG	N
1.100	27.94	72610	2.75	69.9	.816	20.7	88	15	1.3	32	110	490	1.35	34.3	0.142	3.6	9.50	MW	CG	N
1.100	27.94	72610S	2.75	69.9	.816	20.7	75	13	.95	24	71	316	1.35	34.3	0.142	3.6	9.50	SST	CG	N
1.100	27.94	72621	2.75	69.9	.804	20.4	104	18	1.2	30	124	553	1.44	36.7	0.148	3.8	9.75	MW	CG	N
1.100	27.94	72621S	2.75	69.9	.804	20.4	88	15	.91	23	80	356	1.44	36.7	0.148	3.8	9.75	SST	CG	N
1.100	27.94	72511	3.00	76.2	.936	23.8	11	1.9	2.3	57	24	108	.64	16.1	0.082	2.1	7.75	MW	CG	N
1.100	27.94	72511S	3.00	76.2	.936	23.8	9.1	1.6	1.8	45	16	72	.64	16.1	0.082	2.1	7.75	SST	CG	N
1.100	27.94	72522	3.00	76.2	.930	23.6	11	2.0	2.3	58	26	114	.71	18.1	0.085	2.2	8.38	MW	CG	N
1.100	27.94	72522S	3.00	76.2	.930	23.6	9.5	1.7	1.9	48	18	80	.71	18.1	0.085	2.2	8.38	SST	CG	N
1.100	27.94	72534	3.00	76.2	.914	23.2	16	2.8	2.1	54	34	150	.80	20.4	0.093	2.4	8.63	MW	CG	N
1.100	27.94	72534S	3.00	76.2	.914	23.2	14	2.4	1.6	42	22	100	.80	20.4	0.093	2.4	8.63	SST	CG	N
1.100	27.94	72545	3.00	76.2	.908	23.1	17	3.0	2.1	54	36	161	.88	22.3	0.096	2.4	9.13	MW	CG	N
1.100	27.94	72545S	3.00	76.2	.908	23.1	14	2.5	1.7	43	25	109	.88	22.3	0.096	2.4	9.13	SST	CG	N
1.100	27.94	72556	3.00	76.2	.890	22.6	23	4.1	2.0	51	46	206	1.01	25.7	0.105	2.7	9.63	MW	CG	N
1.100	27.94	72556S	3.00	76.2	.890	22.6	20	3.5	1.6	41	32	142	1.01	25.7	0.105	2.7	9.63	SST	CG	N
1.100	27.94	72568	3.00	76.2	.876	22.3	31	5.4	1.8	46	56	251	1.06	27.0	0.112	2.8	9.50	MW	CG	N
1.100	27.94	72568S	3.00	76.2	.876	22.3	26	4.6	1.4	35	37	164	1.06	27.0	0.112	2.8	9.50	SST	CG	N
1.100	27.94	72578	3.00	76.2	.860	21.8	42	7.4	1.6	42	69	308	1.14	29.0	0.120	3.0	9.50	MW	CG	N
1.100	27.94	72578S	3.00	76.2	.860	21.8	36	6.3	1.3	32	45	201	1.14	29.0	0.120	3.0	9.50	SST	CG	N
1.100	27.94	72590	3.00	76.2	.850	21.6	47	8.3	1.7	42	78	347	1.25	31.8	0.125	3.2	10.0	MW	CG	N
1.100	27.94	72590S	3.00	76.2	.850	21.6	40	7.0	1.3	32	51	227	1.25	31.8	0.125	3.2	10.0	SST	CG	N
1.100	27.94	72600	3.00	76.2	.830	21.1	62	11	1.5	39	95	423	1.42	36.0	0.135	3.4	10.5	MW	CG	N
1.100	27.94	72600S	3.00	76.2	.830	21.1	53	9.3	1.2	29	61	272	1.42	36.0	0.135	3.4	10.5	SST	CG	N
1.100	27.94	72611	3.00	76.2	.816	20.7	80	14	1.4	35	110	490	1.46	37.0	0.142	3.6	10.3	MW	CG	N
1.100	27.94	72611S	3.00	76.2	.816	20.7	68	12	1.0	27	71	316	1.46	37.0	0.142	3.6	10.3	SST	CG	N
1.100	27.94	72622	3.00	76.2	.804	20.4	94	16	1.3	34	124	553	1.55	39.5	0.148	3.8	10.5	MW	CG	N
1.100	27.94	72622S	3.00	76.2	.804	20.4	80	14	1.0	25	80	356	1.55	39.5	0.148	3.8	10.5	SST	CG	N
1.100	27.94	72612	3.31	84.1	.816	20.7	64	11	1.6	39	99	442	1.76	44.6	0.142	3.6	12.4	MW	CG	N
1.100	27.94	72612S	3.31	84.1	.816	20.7	54	9.5	1.3	33	71	316	1.76	44.6	0.142	3.6	12.4	SST	CG	N
1.100	27.94	72512	3.50	88.9	.936	23.8	9.1	1.6	2.7	68	24	108	.72	18.2	0.082	2.1	8.75	MW	CG	N
1.100	27.94	72512S	3.50	88.9	.936	23.8	7.7	1.4	2.1	53	16	72	.72	18.2	0.082	2.1	8.75	SST	CG	N
1.100	27.94	72523	3.50	88.9	.930	23.6	9.6	1.7	2.7	68	26	115	.81	20.5	0.085	2.2	9.50	MW	CG	N
1.100	27.94	72523S	3.50	88.9	.930	23.6	8.2	1.4	2.2	56	18	80	.81	20.5	0.085	2.2	9.50	SST	CG	N
1.100	27.94	72535	3.50	88.9	.914	23.2	14	2.4	2.5	63	34	150	.91	23.0	0.093	2.4	9.75	MW	CG	N
1.100	27.94	72535S	3.50	88.9	.914	23.2	12	2.0	1.9	49	22	100	.91	23.0	0.093	2.4	9.75	SST	CG	N
1.100	27.94	72546	3.50	88.9	.908	23.1	14	2.5	2.5	64	36	160	1.00	25.3	0.096	2.4	10.4	MW	CG	N
1.100	27.94	72546S	3.50	88.9	.908	23.1	12	2.1	2.0	51	25	109	1.00	25.3	0.096	2.4	10.4	SST	CG	N
1.100	27.94	72557	3.50	88.9	.890	22.6	20	3.4	2.3	60	46	205	1.16	29.3	0.105	2.7	11.0	MW	CG	N
1.100	27.94	72557S	3.50	88.9	.890	22.6	17	2.9	1.9	49	32	142	1.16	29.3	0.105	2.7	11.0	SST	CG	N
1.100	27.94	72569	3.50	88.9	.876	22.3	26	4.6	2.1											

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.100	27.94	72513S	4.00	101.6	.936	23.8	6.7	1.2	2.4	61	16	72	.80	20.3	0.082	2.1	9.75	SST	CG	N
1.100	27.94	72524	4.00	101.6	.930	23.6	8.3	1.5	3.1	79	26	114	.90	22.9	0.085	2.2	10.6	MW	CG	N
1.100	27.94	72524S	4.00	101.6	.930	23.6	7.1	1.2	2.6	65	18	80	.90	22.9	0.085	2.2	10.6	SST	CG	N
1.100	27.94	72536	4.00	101.6	.914	23.2	12	2.1	2.9	72	34	150	1.01	25.7	0.093	2.4	10.9	MW	CG	N
1.100	27.94	72536S	4.00	101.6	.914	23.2	10	1.8	2.2	56	22	100	1.01	25.7	0.093	2.4	10.9	SST	CG	N
1.100	27.94	72547	4.00	101.6	.908	23.1	13	2.2	2.9	73	36	160	1.12	28.3	0.096	2.4	11.6	MW	CG	N
1.100	27.94	72547S	4.00	101.6	.908	23.1	11	1.9	2.3	59	25	109	1.12	28.3	0.096	2.4	11.6	SST	CG	N
1.100	27.94	72558	4.00	101.6	.890	22.6	17	3.0	2.7	69	46	205	1.30	33.0	0.105	2.7	12.4	MW	CG	N
1.100	27.94	72558S	4.00	101.6	.890	22.6	15	2.5	2.2	56	32	142	1.30	33.0	0.105	2.7	12.4	SST	CG	N
1.100	27.94	72570	4.00	101.6	.876	22.3	23	4.0	2.5	63	56	251	1.37	34.8	0.112	2.8	12.3	MW	CG	N
1.100	27.94	72570S	4.00	101.6	.876	22.3	19	3.4	1.9	48	37	164	1.37	34.8	0.112	2.8	12.3	SST	CG	N
1.100	27.94	72580	4.00	101.6	.860	21.8	31	5.4	2.2	57	69	308	1.47	37.3	0.120	3.0	12.3	MW	CG	N
1.100	27.94	72580S	4.00	101.6	.860	21.8	26	4.6	1.7	44	45	201	1.47	37.3	0.120	3.0	12.3	SST	CG	N
1.100	27.94	72592	4.00	101.6	.850	21.6	34	6.0	2.3	58	78	347	1.63	41.3	0.125	3.2	13.0	MW	CG	N
1.100	27.94	72592S	4.00	101.6	.850	21.6	29	5.1	1.7	44	51	227	1.63	41.3	0.125	3.2	13.0	SST	CG	N
1.100	27.94	72602	4.00	101.6	.830	21.1	45	7.9	2.1	54	95	423	1.86	47.1	0.135	3.4	13.8	MW	CG	N
1.100	27.94	72602S	4.00	101.6	.830	21.1	38	6.7	1.6	41	61	272	1.86	47.1	0.135	3.4	13.8	SST	CG	N
1.100	27.94	72614	4.00	101.6	.816	20.7	59	10	1.9	47	110	490	1.88	47.8	0.142	3.6	13.3	MW	CG	N
1.100	27.94	72614S	4.00	101.6	.816	20.7	50	8.8	1.4	36	71	316	1.88	47.8	0.142	3.6	13.3	SST	CG	N
1.100	27.94	72624	4.00	101.6	.804	20.4	69	12	1.8	46	124	553	2.02	51.2	0.148	3.8	13.6	MW	CG	N
1.100	27.94	72624S	4.00	101.6	.804	20.4	58	10	1.4	35	80	356	2.02	51.2	0.148	3.8	13.6	SST	CG	N
1.100	27.94	72525	4.50	114.3	.930	23.6	7.3	1.3	3.5	89	25	113	1.01	25.6	0.085	2.2	11.9	MW	CG	N
1.100	27.94	72525S	4.50	114.3	.930	23.6	6.2	1.1	2.9	74	18	80	1.01	25.6	0.085	2.2	11.9	SST	CG	N
1.100	27.94	72548	4.50	114.3	.908	23.1	11	1.9	3.3	83	36	161	1.24	31.4	0.096	2.4	12.9	MW	CG	N
1.100	27.94	72548S	4.50	114.3	.908	23.1	9.4	1.7	2.6	66	25	109	1.24	31.4	0.096	2.4	12.9	SST	CG	N
1.100	27.94	72559	4.50	114.3	.890	22.6	15	2.6	3.1	78	46	205	1.44	36.7	0.105	2.7	13.8	MW	CG	N
1.100	27.94	72559S	4.50	114.3	.890	22.6	13	2.2	2.5	64	32	142	1.44	36.7	0.105	2.7	13.8	SST	CG	N
1.100	27.94	72571	4.50	114.3	.876	22.3	20	3.5	2.8	71	56	251	1.53	38.8	0.112	2.8	13.6	MW	CG	N
1.100	27.94	72571S	4.50	114.3	.876	22.3	17	3.0	2.2	55	37	164	1.53	38.8	0.112	2.8	13.6	SST	CG	N
1.100	27.94	72581	4.50	114.3	.860	21.8	27	4.8	2.5	64	69	308	1.64	41.5	0.120	3.0	13.6	MW	CG	N
1.100	27.94	72581S	4.50	114.3	.860	21.8	23	4.1	1.9	49	45	201	1.64	41.5	0.120	3.0	13.6	SST	CG	N
1.100	27.94	72593	4.50	114.3	.850	21.6	30	5.3	2.6	65	78	347	1.81	46.0	0.125	3.2	14.5	MW	CG	N
1.100	27.94	72593S	4.50	114.3	.850	21.6	26	4.5	2.0	50	51	227	1.81	46.0	0.125	3.2	14.5	SST	CG	N
1.100	27.94	72603	4.50	114.3	.830	21.1	39	6.9	2.4	61	95	422	2.09	53.1	0.135	3.4	15.5	MW	CG	N
1.100	27.94	72603S	4.50	114.3	.830	21.1	34	5.9	1.8	46	61	272	2.09	53.1	0.135	3.4	15.5	SST	CG	N
1.100	27.94	72615	4.50	114.3	.816	20.7	51	8.9	2.2	55	110	490	2.13	54.1	0.142	3.6	15.0	MW	CG	N
1.100	27.94	72615S	4.50	114.3	.816	20.7	43	7.6	1.6	42	71	316	2.13	54.1	0.142	3.6	15.0	SST	CG	N
1.100	27.94	72625	4.50	114.3	.804	20.4	61	11	2.1	52	124	553	2.26	57.3	0.148	3.8	15.3	MW	CG	N
1.100	27.94	72625S	4.50	114.3	.804	20.4	51	9.0	1.6	40	80	356	2.26	57.3	0.148	3.8	15.3	SST	CG	N
1.100	27.94	72526	5.00	127.0	.930	23.6	6.6	1.2	3.9	99	26	115	1.09	27.8	0.085	2.2	12.9	MW	CG	N
1.100	27.94	72526S	5.00	127.0	.930	23.6	5.6	.98	3.2	82	18	80	1.09	27.8	0.085	2.2	12.9	SST	CG	N
1.100	27.94	72604	5.00	127.0	.830	21.1	35	6.2	2.7	68	95	423	2.30	58.3	0.135	3.4	17.0	MW	CG	N
1.100	27.94	72604S	5.00	127.0	.830	21.1	30	5.3	2.0	52	61	272	2.30	58.3	0.135	3.4	17.0	SST	CG	N
1.100	27.94	72616	5.00	127.0	.816	20.7	46	8.1	2.4	61	110	490	2.34	59.5	0.142	3.6	16.5	MW	CG	N
1.100	27.94	72616S	5.00	127.0	.816	20.7	39	6.8	1.8	46	71	316	2.34	59.5	0.142	3.6	16.5	SST	CG	N
1.100	27.94	72626	5.00	127.0	.804	20.4	54	9.5	2.3	58	124	553	2.48	63.0	0.148	3.8	16.8	MW	CG	N
1.100	27.94	72626S	5.00	127.0	.804	20.4	46	8.1	1.7	44	80	356	2.48	63.0	0.148	3.8	16.8	SST	CG	N
1.109	28.17	11-8	.69	17.4	.869	22.1	308	54	.16	4.1	49	219	.36	9.1	0.120	3.0	3.00	SPR	CG	N
1.109	28.17	1869	.75	19.1	.965	24.5	8.7	1.5	.32	8.1	2.8	12	.43	11.0	0.072	1.8	6.00	HD	CG	Z
1.109	28.17	S-1258	1.00	25.4	.899	22.8	75	13	.42	11	32	141	.42	10.7	0.105	2.7	4.00	SST	CG	Z
1.109	28.17	3752	1.00	25.4	.859	21.8	134	23	.41	10	54	242	.59	15.1	0.125	3.2	4.75	SPR	CG	Z
1.109	28.17	DD-27	1.06	27.0	.769	19.5	857	150	.13	3.4	114	508	.60	15.1	0.170	4.3	3.50	SST	CG	N
1.109	28.17	LL-100	1.09	27.8	.949	24.1	13	2.2	.59	15	7.6	34	.50	12.7	0.080	2.0	6.25	SPR	CG	N
1.109	28.17	S-34	1.16	29.4	.983	25.0	2.9	.51	.67	17	2.0	8.7	.48	12.3	0.063	1.6	7.50	SST	CG	N
1.109	28.17	11705	1.16	29.4	.921	23.4	36	6.3	.69	17	25	109	.47	11.9	0.094	2.4	5.00	SPR	CG	Z
1.109	28.17	12160	1.25	31.8	.919	23.3	56	9.8	.45	12	26	113	.38	9.7	0.095	2.4	4.00	SPR	CG	Z
1.109	28.17	10621	1.28	32.5	.927	23.5	31	5.5	.72	18	22	100	.46	11.6	0.091	2.3	5.00	SPR	CG	Z
1.109	28.17	12562	1.30	32.9	.993	25.2	7.0	1.2	.92	23	6.5	29	.29	7.4	0.058	1.5	4.00	SPR	C	N
1.109	28.17	S-55	1.38	34.9	.869	22.1	62	11	.62	16	38	169	.76	19.3	0.120	3.0	6.33	SST	CG	N
1.109	28.17	HH-33	1.38	34.9	.809	20.5	206	36	.43	11	90	398	.90	22.9	0.150	3.8	6.00	SPR	CG	N
1.109	28.17	11697	1.53	38.9	.885	22.5	57	10	.70	18	40	178	.67	17.1	0.112	2.8	6.00	SPR	CG	Z
1.109	28.17	2681	1.78	45.2	.861	21.9	59	10	.79	20	47	208	.99	25.2	0.124	3.1	8.00	HD	CG	Z
1.109	28.17	UU-39	1.78	45.2	.795	20.2	184	32	.56	14	102	455	1.18	29.9	0.157	4.0	7.50	SPR	CG	Z
1.109	28.17	S-3060	2.00	50.8	.813	20.7	135	24	.59	15	79	353	1.04	26.3	0.148	3.8	7.00	SST	CG	N
1.109	28.17	B17-150	2.13	54.0	1.013	25.7	.94	.17	1.7	44	1.6	7.3	.38	9.8	0.048	1.2	8.00	SST	CG	N
1.109	28.17	S-1415	2.19	55.6	.959	24.4	4.8	.84	1.5	37	7.0	31	.71	18.1	0.075	1.9	9.50	SST	CG	N
1.109	28.17	11864	2.25	57.2	.737	18.7	299	52	.46	12	137	610	1.58	40.2	0.186	4.7	8.50	SST	CG	N
1.109	28.17	11717	2.56	65.1	.885	22.5	38													




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.109	28.17	3360	4.50	114.3	.909	23.1	11	1.9	2.8	70	30	132	1.60	40.6	0.100	2.5	15.0	SPR	C	Z
1.109	28.17	S-3256	4.91	124.6	.951	24.2	4.5	.80	3.2	81	14	64	.95	24.1	0.079	2.0	12.0	SST	CG	N
1.109	28.17	2727	5.13	130.2	.949	24.1	5.4	.95	4.1	104	22	98	1.04	26.4	0.080	2.0	12.0	MW	C	Z
1.109	28.17	394	8.00	203.2	.889	22.6	8.8	1.5	4.3	110	38	169	2.86	72.6	0.110	2.8	26.0	SPR	CG	Z
1.109	28.17	1817	10.0	254.0	.899	22.8	6.4	1.1	6.9	174	44	195	3.15	80.0	0.105	2.7	29.0	MW	C	Z
1.109	28.17	4039	19.5	495.3	.809	20.5	18	3.2	4.9	125	90	398	7.13	181.0	0.150	3.8	47.5	SPR	CG	Z
1.125	28.58	A14-51	.75	19.1	1.001	25.4	9.4	1.6	.46	12	4.3	19	.29	7.4	0.062	1.6	3.67	SST	C	N
1.125	28.58	1549	.81	20.6	.875	22.2	351	61	.22	5.5	76	340	.50	12.7	0.125	3.2	3.00	MW	C	Z
1.125	28.58	S-205	.88	22.2	1.023	26.0	2.7	.48	.59	15	1.6	7.2	.28	7.1	0.051	1.3	4.50	SST	C	N
1.125	28.58	S-1405	.88	22.2	.915	23.2	82	14	.38	9.7	31	139	.39	10.0	0.105	2.7	3.75	SST	CG	N
1.125	28.58	S-931	.97	24.6	1.023	26.0	1.7	.30	.66	17	1.1	5.0	.31	7.8	0.051	1.3	6.00	SST	CG	N
1.125	28.58	11963	.97	24.6	1.003	25.5	4.1	.72	.60	15	2.5	11	.37	9.3	0.061	1.5	6.00	SPR	CG	Z
1.125	28.58	10482	1.00	25.4	.965	24.5	26	4.5	.61	16	16	70	.32	8.1	0.080	2.0	4.00	SPR	CG	N
1.125	28.58	S-1383	1.06	27.0	.915	23.2	57	10	.55	14	31	139	.47	12.0	0.105	2.7	4.50	SST	CG	N
1.125	28.58	3947	1.19	30.2	.941	23.9	31	5.5	.73	18	23	101	.46	11.7	0.092	2.3	5.00	SPR	CG	Z
1.125	28.58	B17-147	1.22	31.0	1.005	25.5	7.7	1.4	.91	23	7.1	31	.24	6.1	0.060	1.5	4.00	SPR	CG	N
1.125	28.58	S-1236	1.25	31.8	.981	24.9	9.6	1.7	.89	23	8.5	38	.36	9.1	0.072	1.8	5.00	SST	CG	N
1.125	28.58	11742	1.25	31.8	.895	22.7	122	21	.35	8.9	43	190	.46	11.7	0.115	2.9	4.00	SPR	CG	Z
1.125	28.58	12271	1.38	34.9	.995	25.3	4.2	.74	.95	24	4.0	18	.42	10.7	0.065	1.7	6.50	SST	CG	N
1.125	28.58	S-147	1.41	35.7	1.031	26.2	.89	.16	1.0	26	.89	4.0	.40	10.1	0.047	1.2	7.50	SST	C	N
1.125	28.58	S-911	1.47	37.3	.981	24.9	7.3	1.3	1.0	26	7.6	34	.43	11.0	0.072	1.8	6.00	SST	CG	N
1.125	28.58	2945	1.50	38.1	1.017	25.8	5.0	.87	1.0	26	5.2	23	.27	6.9	0.054	1.4	4.00	SPR	C	Z
1.125	28.58	12001	1.50	38.1	.935	23.7	27	4.7	.93	24	25	111	.57	14.5	0.095	2.4	6.00	SPR	CG	Z
1.125	28.58	S-1249	1.50	38.1	.915	23.2	48	8.4	.66	17	31	139	.53	13.3	0.105	2.7	5.00	SST	CG	N
1.125	28.58	S-1561	1.50	38.1	.875	22.2	87	15	.57	15	50	222	.69	17.5	0.125	3.2	5.50	SST	CG	N
1.125	28.58	10624	1.56	39.7	.815	20.7	303	53	.32	8.1	97	432	.78	19.7	0.155	3.9	5.00	SPR	CG	Z
1.125	28.58	M-80	1.59	40.5	.859	21.8	115	20	.55	14	64	283	.80	20.3	0.133	3.4	6.00	SPR	CG	Z
1.125	28.58	S-3242	1.72	43.6	1.003	25.5	3.7	.64	1.4	34	5.0	22	.37	9.3	0.061	1.5	6.00	SST	CG	N
1.125	28.58	3302	1.75	44.5	.875	22.2	58	10	.75	19	44	195	1.00	25.4	0.125	3.2	8.00	HD	CG	Z
1.125	28.58	11433	1.88	47.6	.885	22.5	56	9.8	.87	22	48	216	.87	22.1	0.120	3.0	7.25	HD	CG	Z
1.125	28.58	11335	2.00	50.8	.829	21.1	148	26	.59	15	87	387	1.04	26.3	0.148	3.8	7.00	SPR	CG	Z
1.125	28.58	CC-96	2.00	50.8	.805	20.4	210	37	.51	13	107	474	1.12	28.4	0.160	4.1	7.00	SPR	CG	Z
1.125	28.58	S-3239	2.09	53.2	.945	24.0	19	3.3	1.1	27	20	88	.54	13.7	0.090	2.3	6.00	SST	CG	N
1.125	28.58	4340	2.13	54.0	.855	21.7	66	11	.84	21	55	246	1.28	32.6	0.135	3.4	9.50	SPR	CG	Z
1.125	28.58	S-973	2.28	57.9	.965	24.5	8.2	1.4	1.7	43	14	61	.60	15.2	0.080	2.0	7.50	SST	CG	N
1.125	28.58	2694	2.31	58.7	.933	23.7	20	3.6	1.3	32	26	115	.72	18.3	0.096	2.4	7.50	HD	CG	Z
1.125	28.58	S-1569	2.38	60.3	.875	22.2	69	12	.72	18	50	222	.81	20.6	0.125	3.2	6.50	SST	CG	N
1.125	28.58	10483	2.38	60.3	.831	21.1	159	28	.54	14	85	380	.96	24.3	0.147	3.7	6.50	SPR	CG	Z
1.125	28.58	S-194	2.44	61.9	1.045	26.5	.72	.13	2.2	55	1.6	6.9	.26	6.6	0.040	1.0	5.50	SST	C	N
1.125	28.58	1629	2.50	63.5	.965	24.5	8.6	1.5	1.8	47	16	70	.64	16.3	0.080	2.0	8.00	SPR	CG	Z
1.125	28.58	3965	2.50	63.5	.905	23.0	31	5.4	1.2	31	38	167	.94	23.7	0.110	2.8	8.50	SPR	CG	Z
1.125	28.58	S-466	2.50	63.5	.885	22.5	59	10	.75	19	44	197	.76	19.3	0.120	3.0	6.33	SST	CG	N
1.125	28.58	12017	2.53	64.3	.831	21.1	120	21	.71	18	85	380	1.18	29.9	0.147	3.7	8.00	SPR	CG	Z
1.125	28.58	B8-67	2.66	67.5	.875	22.2	64	11	.86	22	55	243	1.06	27.0	0.125	3.2	7.50	SPR	C	N
1.125	28.58	2567	2.69	68.2	.995	25.3	4.3	.75	2.1	53	9.0	40	.46	11.6	0.065	1.7	7.00	SPR	CG	Z
1.125	28.58	11143	2.69	68.2	.901	22.9	29	5.1	1.4	35	40	176	1.18	29.9	0.112	2.8	9.50	SPR	C	Z
1.125	28.58	11785	2.72	69.0	.919	23.3	28	4.8	1.2	29	32	142	.77	19.6	0.103	2.6	7.50	SPR	CG	N
1.125	28.58	10540	2.72	69.0	.895	22.7	31	5.3	1.4	36	43	190	1.15	29.2	0.115	2.9	10.0	SPR	CG	Z
1.125	28.58	B7-47	2.72	69.0	.845	21.5	82	14	.81	21	67	297	1.16	29.3	0.140	3.6	8.25	SST	CG	N
1.125	28.58	11203	2.75	69.9	.901	22.9	27	4.8	1.5	37	40	176	1.23	31.3	0.112	2.8	10.0	SPR	C	Z
1.125	28.58	12076	2.78	70.6	.811	20.6	175	31	.58	15	101	449	1.18	29.9	0.157	4.0	7.50	SPR	CG	Z
1.125	28.58	2736	2.84	72.2	.855	21.7	70	12	1.3	34	93	414	1.22	30.9	0.135	3.4	9.00	MW	CG	Z
1.125	28.58	825	2.88	73.0	.855	21.7	60	10	1.1	28	67	296	1.52	38.6	0.135	3.4	10.3	HD	C	Z
1.125	28.58	2824	2.94	74.6	.875	22.2	39	6.8	1.6	40	61	271	1.38	34.9	0.125	3.2	11.0	MW	CG	Z
1.125	28.58	S-1131	3.00	76.2	.965	24.5	5.6	.98	2.2	56	12	55	.80	20.3	0.080	2.0	10.0	SST	CG	N
1.125	28.58	10643	3.00	76.2	.943	24.0	14	2.5	1.6	39	22	99	.75	19.1	0.091	2.3	8.25	SPR	CG	Z
1.125	28.58	366	3.00	76.2	.915	23.2	22	3.8	1.5	39	34	150	1.00	25.3	0.105	2.7	9.50	HD	CG	Z
1.125	28.58	59	3.00	76.2	.741	18.8	275	48	.63	16	172	766	2.06	52.4	0.192	4.9	10.8	HD	CG	Z
1.125	28.58	3157	3.19	81.0	.781	19.8	156	27	.84	21	131	585	1.95	49.5	0.172	4.4	11.3	SPR	CG	Z
1.125	28.58	11935	3.25	82.6	.965	24.5	3.2	.56	1.8	46	5.8	26	1.44	36.6	0.080	2.0	18.0	SPR	CG	Z
1.125	28.58	S-169	3.38	85.7	1.031	26.2	.41	.07	2.7	68	1.1	4.8	.71	17.9	0.047	1.2	14.0	SST	C	N
1.125	28.58	3180	3.44	87.3	.749	19.0	230	40	.71	18	162	721	2.16	54.9	0.188	4.8	11.5	SPR	CG	Z
1.125	28.58	4399	3.50	88.9	.915	23.2	14	2.4	2.0	52	28	124	1.47	37.3	0.105	2.7	14.0	SPR	CG	N
1.125	28.58	10297	3.50	88.9	.875	22.2	39	6.8	1.4	36	55	243	1.38	34.9	0.125	3.2	11.0	SPR	CG	Z
1.125	28.58	2519	3.63	92.1	.899	22.8	19	3.3	2.0	52	39	171	1.58	40.2	0.113	2.9	14.0	HD	CG	Z
1.125	28.58	4274	3.75	95.3	.889	22.6	25	4.3	1.9	47	46	205	1.53	39.0	0.118	3.0	13.0	SPR	CG	Z
1.125	28.58	7054	3.75	95.3	.813	20.7	74	13	1.2	30	88	391	2.18	55.5	0.156	4.0	13.0	SST	C	N
1.125	28.58	3083	3.94	100.0	.805	20.4	95	17	1.1	28	107	474	2.08	52.8	0.160	4.1	13.0	SPR	CG	GI
1.125	28.58	S-																		

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.125	28.58	1625	7.50	190.5	.801	20.3	58	10	1.9	48	111	492	3.40	86.4	0.162	4.1	21.0	SPR	CG	Z
1.125	28.58	3270	8.00	203.2	.741	18.8	109	19	1.6	40	172	766	4.61	117.0	0.192	4.9	24.0	SPR	CG	Z
1.125	28.58	374	9.25	235.0	.915	23.2	8.2	1.4	4.1	104	34	150	2.42	61.3	0.105	2.7	22.0	HD	C	Z
1.125	28.58	833	10.0	254.0	.915	23.2	6.1	1.1	5.5	141	34	150	3.05	77.3	0.105	2.7	29.0	HD	CG	Z
1.125	28.58	826	10.0	254.0	.855	21.7	15	2.7	4.3	110	67	296	4.59	116.6	0.135	3.4	34.0	HD	CG	Z
1.125	28.58	820	10.0	254.0	.829	21.1	22	3.8	4.0	101	87	387	5.29	134.4	0.148	3.8	35.8	HD	CG	Z
1.125	28.58	867	11.0	279.4	.885	22.5	9.7	1.7	5.0	127	48	216	4.00	101.6	0.120	3.0	32.3	HD	C	Z
1.125	28.58	838	12.0	304.8	.741	18.8	61	11	2.8	72	172	766	8.02	203.6	0.192	4.9	41.8	HD	CG	Z
1.140	28.96	S-1466	.59	15.1	.858	21.8	496	87	.14	3.4	67	299	.42	10.7	0.141	3.6	3.00	SST	CG	N
1.140	28.96	S-305	1.00	25.4	.956	24.3	31	5.4	.49	13	15	68	.51	12.9	0.092	2.3	4.50	SST	C	N
1.140	28.96	11907	1.09	27.8	1.012	25.7	2.9	.50	.58	15	1.7	7.4	.51	13.0	0.064	1.6	8.00	SST	CG	N
1.140	28.96	S-1047	1.25	31.8	.900	22.9	81	14	.54	14	44	194	.60	15.2	0.120	3.0	5.00	SST	CG	N
1.140	28.96	10889	1.31	33.3	1.046	26.6	.79	.14	.94	24	.74	3.3	.38	9.6	0.047	1.2	8.00	SST	CG	N
1.140	28.96	12321	1.50	38.1	1.030	26.2	2.2	.38	1.1	29	2.4	11	.37	9.4	0.055	1.4	6.75	SPR	CG	Z
1.140	28.96	12644	1.83	46.4	1.032	26.2	2.4	.42	1.5	38	3.5	16	.35	8.9	0.054	1.4	5.50	SST	C	N
1.140	28.96	S-3008	1.88	47.6	.880	22.4	99	17	.54	14	53	236	.72	18.2	0.130	3.3	5.50	SST	CG	N
1.140	28.96	S-1203	1.94	49.2	.880	22.4	87	15	.61	16	53	236	.78	19.8	0.130	3.3	6.00	SST	CG	N
1.140	28.96	S-254	2.00	50.8	.756	19.2	352	62	.42	11	147	653	1.47	37.4	0.192	4.9	7.67	SST	CG	N
1.140	28.96	3999	2.25	57.2	.956	24.3	19	3.3	1.2	30	23	100	.62	15.8	0.092	2.3	6.75	SPR	CG	Z
1.140	28.96	11343	2.41	61.1	.844	21.4	157	27	.55	14	86	383	.96	24.4	0.148	3.8	6.50	SPR	CG	Z
1.140	28.96	3173	2.56	65.1	.956	24.3	13	2.2	1.7	44	22	99	.83	21.0	0.092	2.3	9.00	SPR	CG	Z
1.140	28.96	3156	2.63	66.7	1.028	26.1	2.8	.49	2.0	52	5.7	25	.34	8.5	0.056	1.4	6.00	SPR	CG	Z
1.140	28.96	11130	2.84	72.2	.756	19.2	270	47	.63	16	170	758	2.02	51.2	0.192	4.9	10.5	SPR	CG	Z
1.140	28.96	12755	2.84	72.2	.766	19.5	232	41	.77	19	178	790	2.01	51.1	0.187	4.7	10.8	OT	CG	N
1.140	28.96	S-1168	3.00	76.2	.960	24.4	8.9	1.6	2.1	53	19	83	.90	22.9	0.090	2.3	10.0	SST	CG	N
1.140	28.96	11799	3.13	79.4	.830	21.1	124	22	.77	20	96	427	1.40	35.4	0.155	3.9	9.00	SPR	CG	Z
1.140	28.96	10365	3.19	81.0	.844	21.4	76	13	1.1	29	86	383	1.67	42.3	0.148	3.8	11.3	SPR	CG	Z
1.140	28.96	4312	3.88	98.4	.870	22.1	51	8.9	1.3	33	66	292	1.52	38.6	0.135	3.4	11.3	SPR	CG	Z
1.140	28.96	3158	4.00	101.6	.890	22.6	30	5.2	1.8	46	54	240	1.78	45.2	0.125	3.2	14.0	SPR	CG	Z
1.140	28.96	S-1458	4.88	123.8	.970	24.6	5.1	.88	3.5	88	17	78	1.11	28.1	0.085	2.2	13.0	SST	CG	N
1.140	28.96	10571	4.88	123.8	.890	22.6	23	4.1	2.3	59	54	240	2.06	52.4	0.125	3.2	16.5	SPR	CG	Z
1.140	28.96	12179	5.16	131.0	.814	20.7	75	13	1.5	38	111	494	2.69	68.3	0.163	4.1	16.5	SPR	CG	Z
1.140	28.96	10458	5.25	133.4	.968	24.6	6.7	1.2	2.9	73	19	86	1.03	26.2	0.086	2.2	12.0	SPR	CG	Z
1.140	28.96	10376	5.31	134.9	.966	24.5	7.1	1.2	2.8	72	20	89	1.04	26.5	0.087	2.2	12.0	HD	CG	Z
1.140	28.96	3024	5.63	142.9	.786	20.0	88	15	1.6	41	141	628	3.54	89.9	0.177	4.5	20.0	SPR	CG	Z
1.156	29.36	S-262	.50	12.7	1.062	27.0	2.2	.39	.27	6.7	.59	2.6	.24	6.0	0.047	1.2	4.00	SST	C	N
1.156	29.36	3306	.69	17.4	.996	25.3	32	5.5	.33	8.3	10	46	.36	9.1	0.080	2.0	3.50	SPR	C	Z
1.156	29.36	10831	.81	20.6	1.066	27.1	1.9	.33	.59	15	1.1	5.0	.23	5.7	0.045	1.1	4.00	SST	C	N
1.156	29.36	B8-47	.88	22.2	1.056	26.8	2.4	.41	.65	17	1.5	6.8	.23	5.7	0.050	1.3	4.50	SST	CG	N
1.156	29.36	Q-32	.88	22.2	1.044	26.5	9.4	1.6	.56	14	5.3	23	.17	4.3	0.056	1.4	3.00	SST	CG	N
1.156	29.36	S-1018	.94	23.8	.886	22.5	223	39	.26	6.7	58	260	.51	12.9	0.135	3.4	3.75	SST	CG	N
1.156	29.36	S-1070	1.00	25.4	.832	21.1	584	102	.16	4.2	96	426	.57	14.4	0.162	4.1	3.50	SST	CG	N
1.156	29.36	12237	1.25	31.8	1.046	26.6	2.0	.35	.87	22	1.7	7.6	.39	9.8	0.055	1.4	7.00	SPR	CG	Z
1.156	29.36	3468	1.25	31.8	.980	24.9	24	4.1	.81	21	19	85	.44	11.2	0.088	2.2	5.00	SPR	CG	Z
1.156	29.36	3027	1.25	31.8	.976	24.8	21	3.6	.73	19	15	68	.52	13.1	0.090	2.3	5.75	SPR	CG	Z
1.156	29.36	PP-40	1.28	32.5	.896	22.8	109	19	.53	14	58	258	.72	18.2	0.130	3.3	5.50	SPR	CG	Z
1.156	29.36	4120	1.38	34.9	.986	25.0	20	3.6	.87	22	18	78	.51	13.0	0.085	2.2	5.00	SPR	CG	Z
1.156	29.36	PP-38	1.38	34.9	.896	22.8	52	9.1	.27	6.9	14	62	1.11	28.1	0.130	3.3	8.50	SST	CG	N
1.156	29.36	S-1183	1.44	36.5	1.052	26.7	.80	.14	.84	21	.67	3.0	.60	15.2	0.052	1.3	10.5	SST	C	N
1.156	29.36	10168	1.50	38.1	1.048	26.6	1.9	.34	1.1	29	2.2	9.7	.36	9.3	0.054	1.4	6.75	SPR	CG	Z
1.156	29.36	S-468	1.69	42.8	.946	24.0	26	4.6	.95	24	25	111	.74	18.7	0.105	2.7	7.00	SST	CG	N
1.156	29.36	12208	1.78	45.2	.900	22.9	71	12	.76	19	54	239	1.02	26.0	0.128	3.3	7.00	MW	C	Z
1.156	29.36	11528	1.88	47.6	1.084	27.5	.57	.10	1.7	42	.95	4.2	.22	5.5	0.036	0.9	5.00	SPR	C	Z
1.156	29.36	S-79	1.94	49.2	1.050	26.7	1.5	.27	1.6	40	2.4	11	.36	9.1	0.053	1.3	6.75	SST	CG	N
1.156	29.36	3013	2.00	50.8	1.028	26.1	3.1	.54	1.5	38	4.6	20	.51	13.0	0.064	1.6	8.00	SPR	CG	Z
1.156	29.36	3255	2.13	54.0	.870	22.1	105	18	.73	19	77	342	1.07	27.2	0.143	3.6	7.50	SPR	CG	Z
1.156	29.36	2969	2.50	63.5	1.012	25.7	5.5	.97	2.0	50	11	48	.54	13.7	0.072	1.8	7.50	SPR	CG	Z
1.156	29.36	3368	2.63	66.7	.946	24.0	21	3.6	1.6	40	33	147	.97	24.7	0.105	2.7	9.25	SPR	CG	GI
1.156	29.36	Y-63	2.75	69.9	1.028	26.1	2.8	.49	2.2	56	6.1	27	.56	14.2	0.064	1.6	7.75	SST	C	N
1.156	29.36	3487	2.75	69.9	1.026	26.1	4.0	.69	2.2	56	8.7	39	.52	13.2	0.065	1.7	7.00	HD	C	Z
1.156	29.36	S-469	2.88	73.0	1.048	26.6	1.3	.23	2.4	61	3.2	14	.49	12.3	0.054	1.4	8.00	SST	C	N
1.156	29.36	S-153	3.00	76.2	1.048	26.6	1.3	.22	2.5	64	3.2	14	.50	12.7	0.054	1.4	8.25	SST	C	N
1.156	29.36	S-256	3.00	76.2	.974	24.7	9.0	1.6	2.1	53	19	84	.90	22.8	0.091	2.3	10.0	SST	CG	N
1.156	29.36	11624	3.25	82.6	.916	23.3	23	4.1	1.5	38	35	157	1.74	44.2	0.120	3.0	13.5	SPR	C	Z
1.156	29.36	3269	3.75	95.3	.932	23.7	17	2.9	2.2	55	36	161	1.57	39.8	0.112	2.8	14.0	SPR	CG	Z
1.156	29.36	534	3.84	97.6	.860	21.8	56	9.8	1.5	38	85	378	2.07	52.6	0.148	3.8	14.0	SPR	CG	Z
1.156	29.36	S-3210	3.88	98.4	.892	22.7	40	7.0	1.4	35	55	243	1.45	36.9	0.132	3.4	11.0	SST	CG	N
1.156	29.36	10177	4.13	104.8	.886	22.5	39	6.8	1.7	42	65	289	1.82	46.3	0.135	3.4	13.5	SPR	CG	Z




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.172	29.77	4147	1.50	38.1	.818	20.8	410	72	.34	8.5	138	612	.97	24.7	0.177	4.5	5.50	SPR	CG	Z
1.172	29.77	KK-60	1.75	44.5	1.032	26.2	6.1	1.1	1.3	33	8.0	35	.44	11.1	0.070	1.8	6.25	SPR	CG	Z
1.172	29.77	LL-35	1.78	45.2	1.032	26.2	2.1	.38	.80	20	1.7	7.7	.98	24.9	0.070	1.8	14.0	SPR	CG	Z
1.172	29.77	11389	2.00	50.8	.902	22.9	76	13	.76	19	58	257	.95	24.0	0.135	3.4	7.00	SST	CG	N
1.172	29.77	10680	2.00	50.8	.848	21.5	148	26	.62	16	92	411	1.38	35.0	0.162	4.1	8.50	SPR	CG	Z
1.172	29.77	11122	2.16	54.8	.860	21.8	125	22	.76	19	95	424	1.33	33.7	0.156	4.0	8.50	SPR	CG	Z
1.172	29.77	S-1234	2.19	55.6	1.012	25.7	9.3	1.6	1.5	39	14	63	.50	12.7	0.080	2.0	6.25	SST	CG	N
1.172	29.77	12014	2.34	59.5	1.058	26.9	2.1	.37	1.9	49	4.0	18	.41	10.5	0.057	1.4	7.25	SPR	CG	Z
1.172	29.77	11213	2.38	60.3	.876	22.3	92	16	.90	23	82	365	1.48	37.6	0.148	3.8	9.00	SPR	C	Z
1.172	29.77	1539	2.41	61.1	.932	23.7	43	7.5	1.1	28	47	208	.96	24.4	0.120	3.0	8.00	SPR	CG	Z
1.172	29.77	1797	2.44	61.9	.902	22.9	66	12	.97	25	64	285	1.15	29.2	0.135	3.4	8.50	HD	CG	Z
1.172	29.77	11862	2.44	74.6	1.016	25.8	9.1	1.6	1.6	39	14	62	.51	12.9	0.078	2.0	6.50	SPR	CG	N
1.172	29.77	B17-188	3.50	88.9	1.082	27.5	.41	.07	3.0	76	1.2	5.4	.50	12.6	0.045	1.1	11.0	SST	CG	N
1.172	29.77	S-1244	3.63	92.1	1.012	25.7	7.9	1.4	1.8	46	14	63	.56	14.2	0.080	2.0	7.00	SST	CG	N
1.172	29.77	3016	4.17	106.0	.888	22.6	49	8.5	1.5	39	74	330	1.85	46.9	0.142	3.6	13.0	SPR	CG	GI
1.172	29.77	3670	4.28	108.7	1.074	27.3	.73	.13	3.7	95	2.7	12	.54	13.7	0.049	1.2	10.0	SPR	C	Z
1.172	29.77	11220	6.00	152.4	.788	20.0	143	25	1.2	30	166	740	3.17	80.5	0.192	4.9	16.5	SPR	CG	Z
1.172	29.77	S-1616	7.00	177.8	.988	25.1	3.3	.58	4.7	119	15	69	2.30	58.4	0.092	2.3	24.0	SST	C	N
1.172	29.77	10675	10.8	273.1	.860	21.8	27	4.7	3.5	90	95	424	4.99	126.8	0.156	4.0	32.0	SPR	CG	Z
1.172	29.77	2742	11.3	285.8	.908	23.1	11	2.0	5.2	133	60	267	4.88	124.1	0.132	3.4	36.0	SPR	C	Z
1.188	30.18	10160	.44	11.1	1.028	26.1	43	7.6	.20	5.0	8.6	38	.24	6.1	0.080	2.0	3.00	SPR	CG	Z
1.188	30.18	10661	.66	16.7	1.000	25.4	86	15	.27	6.9	23	103	.28	7.2	0.094	2.4	3.00	SPR	CG	Z
1.188	30.18	S-3078	.75	19.1	.928	23.6	241	42	.21	5.4	51	227	.42	10.7	0.130	3.3	3.25	SST	CG	N
1.188	30.18	S-3178	.75	19.1	.908	23.1	417	73	.15	3.9	63	282	.42	10.7	0.140	3.6	3.00	SST	CG	N
1.188	30.18	2844	.81	20.6	.808	20.5	1256	220	.13	3.2	159	709	.67	16.9	0.190	4.8	3.50	SPR	CG	Z
1.188	30.18	11918	1.00	25.4	1.066	27.1	4.1	.72	.70	18	2.9	13	.31	7.7	0.061	1.5	5.00	SST	CG	N
1.188	30.18	1902	1.13	28.6	1.038	26.4	6.6	1.2	.60	15	4.0	18	.53	13.3	0.075	1.9	7.00	SPR	CG	Z
1.188	30.18	11632	1.22	31.0	1.006	25.6	15	2.6	.58	15	8.7	39	.64	16.2	0.091	2.3	7.00	SPR	CG	Z
1.188	30.18	12540	1.38	34.9	1.028	26.1	17	3.0	.86	22	15	66	.44	11.2	0.080	2.0	4.50	SPR	C	N
1.188	30.18	533	1.38	34.9	.978	24.8	50	8.8	.64	16	32	143	.60	15.3	0.105	2.7	4.75	HD	C	Z
1.188	30.18	11259	1.41	35.7	1.028	26.1	19	3.4	.78	20	15	66	.42	10.7	0.080	2.0	4.25	SPR	C	Z
1.188	30.18	12334	1.50	38.1	1.032	26.2	9.7	1.7	1.0	26	10	45	.47	11.9	0.078	2.0	6.00	SPR	CG	Z
1.188	30.18	11642	1.50	38.1	1.028	26.1	14	2.5	1.0	26	15	66	.40	10.2	0.080	2.0	5.00	SPR	CG	Z
1.188	30.18	3186	1.50	38.1	.774	19.7	932	163	.22	5.6	204	907	1.04	26.3	0.207	5.3	5.00	SPR	CG	Z
1.188	30.18	1849	1.53	38.9	1.006	25.6	30	5.2	.98	25	29	131	.41	10.4	0.091	2.3	4.50	MW	CG	Z
1.188	30.18	11485	1.59	40.5	1.020	25.9	18	3.1	.97	25	17	77	.50	12.8	0.084	2.1	5.00	SPR	C	Z
1.188	30.18	S-3058	1.88	47.6	1.068	27.1	3.2	.56	1.5	38	4.8	21	.39	9.9	0.060	1.5	5.50	SST	C	N
1.188	30.18	2992	1.88	47.6	.938	23.8	65	11	.80	20	52	231	.81	20.6	0.125	3.2	6.50	SPR	CG	Z
1.188	30.18	1889	2.00	50.8	1.044	26.5	6.2	1.1	1.5	37	9.0	40	.54	13.7	0.072	1.8	6.50	HD	C	Z
1.188	30.18	12437	2.00	50.8	1.040	26.4	7.3	1.3	1.5	37	11	48	.54	13.6	0.074	1.9	6.25	SPR	C	Z
1.188	30.18	S-3133	2.00	50.8	.978	24.8	28	4.9	1.1	27	30	132	.76	19.3	0.105	2.7	6.25	SST	C	N
1.188	30.18	S-3186	2.00	50.8	.918	23.3	71	12	.80	20	57	253	.95	24.0	0.135	3.4	7.00	SST	CG	N
1.188	30.18	S-3012	2.00	50.8	.774	19.7	442	77	.40	10	176	781	1.55	39.4	0.207	5.3	7.50	SST	CG	N
1.188	30.18	2792	2.19	55.6	.918	23.3	58	10	.97	25	57	253	1.22	30.9	0.135	3.4	9.00	SPR	CG	Z
1.188	30.18	12036	2.28	57.9	1.068	27.1	3.1	.53	1.9	48	5.8	26	.38	9.5	0.060	1.5	6.25	SPR	CG	Z
1.188	30.18	11160	2.28	57.9	.876	22.3	163	29	.58	15	94	419	1.05	26.7	0.156	4.0	6.75	SPR	CG	Z
1.188	30.18	1924	2.38	60.3	1.004	25.5	16	2.7	1.4	35	22	97	.74	18.7	0.092	2.3	7.00	SPR	C	GI
1.188	30.18	857	2.38	60.3	.918	23.3	68	12	.93	24	63	281	1.22	30.9	0.135	3.4	8.00	HD	C	Z
1.188	30.18	11251	2.41	61.1	.864	21.9	203	36	.46	12	93	415	.97	24.7	0.162	4.1	6.00	SST	CG	N
1.188	30.18	821	2.50	63.5	.892	22.7	85	15	.98	25	83	368	1.37	34.8	0.148	3.8	9.25	HD	CG	Z
1.188	30.18	3382	2.63	66.7	.908	23.1	69	12	1.0	26	70	313	1.26	32.0	0.140	3.6	9.00	SPR	CG	Z
1.188	30.18	869	2.75	69.9	.948	24.1	35	6.1	1.3	33	46	205	1.20	30.5	0.120	3.0	9.00	HD	C	Z
1.188	30.18	3469	2.75	69.9	.918	23.3	58	10	1.1	28	63	281	1.22	30.9	0.135	3.4	9.00	HD	CG	Z
1.188	30.18	B8-64	3.00	76.2	.862	21.9	119	21	.80	20	95	423	1.47	37.3	0.163	4.1	9.00	SST	CG	N
1.188	30.18	11960	3.06	77.8	.908	23.1	64	11	1.1	28	70	313	1.33	33.8	0.140	3.6	9.50	SPR	CG	Z
1.188	30.18	11414	3.13	79.4	.978	24.8	18	3.2	1.8	44	32	143	1.00	25.3	0.105	2.7	9.50	HD	CG	Z
1.188	30.18	11175	3.25	82.6	.892	22.7	88	15	.95	24	83	368	1.33	33.8	0.148	3.8	9.00	SPR	CG	Z
1.188	30.18	840	3.25	82.6	.804	20.4	203	36	.81	21	164	731	2.26	57.3	0.192	4.9	11.8	HD	CG	Z
1.188	30.18	43	3.25	82.6	.734	18.6	434	76	.59	15	255	1136	2.59	65.7	0.227	5.8	11.5	HD	CG	Z
1.188	30.18	S-165	3.50	88.9	1.094	27.8	.46	.08	3.0	76	1.4	6.1	.52	13.1	0.047	1.2	11.0	SST	CG	N
1.188	30.18	S-949	3.94	100.0	.812	20.6	169	30	.79	20	133	592	2.12	53.7	0.188	4.8	11.3	SST	CG	N
1.188	30.18	3673	4.63	117.5	1.026	26.1	3.8	.67	3.5	89	13	59	1.13	28.8	0.081	2.1	14.0	SPR	CG	Z
1.188	30.18	S-362	4.63	117.5	.978	24.8	8.0	1.4	2.8	72	23	101	1.79	45.3	0.105	2.7	17.0	SST	CG	N
1.188	30.18	815	4.63	117.5	.864	21.9	64	11	1.6	42	105	468	2.63	66.9	0.162	4.1	16.3	HD	CG	Z
1.188	30.18	11690	4.75	120.7	.858	21.8	77	13	1.4	37	111	493	2.48	62.9	0.165	4.2	15.0	SPR	CG	Z
1.188	30.18	2704	4.81	122.2	1.028	26.1	3.5	.61	3.6	91	12	55	1.24	31.5	0.080	2.0	14.5	HD	C	Z
1.188	30.18	3260	5.25	133.4	.834	21.2	114	20	1.2	30	136	605	2.48	62.9	0.177	4.5	14.0	SPR	CG	Z
1.188	30.18	3292	5.50	139.7	.834	21.2	114	20	1.2	30	136	605	2.48	62.9	0.177					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.203	30.56	2549	1.34	34.1	1.017	25.8	39	6.9	.56	14	22	99	.37	9.4	0.093	2.4	4.00	SPR	CG	Z
1.203	30.56	12120	1.41	35.7	1.079	27.4	6.4	1.1	1.1	29	7.3	32	.26	6.7	0.062	1.6	4.25	SPR	CG	Z
1.203	30.56	12281	1.47	37.3	1.075	27.3	7.3	1.3	1.1	28	8.0	36	.27	6.9	0.064	1.6	4.25	SPR	CG	Z
1.203	30.56	3370	1.75	44.5	.879	22.3	195	34	.53	14	104	462	1.05	26.7	0.162	4.1	6.50	SPR	CG	Z
1.203	30.56	11695	1.94	49.2	1.019	25.9	9.7	1.7	1.0	26	10	45	.90	22.8	0.092	2.3	9.75	SPR	CG	Z
1.203	30.56	10302	1.94	49.2	.849	21.6	290	51	.46	12	134	598	1.15	29.2	0.177	4.5	6.50	SPR	CG	Z
1.203	30.56	S-1668	1.97	50.0	.849	21.6	290	51	.41	10	119	531	1.06	27.0	0.177	4.5	6.00	SST	CG	N
1.203	30.56	S-3005	2.00	50.8	.849	21.6	252	44	.47	12	119	531	1.15	29.2	0.177	4.5	6.50	SST	CG	N
1.203	30.56	11500	2.00	50.8	.791	20.1	746	131	.27	6.8	199	885	1.34	34.0	0.206	5.2	5.50	SPR	CG	Z
1.203	30.56	11572	2.03	51.6	.907	23.0	168	29	.49	12	82	364	.96	24.4	0.148	3.8	5.50	SPR	CG	N
1.203	30.56	12087	2.06	52.4	.933	23.7	78	14	.80	20	63	278	.95	24.0	0.135	3.4	7.00	SPR	CG	Z
1.203	30.56	B18-166	2.28	57.9	1.003	25.5	19	3.4	1.4	36	27	122	.75	19.1	0.100	2.5	7.50	SPR	CG	N
1.203	30.56	S-241	2.34	59.5	.963	24.5	45	7.9	.92	23	42	185	.78	19.8	0.120	3.0	6.50	SST	CG	N
1.203	30.56	S-337	2.38	60.3	.993	25.2	23	4.0	1.3	33	29	131	.74	18.7	0.105	2.7	7.00	SST	CG	N
1.203	30.56	10291	2.38	60.3	.907	23.0	98	17	.84	21	82	364	1.18	30.1	0.148	3.8	8.00	SPR	CG	Z
1.203	30.56	S-281	2.38	60.3	.907	23.0	93	16	.79	20	74	328	1.11	28.2	0.148	3.8	7.50	SST	CG	N
1.203	30.56	3626	2.75	69.9	1.113	28.3	.54	.09	2.3	58	1.2	5.5	.45	11.4	0.045	1.1	9.00	HD	C	Z
1.203	30.56	10461	2.75	69.9	.999	25.4	20	3.6	1.4	36	29	130	.79	20.1	0.102	2.6	7.75	SPR	CG	Z
1.203	30.56	12301	3.00	76.2	1.113	28.3	.54	.09	2.6	66	1.4	6.3	.41	10.3	0.045	1.1	9.00	SPR	CG	Z
1.203	30.56	4339	3.25	82.6	.753	19.1	485	85	.51	13	246	1096	2.36	60.0	0.225	5.7	10.5	SPR	CG	Z
1.203	30.56	12090	3.38	85.7	1.079	27.4	1.6	.28	2.8	70	4.4	19	.62	15.7	0.062	1.6	10.0	SST	CG	N
1.203	30.56	12002	3.38	85.7	1.013	25.7	14	2.5	1.6	42	24	105	.76	19.3	0.095	2.4	8.00	SPR	CG	Z
1.203	30.56	B18-201	3.47	88.1	1.061	26.9	2.5	.43	2.7	68	6.7	30	.78	19.8	0.071	1.8	11.0	SST	CG	N
1.203	30.56	S-306	3.50	88.9	1.033	26.2	6.7	1.2	2.5	63	17	74	.85	21.6	0.085	2.2	9.00	SST	C	N
1.203	30.56	2955	3.56	90.5	1.063	27.0	2.5	.44	2.7	68	6.7	30	.88	22.2	0.070	1.8	11.5	SPR	C	Z
1.203	30.56	2548	4.38	111.1	.983	25.0	14	2.4	2.6	65	35	157	1.51	38.4	0.110	2.8	13.8	SPR	CG	Z
1.203	30.56	1745	5.13	130.2	1.079	27.4	.99	.17	4.0	103	4.0	18	1.09	27.6	0.062	1.6	16.5	SPR	C	Z
1.203	30.56	10974	5.88	149.2	.963	24.5	15	2.6	3.1	79	46	202	2.16	54.9	0.120	3.0	18.0	HD	CG	Z
1.203	30.56	11826	7.25	184.2	.991	25.2	8.7	1.5	3.5	88	30	135	1.80	45.8	0.106	2.7	16.0	SST	C	N
1.203	30.56	1551	7.75	196.9	.909	23.1	25	4.4	3.2	81	80	357	3.63	92.1	0.147	3.7	24.7	SPR	CG	Z
1.203	30.56	S-346	16.0	406.4	1.023	26.0	1.6	.29	11	290	19	83	3.56	90.3	0.090	2.3	38.5	SST	C	N
1.219	30.96	11552	.94	23.8	.949	24.1	.02	.003	.88	22	.02	.07	.06	1.5	0.135	3.4	3.50	MW	CG	Z
1.219	30.96	3444	.94	23.8	.943	24.0	275	48	.24	6.1	66	293	.48	12.3	0.138	3.5	3.50	SPR	CG	Z
1.219	30.96	B10-8	1.00	25.4	.969	24.6	119	21	.39	9.9	46	206	.50	12.7	0.125	3.2	4.00	SST	CG	N
1.219	30.96	S-974	1.16	29.4	.979	24.9	104	18	.39	10	41	182	.47	11.8	0.120	3.0	4.00	SST	CG	N
1.219	30.96	12701	1.31	33.3	1.057	26.8	17	2.9	.87	22	15	65	.45	11.3	0.081	2.1	4.50	SPR	C	N
1.219	30.96	10875	1.31	33.3	1.009	25.6	28	4.9	.68	17	19	85	.63	16.0	0.105	2.7	6.00	SST	CG	N
1.219	30.96	10704	1.38	34.9	1.075	27.3	9.1	1.6	1.1	27	9.5	42	.32	8.2	0.072	1.8	4.50	SST	CG	N
1.219	30.96	12631	1.38	34.9	1.059	26.9	16	2.8	.91	23	15	65	.44	11.2	0.080	2.0	4.50	HD	C	N
1.219	30.96	11353	1.38	34.9	.895	22.7	297	52	.31	7.8	91	406	.73	18.5	0.162	4.1	4.50	SST	CG	N
1.219	30.96	3451	1.44	36.5	1.035	26.3	36	6.3	.59	15	21	94	.37	9.3	0.092	2.3	4.00	HD	CG	Z
1.219	30.96	2885	1.53	38.9	1.017	25.8	37	6.5	.75	19	28	124	.49	12.5	0.101	2.6	5.00	SPR	CG	Z
1.219	30.96	11164	1.63	41.3	.907	23.0	236	41	.39	9.9	92	409	.78	19.8	0.156	4.0	5.00	SPR	CG	Z
1.219	30.96	KK-71	1.75	44.5	1.039	26.4	29	5.1	.63	16	18	82	.36	9.1	0.090	2.3	4.00	SST	CG	N
1.219	30.96	10304	1.75	44.5	1.009	25.6	32	5.5	.99	25	31	139	.74	18.7	0.105	2.7	6.00	SPR	C	Z
1.219	30.96	12096	1.75	44.5	.859	21.8	384	67	.35	8.8	133	593	.99	25.1	0.180	4.6	5.50	SPR	CG	Z
1.219	30.96	11120	1.97	50.0	.879	22.3	198	35	.60	15	118	526	1.23	31.3	0.170	4.3	7.25	SPR	CG	Z
1.219	30.96	11579	2.22	56.4	.951	24.2	60	11	1.0	25	60	269	1.21	30.6	0.134	3.4	8.00	SPR	CG	N
1.219	30.96	4391	2.33	59.1	.923	23.4	94	16	.86	22	81	360	1.18	30.1	0.148	3.8	8.00	SPR	CG	Z
1.219	30.96	S-955	2.34	59.5	1.035	26.3	14	2.4	1.4	36	20	87	.60	15.2	0.092	2.3	6.50	SST	CG	N
1.219	30.96	S-1336	2.38	60.3	1.037	26.3	14	2.4	1.4	36	19	85	.68	17.3	0.091	2.3	6.50	SST	C	N
1.219	30.96	11320	2.38	60.3	.907	23.0	177	31	.52	13	92	409	.94	23.8	0.156	4.0	6.00	SPR	CG	Z
1.219	30.96	B18-194	2.44	61.9	1.129	28.7	.52	.09	2.0	52	1.1	4.7	.41	10.3	0.045	1.1	9.00	SPR	CG	N
1.219	30.96	11932	2.50	63.5	.829	21.1	387	68	.43	11	168	747	1.37	34.7	0.195	5.0	7.00	SPR	CG	N
1.219	30.96	3404	2.75	69.9	1.009	25.6	23	4.0	1.4	35	31	139	.86	21.7	0.105	2.7	8.00	SPR	CG	Z
1.219	30.96	S-3053	2.88	73.0	1.075	27.3	5.6	.97	1.8	46	10	44	.50	12.8	0.072	1.8	6.00	SST	C	N
1.219	30.96	12328	3.00	76.2	1.119	28.4	1.0	.18	2.6	65	2.6	12	.43	10.8	0.050	1.3	7.50	SPR	C	Z
1.219	30.96	S-1375	3.00	76.2	1.117	28.4	.59	.10	2.4	61	1.4	6.3	.61	15.5	0.051	1.3	11.0	SST	C	N
1.219	30.96	B18-182	3.22	81.8	.725	18.4	574	101	.47	12	267	1188	2.72	69.0	0.247	6.3	11.0	SST	CG	N
1.219	30.96	4302	3.25	82.6	1.009	25.6	16	2.8	2.0	50	31	139	1.05	26.7	0.105	2.7	10.0	SPR	CG	Z
1.219	30.96	11858	3.84	97.6	1.043	26.5	7.6	1.3	2.4	61	18	81	.79	20.1	0.088	2.2	9.00	SST	CG	N
1.219	30.96	7056	4.00	101.6	.865	22.0	99	17	1.2	30	118	525	2.48	62.9	0.177	4.5	13.0	SST	C	N
1.219	30.96	10989	4.06	103.2	.805	20.4	255	45	.78	20	199	887	2.48	63.1	0.207	5.3	12.0	HD	CG	Z
1.219	30.96	283	4.50	114.3	.895	22.7	70	12	1.5	37	103	457	2.27	57.6	0.162	4.1	14.0	HD	CG	Z
1.219	30.96	11731	7.50	190.5	.895	22.7	41	7.2	2.5	64	103	457	3.65	92.6	0.162	4.1	22.5	SPR	CG	Z
1.219	30.96	2841	7.75	196.9	.923	23.4	24	4.2	3.4	86	81	360	3.77	95.9	0.148	3.8	25.5	HD	CG	Z
1.219	30.96	4174	12.0	304.8	1.039	26.4	3.0	.52	6.7	169	20	88	2.25	57.2	0.090	2.3	24.0	SPR	C	Z
1.225	31.12	72627	.88	22.4	1.055	26.8	37	6.4	.59	15	22	97	.29	7.3	0.0					




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.225	31.12	72708S	.88	22.4	.929	23.6	276	48	.26	6.7	73	322	.56	14.1	0.148	3.8	3.75	SST	CG	N
1.225	31.12	72628	1.00	25.4	1.055	26.8	31	5.4	.69	18	22	96	.31	7.8	0.085	2.2	3.63	MW	CG	N
1.225	31.12	72628S	1.00	25.4	1.055	26.8	26	4.6	.62	16	16	72	.31	7.8	0.085	2.2	3.63	SST	CG	N
1.225	31.12	72638	1.00	25.4	1.033	26.2	50	8.8	.65	17	33	146	.35	8.8	0.096	2.4	3.63	MW	CG	N
1.225	31.12	72638S	1.00	25.4	1.033	26.2	43	7.5	.52	13	22	99	.35	8.8	0.096	2.4	3.63	SST	CG	N
1.225	31.12	72652	1.00	25.4	1.015	25.8	70	12	.61	15	42	187	.39	10.0	0.105	2.7	3.75	MW	CG	N
1.225	31.12	72652S	1.00	25.4	1.015	25.8	59	10	.49	12	29	129	.39	10.0	0.105	2.7	3.75	SST	CG	N
1.225	31.12	72665	1.00	25.4	1.001	25.4	88	15	.57	14	50	222	.43	11.0	0.112	2.8	3.88	MW	CG	N
1.225	31.12	72665S	1.00	25.4	1.001	25.4	75	13	.44	11	33	148	.43	11.0	0.112	2.8	3.88	SST	CG	N
1.225	31.12	72680	1.00	25.4	.975	24.8	134	24	.50	13	67	299	.50	12.7	0.125	3.2	4.00	MW	CG	N
1.225	31.12	72680S	1.00	25.4	.975	24.8	114	20	.40	10	46	205	.50	12.7	0.125	3.2	4.00	SST	CG	N
1.225	31.12	72694	1.00	25.4	.955	24.3	183	32	.46	12	84	375	.54	13.7	0.135	3.4	4.00	MW	CG	N
1.225	31.12	72694S	1.00	25.4	.955	24.3	156	27	.36	9.0	55	246	.54	13.7	0.135	3.4	4.00	SST	CG	N
1.225	31.12	72709	1.00	25.4	.929	23.6	270	47	.41	10	110	489	.59	15.0	0.148	3.8	4.00	MW	CG	N
1.225	31.12	72709S	1.00	25.4	.929	23.6	229	40	.32	8.0	73	322	.59	15.0	0.148	3.8	4.00	SST	CG	N
1.225	31.12	72729	1.00	25.4	.901	22.9	415	73	.35	8.8	143	637	.65	16.5	0.162	4.1	4.00	MW	CG	N
1.225	31.12	72729S	1.00	25.4	.901	22.9	352	62	.26	6.5	91	404	.65	16.5	0.162	4.1	4.00	SST	CG	N
1.225	31.12	72639	1.25	31.8	1.033	26.2	39	6.7	.84	21	32	144	.41	10.4	0.096	2.4	4.25	MW	CG	N
1.225	31.12	72639S	1.25	31.8	1.033	26.2	33	5.7	.68	17	22	99	.41	10.4	0.096	2.4	4.25	SST	CG	N
1.225	31.12	72653	1.25	31.8	1.015	25.8	53	9.2	.79	20	42	186	.46	11.7	0.105	2.7	4.38	MW	CG	N
1.225	31.12	72653S	1.25	31.8	1.015	25.8	45	7.9	.64	16	29	129	.46	11.7	0.105	2.7	4.38	SST	CG	N
1.225	31.12	72666	1.25	31.8	1.001	25.4	67	12	.75	19	50	221	.50	12.8	0.112	2.8	4.50	MW	CG	N
1.225	31.12	72666S	1.25	31.8	1.001	25.4	57	9.9	.59	15	33	148	.50	12.8	0.112	2.8	4.50	SST	CG	N
1.225	31.12	72681	1.25	31.8	.975	24.8	101	18	.67	17	68	301	.58	14.7	0.125	3.2	4.63	MW	CG	N
1.225	31.12	72681S	1.25	31.8	.975	24.8	86	15	.54	14	46	205	.58	14.7	0.125	3.2	4.63	SST	CG	N
1.225	31.12	72695	1.25	31.8	.955	24.3	136	24	.61	15	83	369	.64	16.3	0.135	3.4	4.75	MW	CG	N
1.225	31.12	72695S	1.25	31.8	.955	24.3	116	20	.48	12	55	246	.64	16.3	0.135	3.4	4.75	SST	CG	N
1.225	31.12	72710	1.25	31.8	.929	23.6	199	35	.55	14	109	484	.70	17.9	0.148	3.8	4.75	MW	CG	N
1.225	31.12	72710S	1.25	31.8	.929	23.6	169	30	.43	11	73	322	.70	17.9	0.148	3.8	4.75	SST	CG	N
1.225	31.12	72629	1.50	38.1	1.055	26.8	19	3.4	1.1	28	21	96	.39	10.0	0.085	2.2	4.63	MW	CG	N
1.225	31.12	72629S	1.50	38.1	1.055	26.8	16	2.9	.99	25	16	72	.39	10.0	0.085	2.2	4.63	SST	CG	N
1.225	31.12	72640	1.50	38.1	1.033	26.2	31	5.4	1.0	27	32	144	.46	11.6	0.096	2.4	4.75	MW	CG	N
1.225	31.12	72640S	1.50	38.1	1.033	26.2	26	4.6	.84	21	22	99	.46	11.6	0.096	2.4	4.75	SST	CG	N
1.225	31.12	72654	1.50	38.1	1.015	25.8	43	7.4	.99	25	42	187	.51	13.0	0.105	2.7	4.88	MW	CG	N
1.225	31.12	72654S	1.50	38.1	1.015	25.8	36	6.3	.80	20	29	129	.51	13.0	0.105	2.7	4.88	SST	CG	N
1.225	31.12	72667	1.50	38.1	1.001	25.4	54	9.4	.94	24	50	224	.56	14.2	0.112	2.8	5.00	MW	CG	N
1.225	31.12	72667S	1.50	38.1	1.001	25.4	46	8.0	.73	19	33	148	.56	14.2	0.112	2.8	5.00	SST	CG	N
1.225	31.12	72682	1.50	38.1	.975	24.8	81	14	.84	21	68	302	.66	16.7	0.125	3.2	5.25	MW	CG	N
1.225	31.12	72682S	1.50	38.1	.975	24.8	69	12	.67	17	46	205	.66	16.7	0.125	3.2	5.25	SST	CG	N
1.225	31.12	72696	1.50	38.1	.955	24.3	116	20	.74	19	86	383	.69	17.6	0.135	3.4	5.13	MW	CG	N
1.225	31.12	72696S	1.50	38.1	.955	24.3	98	17	.56	14	55	246	.69	17.6	0.135	3.4	5.13	SST	CG	N
1.225	31.12	72711	1.50	38.1	.929	23.6	158	28	.69	17	108	481	.81	20.7	0.148	3.8	5.50	MW	CG	N
1.225	31.12	72711S	1.50	38.1	.929	23.6	134	23	.54	14	73	322	.81	20.7	0.148	3.8	5.50	SST	CG	N
1.225	31.12	72730	1.50	38.1	.901	22.9	238	42	.60	15	143	637	.89	22.6	0.162	4.1	5.50	MW	CG	N
1.225	31.12	72730S	1.50	38.1	.901	22.9	203	35	.45	11	91	404	.89	22.6	0.162	4.1	5.50	SST	CG	N
1.225	31.12	72743	1.50	38.1	.871	22.1	353	62	.52	13	185	824	.97	24.7	0.177	4.5	5.50	MW	CG	N
1.225	31.12	72743S	1.50	38.1	.871	22.1	300	53	.39	9.9	118	523	.97	24.7	0.177	4.5	5.50	SST	CG	N
1.225	31.12	72751	1.50	38.1	.841	21.4	516	90	.44	11	226	1005	1.03	26.2	0.192	4.9	5.38	MW	CG	N
1.225	31.12	72751S	1.50	38.1	.841	21.4	439	77	.31	8.0	138	613	1.03	26.2	0.192	4.9	5.38	SST	CG	N
1.225	31.12	72641	1.75	44.5	1.033	26.2	26	4.6	1.2	32	33	145	.50	12.8	0.096	2.4	5.25	MW	CG	N
1.225	31.12	72641S	1.75	44.5	1.033	26.2	22	3.9	1.0	25	22	99	.50	12.8	0.096	2.4	5.25	SST	CG	N
1.225	31.12	72656	1.75	44.5	1.015	25.8	37	6.5	1.2	30	44	194	.56	14.3	0.105	2.7	5.38	MW	CG	N
1.225	31.12	72656S	1.75	44.5	1.015	25.8	31	5.5	.92	23	29	129	.56	14.3	0.105	2.7	5.38	SST	CG	N
1.225	31.12	72669	1.75	44.5	1.001	25.4	51	8.9	1.0	25	51	227	.59	14.9	0.112	2.8	5.25	MW	CG	N
1.225	31.12	72669S	1.75	44.5	1.001	25.4	43	7.6	.77	19	33	148	.59	14.9	0.112	2.8	5.25	SST	CG	N
1.225	31.12	72683	1.75	44.5	.975	24.8	67	12	1.0	26	68	304	.73	18.7	0.125	3.2	5.88	MW	CG	N
1.225	31.12	72683S	1.75	44.5	.975	24.8	57	10	.81	20	46	205	.73	18.7	0.125	3.2	5.88	SST	CG	N
1.225	31.12	72698	1.75	44.5	.955	24.3	92	16	.93	24	86	383	.81	20.6	0.135	3.4	6.00	MW	CG	N
1.225	31.12	72698S	1.75	44.5	.955	24.3	78	14	.71	18	55	246	.81	20.6	0.135	3.4	6.00	SST	CG	N
1.225	31.12	72713	1.75	44.5	.929	23.6	134	23	.84	21	113	501	.91	23.0	0.148	3.8	6.13	MW	CG	N
1.225	31.12	72713S	1.75	44.5	.929	23.6	114	20	.64	16	73	322	.91	23.0	0.148	3.8	6.13	SST	CG	N
1.225	31.12	72630	2.00	50.8	1.055	26.8	14	2.5	1.5	39	21	95	.48	12.1	0.085	2.2	5.63	MW	CG	N
1.225	31.12	72630S	2.00	50.8	1.055	26.8	12	2.1	1.4	34	16	72	.48	12.1	0.085	2.2	5.63	SST	CG	N
1.225	31.12	72642	2.00	50.8	1.033	26.2	23	3.9	1.4	37	33	145	.55	14.0	0.096	2.4	5.75	MW	CG	N
1.225	31.12	72642S	2.00	50.8	1.033	26.2	19	3.3	1.2	29	22	99	.55	14.0	0.096	2.4	5.75	SST	CG	N
1.225	31.12	72657	2.00	50.8	1.015	25.8	31	5.4	1.4	35	42	187	.63	16.0	0.105	2.7	6.00	MW	CG	N
1.225	31.12	72657S	2.00	50.8	1.015	25.8	26	4.6	1.1	28	29	129	.63	16.0	0.105	2.7	6.00	SST	CG	N
1.225	31.12	72670	2.00	50.8	1.001	25.4	39	6.7	1.3	33	50	223	.70	17.8	0.112	2.8	6.25	MW	CG	N

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.225	31.12	72752S	2.00	50.8	.841	21.4	303	53	.45	12	138	613	1.34	34.1	0.192	4.9	7.00	SST	CG	N
1.225	31.12	72759	2.00	50.8	.811	20.6	505	88	.55	14	278	1237	1.45	36.8	0.207	5.3	7.00	MW	CG	N
1.225	31.12	72759S	2.00	50.8	.811	20.6	429	75	.40	10	171	761	1.45	36.8	0.207	5.3	7.00	SST	CG	N
1.225	31.12	72643	2.25	57.2	1.033	26.2	20	3.5	1.7	42	33	145	.60	15.2	0.096	2.4	6.25	MW	CG	N
1.225	31.12	72643S	2.25	57.2	1.033	26.2	17	2.9	1.3	33	22	99	.60	15.2	0.096	2.4	6.25	SST	CG	N
1.225	31.12	72685	2.25	57.2	.975	24.8	50	8.8	1.3	34	68	301	.91	23.0	0.125	3.2	7.25	MW	CG	N
1.225	31.12	72685S	2.25	57.2	.975	24.8	43	7.5	1.1	27	46	205	.91	23.0	0.125	3.2	7.25	SST	CG	N
1.225	31.12	72721	2.25	57.2	.913	23.2	130	23	.99	25	128	571	1.15	29.2	0.156	4.0	7.38	MW	CG	N
1.225	31.12	72721S	2.25	57.2	.913	23.2	111	19	.74	19	81	362	1.15	29.2	0.156	4.0	7.38	SST	CG	N
1.225	31.12	72732	2.25	57.2	.901	22.9	151	26	.95	24	143	637	1.22	30.9	0.162	4.1	7.50	MW	CG	N
1.225	31.12	72732S	2.25	57.2	.901	22.9	128	22	.71	18	91	404	1.22	30.9	0.162	4.1	7.50	SST	CG	N
1.225	31.12	72631	2.50	63.5	1.055	26.8	11	1.9	1.9	49	21	96	.56	14.3	0.085	2.2	6.63	MW	CG	N
1.225	31.12	72631S	2.50	63.5	1.055	26.8	9.4	1.7	1.7	44	16	72	.56	14.3	0.085	2.2	6.63	SST	CG	N
1.225	31.12	72644	2.50	63.5	1.033	26.2	18	3.1	1.8	47	32	144	.66	16.8	0.096	2.4	6.88	MW	CG	N
1.225	31.12	72644S	2.50	63.5	1.033	26.2	15	2.6	1.5	38	22	99	.66	16.8	0.096	2.4	6.88	SST	CG	N
1.225	31.12	72658	2.50	63.5	1.015	25.8	24	4.2	1.8	44	42	187	.75	19.0	0.105	2.7	7.13	MW	CG	N
1.225	31.12	72658S	2.50	63.5	1.015	25.8	20	3.6	1.4	36	29	129	.75	19.0	0.105	2.7	7.13	SST	CG	N
1.225	31.12	72671	2.50	63.5	1.001	25.4	30	5.3	1.7	42	50	222	.84	21.3	0.112	2.8	7.50	MW	CG	N
1.225	31.12	72671S	2.50	63.5	1.001	25.4	26	4.5	1.3	33	33	148	.84	21.3	0.112	2.8	7.50	SST	CG	N
1.225	31.12	72686	2.50	63.5	.975	24.8	45	7.8	1.5	38	68	302	.98	25.0	0.125	3.2	7.88	MW	CG	N
1.225	31.12	72686S	2.50	63.5	.975	24.8	38	6.7	1.2	31	46	205	.98	25.0	0.125	3.2	7.88	SST	CG	N
1.225	31.12	72700	2.50	63.5	.955	24.3	64	11	1.3	34	86	383	1.05	26.6	0.135	3.4	7.75	MW	CG	N
1.225	31.12	72700S	2.50	63.5	.955	24.3	54	9.5	1.0	26	55	246	1.05	26.6	0.135	3.4	7.75	SST	CG	N
1.225	31.12	72715	2.50	63.5	.929	23.6	86	15	1.3	32	109	483	1.24	31.5	0.148	3.8	8.38	MW	CG	N
1.225	31.12	72715S	2.50	63.5	.929	23.6	73	13	.99	25	73	322	1.24	31.5	0.148	3.8	8.38	SST	CG	N
1.225	31.12	72722	2.50	63.5	.913	23.2	113	20	1.1	29	128	571	1.27	32.2	0.156	4.0	8.13	MW	CG	N
1.225	31.12	72722S	2.50	63.5	.913	23.2	96	17	.85	22	81	362	1.27	32.2	0.156	4.0	8.13	SST	CG	N
1.225	31.12	72733	2.50	63.5	.901	22.9	131	23	1.1	28	143	637	1.34	33.9	0.162	4.1	8.25	MW	CG	N
1.225	31.12	72733S	2.50	63.5	.901	22.9	111	19	.82	21	91	404	1.34	33.9	0.162	4.1	8.25	SST	CG	N
1.225	31.12	72745	2.50	63.5	.871	22.1	189	33	.98	25	185	824	1.50	38.2	0.177	4.5	8.50	MW	CG	N
1.225	31.12	72745S	2.50	63.5	.871	22.1	160	28	.73	19	118	523	1.50	38.2	0.177	4.5	8.50	SST	CG	N
1.225	31.12	72753	2.50	63.5	.841	21.4	272	48	.83	21	226	1005	1.63	41.5	0.192	4.9	8.50	MW	CG	N
1.225	31.12	72753S	2.50	63.5	.841	21.4	231	41	.60	15	138	613	1.63	41.5	0.192	4.9	8.50	SST	CG	N
1.225	31.12	72760	2.50	63.5	.811	20.6	384	67	.73	19	281	1248	1.76	44.7	0.207	5.3	8.50	MW	CG	N
1.225	31.12	72760S	2.50	63.5	.811	20.6	326	57	.52	13	171	761	1.76	44.7	0.207	5.3	8.50	SST	CG	N
1.225	31.12	72645	2.75	69.9	1.033	26.2	16	2.8	2.0	52	32	144	.71	18.0	0.096	2.4	7.38	MW	CG	N
1.225	31.12	72645S	2.75	69.9	1.033	26.2	14	2.4	1.6	42	22	99	.71	18.0	0.096	2.4	7.38	SST	CG	N
1.225	31.12	72687	2.75	69.9	.975	24.8	40	7.1	1.7	43	68	302	1.06	27.0	0.125	3.2	8.50	MW	CG	N
1.225	31.12	72687S	2.75	69.9	.975	24.8	34	6.0	1.3	34	46	205	1.06	27.0	0.125	3.2	8.50	SST	CG	N
1.225	31.12	72632	3.00	76.2	1.055	26.8	9.1	1.6	2.4	60	21	95	.65	16.5	0.085	2.2	7.63	MW	CG	N
1.225	31.12	72632S	3.00	76.2	1.055	26.8	7.7	1.4	2.1	53	16	72	.65	16.5	0.085	2.2	7.63	SST	CG	N
1.225	31.12	72646	3.00	76.2	1.033	26.2	15	2.5	2.2	57	33	145	.76	19.2	0.096	2.4	7.88	MW	CG	N
1.225	31.12	72646S	3.00	76.2	1.033	26.2	12	2.2	1.8	46	22	99	.76	19.2	0.096	2.4	7.88	SST	CG	N
1.225	31.12	72659	3.00	76.2	1.015	25.8	20	3.4	2.1	54	42	186	.88	22.3	0.105	2.7	8.38	MW	CG	N
1.225	31.12	72659S	3.00	76.2	1.015	25.8	17	2.9	1.7	44	29	129	.88	22.3	0.105	2.7	8.38	SST	CG	N
1.225	31.12	72672	3.00	76.2	1.001	25.4	25	4.3	2.0	52	50	223	.97	24.5	0.112	2.8	8.63	MW	CG	N
1.225	31.12	72672S	3.00	76.2	1.001	25.4	21	3.7	1.6	40	33	148	.97	24.5	0.112	2.8	8.63	SST	CG	N
1.225	31.12	72688	3.00	76.2	.975	24.8	37	6.4	1.9	47	68	304	1.14	29.0	0.125	3.2	9.13	MW	CG	N
1.225	31.12	72688S	3.00	76.2	.975	24.8	31	5.5	1.5	37	46	205	1.14	29.0	0.125	3.2	9.13	SST	CG	N
1.225	31.12	72701	3.00	76.2	.955	24.3	52	9.1	1.6	42	86	383	1.23	31.3	0.135	3.4	9.13	MW	CG	N
1.225	31.12	72701S	3.00	76.2	.955	24.3	44	7.8	1.2	32	55	246	1.23	31.3	0.135	3.4	9.13	SST	CG	N
1.225	31.12	72716	3.00	76.2	.929	23.6	70	12	1.5	39	108	480	1.46	37.1	0.148	3.8	9.88	MW	CG	N
1.225	31.12	72716S	3.00	76.2	.929	23.6	60	10	1.2	31	73	322	1.46	37.1	0.148	3.8	9.88	SST	CG	N
1.225	31.12	72723	3.00	76.2	.913	23.2	93	16	1.4	35	128	571	1.48	37.6	0.156	4.0	9.50	MW	CG	N
1.225	31.12	72723S	3.00	76.2	.913	23.2	79	14	1.0	26	81	362	1.48	37.6	0.156	4.0	9.50	SST	CG	N
1.225	31.12	72734	3.00	76.2	.901	22.9	107	19	1.3	34	143	637	1.56	39.6	0.162	4.1	9.63	MW	CG	N
1.225	31.12	72734S	3.00	76.2	.901	22.9	91	16	1.0	25	91	404	1.56	39.6	0.162	4.1	9.63	SST	CG	N
1.225	31.12	72746	3.00	76.2	.871	22.1	153	27	1.2	31	185	824	1.77	45.0	0.177	4.5	10.0	MW	CG	N
1.225	31.12	72746S	3.00	76.2	.871	22.1	130	23	.90	23	118	523	1.77	45.0	0.177	4.5	10.0	SST	CG	N
1.225	31.12	72754	3.00	76.2	.841	21.4	220	39	1.0	26	226	1005	1.92	48.8	0.192	4.9	10.0	MW	CG	N
1.225	31.12	72754S	3.00	76.2	.841	21.4	187	33	.74	19	138	613	1.92	48.8	0.192	4.9	10.0	SST	CG	N
1.225	31.12	72761	3.00	76.2	.811	20.6	310	54	.90	23	280	1245	2.10	53.2	0.207	5.3	10.1	MW	CG	N
1.225	31.12	72761S	3.00	76.2	.811	20.6	263	46	.65	17	171	761	2.10	53.2	0.207	5.3	10.1	SST	CG	N
1.225	31.12	72633	3.50	88.9	1.055	26.8	7.8	1.4	2.8	71	22	96	.72	18.4	0.085	2.2	8.50	MW	CG	N
1.225	31.12	72633S	3.50	88.9	1.055	26.8	6.6	1.2	2.5	62	16	72	.72	18.4	0.085	2.2	8.50	SST	CG	N
1.225	31.12	72647	3.50	88.9	1.033	26.2	12	2.2	2.6	67	33	145	.85	21.6	0.096	2.4	8.88	MW	CG	N
1.225	31.12	72647S	3.50	88.9	1.033	26.2	10	1.8	2.1	54	22	99	.85	21.6	0.096	2.4	8.88	SST	CG	N
1.225	31.12	72660	3.50	88.9	1.015	25.8														




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	EN DS	FIN ISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.225	31.12	72735S	3.50	88.9	.901	22.9	76	13	1.2	30	91	404	1.82	46.3	0.162	4.1	11.3	SST	CG	N
1.225	31.12	72747	3.50	88.9	.871	22.1	129	23	1.4	37	185	824	2.04	51.7	0.177	4.5	11.5	MW	CG	N
1.225	31.12	72747S	3.50	88.9	.871	22.1	109	19	1.1	27	118	523	2.04	51.7	0.177	4.5	11.5	SST	CG	N
1.225	31.12	72755	3.50	88.9	.841	21.4	185	32	1.2	31	226	1005	2.23	56.7	0.192	4.9	11.6	MW	CG	N
1.225	31.12	72755S	3.50	88.9	.841	21.4	157	28	.88	22	138	613	2.23	56.7	0.192	4.9	11.6	SST	CG	N
1.225	31.12	72762	3.50	88.9	.811	20.6	259	45	1.1	27	281	1248	2.41	61.1	0.207	5.3	11.6	MW	CG	N
1.225	31.12	72762S	3.50	88.9	.811	20.6	220	39	.78	20	171	761	2.41	61.1	0.207	5.3	11.6	SST	CG	N
1.225	31.12	72725	3.75	95.3	.913	23.2	72	13	1.8	45	128	571	1.81	46.1	0.156	4.0	11.6	MW	CG	N
1.225	31.12	72725S	3.75	95.3	.913	23.2	61	11	1.3	34	81	362	1.81	46.1	0.156	4.0	11.6	SST	CG	N
1.225	31.12	72736	3.75	95.3	.901	22.9	85	15	1.7	43	143	637	1.90	48.3	0.162	4.1	11.8	MW	CG	N
1.225	31.12	72736S	3.75	95.3	.901	22.9	72	13	1.3	32	91	404	1.90	48.3	0.162	4.1	11.8	SST	CG	N
1.225	31.12	72634	4.00	101.6	1.055	26.8	6.7	1.2	3.2	81	21	95	.81	20.5	0.085	2.2	9.50	MW	CG	N
1.225	31.12	72634S	4.00	101.6	1.055	26.8	5.7	1.0	2.9	73	16	72	.81	20.5	0.085	2.2	9.50	SST	CG	N
1.225	31.12	72648	4.00	101.6	1.033	26.2	11	1.9	3.1	78	33	145	.95	24.1	0.096	2.4	9.88	MW	CG	N
1.225	31.12	72648S	4.00	101.6	1.033	26.2	9.1	1.6	2.4	62	22	99	.95	24.1	0.096	2.4	9.88	SST	CG	N
1.225	31.12	72661	4.00	101.6	1.015	25.8	15	2.5	2.9	73	42	186	1.12	28.3	0.105	2.7	10.6	MW	CG	N
1.225	31.12	72661S	4.00	101.6	1.015	25.8	12	2.2	2.3	60	29	129	1.12	28.3	0.105	2.7	10.6	SST	CG	N
1.225	31.12	72674	4.00	101.6	1.001	25.4	18	3.2	2.8	70	50	222	1.25	31.6	0.112	2.8	11.1	MW	CG	N
1.225	31.12	72674S	4.00	101.6	1.001	25.4	15	2.7	2.2	55	33	148	1.25	31.6	0.112	2.8	11.1	SST	CG	N
1.225	31.12	72690	4.00	101.6	.975	24.8	27	4.7	2.5	64	68	303	1.47	37.3	0.125	3.2	11.8	MW	CG	N
1.225	31.12	72690S	4.00	101.6	.975	24.8	23	4.0	2.0	51	46	205	1.47	37.3	0.125	3.2	11.8	SST	CG	N
1.225	31.12	72703	4.00	101.6	.955	24.3	41	7.1	2.1	54	86	383	1.50	38.1	0.135	3.4	11.1	MW	CG	N
1.225	31.12	72703S	4.00	101.6	.955	24.3	34	6.0	1.6	41	55	246	1.50	38.1	0.135	3.4	11.1	SST	CG	N
1.225	31.12	72718	4.00	101.6	.929	23.6	51	9.0	2.1	54	108	481	1.89	47.9	0.148	3.8	12.8	MW	CG	N
1.225	31.12	72718S	4.00	101.6	.929	23.6	44	7.6	1.7	42	73	322	1.89	47.9	0.148	3.8	12.8	SST	CG	N
1.225	31.12	72726	4.00	101.6	.913	23.2	68	12	1.9	48	128	571	1.91	48.5	0.156	4.0	12.3	MW	CG	N
1.225	31.12	72726S	4.00	101.6	.913	23.2	58	10	1.4	36	81	362	1.91	48.5	0.156	4.0	12.3	SST	CG	N
1.225	31.12	72737	4.00	101.6	.901	22.9	78	14	1.8	47	143	637	2.05	51.9	0.162	4.1	12.6	MW	CG	N
1.225	31.12	72737S	4.00	101.6	.901	22.9	66	12	1.4	35	91	404	2.05	51.9	0.162	4.1	12.6	SST	CG	N
1.225	31.12	72748	4.00	101.6	.871	22.1	111	19	1.7	42	185	824	2.30	58.4	0.177	4.5	13.0	MW	CG	N
1.225	31.12	72748S	4.00	101.6	.871	22.1	94	17	1.2	32	118	523	2.30	58.4	0.177	4.5	13.0	SST	CG	N
1.225	31.12	72756	4.00	101.6	.841	21.4	159	28	1.4	36	226	1005	2.52	64.0	0.192	4.9	13.1	MW	CG	N
1.225	31.12	72756S	4.00	101.6	.841	21.4	135	24	1.0	26	138	613	2.52	64.0	0.192	4.9	13.1	SST	CG	N
1.225	31.12	72763	4.00	101.6	.811	20.6	223	39	1.3	32	281	1248	2.74	69.7	0.207	5.3	13.3	MW	CG	N
1.225	31.12	72763S	4.00	101.6	.811	20.6	190	33	.90	23	171	761	2.74	69.7	0.207	5.3	13.3	SST	CG	N
1.225	31.12	72635	4.50	114.3	1.055	26.8	6.0	1.1	3.6	92	22	96	.89	22.7	0.085	2.2	10.5	MW	CG	N
1.225	31.12	72635S	4.50	114.3	1.055	26.8	5.1	.89	3.2	81	16	72	.89	22.7	0.085	2.2	10.5	SST	CG	N
1.225	31.12	72649	4.50	114.3	1.033	26.2	9.5	1.7	3.5	88	33	146	1.04	26.5	0.096	2.4	10.9	MW	CG	N
1.225	31.12	72649S	4.50	114.3	1.033	26.2	8.1	1.4	2.7	70	22	99	1.04	26.5	0.096	2.4	10.9	SST	CG	N
1.225	31.12	72662	4.50	114.3	1.015	25.8	13	2.2	3.3	83	42	186	1.23	31.3	0.105	2.7	11.8	MW	CG	N
1.225	31.12	72662S	4.50	114.3	1.015	25.8	11	1.9	2.7	67	29	129	1.23	31.3	0.105	2.7	11.8	SST	CG	N
1.225	31.12	72676	4.50	114.3	1.001	25.4	18	3.2	2.8	71	51	227	1.23	31.3	0.112	2.8	11.0	MW	CG	N
1.225	31.12	72676S	4.50	114.3	1.001	25.4	15	2.7	2.2	55	33	148	1.23	31.3	0.112	2.8	11.0	SST	CG	N
1.225	31.12	72691	4.50	114.3	.975	24.8	24	4.2	2.9	73	68	301	1.64	41.7	0.125	3.2	13.1	MW	CG	N
1.225	31.12	72691S	4.50	114.3	.975	24.8	20	3.5	2.3	58	46	205	1.64	41.7	0.125	3.2	13.1	SST	CG	N
1.225	31.12	72705	4.50	114.3	.955	24.3	32	5.7	2.7	68	86	383	1.81	45.9	0.135	3.4	13.4	MW	CG	N
1.225	31.12	72705S	4.50	114.3	.955	24.3	27	4.8	2.0	51	55	246	1.81	45.9	0.135	3.4	13.4	SST	CG	N
1.225	31.12	72719	4.50	114.3	.929	23.6	45	7.9	2.4	61	108	480	2.11	53.6	0.148	3.8	14.3	MW	CG	N
1.225	31.12	72719S	4.50	114.3	.929	23.6	38	6.7	1.9	48	73	322	2.11	53.6	0.148	3.8	14.3	SST	CG	N
1.225	31.12	72727	4.50	114.3	.913	23.2	60	11	2.1	54	128	571	2.13	54.0	0.156	4.0	13.6	MW	CG	N
1.225	31.12	72727S	4.50	114.3	.913	23.2	51	8.9	1.6	41	81	362	2.13	54.0	0.156	4.0	13.6	SST	CG	N
1.225	31.12	72738	4.50	114.3	.901	22.9	69	12	2.1	53	143	637	2.27	57.6	0.162	4.1	14.0	MW	CG	N
1.225	31.12	72738S	4.50	114.3	.901	22.9	58	10	1.6	40	91	404	2.27	57.6	0.162	4.1	14.0	SST	CG	N
1.225	31.12	72749	4.50	114.3	.871	22.1	98	17	1.9	48	185	824	2.57	65.2	0.177	4.5	14.5	MW	CG	N
1.225	31.12	72749S	4.50	114.3	.871	22.1	83	15	1.4	36	118	523	2.57	65.2	0.177	4.5	14.5	SST	CG	N
1.225	31.12	72757	4.50	114.3	.841	21.4	140	24	1.6	41	226	1005	2.81	71.3	0.192	4.9	14.6	MW	CG	N
1.225	31.12	72757S	4.50	114.3	.841	21.4	119	21	1.2	29	138	613	2.81	71.3	0.192	4.9	14.6	SST	CG	N
1.225	31.12	72764	4.50	114.3	.811	20.6	196	34	1.4	36	281	1248	3.05	77.6	0.207	5.3	14.8	MW	CG	N
1.225	31.12	72764S	4.50	114.3	.811	20.6	167	29	1.0	26	171	761	3.05	77.6	0.207	5.3	14.8	SST	CG	N
1.225	31.12	72636	5.00	127.0	1.055	26.8	5.3	.93	4.0	102	21	95	.98	24.8	0.085	2.2	11.5	MW	CG	N
1.225	31.12	72636S	5.00	127.0	1.055	26.8	4.5	.79	3.6	92	16	72	.98	24.8	0.085	2.2	11.5	SST	CG	N
1.225	31.12	72650	5.00	127.0	1.033	26.2	8.5	1.5	3.8	98	33	145	1.15	29.3	0.096	2.4	12.0	MW	CG	N
1.225	31.12	72650S	5.00	127.0	1.033	26.2	7.2	1.3	3.1	78	22	99	1.15	29.3	0.096	2.4	12.0	SST	CG	N
1.225	31.12	72663	5.00	127.0	1.015	25.8	12	2.0	3.6	93	42	187	1.35	34.3	0.105	2.7	12.9	MW	CG	N
1.225	31.12	72663S	5.00	127.0	1.015	25.8	9.8	1.7	3.0	75	29	129	1.35	34.3	0.105	2.7	12.9	SST	CG	N
1.225	31.12	72678	5.00	127.0	1.001	25.4	16	2.9	3.1	79	51	227	1.36	34.5	0.112	2.8	12.1	MW	CG	N
1.225	31.12	72678S	5.00	127.0	1.001	25.4	14	2.4	2.4	61	33	148	1.36	34.5						

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.225	31.12	72758S	5.00	127.0	.841	21.4	106	19	1.3	33	138	613	3.12	79.2	0.192	4.9	16.3	SST	CG	N
1.225	31.12	72765	5.00	127.0	.811	20.6	175	31	1.6	41	281	1248	3.39	86.1	0.207	5.3	16.4	MW	CG	N
1.225	31.12	72765S	5.00	127.0	.811	20.6	148	26	1.2	29	171	761	3.39	86.1	0.207	5.3	16.4	SST	CG	N
1.225	31.12	72740	5.25	133.4	.901	22.9	60	11	2.4	61	143	637	2.55	64.8	0.162	4.1	15.8	MW	CG	N
1.225	31.12	72740S	5.25	133.4	.901	22.9	51	8.9	1.8	45	91	404	2.55	64.8	0.162	4.1	15.8	SST	CG	N
1.225	31.12	72741	5.50	139.7	.901	22.9	56	9.8	2.6	65	143	637	2.71	68.9	0.162	4.1	16.8	MW	CG	N
1.225	31.12	72741S	5.50	139.7	.901	22.9	48	8.3	1.9	48	91	404	2.71	68.9	0.162	4.1	16.8	SST	CG	N
1.225	31.12	72742	6.00	152.4	.901	22.9	51	8.9	2.8	71	143	637	2.94	74.6	0.162	4.1	18.1	MW	CG	N
1.225	31.12	72742S	6.00	152.4	.901	22.9	43	7.6	2.1	53	91	404	2.94	74.6	0.162	4.1	18.1	SST	CG	N
1.234	31.34	11740	.69	17.4	1.030	26.2	107	19	.26	6.7	28	126	.31	7.8	0.102	2.6	3.00	SPR	CG	Z
1.234	31.34	1192	.78	19.8	1.074	27.3	38	6.7	.38	9.5	14	64	.24	6.1	0.080	2.0	3.00	SPR	CG	N
1.234	31.34	3237	.84	21.4	1.082	27.5	31	5.4	.40	10	12	55	.23	5.8	0.076	1.9	3.00	SPR	CG	Z
1.234	31.34	3045	.88	22.2	1.110	28.2	7.0	1.2	.63	16	4.5	20	.24	6.1	0.062	1.6	4.00	SPR	CG	Z
1.234	31.34	1805	.88	22.2	1.080	27.4	33	5.7	.55	14	18	80	.23	5.9	0.077	2.0	3.00	MW	CG	Z
1.234	31.34	EE-77	.94	23.8	.954	24.2	281	49	.24	6.1	68	302	.49	12.4	0.140	3.6	3.50	SPR	CG	Z
1.234	31.34	12495	1.03	26.2	1.040	26.4	58	10	.42	11	24	109	.34	8.6	0.097	2.5	3.50	SPR	CG	Z
1.234	31.34	12094	1.19	30.2	.984	25.0	103	18	.49	12	50	223	.56	14.3	0.125	3.2	4.50	SPR	CG	Z
1.234	31.34	11597	1.31	33.3	.994	25.2	54	9.4	.47	12	25	113	.84	21.3	0.120	3.0	6.00	SPR	CG	Z
1.234	31.34	10120	1.38	34.9	1.100	27.9	3.7	.64	.91	23	3.3	15	.47	11.9	0.067	1.7	7.00	SPR	CG	Z
1.234	31.34	10499	1.41	35.7	1.040	26.4	58	10	.42	11	24	109	.34	8.6	0.097	2.5	3.50	SPR	CG	Z
1.234	31.34	10913	1.44	36.5	1.122	28.5	1.6	.29	1.1	27	1.8	7.8	.37	9.5	0.056	1.4	6.67	SST	CG	N
1.234	31.34	3202	1.50	38.1	1.080	27.4	8.7	1.5	1.1	27	9.2	41	.44	11.2	0.077	2.0	5.75	SPR	CG	Z
1.234	31.34	3430	1.63	41.3	1.050	26.7	28	4.8	.76	19	21	93	.41	10.5	0.092	2.3	4.50	SPR	CG	Z
1.234	31.34	2663	1.63	41.3	.910	23.1	268	47	.38	9.6	102	452	.81	20.6	0.162	4.1	5.00	SPR	CG	Z
1.234	31.34	S-338	1.75	44.5	1.110	28.2	2.3	.40	1.3	33	3.0	13	.43	11.0	0.062	1.6	7.00	SST	CG	N
1.234	31.34	S-1677	1.75	44.5	1.026	26.1	26	4.5	1.1	27	28	124	.62	15.8	0.104	2.6	6.00	SST	CG	N
1.234	31.34	S-963	1.81	46.0	1.066	27.1	20	3.6	.76	19	16	69	.34	8.5	0.084	2.1	4.00	SST	CG	N
1.234	31.34	EE-88	2.00	50.8	.694	17.6	2132	373	.18	4.6	390	1734	1.62	41.1	0.270	6.9	6.00	SPR	CG	Z
1.234	31.34	12000	2.25	57.2	.848	21.5	272	48	.59	15	161	717	1.64	41.7	0.193	4.9	8.50	SPR	CG	Z
1.234	31.34	2641	2.34	59.5	1.024	26.0	24	4.3	1.5	38	36	162	.84	21.3	0.105	2.7	7.00	MW	C	Z
1.234	31.34	PP-44	2.69	68.2	1.134	28.8	.40	.07	1.9	47	.75	3.3	.83	21.0	0.050	1.3	15.5	SPR	C	Z
1.234	31.34	10578	2.75	69.9	1.024	26.0	20	3.5	1.5	39	31	138	.84	21.3	0.105	2.7	8.00	SPR	CG	Z
1.234	31.34	1759	2.78	70.6	1.064	27.0	11	2.0	1.5	39	17	77	.50	12.6	0.085	2.2	6.00	SPR	CG	Z
1.234	31.34	S-3061	3.13	79.4	1.062	27.0	10	1.8	1.7	42	17	74	.65	16.4	0.086	2.2	6.50	SST	C	N
1.234	31.34	11787	3.16	80.2	.852	21.6	211	37	.74	19	156	696	1.91	48.5	0.191	4.9	10.0	SPR	CG	Z
1.234	31.34	3465	3.50	88.9	.794	20.2	359	63	.63	16	226	1006	2.42	61.5	0.220	5.6	11.0	SPR	CG	Z
1.234	31.34	S-458	3.63	92.1	1.110	28.2	.96	.17	2.8	70	2.6	12	.87	22.0	0.062	1.6	14.0	SST	CG	N
1.234	31.34	2724	4.00	101.6	.994	25.2	21	3.7	2.1	54	44	198	1.59	40.4	0.120	3.0	12.3	HD	C	Z
1.234	31.34	2768	4.19	106.4	.964	24.5	36	6.3	1.7	43	61	272	1.62	41.1	0.135	3.4	12.0	SPR	CG	Z
1.234	31.34	397	5.44	138.1	.880	22.4	94	16	1.4	36	131	585	2.61	66.3	0.177	4.5	14.8	SPR	CG	Z
1.234	31.34	10341	6.00	152.4	.820	20.8	174	30	1.1	29	197	878	3.31	84.1	0.207	5.3	16.0	SPR	CG	Z
1.250	31.75	BB-44	.50	12.7	1.176	29.9	1.3	.23	.35	8.9	.46	2.1	.15	3.8	0.037	0.9	3.00	SST	C	N
1.250	31.75	10830	.50	12.7	1.070	27.2	54	9.4	.23	5.8	12	55	.27	6.9	0.090	2.3	3.00	SST	CG	N
1.250	31.75	2891	.63	15.9	1.126	28.6	5.3	.93	.35	9.0	1.9	8.4	.27	6.9	0.062	1.6	4.33	SPR	CG	Z
1.250	31.75	10971	.75	19.1	1.060	26.9	67	12	.31	7.9	21	94	.29	7.2	0.095	2.4	3.00	SST	CG	N
1.250	31.75	12207	.75	19.1	1.050	26.7	47	8.3	.35	8.9	17	74	.40	10.2	0.100	2.5	4.00	SPR	CG	Z
1.250	31.75	3963	.75	19.1	1.046	26.6	118	21	.24	6.1	28	125	.29	7.4	0.102	2.6	3.00	SPR	CG	Z
1.250	31.75	2887	.94	23.8	1.130	28.7	7.4	1.3	.73	18	5.4	24	.21	5.3	0.060	1.5	3.50	SPR	CG	Z
1.250	31.75	10231	1.06	27.0	.800	20.3	1955	342	.12	3.1	239	1061	.84	21.4	0.225	5.7	3.75	SPR	CG	Z
1.250	31.75	S-3158	1.13	28.6	1.068	27.1	20	3.5	.69	18	14	62	.43	11.0	0.091	2.3	4.75	SST	CG	N
1.250	31.75	S-148	1.25	31.8	1.126	28.6	5.5	.96	.94	24	5.2	23	.31	7.9	0.062	1.6	4.00	SST	C	N
1.250	31.75	829	1.25	31.8	1.010	25.7	89	16	.50	13	44	195	.64	16.3	0.120	3.0	4.33	HD	C	Z
1.250	31.75	S-1436	1.31	33.3	1.040	26.4	40	7.1	.70	18	28	126	.47	12.0	0.105	2.7	4.50	SST	CG	N
1.250	31.75	3044	1.34	34.1	1.106	28.1	7.9	1.4	.98	25	7.7	34	.36	9.1	0.072	1.8	5.00	SPR	CG	Z
1.250	31.75	S-475	1.38	34.9	.896	22.8	331	58	.35	8.9	115	513	.89	22.5	0.177	4.5	5.00	SST	CG	N
1.250	31.75	1933	1.38	34.9	.896	22.8	286	50	.31	8.0	89	398	1.06	27.0	0.177	4.5	6.00	SPR	CG	Z
1.250	31.75	807	1.63	41.3	.866	22.0	412	72	.38	9.7	157	699	1.15	29.3	0.192	4.9	6.00	HD	CG	Z
1.250	31.75	B18-196	1.72	43.6	.982	24.9	74	13	.72	18	53	236	.80	20.4	0.134	3.4	6.00	SST	CG	N
1.250	31.75	B17-153	1.75	44.5	1.164	29.6	.13	.02	.80	20	.10	.47	.95	24.0	0.043	1.1	21.0	SST	C	N
1.250	31.75	I-60A	1.75	44.5	1.126	28.6	1.8	.32	1.1	29	2.0	9.1	.62	15.7	0.062	1.6	9.00	HD	C	BO
1.250	31.75	11708	1.75	44.5	.892	22.7	400	70	.34	8.5	134	597	.90	22.7	0.179	4.5	5.00	SPR	CG	Z
1.250	31.75	3455	1.75	44.5	.890	22.6	308	54	.42	11	130	579	1.08	27.4	0.180	4.6	6.00	SPR	CG	Z
1.250	31.75	2936	1.78	45.2	1.116	28.3	5.8	1.0	1.4	37	8.4	38	.34	8.5	0.067	1.7	5.00	SPR	CG	Z
1.250	31.75	1901	2.00	50.8	1.040	26.4	23	4.1	1.3	32	29	131	.74	18.7	0.105	2.7	7.00	SPR	CG	Z
1.250	31.75	S-3247	2.03	51.6	1.130	28.7	1.2	.21	1.4	36	1.8	7.8	.60	15.2	0.060	1.5	10.0	SST	CG	N
1.250	31.75	12608	2.25	57.2	1.116	28.3	4.1	.72	1.8	47	7.5	34	.42	10.6	0.067	1.7	6.25	MW	CG	T
1.250	31.75	11298	2.28	57.9	.910	23.1	224	39	.52	13	116	514	1.06	27.0	0.170	4.3	6.25	SPR	CG	Z
1.250	31.75	10995	2.31	58.7	.954	24.2	86	15	.92	23	79	351	1.18	30.1	0.148	3.8				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.250	31.75	858	3.13	79.4	.974	24.7	49	8.7	1.3	33	64	286	1.33	33.9	0.138	3.5	9.67	HD	CG	Z
1.250	31.75	S-1625	3.25	82.6	1.106	28.1	3.9	.69	2.5	63	9.7	43	.59	15.1	0.072	1.8	7.25	SST	C	N
1.250	31.75	3344	3.25	82.6	1.036	26.3	18	3.2	1.8	46	32	144	.96	24.5	0.107	2.7	9.00	SPR	CG	Z
1.250	31.75	S-274	3.38	85.7	1.100	27.9	4.6	.80	2.4	61	11	49	.62	15.9	0.075	1.9	7.33	SST	C	N
1.250	31.75	11644	3.41	86.5	1.124	28.5	2.3	.40	2.9	74	6.5	29	.50	12.8	0.063	1.6	8.00	SPR	CG	Z
1.250	31.75	810	3.63	92.1	.896	22.8	111	19	1.2	30	130	578	2.18	55.4	0.177	4.5	12.3	HD	CG	Z
1.250	31.75	S-1166	3.75	95.3	1.010	25.7	21	3.7	1.9	48	40	178	1.26	32.0	0.120	3.0	10.5	SST	CG	N
1.250	31.75	11102	4.00	101.6	1.040	26.4	10	1.8	2.6	66	27	120	1.39	35.3	0.105	2.7	13.3	SPR	CG	Z
1.250	31.75	859	4.00	101.6	.980	24.9	34	5.9	1.8	46	60	268	1.65	42.0	0.135	3.4	12.3	HD	CG	Z
1.250	31.75	34	4.00	101.6	.954	24.2	49	8.6	1.6	41	79	351	1.85	47.0	0.148	3.8	12.5	HD	CG	Z
1.250	31.75	33	4.00	101.6	.800	20.3	302	53	.79	20	239	1061	3.00	76.2	0.225	5.7	13.3	HD	CG	Z
1.250	31.75	4264	4.50	114.3	1.010	25.7	23	4.0	1.9	49	44	195	1.44	36.6	0.120	3.0	11.0	SPR	C	Z
1.250	31.75	3179	4.59	116.7	1.024	26.0	10	1.8	2.6	65	26	115	2.02	51.3	0.113	2.9	18.0	SPR	CG	Z
1.250	31.75	11681	4.63	117.5	.980	24.9	26	4.5	2.4	60	60	268	2.09	53.1	0.135	3.4	15.5	SPR	CG	Z
1.250	31.75	S-954	4.75	120.7	1.124	28.5	.74	.13	3.6	90	2.6	12	1.20	30.4	0.063	1.6	18.0	SST	C	N
1.250	31.75	1765	4.75	120.7	1.068	27.1	5.8	1.0	3.5	88	20	89	1.18	30.0	0.091	2.3	13.0	HD	CG	Z
1.250	31.75	4100	5.00	127.0	.814	20.7	328	57	.69	18	226	1007	2.40	60.9	0.218	5.5	11.0	SPR	CG	Z
1.250	31.75	3145	5.06	128.6	.896	22.8	143	25	.91	23	130	578	1.77	45.0	0.177	4.5	10.0	SPR	CG	Z
1.250	31.75	12772	5.75	146.1	.950	24.1	36	6.2	2.2	57	80	357	2.75	69.9	0.150	3.8	17.3	HD	C	Z
1.250	31.75	3448	6.00	152.4	1.136	28.9	1.1	.20	4.9	124	5.5	24	.63	15.9	0.057	1.4	10.0	SPR	C	Z
1.250	31.75	248	6.25	158.8	.926	23.5	51	9.0	2.0	50	100	447	2.75	70.0	0.162	4.1	17.0	HD	CG	Z
1.250	31.75	3043	6.38	161.9	.990	25.1	19	3.2	2.9	74	54	240	2.31	58.6	0.130	3.3	17.8	SPR	CG	Z
1.250	31.75	S-959	6.88	174.6	.956	24.3	22	3.8	3.2	81	70	310	3.23	82.1	0.147	3.7	22.0	SST	CG	N
1.250	31.75	3210	7.00	177.8	.926	23.5	57	10	1.8	45	100	447	2.51	63.8	0.162	4.1	15.5	SPR	CG	Z
1.250	31.75	2725	7.63	193.7	.954	24.2	26	4.6	3.0	76	79	351	3.18	80.8	0.148	3.8	21.5	SPR	CG	Z
1.250	31.75	12648	8.00	203.2	1.066	27.1	12	2.1	1.7	44	21	92	.78	19.9	0.092	2.3	7.50	SPR	C	Z
1.250	31.75	12658	8.00	203.2	1.062	27.0	4.6	.81	6.2	158	29	128	1.76	44.8	0.094	2.4	17.8	MW	C	Z
1.250	31.75	4181	8.00	203.2	1.010	25.7	9.8	1.7	4.5	113	44	195	2.88	73.2	0.120	3.0	23.0	SPR	C	Z
1.250	31.75	849	8.00	203.2	.926	23.5	32	5.6	3.1	80	100	447	4.21	107.0	0.162	4.1	26.0	HD	CG	Z
1.250	31.75	2996	8.38	212.7	1.022	26.0	7.3	1.3	5.2	132	38	168	2.82	71.7	0.114	2.9	24.8	SPR	CG	Z
1.250	31.75	822	10.0	254.0	.954	24.2	18	3.2	4.3	110	79	351	4.48	113.7	0.148	3.8	30.3	HD	CG	Z
1.250	31.75	3460	11.8	298.5	1.066	27.1	2.8	.48	7.5	190	21	92	2.48	63.1	0.092	2.3	26.0	HD	C	GI
1.250	31.75	868	12.0	304.8	1.010	25.7	6.7	1.2	6.6	167	44	195	4.08	103.6	0.120	3.0	33.0	HD	C	Z
1.250	31.75	860	12.0	304.8	.980	24.9	11	1.8	5.7	146	60	268	4.83	122.6	0.135	3.4	34.8	HD	C	Z
1.250	31.75	839	12.0	304.8	.866	22.0	55	9.6	2.9	73	157	699	6.14	156.1	0.192	4.9	32.0	HD	CG	Z
1.250	31.75	802	12.0	304.8	.836	21.2	67	12	2.9	73	195	868	7.56	191.9	0.207	5.3	36.5	HD	CG	Z
1.250	31.75	834	12.0	304.8	.800	20.3	93	16	2.6	65	239	1061	8.72	221.5	0.225	5.7	38.8	HD	CG	Z
1.250	31.75	S-3047	16.0	406.4	1.070	27.2	1.5	.26	12	313	18	80	3.51	89.2	0.090	2.3	38.0	SST	C	N
1.250	31.75	4000	19.0	482.6	1.000	25.4	5.9	1.0	8.4	214	50	220	5.50	139.7	0.125	3.2	44.0	SPR	CG	Z
1.250	31.75	4045	24.8	628.7	.750	19.1	97	17	3.3	84	322	1431	15.0	381.0	0.250	6.4	60.0	SPR	CG	Z
1.266	32.16	S-3199	.75	19.1	1.124	28.5	19	3.3	.49	12	9.2	41	.21	5.4	0.071	1.8	3.00	SST	CG	N
1.266	32.16	2957	1.41	35.7	1.056	26.8	45	7.8	.68	17	30	134	.47	12.0	0.105	2.7	4.50	SPR	CG	Z
1.266	32.16	10292	1.44	36.5	1.094	27.8	19	3.4	.91	23	17	77	.39	9.8	0.086	2.2	4.50	SPR	CG	Z
1.266	32.16	11212	1.53	38.9	.926	23.5	304	53	.38	9.5	114	508	.85	21.6	0.170	4.3	5.00	SPR	CG	Z
1.266	32.16	11210	1.63	41.3	.970	24.6	165	29	.47	12	78	347	.89	22.6	0.148	3.8	5.00	SPR	C	Z
1.266	32.16	2600	1.75	44.5	1.056	26.8	41	7.1	1.0	26	42	188	.50	12.7	0.105	2.7	4.75	MW	CG	Z
1.266	32.16	11796	1.97	50.0	1.164	29.6	1.1	.19	1.6	42	1.7	7.8	.33	8.4	0.051	1.3	6.50	SST	CG	N
1.266	32.16	B18-186	2.03	51.6	.766	19.5	1357	238	.20	5.0	268	1192	1.38	34.9	0.250	6.4	5.50	SST	CG	N
1.266	32.16	11857	2.47	62.7	1.128	28.7	6.3	1.1	1.5	38	9.5	42	.35	8.8	0.069	1.8	5.00	SPR	CG	N
1.266	32.16	S-348	2.75	69.9	1.016	25.8	37	6.5	1.2	30	45	199	.94	23.8	0.125	3.2	7.50	SST	CG	N
1.266	32.16	10169	2.75	69.9	.912	23.2	156	27	.82	21	128	571	1.59	40.5	0.177	4.5	9.00	SPR	CG	Z
1.266	32.16	11503	2.75	69.9	.850	21.6	284	50	.46	12	131	584	2.29	58.1	0.208	5.3	10.0	SPR	CG	Z
1.266	32.16	11700	3.09	78.6	1.182	30.0	.81	.14	2.8	72	2.3	10	.25	6.4	0.042	1.1	5.00	SPR	C	Z
1.266	32.16	11788	3.31	84.1	1.054	26.8	17	2.9	1.9	48	31	138	.95	24.2	0.106	2.7	9.00	SPR	CG	Z
1.266	32.16	S-335	4.00	101.6	.882	22.4	224	39	.60	15	134	595	1.56	39.6	0.192	4.9	8.00	SST	CG	N
1.266	32.16	10515	4.13	104.8	1.056	26.8	9.7	1.7	2.7	69	26	117	1.42	36.0	0.105	2.7	13.5	SPR	CG	Z
1.266	32.16	12512	4.19	106.3	.922	23.4	120	21	1.4	35	165	736	1.89	48.1	0.172	4.4	10.0	MW	C	N
1.266	32.16	S-1128	4.25	108.0	1.142	29.0	1.1	.19	3.4	87	3.6	16	.81	20.5	0.062	1.6	12.0	SST	C	N
1.266	32.16	11903	5.09	129.4	1.144	29.1	.63	.11	3.9	100	2.5	11	1.16	29.4	0.061	1.5	18.0	SST	C	N
1.266	32.16	2712	6.00	152.4	.954	24.2	37	6.4	2.4	62	89	395	3.16	80.3	0.156	4.0	20.0	SPR	CG	Z
1.266	32.16	11562	7.25	184.2	1.028	26.1	12	2.0	3.7	93	42	188	2.32	58.9	0.119	3.0	18.5	SPR	CG	GI
1.266	32.16	3283	8.00	203.2	1.026	26.1	9.4	1.7	4.6	117	43	193	2.88	73.2	0.120	3.0	23.0	HD	C	Z
1.266	32.16	4164	8.25	209.6	.906	23.0	51	9.0	2.5	64	129	573	4.50	114.3	0.180	4.6	25.0	SPR	CG	Z
1.266	32.16	3377	9.38	238.1	1.052	26.7	5.5	.96	5.8	147	32	142	2.68	67.9	0.107	2.7	24.0	SPR	C	Z
1.281	32.54	B8-59	.59	15.1	1.125	28.6	11	1.9	.24	6.1	2.6	12	.35	8.9	0.078	2.0	4.50	SST	CG	N
1.281	32.54	3620	.69	17.4	1.157	29.4	3.9	.68	.38	9.6	1.5	6.6	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
1.281	32.54	S-1683	.95	24.2	.997	25.3	229	40	.27	6.8	62	274	.50	12.6	0.142	3.6	3.50	SST	CG	N
1.281	32.54	S-30																		

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.281	32.54	S-3055	3.50	88.9	1.137	28.9	2.9	.51	2.8	72	8.2	37	.68	17.4	0.072	1.8	8.50	SST	C	N
1.281	32.54	11645	4.00	101.6	1.153	29.3	2.2	.39	3.4	86	7.5	33	.58	14.6	0.064	1.6	8.00	SPR	C	Z
1.281	32.54	11665	4.00	101.6	.965	24.5	58	10	1.6	40	91	406	2.05	52.2	0.158	4.0	13.0	SPR	CG	Z
1.281	32.54	S-1604	4.13	104.8	1.155	29.3	1.1	.19	3.3	84	3.7	16	.82	20.8	0.063	1.6	12.0	SST	CG	N
1.281	32.54	S-431	4.31	109.5	1.121	28.5	3.0	.52	3.4	85	10	45	.95	24.1	0.080	2.0	11.8	SST	CG	N
1.281	32.54	1843	5.00	127.0	1.171	29.7	.89	.16	4.4	112	3.9	17	.61	15.4	0.055	1.4	10.0	HD	C	Z
1.281	32.54	S-3224	5.31	134.9	1.101	28.0	4.1	.72	4.1	103	17	74	1.26	32.0	0.090	2.3	14.0	SST	CG	N
1.281	32.54	2879	6.19	157.2	.969	24.6	33	5.8	2.6	67	88	391	3.12	79.2	0.156	4.0	20.0	SPR	CG	Z
1.281	32.54	S-1017	11.0	279.4	.961	24.4	24	4.3	3.4	87	84	374	4.12	104.6	0.160	4.1	25.8	SST	CG	N
1.296	32.92	4360	.50	12.7	1.194	30.3	5.0	.88	.35	8.8	1.7	7.8	.15	3.9	0.051	1.3	3.00	SPR	CG	Z
1.296	32.92	11527	1.25	31.8	1.086	27.6	52	9.1	.57	15	30	131	.53	13.3	0.105	2.7	4.00	SPR	CG	Z
1.296	32.92	3655	1.50	38.1	1.114	28.3	20	3.6	.94	24	19	86	.43	11.0	0.091	2.3	4.75	SPR	CG	Z
1.296	32.92	10402	1.63	41.3	1.086	27.6	34	6.0	.86	22	30	131	.53	13.3	0.105	2.7	5.00	SPR	CG	Z
1.296	32.92	3409	1.63	41.3	1.080	27.4	39	6.8	.83	21	32	143	.54	13.7	0.108	2.7	5.00	SPR	CG	Z
1.296	32.92	3955	1.69	42.8	1.172	29.8	2.8	.49	1.3	32	3.5	16	.43	11.0	0.062	1.6	6.00	SPR	C	Z
1.296	32.92	2550	1.75	44.5	1.100	27.9	22	3.9	1.2	31	27	119	.54	13.7	0.098	2.5	5.50	MW	CG	Z
1.296	32.92	12015	1.75	44.5	1.086	27.6	34	6.0	.86	22	30	131	.53	13.3	0.105	2.7	5.00	SPR	CG	Z
1.296	32.92	10902	2.38	60.3	1.116	28.3	7.9	1.4	1.7	42	13	59	.72	18.3	0.090	2.3	8.00	SST	CG	N
1.296	32.92	11771	2.50	63.5	1.046	26.6	55	9.6	.88	22	48	213	.75	19.1	0.125	3.2	6.00	SPR	CG	Z
1.296	32.92	3151	2.56	65.1	1.184	30.1	1.2	.22	2.1	54	2.6	12	.45	11.4	0.056	1.4	8.00	SPR	CG	Z
1.296	32.92	S-977	2.66	67.5	1.026	26.1	44	7.7	1.2	30	53	234	1.08	27.4	0.135	3.4	8.00	SST	CG	N
1.296	32.92	11638	2.72	69.0	1.086	27.6	13	2.3	1.7	42	22	96	1.05	26.7	0.105	2.7	10.0	SPR	CG	Z
1.296	32.92	1845	2.75	69.9	1.100	27.9	22	3.9	1.5	39	34	150	.54	13.7	0.098	2.5	5.50	MW	CG	Z
1.296	32.92	3359	2.75	69.9	1.046	26.6	40	7.0	1.2	31	48	213	1.06	27.0	0.125	3.2	7.50	SPR	C	Z
1.296	32.92	3744	2.94	74.6	1.096	27.8	17	2.9	1.5	39	26	114	.70	17.8	0.100	2.5	7.00	SPR	CG	Z
1.296	32.92	S-3017	3.00	76.2	1.172	29.8	1.4	.25	2.4	60	3.3	15	.62	15.7	0.062	1.6	9.00	SST	C	N
1.296	32.92	11265	3.00	76.2	.972	24.7	97	17	1.0	25	97	432	1.46	37.0	0.162	4.1	9.00	SPR	CG	N
1.296	32.92	2828	3.75	95.3	.796	20.2	497	87	.63	16	312	1389	2.97	75.4	0.250	6.4	12.0	SPR	CG	Z
1.296	32.92	11966	4.00	101.6	.984	25.0	52	9.1	1.7	42	87	387	2.03	51.5	0.156	4.0	13.0	SPR	CG	Z
1.296	32.92	S-160	4.50	114.3	1.112	28.2	5.4	.95	3.4	85	18	80	1.15	29.2	0.092	2.3	11.5	SST	C	N
1.296	32.92	12128	4.94	125.4	1.188	30.2	.80	.14	4.3	110	3.5	15	.59	15.1	0.054	1.4	10.0	SPR	C	Z
1.296	32.92	11734	4.94	125.4	1.008	25.6	35	6.2	2.0	51	70	314	1.94	49.4	0.144	3.7	13.5	SPR	CG	Z
1.296	32.92	S-1657	6.00	152.4	1.156	29.4	1.7	.29	5.2	131	8.6	38	.84	21.3	0.070	1.8	12.0	SST	CG	N
1.296	32.92	4133	6.75	171.5	.992	25.2	39	6.9	2.0	52	81	358	2.28	57.9	0.152	3.9	15.0	SPR	CG	GI
1.296	32.92	4025	22.0	558.8	1.046	26.6	3.4	.59	13	330	44	194	7.31	185.7	0.125	3.2	58.5	SST	CG	N
1.312	33.32	S-1499	.94	23.8	1.188	30.2	2.7	.47	.60	15	1.6	7.2	.34	8.7	0.062	1.6	5.50	SST	CG	N
1.312	33.32	10053	1.13	28.6	.812	20.6	3125	547	.10	2.5	309	1375	.88	22.2	0.250	6.4	3.50	SPR	CG	Z
1.312	33.32	3325	1.19	30.2	1.072	27.2	88	15	.48	12	42	187	.48	12.2	0.120	3.0	4.00	SPR	CG	Z
1.312	33.32	S-198	1.22	31.0	1.102	28.0	44	7.7	.61	16	27	120	.42	10.7	0.105	2.7	4.00	SST	CG	N
1.312	33.32	S-1275	1.38	34.9	1.112	28.2	20	3.5	.83	21	17	74	.55	14.0	0.100	2.5	5.50	SST	CG	N
1.312	33.32	S-3223	1.44	36.5	1.152	29.3	14	2.4	.91	23	13	57	.32	8.1	0.080	2.0	4.00	SST	CG	N
1.312	33.32	10670	1.81	46.0	1.102	28.0	29	5.1	.92	23	27	120	.53	13.3	0.105	2.7	5.00	SST	CG	N
1.312	33.32	271	1.88	47.6	.988	25.1	145	25	.66	17	96	427	1.05	26.7	0.162	4.1	6.50	HD	CG	Z
1.312	33.32	12127	1.91	48.4	1.050	26.7	86	15	.62	16	53	235	.66	16.6	0.131	3.3	5.00	SPR	CG	Z
1.312	33.32	10505	1.94	49.2	1.126	28.6	17	3.0	1.2	31	20	91	.51	13.0	0.093	2.4	5.50	SPR	CG	Z
1.312	33.32	3021	1.94	49.2	1.102	28.0	25	4.4	1.2	30	29	130	.63	16.0	0.105	2.7	6.00	SPR	CG	Z
1.312	33.32	11986	2.09	53.2	.897	22.8	396	69	.48	12	188	837	1.45	36.9	0.208	5.3	7.00	SPR	CG	Z
1.312	33.32	S-1422	2.38	60.3	1.152	29.3	7.3	1.3	1.7	44	13	57	.54	13.7	0.080	2.0	5.75	SST	C	N
1.312	33.32	S-3170	2.50	63.5	1.136	28.9	5.8	1.0	1.7	43	10	44	.79	20.1	0.088	2.2	9.00	SST	CG	N
1.312	33.32	3169	2.63	66.7	.986	25.0	103	18	.95	24	98	435	1.39	35.2	0.163	4.1	8.50	SPR	CG	Z
1.312	33.32	1877	2.88	73.0	1.116	28.3	21	3.7	1.6	40	33	148	.64	16.2	0.098	2.5	5.50	MW	C	Z
1.312	33.32	2988	2.94	74.6	1.062	27.0	35	6.1	1.4	35	47	210	1.08	27.4	0.125	3.2	8.50	SPR	CG	Z
1.312	33.32	10109	3.25	82.6	1.192	30.3	2.7	.47	2.2	57	6.1	27	.39	9.9	0.060	1.5	5.50	SPR	C	Z
1.312	33.32	3397	3.50	88.9	1.172	29.8	4.5	.79	2.0	51	9.1	41	.49	12.4	0.070	1.8	6.00	SPR	C	Z
1.312	33.32	S-1628	3.53	89.7	1.170	29.7	1.8	.31	2.7	69	4.8	22	.82	20.7	0.071	1.8	11.5	SST	CG	N
1.312	33.32	12056	3.56	90.5	.952	24.2	116	20	1.1	27	125	555	1.98	50.3	0.180	4.6	11.0	SPR	CG	N
1.312	33.32	10044	3.63	92.1	.862	21.9	319	56	.72	18	229	1018	2.48	62.9	0.225	5.7	11.0	SPR	CG	Z
1.312	33.32	4361	4.00	101.6	1.102	28.0	11	2.0	2.6	65	29	130	1.13	28.7	0.105	2.7	10.8	SPR	CG	Z
1.312	33.32	11434	4.00	101.6	.938	23.8	154	27	.90	23	139	620	1.87	47.5	0.187	4.7	10.0	SPR	CG	Z
1.312	33.32	2749	4.69	119.0	.788	20.0	600	105	.57	14	341	1518	3.08	78.2	0.262	6.7	11.8	SPR	CG	Z
1.312	33.32	12144	4.75	120.7	1.010	25.7	33	5.8	2.3	57	74	331	2.49	63.3	0.151	3.8	16.5	SPR	CG	Z
1.312	33.32	12012	4.94	125.4	1.204	30.6	.77	.13	4.3	110	3.3	15	.59	15.1	0.054	1.4	10.0	SPR	C	Z
1.312	33.32	11488	5.09	129.4	1.205	30.6	.74	.13	4.5	114	3.3	15	.59	14.9	0.054	1.4	10.0	SPR	CG	Z
1.312	33.32	3048	5.25	133.4	1.042	26.5	24	4.3	2.4	60	58	256	1.89	48.0	0.135	3.4	14.0	SPR	CG	Z
1.312	33.32	12108	5.41	137.3	1.094	27.8	12	2.1	2.7	68	33	145	1.25	31.8	0.109	2.8	11.5	SPR	CG	GI
1.312	33.32	S-456	5.63	142.9	1.092	27.7	7.8	1.4	3.8	96	30	132	1.71	43.3	0.110	2.8	15.5	SST	CG	N
1.312	33.32	10399	6.00	152.4	1.086	27.6	10	1.8	3.5	89	35	156	1.75	44.5	0.113	2.9	15.5	SPR	CG	Z
1.312	33.32	336	6.00	152.4	.958</															




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.328	33.73	11605	2.69	68.2	1.088	27.6	34	5.9	1.2	31	41	184	.96	24.4	0.120	3.0	7.00	SPR	C	Z
1.328	33.73	S-953	2.75	69.9	1.202	30.5	1.9	.34	2.3	59	4.5	20	.44	11.2	0.063	1.6	7.00	SST	CG	N
1.328	33.73	S-261	3.13	79.4	1.226	31.1	.90	.16	2.7	70	2.5	11	.38	9.7	0.051	1.3	6.50	SST	C	N
1.328	33.73	S-377	4.38	111.1	1.058	26.9	24	4.3	2.1	53	51	228	1.62	41.1	0.135	3.4	12.0	SST	CG	N
1.328	33.73	11625	5.00	127.0	1.226	31.1	.58	.10	4.5	114	2.6	12	.51	13.0	0.051	1.3	10.0	SPR	CG	Z
1.328	33.73	3084	5.38	136.5	1.058	26.9	23	4.1	2.4	62	57	253	1.89	48.0	0.135	3.4	14.0	SPR	CG	Z
1.328	33.73	11526	5.50	139.7	1.116	28.3	11	1.9	2.8	71	30	132	1.31	33.2	0.106	2.7	11.3	SPR	CG	GI
1.328	33.73	10840	5.69	144.4	1.114	28.3	6.2	1.1	3.7	93	23	101	2.01	51.0	0.107	2.7	18.8	SPR	CG	Z
1.328	33.73	S-1658	6.00	152.4	1.087	27.6	13	2.3	2.9	73	38	170	1.48	37.5	0.121	3.1	12.5	SST	CG	N
1.328	33.73	3082	8.00	203.2	1.016	25.8	27	4.8	3.1	79	85	378	3.32	84.2	0.156	4.0	21.3	SPR	CG	Z
1.328	33.73	4306	8.25	209.6	.974	24.7	54	9.5	2.3	57	123	547	3.36	85.4	0.177	4.5	19.0	SPR	CG	Z
1.343	34.11	2634	.88	22.2	1.183	30.0	29	5.1	.45	12	13	59	.24	6.1	0.080	2.0	3.00	SPR	CG	Z
1.343	34.11	2774	1.50	38.1	1.191	30.3	5.9	1.0	1.0	27	6.2	27	.46	11.6	0.076	1.9	6.00	SPR	CG	Z
1.343	34.11	11807	1.50	38.1	1.181	30.0	12	2.2	1.1	28	14	61	.36	9.3	0.081	2.1	4.50	SPR	CG	Z
1.343	34.11	10639	1.72	43.6	.843	21.4	1229	215	.25	6.3	303	1348	1.38	34.9	0.250	6.4	5.50	SPR	CG	GI
1.343	34.11	2777	1.75	44.5	1.193	30.3	5.8	1.0	1.3	33	7.5	34	.44	11.2	0.075	1.9	6.00	MW	CG	Z
1.343	34.11	3061	1.88	47.6	1.155	29.3	18	3.1	1.2	29	21	91	.49	12.5	0.094	2.4	5.25	SPR	CG	Z
1.343	34.11	11643	1.88	47.6	1.151	29.2	25	4.4	.87	22	22	97	.43	11.0	0.096	2.4	4.50	SPR	CG	Z
1.343	34.11	1717	2.09	53.2	1.233	31.3	2.5	.43	1.8	45	4.4	20	.30	7.7	0.055	1.4	4.50	HD	C	Z
1.343	34.11	11567	2.34	59.5	1.205	30.6	2.6	.46	1.7	44	4.5	20	.62	15.8	0.069	1.8	8.00	SPR	CG	Z
1.343	34.11	10425	2.38	60.3	1.217	30.9	2.9	.50	2.0	51	5.8	26	.36	9.2	0.063	1.6	5.75	SPR	CG	Z
1.343	34.11	11387	2.38	60.3	1.163	29.5	9.6	1.7	1.7	44	17	74	.63	16.0	0.090	2.3	7.00	MW	CG	Z
1.343	34.11	11929	2.41	61.1	1.111	28.2	20	3.5	1.4	35	27	122	1.04	26.5	0.116	2.9	9.00	SPR	CG	Z
1.343	34.11	4370	2.56	65.1	.893	22.7	479	84	.47	12	224	998	1.69	42.9	0.225	5.7	7.50	SPR	CG	GI
1.343	34.11	3278	2.63	66.7	1.029	26.1	100	17	.86	22	86	381	1.14	28.9	0.157	4.0	7.25	SPR	CG	Z
1.343	34.11	12112	2.69	68.2	1.103	28.0	33	5.7	1.3	32	41	182	.84	21.3	0.120	3.0	7.00	SPR	CG	Z
1.343	34.11	11721	3.06	77.8	1.101	28.0	28	4.9	1.5	38	42	187	.97	24.6	0.121	3.1	8.00	SPR	CG	Z
1.343	34.11	3267	3.13	79.4	.969	24.6	175	31	.78	20	136	607	1.59	40.4	0.187	4.7	8.50	SPR	CG	Z
1.343	34.11	10658	3.31	84.1	1.219	31.0	1.8	.31	2.8	70	4.9	22	.54	13.8	0.062	1.6	7.75	SPR	C	Z
1.343	34.11	S-1605	4.03	102.4	1.139	28.9	8.3	1.4	2.8	72	23	104	1.20	30.4	0.102	2.6	10.8	SST	CG	N
1.343	34.11	11904	4.13	104.8	1.227	31.2	1.2	.21	3.6	93	4.5	20	.48	12.2	0.058	1.5	8.25	SPR	CG	N
1.343	34.11	S-155	4.50	114.3	1.227	31.2	1.1	.19	4.0	102	4.3	19	.48	12.2	0.058	1.5	8.25	SST	CG	N
1.343	34.11	S-353	4.50	114.3	1.199	30.5	1.6	.29	3.6	92	5.9	26	.86	21.9	0.072	1.8	12.0	SST	CG	N
1.343	34.11	10090	5.50	139.7	.893	22.7	176	31	1.3	32	224	998	3.83	97.2	0.225	5.7	17.0	SPR	CG	Z
1.343	34.11	4137	5.75	146.1	1.073	27.3	23	4.0	2.5	63	56	251	1.89	48.0	0.135	3.4	14.0	SPR	CG	Z
1.343	34.11	10445	5.75	146.1	1.073	27.3	19	3.3	3.0	77	56	251	2.23	56.6	0.135	3.4	16.5	SPR	CG	Z
1.343	34.11	396	7.09	180.2	1.103	28.0	9.1	1.6	4.5	115	41	182	2.39	60.7	0.120	3.0	20.0	SPR	CG	Z
1.343	34.11	12439	10.0	254.0	1.017	25.8	25	4.3	3.9	98	96	426	4.56	115.9	0.163	4.1	27.0	SPR	C	N
1.343	34.11	1623	10.4	263.5	.989	25.1	33	5.8	3.7	93	122	541	5.09	129.3	0.177	4.5	28.8	SPR	CG	Z
1.343	34.11	4014	15.8	400.1	1.049	26.6	8.5	1.5	8.5	216	72	322	7.06	179.2	0.147	3.7	48.0	SPR	CG	Z
1.359	34.52	10424	.50	12.7	1.177	29.9	73	13	.25	6.5	18	82	.24	6.2	0.091	2.3	2.67	SPR	CG	GI
1.359	34.52	LL-79	.50	12.7	1.159	29.4	128	22	.18	4.5	23	101	.25	6.4	0.100	2.5	2.50	SST	CG	N
1.359	34.52	EE-84	1.19	30.2	1.099	27.9	55	9.7	.41	10	23	100	.78	19.8	0.130	3.3	6.00	SPR	CG	N
1.359	34.52	2664	1.19	30.2	.977	24.8	639	112	.22	5.7	144	638	.74	18.8	0.191	4.9	4.00	SPR	CG	Z
1.359	34.52	11677	1.22	31.0	1.199	30.5	7.0	1.2	.74	19	5.2	23	.48	12.2	0.080	2.0	6.00	SPR	CG	Z
1.359	34.52	S-1261	1.25	31.8	1.253	31.8	2.5	.44	1.0	25	2.5	11	.25	6.4	0.053	1.3	3.75	SST	C	N
1.359	34.52	11824	1.28	32.5	1.179	29.9	18	3.2	.90	23	16	73	.38	9.7	0.090	2.3	4.25	SST	CG	N
1.359	34.52	JJ-52	1.28	32.5	1.119	28.4	78	14	.52	13	41	180	.48	12.2	0.120	3.0	4.00	SPR	CG	N
1.359	34.52	11551	1.31	33.3	1.135	28.8	58	10	.57	14	33	147	.56	14.2	0.112	2.8	4.00	SPR	CG	Z
1.359	34.52	11867	1.47	37.3	1.221	31.0	5.1	.89	1.1	27	5.3	24	.41	10.5	0.069	1.8	5.00	SPR	C	N
1.359	34.52	10511	1.50	38.1	1.247	31.7	2.6	.45	1.2	30	3.0	14	.31	7.8	0.056	1.4	4.50	SPR	C	Z
1.359	34.52	B18-180	1.50	38.1	.879	22.3	1098	192	.20	5.2	225	1000	1.14	29.0	0.240	6.1	4.75	SST	CG	N
1.359	34.52	3433	1.88	47.6	1.159	29.4	21	3.6	1.2	30	24	109	.65	16.5	0.100	2.5	5.50	SPR	C	Z
1.359	34.52	11789	1.94	49.2	1.025	26.0	165	29	.62	16	102	452	1.00	25.5	0.167	4.2	6.00	SPR	CG	Z
1.359	34.52	3747	2.13	54.0	1.159	29.4	24	4.2	1.0	26	24	109	.50	12.7	0.100	2.5	5.00	SPR	CG	Z
1.359	34.52	S-3235	2.19	55.6	1.065	27.1	61	11	1.1	27	65	287	1.10	28.0	0.147	3.7	7.50	SST	CG	N
1.359	34.52	12514	2.25	57.2	1.069	27.2	75	13	1.1	29	84	374	1.12	28.5	0.145	3.7	6.75	MW	C	N
1.359	34.52	11922	2.28	57.9	1.267	32.2	.15	.03	1.4	35	.20	.90	.92	23.4	0.046	1.2	19.0	SST	C	N
1.359	34.52	2564	2.63	66.7	1.199	30.5	7.0	1.2	1.9	47	13	58	.48	12.2	0.080	2.0	6.00	SPR	CG	Z
1.359	34.52	S-960	2.69	68.2	1.177	29.9	11	1.9	1.6	41	17	76	.55	13.9	0.091	2.3	6.00	SST	CG	N
1.359	34.52	3373	2.75	69.9	1.215	30.9	3.6	.63	2.2	55	7.9	35	.58	14.6	0.072	1.8	7.00	HD	C	Z
1.359	34.52	11409	2.75	69.9	1.119	28.4	30	5.2	1.4	35	41	180	.99	25.1	0.120	3.0	7.25	SPR	C	Z
1.359	34.52	11520	2.75	69.9	1.045	26.5	94	17	.90	23	85	377	1.31	33.2	0.157	4.0	7.33	SPR	CG	Z
1.359	34.52	B17-171	3.00	76.2	1.151	29.2	19	3.3	1.3	34	25	113	.62	15.8	0.104	2.6	6.00	SST	CG	N
1.359	34.52	10476	3.13	79.4	1.063	27.0	55	9.7	1.3	33	73	325	1.33	33.8	0.148	3.8	9.00	SPR	CG	Z
1.359	34.52	3102	3.25	82.6	1.207	30.7	4.5	.80	2.5	63	11	50	.61	15.4	0.076	1.9	7.00	SPR	C	Z
1.359	34.52	S-3112	3.25	82.6	1.199	30.5	4.7	.82	2.6	66	12	54	.66	16.8	0.080	2.0	7.25	SST	C	N
1.359	34.52	S-958	3																	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.359	34.52	2979	11.1	282.6	.835	21.2	257	45	1.3	33	332	1475	5.76	146.4	0.262	6.7	22.0	SPR	CG	Z
1.375	34.93	11808	.63	15.9	1.257	31.9	4.4	.76	.40	10	1.8	7.8	.22	5.6	0.059	1.5	3.75	SPR	CG	Z
1.375	34.93	BB-59	1.00	25.4	1.275	32.4	3.9	.68	.85	22	3.3	15	.15	3.8	0.050	1.3	3.00	SPR	CG	N
1.375	34.93	3393	1.19	30.2	1.125	28.6	80	14	.57	14	45	201	.53	13.5	0.125	3.2	4.25	SPR	CG	Z
1.375	34.93	GG-76	1.19	30.2	.995	25.3	499	87	.24	6.1	120	536	.76	19.3	0.190	4.8	4.00	SST	CG	N
1.375	34.93	12539	1.20	30.5	1.081	27.5	207	36	.34	8.7	71	315	.70	17.7	0.147	3.7	3.75	SPR	CL	N
1.375	34.93	11883	1.22	31.0	1.271	32.3	3.0	.53	1.0	26	3.1	14	.18	4.6	0.052	1.3	3.50	SPR	CG	N
1.375	34.93	917	1.25	31.8	1.165	29.6	43	7.5	.65	17	28	124	.42	10.7	0.105	2.7	4.00	HD	CG	Z
1.375	34.93	3346	1.25	31.8	1.151	29.2	56	9.8	.58	15	33	145	.45	11.4	0.112	2.8	4.00	SPR	CG	Z
1.375	34.93	12140	1.59	40.5	1.115	28.3	47	8.3	.75	19	35	157	.85	21.5	0.130	3.3	6.50	SPR	CG	N
1.375	34.93	S-1087	1.63	41.3	1.135	28.8	48	8.4	.77	19	37	163	.57	14.5	0.120	3.0	4.75	SST	CG	N
1.375	34.93	11628	1.63	41.3	1.123	28.5	41	7.2	.81	20	33	148	.82	20.8	0.126	3.2	6.50	SPR	CG	Z
1.375	34.93	S-326	1.69	42.8	1.105	28.1	63	11	.78	20	50	221	.74	18.9	0.135	3.4	5.50	SST	CG	N
1.375	34.93	3560	1.75	44.5	.991	25.2	393	69	.37	9.3	144	641	.96	24.4	0.192	4.9	5.00	SPR	CG	Z
1.375	34.93	10401	1.97	50.0	1.063	27.0	104	18	.79	20	82	366	1.01	25.8	0.156	4.0	6.50	SPR	CG	Z
1.375	34.93	12610	2.00	50.8	1.041	26.4	141	25	.71	18	100	447	1.09	27.6	0.167	4.2	6.50	SPR	CG	Z
1.375	34.93	10299	2.13	54.0	1.193	30.3	13	2.3	1.4	35	18	81	.50	12.7	0.091	2.3	5.50	SPR	CG	Z
1.375	34.93	11671	2.13	54.0	1.041	26.4	141	25	.71	18	100	447	1.09	27.6	0.167	4.2	6.50	SPR	CG	Z
1.375	34.93	12779	2.19	55.6	1.079	27.4	79	14	.92	23	72	321	1.00	25.4	0.148	3.8	6.75	HD	CG	Z
1.375	34.93	4400	2.22	56.4	1.179	29.9	15	2.6	1.5	39	23	101	.61	15.6	0.098	2.5	6.25	SPR	CG	Z
1.375	34.93	4343	2.25	57.2	1.193	30.3	10	1.8	1.7	42	17	76	.59	15.0	0.091	2.3	6.50	SPR	CG	Z
1.375	34.93	S-1388	2.31	58.7	1.191	30.3	6.8	1.2	1.6	39	11	47	.76	19.3	0.092	2.3	8.25	SST	CG	N
1.375	34.93	11839	2.34	59.5	1.187	30.1	7.6	1.3	1.6	40	12	53	.78	19.7	0.094	2.4	8.25	SST	CG	N
1.375	34.93	S-450	2.44	61.9	1.191	30.3	7.1	1.2	1.7	43	12	54	.74	18.7	0.092	2.3	8.00	SST	CG	N
1.375	34.93	10309	2.44	61.9	1.021	25.9	164	29	.73	18	119	530	1.24	31.5	0.177	4.5	7.00	SPR	CG	Z
1.375	34.93	10348	2.50	63.5	1.193	30.3	8.5	1.5	1.8	46	15	68	.68	17.3	0.091	2.3	7.50	SPR	CG	Z
1.375	34.93	12092	2.50	63.5	1.167	29.6	18	3.2	1.4	35	25	112	.73	18.5	0.104	2.6	6.00	SST	C	N
1.375	34.93	73	2.50	63.5	1.105	28.1	48	8.4	1.2	29	55	245	.98	24.9	0.135	3.4	7.25	HD	CG	Z
1.375	34.93	S-347	2.50	63.5	1.105	28.1	46	8.0	1.1	28	50	221	.91	23.1	0.135	3.4	6.75	SST	CG	N
1.375	34.93	12420	2.75	69.9	1.277	32.4	.89	.16	2.4	61	2.1	9.5	.34	8.7	0.049	1.2	6.00	SPR	C	Z
1.375	34.93	269	2.75	69.9	1.135	28.8	27	4.8	1.5	37	40	178	1.02	25.9	0.120	3.0	7.50	HD	C	Z
1.375	34.93	3464	2.75	69.9	1.105	28.1	31	5.5	1.3	32	40	176	1.49	37.7	0.135	3.4	10.0	HD	C	Z
1.375	34.93	54	2.75	69.9	1.021	25.9	122	21	.98	25	119	530	1.55	39.3	0.177	4.5	8.75	HD	CG	Z
1.375	34.93	10742	2.88	73.0	1.215	30.9	5.4	.95	2.3	59	13	56	.56	14.2	0.080	2.0	7.00	SPR	CG	Z
1.375	34.93	4355	2.94	74.6	1.205	30.6	4.0	.70	2.0	51	8.1	36	.91	23.2	0.085	2.2	10.8	SPR	CG	Z
1.375	34.93	S-1209	3.00	76.2	1.135	28.8	20	3.5	1.8	46	37	163	1.02	25.9	0.120	3.0	8.50	SST	CG	N
1.375	34.93	11266	3.00	76.2	1.021	25.9	153	27	.69	18	106	471	1.19	30.3	0.177	4.5	6.75	SST	CG	N
1.375	34.93	12048	3.47	88.1	1.125	28.6	28	4.8	1.6	42	45	201	1.06	27.0	0.125	3.2	8.50	SPR	CG	N
1.375	34.93	1557	3.50	88.9	1.259	32.0	.89	.16	2.9	73	2.5	11	.64	16.2	0.058	1.5	10.0	SPR	C	Z
1.375	34.93	S-289	3.75	95.3	1.251	31.8	1.5	.26	3.2	82	4.8	21	.53	13.4	0.062	1.6	7.50	SST	C	N
1.375	34.93	2591	3.75	95.3	1.231	31.3	1.6	.27	2.8	71	4.3	19	.95	24.2	0.072	1.8	13.3	HD	CG	Z
1.375	34.93	S-103	3.75	95.3	1.231	31.3	2.6	.46	3.1	79	8.2	37	.63	16.0	0.072	1.8	7.75	SST	C	N
1.375	34.93	S-1355	3.75	95.3	1.199	30.5	7.0	1.2	2.3	58	16	72	.62	15.6	0.088	2.2	7.00	SST	CG	N
1.375	34.93	S-445	3.75	95.3	1.175	29.8	6.0	1.1	2.6	65	15	68	1.20	30.5	0.100	2.5	12.0	SST	CG	N
1.375	34.93	898	3.75	95.3	1.105	28.1	29	5.2	1.9	48	55	245	1.55	39.4	0.135	3.4	10.5	HD	C	Z
1.375	34.93	S-195	3.75	95.3	1.063	27.0	63	11	1.2	30	73	325	1.33	33.7	0.156	4.0	8.50	SST	CG	N
1.375	34.93	S-327	3.88	98.4	1.231	31.3	2.6	.46	3.2	82	8.6	38	.63	16.0	0.072	1.8	7.75	SST	C	N
1.375	34.93	3987	4.00	101.6	1.021	25.9	80	14	1.5	38	119	530	2.17	55.1	0.177	4.5	12.3	SPR	CG	Z
1.375	34.93	861	4.13	104.8	1.105	28.1	27	4.7	2.1	52	55	245	1.53	38.9	0.135	3.4	11.3	HD	CG	Z
1.375	34.93	11513	4.38	111.1	1.217	30.9	3.7	.64	3.4	86	12	56	.79	20.1	0.079	2.0	9.00	SPR	CG	Z
1.375	34.93	823	4.38	111.1	1.079	27.4	36	6.3	2.0	51	72	321	1.83	46.4	0.148	3.8	13.3	HD	CG	Z
1.375	34.93	811	4.50	114.3	1.021	25.9	70	12	1.7	43	119	530	2.43	61.8	0.177	4.5	13.8	HD	CG	Z
1.375	34.93	10363	4.75	120.7	1.181	30.0	6.8	1.2	3.3	83	22	98	1.07	27.1	0.097	2.5	11.0	SPR	CG	Z
1.375	34.93	S-3002	5.38	136.5	1.221	31.0	3.3	.59	3.2	82	11	48	.69	17.6	0.077	2.0	8.00	SST	C	N
1.375	34.93	7005	5.38	136.5	1.001	25.4	75	13	1.8	45	134	594	3.30	83.8	0.187	4.7	16.3	HD	C	Z
1.375	34.93	389	6.00	152.4	1.135	28.8	13	2.2	3.2	81	40	178	1.68	42.7	0.120	3.0	14.0	HD	CG	Z
1.375	34.93	11977	6.50	165.1	.989	25.1	107	19	1.4	35	146	651	2.56	65.0	0.193	4.9	13.3	SPR	CG	Z
1.375	34.93	845	8.00	203.2	1.021	25.9	44	7.8	2.7	68	119	530	3.63	92.2	0.177	4.5	20.5	HD	CG	Z
1.375	34.93	383	9.75	247.7	1.215	30.9	1.1	.19	7.5	191	8.1	36	2.24	56.9	0.080	2.0	27.0	HD	C	Z
1.375	34.93	850	10.0	254.0	1.051	26.7	21	3.6	4.4	112	92	409	4.81	122.1	0.162	4.1	28.7	HD	C	Z
1.375	34.93	11489	10.9	277.8	1.019	25.9	32	5.6	3.8	97	121	539	5.25	133.4	0.178	4.5	28.5	HD	CG	Z
1.375	34.93	862	12.0	304.8	1.105	28.1	8.6	1.5	6.4	162	55	245	4.32	109.7	0.135	3.4	31.0	HD	C	Z
1.375	34.93	824	12.0	304.8	1.079	27.4	12	2.2	5.9	149	72	321	4.79	121.5	0.148	3.8	32.3	HD	CG	Z
1.375	34.93	841	12.0	304.8	.991	25.2	35	6.1	4.2	106	144	641	6.91	175.6	0.192	4.9	36.0	HD	CG	Z
1.375	34.93	803	12.0	304.8	.961	24.4	49	8.5	3.7	93	179	798	7.45	189.3	0.207	5.3	36.0	HD	CG	Z
1.375	34.93	801	12.0	304.8	.925	23.5	79	14	2.8	70	220	977	7.31	185.7	0.225	5.7	32.5	HD	CG	Z
1.390	35.31	10492	.78	19.8	1.118	28.4	249	44	.22	5.7	56	248	.41	10.4	0.136	3.5	3.00	SPR	CG	GI
1.390	35.31	S-401	.94	23.8	1.120	28.4														




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.390	35.31	S-1245	3.25	82.6	1.150	29.2	25	4.4	1.4	36	36	161	.84	21.3	0.120	3.0	7.00	SST	CG	N
1.390	35.31	3394	5.50	139.7	1.120	28.4	16	2.8	3.1	78	49	220	2.43	61.7	0.135	3.4	17.0	SPR	C	Z
1.390	35.31	11308	5.75	146.1	1.230	31.2	2.9	.51	4.4	112	13	57	.88	22.4	0.080	2.0	11.0	SPR	CG	Z
1.390	35.31	12680	5.88	149.2	1.114	28.3	18	3.2	3.2	82	58	259	2.45	62.2	0.138	3.5	16.8	SPR	C	Z
1.390	35.31	3398	6.50	165.1	1.006	25.6	103	18	1.4	35	143	635	2.50	63.4	0.192	4.9	13.0	SPR	CG	Z
1.390	35.31	3187	7.00	177.8	1.150	29.2	12	2.1	3.3	83	40	177	1.68	42.7	0.120	3.0	14.0	SPR	CG	Z
1.390	35.31	11978	8.00	203.2	1.034	26.3	44	7.7	2.7	69	120	533	3.65	92.7	0.178	4.5	20.5	SPR	CG	Z
1.390	35.31	12444	10.0	254.0	1.066	27.1	21	3.7	4.3	108	91	405	4.54	115.2	0.162	4.1	27.0	SPR	C	N
1.400	35.56	72766	2.25	57.2	1.076	27.3	116	20	1.1	28	127	563	1.05	26.7	0.162	4.1	6.50	MW	CG	N
1.400	35.56	72766S	2.25	57.2	1.076	27.3	99	17	.81	21	80	357	1.05	26.7	0.162	4.1	6.50	SST	CG	N
1.400	35.56	72775	2.25	57.2	1.046	26.6	169	30	.97	25	164	730	1.17	29.8	0.177	4.5	6.63	MW	CG	N
1.400	35.56	72775S	2.25	57.2	1.046	26.6	143	25	.73	18	104	463	1.17	29.8	0.177	4.5	6.63	SST	CG	N
1.400	35.56	72767	2.50	63.5	1.076	27.3	103	18	1.2	31	127	563	1.15	29.3	0.162	4.1	7.13	MW	CG	N
1.400	35.56	72767S	2.50	63.5	1.076	27.3	87	15	.92	23	80	357	1.15	29.3	0.162	4.1	7.13	SST	CG	N
1.400	35.56	72776	2.50	63.5	1.046	26.6	149	26	1.1	28	164	730	1.26	32.0	0.177	4.5	7.13	MW	CG	N
1.400	35.56	72776S	2.50	63.5	1.046	26.6	127	22	.82	21	104	463	1.26	32.0	0.177	4.5	7.13	SST	CG	N
1.400	35.56	72768	3.00	76.2	1.076	27.3	84	15	1.5	39	127	563	1.34	33.9	0.162	4.1	8.25	MW	CG	N
1.400	35.56	72768S	3.00	76.2	1.076	27.3	71	12	1.1	29	80	357	1.34	33.9	0.162	4.1	8.25	SST	CG	N
1.400	35.56	72777	3.00	76.2	1.046	26.6	120	21	1.4	35	164	730	1.48	37.7	0.177	4.5	8.38	MW	CG	N
1.400	35.56	72777S	3.00	76.2	1.046	26.6	102	18	1.0	26	104	463	1.48	37.7	0.177	4.5	8.38	SST	CG	N
1.400	35.56	72769	3.50	88.9	1.076	27.3	70	12	1.8	46	127	563	1.52	38.6	0.162	4.1	9.38	MW	CG	N
1.400	35.56	72769S	3.50	88.9	1.076	27.3	60	10	1.3	34	80	357	1.52	38.6	0.162	4.1	9.38	SST	CG	N
1.400	35.56	72778	3.50	88.9	1.046	26.6	100	18	1.6	42	164	730	1.73	43.8	0.177	4.5	9.75	MW	CG	N
1.400	35.56	72778S	3.50	88.9	1.046	26.6	85	15	1.2	31	104	463	1.73	43.8	0.177	4.5	9.75	SST	CG	N
1.400	35.56	72770	4.00	101.6	1.076	27.3	61	11	2.1	53	127	563	1.72	43.7	0.162	4.1	10.6	MW	CG	N
1.400	35.56	72770S	4.00	101.6	1.076	27.3	52	9.0	1.6	39	80	357	1.72	43.7	0.162	4.1	10.6	SST	CG	N
1.400	35.56	72779	4.00	101.6	1.046	26.6	87	15	1.9	48	164	730	1.92	48.9	0.177	4.5	10.9	MW	CG	N
1.400	35.56	72779S	4.00	101.6	1.046	26.6	74	13	1.4	36	104	463	1.92	48.9	0.177	4.5	10.9	SST	CG	N
1.400	35.56	72771	4.25	108.0	1.076	27.3	57	10	2.2	57	127	563	1.80	45.8	0.162	4.1	11.1	MW	CG	N
1.400	35.56	72771S	4.25	108.0	1.076	27.3	48	8.5	1.7	42	80	357	1.80	45.8	0.162	4.1	11.1	SST	CG	N
1.400	35.56	72780	4.25	108.0	1.046	26.6	81	14	2.0	51	164	730	2.04	51.7	0.177	4.5	11.5	MW	CG	N
1.400	35.56	72780S	4.25	108.0	1.046	26.6	69	12	1.5	38	104	463	2.04	51.7	0.177	4.5	11.5	SST	CG	N
1.400	35.56	72772	4.50	114.3	1.076	27.3	54	9.4	2.4	60	127	563	1.90	48.3	0.162	4.1	11.8	MW	CG	N
1.400	35.56	72772S	4.50	114.3	1.076	27.3	45	8.0	1.8	45	80	357	1.90	48.3	0.162	4.1	11.8	SST	CG	N
1.400	35.56	72781	4.50	114.3	1.046	26.6	76	13	2.2	55	164	730	2.15	54.5	0.177	4.5	12.1	MW	CG	N
1.400	35.56	72781S	4.50	114.3	1.046	26.6	65	11	1.6	41	104	463	2.15	54.5	0.177	4.5	12.1	SST	CG	N
1.400	35.56	72773	5.00	127.0	1.076	27.3	48	8.4	2.7	67	127	563	2.09	53.0	0.162	4.1	12.9	MW	CG	N
1.400	35.56	72773S	5.00	127.0	1.076	27.3	41	7.1	2.0	50	80	357	2.09	53.0	0.162	4.1	12.9	SST	CG	N
1.400	35.56	72782	5.00	127.0	1.046	26.6	69	12	2.4	60	164	730	2.32	59.0	0.177	4.5	13.1	MW	CG	N
1.400	35.56	72782S	5.00	127.0	1.046	26.6	59	10	1.8	45	104	463	2.32	59.0	0.177	4.5	13.1	SST	CG	N
1.400	35.56	72774	5.25	133.4	1.076	27.3	45	7.9	2.8	71	127	563	2.19	55.5	0.162	4.1	13.5	MW	CG	N
1.400	35.56	72774S	5.25	133.4	1.076	27.3	39	6.8	2.1	53	80	357	2.19	55.5	0.162	4.1	13.5	SST	CG	N
1.400	35.56	72783	5.25	133.4	1.046	26.6	65	11	2.5	64	164	730	2.46	62.4	0.177	4.5	13.9	MW	CG	N
1.400	35.56	72783S	5.25	133.4	1.046	26.6	55	9.7	1.9	48	104	463	2.46	62.4	0.177	4.5	13.9	SST	CG	N
1.406	35.71	S-1241	.75	19.1	1.136	28.9	202	35	.24	6.1	49	216	.41	10.3	0.135	3.4	3.00	SST	CG	N
1.406	35.71	S-70	.88	22.2	1.246	31.6	15	2.6	.60	15	8.7	39	.28	7.1	0.080	2.0	3.50	SST	CG	N
1.406	35.71	S-3246	1.00	25.4	1.322	33.6	.78	.14	.83	21	.65	2.9	.17	4.3	0.042	1.1	4.00	SST	CG	N
1.406	35.71	S-3024	1.00	25.4	1.256	31.9	9.6	1.7	.64	16	6.2	27	.36	9.0	0.075	1.9	3.75	SST	C	N
1.406	35.71	S-3018	1.13	28.6	1.226	31.1	18	3.2	.68	17	12	54	.45	11.4	0.090	2.3	4.00	SST	C	N
1.406	35.71	S-3075	1.13	28.6	1.032	26.2	563	99	.20	5.1	113	501	.65	16.6	0.187	4.7	3.50	SST	CG	N
1.406	35.71	NN-77	1.22	31.0	1.086	27.6	288	50	.27	6.8	77	343	.56	14.2	0.160	4.1	3.50	SST	CG	N
1.406	35.71	3017	1.25	31.8	1.282	32.6	2.5	.44	.85	22	2.1	9.4	.40	10.2	0.062	1.6	5.50	SPR	C	Z
1.406	35.71	11980	1.25	31.8	1.082	27.5	343	60	.26	6.7	90	401	.57	14.4	0.162	4.1	3.50	SPR	CG	Z
1.406	35.71	3324	1.28	32.5	1.166	29.6	47	8.2	.68	17	32	142	.60	15.2	0.120	3.0	5.00	HD	CG	Z
1.406	35.71	12192	1.34	34.1	1.296	32.9	2.1	.37	1.0	26	2.2	9.9	.30	7.7	0.055	1.4	4.50	SPR	C	Z
1.406	35.71	11908	1.50	38.1	1.300	33.0	1.6	.28	1.2	31	2.0	8.7	.29	7.4	0.053	1.3	4.50	SST	C	N
1.406	35.71	12009	1.50	38.1	1.296	32.9	.82	.14	1.0	26	.85	3.8	.47	11.9	0.055	1.4	8.50	SPR	CG	GI
1.406	35.71	S-333	1.50	38.1	1.136	28.9	67	12	.72	18	49	216	.68	17.1	0.135	3.4	5.00	SST	CG	N
1.406	35.71	S-1676	1.63	41.3	1.240	31.5	13	2.3	1.0	26	13	59	.42	10.5	0.083	2.1	4.00	SST	C	N
1.406	35.71	281	1.75	44.5	1.110	28.2	104	18	.68	17	71	315	.79	20.0	0.148	3.8	5.00	HD	CG	Z
1.406	35.71	11424	1.91	48.4	1.032	26.2	216	38	.61	15	131	582	1.22	30.9	0.187	4.7	6.50	SPR	CG	N
1.406	35.71	11283	2.13	54.0	1.224	31.1	8.7	1.5	1.5	38	13	57	.64	16.2	0.091	2.3	7.00	HD	CG	Z
1.406	35.71	10547	2.13	54.0	1.034	26.3	199	35	.65	16	129	573	1.26	31.9	0.186	4.7	6.75	SPR	CG	Z
1.406	35.71	S-1250	2.50	63.5	1.136	28.9	43	7.5	1.1	29	49	216	.91	23.1	0.135	3.4	6.75	SST	CG	N
1.406	35.71	12058	3.16	80.2	.992	25.2	236	41	.75	19	176	782	1.76	44.7	0.207	5.3	8.50	SPR	CG	Z
1.406	35.71	1683	3.25	82.6	.984	25.0	257	45	.72	18	186	826	1.79	45.6	0.211	5.4	8.50	SPR	CG	Z
1.406	35.71	S-1214	3.75	95.3	1.222	31.0	4.4	.77	2.7	70	12	53	1.01	25.7	0.09					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.406	35.71	4013	18.5	469.9	1.046	26.6	16	2.9	7.1	181	117	521	9.36	237.7	0.180	4.6	52.0	SPR	CG	Z
1.421	36.09	S-336	1.19	30.2	1.203	30.6	46	8.0	.61	16	28	125	.41	10.4	0.109	2.8	3.75	SST	CG	N
1.421	36.09	S-1229	1.38	34.9	1.321	33.6	1.0	.18	1.1	27	1.1	4.8	.30	7.6	0.050	1.3	5.00	SST	C	N
1.421	36.09	4395	2.19	55.6	1.249	31.7	7.0	1.2	1.6	41	11	50	.58	14.7	0.086	2.2	6.75	SPR	CG	Z
1.421	36.09	S-3229	2.50	63.5	1.275	32.4	4.4	.78	2.0	51	9.0	40	.46	11.7	0.073	1.9	5.33	SST	C	N
1.421	36.09	2733	2.50	63.5	1.171	29.7	40	7.1	1.5	39	61	272	.75	19.1	0.125	3.2	6.00	MW	CG	Z
1.421	36.09	1913	2.75	69.9	1.211	30.8	11	1.9	1.8	46	20	88	.95	24.0	0.105	2.7	9.00	SPR	CG	Z
1.421	36.09	3328	2.75	69.9	1.001	25.4	242	42	.75	19	182	807	1.79	45.3	0.210	5.3	8.50	SPR	CG	Z
1.421	36.09	S-3022	3.00	76.2	1.109	28.2	66	12	1.1	27	71	315	1.17	29.7	0.156	4.0	7.50	SST	CG	N
1.421	36.09	11930	3.03	77.0	1.211	30.8	15	2.7	1.8	45	27	120	.74	18.7	0.105	2.7	7.00	SPR	CG	Z
1.421	36.09	4194	4.00	101.6	1.281	32.5	1.3	.22	3.0	77	3.8	17	.98	24.9	0.070	1.8	13.0	SPR	C	Z
1.421	36.09	3141	5.13	130.2	1.261	32.0	2.6	.45	4.1	105	11	47	1.00	25.4	0.080	2.0	11.5	SPR	C	Z
1.421	36.09	12460	12.0	304.8	1.003	25.5	55	9.5	3.3	83	179	796	6.32	160.6	0.209	5.3	30.3	SPR	CG	N
1.421	36.09	4018	27.5	698.5	.921	23.4	60	11	4.8	122	289	1285	15.0	381.0	0.250	6.4	60.0	SPR	CG	N
1.437	36.50	S-1550	.56	14.3	1.237	31.4	70	12	.29	7.3	20	89	.28	7.0	0.100	2.5	2.75	SST	CG	N
1.437	36.50	DD-88	.69	17.4	1.217	30.9	45	7.9	.25	6.3	11	49	.44	11.2	0.110	2.8	4.00	SPR	CG	Z
1.437	36.50	S-3059	.88	22.2	1.281	32.5	12	2.2	.52	13	6.4	29	.35	8.9	0.078	2.0	3.50	SST	C	N
1.437	36.50	12222	1.00	25.4	1.293	32.8	15	2.7	.60	15	9.1	40	.22	5.5	0.072	1.8	3.00	SPR	CG	Z
1.437	36.50	S-151	1.50	38.1	1.347	34.2	.32	.06	1.1	28	.35	1.5	.41	10.3	0.045	1.1	8.00	SST	C	N
1.437	36.50	S-1033	1.50	38.1	1.277	32.4	5.9	1.0	.98	25	5.7	26	.52	13.2	0.080	2.0	5.50	SST	C	N
1.437	36.50	11360	1.50	38.1	1.255	31.9	12	2.1	1.0	27	12	56	.46	11.6	0.091	2.3	5.00	SST	CG	N
1.437	36.50	3071	1.50	38.1	1.173	29.8	56	9.8	.77	20	43	193	.73	18.4	0.132	3.4	5.50	SPR	CG	Z
1.437	36.50	S-944	1.69	42.8	1.237	31.4	26	4.6	.82	21	21	95	.40	10.2	0.100	2.5	4.00	SST	CG	N
1.437	36.50	12487	1.75	44.5	1.317	33.5	1.0	.18	1.2	31	1.3	5.6	.54	13.7	0.060	1.5	8.00	SST	C	N
1.437	36.50	B17-167	1.84	46.8	1.125	28.6	135	24	.58	15	79	351	.78	19.8	0.156	4.0	5.00	SPR	CG	N
1.437	36.50	11531	2.72	69.0	1.013	25.7	234	41	.65	17	152	678	2.07	52.5	0.212	5.4	8.75	SPR	CG	Z
1.437	36.50	3909	2.75	69.9	1.317	33.5	1.8	.31	2.3	59	4.2	18	.42	10.7	0.060	1.5	6.00	SPR	C	Z
1.437	36.50	3288	2.75	69.9	1.017	25.8	275	48	.65	17	180	799	1.58	40.0	0.210	5.3	7.50	SPR	CG	Z
1.437	36.50	12069	2.88	73.0	1.287	32.7	3.0	.53	2.3	58	6.8	30	.60	15.2	0.075	1.9	8.00	SPR	CG	Z
1.437	36.50	3704	3.00	76.2	1.327	33.7	1.2	.22	2.7	68	3.3	15	.33	8.4	0.055	1.4	6.00	SPR	CG	Z
1.437	36.50	2753	3.13	79.4	1.287	32.7	3.0	.53	2.5	64	7.6	34	.60	15.2	0.075	1.9	8.00	HD	CG	Z
1.437	36.50	10719	3.31	84.1	1.335	33.9	.52	.09	2.9	72	1.5	6.6	.46	11.7	0.051	1.3	9.00	SPR	CG	Z
1.437	36.50	3407	3.38	85.7	1.177	29.9	31	5.4	1.5	39	47	210	1.04	26.4	0.130	3.3	8.00	SPR	CG	Z
1.437	36.50	S-303	3.59	91.3	1.277	32.4	2.6	.46	2.8	71	7.3	32	.80	20.3	0.080	2.0	10.0	SST	CG	N
1.437	36.50	10594	3.75	95.3	1.265	32.1	3.2	.56	2.7	69	8.7	39	1.03	26.2	0.086	2.2	12.0	SPR	CG	Z
1.437	36.50	10823	4.00	101.6	1.167	29.6	30	5.2	1.8	45	53	235	1.38	35.1	0.135	3.4	9.25	SPR	C	Z
1.437	36.50	S-369	4.88	123.8	1.137	28.9	37	6.5	1.7	43	63	278	1.50	38.1	0.150	3.8	10.0	SST	CG	N
1.437	36.50	7007	5.63	142.9	1.023	26.0	100	18	1.7	44	172	767	3.60	91.4	0.207	5.3	16.3	HD	C	Z
1.437	36.50	3049	6.88	174.6	1.077	27.4	47	8.3	2.4	62	115	510	3.26	82.9	0.180	4.6	18.0	SPR	CG	Z
1.437	36.50	10454	8.88	225.4	1.187	30.1	13	2.2	3.5	88	43	193	2.02	51.2	0.125	3.2	15.8	SPR	CG	Z
1.437	36.50	4236	14.5	368.3	1.083	27.5	20	3.6	5.6	142	114	509	6.64	168.6	0.177	4.5	36.5	SPR	C	Z
1.437	36.50	4040	20.5	520.7	1.113	28.3	12	2.1	7.4	188	88	392	6.40	162.6	0.162	4.1	40.0	SPR	CG	Z
1.437	36.50	4029	23.0	584.2	1.113	28.3	12	2.1	7.2	183	88	392	6.64	168.7	0.162	4.1	41.0	SPR	CG	Z
1.453	36.91	3299	1.53	38.9	1.227	31.2	49	8.5	.65	17	32	142	.45	11.5	0.113	2.9	4.00	SPR	CG	Z
1.453	36.91	3297	1.75	44.5	1.243	31.6	12	2.1	.91	23	11	48	.84	21.3	0.105	2.7	8.00	HD	CG	Z
1.453	36.91	12297	1.94	49.2	1.323	33.6	3.2	.56	1.6	41	5.2	23	.33	8.3	0.065	1.7	5.00	SPR	CG	Z
1.453	36.91	10339	2.06	52.4	1.233	31.3	35	6.1	.85	21	29	131	.50	12.6	0.110	2.8	4.50	SPR	CG	Z
1.453	36.91	4359	2.06	52.4	1.069	27.2	216	38	.63	16	137	610	1.25	31.7	0.192	4.9	6.50	SPR	CG	Z
1.453	36.91	11791	2.41	61.1	1.203	30.6	37	6.6	1.1	29	43	191	.75	19.1	0.125	3.2	6.00	SPR	CG	Z
1.453	36.91	12616	2.50	63.5	1.203	30.6	37	6.6	1.6	41	60	267	.88	22.2	0.125	3.2	6.00	MW	C	N
1.453	36.91	B11-63	2.84	72.2	1.157	29.4	62	11	1.1	28	69	305	1.04	26.3	0.148	3.8	7.00	SPR	CG	N
1.453	36.91	B17-203	2.88	73.0	1.275	32.4	6.3	1.1	2.3	57	14	63	.62	15.8	0.089	2.3	7.00	SST	CG	N
1.453	36.91	11238	3.00	76.2	1.141	29.0	58	10	1.4	34	78	348	1.37	34.7	0.156	4.0	8.75	SPR	CG	Z
1.453	36.91	12177	3.03	77.0	1.269	32.2	7.8	1.4	2.3	58	18	80	.67	16.9	0.092	2.3	7.25	SPR	CG	GI
1.453	36.91	4026	20.3	514.4	1.123	28.5	12	2.1	7.8	197	92	410	7.26	184.4	0.165	4.2	44.0	SPR	CG	Z
1.453	36.91	4038	21.0	533.4	1.099	27.9	16	2.9	6.9	176	113	503	7.70	195.6	0.177	4.5	43.5	SPR	CG	Z
1.453	36.91	4032	22.5	571.5	1.093	27.8	16	2.7	7.3	185	114	505	8.82	224.0	0.180	4.6	49.0	SPR	CG	Z
1.460	37.08	72784	1.50	38.1	1.236	31.4	41	7.2	1.0	26	42	188	.48	12.1	0.112	2.8	4.25	MW	CG	N
1.460	37.08	72784S	1.50	38.1	1.236	31.4	35	6.1	.80	20	28	125	.48	12.1	0.112	2.8	4.25	SST	CG	N
1.460	37.08	72794	1.50	38.1	1.210	30.7	61	11	.95	24	58	257	.55	13.9	0.125	3.2	4.38	MW	CG	N
1.460	37.08	72794S	1.50	38.1	1.210	30.7	52	9.0	.76	19	39	173	.55	13.9	0.125	3.2	4.38	SST	CG	N
1.460	37.08	72800	1.50	38.1	1.190	30.2	80	14	.89	23	72	319	.61	15.4	0.135	3.4	4.50	MW	CG	N
1.460	37.08	72800S	1.50	38.1	1.190	30.2	68	12	.69	17	47	209	.61	15.4	0.135	3.4	4.50	SST	CG	N
1.460	37.08	72810	1.50	38.1	1.164	29.6	114	20	.82	21	93	412	.68	17.4	0.148	3.8	4.63	MW	CG	N
1.460	37.08	72810S	1.50	38.1	1.164	29.6	97	17	.64	16	62	274	.68	17.4	0.148	3.8	4.63	SST	CG	N
1.460	37.08	72817	1.50	38.1	1.148	29.2	143	25	.76	19	109	485	.72	18.3	0.156	4.0	4.63	MW	CG	N
1.460	37.08	72817S	1.50	38.1	1.148	29.2	122	21	.57	14	69	307	.72	18.3	0.156	4.0	4.63	SST	CG	N
1.460	37.08	72832	1.50																	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.460	37.08	72819S	2.00	50.8	1.148	29.2	86	15	.81	20	69	307	.90	22.8	0.156	4.0	5.75	SST	CG	N
1.460	37.08	72833	2.00	50.8	1.136	28.9	114	20	1.0	26	117	521	.97	24.7	0.162	4.1	6.00	MW	CG	N
1.460	37.08	72833S	2.00	50.8	1.136	28.9	97	17	.80	20	77	343	.97	24.7	0.162	4.1	6.00	SST	CG	N
1.460	37.08	72843	2.00	50.8	1.106	28.1	167	29	.94	24	157	696	1.06	27.0	0.177	4.5	6.00	MW	CG	N
1.460	37.08	72843S	2.00	50.8	1.106	28.1	142	25	.71	18	100	445	1.06	27.0	0.177	4.5	6.00	SST	CG	N
1.460	37.08	72786	2.50	63.5	1.236	31.4	23	4.0	1.8	46	42	188	.67	17.1	0.112	2.8	6.00	MW	CG	N
1.460	37.08	72786S	2.50	63.5	1.236	31.4	20	3.4	1.4	36	28	125	.67	17.1	0.112	2.8	6.00	SST	CG	N
1.460	37.08	72796	2.50	63.5	1.210	30.7	34	5.9	1.7	43	57	255	.80	20.2	0.125	3.2	6.38	MW	CG	N
1.460	37.08	72796S	2.50	63.5	1.210	30.7	29	5.0	1.4	35	39	173	.80	20.2	0.125	3.2	6.38	SST	CG	N
1.460	37.08	72802	2.50	63.5	1.190	30.2	44	7.8	1.6	41	71	316	.89	22.7	0.135	3.4	6.63	MW	CG	N
1.460	37.08	72802S	2.50	63.5	1.190	30.2	38	6.6	1.2	32	47	209	.89	22.7	0.135	3.4	6.63	SST	CG	N
1.460	37.08	72812	2.50	63.5	1.164	29.6	62	11	1.5	38	92	409	1.02	25.8	0.148	3.8	6.88	MW	CG	N
1.460	37.08	72812S	2.50	63.5	1.164	29.6	53	9.2	1.2	30	62	274	1.02	25.8	0.148	3.8	6.88	SST	CG	N
1.460	37.08	72821	2.50	63.5	1.148	29.2	78	14	1.4	36	109	485	1.07	27.2	0.156	4.0	6.88	MW	CG	N
1.460	37.08	72821S	2.50	63.5	1.148	29.2	66	12	1.0	27	69	307	1.07	27.2	0.156	4.0	6.88	SST	CG	N
1.460	37.08	72834	2.50	63.5	1.136	28.9	88	15	1.3	34	118	526	1.15	29.3	0.162	4.1	7.13	MW	CG	N
1.460	37.08	72834S	2.50	63.5	1.136	28.9	75	13	1.0	26	77	343	1.15	29.3	0.162	4.1	7.13	SST	CG	N
1.460	37.08	72845	2.50	63.5	1.106	28.1	128	22	1.2	31	156	693	1.28	32.6	0.177	4.5	7.25	MW	CG	N
1.460	37.08	72845S	2.50	63.5	1.106	28.1	109	19	.92	23	100	445	1.28	32.6	0.177	4.5	7.25	SST	CG	N
1.460	37.08	72856	2.50	63.5	1.086	27.6	168	29	1.1	27	179	795	1.33	33.8	0.187	4.7	7.13	MW	CG	N
1.460	37.08	72856S	2.50	63.5	1.086	27.6	143	25	.76	19	109	484	1.33	33.8	0.187	4.7	7.13	SST	CG	N
1.460	37.08	72787	3.00	76.2	1.236	31.4	19	3.3	2.2	57	42	188	.77	19.6	0.112	2.8	6.88	MW	CG	N
1.460	37.08	72787S	3.00	76.2	1.236	31.4	16	2.8	1.7	44	28	125	.77	19.6	0.112	2.8	6.88	SST	CG	N
1.460	37.08	72797	3.00	76.2	1.210	30.7	28	4.8	2.1	53	57	255	.92	23.4	0.125	3.2	7.38	MW	CG	N
1.460	37.08	72797S	3.00	76.2	1.210	30.7	23	4.1	1.7	42	39	173	.92	23.4	0.125	3.2	7.38	SST	CG	N
1.460	37.08	72803	3.00	76.2	1.190	30.2	36	6.3	2.0	50	71	317	1.03	26.1	0.135	3.4	7.63	MW	CG	N
1.460	37.08	72803S	3.00	76.2	1.190	30.2	31	5.4	1.5	39	47	209	1.03	26.1	0.135	3.4	7.63	SST	CG	N
1.460	37.08	72813	3.00	76.2	1.164	29.6	51	8.9	1.8	46	92	409	1.18	30.1	0.148	3.8	8.00	MW	CG	N
1.460	37.08	72813S	3.00	76.2	1.164	29.6	43	7.5	1.4	36	62	274	1.18	30.1	0.148	3.8	8.00	SST	CG	N
1.460	37.08	72823	3.00	76.2	1.148	29.2	63	11	1.7	44	109	485	1.25	31.7	0.156	4.0	8.00	MW	CG	N
1.460	37.08	72823S	3.00	76.2	1.148	29.2	54	9.4	1.3	33	69	307	1.25	31.7	0.156	4.0	8.00	SST	CG	N
1.460	37.08	72835	3.00	76.2	1.136	28.9	71	13	1.6	42	117	522	1.36	34.5	0.162	4.1	8.38	MW	CG	N
1.460	37.08	72835S	3.00	76.2	1.136	28.9	61	11	1.3	32	77	343	1.36	34.5	0.162	4.1	8.38	SST	CG	N
1.460	37.08	72847	3.00	76.2	1.106	28.1	104	18	1.5	39	158	701	1.48	37.7	0.177	4.5	8.38	MW	CG	N
1.460	37.08	72847S	3.00	76.2	1.106	28.1	88	15	1.1	29	100	445	1.48	37.7	0.177	4.5	8.38	SST	CG	N
1.460	37.08	72857	3.00	76.2	1.086	27.6	138	24	1.3	33	179	795	1.52	38.6	0.187	4.7	8.13	MW	CG	N
1.460	37.08	72857S	3.00	76.2	1.086	27.6	117	21	.93	24	109	484	1.52	38.6	0.187	4.7	8.13	SST	CG	N
1.460	37.08	72788	3.50	88.9	1.236	31.4	16	2.8	2.6	67	42	188	.87	22.0	0.112	2.8	7.75	MW	CG	N
1.460	37.08	72788S	3.50	88.9	1.236	31.4	14	2.4	2.1	52	28	125	.87	22.0	0.112	2.8	7.75	SST	CG	N
1.460	37.08	72798	3.50	88.9	1.210	30.7	23	4.1	2.5	62	57	254	1.05	26.6	0.125	3.2	8.38	MW	CG	N
1.460	37.08	72798S	3.50	88.9	1.210	30.7	20	3.5	2.0	50	39	173	1.05	26.6	0.125	3.2	8.38	SST	CG	N
1.460	37.08	72804	3.50	88.9	1.190	30.2	31	5.4	2.3	59	71	316	1.18	30.0	0.135	3.4	8.75	MW	CG	N
1.460	37.08	72804S	3.50	88.9	1.190	30.2	26	4.6	1.8	46	47	209	1.18	30.0	0.135	3.4	8.75	SST	CG	N
1.460	37.08	72814	3.50	88.9	1.164	29.6	43	7.5	2.1	55	92	408	1.35	34.3	0.148	3.8	9.13	MW	CG	N
1.460	37.08	72814S	3.50	88.9	1.164	29.6	36	6.4	1.7	43	62	274	1.35	34.3	0.148	3.8	9.13	SST	CG	N
1.460	37.08	72825	3.50	88.9	1.148	29.2	53	9.4	2.0	52	109	485	1.44	36.7	0.156	4.0	9.25	MW	CG	N
1.460	37.08	72825S	3.50	88.9	1.148	29.2	45	7.9	1.5	39	69	307	1.44	36.7	0.156	4.0	9.25	SST	CG	N
1.460	37.08	72836	3.50	88.9	1.136	28.9	60	11	2.0	50	118	524	1.54	39.1	0.162	4.1	9.50	MW	CG	N
1.460	37.08	72836S	3.50	88.9	1.136	28.9	51	8.9	1.5	38	77	343	1.54	39.1	0.162	4.1	9.50	SST	CG	N
1.460	37.08	72849	3.50	88.9	1.106	28.1	87	15	1.8	46	157	698	1.70	43.3	0.177	4.5	9.63	MW	CG	N
1.460	37.08	72849S	3.50	88.9	1.106	28.1	74	13	1.3	34	100	445	1.70	43.3	0.177	4.5	9.63	SST	CG	N
1.460	37.08	72858	3.50	88.9	1.086	27.6	116	20	1.5	39	179	795	1.75	44.5	0.187	4.7	9.38	MW	CG	N
1.460	37.08	72858S	3.50	88.9	1.086	27.6	99	17	1.1	28	109	484	1.75	44.5	0.187	4.7	9.38	SST	CG	N
1.460	37.08	72789	4.00	101.6	1.236	31.4	14	2.4	3.0	77	42	188	.97	24.5	0.112	2.8	8.63	MW	CG	N
1.460	37.08	72789S	4.00	101.6	1.236	31.4	12	2.1	2.4	61	28	125	.97	24.5	0.112	2.8	8.63	SST	CG	N
1.460	37.08	72799	4.00	101.6	1.210	30.7	20	3.5	2.8	72	57	256	1.16	29.4	0.125	3.2	9.25	MW	CG	N
1.460	37.08	72799S	4.00	101.6	1.210	30.7	17	3.0	2.3	58	39	173	1.16	29.4	0.125	3.2	9.25	SST	CG	N
1.460	37.08	72805	4.00	101.6	1.190	30.2	27	4.6	2.7	68	71	316	1.32	33.4	0.135	3.4	9.75	MW	CG	N
1.460	37.08	72805S	4.00	101.6	1.190	30.2	23	3.9	2.1	53	47	209	1.32	33.4	0.135	3.4	9.75	SST	CG	N
1.460	37.08	72815	4.00	101.6	1.164	29.6	37	6.5	2.5	63	92	409	1.52	38.5	0.148	3.8	10.3	MW	CG	N
1.460	37.08	72815S	4.00	101.6	1.164	29.6	31	5.5	2.0	50	62	274	1.52	38.5	0.148	3.8	10.3	SST	CG	N
1.460	37.08	72827	4.00	101.6	1.148	29.2	46	8.1	2.4	60	109	485	1.60	40.6	0.156	4.0	10.3	MW	CG	N
1.460	37.08	72827S	4.00	101.6	1.148	29.2	39	6.9	1.8	45	69	307	1.60	40.6	0.156	4.0	10.3	SST	CG	N
1.460	37.08	72837	4.00	101.6	1.136	28.9	52	9.1	2.3	57	117	522	1.74	44.2	0.162	4.1	10.8	MW	CG	N
1.460	37.08	72837S	4.00	101.6	1.136	28.9	44	7.7	1.7	44	77	343	1.74	44.2	0.162	4.1	10.8	SST	CG	N
1.460	37.08	72851	4.00	101.6	1.106	28.1	75	13	2.1	53	156	695	1.92	48.9	0.177	4.5	10.9	MW	CG	N
1.460	37.08	72851S	4.00	101.6	1.106	28.1	64	11	1.6	40	100									

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH		
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm						
1.460	37.08	72853S	4.50	114.3	1.106	28.1	56	9.9	1.8	45	100	445	2.15	54.5	0.177	4.5	12.1	SST	CG	N		
1.460	37.08	72861	4.50	114.3	1.086	27.6	86	15	2.1	53	179	795	2.22	56.4	0.187	4.7	11.9	MW	CG	N		
1.460	37.08	72861S	4.50	114.3	1.086	27.6	73	13	1.5	38	109	484	2.22	56.4	0.187	4.7	11.9	SST	CG	N		
1.460	37.08	72793	5.00	127.0	1.236	31.4	13	2.2	3.4	88	43	192	1.05	26.7	0.112	2.8	9.38	MW	CG	N		
1.460	37.08	72793S	5.00	127.0	1.236	31.4	11	1.9	2.7	67	28	125	1.05	26.7	0.112	2.8	9.38	SST	CG	N		
1.460	37.08	72809	5.00	127.0	1.190	30.2	21	3.7	3.4	87	73	324	1.57	39.9	0.135	3.4	11.6	MW	CG	N		
1.460	37.08	72809S	5.00	127.0	1.190	30.2	18	3.2	2.6	66	47	209	1.57	39.9	0.135	3.4	11.6	SST	CG	N		
1.460	37.08	72831	5.00	127.0	1.148	29.2	36	6.4	3.0	76	109	485	1.97	50.0	0.156	4.0	12.6	MW	CG	N		
1.460	37.08	72831S	5.00	127.0	1.148	29.2	31	5.4	2.2	57	69	307	1.97	50.0	0.156	4.0	12.6	SST	CG	N		
1.460	37.08	72839	5.00	127.0	1.136	28.9	41	7.1	2.9	73	117	522	2.13	54.0	0.162	4.1	13.1	MW	CG	N		
1.460	37.08	72839S	5.00	127.0	1.136	28.9	35	6.1	2.2	57	77	343	2.13	54.0	0.162	4.1	13.1	SST	CG	N		
1.460	37.08	72855	5.00	127.0	1.106	28.1	59	10	2.7	67	157	698	2.35	59.6	0.177	4.5	13.3	MW	CG	N		
1.460	37.08	72855S	5.00	127.0	1.106	28.1	50	8.8	2.0	51	100	445	2.35	59.6	0.177	4.5	13.3	SST	CG	N		
1.460	37.08	72862	5.00	127.0	1.086	27.6	77	13	2.3	59	179	795	2.45	62.3	0.187	4.7	13.1	MW	CG	N		
1.460	37.08	72862S	5.00	127.0	1.086	27.6	65	11	1.7	42	109	484	2.45	62.3	0.187	4.7	13.1	SST	CG	N		
1.460	37.08	72863	5.25	133.4	1.086	27.6	73	13	2.4	62	179	795	2.55	64.7	0.187	4.7	13.6	MW	CG	N		
1.460	37.08	72863S	5.25	133.4	1.086	27.6	62	11	1.8	45	109	484	2.55	64.7	0.187	4.7	13.6	SST	CG	N		
1.468	37.29	S-3052	.69	17.4	1.410	35.8		.30	.05	.57	15		.17	.75	.12	2.9	0.029	0.7	3.00	SST	C	N
1.468	37.29	1853	1.00	25.4	1.198	30.4	134	24	.39	9.8	52	231	.47	12.0	0.135	3.4	3.50	SPR	CG	Z		
1.468	37.29	3496	1.31	33.3	1.258	32.0	28	4.8	.84	21	23	103	.47	12.0	0.105	2.7	4.50	SPR	CG	Z		
1.468	37.29	3456	1.31	33.3	1.018	25.9	959	168	.22	5.5	207	922	.90	22.9	0.225	5.7	4.00	SPR	CG	Z		
1.468	37.29	11426	1.50	38.1	1.054	26.8	389	68	.37	9.5	146	648	1.04	26.3	0.207	5.3	5.00	SST	CG	N		
1.468	37.29	S-1669	1.56	39.7	1.308	33.2	13	2.3	.88	22	11	51	.28	7.1	0.080	2.0	3.50	SST	CG	N		
1.468	37.29	S-1358	1.75	44.5	1.268	32.2	24	4.3	.86	22	21	93	.40	10.2	0.100	2.5	4.00	SST	CG	N		
1.468	37.29	S-1443	1.84	46.8	1.054	26.8	327	57	.45	11	146	648	1.14	28.9	0.207	5.3	5.50	SST	CG	N		
1.468	37.29	S-3192	2.00	50.8	1.272	32.3	18	3.2	1.1	27	20	88	.44	11.2	0.098	2.5	4.50	SST	CG	N		
1.468	37.29	S-1632	2.06	52.4	1.094	27.8	212	37	.51	13	108	482	1.03	26.2	0.187	4.7	5.50	SST	CG	N		
1.468	37.29	11881	2.13	54.0	1.230	31.2	39	6.9	.94	24	37	163	.60	15.1	0.119	3.0	5.00	SPR	CG	N		
1.468	37.29	S-987	2.13	54.0	1.226	31.1	35	6.2	1.0	25	35	157	.60	15.2	0.121	3.1	5.00	SST	CG	N		
1.468	37.29	10336	2.19	55.6	.718	18.2	7917	1386	.10	2.6	799	3554	1.78	45.2	0.375	9.5	4.75	SPR	CG	Z		
1.468	37.29	10368	2.25	57.2	1.084	27.5	235	41	.58	15	136	604	1.15	29.3	0.192	4.9	6.00	SPR	CG	Z		
1.468	37.29	10317	2.38	60.3	1.068	27.1	215	38	.71	18	153	680	1.45	36.8	0.200	5.1	7.25	SPR	CG	Z		
1.468	37.29	1743	2.41	61.1	1.304	33.1		4.9	.85	1.8	44	38	.66	16.7	0.082	2.1	7.00	HD	C	Z		
1.468	37.29	S-1595	2.44	61.9	1.258	32.0		7.9	1.4	1.3	33	10	46	1.13	28.7	0.105	2.7	9.75	SST	CG	N	
1.468	37.29	10048	2.44	61.9	1.054	26.8	251	44	.67	17	169	752	1.50	38.1	0.207	5.3	7.25	SPR	CG	Z		
1.468	37.29	S-3057	2.50	63.5	1.284	32.6	11	2.0	1.4	36	16	73	.55	14.0	0.092	2.3	5.00	SST	C	N		
1.468	37.29	10204	2.50	63.5	1.084	27.5	235	41	.58	15	136	604	1.15	29.3	0.192	4.9	6.00	SPR	CG	Z		
1.468	37.29	10371	2.53	64.3	1.068	27.1	215	38	.71	18	153	680	1.45	36.8	0.200	5.1	7.25	SPR	CG	Z		
1.468	37.29	S-3165	2.69	68.2	1.258	32.0	12	2.1	2.0	50	23	104	.74	18.7	0.105	2.7	7.00	SST	CG	N		
1.468	37.29	11496	2.75	69.9	1.048	26.6	234	41	.75	19	176	784	1.89	48.0	0.210	5.3	8.00	SPR	CG	Z		
1.468	37.29	S-3222	3.00	76.2	1.172	29.8	53	9.3	1.2	29	61	272	1.04	26.3	0.148	3.8	7.00	SST	CG	N		
1.468	37.29	B17-200	3.28	83.3	1.232	31.3	17	2.9	2.0	50	33	145	.94	24.0	0.118	3.0	8.00	SST	CG	N		
1.468	37.29	S-1598	3.50	88.9	1.310	33.3		2.3	.41	2.6	67	6.1	27	.87	22.1	0.079	2.0	10.0	SST	CG	N	
1.468	37.29	S-3066	3.63	92.1	1.298	33.0		5.5	.96	2.5	63	14	61	.55	14.0	0.085	2.2	6.50	SST	CG	N	
1.468	37.29	S-3184	4.50	114.3	1.268	32.2		7.5	1.3	2.8	71	21	93	.85	21.6	0.100	2.5	8.50	SST	CG	N	
1.468	37.29	12270	4.59	116.7	1.298	33.0		3.5	.62	3.7	95	13	59	.85	21.6	0.085	2.2	10.0	SPR	CG	Z	
1.468	37.29	12440	4.81	122.2	1.032	26.2	148	26	1.3	34	196	874	2.89	73.4	0.218	5.5	13.3	SPR	CG	Z		
1.468	37.29	S-970	5.13	130.2	1.240	31.5		8.8	1.5	3.4	85	30	131	1.33	33.8	0.114	2.9	11.7	SST	CG	N	
1.468	37.29	S-3216	5.25	133.4	1.310	33.3		1.6	.28	4.2	106	6.7	30	1.07	27.1	0.079	2.0	13.5	SST	CG	N	
1.468	37.29	10388	5.75	146.1	1.030	26.2	148	26	1.3	34	199	886	2.96	75.1	0.219	5.6	13.5	SPR	CG	Z		
1.468	37.29	11172	6.00	152.4	1.028	26.1	161	28	1.2	31	194	864	3.03	76.8	0.220	5.6	12.8	SPR	C	Z		
1.484	37.69	S-1603	1.53	38.9	1.072	27.2	367	64	.30	7.5	108	481	1.24	31.4	0.206	5.2	5.00	SST	CG	N		
1.484	37.69	S-383	3.25	82.6	1.274	32.4	13	2.3	1.9	47	24	107	.68	17.3	0.105	2.7	6.50	SST	CG	N		
1.484	37.69	3023	3.38	85.7	1.172	29.8	61	11	1.3	32	77	341	1.25	31.7	0.156	4.0	8.00	SPR	CG	Z		
1.484	37.69	S-1655	3.75	95.3	1.070	27.2	125	22	1.2	29	144	641	2.28	57.8	0.207	5.3	11.0	SST	CG	N		
1.484	37.69	12412	5.00	127.0	1.380	35.1		.80	.14	4.4	112	3.5	16	.39	9.9	0.052	1.3	6.50	SPR	C	Z	
1.484	37.69	1735	9.00	228.6	1.160	29.5	20	3.6	4.2	107	86	381	3.73	94.6	0.162	4.1	23.0	SPR	CG	Z		
1.500	38.10	11898	.84	21.4	1.230	31.2	125	22	.37	9.3	46	203	.45	11.4	0.135	3.4	3.33	SST	CG	N		
1.500	38.10	3804	1.25	31.8	1.290	32.8	32	5.6	.80	20	26	114	.42	10.7	0.105	2.7	4.00	SPR	CG	Z		
1.500	38.10	12635	1.56	39.7	1.184	30.1	185	32	.60	15	110	491	.79	20.1	0.158	4.0	4.00	MW	C	N		
1.500	38.10	S-1197	1.75	44.5	1.380	35.1		2.0	.35	1.4	36	12	.35	8.8	0.060	1.5	4.75	SST	C	N		
1.500	38.10	S-3032	1.75	44.5	1.374	34.9		2.5	.44	1.4	36	3.5	16	.34	8.7	0.063	1.6	4.50	SST	C	N	
1.500	38.10	11471	1.75	44.5	1.340	34.0		6.3	1.1	1.3	34	8.4	37	.42	10.7	0.080	2.0	5.25	HD	CG	Z	
1.500	38.10	12544	1.75	44.5	1.188	30.2	140	25	.61	15	85	380	.86	21.8	0.156	4.0	4.50	OT	C	N		
1.500	38.10	10405	1.94	49.2	1.274	32.4	27	4.7	1.1	29	31	137	.59	15.1	0.113	2.9	5.25	SPR	CG	N		
1.500	38.10	3647	2.06	52.4	1.376	35.0		2.4	.42	1.7	43	4.0	18	.37	9.4	0.062	1.6	5.00	SPR	C	Z	
1.500	38.10	10145	2.13	54.0	1.086	27.6	376	66	.44	11	166	737										




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.500	38.10	3015	3.06	77.8	1.220	31.0	40	7.0	1.4	36	57	251	1.05	26.7	0.140	3.6	7.50	SPR	CG	Z
1.500	38.10	S-329	3.25	82.6	1.404	35.7	.29	.05	2.7	70	.79	3.5	.50	12.8	0.048	1.2	9.50	SST	C	N
1.500	38.10	531	3.25	82.6	1.204	30.6	43	7.5	1.6	39	67	296	1.26	32.0	0.148	3.8	8.50	HD	CG	Z
1.500	38.10	S-1602	3.31	84.1	1.340	34.0	2.8	.49	2.6	65	7.2	32	.76	19.3	0.080	2.0	8.50	SST	CG	N
1.500	38.10	B18-174	3.31	84.1	1.050	26.7	245	43	.83	21	203	905	2.08	52.9	0.225	5.7	9.25	SPR	CG	N
1.500	38.10	10372	3.63	92.1	1.064	27.0	193	34	1.0	25	193	857	2.18	55.4	0.218	5.5	10.0	SPR	CG	Z
1.500	38.10	11970	3.75	95.3	1.174	29.8	71	12	1.2	31	86	384	1.30	33.1	0.163	4.1	8.00	SPR	CG	Z
1.500	38.10	S-3230	3.78	96.0	1.086	27.6	120	21	1.2	30	143	635	2.28	57.8	0.207	5.3	11.0	SST	CG	N
1.500	38.10	S-1327	4.00	101.6	1.392	35.4	.56	.10	3.5	89	2.0	8.8	.50	12.7	0.054	1.4	8.25	SST	C	N
1.500	38.10	S-1649	4.00	101.6	1.240	31.5	17	2.9	2.5	62	41	182	1.37	34.7	0.130	3.3	10.5	SST	CG	N
1.500	38.10	32	4.00	101.6	1.230	31.2	24	4.2	2.1	53	51	226	1.32	33.4	0.135	3.4	9.75	HD	CG	Z
1.500	38.10	11514	4.16	105.6	1.282	32.6	11	1.9	2.7	68	29	128	1.09	27.7	0.109	2.8	9.00	SPR	CG	Z
1.500	38.10	3380	4.25	108.0	1.286	32.7	10	1.7	2.7	69	27	121	1.07	27.2	0.107	2.7	9.00	SPR	C	Z
1.500	38.10	S-3167	4.50	114.3	1.300	33.0	7.3	1.3	2.8	72	21	92	.83	21.0	0.100	2.5	8.25	SST	CG	N
1.500	38.10	11976	4.50	114.3	1.260	32.0	22	3.8	1.7	43	37	164	.87	22.1	0.120	3.0	7.25	SPR	CG	Z
1.500	38.10	4259	4.50	114.3	1.012	25.7	321	56	.80	20	257	1143	2.44	62.0	0.244	6.2	10.0	SPR	CG	Z
1.500	38.10	3135	4.56	115.9	1.300	33.0	8.3	1.4	2.7	68	22	99	.83	21.2	0.100	2.5	8.33	SPR	CG	Z
1.500	38.10	12042	4.59	116.7	1.250	31.8	16	2.8	2.6	67	42	185	1.31	33.3	0.125	3.2	10.5	SPR	CG	Z
1.500	38.10	2847	4.88	123.8	1.176	29.9	57	10	1.5	38	85	377	1.50	38.1	0.162	4.1	9.25	SPR	CG	Z
1.500	38.10	7058	5.00	127.0	1.032	26.2	161	28	1.2	30	192	853	3.39	86.2	0.234	5.9	13.5	SST	C	N
1.500	38.10	S-467	5.13	130.2	1.250	31.8	9.8	1.7	3.4	86	33	147	1.75	44.5	0.125	3.2	14.0	SST	CG	N
1.500	38.10	7009	5.88	149.2	1.050	26.7	125	22	1.6	41	203	905	3.90	99.1	0.225	5.7	16.3	HD	C	Z
1.500	38.10	3440	6.00	152.4	1.290	32.8	4.0	.70	4.1	104	17	74	1.89	48.0	0.105	2.7	18.0	SPR	CG	Z
1.500	38.10	3378	6.75	171.5	1.070	27.2	90	16	2.0	52	185	823	3.87	98.3	0.215	5.5	18.0	SPR	CG	Z
1.500	38.10	S-985	6.88	174.6	1.250	31.8	9.0	1.6	4.2	107	38	169	1.88	47.6	0.125	3.2	15.0	SST	CG	N
1.500	38.10	846	8.00	203.2	1.146	29.1	31	5.5	3.5	89	110	489	3.81	96.7	0.177	4.5	21.5	HD	CG	Z
1.500	38.10	12152	8.63	219.1	1.156	29.4	27	4.7	3.8	96	101	449	3.78	96.1	0.172	4.4	22.0	SPR	CG	Z
1.500	38.10	4222	10.0	254.0	1.290	32.8	2.9	.50	7.4	189	21	95	2.57	65.3	0.105	2.7	24.5	SPR	CG	Z
1.500	38.10	10256	10.0	254.0	1.116	28.3	49	8.6	2.7	69	133	592	3.98	101.2	0.192	4.9	19.8	SPR	C	GI
1.500	38.10	863	12.0	304.8	1.230	31.2	7.5	1.3	6.8	172	51	226	3.65	92.6	0.135	3.4	27.0	HD	CG	Z
1.500	38.10	532	12.0	304.8	1.204	30.6	11	1.8	6.3	161	67	296	4.37	110.9	0.148	3.8	28.5	HD	C	Z
1.500	38.10	851	12.0	304.8	1.176	29.9	17	2.9	5.1	130	85	377	4.54	115.2	0.162	4.1	27.0	HD	C	Z
1.500	38.10	842	12.0	304.8	1.116	28.3	29	5.0	4.7	118	133	592	6.24	158.5	0.192	4.9	32.5	HD	CG	Z
1.500	38.10	804	12.0	304.8	1.086	27.6	39	6.9	4.2	107	166	737	6.83	173.5	0.207	5.3	33.0	HD	CG	Z
1.500	38.10	835	12.0	304.8	1.050	26.7	57	9.9	3.6	91	203	905	7.50	190.5	0.225	5.7	33.3	HD	CG	Z
1.515	38.48	12679	1.50	38.1	1.203	30.6	151	26	.50	13	75	334	.82	20.8	0.156	4.0	4.25	SPR	C	N
1.515	38.48	S-989	1.91	48.4	1.135	28.8	204	36	.54	14	110	490	1.05	26.5	0.190	4.8	5.50	SST	CG	N
1.515	38.48	S-288	2.13	54.0	1.371	34.8	2.5	.44	1.7	42	4.1	18	.47	11.9	0.072	1.8	6.50	SST	CG	N
1.515	38.48	11872	2.16	54.8	1.141	29.0	214	38	.57	14	122	543	1.03	26.1	0.187	4.7	5.50	SPR	CG	N
1.515	38.48	11178	2.31	58.7	1.099	27.9	344	60	.48	12	167	741	1.14	29.1	0.208	5.3	5.50	SPR	CG	Z
1.515	38.48	2923	2.50	63.5	1.245	31.6	28	5.0	1.2	30	34	150	1.31	33.2	0.135	3.4	8.67	SPR	C	Z
1.515	38.48	2775	2.50	63.5	1.227	31.2	37	6.5	1.1	29	42	186	1.37	34.7	0.144	3.7	8.50	SPR	C	Z
1.515	38.48	11116	2.50	63.5	1.141	29.0	214	38	.57	14	122	543	1.03	26.1	0.187	4.7	5.50	SPR	CG	N
1.515	38.48	1519	2.75	69.9	1.075	27.3	282	49	.67	17	189	840	1.65	41.9	0.220	5.6	7.50	SPR	CG	Z
1.515	38.48	S-3092	3.00	76.2	1.279	32.5	12	2.1	1.8	45	21	93	1.24	31.5	0.118	3.0	9.50	SST	C	N
1.515	38.48	S-109	3.00	76.2	1.015	25.8	322	56	.63	16	201	894	2.38	60.3	0.250	6.4	9.50	SST	CG	N
1.515	38.48	2706	4.84	123.0	1.191	30.3	57	10	1.5	37	84	373	1.46	37.0	0.162	4.1	9.00	SPR	CG	Z
1.515	38.48	3323	6.75	171.5	1.105	28.1	71	12	2.3	57	160	710	3.69	93.7	0.205	5.2	18.0	SPR	CG	Z
1.515	38.48	3418	6.75	171.5	1.075	27.3	97	17	1.9	50	189	840	3.96	100.6	0.220	5.6	18.0	SPR	CG	Z
1.515	38.48	3414	8.50	215.9	1.065	27.1	86	15	2.3	60	202	897	4.95	125.7	0.225	5.7	22.0	SPR	CG	Z
1.531	38.89	11262	1.19	30.2	1.247	31.7	77	14	.55	14	42	189	.64	16.2	0.142	3.6	4.50	SST	CG	N
1.531	38.89	11155	1.25	31.8	1.247	31.7	97	17	.60	15	58	257	.60	15.3	0.142	3.6	4.25	SPR	CG	Z
1.531	38.89	S-1648	1.41	35.7	1.321	33.6	21	3.7	.93	24	20	89	.47	12.0	0.105	2.7	4.50	SST	CG	N
1.531	38.89	1675	1.50	38.1	1.399	35.5	3.3	.57	1.1	29	3.7	16	.37	9.5	0.066	1.7	4.67	SPR	C	Z
1.531	38.89	10648	1.63	41.3	1.371	34.8	6.4	1.1	1.2	31	7.9	35	.40	10.2	0.080	2.0	5.00	SPR	CG	Z
1.531	38.89	S-85	2.00	50.8	1.387	35.2	3.9	.69	1.6	40	6.2	28	.41	10.5	0.072	1.8	4.75	SST	C	N
1.531	38.89	S-405	2.00	50.8	1.147	29.1	202	35	.56	14	113	501	1.06	26.8	0.192	4.9	5.50	SST	CG	N
1.531	38.89	11152	2.19	55.6	1.091	27.7	498	87	.38	9.5	187	832	1.10	27.9	0.220	5.6	5.00	SPR	CG	Z
1.531	38.89	4397	2.22	56.4	1.321	33.6	13	2.2	1.5	38	19	85	.71	18.0	0.105	2.7	6.75	SPR	CG	N
1.531	38.89	10391	2.25	57.2	1.105	28.1	431	75	.41	10	177	787	1.07	27.1	0.213	5.4	5.00	SPR	CG	Z
1.531	38.89	10319	2.44	61.9	1.117	28.4	284	50	.57	15	163	724	1.24	31.5	0.207	5.3	6.00	SPR	CG	Z
1.531	38.89	10835	3.00	76.2	1.305	33.1	17	3.0	1.6	41	28	123	.71	17.9	0.113	2.9	6.25	SST	CG	N
1.531	38.89	4242	3.00	76.2	1.207	30.7	110	19	.75	19	83	370	.89	22.6	0.162	4.1	5.50	SPR	CG	Z
1.531	38.89	S-3111	3.38	85.7	1.321	33.6	12	2.0	2.0	51	23	104	.68	17.3	0.105	2.7	6.50	SST	CG	N
1.531	38.89	4115	4.25	108.0	.907	23.0	1003	176	.48	12	478	2128	2.96	75.3	0.312	7.9	9.50	SPR	CG	Z
1.531	38.89	S-449	6.50	165.1	1.147	29.1	46	8.0	2.5	63	113	501	3.36	85.3	0.192	4.9	17.5	SST	CG	N
1.546	39.27	10324	1.25	31.8	1.276	32.4	113	20	.44	11	49	219	.47	12.0	0.13					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.562	39.67	12057	1.06	27.0	1.322	33.6	66	12	.54	14	35	158	.42	10.7	0.120	3.0	3.50	SPR	CG	Z
1.562	39.67	11154	1.13	28.6	1.266	32.2	122	21	.53	13	64	285	.59	15.0	0.148	3.8	4.00	SPR	CG	Z
1.562	39.67	10428	1.19	30.2	1.266	32.2	108	19	.56	14	61	270	.63	16.0	0.148	3.8	4.25	SPR	CG	Z
1.562	39.67	10318	1.25	31.8	1.250	31.8	175	31	.42	11	73	325	.59	14.9	0.156	4.0	3.75	SPR	CG	Z
1.562	39.67	10131	1.28	32.5	1.250	31.8	153	27	.48	12	73	325	.62	15.8	0.156	4.0	4.00	SPR	CG	Z
1.562	39.67	3348	1.38	34.9	1.418	36.0	9.3	1.6	.90	23	8.4	37	.31	7.8	0.072	1.8	3.25	HD	C	Z
1.562	39.67	3355	1.88	47.6	1.312	33.3	47	8.3	.85	21	40	178	.56	14.3	0.125	3.2	4.50	HD	CG	Z
1.562	39.67	10333	2.00	50.8	1.148	29.2	250	44	.64	16	160	711	1.29	32.9	0.207	5.3	6.25	SPR	CG	Z
1.562	39.67	3701	2.38	60.3	1.444	36.7	1.5	.26	2.1	52	3.0	13	.32	8.2	0.059	1.5	5.50	SPR	CG	Z
1.562	39.67	11170	2.56	65.1	1.188	30.2	169	30	.70	18	119	528	1.12	28.5	0.187	4.7	6.00	SPR	CG	Z
1.562	39.67	11177	2.56	65.1	1.188	30.2	225	39	.53	13	119	528	.94	23.7	0.187	4.7	5.00	SPR	CG	Z
1.562	39.67	11996	2.63	66.7	.876	22.3	2312	405	.26	6.6	599	2665	2.32	58.8	0.343	8.7	6.75	SPR	CG	Z
1.562	39.67	852	2.75	69.9	1.238	31.4	69	12	1.2	30	82	363	1.17	29.8	0.162	4.1	7.25	HD	CG	Z
1.562	39.67	S-314	3.16	80.2	1.436	36.5	2.1	.37	2.6	66	5.6	25	.36	9.2	0.063	1.6	4.75	SST	C	N
1.562	39.67	4346	3.63	92.1	1.178	29.9	76	13	1.3	34	100	446	2.30	58.5	0.192	4.9	12.0	SPR	CG	Z
1.562	39.67	895	4.00	101.6	.996	25.3	497	87	.74	19	367	1633	3.08	78.2	0.283	7.2	11.0	HD	CG	Z
1.562	39.67	812	4.25	108.0	1.208	30.7	57	10	1.9	47	106	471	2.01	51.0	0.177	4.5	11.3	HD	CG	Z
1.562	39.67	678	4.38	111.1	1.076	27.3	213	37	1.2	29	245	1090	2.98	75.6	0.243	6.2	12.3	HD	CG	Z
1.562	39.67	11669	4.84	123.0	1.478	37.5	.07	.01	4.0	103	.30	1.3	.80	20.3	0.042	1.1	19.0	SPR	CG	N
1.562	39.67	3244	5.00	127.0	1.202	30.5	54	9.5	2.0	50	106	472	2.25	57.2	0.180	4.6	12.5	SPR	CG	Z
1.562	39.67	10570	5.00	127.0	1.108	28.1	153	27	1.3	33	201	895	3.07	77.9	0.227	5.8	12.5	SPR	C	Z
1.562	39.67	S-3110	5.50	139.7	1.380	35.1	4.7	.82	3.2	81	15	67	.71	17.9	0.091	2.3	7.75	SST	CG	N
1.562	39.67	11509	6.41	162.7	1.260	32.0	20	3.5	3.3	84	66	295	2.47	62.6	0.151	3.8	15.3	SPR	CG	Z
1.562	39.67	911	7.50	190.5	1.266	32.2	15	2.6	4.3	110	64	285	2.74	69.5	0.148	3.8	18.5	HD	CG	Z
1.562	39.67	2735	11.4	290.5	1.362	34.6	2.9	.51	7.3	186	21	95	1.78	45.1	0.100	2.5	17.8	SPR	CG	Z
1.578	40.08	12276	1.00	25.4	1.496	38.0	.37	.07	.75	19	.28	1.3	.25	6.2	0.041	1.0	5.00	SPR	C	Z
1.578	40.08	11148	1.25	31.8	1.266	32.2	169	30	.43	11	72	322	.59	14.9	0.156	4.0	3.75	SPR	CG	Z
1.578	40.08	3358	1.31	33.3	1.204	30.6	435	76	.27	6.9	118	523	.65	16.6	0.187	4.7	3.50	SPR	CG	Z
1.578	40.08	10349	1.56	39.7	1.368	34.7	14	2.4	.93	24	13	57	.63	16.0	0.105	2.7	6.00	SPR	CG	Z
1.578	40.08	S-162	1.63	41.3	1.426	36.2	2.9	.51	1.2	29	3.3	15	.48	12.1	0.076	1.9	6.25	SST	CG	N
1.578	40.08	S-3227	1.72	43.6	1.394	35.4	5.6	.97	1.1	27	6.0	27	.64	16.4	0.092	2.3	7.00	SST	CG	N
1.578	40.08	11774	2.38	60.3	1.462	37.1	1.9	.32	2.1	54	3.9	17	.26	6.6	0.058	1.5	4.50	SPR	CG	Z
1.578	40.08	10329	2.44	61.9	1.164	29.6	241	42	.66	17	158	704	1.29	32.9	0.207	5.3	6.25	SPR	CG	Z
1.578	40.08	11629	2.50	63.5	1.338	34.0	14	2.4	1.4	36	20	87	1.08	27.4	0.120	3.0	9.00	SPR	CG	Z
1.578	40.08	S-3189	3.00	76.2	1.308	33.2	28	4.8	1.6	40	44	194	.95	24.0	0.135	3.4	7.00	SST	CG	N
1.578	40.08	10689	3.38	85.7	1.458	37.0	.74	.13	2.8	70	2.0	9.0	.62	15.6	0.060	1.5	9.25	SPR	C	Z
1.578	40.08	3486	3.75	95.3	1.328	33.7	16	2.9	2.4	62	40	176	1.13	28.6	0.125	3.2	9.00	HD	CG	Z
1.578	40.08	S-298	4.16	105.6	1.404	35.7	4.8	.84	2.8	72	14	61	.57	14.4	0.087	2.2	6.50	SST	CG	N
1.578	40.08	S-3193	6.75	171.5	1.398	35.5	1.7	.30	5.2	133	8.8	39	1.53	38.9	0.090	2.3	17.0	SST	CG	N
1.578	40.08	11965	7.69	195.2	1.190	30.2	52	9.1	2.5	64	131	583	3.25	82.5	0.194	4.9	16.8	SPR	CG	GI
1.580	40.13	72864	2.50	63.5	1.166	29.6	210	37	1.1	27	223	994	1.42	36.1	0.207	5.3	6.88	MW	CG	N
1.580	40.13	72864S	2.50	63.5	1.166	29.6	179	31	.76	19	136	606	1.42	36.1	0.207	5.3	6.88	SST	CG	N
1.580	40.13	72865	3.00	76.2	1.166	29.6	170	30	1.3	33	223	994	1.66	42.1	0.207	5.3	8.00	MW	CG	N
1.580	40.13	72865S	3.00	76.2	1.166	29.6	145	25	.94	24	136	606	1.66	42.1	0.207	5.3	8.00	SST	CG	N
1.580	40.13	72866	3.50	88.9	1.166	29.6	142	25	1.6	40	223	994	1.89	48.0	0.207	5.3	9.13	MW	CG	N
1.580	40.13	72866S	3.50	88.9	1.166	29.6	121	21	1.1	29	136	606	1.89	48.0	0.207	5.3	9.13	SST	CG	N
1.580	40.13	72867	4.00	101.6	1.166	29.6	121	21	1.8	47	223	994	2.15	54.5	0.207	5.3	10.4	MW	CG	N
1.580	40.13	72867S	4.00	101.6	1.166	29.6	103	18	1.3	34	136	606	2.15	54.5	0.207	5.3	10.4	SST	CG	N
1.580	40.13	72868	4.50	114.3	1.166	29.6	107	19	2.1	53	223	994	2.38	60.5	0.207	5.3	11.5	MW	CG	N
1.580	40.13	72868S	4.50	114.3	1.166	29.6	91	16	1.5	38	136	606	2.38	60.5	0.207	5.3	11.5	SST	CG	N
1.580	40.13	72869	5.00	127.0	1.166	29.6	95	17	2.4	60	223	994	2.64	67.0	0.207	5.3	12.8	MW	CG	N
1.580	40.13	72869S	5.00	127.0	1.166	29.6	81	14	1.7	43	136	606	2.64	67.0	0.207	5.3	12.8	SST	CG	N
1.580	40.13	72870	5.50	139.7	1.166	29.6	86	15	2.6	66	223	994	2.87	73.0	0.207	5.3	13.9	MW	CG	N
1.580	40.13	72870S	5.50	139.7	1.166	29.6	73	13	1.9	47	136	606	2.87	73.0	0.207	5.3	13.9	SST	CG	N
1.580	40.13	72871	6.00	152.4	1.166	29.6	79	14	2.8	72	223	994	3.08	78.2	0.207	5.3	14.9	MW	CG	N
1.580	40.13	72871S	6.00	152.4	1.166	29.6	67	12	2.0	52	136	606	3.08	78.2	0.207	5.3	14.9	SST	CG	N
1.593	40.46	11608	1.88	47.6	1.181	30.0	243	42	.43	11	105	467	1.44	36.6	0.206	5.2	6.00	SPR	CG	Z
1.593	40.46	S-1600	2.25	57.2	1.347	34.2	15	2.7	1.1	29	18	78	1.11	28.1	0.123	3.1	8.00	SST	CG	N
1.593	40.46	3428	2.50	63.5	1.343	34.1	16	2.8	1.4	35	22	97	1.13	28.6	0.125	3.2	9.00	HD	CG	Z
1.593	40.46	S-991	2.63	66.7	1.417	36.0	7.3	1.3	1.9	48	14	62	.44	11.2	0.088	2.2	5.00	SST	CG	N
1.593	40.46	10825	4.25	108.0	1.351	34.3	19	3.4	1.8	47	36	159	.97	24.6	0.121	3.1	7.00	SPR	C	Z
1.593	40.46	3641	5.00	127.0	1.453	36.9	1.2	.21	4.3	109	5.3	23	.70	17.8	0.070	1.8	10.0	HD	CG	Z
1.593	40.46	3109	5.13	130.2	1.343	34.1	11	1.9	3.5	89	39	173	1.63	41.3	0.125	3.2	12.0	SPR	C	Z
1.593	40.46	S-359	5.13	130.2	1.179	29.9	108	19	1.3	32	135	601	2.07	52.6	0.207	5.3	10.0	SST	CG	N
1.609	40.87	10451	1.28	32.5	1.277	32.4	208	36	.41	10	85	379	.62	15.8	0.166	4.2	3.75	SPR	CG	Z
1.609	40.87	2717	1.56	39.7	1.409	35.8	8.4	1.5	.76	19	6.4	28	.80	20.3	0.100	2.5	7.00	SPR	C	Z
1.609	40.87	11957	1.69	42.8	1.423	36.1	5.5	.96	1.0	26	5.7	25	.65	16.5	0.093	2.4	7.00	SPR</		




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.625	41.28	1535	1.58	40.1	1.415	35.9	15	2.7	1.0	26	16	70	.55	14.0	0.105	2.7	5.25	SPR	CG	Z
1.625	41.28	10045	1.63	41.3	1.481	37.6		5.2	1.3	32	6.5	29	.36	9.1	0.072	1.8	4.00	SPR	CG	Z
1.625	41.28	10015	1.63	41.3	1.001	25.4	3009	527	.15	3.8	456	2026	1.25	31.7	0.312	7.9	4.00	SPR	CG	Z
1.625	41.28	10101	2.25	57.2	1.175	29.8	448	78	.42	11	189	842	1.13	28.6	0.225	5.7	5.00	SPR	CG	Z
1.625	41.28	10362	2.44	61.9	1.189	30.2	359	63	.50	13	179	797	1.15	29.1	0.218	5.5	5.25	SPR	CG	Z
1.625	41.28	S-240	2.50	63.5	1.501	38.1		1.8	2.2	55	4.0	18	.35	8.9	0.062	1.6	4.67	SST	C	N
1.625	41.28	3294	2.63	66.7	1.281	32.5	117	21	.80	20	94	417	.95	24.0	0.172	4.4	5.50	SPR	CG	Z
1.625	41.28	S-84	3.50	88.9	1.241	31.5	115	20	.92	23	106	474	1.54	39.0	0.192	4.9	7.00	SST	C	N
1.625	41.28	S-275	3.75	95.3	1.375	34.9	14	2.4	2.5	64	35	156	1.06	27.0	0.125	3.2	8.50	SST	CG	N
1.625	41.28	12119	3.84	97.6	1.375	34.9	12	2.1	2.5	64	31	138	1.31	33.3	0.125	3.2	10.5	SPR	CG	Z
1.625	41.28	12725	4.30	109.2	1.443	36.7		3.0	3.2	81	9.7	43	1.09	27.7	0.091	2.3	11.0	HD	C	N
1.625	41.28	369	4.50	114.3	1.139	28.9	200	35	1.2	30	237	1053	2.79	71.0	0.243	6.2	11.5	HD	CG	Z
1.625	41.28	2793	5.63	142.9	1.343	34.1	13	2.3	3.5	89	47	209	2.12	53.7	0.141	3.6	15.0	SPR	CG	GI
1.625	41.28	10393	7.25	184.2	1.137	28.9	119	21	2.0	51	239	1065	4.45	113.1	0.244	6.2	18.3	SPR	CG	Z
1.625	41.28	843	12.0	304.8	1.241	31.5	24	4.2	5.1	130	124	550	5.66	143.9	0.192	4.9	29.5	HD	CG	Z
1.640	41.66	S-1465	1.38	34.9	1.464	37.2	13	2.3	.98	25	13	58	.40	10.1	0.088	2.2	3.50	SST	C	N
1.640	41.66	B17-193	1.47	37.3	1.280	32.5	215	38	.41	10	87	389	.72	18.3	0.180	4.6	4.00	SST	CG	N
1.640	41.66	S-965	1.69	42.8	1.344	34.1	60	11	.92	23	55	245	.74	18.8	0.148	3.8	5.00	SST	CG	N
1.640	41.66	3008	1.88	47.6	1.496	38.0	4.0	.70	1.6	39	6.2	28	.32	8.2	0.072	1.8	4.50	SPR	CG	GI
1.640	41.66	3105	2.00	50.8	1.370	34.8	49	8.5	.96	24	47	207	.66	16.7	0.135	3.4	5.00	SPR	CG	Z
1.640	41.66	S-1666	2.25	57.2	1.370	34.8	41	7.3	1.0	26	42	187	.68	17.1	0.135	3.4	5.00	SST	CG	N
1.640	41.66	3239	2.25	57.2	1.286	32.7	120	21	.84	21	101	450	1.02	25.9	0.177	4.5	5.75	SPR	CG	Z
1.640	41.66	S-3237	2.34	59.5	1.390	35.3	20	3.5	1.5	39	30	135	.81	20.6	0.125	3.2	6.50	SST	CG	N
1.640	41.66	10665	2.38	60.3	1.190	30.2	433	76	.43	11	188	835	1.13	28.6	0.225	5.7	5.00	SPR	CG	Z
1.640	41.66	S-102	3.25	82.6	1.328	33.7	38	6.6	1.6	42	62	275	1.25	31.7	0.156	4.0	8.00	SST	CG	N
1.640	41.66	4193	3.25	82.6	1.016	25.8	969	170	.47	12	452	2011	2.50	63.4	0.312	7.9	8.00	SPR	CG	Z
1.640	41.66	2990	3.38	85.7	1.476	37.5		3.4	2.7	69	9.3	42	.66	16.7	0.082	2.1	7.00	SPR	C	Z
1.640	41.66	S-319	3.63	92.1	1.300	33.0	43	7.5	1.9	47	80	355	1.64	41.7	0.170	4.3	9.67	SST	CG	N
1.640	41.66	S-1188	3.75	95.3	1.506	38.3		1.3	3.2	82	4.2	19	.54	13.6	0.067	1.7	7.00	SST	C	N
1.640	41.66	3174	4.00	101.6	1.506	38.3		.99	3.3	84	3.3	15	.70	17.9	0.067	1.7	9.50	SPR	C	Z
1.640	41.66	1861	4.31	109.5	1.370	34.8	18	3.2	2.6	66	47	207	1.32	33.4	0.135	3.4	9.75	HD	CG	Z
1.640	41.66	1833	4.78	121.4	1.324	33.6	46	8.0	1.6	40	72	322	1.26	32.1	0.158	4.0	8.00	HD	CG	GI
1.640	41.66	3307	5.75	146.1	1.286	32.7	41	7.2	2.5	63	101	450	2.30	58.4	0.177	4.5	13.0	SPR	CG	Z
1.640	41.66	4404	8.00	203.2	1.430	36.3		4.6	5.1	130	24	105	1.42	36.0	0.105	2.7	12.5	SPR	C	GI
1.656	42.06	10529	1.16	29.4	1.430	36.3	51	8.9	.55	14	28	125	.37	9.3	0.113	2.9	3.25	SPR	CG	Z
1.656	42.06	11542	2.03	51.6	1.416	36.0	18	3.2	1.1	29	21	92	.90	22.9	0.120	3.0	6.50	SPR	CG	GI
1.656	42.06	10373	2.38	60.3	1.206	30.6	457	80	.41	10	186	827	1.07	27.2	0.225	5.7	4.75	SPR	CG	Z
1.656	42.06	S-283	2.88	73.0	1.406	35.7	21	3.7	1.6	41	35	154	.75	19.1	0.125	3.2	6.00	SST	CG	N
1.656	42.06	S-1642	9.19	233.4	1.092	27.7	154	27	1.9	47	286	1270	6.27	159.4	0.282	7.2	22.3	SST	CG	N
1.672	42.47	12618	4.00	101.6	1.318	33.5	42	7.3	1.9	49	81	358	2.08	52.8	0.177	4.5	10.8	SST	C	N
1.687	42.85	S-3070	1.38	34.9	1.531	38.9		3.7	.91	23	3.4	15	.47	11.9	0.078	2.0	5.00	SST	C	N
1.687	42.85	1948	1.50	38.1	1.531	38.9		4.3	1.1	28	4.7	21	.39	9.9	0.078	2.0	5.00	SPR	CG	Z
1.687	42.85	72872	1.50	38.1	1.417	36.0	64	11	.96	24	62	275	.54	13.7	0.135	3.4	4.00	MW	CG	N
1.687	42.85	72872S	1.50	38.1	1.417	36.0	55	9.6	.75	19	41	182	.54	13.7	0.135	3.4	4.00	SST	CG	N
1.687	42.85	72880	1.50	38.1	1.391	35.3	90	16	.89	23	80	355	.61	15.5	0.148	3.8	4.13	MW	CG	N
1.687	42.85	72880S	1.50	38.1	1.391	35.3	76	13	.70	18	54	239	.61	15.5	0.148	3.8	4.13	SST	CG	N
1.687	42.85	72882	1.50	38.1	1.375	34.9	112	20	.85	22	95	423	.64	16.3	0.156	4.0	4.13	MW	CG	N
1.687	42.85	72882S	1.50	38.1	1.375	34.9	95	17	.63	16	60	268	.64	16.3	0.156	4.0	4.13	SST	CG	N
1.687	42.85	72897	1.50	38.1	1.363	34.6	126	22	.81	21	102	454	.69	17.5	0.162	4.1	4.25	MW	CG	N
1.687	42.85	72897S	1.50	38.1	1.363	34.6	107	19	.63	16	67	300	.69	17.5	0.162	4.1	4.25	SST	CG	N
1.687	42.85	72898	1.50	38.1	1.333	33.9	178	31	.75	19	133	591	.75	19.1	0.177	4.5	4.25	MW	CG	N
1.687	42.85	72898S	1.50	38.1	1.333	33.9	151	26	.58	15	87	389	.75	19.1	0.177	4.5	4.25	SST	CG	N
1.687	42.85	72909	1.50	38.1	1.303	33.1	247	43	.66	17	163	726	.84	21.3	0.192	4.9	4.38	MW	CG	N
1.687	42.85	72909S	1.50	38.1	1.303	33.1	210	37	.49	12	103	457	.84	21.3	0.192	4.9	4.38	SST	CG	N
1.687	42.85	365	1.88	47.6	1.333	33.9	142	25	.69	18	98	438	.86	21.9	0.177	4.5	5.00	HD	CG	Z
1.687	42.85	11380	2.00	50.8	1.505	38.2	12	2.2	1.1	29	14	62	.34	8.7	0.091	2.3	3.75	SST	CG	N
1.687	42.85	72873	2.00	50.8	1.417	36.0	46	8.0	1.4	35	62	277	.64	16.3	0.135	3.4	4.75	MW	CG	N
1.687	42.85	72873S	2.00	50.8	1.417	36.0	39	6.8	1.0	27	41	182	.64	16.3	0.135	3.4	4.75	SST	CG	N
1.687	42.85	72884	2.00	50.8	1.375	34.9	79	14	1.2	31	95	423	.78	19.8	0.156	4.0	5.00	MW	CG	N
1.687	42.85	72884S	2.00	50.8	1.375	34.9	67	12	.90	23	60	268	.78	19.8	0.156	4.0	5.00	SST	CG	N
1.687	42.85	72899	2.00	50.8	1.333	33.9	124	22	1.0	27	130	577	.95	24.2	0.177	4.5	5.38	MW	CG	N
1.687	42.85	72899S	2.00	50.8	1.333	33.9	105	18	.83	21	87	389	.95	24.2	0.177	4.5	5.38	SST	CG	N
1.687	42.85	72910	2.00	50.8	1.303	33.1	171	30	.97	25	165	736	1.03	26.2	0.192	4.9	5.38	MW	CG	N
1.687	42.85	72910S	2.00	50.8	1.303	33.1	145	25	.71	18	103	457	1.03	26.2	0.192	4.9	5.38	SST	CG	N
1.687	42.85	S-3065	2.25	57.2	1.407	35.7	43	7.6	1.1	27	46	202	.70	17.8	0.140	3.6	5.00	SST	CG	N
1.687	42.85	72874	2.50	63.5	1.417	36.0	36	6.2	1.7	44	62	275	.76	19.3	0.135	3.4	5.63	MW	CG	N
1.687	42.85	72874S	2.50	63.5	1.417	36.0	30	5.3	1.4	34	41	182	.76	19.3	0.135	3.4	5.63	SST	CG	N
1.687	42.85	72886	2.50	63.5	1.375</															

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.687	42.85	72888	3.00	76.2	1.375	34.9	50	8.7	1.9	49	95	423	1.05	26.7	0.156	4.0	6.75	MW	CG	N
1.687	42.85	72888S	3.00	76.2	1.375	34.9	42	7.4	1.4	36	60	268	1.05	26.7	0.156	4.0	6.75	SST	CG	N
1.687	42.85	72903	3.00	76.2	1.333	33.9	79	14	1.7	44	136	603	1.28	32.6	0.177	4.5	7.25	MW	CG	N
1.687	42.85	72903S	3.00	76.2	1.333	33.9	67	12	1.3	33	87	389	1.28	32.6	0.177	4.5	7.25	SST	CG	N
1.687	42.85	72912	3.00	76.2	1.303	33.1	106	18	1.6	40	165	733	1.44	36.6	0.192	4.9	7.50	MW	CG	N
1.687	42.85	72912S	3.00	76.2	1.303	33.1	90	16	1.1	29	103	457	1.44	36.6	0.192	4.9	7.50	SST	CG	N
1.687	42.85	72918	3.00	76.2	1.251	31.8	181	32	1.3	34	242	1077	1.66	42.2	0.218	5.5	7.63	MW	CG	N
1.687	42.85	72918S	3.00	76.2	1.251	31.8	154	27	.97	25	149	663	1.66	42.2	0.218	5.5	7.63	SST	CG	N
1.687	42.85	72926	3.00	76.2	1.219	31.0	249	44	1.2	30	292	1299	1.78	45.3	0.234	5.9	7.63	MW	CG	N
1.687	42.85	72926S	3.00	76.2	1.219	31.0	211	37	.82	21	173	768	1.78	45.3	0.234	5.9	7.63	SST	CG	N
1.687	42.85	11253	3.00	76.2	1.201	30.5	290	51	.79	20	229	1018	1.88	47.8	0.243	6.2	7.75	SPR	CG	Z
1.687	42.85	72876	3.50	88.9	1.417	36.0	25	4.3	2.5	64	62	275	.98	24.9	0.135	3.4	7.25	MW	CG	N
1.687	42.85	72876S	3.50	88.9	1.417	36.0	21	3.6	2.0	50	41	182	.98	24.9	0.135	3.4	7.25	SST	CG	N
1.687	42.85	72890	3.50	88.9	1.375	34.9	42	7.3	2.3	58	95	423	1.19	30.2	0.156	4.0	7.63	MW	CG	N
1.687	42.85	72890S	3.50	88.9	1.375	34.9	36	6.2	1.7	43	60	268	1.19	30.2	0.156	4.0	7.63	SST	CG	N
1.687	42.85	72905	3.50	88.9	1.333	33.9	66	12	2.1	52	137	609	1.44	36.5	0.177	4.5	8.13	MW	CG	N
1.687	42.85	72905S	3.50	88.9	1.333	33.9	56	9.9	1.5	39	87	389	1.44	36.5	0.177	4.5	8.13	SST	CG	N
1.687	42.85	72913	3.50	88.9	1.303	33.1	89	16	1.8	47	163	727	1.66	42.1	0.192	4.9	8.63	MW	CG	N
1.687	42.85	72913S	3.50	88.9	1.303	33.1	75	13	1.4	35	103	457	1.66	42.1	0.192	4.9	8.63	SST	CG	N
1.687	42.85	72919	3.50	88.9	1.251	31.8	152	27	1.6	40	242	1077	1.91	48.5	0.218	5.5	8.75	MW	CG	N
1.687	42.85	72919S	3.50	88.9	1.251	31.8	129	23	1.2	29	149	663	1.91	48.5	0.218	5.5	8.75	SST	CG	N
1.687	42.85	72927	3.50	88.9	1.219	31.0	208	36	1.4	36	292	1299	2.05	52.0	0.234	5.9	8.75	MW	CG	N
1.687	42.85	72927S	3.50	88.9	1.219	31.0	176	31	.98	25	173	768	2.05	52.0	0.234	5.9	8.75	SST	CG	N
1.687	42.85	72877	4.00	101.6	1.417	36.0	21	3.7	2.9	74	62	275	1.08	27.4	0.135	3.4	8.00	MW	CG	N
1.687	42.85	72877S	4.00	101.6	1.417	36.0	18	3.2	2.3	58	41	182	1.08	27.4	0.135	3.4	8.00	SST	CG	N
1.687	42.85	72892	4.00	101.6	1.375	34.9	36	6.3	2.6	67	95	423	1.35	34.2	0.156	4.0	8.63	MW	CG	N
1.687	42.85	72892S	4.00	101.6	1.375	34.9	31	5.4	2.0	50	60	268	1.35	34.2	0.156	4.0	8.63	SST	CG	N
1.687	42.85	72906	4.00	101.6	1.333	33.9	56	9.8	2.3	59	131	581	1.66	42.1	0.177	4.5	9.38	MW	CG	N
1.687	42.85	72906S	4.00	101.6	1.333	33.9	47	8.3	1.8	47	87	389	1.66	42.1	0.177	4.5	9.38	SST	CG	N
1.687	42.85	72914	4.00	101.6	1.303	33.1	76	13	2.2	55	164	731	1.85	46.9	0.192	4.9	9.63	MW	CG	N
1.687	42.85	72914S	4.00	101.6	1.303	33.1	65	11	1.6	40	103	457	1.85	46.9	0.192	4.9	9.63	SST	CG	N
1.687	42.85	72920	4.00	101.6	1.251	31.8	130	23	1.8	47	240	1068	2.15	54.7	0.218	5.5	9.88	MW	CG	N
1.687	42.85	72920S	4.00	101.6	1.251	31.8	111	19	1.3	34	149	663	2.15	54.7	0.218	5.5	9.88	SST	CG	N
1.687	42.85	72928	4.00	101.6	1.219	31.0	178	31	1.6	42	292	1299	2.31	58.7	0.234	5.9	9.88	MW	CG	N
1.687	42.85	72928S	4.00	101.6	1.219	31.0	151	27	1.1	29	173	768	2.31	58.7	0.234	5.9	9.88	SST	CG	N
1.687	42.85	S-1217	4.25	108.0	1.477	37.5	7.7	1.3	2.8	70	21	94	.74	18.7	0.105	2.7	7.00	SST	CG	N
1.687	42.85	3497	4.38	111.1	1.417	36.0	16	2.9	2.8	70	45	202	1.32	33.4	0.135	3.4	9.75	HD	CG	Z
1.687	42.85	72878	4.50	114.3	1.417	36.0	19	3.3	3.3	84	62	275	1.20	30.4	0.135	3.4	8.88	MW	CG	N
1.687	42.85	72878S	4.50	114.3	1.417	36.0	16	2.8	2.6	65	41	182	1.20	30.4	0.135	3.4	8.88	SST	CG	N
1.687	42.85	72894	4.50	114.3	1.375	34.9	32	5.6	3.0	76	95	423	1.48	37.6	0.156	4.0	9.50	MW	CG	N
1.687	42.85	72894S	4.50	114.3	1.375	34.9	27	4.7	2.2	57	60	268	1.48	37.6	0.156	4.0	9.50	SST	CG	N
1.687	42.85	72907	4.50	114.3	1.333	33.9	49	8.6	2.7	68	131	582	1.84	46.6	0.177	4.5	10.4	MW	CG	N
1.687	42.85	72907S	4.50	114.3	1.333	33.9	42	7.3	2.1	53	87	389	1.84	46.6	0.177	4.5	10.4	SST	CG	N
1.687	42.85	4162	4.50	114.3	1.327	33.7	55	9.6	1.8	46	99	439	1.80	45.7	0.180	4.6	10.0	SPR	CG	Z
1.687	42.85	72915	4.50	114.3	1.303	33.1	67	12	2.4	62	163	727	2.06	52.4	0.192	4.9	10.8	MW	CG	N
1.687	42.85	72915S	4.50	114.3	1.303	33.1	57	10	1.8	46	103	457	2.06	52.4	0.192	4.9	10.8	SST	CG	N
1.687	42.85	72921	4.50	114.3	1.251	31.8	114	20	2.1	53	240	1066	2.40	60.9	0.218	5.5	11.0	MW	CG	N
1.687	42.85	72921S	4.50	114.3	1.251	31.8	97	17	1.5	39	149	663	2.40	60.9	0.218	5.5	11.0	SST	CG	N
1.687	42.85	72929	4.50	114.3	1.219	31.0	156	27	1.9	48	292	1299	2.57	65.4	0.234	5.9	11.0	MW	CG	N
1.687	42.85	72929S	4.50	114.3	1.219	31.0	133	23	1.3	33	173	768	2.57	65.4	0.234	5.9	11.0	SST	CG	N
1.687	42.85	S-435	5.00	127.0	1.417	36.0	13	2.4	3.0	77	41	182	1.38	35.1	0.135	3.4	10.3	SST	CG	N
1.687	42.85	72879	5.00	127.0	1.417	36.0	17	2.9	3.7	94	62	275	1.30	33.0	0.135	3.4	9.63	MW	CG	N
1.687	42.85	72879S	5.00	127.0	1.417	36.0	14	2.5	2.9	73	41	182	1.30	33.0	0.135	3.4	9.63	SST	CG	N
1.687	42.85	1851	5.00	127.0	1.385	35.2	21	3.6	3.0	76	62	274	1.81	46.0	0.151	3.8	12.0	SPR	CG	Z
1.687	42.85	72896	5.00	127.0	1.375	34.9	28	5.0	3.3	85	95	423	1.62	41.1	0.156	4.0	10.4	MW	CG	N
1.687	42.85	72896S	5.00	127.0	1.375	34.9	24	4.2	2.5	63	60	268	1.62	41.1	0.156	4.0	10.4	SST	CG	N
1.687	42.85	72908	5.00	127.0	1.333	33.9	44	7.7	3.0	76	131	582	2.01	51.1	0.177	4.5	11.4	MW	CG	N
1.687	42.85	72908S	5.00	127.0	1.333	33.9	37	6.5	2.3	60	87	389	2.01	51.1	0.177	4.5	11.4	SST	CG	N
1.687	42.85	72916	5.00	127.0	1.303	33.1	60	10	2.7	70	164	730	2.26	57.3	0.192	4.9	11.8	MW	CG	N
1.687	42.85	72916S	5.00	127.0	1.303	33.1	51	8.9	2.0	51	103	457	2.26	57.3	0.192	4.9	11.8	SST	CG	N
1.687	42.85	72922	5.00	127.0	1.251	31.8	102	18	2.4	61	243	1082	2.62	66.4	0.218	5.5	12.0	MW	CG	N
1.687	42.85	72922S	5.00	127.0	1.251	31.8	87	15	1.7	44	149	663	2.62	66.4	0.218	5.5	12.0	SST	CG	N
1.687	42.85	72930	5.00	127.0	1.219	31.0	139	24	2.1	53	292	1299	2.84	72.1	0.234	5.9	12.1	MW	CG	N
1.687	42.85	72930S	5.00	127.0	1.219	31.0	118	21	1.5	37	173	768	2.84	72.1	0.234	5.9	12.1	SST	CG	N
1.687	42.85	72923	5.50	139.7	1.251	31.8	91	16	2.6	66	238	1057	2.89	73.4	0.218	5.5	13.3	MW	CG	N
1.687	42.85	72923S	5.50	139.7	1.251	31.8	77	14	1.9	49	149	663	2.89	73.4	0.218	5.5	13.3	SST	CG	N
1.687	42.85	72931	5.																	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.703	43.26	11835	1.75	44.5	1.547	39.3	4.0	.70	1.4	35	5.5	25	.37	9.4	0.078	2.0	4.75	SST	CG	N
1.703	43.26	11842	1.84	46.8	1.593	40.5	1.2	.20	1.6	39	1.8	8.0	.29	7.3	0.055	1.4	4.25	SST	CG	N
1.703	43.26	S-3034	4.00	101.6	1.467	37.3	7.2	1.3	2.8	70	20	88	1.24	31.5	0.118	3.0	10.5	SST	CG	N
1.703	43.26	S-3109	4.38	111.1	1.453	36.9	9.7	1.7	3.1	79	30	135	1.25	31.8	0.125	3.2	10.0	SST	CG	N
1.703	43.26	S-956	4.38	111.1	1.433	36.4	13	2.4	3.0	76	40	180	1.35	34.3	0.135	3.4	10.0	SST	CG	N
1.703	43.26	1639	7.00	177.8	1.407	35.7	15	2.7	3.9	98	59	263	2.22	56.4	0.148	3.8	14.0	SPR	C	Z
1.703	43.26	11925	9.25	235.0	1.363	34.6	13	2.3	4.7	118	62	276	4.59	116.6	0.170	4.3	27.0	SPR	CG	GI
1.703	43.26	10259	10.3	260.4	1.217	30.9	83	14	2.7	70	227	1009	5.23	132.7	0.243	6.2	21.5	SPR	CG	Z
1.703	43.26	12459	20.0	508.0	1.493	37.9	1.1	.19	16	401	17	77	4.23	107.3	0.105	2.7	39.3	SPR	O	N
1.718	43.64	S-1481	1.31	33.3	1.574	40.0	3.8	.66	.95	24	3.6	16	.36	9.1	0.072	1.8	4.00	SST	C	N
1.718	43.64	4315	3.50	88.9	1.344	34.1	75	13	1.4	37	109	483	1.59	40.4	0.187	4.7	8.50	SPR	CG	Z
1.718	43.64	S-1507	5.00	127.0	1.594	40.5	.71	.12	4.5	115	3.2	14	.48	12.2	0.062	1.6	7.75	SST	CG	N
1.718	43.64	3934	5.00	127.0	1.558	39.6	1.7	.29	4.1	105	6.9	31	.88	22.4	0.080	2.0	10.0	SPR	C	Z
1.718	43.64	2525	5.00	127.0	1.548	39.3	2.2	.38	4.1	103	8.8	39	.94	23.7	0.085	2.2	10.0	SPR	C	Z
1.718	43.64	4337	5.50	139.7	1.094	27.8	577	101	.75	19	435	1934	3.28	83.2	0.312	7.9	10.5	SPR	CG	Z
1.718	43.64	S-1622	6.13	155.6	1.518	38.6	3.6	.63	5.0	127	18	80	1.03	26.2	0.100	2.5	10.3	SST	CG	N
1.718	43.64	238	7.00	177.8	1.422	36.1	15	2.7	3.9	98	59	260	2.04	51.7	0.148	3.8	13.8	SPR	CG	Z
1.718	43.64	3176	8.75	222.3	1.500	38.1	4.2	.74	5.9	151	25	112	1.47	37.4	0.109	2.8	13.0	SPR	CG	Z
1.734	44.04	12130	1.56	39.7	1.284	32.6	460	81	.39	9.8	178	793	.97	24.7	0.225	5.7	4.33	SPR	CG	Z
1.734	44.04	1669	2.00	50.8	1.324	33.6	178	31	.77	20	137	608	1.23	31.2	0.205	5.2	6.00	SPR	CG	Z
1.734	44.04	S-3044	2.25	57.2	1.464	37.2	25	4.4	1.4	37	37	163	.81	20.6	0.135	3.4	6.00	SST	CG	N
1.734	44.04	11285	2.38	60.3	1.552	39.4	4.6	.81	1.7	44	8.0	35	.66	16.8	0.091	2.3	6.25	SST	C	N
1.734	44.04	10361	2.50	63.5	1.284	32.6	238	42	.75	19	178	793	1.46	37.2	0.225	5.7	6.50	SPR	CG	Z
1.734	44.04	1595	3.38	85.7	1.010	25.7	1821	319	.40	10	722	3209	2.63	66.7	0.362	9.2	7.25	OT	CG	Z
1.734	44.04	S-382	3.44	87.3	1.576	40.0	2.1	.38	2.8	71	6.0	27	.63	16.1	0.079	2.0	7.00	SST	C	N
1.734	44.04	4191	3.75	95.3	1.414	35.9	30	5.3	2.2	55	65	289	1.60	40.6	0.160	4.1	10.0	SPR	CG	GI
1.734	44.04	11793	5.47	138.9	1.094	27.8	627	110	.74	19	464	2062	3.84	97.5	0.320	8.1	10.5	SPR	CG	Z
1.734	44.04	12550	5.47	138.9	1.110	28.2	474	83	.91	23	431	1918	3.74	95.1	0.312	7.9	12.0	SPR	CG	Z
1.734	44.04	12681	5.50	139.7	1.072	27.2	625	109	.82	21	510	2269	3.97	100.9	0.331	8.4	12.0	SPR	CG	Z
1.734	44.04	S-967	6.38	161.9	1.574	40.0	1.3	.22	5.5	140	6.9	31	.88	22.4	0.080	2.0	11.0	SST	CG	N
1.734	44.04	1946	7.25	184.2	1.484	37.7	8.7	1.5	4.2	106	36	161	1.46	37.0	0.125	3.2	11.7	SPR	CG	Z
1.734	44.04	12106	7.81	198.4	1.588	40.3	.91	.16	6.9	175	6.3	28	.93	23.6	0.073	1.9	11.8	SPR	C	Z
1.750	44.45	S-273	.84	21.4	1.396	35.5	214	38	.22	5.7	48	213	.62	15.7	0.177	4.5	3.50	SST	CG	N
1.750	44.45	S-41	1.00	25.4	1.396	35.5	315	55	.27	6.8	84	376	.53	13.5	0.177	4.5	3.00	SST	CG	N
1.750	44.45	3331	1.44	36.5	1.184	30.1	1460	256	.23	5.8	333	1480	1.13	28.8	0.283	7.2	4.00	SPR	CG	Z
1.750	44.45	1799	1.50	38.1	1.454	36.9	56	9.8	.76	19	42	189	.74	18.8	0.148	3.8	5.00	HD	CG	Z
1.750	44.45	1633	1.50	38.1	1.396	35.5	121	21	.62	16	74	331	.89	22.5	0.177	4.5	5.00	HD	CG	N
1.750	44.45	1919	1.63	41.3	1.454	36.9	96	17	.60	15	58	256	.70	17.9	0.148	3.8	3.75	SPR	C	Z
1.750	44.45	11600	1.75	44.5	1.396	35.5	121	21	.69	17	83	370	1.06	27.0	0.177	4.5	5.00	SPR	CG	Z
1.750	44.45	3301	2.00	50.8	1.566	39.8	11	2.0	1.3	34	15	66	.46	11.7	0.092	2.3	4.00	SPR	C	Z
1.750	44.45	12458	2.31	58.7	1.516	38.5	9.1	1.6	1.3	32	12	51	1.05	26.7	0.117	3.0	8.00	SST	C	N
1.750	44.45	10841	2.38	60.3	1.460	37.1	35	6.2	1.4	35	49	217	.85	21.6	0.145	3.7	6.00	SST	CG	N
1.750	44.45	10653	2.56	65.1	1.300	33.0	231	40	.77	19	177	787	1.46	37.2	0.225	5.7	6.50	SPR	CG	Z
1.750	44.45	S-1663	2.66	67.5	1.396	35.5	80	14	1.1	27	84	376	1.06	27.0	0.177	4.5	6.00	SST	CG	N
1.750	44.45	11499	3.00	76.2	1.426	36.2	35	6.2	1.4	35	49	217	1.62	41.1	0.162	4.1	9.00	SPR	C	Z
1.750	44.45	3447	3.13	79.4	1.616	41.0	1.3	.22	2.6	66	3.3	15	.52	13.2	0.067	1.7	6.75	SPR	C	Z
1.750	44.45	380	3.50	88.9	1.426	36.2	43	7.5	1.7	43	73	326	1.26	31.9	0.162	4.1	7.75	HD	CG	Z
1.750	44.45	31	4.00	101.6	1.426	36.2	37	6.4	2.0	51	73	326	1.42	36.0	0.162	4.1	8.75	HD	CG	Z
1.750	44.45	11825	4.06	103.2	1.604	40.7	1.2	.21	3.4	87	4.1	18	.62	15.8	0.073	1.9	8.50	SST	CG	N
1.750	44.45	S-1294	4.75	120.7	1.590	40.4	3.1	.55	3.1	78	9.6	43	.44	11.2	0.080	2.0	5.50	SST	C	N
1.750	44.45	11497	4.78	121.4	1.510	38.4	8.1	1.4	3.4	86	28	122	1.38	35.1	0.120	3.0	10.5	SPR	CG	Z
1.750	44.45	11578	4.81	122.2	1.582	40.2	2.8	.49	4.1	104	12	51	.71	18.1	0.084	2.1	7.50	SPR	C	N
1.750	44.45	S-3176	5.00	127.0	1.532	38.9	5.0	.87	3.8	97	19	84	1.20	30.5	0.109	2.8	10.0	SST	C	N
1.750	44.45	1783	5.38	136.5	1.480	37.6	16	2.8	3.8	96	61	273	1.35	34.3	0.135	3.4	9.00	MW	C	Z
1.750	44.45	S-3194	6.00	152.4	1.592	40.4	1.2	.21	5.1	128	6.0	27	.95	24.1	0.079	2.0	11.0	SST	C	N
1.750	44.45	10657	6.00	152.4	1.544	39.2	5.2	.91	4.0	102	21	93	.93	23.5	0.103	2.6	9.00	SPR	CG	GI
1.750	44.45	12126	6.81	173.0	1.426	36.2	15	2.5	3.7	95	54	242	3.08	78.2	0.162	4.1	19.0	SPR	CG	Z
1.750	44.45	7011	7.00	177.8	1.184	30.1	200	35	1.7	42	333	1480	5.00	127.0	0.283	7.2	16.6	HD	C	Z
1.750	44.45	3474	7.00	177.8	1.010	25.7	1079	189	.63	16	677	3010	4.26	108.1	0.370	9.4	11.5	SPR	CG	Z
1.750	44.45	3194	7.31	185.7	1.454	36.9	14	2.4	4.2	108	58	256	2.06	52.3	0.148	3.8	14.0	SPR	CG	Z
1.750	44.45	1677	7.50	190.5	1.310	33.3	63	11	2.6	67	166	737	3.74	95.0	0.220	5.6	17.0	SPR	CG	Z
1.750	44.45	4323	8.00	203.2	1.606	40.8	.82	.14	7.1	179	5.8	26	.94	23.8	0.072	1.8	12.0	SPR	C	Z
1.750	44.45	1779	10.0	254.0	1.426	36.2	14	2.4	5.3	135	73	326	3.40	86.4	0.162	4.1	20.0	HD	C	Z
1.750	44.45	847	10.0	254.0	1.396	35.5	19	3.3	5.1	128	95	423	3.76	95.5	0.177	4.5	21.3	HD	CG	Z
1.750	44.45	853	12.0	304.8	1.426	36.2	11	2.0	6.5	166	73	326	4.05	102.9	0.162	4.1	24.0	HD	C	Z
1.750	44.45	844	12.0	304.8	1.366	34.7	21	3.7	5.5	140	115	513	5.14	130.5	0.192	4.9	26.8	HD	CG	Z
1.750	44.45	805	12.0	304.8	1.336	33.9	28	4.9	5.1	130	144	640	5.69	144.6</						

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.781	45.24	3303	1.88	47.6	1.145	29.1	1878	329	.24	6.0	445	1980	1.43	36.3	0.318	8.1	4.50	SPR	CG	Z
1.781	45.24	1687	2.00	50.8	1.485	37.7	53	9.2	1.1	27	57	252	.74	18.8	0.148	3.8	5.00	SPR	CG	Z
1.781	45.24	S-1671	2.25	57.2	1.511	38.4	27	4.8	1.4	36	39	173	.74	18.9	0.135	3.4	5.50	SST	CG	N
1.781	45.24	11716	2.28	57.9	1.511	38.4	21	3.7	1.3	34	29	127	.95	24.0	0.135	3.4	7.00	SPR	CG	Z
1.781	45.24	S-1528	3.00	76.2	1.541	39.1	14	2.5	2.0	51	29	127	.72	18.3	0.120	3.0	6.00	SST	CG	N
1.781	45.24	11609	3.53	89.7	1.309	33.2	161	28	1.1	27	170	755	2.48	62.9	0.236	6.0	9.50	SPR	CG	Z
1.781	45.24	S-227	4.25	108.0	1.621	41.2	1.8	.32	3.6	90	6.5	29	.69	17.6	0.080	2.0	7.67	SST	C	N
1.781	45.24	2930	4.56	115.9	1.531	38.9	13	2.2	2.8	70	35	157	1.04	26.4	0.125	3.2	8.25	SPR	CG	Z
1.781	45.24	S-1638	5.19	131.8	1.563	39.7	4.8	.84	4.0	101	19	85	1.20	30.5	0.109	2.8	10.0	SST	C	N
1.781	45.24	3419	5.75	146.1	1.367	34.7	68	12	2.1	53	142	630	2.48	63.1	0.207	5.3	12.0	SPR	CG	Z
1.781	45.24	S-1005	6.75	171.5	1.557	39.5	6.0	1.1	3.8	98	23	103	1.01	25.6	0.112	2.8	9.00	SST	CG	N
1.781	45.24	S-3083	16.0	406.4	1.515	38.5	3.4	.59	11	280	37	165	3.72	94.6	0.133	3.4	28.0	SST	CG	N
1.796	45.62	4153	3.00	76.2	1.662	42.2	1.4	.25	2.5	64	3.5	16	.47	11.9	0.067	1.7	6.00	SPR	C	Z
1.796	45.62	12168	3.47	88.1	1.306	33.2	198	35	1.1	28	221	985	2.21	56.0	0.245	6.2	9.00	SPR	CG	Z
1.796	45.62	10906	3.50	88.9	1.530	38.9	12	2.1	2.6	67	31	138	.86	22.0	0.133	3.4	6.50	PB	CG	N
1.796	45.62	B17-198	4.00	101.6	1.640	41.7	1.5	.26	3.3	83	4.8	21	.73	18.5	0.078	2.0	8.33	SST	C	N
1.796	45.62	3494	4.38	111.1	1.296	32.9	190	33	1.2	31	235	1044	2.50	63.5	0.250	6.4	10.0	SPR	CG	Z
1.796	45.62	S-983	5.00	127.0	1.472	37.4	38	6.6	1.7	43	63	282	1.17	29.8	0.162	4.1	7.25	SST	CG	N
1.796	45.62	11854	6.50	165.1	1.576	40.0	6.3	1.1	3.8	97	24	107	.99	25.1	0.110	2.8	9.00	SPR	CG	N
1.796	45.62	1621	11.0	279.4	1.416	36.0	23	4.0	4.8	123	109	486	4.18	106.2	0.190	4.8	22.0	HD	CG	Z
1.812	46.02	11994	1.25	31.8	1.516	38.5	75	13	.66	17	49	219	.59	15.0	0.148	3.8	4.00	SPR	CG	Z
1.812	46.02	2758	2.31	58.7	1.542	39.2	22	3.8	1.4	34	29	130	.96	24.4	0.135	3.4	7.00	SPR	CG	Z
1.812	46.02	1583	3.03	77.0	1.692	43.0	.69	.12	2.6	65	1.8	7.9	.48	12.2	0.060	1.5	7.00	SPR	C	Z
1.812	46.02	4349	3.25	82.6	1.542	39.2	20	3.5	2.1	53	42	188	.95	24.0	0.135	3.4	7.00	SPR	CG	Z
1.812	46.02	11115	3.34	84.9	1.342	34.1	186	33	1.0	27	194	865	1.88	47.8	0.235	6.0	8.00	SPR	CG	Z
1.812	46.02	S-3171	3.38	85.7	1.362	34.6	160	28	.90	23	144	641	1.80	45.7	0.225	5.7	7.00	SST	CG	N
1.812	46.02	10478	3.50	88.9	1.342	34.1	194	34	1.0	25	194	865	1.82	46.3	0.235	6.0	7.75	SPR	CG	Z
1.812	46.02	3081	6.00	152.4	1.428	36.3	51	8.9	2.2	56	112	497	2.11	53.6	0.192	4.9	11.0	SPR	CG	Z
1.812	46.02	3298	6.00	152.4	1.392	35.4	68	12	2.1	54	145	646	2.52	64.0	0.210	5.3	12.0	SPR	CG	Z
1.812	46.02	10990	6.50	165.1	1.428	36.3	50	8.7	2.2	57	112	497	2.16	54.9	0.192	4.9	11.3	HD	CG	Z
1.812	46.02	1523	10.4	263.5	1.392	35.4	34	6.0	4.3	109	145	646	4.62	117.3	0.210	5.3	22.0	HD	CG	Z
1.812	46.02	386	10.5	266.7	1.398	35.5	32	5.6	4.4	111	139	620	4.55	115.7	0.207	5.3	22.0	HD	CG	Z
1.828	46.43	12075	1.41	35.7	1.474	37.4	105	18	.52	13	54	242	.89	22.5	0.177	4.5	5.00	SPR	CG	Z
1.828	46.43	S-1193	1.44	36.5	1.618	41.1	15	2.6	1.0	26	15	67	.42	10.7	0.105	2.7	4.00	SST	CG	N
1.828	46.43	S-3049	3.50	88.9	1.588	40.3	7.4	1.3	2.4	61	18	80	1.08	27.4	0.120	3.0	9.00	SST	CG	N
1.828	46.43	11802	5.81	147.6	1.558	39.6	9.2	1.6	4.1	104	37	167	1.72	43.7	0.135	3.4	12.8	SPR	CG	GI
1.828	46.43	1801	8.00	203.2	1.532	38.9	15	2.6	5.2	131	77	343	1.74	44.2	0.148	3.8	11.8	MW	CG	GI
1.828	46.43	3421	8.25	209.6	1.368	34.7	56	9.9	3.2	82	181	806	4.49	113.9	0.230	5.8	19.5	SPR	CG	BO
1.843	46.81	S-3173	1.38	34.9	1.593	40.5	30	5.3	.88	22	26	117	.50	12.7	0.125	3.2	4.00	SST	CG	N
1.843	46.81	11765	1.94	49.2	1.701	43.2	1.6	.29	1.5	38	2.5	11	.43	10.8	0.071	1.8	6.00	SPR	CG	Z
1.843	46.81	10444	2.88	73.0	1.683	42.7	1.9	.33	2.2	55	4.1	18	.70	17.8	0.080	2.0	7.75	SPR	C	Z
1.843	46.81	3304	5.75	146.1	1.483	37.7	44	7.7	2.1	53	91	404	1.71	43.4	0.180	4.6	9.50	SPR	CG	Z
1.843	46.81	3381	6.00	152.4	1.489	37.8	36	6.3	2.5	64	91	403	1.86	47.2	0.177	4.5	10.5	SPR	CG	Z
1.843	46.81	4325	17.3	438.2	1.429	36.3	22	3.9	6.1	156	137	610	6.00	152.5	0.207	5.3	29.0	SPR	CG	Z
1.859	47.22	S-426	2.94	74.6	1.619	41.1	14	2.5	1.9	49	27	122	.66	16.8	0.120	3.0	5.50	SST	CG	N
1.859	47.22	S-979	3.13	79.4	1.409	35.8	147	26	.96	24	141	626	1.58	40.0	0.225	5.7	7.00	SST	CG	N
1.859	47.22	3399	4.13	104.8	1.235	31.4	589	103	.69	18	406	1807	2.57	65.4	0.312	7.9	8.25	SPR	CG	Z
1.859	47.22	S-1185	5.75	146.1	1.675	42.5	1.7	.30	4.6	117	7.9	35	1.15	29.2	0.092	2.3	11.5	SST	C	N
1.875	47.63	S-3064	1.25	31.8	1.715	43.6	5.9	1.0	.89	23	5.3	23	.36	9.1	0.080	2.0	3.50	SST	C	N
1.875	47.63	12678	1.63	41.3	1.689	42.9	6.6	1.2	1.2	31	8.0	35	.42	10.6	0.093	2.4	4.50	SST	CG	N
1.875	47.63	4308	1.88	47.6	1.741	44.2	1.1	.19	1.4	35	1.5	6.6	.50	12.8	0.067	1.7	6.50	SPR	C	Z
1.875	47.63	S-1228	2.13	54.0	1.691	43.0	2.6	.46	1.4	35	3.7	16	.74	18.7	0.092	2.3	8.00	SST	CG	N
1.875	47.63	10751	2.31	58.7	1.625	41.3	22	3.8	1.5	39	34	149	.63	15.9	0.125	3.2	5.00	SPR	CG	Z
1.875	47.63	10462	2.50	63.5	1.579	40.1	41	7.2	1.3	33	54	239	.78	19.7	0.148	3.8	5.25	SPR	CG	Z
1.875	47.63	4273	2.88	73.0	1.615	41.0	18	3.2	2.0	51	37	163	.81	20.6	0.130	3.3	6.25	SPR	CG	Z
1.875	47.63	4159	3.00	76.2	1.151	29.2	1521	266	.40	10	602	2677	2.57	65.3	0.362	9.2	7.00	SPR	CG	N
1.875	47.63	S-947	3.09	78.6	1.635	41.5	14	2.4	2.0	50	27	121	.66	16.8	0.120	3.0	5.50	SST	CG	N
1.875	47.63	4155	3.38	85.7	1.571	39.9	25	4.4	2.2	55	54	240	1.22	30.9	0.152	3.9	8.00	SPR	CG	Z
1.875	47.63	S-3139	4.25	108.0	1.605	40.8	15	2.6	2.5	62	37	164	1.11	28.3	0.135	3.4	7.25	SST	C	N
1.875	47.63	S-141	4.41	111.9	1.605	40.8	13	2.3	2.8	71	37	164	1.08	27.4	0.135	3.4	8.00	SST	CG	N
1.875	47.63	4331	4.50	114.3	1.125	28.6	1203	211	.55	14	665	2957	3.38	85.7	0.375	9.5	9.00	SPR	CG	GI
1.875	47.63	S-969	4.63	117.5	1.605	40.8	9.9	1.7	3.1	80	31	138	1.49	37.7	0.135	3.4	10.0	SST	C	N
1.875	47.63	11519	5.03	127.8	1.637	41.6	8.9	1.6	3.3	83	29	129	1.07	27.2	0.119	3.0	8.00	SPR	CG	Z
1.875	47.63	10360	5.50	139.7	1.649	41.9	6.1	1.1	4.1	103	25	111	1.02	25.8	0.113	2.9	9.00	SPR	CG	Z
1.875	47.63	4188	7.75	196.9	1.521	38.6	29	5.0	3.1	79	89	396	2.12	53.9	0.177	4.5	12.0	SPR	CG	GI
1.875	47.63	2868	8.25	209.6	1.773	45.0	.22	.04	7.7	196	1.7	7.7	.52	13.1	0.051	1.3	9.00	MW	C	Z
1.875	47.63	4338	11.5	292.1	1.425	36.2	59	10	3.2	81	187	830	3.60							




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.906	48.41	1867	1.75	44.5	1.666	42.3	26	4.6	1.1	28	29	130	.48	12.2	0.120	3.0	4.00	HD	CG	Z
1.906	48.41	12053	1.78	45.2	1.680	42.7	14	2.4	1.1	28	15	66	.68	17.2	0.113	2.9	5.00	SPR	C	N
1.906	48.41	S-378	1.78	45.2	1.656	42.1	22	3.9	1.1	28	24	107	.69	17.5	0.125	3.2	4.50	SST	C	N
1.906	48.41	S-952	1.97	50.0	1.582	40.2	65	11	.92	23	60	267	.73	18.5	0.162	4.1	4.50	SST	CG	N
1.906	48.41	1667	2.59	65.9	1.182	30.0	2439	427	.27	7.0	668	2971	1.72	43.7	0.362	9.2	4.75	OT	CG	Z
1.906	48.41	11574	2.63	66.7	1.610	40.9	32	5.6	1.6	40	50	224	1.04	26.3	0.148	3.8	6.00	SPR	CG	N
1.906	48.41	S-957	2.75	69.9	1.582	40.2	36	6.3	1.7	42	60	267	1.05	26.7	0.162	4.1	6.50	SST	CG	N
1.906	48.41	S-184	3.13	79.4	1.582	40.2	41	7.1	1.5	38	60	267	.97	24.7	0.162	4.1	6.00	SST	CG	N
1.906	48.41	4165	4.00	101.6	1.636	41.6	15	2.6	2.7	69	40	179	1.05	26.6	0.135	3.4	7.75	SPR	CG	Z
1.906	48.41	1835	4.00	101.6	1.622	41.2	28	5.0	2.3	59	66	292	.82	20.8	0.142	3.6	5.75	MW	CG	Z
1.906	48.41	S-978	4.25	108.0	1.636	41.6	14	2.5	2.6	66	36	162	.99	25.1	0.135	3.4	7.33	SST	CG	N
1.906	48.41	11646	5.75	146.1	1.662	42.2	56	9.8	.55	14	31	137	.37	9.3	0.122	3.1	3.00	SPR	CG	Z
1.906	48.41	3281	6.13	155.6	1.420	36.1	141	25	1.4	37	205	911	2.45	62.2	0.243	6.2	10.0	SPR	CG	Z
1.906	48.41	3148	7.00	177.8	1.532	38.9	35	6.2	2.8	71	99	438	2.26	57.3	0.187	4.7	12.0	SPR	CG	Z
1.906	48.41	3417	7.50	190.5	1.340	34.0	160	28	1.9	49	309	1372	4.39	111.4	0.283	7.2	15.5	SPR	CG	Z
1.906	48.41	10088	8.75	222.3	1.562	39.7	21	3.7	3.8	98	81	359	2.32	59.0	0.172	4.4	13.5	SPR	CG	Z
1.906	48.41	3098	9.31	236.5	1.456	37.0	48	8.4	3.4	87	163	727	4.11	104.3	0.225	5.7	18.3	SPR	CG	Z
1.921	48.79	3142	.75	19.1	1.721	43.7	24	4.2	.45	11	11	48	.30	7.6	0.100	2.5	3.00	SPR	CG	Z
1.921	48.79	3330	1.00	25.4	1.731	44.0	19	3.4	.72	18	14	61	.29	7.2	0.095	2.4	3.00	SPR	CG	Z
1.921	48.79	11861	1.66	42.1	1.609	40.9	92	16	.58	15	53	237	.55	13.9	0.156	4.0	3.50	SST	CG	N
1.921	48.79	S-988	1.69	42.8	1.597	40.6	47	8.3	.82	21	39	174	.86	21.9	0.162	4.1	5.33	SST	CG	N
1.921	48.79	S-941	2.25	57.2	1.739	44.2	4.7	.82	1.7	43	7.9	35	.55	13.9	0.091	2.3	5.00	SST	C	N
1.921	48.79	3310	4.25	108.0	1.651	41.9	14	2.4	2.9	73	40	178	1.08	27.4	0.135	3.4	8.00	SPR	CG	Z
1.921	48.79	S-379	4.25	108.0	1.651	41.9	9.1	1.6	2.9	74	26	118	1.35	34.3	0.135	3.4	10.0	SST	CG	N
1.921	48.79	11505	8.75	222.3	1.577	40.1	21	3.6	3.9	98	80	356	2.46	62.6	0.172	4.4	13.3	SPR	CG	Z
1.921	48.79	4054	22.5	571.5	1.471	37.4	18	3.1	9.0	229	162	722	10.1	257.2	0.225	5.7	44.0	SPR	C	Z
1.937	49.20	12114	1.50	38.1	1.563	39.7	109	19	.57	14	62	274	.94	23.7	0.187	4.7	5.00	SPR	CG	Z
1.937	49.20	72933	2.00	50.8	1.641	41.7	52	9.0	1.4	34	70	310	.65	16.4	0.148	3.8	4.38	MW	CG	N
1.937	49.20	72933S	2.00	50.8	1.641	41.7	44	7.7	1.1	27	47	209	.65	16.4	0.148	3.8	4.38	SST	CG	N
1.937	49.20	72942	2.00	50.8	1.625	41.3	64	11	1.3	33	83	371	.68	17.3	0.156	4.0	4.38	MW	CG	N
1.937	49.20	72942S	2.00	50.8	1.625	41.3	54	9.5	.97	25	53	235	.68	17.3	0.156	4.0	4.38	SST	CG	N
1.937	49.20	72959	2.00	50.8	1.613	41.0	71	12	1.3	32	90	400	.73	18.5	0.162	4.1	4.50	MW	CG	N
1.937	49.20	72959S	2.00	50.8	1.613	41.0	60	11	.98	25	59	263	.73	18.5	0.162	4.1	4.50	SST	CG	N
1.937	49.20	72976	2.00	50.8	1.553	39.4	124	22	1.0	26	129	575	.96	24.4	0.192	4.9	5.00	MW	CG	N
1.937	49.20	72976S	2.00	50.8	1.553	39.4	106	18	.86	22	90	402	.96	24.4	0.192	4.9	5.00	SST	CG	N
1.937	49.20	72934	2.50	63.5	1.641	41.7	40	7.0	1.8	45	70	312	.74	18.8	0.148	3.8	5.00	MW	CG	N
1.937	49.20	72934S	2.50	63.5	1.641	41.7	34	5.9	1.4	35	47	209	.74	18.8	0.148	3.8	5.00	SST	CG	N
1.937	49.20	72944	2.50	63.5	1.625	41.3	49	8.6	1.7	43	83	371	.80	20.3	0.156	4.0	5.13	MW	CG	N
1.937	49.20	72944S	2.50	63.5	1.625	41.3	42	7.3	1.3	32	53	235	.80	20.3	0.156	4.0	5.13	SST	CG	N
1.937	49.20	72960	2.50	63.5	1.613	41.0	55	9.5	1.6	42	90	400	.85	21.6	0.162	4.1	5.25	MW	CG	N
1.937	49.20	72960S	2.50	63.5	1.613	41.0	46	8.1	1.3	32	59	263	.85	21.6	0.162	4.1	5.25	SST	CG	N
1.937	49.20	72967	2.50	63.5	1.583	40.2	75	13	1.5	39	114	509	.97	24.7	0.177	4.5	5.50	MW	CG	N
1.937	49.20	72967S	2.50	63.5	1.583	40.2	64	11	1.2	31	77	341	.97	24.7	0.177	4.5	5.50	SST	CG	N
1.937	49.20	72977	2.50	63.5	1.553	39.4	101	18	1.4	36	144	640	1.08	27.4	0.192	4.9	5.63	MW	CG	N
1.937	49.20	72977S	2.50	63.5	1.553	39.4	86	15	1.0	27	90	402	1.08	27.4	0.192	4.9	5.63	SST	CG	N
1.937	49.20	72985	2.50	63.5	1.523	38.7	141	25	1.3	33	185	823	1.16	29.6	0.207	5.3	5.63	MW	CG	N
1.937	49.20	72985S	2.50	63.5	1.523	38.7	120	21	.94	24	113	501	1.16	29.6	0.207	5.3	5.63	SST	CG	N
1.937	49.20	72994	2.50	63.5	1.487	37.8	194	34	1.2	30	229	1020	1.29	32.9	0.225	5.7	5.75	MW	CG	N
1.937	49.20	72994S	2.50	63.5	1.487	37.8	165	29	.82	21	136	603	1.29	32.9	0.225	5.7	5.75	SST	CG	N
1.937	49.20	73009	2.50	63.5	1.437	36.5	296	52	1.0	25	296	1319	1.50	38.1	0.250	6.4	6.00	MW	CG	N
1.937	49.20	73009S	2.50	63.5	1.437	36.5	252	44	.73	19	184	820	1.50	38.1	0.250	6.4	6.00	SST	CG	N
1.937	49.20	12700	2.59	65.9	1.433	36.4	404	71	.56	14	224	998	1.26	32.0	0.252	6.4	5.00	SPR	CG	Z
1.937	49.20	11804	2.59	65.9	1.433	36.4	605	106	.37	9.4	224	998	1.01	25.6	0.252	6.4	4.00	SPR	CG	Z
1.937	49.20	3406	3.00	76.2	1.767	44.9	4.3	.75	2.5	64	11	48	.49	12.4	0.085	2.2	4.75	SPR	C	Z
1.937	49.20	72935	3.00	76.2	1.641	41.7	33	5.7	2.1	55	70	311	.85	21.6	0.148	3.8	5.75	MW	CG	N
1.937	49.20	72935S	3.00	76.2	1.641	41.7	28	4.8	1.7	43	47	209	.85	21.6	0.148	3.8	5.75	SST	CG	N
1.937	49.20	72946	3.00	76.2	1.625	41.3	40	7.0	2.1	53	83	371	.90	22.8	0.156	4.0	5.75	MW	CG	N
1.937	49.20	72946S	3.00	76.2	1.625	41.3	34	6.0	1.5	39	53	235	.90	22.8	0.156	4.0	5.75	SST	CG	N
1.937	49.20	72961	3.00	76.2	1.613	41.0	44	7.8	2.0	52	90	400	.97	24.7	0.162	4.1	6.00	MW	CG	N
1.937	49.20	72961S	3.00	76.2	1.613	41.0	38	6.6	1.6	40	59	263	.97	24.7	0.162	4.1	6.00	SST	CG	N
1.937	49.20	72968	3.00	76.2	1.583	40.2	61	11	1.9	48	115	512	1.11	28.1	0.177	4.5	6.25	MW	CG	N
1.937	49.20	72968S	3.00	76.2	1.583	40.2	52	9.1	1.5	38	77	341	1.11	28.1	0.177	4.5	6.25	SST	CG	N
1.937	49.20	72978	3.00	76.2	1.553	39.4	82	14	1.8	45	144	639	1.25	31.7	0.192	4.9	6.50	MW	CG	N
1.937	49.20	72978S	3.00	76.2	1.553	39.4	70	12	1.3	33	90	402	1.25	31.7	0.192	4.9	6.50	SST	CG	N
1.937	49.20	72986	3.00	76.2	1.523	38.7	118	21	1.6	40	185	823	1.32	33.5	0.207	5.3	6.38	MW	CG	N
1.937	49.20	72986S	3.00	76.2	1.523	38.7	100	18	1.1	29	113	501	1.32	33.5	0.207	5.3	6.38	SST	CG	N
1.937	49.20	72996	3.00	76.2	1.487	37.8	156	27	1.5	37	229	1020	1.52	38.6	0.225	5.7	6.75	MW	CG	N</

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.937	49.20	72979S	3.50	88.9	1.553	39.4	58	10	1.5	39	90	402	1.42	36.0	0.192	4.9	7.38	SST	CG	N
1.937	49.20	72987	3.50	88.9	1.523	38.7	95	17	1.9	49	185	823	1.53	38.8	0.207	5.3	7.38	MW	CG	N
1.937	49.20	72987S	3.50	88.9	1.523	38.7	81	14	1.4	35	113	501	1.53	38.8	0.207	5.3	7.38	SST	CG	N
1.937	49.20	72998	3.50	88.9	1.487	37.8	131	23	1.8	45	229	1020	1.72	43.6	0.225	5.7	7.63	MW	CG	N
1.937	49.20	72998S	3.50	88.9	1.487	37.8	111	19	1.2	31	136	603	1.72	43.6	0.225	5.7	7.63	SST	CG	N
1.937	49.20	73011	3.50	88.9	1.437	36.5	198	35	1.5	39	303	1346	1.97	50.0	0.250	6.4	7.88	MW	CG	N
1.937	49.20	73011S	3.50	88.9	1.437	36.5	168	29	1.1	28	184	820	1.97	50.0	0.250	6.4	7.88	SST	CG	N
1.937	49.20	72937	4.00	101.6	1.641	41.7	24	4.2	2.9	75	70	311	1.05	26.8	0.148	3.8	7.13	MW	CG	N
1.937	49.20	72937S	4.00	101.6	1.641	41.7	20	3.5	2.3	59	47	209	1.05	26.8	0.148	3.8	7.13	SST	CG	N
1.937	49.20	72950	4.00	101.6	1.625	41.3	29	5.1	2.9	72	83	371	1.11	28.2	0.156	4.0	7.13	MW	CG	N
1.937	49.20	72950S	4.00	101.6	1.625	41.3	25	4.3	2.1	54	53	235	1.11	28.2	0.156	4.0	7.13	SST	CG	N
1.937	49.20	72963	4.00	101.6	1.613	41.0	32	5.7	2.8	71	90	400	1.22	30.9	0.162	4.1	7.50	MW	CG	N
1.937	49.20	72963S	4.00	101.6	1.613	41.0	27	4.8	2.2	55	59	263	1.22	30.9	0.162	4.1	7.50	SST	CG	N
1.937	49.20	72970	4.00	101.6	1.583	40.2	44	7.7	2.6	66	115	511	1.39	35.4	0.177	4.5	7.88	MW	CG	N
1.937	49.20	72970S	4.00	101.6	1.583	40.2	37	6.6	2.0	52	77	341	1.39	35.4	0.177	4.5	7.88	SST	CG	N
1.937	49.20	72980	4.00	101.6	1.553	39.4	59	10	2.4	61	143	637	1.58	40.2	0.192	4.9	8.25	MW	CG	N
1.937	49.20	72980S	4.00	101.6	1.553	39.4	50	8.8	1.8	46	90	402	1.58	40.2	0.192	4.9	8.25	SST	CG	N
1.937	49.20	72988	4.00	101.6	1.523	38.7	82	14	2.3	57	185	823	1.71	43.4	0.207	5.3	8.25	MW	CG	N
1.937	49.20	72988S	4.00	101.6	1.523	38.7	70	12	1.6	41	113	501	1.71	43.4	0.207	5.3	8.25	SST	CG	N
1.937	49.20	73000	4.00	101.6	1.487	37.8	112	20	2.0	52	229	1020	1.91	48.6	0.225	5.7	8.50	MW	CG	N
1.937	49.20	73000S	4.00	101.6	1.487	37.8	95	17	1.4	36	136	603	1.91	48.6	0.225	5.7	8.50	SST	CG	N
1.937	49.20	73012	4.00	101.6	1.437	36.5	169	30	1.8	45	302	1342	2.22	56.4	0.250	6.4	8.88	MW	CG	N
1.937	49.20	73012S	4.00	101.6	1.437	36.5	144	25	1.3	33	184	820	2.22	56.4	0.250	6.4	8.88	SST	CG	N
1.937	49.20	3420	4.44	112.7	1.371	34.8	254	45	1.2	30	304	1352	2.83	71.9	0.283	7.2	10.0	SPR	CG	BO
1.937	49.20	72938	4.50	114.3	1.641	41.7	21	3.7	3.4	85	70	312	1.15	29.1	0.148	3.8	7.75	MW	CG	N
1.937	49.20	72938S	4.50	114.3	1.641	41.7	18	3.1	2.6	67	47	209	1.15	29.1	0.148	3.8	7.75	SST	CG	N
1.937	49.20	72952	4.50	114.3	1.625	41.3	26	4.5	3.2	82	83	371	1.23	31.2	0.156	4.0	7.88	MW	CG	N
1.937	49.20	72952S	4.50	114.3	1.625	41.3	22	3.8	2.4	61	53	235	1.23	31.2	0.156	4.0	7.88	SST	CG	N
1.937	49.20	72964	4.50	114.3	1.613	41.0	28	5.0	3.2	80	90	400	1.34	33.9	0.162	4.1	8.25	MW	CG	N
1.937	49.20	72964S	4.50	114.3	1.613	41.0	24	4.2	2.4	62	59	263	1.34	33.9	0.162	4.1	8.25	SST	CG	N
1.937	49.20	72971	4.50	114.3	1.583	40.2	39	6.8	3.0	76	115	513	1.53	38.8	0.177	4.5	8.63	MW	CG	N
1.937	49.20	72971S	4.50	114.3	1.583	40.2	33	5.8	2.3	59	77	341	1.53	38.8	0.177	4.5	8.63	SST	CG	N
1.937	49.20	72981	4.50	114.3	1.553	39.4	52	9.1	2.8	70	144	642	1.73	43.9	0.192	4.9	9.00	MW	CG	N
1.937	49.20	72981S	4.50	114.3	1.553	39.4	44	7.8	2.0	52	90	402	1.73	43.9	0.192	4.9	9.00	SST	CG	N
1.937	49.20	72989	4.50	114.3	1.523	38.7	72	13	2.6	65	185	823	1.89	48.0	0.207	5.3	9.13	MW	CG	N
1.937	49.20	72989S	4.50	114.3	1.523	38.7	61	11	1.8	47	113	501	1.89	48.0	0.207	5.3	9.13	SST	CG	N
1.937	49.20	73002	4.50	114.3	1.487	37.8	98	17	2.3	59	229	1020	2.14	54.3	0.225	5.7	9.50	MW	CG	N
1.937	49.20	73002S	4.50	114.3	1.487	37.8	84	15	1.6	41	136	603	2.14	54.3	0.225	5.7	9.50	SST	CG	N
1.937	49.20	73013	4.50	114.3	1.437	36.5	148	26	2.0	52	301	1339	2.47	62.7	0.250	6.4	9.88	MW	CG	N
1.937	49.20	73013S	4.50	114.3	1.437	36.5	126	22	1.5	37	184	820	2.47	62.7	0.250	6.4	9.88	SST	CG	N
1.937	49.20	72939	5.00	127.0	1.641	41.7	19	3.3	3.7	95	70	311	1.26	32.0	0.148	3.8	8.50	MW	CG	N
1.937	49.20	72939S	5.00	127.0	1.641	41.7	16	2.8	3.0	75	47	209	1.26	32.0	0.148	3.8	8.50	SST	CG	N
1.937	49.20	72954	5.00	127.0	1.625	41.3	23	4.0	3.6	92	83	371	1.33	33.7	0.156	4.0	8.50	MW	CG	N
1.937	49.20	72954S	5.00	127.0	1.625	41.3	20	3.4	2.7	69	53	235	1.33	33.7	0.156	4.0	8.50	SST	CG	N
1.937	49.20	72965	5.00	127.0	1.613	41.0	25	4.4	3.5	90	90	400	1.46	37.0	0.162	4.1	9.00	MW	CG	N
1.937	49.20	72965S	5.00	127.0	1.613	41.0	22	3.8	2.7	69	59	263	1.46	37.0	0.162	4.1	9.00	SST	CG	N
1.937	49.20	72972	5.00	127.0	1.583	40.2	35	6.1	3.3	84	115	511	1.68	42.7	0.177	4.5	9.50	MW	CG	N
1.937	49.20	72972S	5.00	127.0	1.583	40.2	29	5.2	2.6	66	77	341	1.68	42.7	0.177	4.5	9.50	SST	CG	N
1.937	49.20	72982	5.00	127.0	1.553	39.4	47	8.1	3.1	79	144	642	1.90	48.2	0.192	4.9	9.88	MW	CG	N
1.937	49.20	72982S	5.00	127.0	1.553	39.4	40	6.9	2.3	58	90	402	1.90	48.2	0.192	4.9	9.88	SST	CG	N
1.937	49.20	72990	5.00	127.0	1.523	38.7	64	11	2.9	73	185	823	2.07	52.6	0.207	5.3	10.0	MW	CG	N
1.937	49.20	72990S	5.00	127.0	1.523	38.7	54	9.5	2.1	53	113	501	2.07	52.6	0.207	5.3	10.0	SST	CG	N
1.937	49.20	73004	5.00	127.0	1.487	37.8	88	15	2.6	67	229	1020	2.33	59.3	0.225	5.7	10.4	MW	CG	N
1.937	49.20	73004S	5.00	127.0	1.487	37.8	74	13	1.8	46	136	603	2.33	59.3	0.225	5.7	10.4	SST	CG	N
1.937	49.20	73014	5.00	127.0	1.437	36.5	132	23	2.3	58	301	1337	2.72	69.1	0.250	6.4	10.9	MW	CG	N
1.937	49.20	73014S	5.00	127.0	1.437	36.5	112	20	1.6	42	184	820	2.72	69.1	0.250	6.4	10.9	SST	CG	N
1.937	49.20	11895	5.25	133.4	1.583	40.2	33	5.8	2.6	66	86	384	1.73	43.8	0.177	4.5	9.75	SPR	CG	N
1.937	49.20	72940	5.50	139.7	1.641	41.7	17	3.0	4.1	105	70	312	1.35	34.3	0.148	3.8	9.13	MW	CG	N
1.937	49.20	72940S	5.50	139.7	1.641	41.7	14	2.5	3.3	83	47	209	1.35	34.3	0.148	3.8	9.13	SST	CG	N
1.937	49.20	72956	5.50	139.7	1.625	41.3	21	3.6	4.0	102	83	371	1.44	36.7	0.156	4.0	9.25	MW	CG	N
1.937	49.20	72956S	5.50	139.7	1.625	41.3	18	3.1	3.0	76	53	235	1.44	36.7	0.156	4.0	9.25	SST	CG	N
1.937	49.20	72966	5.50	139.7	1.613	41.0	23	4.0	3.9	100	90	399	1.58	40.1	0.162	4.1	9.75	MW	CG	N
1.937	49.20	72966S	5.50	139.7	1.613	41.0	19	3.4	3.0	77	59	263	1.58	40.1	0.162	4.1	9.75	SST	CG	N
1.937	49.20	72973	5.50	139.7	1.583	40.2	31	5.5	3.7	94	115	511	1.81	46.1	0.177	4.5	10.3	MW	CG	N
1.937	49.20	72973S	5.50	139.7	1.583	40.2	27	4.6	2.9	73	77	341	1.81	46.1	0.177	4.5	10.3	SST	CG	N
1.937	49.20	72983	5.50	139.7	1.553	39.4	42	7.3	3.4	87	144	640	2.06	52.4	0.192	4.9	10.8	MW	CG	N
1.937																				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
1.937	49.20	72992S	6.00	152.4	1.523	38.7	45	7.8	2.5	64	113	501	2.41	61.1	0.207	5.3	11.6	SST	CG	N
1.937	49.20	73008	6.00	152.4	1.487	37.8	72	13	3.2	81	229	1020	2.76	70.0	0.225	5.7	12.3	MW	CG	N
1.937	49.20	73008S	6.00	152.4	1.487	37.8	61	11	2.2	56	136	603	2.76	70.0	0.225	5.7	12.3	SST	CG	N
1.937	49.20	73016	6.00	152.4	1.437	36.5	108	19	2.8	71	300	1334	3.22	81.8	0.250	6.4	12.9	MW	CG	N
1.937	49.20	73016S	6.00	152.4	1.437	36.5	92	16	2.0	51	184	820	3.22	81.8	0.250	6.4	12.9	SST	CG	N
1.937	49.20	S-3191	7.00	177.8	1.711	43.5	3.1	.54	5.4	138	17	75	1.58	40.2	0.113	2.9	13.0	SST	C	N
1.953	49.61	11926	1.50	38.1	1.579	40.1	106	19	.57	14	60	267	.94	23.7	0.187	4.7	5.00	SPR	CG	Z
1.953	49.61	12080	1.56	39.7	1.829	46.5	1.3	.24	1.2	31	1.7	7.4	.33	8.4	0.062	1.6	4.33	SPR	C	Z
1.953	49.61	S-3080	1.88	47.6	1.657	42.1	51	8.9	.91	23	47	207	.59	15.0	0.148	3.8	4.00	SST	CG	N
1.953	49.61	S-92	2.75	69.9	1.579	40.1	139	24	.60	15	83	369	.75	19.0	0.187	4.7	4.00	SST	CG	N
1.953	49.61	S-380	4.13	104.8	1.683	42.7	12	2.2	2.9	73	35	158	1.03	26.1	0.135	3.4	7.67	SST	CG	N
1.953	49.61	11985	4.88	123.8	1.641	41.7	15	2.6	3.0	76	44	196	1.87	47.5	0.156	4.0	12.0	SPR	CG	Z
1.953	49.61	S-3050	5.25	133.4	1.599	40.6	28	4.9	2.7	68	76	339	1.73	43.8	0.177	4.5	9.75	SST	CG	N
1.953	49.61	3375	5.25	133.4	1.329	33.8	385	67	1.0	26	389	1730	3.12	79.2	0.312	7.9	10.0	SPR	CG	Z
1.953	49.61	2687	6.38	161.9	1.599	40.6	19	3.4	3.7	94	72	321	2.66	67.4	0.177	4.5	15.0	HD	CG	Z
1.953	49.61	S-257	6.38	161.9	1.539	39.1	36	6.3	3.1	79	112	497	2.90	73.6	0.207	5.3	14.0	SST	CG	N
1.968	49.99	3376	4.00	101.6	1.594	40.5	104	18	.92	23	96	425	.94	23.7	0.187	4.7	5.00	SPR	CG	Z
1.968	49.99	12626	4.25	108.0	1.83	46.4	12	2.1	3.0	76	35	155	1.05	26.7	.135	3.4	7.75	SST	C	N
1.968	49.99	S-1645	5.50	139.7	1.774	45.1	3.1	.55	4.6	117	14	64	.73	18.5	0.097	2.5	7.50	SST	CG	N
1.968	49.99	4197	8.00	203.2	1.528	38.8	45	7.9	3.3	84	149	661	3.74	95.0	0.220	5.6	16.0	SPR	CG	Z
1.968	49.99	12552	8.00	203.2	1.518	38.6	50	8.7	3.2	81	159	706	3.60	91.4	0.225	5.7	16.0	HD	CG	Z
1.968	49.99	10237	8.00	203.2	1.306	33.2	281	49	1.6	41	458	2037	5.30	134.5	0.331	8.4	16.0	SPR	CG	Z
1.968	49.99	4042	22.0	558.8	1.518	38.6	20	3.6	7.8	197	159	706	8.10	205.7	0.225	5.7	36.0	SPR	CG	Z
1.984	50.39	3170	1.22	31.0	1.756	44.6	15	2.6	.71	18	10	47	.51	13.0	0.114	2.9	4.50	SPR	CG	Z
1.984	50.39	1681	1.25	31.8	1.744	44.3	23	4.0	.77	20	18	79	.48	12.2	0.120	3.0	4.00	SPR	CG	Z
1.984	50.39	S-3071	1.50	38.1	1.774	45.1	15	2.7	1.0	26	16	70	.47	12.0	0.105	2.7	3.50	SST	C	N
1.984	50.39	1875	1.69	42.8	1.704	43.3	88	15	.69	17	61	269	.42	10.7	0.140	3.6	3.00	MW	CG	N
1.984	50.39	4177	2.88	73.0	1.600	40.6	91	16	1.1	29	103	456	1.10	28.0	0.192	4.9	5.75	SPR	CG	Z
2.000	50.80	S-1243	1.75	44.5	1.550	39.4	229	40	.57	15	132	585	1.01	25.7	0.225	5.7	4.50	SST	CG	N
2.000	50.80	S-120	1.88	47.6	1.616	41.0	144	25	.61	15	88	390	.77	19.5	0.192	4.9	4.00	SST	CG	N
2.000	50.80	11050	2.00	50.8	1.514	38.5	370	65	.53	13	196	871	1.09	27.8	0.243	6.2	4.50	HD	CG	Z
2.000	50.80	11247	2.41	61.1	1.836	46.6	4.6	.81	2.1	53	9.6	43	.33	8.3	0.082	2.1	4.00	MW	CG	N
2.000	50.80	S-365	2.50	63.5	1.876	47.7	.68	.12	2.1	53	1.4	6.3	.42	10.6	0.062	1.6	5.75	SST	C	N
2.000	50.80	11991	2.50	63.5	1.620	41.1	74	13	1.3	33	98	434	1.19	30.2	0.190	4.8	6.25	SPR	CG	Z
2.000	50.80	1795	2.94	74.6	1.730	43.9	23	4.0	1.7	43	39	171	.71	18.0	0.135	3.4	5.25	SPR	CG	Z
2.000	50.80	1673	3.50	88.9	1.550	39.4	125	22	1.2	32	156	695	1.63	41.4	0.225	5.7	7.25	HD	CG	Z
2.000	50.80	S-1650	3.63	92.1	1.828	46.4	1.9	.33	3.0	76	5.7	25	.62	15.8	0.086	2.2	7.25	SST	CG	N
2.000	50.80	S-982	3.63	92.1	1.626	41.3	73	13	1.1	28	81	361	1.03	26.1	0.187	4.7	5.50	SST	CG	N
2.000	50.80	4145	4.00	101.6	1.376	35.0	472	83	.81	20	381	1694	2.50	63.4	0.312	7.9	8.00	SPR	CG	Z
2.000	50.80	S-461	4.50	114.3	1.614	41.0	45	7.9	2.0	50	89	396	1.64	41.7	0.193	4.9	8.50	SST	CG	N
2.000	50.80	S-3113	4.63	117.5	1.676	42.6	17	3.0	3.0	76	52	232	1.62	41.1	0.162	4.1	10.0	SST	CG	N
2.000	50.80	1947	5.09	129.4	1.800	45.7	3.9	.68	4.3	108	17	74	.84	21.3	0.100	2.5	7.38	SPR	C	Z
2.000	50.80	11446	5.63	142.9	1.750	44.5	5.9	1.0	4.1	105	24	109	1.50	38.1	0.125	3.2	11.0	SPR	C	Z
2.000	50.80	3094	6.13	155.6	1.830	46.5	1.5	.27	5.4	136	8.2	36	.77	19.4	0.085	2.2	9.00	SPR	CG	GI
2.000	50.80	3485	6.50	165.1	1.730	43.9	11	2.0	3.4	86	39	171	1.28	32.6	0.135	3.4	8.50	HD	C	GI
2.000	50.80	10441	8.00	203.2	1.550	39.4	51	8.9	3.1	78	156	695	3.38	85.7	0.225	5.7	15.0	SPR	CG	N
2.000	50.80	10247	8.50	215.9	1.434	36.4	152	27	1.9	49	295	1314	3.96	100.6	0.283	7.2	14.0	SPR	CG	GI
2.000	50.80	4239	9.25	235.0	1.550	39.4	41	7.2	3.8	96	156	695	4.05	102.9	0.225	5.7	18.0	SPR	CG	Z
2.000	50.80	3489	9.88	250.8	1.476	37.5	76	13	3.1	79	236	1050	4.98	126.4	0.262	6.7	19.0	SPR	CG	Z
2.000	50.80	S-3198	11.0	279.4	1.768	44.9	3.1	.54	7.5	191	23	103	1.54	39.0	0.116	2.9	13.3	SST	CG	N
2.000	50.80	3124	11.1	282.6	1.750	44.5	5.3	.93	5.9	150	32	140	1.50	38.1	0.125	3.2	12.0	SPR	CG	Z
2.000	50.80	4385	11.8	298.5	1.616	41.0	14	2.5	6.9	174	96	429	4.90	124.4	0.192	4.9	25.5	SPR	CG	Z
2.000	50.80	813	12.0	304.8	1.646	41.8	12	2.1	6.8	174	84	373	3.72	94.4	0.177	4.5	21.0	HD	CG	Z
2.000	50.80	806	12.0	304.8	1.586	40.3	22	3.8	5.9	150	127	565	4.81	122.2	0.207	5.3	23.3	HD	CG	Z
2.000	50.80	837	12.0	304.8	1.550	39.4	30	5.2	5.2	133	156	695	5.40	137.2	0.225	5.7	24.0	HD	CG	Z
2.000	50.80	676	12.0	304.8	1.376	35.0	142	25	2.7	68	381	1694	6.86	174.3	0.312	7.9	22.0	SPR	CG	Z
2.015	51.18	S-1665	2.34	59.5	1.565	39.8	175	31	.75	19	131	581	1.18	30.0	0.225	5.7	5.25	SST	CG	N
2.015	51.18	S-1664	2.44	61.9	1.565	39.8	190	33	.69	17	131	581	1.13	28.6	0.225	5.7	5.00	SST	CG	N
2.015	51.18	11975	3.41	86.5	1.745	44.3	14	2.5	2.5	63	35	157	.95	24.0	0.135	3.4	7.00	SPR	CG	Z
2.031	51.59	S-3196	4.66	118.3	1.873	47.6	1.3	.23	4.0	102	5.4	24	.63	16.1	0.079	2.0	7.00	SST	C	N
2.031	51.59	3413	5.25	133.4	1.847	46.9	2.0	.35	4.3	110	8.7	39	.92	23.4	0.092	2.3	9.00	SPR	C	Z
2.031	51.59	4353	6.75	171.5	1.465	37.2	145	25	2.0	51	291	1296	3.79	96.4	0.283	7.2	13.5	SPR	CG	Z
2.046	51.97	11931	1.53	38.9	1.794	45.6	20	3.6	.96	24	20	88	.57	14.4	0.126	3.2	4.50	SPR	CG	Z
2.046	51.97	10651	2.53	64.3	1.522	38.7	434	76	.53	14	231	1028	1.25	31.6	0.262	6.7	4.75	SPR	CG	Z
2.046	51.97	3379	3.13	79.4	1.692	43.0	43	7.6	1.9	48	82	363	1.24	31.5	0.177	4.5	7.00	SPR	CG	GI
2.046	51.97	S-1619	3.75	95.3	1.924	48.9	.75	.13	3.4	88	2.6	12	.31	7.7	0.061	1.5	5.00	SST	CG	N
2.046	51.97	11607	5.63	142.9	1.785	45.3	6.6	1.2	4.1	103	27	119								

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.062	52.37	11730	5.25	133.4	1.890	48.0	1.5	.25	4.5	114	6.5	29	.77	19.7	0.086	2.2	9.00	SPR	CG	GI
2.062	52.37	1839	5.50	139.7	1.918	48.7	.40	.07	4.4	112	1.8	7.8	1.10	27.9	0.072	1.8	14.3	HD	C	Z
2.062	52.37	11905	7.09	180.2	1.708	43.4	23	4.1	3.5	88	81	362	1.95	49.5	0.177	4.5	11.0	SPR	CG	N
2.062	52.37	3259	8.88	225.4	1.538	39.1	116	20	2.2	56	258	1148	3.14	79.9	0.262	6.7	12.0	OT	CG	Z
2.062	52.37	4178	9.00	228.6	1.538	39.1	83	15	2.8	70	229	1021	4.19	106.5	0.262	6.7	16.0	SPR	CG	BO
2.062	52.37	3261	9.00	228.6	1.496	38.0	126	22	2.6	65	323	1438	4.25	107.8	0.283	7.2	15.0	OT	CG	Z
2.062	52.37	3263	9.19	233.4	1.538	39.1	97	17	2.7	68	258	1148	3.67	93.2	0.262	6.7	14.0	OT	CG	Z
2.062	52.37	S-3014	9.75	247.7	1.750	44.5	7.4	1.3	6.7	171	50	221	2.57	65.4	0.156	4.0	16.5	SST	CG	N
2.078	52.78	12073	1.75	44.5	1.942	49.3	1.2	.21	1.4	36	1.7	7.6	.35	8.9	0.068	1.7	5.00	SPR	CG	Z
2.078	52.78	11813	4.34	110.3	1.838	46.7	7.9	1.4	3.4	86	27	120	.84	21.3	0.120	3.0	7.00	SPR	CG	Z
2.078	52.78	S-1661	4.44	112.7	1.870	47.5	4.3	.75	3.8	96	16	72	.68	17.2	0.104	2.6	6.50	SST	CG	N
2.094	53.19	3372	1.38	34.9	1.644	41.8	564	99	.27	6.7	150	666	.68	17.1	0.225	5.7	3.00	SPR	CG	Z
2.094	53.19	11715	1.75	44.5	1.956	49.7	1.3	.23	1.4	36	1.8	8.2	.35	8.8	0.069	1.8	5.00	SPR	CG	GI
2.094	53.19	4298	2.25	57.2	1.854	47.1	14	2.5	1.7	43	24	105	.57	14.5	0.120	3.0	4.75	SPR	CG	Z
2.094	53.19	11869	2.53	64.3	1.782	45.3	19	3.3	1.4	35	26	114	1.17	29.7	0.156	4.0	7.50	SST	CG	N
2.094	53.19	10400	4.50	114.3	1.798	45.7	17	3.0	2.8	72	48	215	1.11	28.2	0.148	3.8	7.50	SPR	CG	Z
2.109	53.57	3229	1.06	27.0	1.721	43.7	193	34	.38	9.7	74	329	.68	17.2	0.194	4.9	3.50	SPR	CG	Z
2.109	53.57	S-389	1.38	34.9	1.585	40.3	703	123	.26	6.7	186	826	.89	22.6	0.262	6.7	3.38	SST	CG	N
2.109	53.57	2754	1.50	38.1	1.869	47.5	38	6.6	.98	25	37	165	.36	9.1	0.120	3.0	3.00	MW	CG	Z
2.109	53.57	12083	1.66	42.1	1.899	48.2	14	2.5	1.3	32	18	82	.37	9.3	0.105	2.7	3.50	SPR	CG	Z
2.109	53.57	S-1644	2.06	52.4	1.785	45.3	28	4.9	1.0	27	29	131	1.01	25.7	0.162	4.1	6.25	SST	CG	N
2.109	53.57	3452	2.25	57.2	1.925	48.9	4.2	.73	1.8	45	7.5	33	.46	11.7	0.092	2.3	5.00	SPR	CG	Z
2.109	53.57	S-1674	2.50	63.5	1.989	50.5	.55	.10	2.1	54	1.2	5.2	.39	9.9	0.060	1.5	5.50	SST	C	N
2.109	53.57	2688	2.88	73.0	1.705	43.3	86	15	1.3	33	112	500	1.21	30.8	0.202	5.1	6.00	SPR	CG	Z
2.109	53.57	1615	2.91	73.8	1.321	33.6	1962	344	.35	8.8	677	3012	2.17	55.0	0.394	10.0	5.50	SPR	CG	Z
2.109	53.57	11849	4.63	117.5	1.917	48.7	3.8	.66	3.4	88	13	58	.62	15.8	0.096	2.4	5.50	SST	C	N
2.109	53.57	S-152	4.84	123.0	1.927	48.9	2.6	.46	4.3	109	11	50	.55	13.9	0.091	2.3	6.00	SST	CG	N
2.109	53.57	S-3023	5.50	139.7	1.749	44.4	17	3.0	3.3	83	57	252	2.25	57.2	0.180	4.6	12.5	SST	CG	N
2.109	53.57	S-3236	6.03	153.2	1.899	48.2	3.8	.66	4.5	115	17	76	.81	20.7	0.105	2.7	7.75	SST	CG	N
2.109	53.57	12627	8.50	215.9	1.649	41.9	56	9.9	2.8	71	159	706	2.93	74.5	0.230	5.8	12.8	SPR	CG	N
2.125	53.98	S-3151	.69	17.4	1.875	47.6	76	13	.25	6.3	19	85	.44	11.1	0.125	3.2	2.50	SST	C	N
2.125	53.98	S-3072	3.63	92.1	1.813	46.1	1.6	2.8	2.4	60	38	171	1.25	31.7	0.156	4.0	8.00	SST	CG	N
2.125	53.98	10607	5.38	136.5	1.915	48.6	21	.37	4.1	105	8.6	38	1.26	32.0	0.105	2.7	11.0	SST	C	N
2.125	53.98	11860	5.38	136.5	1.899	48.2	5.5	.96	4.0	102	22	98	.93	23.7	0.113	2.9	7.25	SPR	C	N
2.125	53.98	S-3168	5.50	139.7	1.899	48.2	5.0	.88	4.0	102	20	89	.79	20.1	0.113	2.9	7.00	SST	CG	N
2.125	53.98	S-3213	5.66	143.7	1.859	47.2	6.1	1.1	4.3	109	26	117	1.36	34.6	0.133	3.4	10.3	SST	CG	N
2.125	53.98	12054	6.03	153.2	1.915	48.6	3.3	.57	5.2	132	17	75	.81	20.7	0.105	2.7	7.75	SST	CG	N
2.125	53.98	4332	6.50	165.1	1.511	38.4	202	35	1.7	43	344	1531	3.84	97.5	0.307	7.8	12.5	SPR	CG	Z
2.125	53.98	S-1640	6.75	171.5	1.813	46.1	13	2.3	3.7	93	48	215	1.48	37.6	0.156	4.0	9.50	SST	CG	N
2.125	53.98	S-3093	7.00	177.8	1.941	49.3	2.8	.50	4.0	102	11	51	.62	15.8	0.092	2.3	5.75	SST	C	N
2.125	53.98	S-3161	7.00	177.8	1.855	47.1	7.0	1.2	4.7	118	33	145	1.42	36.0	0.135	3.4	9.50	SST	C	N
2.140	54.36	S-2111	2.34	59.5	1.984	50.4	1.7	.29	1.9	49	3.2	14	.41	10.4	0.078	2.0	5.25	SST	CG	N
2.140	54.36	S-89	2.63	66.7	1.700	43.2	83	14	1.1	28	90	399	1.54	39.1	0.220	5.6	7.00	SST	CG	N
2.140	54.36	S-101	3.13	79.4	1.828	46.4	31	5.4	1.6	40	48	213	.78	19.7	0.156	4.0	5.00	SST	CG	N
2.140	54.36	S-3073	3.25	82.6	1.766	44.9	34	6.0	1.8	45	60	267	1.50	38.0	0.187	4.7	8.00	SST	CG	N
2.140	54.36	11604	3.50	88.9	2.006	51.0	.81	.14	3.0	77	2.5	11	.47	11.9	0.067	1.7	6.00	SPR	CG	Z
2.140	54.36	S-174	4.38	111.1	1.920	48.8	6.3	1.1	2.9	75	18	82	.61	15.4	0.110	2.8	5.50	SST	CG	N
2.140	54.36	S-447	5.16	131.0	1.930	49.0	6.0	1.1	2.8	71	17	75	.53	13.3	0.105	2.7	5.00	SST	C	N
2.140	54.36	1841	5.75	146.1	1.936	49.2	3.7	.64	4.9	125	18	81	.82	20.7	0.102	2.6	7.00	MW	C	Z
2.140	54.36	S-258	6.38	161.9	1.890	48.0	4.1	.73	5.0	127	21	92	1.38	34.9	0.125	3.2	11.0	SST	CG	N
2.140	54.36	S-3019	8.88	225.4	1.780	45.2	15	2.5	4.7	119	68	302	2.52	64.0	0.180	4.6	14.0	SST	CG	N
2.140	54.36	4101	9.00	228.6	1.516	38.5	127	22	2.8	71	359	1595	6.08	154.5	0.312	7.9	19.5	SPR	CG	Z
2.156	54.76	11786	1.47	37.3	2.000	50.8	4.0	.69	1.2	30	4.7	21	.27	6.9	0.078	2.0	3.50	SPR	CG	N
2.156	54.76	S-3036	5.50	139.7	1.886	47.9	6.3	1.1	4.2	105	26	116	1.35	34.3	0.135	3.4	10.0	SST	CG	N
2.172	55.17	11823	5.75	146.1	1.962	49.8	3.5	.61	4.7	120	17	74	.74	18.7	0.105	2.7	7.00	SST	CG	N
2.187	55.55	3493	1.75	44.5	1.927	48.9	16	2.8	1.1	28	17	77	.65	16.5	0.130	3.3	5.00	SPR	CG	Z
2.187	55.55	3059	2.13	54.0	1.917	48.7	26	4.6	1.4	34	35	157	.56	14.1	0.135	3.4	4.00	SPR	CG	GI
2.187	55.55	73017	4.00	101.6	1.773	45.0	68	12	1.9	49	131	584	1.45	36.8	0.207	5.3	7.00	OT	CG	N
2.187	55.55	73024	4.00	101.6	1.751	44.5	81	14	1.9	48	153	680	1.58	40.2	0.218	5.5	7.25	OT	CG	N
2.187	55.55	73031	4.00	101.6	1.687	42.8	134	24	1.6	42	220	980	1.94	49.2	0.250	6.4	7.75	OT	CG	N
2.187	55.55	73038	4.00	101.6	1.625	41.3	216	38	1.4	35	300	1335	2.25	57.1	0.281	7.1	8.00	OT	CG	N
2.187	55.55	73045	4.00	101.6	1.563	39.7	344	60	1.1	29	396	1759	2.50	63.4	0.312	7.9	8.00	OT	CG	N
2.187	55.55	73052	4.00	101.6	1.501	38.1	552	97	.92	23	508	2261	2.66	67.5	0.343	8.7	7.75	OT	CG	N
2.187	55.55	73059	4.00	101.6	1.437	36.5	831	146	.79	20	657	2922	2.91	73.8	0.375	9.5	7.75	OT	CG	N
2.187	55.55	73066	4.00	101.6	1.401	35.6	1080	189	.68	17	733	3262	2.95	74.9	0.393	10.0	7.50	OT	CG	N
2.187	55.55	S-1641	4.09	104.0	1.813	46.1	41	7.2	1.8	46	74	331	1.26	32.1	0.187	4.7	6.75	SST	CG	N
2.187	55.55	S-113	5.00	127.0	1.977	50.2	2.8	.49	4.1	103	11	51	.95	24.0						




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.187	55.55	73040	6.00	152.4	1.625	41.3	136	24	2.2	56	300	1335	3.23	82.1	0.281	7.1	11.5	OT	CG	N
2.187	55.55	73047	6.00	152.4	1.563	39.7	218	38	1.8	46	396	1759	3.59	91.1	0.312	7.9	11.5	OT	CG	N
2.187	55.55	73054	6.00	152.4	1.501	38.1	343	60	1.5	38	508	2261	3.86	98.0	0.343	8.7	11.3	OT	CG	N
2.187	55.55	73061	6.00	152.4	1.437	36.5	514	90	1.3	32	657	2922	4.24	107.6	0.375	9.5	11.3	OT	CG	N
2.187	55.55	73068	6.00	152.4	1.401	35.6	664	116	1.1	28	733	3262	4.30	109.3	0.393	10.0	11.0	OT	CG	N
2.187	55.55	3074	6.38	161.9	2.043	51.9		.68 .12	5.7	145		3.9 17	.65	16.5	0.072	1.8	8.00	SPR	C	Z
2.187	55.55	73020	7.00	177.8	1.773	45.0	38	6.6	3.5	88	131	584	2.28	57.9	0.207	5.3	11.0	OT	CG	N
2.187	55.55	73027	7.00	177.8	1.751	44.5	44	7.6	3.5	89	153	680	2.56	65.1	0.218	5.5	11.8	OT	CG	N
2.187	55.55	73034	7.00	177.8	1.687	42.8	72	13	3.1	78	220	980	3.19	80.9	0.250	6.4	12.7	OT	CG	N
2.187	55.55	73041	7.00	177.8	1.625	41.3	115	20	2.6	66	300	1335	3.72	94.6	0.281	7.1	13.3	OT	CG	N
2.187	55.55	73048	7.00	177.8	1.563	39.7	183	32	2.2	55	396	1759	4.15	105.4	0.312	7.9	13.3	OT	CG	N
2.187	55.55	73055	7.00	177.8	1.501	38.1	289	51	1.8	45	508	2261	4.46	113.2	0.343	8.7	13.0	OT	CG	N
2.187	55.55	73062	7.00	177.8	1.437	36.5	432	76	1.5	39	657	2922	4.90	124.4	0.375	9.5	13.1	OT	CG	N
2.187	55.55	73069	7.00	177.8	1.401	35.6	559	98	1.3	33	733	3262	4.96	126.0	0.393	10.0	12.6	OT	CG	N
2.187	55.55	73021	8.00	203.2	1.773	45.0	32	5.7	4.1	103	131	584	2.59	65.9	0.207	5.3	12.5	OT	CG	N
2.187	55.55	73028	8.00	203.2	1.751	44.5	38	6.6	4.0	103	153	680	2.89	73.4	0.218	5.5	13.3	OT	CG	N
2.187	55.55	73035	8.00	203.2	1.687	42.8	62	11	3.6	91	220	980	3.63	92.1	0.250	6.4	14.5	OT	CG	N
2.187	55.55	73042	8.00	203.2	1.625	41.3	100	17	3.0	77	300	1335	4.21	107.0	0.281	7.1	15.0	OT	CG	N
2.187	55.55	73049	8.00	203.2	1.563	39.7	157	28	2.5	64	396	1759	4.72	119.9	0.312	7.9	15.1	OT	CG	N
2.187	55.55	73056	8.00	203.2	1.501	38.1	249	44	2.0	52	508	2261	5.06	128.5	0.343	8.7	14.7	OT	CG	N
2.187	55.55	73063	8.00	203.2	1.437	36.5	372	65	1.8	45	657	2922	5.57	141.5	0.375	9.5	14.9	OT	CG	N
2.187	55.55	73070	8.00	203.2	1.401	35.6	480	84	1.5	39	733	3262	5.65	143.5	0.393	10.0	14.4	OT	CG	N
2.187	55.55	73022	9.00	228.6	1.773	45.0	28	5.0	4.6	118	131	584	2.90	73.7	0.207	5.3	14.0	OT	CG	N
2.187	55.55	73029	9.00	228.6	1.751	44.5	33	5.8	4.6	117	153	680	3.22	81.8	0.218	5.5	14.8	OT	CG	N
2.187	55.55	73036	9.00	228.6	1.687	42.8	55	9.7	4.0	101	220	980	4.00	101.6	0.250	6.4	16.0	OT	CG	N
2.187	55.55	73043	9.00	228.6	1.625	41.3	88	15	3.4	87	300	1335	4.70	119.5	0.281	7.1	16.7	OT	CG	N
2.187	55.55	73050	9.00	228.6	1.563	39.7	139	24	2.8	72	396	1759	5.27	133.7	0.312	7.9	16.9	OT	CG	N
2.187	55.55	73057	9.00	228.6	1.501	38.1	219	38	2.3	59	508	2261	5.66	143.8	0.343	8.7	16.5	OT	CG	N
2.187	55.55	73064	9.00	228.6	1.437	36.5	327	57	2.0	51	657	2922	6.23	158.4	0.375	9.5	16.6	OT	CG	N
2.187	55.55	73071	9.00	228.6	1.401	35.6	422	74	1.7	44	733	3262	6.32	160.4	0.393	10.0	16.1	OT	CG	N
2.187	55.55	73023	10.0	254.0	1.773	45.0	26	4.5	5.1	130	131	584	3.16	80.3	0.207	5.3	15.3	OT	CG	N
2.187	55.55	73030	10.0	254.0	1.751	44.5	30	5.2	5.1	130	153	680	3.55	90.1	0.218	5.5	16.3	OT	CG	N
2.187	55.55	73037	10.0	254.0	1.687	42.8	50	8.7	4.4	112	220	980	4.38	111.2	0.250	6.4	17.5	OT	CG	N
2.187	55.55	73044	10.0	254.0	1.625	41.3	78	14	3.8	97	300	1335	5.20	132.1	0.281	7.1	18.5	OT	CG	N
2.187	55.55	73051	10.0	254.0	1.563	39.7	124	22	3.2	81	396	1759	5.81	147.6	0.312	7.9	18.6	OT	CG	N
2.187	55.55	73058	10.0	254.0	1.501	38.1	195	34	2.6	66	508	2261	6.26	159.0	0.343	8.7	18.2	OT	CG	N
2.187	55.55	73065	10.0	254.0	1.437	36.5	292	51	2.3	57	657	2922	6.89	175.0	0.375	9.5	18.4	OT	CG	N
2.187	55.55	73072	10.0	254.0	1.401	35.6	376	66	2.0	50	733	3262	7.00	177.7	0.393	10.0	17.8	OT	CG	N
2.203	55.96	4276	5.00	127.0	1.933	49.1	10	1.8	3.4	87	35	156	.98	24.9	0.135	3.4	7.25	SPR	CG	Z
2.219	56.36	3072	1.38	34.9	1.695	43.1	904	158	.24	6.0	214	954	.79	20.0	0.262	6.7	3.00	SPR	CG	Z
2.219	56.36	12615	1.75	44.5	2.035	51.7	4.7	.81	1.3	33	6.0	27	.46	11.7	0.092	2.3	4.00	SST	C	Z
2.219	56.36	11297	3.75	95.3	1.907	48.4	24	4.2	2.2	55	52	232	.94	23.8	0.156	4.0	6.00	SPR	CG	Z
2.219	56.36	4227	5.75	146.1	1.949	49.5	10	1.8	3.5	88	35	155	.98	24.9	0.135	3.4	7.25	SPR	CG	Z
2.234	56.74	3205	5.00	127.0	1.820	46.2	47	8.2	2.4	62	114	509	1.81	46.0	0.207	5.3	8.75	SPR	CG	Z
2.250	57.15	S-3219	2.09	53.2	1.954	49.6	15	2.7	1.2	30	18	81	.93	23.5	0.148	3.8	6.25	SST	CG	N
2.250	57.15	S-3215	3.25	82.6	2.040	51.8	6.3	1.1	2.6	65	16	71	.47	12.0	0.105	2.7	4.50	SST	CG	N
2.250	57.15	4394	5.25	133.4	1.750	44.5	134	23	1.4	36	191	848	1.81	46.0	0.250	6.4	7.25	SPR	CG	Z
2.250	57.15	4366	5.75	146.1	1.374	34.9	1046	183	.81	21	845	3759	4.60	116.8	0.438	11.1	10.5	SPR	CG	Z
2.250	57.15	4218	7.00	177.8	1.926	48.9	15	2.6	3.8	98	58	256	1.50	38.1	0.162	4.1	9.25	SPR	CG	N
2.250	57.15	S-355	7.50	190.5	1.980	50.3	4.1	.71	5.6	143	23	102	1.86	47.1	0.135	3.4	12.8	SST	C	N
2.250	57.15	1935	8.13	206.4	1.836	46.6	31	5.4	3.7	93	114	505	2.48	63.1	0.207	5.3	12.0	SPR	CG	Z
2.250	57.15	S-354	9.25	235.0	2.010	51.1	2.2	.39	7.6	192	17	75	1.68	42.7	0.120	3.0	14.0	SST	CG	N
2.250	57.15	10161	9.50	241.3	1.726	43.8	72	13	2.9	75	212	942	3.67	93.2	0.262	6.7	14.0	SPR	CG	N
2.250	57.15	10275	9.50	241.3	1.684	42.8	105	18	2.5	64	265	1180	3.82	97.1	0.283	7.2	13.5	SPR	CG	Z
2.250	57.15	7013	10.0	254.0	1.500	38.1	250	44	2.3	58	570	2534	7.70	195.6	0.375	9.5	19.3	HD	C	Z
2.250	57.15	10692	14.0	355.6	1.876	47.7	9.0	1.6	9.3	236	83	371	4.72	119.9	0.187	4.7	24.3	SPR	C	Z
2.250	57.15	7015	16.0	406.4	1.500	38.1	150	26	3.8	96	570	2534	12.0	304.8	0.375	9.5	30.8	HD	C	Z
2.266	57.56	S-1660	2.78	70.6	1.832	46.5	110	19	1.0	26	112	497	1.09	27.6	0.217	5.5	5.00	SST	CG	N
2.281	57.94	S-1646	1.38	34.9	1.987	50.5	46	8.1	.85	22	39	175	.49	12.4	0.147	3.7	3.33	SST	CG	N
2.281	57.94	10272	9.50	241.3	1.715	43.6	108	19	2.4	62	262	1165	3.61	91.6	0.283	7.2	12.8	SPR	CG	Z
2.296	58.32	10984	1.94	49.2	1.796	45.6	219	38	.69	17	150	669	1.25	31.8	0.250	6.4	5.00	HD	CG	N
2.296	58.32	S-1629	8.09	205.6	2.058	52.3	3.3	.58	6.6	167	22	97	1.13	28.7	0.119	3.0	9.50	SST	CG	N
2.296	58.32	S-1659	10.4	263.5	2.058	52.3	3.1	.54	7.0	178	22	97	1.19	30.2	0.119	3.0	10.0	SST	CG	N
2.312	58.72	12082	1.97	50.0	2.188	55.6	.47	.08	1.5	39	.72	3.2	.43	11.0	0.062	1.6	6.00	SPR	C	Z
2.312	58.72	4198	3.00	76.2	2.122	53.9	2.1	.38	2.2	57	4.8	21	.76	19.3	0.095	2.4	7.00	SPR	C	Z
2.312	58.72	4354	3.25	82.6	1.588	40.3	888	155	.57	14	502	2235	2.08	52.9	0.362	9.2	5.75</			

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.343	59.51	3488	7.00	177.8	2.019	51.3	11	1.9	5.1	128	54	238	1.94	49.4	0.162	4.1	11.0	SPR	C	Z
2.343	59.51	10271	8.00	203.2	1.681	42.7	242	42	1.6	41	392	1744	3.56	90.4	0.331	8.4	10.8	SPR	CG	Z
2.343	59.51	S-376	8.25	209.6	1.779	45.2	72	13	2.9	73	209	929	4.09	103.9	0.282	7.2	14.5	SST	CG	N
2.359	59.92	10440	3.09	78.6	1.793	45.5	344	60	.74	19	254	1129	1.42	35.9	0.283	7.2	5.00	SPR	CG	N
2.359	59.92	S-427	4.88	123.8	1.909	48.5	51	8.9	2.2	56	113	501	1.91	48.6	0.225	5.7	8.50	SST	CG	N
2.375	60.33	10367	3.00	76.2	1.875	47.6	146	26	1.2	31	181	806	1.50	38.1	0.250	6.4	6.00	SPR	CG	Z
2.375	60.33	S-1662	4.16	105.6	2.063	52.4	12	2.0	2.9	74	33	149	1.25	31.7	0.156	4.0	8.00	SST	CG	N
2.375	60.33	S-1654	4.44	112.7	2.063	52.4	15	2.5	3.0	76	43	193	1.05	26.7	0.156	4.0	6.75	SST	CG	N
2.375	60.33	4006	4.75	120.7	1.501	38.1	1200	210	.67	17	802	3569	3.50	88.8	0.437	11.1	8.00	SPR	CG	BO
2.375	60.33	S-315	4.94	125.4	2.165	55.0	3.2	.57	4.3	109	14	62	.63	16.0	0.105	2.7	6.00	SST	CG	N
2.375	60.33	S-318	5.75	146.1	2.165	55.0	2.7	.48	5.0	128	14	61	.71	18.0	0.105	2.7	6.75	SST	CG	N
2.375	60.33	S-3094	6.63	168.3	2.063	52.4	14	2.4	3.2	82	43	193	1.04	26.4	0.156	4.0	6.75	SST	CG	N
2.375	60.33	4326	7.50	190.5	2.051	52.1	12	2.1	4.5	114	55	243	1.54	39.1	0.162	4.1	9.50	SPR	CG	Z
2.375	60.33	12043	9.56	242.9	2.079	52.8	6.9	1.2	6.2	157	43	191	1.63	41.4	0.148	3.8	11.0	SPR	CG	Z
2.375	60.33	S-137	11.8	298.5	2.063	52.4	5.4	.95	8.0	203	43	193	2.26	57.5	0.156	4.0	14.5	SST	CG	N
2.375	60.33	4405	11.8	298.5	1.751	44.5	113	20	2.9	73	326	1451	4.91	124.8	0.312	7.9	15.8	SPR	CG	Z
2.390	60.71	4168	3.13	79.4	2.036	51.7	43	7.6	1.6	41	71	314	.89	22.5	0.177	4.5	5.00	SPR	CG	Z
2.406	61.11	S-149	2.13	54.0	2.110	53.6	19	3.3	1.4	37	27	122	.69	17.4	0.148	3.8	4.67	SST	CG	N
2.406	61.11	11573	3.06	77.8	2.242	56.9	3.5	.60	2.3	59	8.1	36	.37	9.4	0.082	2.1	3.50	SPR	C	N
2.406	61.11	4112	3.13	79.4	2.052	52.1	42	7.4	1.7	42	70	312	.89	22.5	0.177	4.5	5.00	SPR	CG	Z
2.406	61.11	S-986	3.16	80.2	1.992	50.6	65	11	1.4	36	92	408	1.10	28.0	0.207	5.3	5.33	SST	CG	N
2.406	61.11	10582	3.75	95.3	1.876	47.7	161	28	1.3	33	206	914	1.72	43.8	0.265	6.7	6.50	SPR	CG	N
2.406	61.11	10278	4.00	101.6	1.882	47.8	153	27	1.3	33	199	884	1.70	43.3	0.262	6.7	6.50	SPR	CG	N
2.406	61.11	S-161	4.13	104.8	2.094	53.2	11	1.9	2.9	73	31	139	1.25	31.7	0.156	4.0	8.00	SST	CG	N
2.406	61.11	S-964	4.88	123.8	2.196	55.8	3.1	.55	4.1	105	13	57	.74	18.7	0.105	2.7	6.00	SST	C	N
2.406	61.11	11506	5.13	130.2	1.972	50.1	51	8.9	2.4	61	122	545	1.95	49.6	0.217	5.5	8.00	SPR	CG	Z
2.406	61.11	S-396	7.00	177.8	2.166	55.0	3.7	.65	5.8	146	21	95	.95	24.0	0.120	3.0	8.00	SST	CG	N
2.406	61.11	S-3098	16.0	406.4	2.094	53.2	5.9	1.0	7.2	183	43	191	2.08	52.8	0.156	4.0	13.3	SST	CG	N
2.421	61.49	10276	3.00	76.2	1.855	47.1	252	44	.99	25	248	1102	1.63	41.3	0.283	7.2	5.75	SPR	CG	N
2.437	61.90	4203	3.00	76.2	2.083	52.9	41	7.1	1.7	43	69	308	.89	22.5	0.177	4.5	5.00	SPR	CG	Z
2.437	61.90	73073	4.00	101.6	1.875	47.6	170	30	1.6	41	271	1207	2.04	51.8	0.281	7.1	7.26	OT	CG	N
2.437	61.90	73079	4.00	101.6	1.813	46.1	270	47	1.3	34	358	1594	2.26	57.5	0.312	7.9	7.26	OT	CG	N
2.437	61.90	73085	4.00	101.6	1.751	44.5	412	72	1.1	28	461	2052	2.49	63.3	0.343	8.7	7.26	OT	CG	N
2.437	61.90	73091	4.00	101.6	1.713	43.5	526	92	1.0	26	539	2399	2.63	66.7	0.362	9.2	7.25	OT	CG	N
2.437	61.90	73097	4.00	101.6	1.687	42.8	617	108	.97	25	597	2657	2.72	69.1	0.375	9.5	7.26	OT	CG	N
2.437	61.90	73103	4.00	101.6	1.651	41.9	765	134	.87	22	668	2970	2.85	72.4	0.393	10.0	7.25	OT	CG	N
2.437	61.90	73109	4.00	101.6	1.625	41.3	932	163	.79	20	733	3261	2.84	72.2	0.406	10.3	7.00	OT	CG	N
2.437	61.90	73115	4.00	101.6	1.563	39.7	1310	229	.67	17	883	3929	3.06	77.7	0.437	11.1	7.00	OT	CG	N
2.437	61.90	73074	5.00	127.0	1.875	47.6	132	23	2.1	52	271	1207	2.47	62.6	0.281	7.1	8.78	OT	CG	N
2.437	61.90	73080	5.00	127.0	1.813	46.1	210	37	1.7	43	358	1594	2.73	69.4	0.312	7.9	8.76	OT	CG	N
2.437	61.90	73086	5.00	127.0	1.751	44.5	315	55	1.5	37	461	2052	3.05	77.4	0.343	8.7	8.88	OT	CG	N
2.437	61.90	73092	5.00	127.0	1.713	43.5	402	70	1.3	34	539	2399	3.21	81.6	0.362	9.2	8.87	OT	CG	N
2.437	61.90	73098	5.00	127.0	1.687	42.8	472	83	1.3	32	597	2657	3.33	84.5	0.375	9.5	8.87	OT	CG	N
2.437	61.90	73104	5.00	127.0	1.651	41.9	584	102	1.1	29	668	2970	3.49	88.6	0.393	10.0	8.88	OT	CG	N
2.437	61.90	73110	5.00	127.0	1.625	41.3	704	123	1.0	26	733	3261	3.50	88.9	0.406	10.3	8.62	OT	CG	N
2.437	61.90	73116	5.00	127.0	1.563	39.7	989	173	.89	23	883	3929	3.77	95.7	0.437	11.1	8.63	OT	CG	N
2.437	61.90	3110	5.13	130.2	2.125	54.0	17	3.0	2.8	72	48	212	.98	24.8	0.156	4.0	6.25	SPR	CG	Z
2.437	61.90	73075	6.00	152.4	1.875	47.6	108	19	2.5	64	271	1207	2.89	73.4	0.281	7.1	10.3	OT	CG	N
2.437	61.90	73081	6.00	152.4	1.813	46.1	169	30	2.1	54	358	1594	3.24	82.4	0.312	7.9	10.4	OT	CG	N
2.437	61.90	73087	6.00	152.4	1.751	44.5	255	45	1.8	46	461	2052	3.60	91.5	0.343	8.7	10.5	OT	CG	N
2.437	61.90	73093	6.00	152.4	1.713	43.5	325	57	1.7	42	539	2399	3.80	96.6	0.362	9.2	10.5	OT	CG	N
2.437	61.90	73099	6.00	152.4	1.687	42.8	381	67	1.6	40	597	2657	3.94	100.1	0.375	9.5	10.5	OT	CG	N
2.437	61.90	73105	6.00	152.4	1.651	41.9	472	83	1.4	36	668	2970	4.13	104.9	0.393	10.0	10.5	OT	CG	N
2.437	61.90	73111	6.00	152.4	1.625	41.3	574	101	1.3	32	733	3261	4.11	104.4	0.406	10.3	10.1	OT	CG	N
2.437	61.90	73117	6.00	152.4	1.563	39.7	794	139	1.1	28	883	3929	4.48	113.8	0.437	11.1	10.3	OT	CG	N
2.437	61.90	73076	7.00	177.8	1.875	47.6	92	16	3.0	75	271	1207	3.29	83.7	0.281	7.1	11.7	OT	CG	N
2.437	61.90	73082	7.00	177.8	1.813	46.1	142	25	2.5	64	358	1594	3.74	95.1	0.312	7.9	12.0	OT	CG	N
2.437	61.90	73088	7.00	177.8	1.751	44.5	217	38	2.1	54	461	2052	4.11	104.4	0.343	8.7	12.0	OT	CG	N
2.437	61.90	73094	7.00	177.8	1.713	43.5	273	48	2.0	50	539	2399	4.39	111.5	0.362	9.2	12.1	OT	CG	N
2.437	61.90	73100	7.00	177.8	1.687	42.8	320	56	1.9	47	597	2657	4.55	115.6	0.375	9.5	12.1	OT	CG	N
2.437	61.90	73106	7.00	177.8	1.651	41.9	396	69	1.7	43	668	2970	4.77	121.2	0.393	10.0	12.1	OT	CG	N
2.437	61.90	73112	7.00	177.8	1.625	41.3	478	84	1.5	39	733	3261	4.77	121.2	0.406	10.3	11.8	OT	CG	N
2.437	61.90	73118	7.00	177.8	1.563	39.7	664	116	1.3	34	883	3929	5.19	131.7	0.437	11.1	11.9	OT	CG	N
2.437	61.90	10236	7.75	196.9	1.847	46.9	138	24	2.0	51	278	1237	2.95	74.9	0.295	7.5	10.0	SPR	CG	N
2.437	61.90	S-3232	7.88	200.0	2.137	54.3	11	2.0	3.3	84	38	168	1.01	25.7	0.150	3.8	6.75	SST	CG	N
2.437	61.90	73077	8.00	203.2	1.875	47.6	79	14	3.4	87	271	1207	3.74	95.1	0.281	7.1	13.3	OT		




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.437	61.90	73120	10.0	254.0	1.563	39.7	448	78	2.0	50	883	3929	7.27	184.6	0.437	11.1	16.6	OT	CG	N
2.437	61.90	3483	10.8	273.1	1.987	50.5	28	5.0	4.6	116	130	577	3.15	80.0	0.225	5.7	14.0	SPR	CG	Z
2.437	61.90	10163	11.0	279.4	1.813	46.1	105	18	3.0	77	319	1417	4.84	122.8	0.312	7.9	15.5	SPR	CG	N
2.468	62.69	4185	3.75	95.3	2.132	54.2	24	4.1	2.5	63	59	261	1.01	25.6	0.168	4.3	6.00	SPR	CG	Z
2.468	62.69	4129	6.75	171.5	2.054	52.2	23	4.0	4.3	108	97	433	2.48	63.1	0.207	5.3	12.0	SPR	CG	Z
2.468	62.69	4379	7.50	190.5	1.806	45.9	262	46	1.4	36	374	1664	2.90	73.6	0.331	8.4	8.75	SPR	CG	N
2.500	63.50	11956	2.22	56.4	2.174	55.2	32	5.6	1.5	38	47	210	.73	18.6	0.163	4.1	4.50	SPR	CG	Z
2.500	63.50	10941	4.00	101.6	1.376	35.0	5254	920	.28	7.2	1483	6595	3.23	82.1	0.562	14.3	5.75	SPR	CG	N
2.500	63.50	12591	5.00	127.0	2.202	55.9	11	1.9	3.8	97	42	185	1.19	30.3	0.149	3.8	7.00	SPR	C	N
2.500	63.50	4313	5.50	139.7	2.000	50.8	99	17	1.8	44	173	768	1.75	44.5	0.250	6.4	7.00	SPR	CG	Z
2.500	63.50	10286	6.50	165.1	1.812	46.0	259	45	1.6	40	404	1797	3.35	85.2	0.344	8.7	9.75	SPR	CG	Z
2.500	63.50	10238	7.75	196.9	1.888	48.0	140	25	2.1	53	294	1307	3.21	81.6	0.306	7.8	10.5	SPR	CG	N
2.500	63.50	10310	9.63	244.5	1.776	45.1	235	41	2.0	51	469	2084	4.62	117.2	0.362	9.2	12.8	SPR	CG	N
2.500	63.50	S-1639	10.5	266.7	2.030	51.6	20	3.6	6.0	152	121	539	4.35	110.4	0.235	6.0	18.5	SST	CG	N
2.500	63.50	S-3082	17.0	431.8	2.188	55.6	2.6	.45	13	332	34	149	3.93	99.7	0.156	4.0	25.0	SST	CG	N
2.562	65.07	S-1651	1.94	49.2	2.178	55.3	43	7.6	.98	25	42	189	.96	24.4	0.192	4.9	5.00	SST	CG	N
2.578	65.48	3391	3.50	88.9	1.888	48.0	457	80	.87	22	396	1762	2.07	52.6	0.345	8.8	6.00	SPR	CG	Z
2.593	65.86	S-410	8.75	222.3	2.383	60.5	2.0	.35	7.1	180	14	62	.74	18.7	0.105	2.7	7.00	SST	CG	N
2.593	65.86	11896	9.63	244.5	2.123	53.9	30	5.3	4.6	116	139	618	3.06	77.6	0.235	6.0	13.0	SPR	CG	N
2.625	66.68	11969	2.84	72.2	2.191	55.7	91	16	1.2	31	113	501	.98	24.8	0.217	5.5	4.50	SPR	CG	Z
2.625	66.68	S-980	3.00	76.2	2.445	62.1	1.9	.34	2.5	63	4.8	21	.51	12.9	0.090	2.3	4.67	SST	C	N
2.625	66.68	S-418	3.00	76.2	2.433	61.8	3.3	.57	2.5	64	8.3	37	.48	12.2	0.096	2.4	4.00	SST	C	N
2.625	66.68	S-993	3.88	98.4	2.097	53.3	95	17	1.6	42	155	688	1.82	46.1	0.264	6.7	7.00	SST	CG	N
2.625	66.68	4410	4.00	101.6	1.749	44.4	1012	177	.82	21	834	3709	3.07	77.9	0.438	11.1	7.00	OT	CG	N
2.687	68.25	4135	2.50	63.5	2.437	61.9	12	2.0	2.0	50	23	102	.51	13.0	0.125	3.2	4.00	SPR	CG	Z
2.687	68.25	73121	4.00	101.6	2.063	52.4	226	40	1.4	37	327	1456	2.03	51.5	0.312	7.9	6.50	OT	CG	N
2.687	68.25	73128	4.00	101.6	2.001	50.8	343	60	1.2	31	422	1877	2.23	56.6	0.343	8.7	6.50	OT	CG	N
2.687	68.25	73135	4.00	101.6	1.963	49.9	437	76	1.1	29	494	2196	2.35	59.8	0.362	9.2	6.50	OT	CG	N
2.687	68.25	73142	4.00	101.6	1.937	49.2	511	90	1.1	27	547	2434	2.44	61.9	0.375	9.5	6.50	OT	CG	N
2.687	68.25	73149	4.00	101.6	1.901	48.3	631	111	.97	25	612	2723	2.55	64.9	0.393	10.0	6.50	OT	CG	N
2.687	68.25	73156	4.50	114.3	1.875	47.6	627	110	1.1	27	673	2992	2.94	74.8	0.406	10.3	7.25	OT	CG	N
2.687	68.25	73163	4.50	114.3	1.813	46.1	877	154	.93	24	812	3610	3.17	80.5	0.437	11.1	7.25	OT	CG	N
2.687	68.25	73170	4.50	114.3	1.751	44.5	1262	221	.78	20	988	4395	3.28	83.2	0.468	11.9	7.00	OT	CG	N
2.687	68.25	3327	4.88	123.8	2.313	58.8	16	2.8	3.2	81	51	228	1.68	42.7	0.187	4.7	9.00	SPR	CG	Z
2.687	68.25	73122	5.00	127.0	2.063	52.4	175	31	1.9	47	327	1456	2.43	61.8	0.312	7.9	7.80	OT	CG	N
2.687	68.25	73129	5.00	127.0	2.001	50.8	262	46	1.6	41	422	1877	2.71	68.8	0.343	8.7	7.90	OT	CG	N
2.687	68.25	73136	5.00	127.0	1.963	49.9	334	59	1.5	38	494	2196	2.85	72.4	0.362	9.2	7.88	OT	CG	N
2.687	68.25	73143	5.00	127.0	1.937	49.2	392	69	1.4	35	547	2434	2.95	75.0	0.375	9.5	7.88	OT	CG	N
2.687	68.25	73150	5.00	127.0	1.901	48.3	481	84	1.3	32	612	2723	3.11	78.9	0.393	10.0	7.90	OT	CG	N
2.687	68.25	73157	5.00	127.0	1.875	47.6	549	96	1.2	31	673	2992	3.25	82.5	0.406	10.3	8.00	OT	CG	N
2.687	68.25	73164	5.00	127.0	1.813	46.1	767	134	1.1	27	812	3610	3.50	88.8	0.437	11.1	8.00	OT	CG	N
2.687	68.25	73171	5.00	127.0	1.751	44.5	1107	194	.89	23	988	4395	3.60	91.5	0.468	11.9	7.70	OT	CG	N
2.687	68.25	73123	6.00	152.4	2.063	52.4	143	25	2.3	58	327	1456	2.85	72.4	0.312	7.9	9.13	OT	CG	N
2.687	68.25	73130	6.00	152.4	2.001	50.8	213	37	2.0	50	422	1877	3.17	80.6	0.343	8.7	9.25	OT	CG	N
2.687	68.25	73137	6.00	152.4	1.963	49.9	271	47	1.8	46	494	2196	3.35	85.0	0.362	9.2	9.25	OT	CG	N
2.687	68.25	73144	6.00	152.4	1.937	49.2	317	56	1.7	44	547	2434	3.47	88.1	0.375	9.5	9.25	OT	CG	N
2.687	68.25	73151	6.00	152.4	1.901	48.3	389	68	1.6	40	612	2723	3.65	92.8	0.393	10.0	9.30	OT	CG	N
2.687	68.25	73158	6.00	152.4	1.875	47.6	445	78	1.5	38	673	2992	3.82	96.9	0.406	10.3	9.40	OT	CG	N
2.687	68.25	73165	6.00	152.4	1.813	46.1	618	108	1.3	33	812	3610	4.13	104.9	0.437	11.1	9.45	OT	CG	N
2.687	68.25	73172	6.00	152.4	1.751	44.5	890	156	1.1	28	988	4395	4.25	108.1	0.468	11.9	9.09	OT	CG	N
2.687	68.25	10182	6.25	158.8	2.417	61.4	7.7	1.3	3.8	96	29	129	.91	23.1	0.135	3.4	5.75	SPR	C	Z
2.687	68.25	73124	7.00	177.8	2.063	52.4	120	21	2.7	70	327	1456	3.28	83.2	0.312	7.9	10.5	OT	CG	N
2.687	68.25	73131	7.00	177.8	2.001	50.8	180	31	2.3	60	422	1877	3.64	92.4	0.343	8.7	10.6	OT	CG	N
2.687	68.25	73138	7.00	177.8	1.963	49.9	228	40	2.2	55	494	2196	3.85	97.7	0.362	9.2	10.6	OT	CG	N
2.687	68.25	73145	7.00	177.8	1.937	49.2	267	47	2.1	52	547	2434	3.98	101.2	0.375	9.5	10.6	OT	CG	N
2.687	68.25	73152	7.00	177.8	1.901	48.3	327	57	1.9	48	612	2723	4.21	106.8	0.393	10.0	10.7	OT	CG	N
2.687	68.25	73159	7.00	177.8	1.875	47.6	374	65	1.8	46	673	2992	4.38	111.4	0.406	10.3	10.8	OT	CG	N
2.687	68.25	73166	7.00	177.8	1.813	46.1	517	91	1.6	40	812	3610	4.76	121.0	0.437	11.1	10.9	OT	CG	N
2.687	68.25	73173	7.00	177.8	1.751	44.5	743	130	1.3	34	988	4395	4.91	124.8	0.468	11.9	10.5	OT	CG	N
2.687	68.25	73125	8.00	203.2	2.063	52.4	104	18	3.1	80	327	1456	3.67	93.1	0.312	7.9	11.7	OT	CG	N
2.687	68.25	73132	8.00	203.2	2.001	50.8	156	27	2.7	69	422	1877	4.08	103.7	0.343	8.7	11.9	OT	CG	N
2.687	68.25	73139	8.00	203.2	1.963	49.9	196	34	2.5	64	494	2196	4.34	110.3	0.362	9.2	12.0	OT	CG	N
2.687	68.25	73146	8.00	203.2	1.937	49.2	230	40	2.4	60	547	2434	4.50	114.3	0.375	9.5	12.0	OT	CG	N
2.687	68.25	73153	8.00	203.2	1.901	48.3	281	49	2.2	55	612	2723	4.76	120.8	0.393	10.0	12.1	OT	CG	N
2.687	68.25	73160	8.00	203.2	1.875	47.6	321	56	2.1	53	673	2992	4.97	126.3	0.406	10.3	12.2	OT	CG	N
2.687	68.25	73167	8.00	203.2	1.813	46.1	445	78	1.8	46	812	361								

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.687	68.25	73155	10.0	254.0	1.901	48.3	220	39	2.8	71	612	2723	5.86	148.7	0.393	10.0	14.9	OT	CG	N
2.687	68.25	73162	10.0	254.0	1.875	47.6	251	44	2.7	68	673	2992	6.13	155.7	0.406	10.3	15.1	OT	CG	N
2.687	68.25	73169	10.0	254.0	1.813	46.1	347	61	2.3	59	812	3610	6.67	169.3	0.437	11.1	15.3	OT	CG	N
2.687	68.25	73176	10.0	254.0	1.751	44.5	497	87	2.0	50	988	4395	6.88	174.7	0.468	11.9	14.7	OT	CG	N
2.703	68.66	4157	6.25	158.8	2.433	61.8	6.6	1.2	4.3	110	29	128	.98	24.9	0.135	3.4	6.25	SPR	C	GI
2.703	68.66	12019	7.00	177.8	2.493	63.3	2.2	.39	6.3	160	14	62	.68	17.3	0.105	2.7	6.50	SPR	CG	Z
2.734	69.44	1920	3.75	95.3	2.524	64.1	1.3	.23	2.7	68	3.5	16	1.09	27.6	0.105	2.7	9.33	SPR	C	Z
2.734	69.44	3058	5.00	127.0	2.422	61.5	12	2.2	3.4	87	43	190	.94	23.8	0.156	4.0	6.00	SPR	CG	Z
2.734	69.44	3238	6.25	158.8	2.454	62.3	7.3	1.3	4.3	110	32	141	.89	22.5	0.140	3.6	6.33	SPR	CG	Z
2.750	69.85	S-3157	2.50	63.5	2.366	60.1	81	14	.80	20	65	287	.62	15.8	0.192	4.9	3.25	SST	CG	N
2.750	69.85	4336	4.75	120.7	2.300	58.4	65	11	1.8	45	116	514	1.24	31.4	0.225	5.7	5.50	SPR	CG	Z
2.750	69.85	4086	6.25	158.8	2.000	50.8	303	53	1.6	40	476	2118	3.38	85.7	0.375	9.5	9.00	HD	CG	N
2.750	69.85	4093	8.50	215.9	1.250	31.8	7107	1245	.36	9.2	2563	11400	7.50	190.5	0.750	19.1	10.0	HD	CG	N
2.750	69.85	S-3116	14.0	355.6	2.438	61.9	6.1	1.1	6.2	158	38	167	1.40	35.7	0.156	4.0	9.00	SST	CG	N
2.796	71.02	11890	9.00	228.6	2.564	65.1	1.5	.27	7.8	197	12	53	1.25	31.7	0.116	2.9	9.75	SST	C	N
2.812	71.42	4328	1.63	41.3	1.938	49.2	3913	685	.18	4.5	693	3082	1.31	33.3	0.437	11.1	3.00	SPR	CG	Z
2.812	71.42	4334	13.0	330.2	2.246	57.0	33	5.7	6.6	168	215	958	5.52	140.2	0.283	7.2	19.5	SPR	CG	Z
2.875	73.03	S-3095	2.88	73.0	2.351	59.7	189	33	.74	19	139	617	.98	25.0	0.262	6.7	3.75	SST	CG	N
2.875	73.03	S-3159	3.00	76.2	2.625	66.7	15	2.6	1.4	35	20	90	.50	12.7	0.125	3.2	3.00	SST	C	N
2.875	73.03	S-86	3.00	76.2	2.491	63.3	39	6.8	1.6	40	62	275	.82	20.7	0.192	4.9	4.25	SST	CG	N
2.875	73.03	S-995	3.63	92.1	2.309	58.6	107	19	1.6	41	174	775	1.76	44.6	0.283	7.2	6.25	SST	CG	N
2.875	73.03	4240	6.75	171.5	2.087	53.0	378	66	1.4	35	516	2293	3.15	80.1	0.394	10.0	8.00	SPR	CG	Z
2.875	73.03	4314	7.50	190.5	2.375	60.3	52	9.1	2.9	74	151	673	2.00	50.8	0.250	6.4	8.00	SPR	CG	Z
2.875	73.03	S-3124	8.50	215.9	2.375	60.3	39	6.8	3.3	84	127	566	2.25	57.2	0.250	6.4	9.00	SST	CG	N
2.875	73.03	S-1591	8.50	215.9	2.375	60.3	39	6.8	3.3	84	127	566	2.25	57.2	0.250	6.4	9.00	SST	CG	N
2.875	73.03	11314	12.8	323.9	2.213	56.2	71	12	4.6	116	325	1445	5.54	140.8	0.331	8.4	16.8	SPR	CG	N
2.906	73.81	3313	1.50	38.1	2.492	63.3	135	24	.66	17	89	395	.62	15.8	0.207	5.3	3.00	SPR	CG	Z
2.906	73.81	73177	4.00	101.6	2.344	59.5	116	20	2.0	50	230	1023	1.76	44.8	0.281	7.1	6.27	OT	CG	N
2.906	73.81	73183	4.00	101.6	2.282	58.0	184	32	1.7	42	304	1353	1.95	49.5	0.312	7.9	6.24	OT	CG	N
2.906	73.81	73189	4.00	101.6	2.220	56.4	278	49	1.4	36	392	1746	2.14	54.5	0.343	8.7	6.25	OT	CG	N
2.906	73.81	73195	4.00	101.6	2.182	55.4	352	62	1.3	33	459	2044	2.27	57.6	0.362	9.2	6.26	OT	CG	N
2.906	73.81	73201	4.00	101.6	2.156	54.8	412	72	1.2	31	509	2266	2.35	59.6	0.375	9.5	6.26	OT	CG	N
2.906	73.81	73207	4.00	101.6	2.120	53.8	508	89	1.1	29	570	2536	2.46	62.4	0.393	10.0	6.25	OT	CG	N
2.906	73.81	73178	5.00	127.0	2.344	59.5	90	16	2.6	65	230	1023	2.11	53.6	0.281	7.1	7.51	OT	CG	N
2.906	73.81	73184	5.00	127.0	2.282	58.0	142	25	2.1	54	304	1353	2.34	59.4	0.312	7.9	7.50	OT	CG	N
2.906	73.81	73190	5.00	127.0	2.220	56.4	211	37	1.9	47	392	1746	2.61	66.2	0.343	8.7	7.60	OT	CG	N
2.906	73.81	73196	5.00	127.0	2.182	55.4	273	48	1.7	43	459	2044	2.71	68.9	0.362	9.2	7.49	OT	CG	N
2.906	73.81	73202	5.00	127.0	2.156	54.8	312	55	1.6	41	509	2266	2.86	72.6	0.375	9.5	7.62	OT	CG	N
2.906	73.81	73208	5.00	127.0	2.120	53.8	384	67	1.5	38	570	2536	3.00	76.1	0.393	10.0	7.63	OT	CG	N
2.906	73.81	73213	5.00	127.0	2.094	53.2	435	76	1.4	37	627	2788	3.14	79.9	0.406	10.3	7.75	OT	CG	N
2.906	73.81	73219	5.00	127.0	2.032	51.6	633	111	1.2	30	757	3368	3.28	83.3	0.437	11.1	7.50	OT	CG	N
2.906	73.81	73225	5.00	127.0	1.970	50.0	865	151	1.1	27	923	4105	3.51	89.2	0.468	11.9	7.50	OT	CG	N
2.906	73.81	73231	5.00	127.0	1.906	48.4	1228	215	.87	22	1074	4779	3.63	92.1	0.500	12.7	7.25	OT	CG	N
2.906	73.81	73237	5.00	127.0	1.844	46.8	1625	285	.79	20	1276	5674	3.85	97.8	0.531	13.5	7.25	OT	CG	N
2.906	73.81	73179	6.00	152.4	2.344	59.5	73	13	3.2	80	230	1023	2.47	62.7	0.281	7.1	8.79	OT	CG	N
2.906	73.81	73185	6.00	152.4	2.282	58.0	116	20	2.6	67	304	1353	2.72	69.2	0.312	7.9	8.73	OT	CG	N
2.906	73.81	73191	6.00	152.4	2.220	56.4	172	30	2.3	58	392	1746	3.04	77.3	0.343	8.7	8.87	OT	CG	N
2.906	73.81	73197	6.00	152.4	2.182	55.4	218	38	2.1	54	459	2044	3.21	81.6	0.362	9.2	8.88	OT	CG	N
2.906	73.81	73203	6.00	152.4	2.156	54.8	255	45	2.0	51	509	2266	3.33	84.5	0.375	9.5	8.88	OT	CG	N
2.906	73.81	73209	6.00	152.4	2.120	53.8	313	55	1.8	46	570	2536	3.50	88.9	0.393	10.0	8.90	OT	CG	N
2.906	73.81	73214	6.00	152.4	2.094	53.2	351	61	1.8	45	627	2788	3.70	94.1	0.406	10.3	9.12	OT	CG	N
2.906	73.81	73220	6.00	152.4	2.032	51.6	507	89	1.5	38	757	3368	3.88	98.5	0.437	11.1	8.87	OT	CG	N
2.906	73.81	73226	6.00	152.4	1.970	50.0	692	121	1.3	34	923	4105	4.15	105.5	0.468	11.9	8.88	OT	CG	N
2.906	73.81	73232	6.00	152.4	1.906	48.4	977	171	1.1	28	1074	4779	4.30	109.2	0.500	12.7	8.60	OT	CG	N
2.906	73.81	73238	6.00	152.4	1.844	46.8	1288	226	.99	25	1276	5674	4.58	116.3	0.531	13.5	8.62	OT	CG	N
2.906	73.81	4080	6.50	165.1	1.782	45.3	1856	325	.71	18	1315	5849	4.50	114.2	0.562	14.3	8.00	SPR	CG	N
2.906	73.81	73180	7.00	177.8	2.344	59.5	62	11	3.7	94	230	1023	2.81	71.3	0.281	7.1	9.99	OT	CG	N
2.906	73.81	73186	7.00	177.8	2.282	58.0	98	17	3.1	79	304	1353	3.11	79.0	0.312	7.9	9.96	OT	CG	N
2.906	73.81	73192	7.00	177.8	2.220	56.4	145	25	2.7	69	392	1746	3.48	88.4	0.343	8.7	10.2	OT	CG	N
2.906	73.81	73198	7.00	177.8	2.182	55.4	184	32	2.5	63	459	2044	3.67	93.3	0.362	9.2	10.1	OT	CG	N
2.906	73.81	73204	7.00	177.8	2.156	54.8	213	37	2.4	61	509	2266	3.84	97.5	0.375	9.5	10.2	OT	CG	N
2.906	73.81	73210	7.00	177.8	2.120	53.8	262	46	2.2	55	570	2536	4.03	102.3	0.393	10.0	10.2	OT	CG	N
2.906	73.81	73215	7.00	177.8	2.094	53.2	294	51	2.1	54	627	2788	4.26	108.3	0.406	10.3	10.5	OT	CG	N
2.906	73.81	73221	7.00	177.8	2.032	51.6	422	74	1.8	46	757	3368	4.48	113.8	0.437	11.1	10.3	OT	CG	N
2.906	73.81	73227	7.00	177.8	1.970	50.0	577	101	1.6	41	923	4105	4.80	121.8	0.468	11.9	10.2	OT	CG	N
2.906	73.81	73233	7.00	177.8	1.906	48.4	819	143	1.3	33	1074	4779								




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
2.906	73.81	73194	10.0	254.0	2.220	56.4	98	17	4.0	102	392	1746	4.82	122.5	0.343	8.7	14.1	OT	CG	N
2.906	73.81	73200	10.0	254.0	2.182	55.4	125	22	3.7	93	459	2044	5.07	128.7	0.362	9.2	14.0	OT	CG	N
2.906	73.81	73206	10.0	254.0	2.156	54.8	143	25	3.6	90	509	2266	5.35	135.8	0.375	9.5	14.3	OT	CG	N
2.906	73.81	73212	10.0	254.0	2.120	53.8	176	31	3.2	82	570	2536	5.61	142.5	0.393	10.0	14.3	OT	CG	N
2.906	73.81	73217	10.0	254.0	2.094	53.2	198	35	3.2	80	627	2788	5.94	150.8	0.406	10.3	14.6	OT	CG	N
2.906	73.81	73223	10.0	254.0	2.032	51.6	284	50	2.7	68	757	3368	6.23	158.3	0.437	11.1	14.3	OT	CG	N
2.906	73.81	73229	10.0	254.0	1.970	50.0	388	68	2.4	60	923	4105	6.68	169.6	0.468	11.9	14.3	OT	CG	N
2.906	73.81	73235	10.0	254.0	1.906	48.4	543	95	2.0	50	1074	4779	6.94	176.3	0.500	12.7	13.9	OT	CG	N
2.906	73.81	73241	10.0	254.0	1.844	46.8	711	125	1.8	46	1276	5674	7.43	188.8	0.531	13.5	14.0	OT	CG	N
2.906	73.81	73218	12.0	304.8	2.094	53.2	163	29	3.8	98	627	2788	7.04	178.8	0.406	10.3	17.3	OT	CG	N
2.906	73.81	73224	12.0	304.8	2.032	51.6	232	41	3.3	83	757	3368	7.44	188.9	0.437	11.1	17.0	OT	CG	N
2.906	73.81	73230	12.0	304.8	1.970	50.0	317	56	2.9	74	923	4105	7.96	202.2	0.468	11.9	17.0	OT	CG	N
2.906	73.81	73236	12.0	304.8	1.906	48.4	445	78	2.4	61	1074	4779	8.25	209.5	0.500	12.7	16.5	OT	CG	N
2.906	73.81	73242	12.0	304.8	1.844	46.8	583	102	2.2	56	1276	5674	8.83	224.3	0.531	13.5	16.6	OT	CG	N
2.938	74.63	10799	3.25	82.6	2.728	69.3	2.7	.48	2.8	71	7.6	34	.47	12.0	0.105	2.7	4.50	SST	CG	N
2.938	74.63	12628	3.38	85.7	2.524	64.1	52	9.1	1.7	43	88	391	.93	23.7	0.207	5.3	4.50	SPR	CG	Z
2.938	74.63	11779	5.81	147.6	2.564	65.1	11	1.8	3.9	100	42	185	1.87	47.5	0.187	4.7	10.0	SPR	CG	Z
2.938	74.63	4055	8.00	203.2	1.564	39.7	3509	615	.59	15	2088	9287	6.87	174.5	0.687	17.4	10.0	HD	CG	N
2.938	74.63	S-3153	10.5	266.7	2.564	65.1	9.2	1.6	6.1	155	56	249	1.87	47.5	0.187	4.7	10.0	SST	CG	N
2.984	75.79	12443	7.00	177.8	2.782	70.7	1.0	.18	6.1	156	6.2	28	.86	21.8	0.101	2.6	7.50	SST	CG	N
3.000	76.20	4138	1.75	44.5	2.586	65.7	81	14	1.0	26	83	368	.72	18.4	0.207	5.3	3.50	SPR	CG	Z
3.000	76.20	11357	2.00	50.8	2.376	60.4	561	98	.47	12	262	1167	1.01	25.8	0.312	7.9	3.25	SPR	CG	Z
3.000	76.20	S-3221	2.72	69.0	2.618	66.5	31	5.4	1.9	47	57	253	.86	21.8	0.191	4.9	4.50	SST	CG	N
3.000	76.20	S-3030	9.00	228.6	2.616	66.4	13	2.2	4.6	118	59	264	1.54	39.0	0.192	4.9	8.00	SST	CG	N
3.000	76.20	4241	11.0	279.4	2.616	66.4	9.8	1.7	7.0	179	69	307	2.11	53.6	0.192	4.9	11.0	SPR	CG	Z
3.031	76.99	S-3218	2.25	57.2	2.595	65.9	43	7.6	1.2	29	50	222	1.09	27.7	0.218	5.5	5.00	SST	CG	N
3.031	76.99	4249	4.63	117.5	2.345	59.6	341	60	.98	25	335	1492	1.72	43.6	0.343	8.7	5.00	SPR	CG	Z
3.125	79.38	11570	2.09	53.2	2.929	74.4	2.4	.42	1.6	41	3.8	17	.49	12.4	0.098	2.5	4.00	SPR	CG	N
3.125	79.38	10819	4.69	119.0	2.313	58.8	486	85	1.1	27	521	2319	2.44	61.9	0.406	10.3	6.00	SPR	CG	N
3.140	79.76	11606	1.50	38.1	2.764	70.2	23	4.1	.37	9.4	8.7	39	1.13	28.7	0.188	4.8	5.00	SPR	CG	Z
3.156	80.16	S-992	1.88	47.6	2.832	71.9	32	5.6	1.2	29	37	164	.49	12.3	0.162	4.1	3.00	SST	CG	N
3.156	80.16	S-249	3.19	81.0	2.860	72.6	11	1.9	2.6	66	29	128	.59	15.0	0.148	3.8	4.00	SST	CG	N
3.156	80.16	73243	5.00	127.0	2.470	62.7	179	31	2.0	52	363	1616	2.40	61.0	0.343	8.7	7.00	OT	CG	N
3.156	80.16	73249	5.00	127.0	2.432	61.8	226	40	1.9	48	426	1893	2.53	64.4	0.362	9.2	7.00	OT	CG	N
3.156	80.16	73255	5.00	127.0	2.406	61.1	264	46	1.8	45	472	2099	2.63	66.7	0.375	9.5	7.00	OT	CG	N
3.156	80.16	73261	5.00	127.0	2.370	60.2	325	57	1.6	41	529	2351	2.75	69.9	0.393	10.0	7.00	OT	CG	N
3.156	80.16	73267	5.00	127.0	2.344	59.5	376	66	1.5	39	581	2585	2.84	72.2	0.406	10.3	7.00	OT	CG	N
3.156	80.16	73273	5.00	127.0	2.282	58.0	522	91	1.3	34	703	3126	3.06	77.7	0.437	11.1	7.00	OT	CG	N
3.156	80.16	73279	5.00	127.0	2.220	56.4	710	124	1.2	31	858	3814	3.28	83.2	0.468	11.9	7.00	OT	CG	N
3.156	80.16	73285	5.00	127.0	2.156	54.8	959	168	1.0	26	999	4446	3.50	88.9	0.500	12.7	7.00	OT	CG	N
3.156	80.16	73291	5.00	127.0	2.094	53.2	1264	221	.94	24	1188	5286	3.72	94.4	0.531	13.5	7.00	OT	CG	N
3.156	80.16	4023-A	5.50	139.7	1.996	50.7	2003	351	.66	17	1316	5852	3.92	99.4	0.580	14.7	6.75	SPR	CG	N
3.156	80.16	73244	6.00	152.4	2.470	62.7	146	26	2.5	63	363	1616	2.79	70.8	0.343	8.7	8.12	OT	CG	N
3.156	80.16	73250	6.00	152.4	2.432	61.8	185	32	2.3	58	426	1893	2.94	74.7	0.362	9.2	8.12	OT	CG	N
3.156	80.16	73256	6.00	152.4	2.406	61.1	212	37	2.2	57	472	2099	3.09	78.6	0.375	9.5	8.25	OT	CG	N
3.156	80.16	73262	6.00	152.4	2.370	60.2	260	46	2.0	52	529	2351	3.24	82.4	0.393	10.0	8.25	OT	CG	N
3.156	80.16	73268	6.00	152.4	2.344	59.5	350	61	1.7	42	581	2585	2.99	76.0	0.406	10.3	7.37	OT	CG	N
3.156	80.16	73274	6.00	152.4	2.282	58.0	421	74	1.7	42	703	3126	3.58	91.0	0.437	11.1	8.20	OT	CG	N
3.156	80.16	73280	6.00	152.4	2.220	56.4	568	99	1.5	38	858	3814	3.86	98.1	0.468	11.9	8.25	OT	CG	N
3.156	80.16	73286	6.00	152.4	2.156	54.8	767	134	1.3	33	999	4446	4.13	104.8	0.500	12.7	8.25	OT	CG	N
3.156	80.16	73292	6.00	152.4	2.094	53.2	1011	177	1.2	30	1188	5286	4.38	111.3	0.531	13.5	8.25	OT	CG	N
3.156	80.16	73245	7.00	177.8	2.470	62.7	123	22	2.9	75	363	1616	3.17	80.6	0.343	8.7	9.25	OT	CG	N
3.156	80.16	73251	7.00	177.8	2.432	61.8	156	27	2.7	69	426	1893	3.35	85.1	0.362	9.2	9.25	OT	CG	N
3.156	80.16	73257	7.00	177.8	2.406	61.1	179	31	2.6	67	472	2099	3.52	89.3	0.375	9.5	9.38	OT	CG	N
3.156	80.16	73263	7.00	177.8	2.370	60.2	220	39	2.4	61	529	2351	3.68	93.6	0.393	10.0	9.38	OT	CG	N
3.156	80.16	73269	7.00	177.8	2.344	59.5	255	45	2.3	58	581	2585	3.81	96.7	0.406	10.3	9.38	OT	CG	N
3.156	80.16	73275	7.00	177.8	2.282	58.0	352	62	2.0	51	703	3126	4.11	104.3	0.437	11.1	9.40	OT	CG	N
3.156	80.16	73281	7.00	177.8	2.220	56.4	473	83	1.8	46	858	3814	4.45	112.9	0.468	11.9	9.50	OT	CG	N
3.156	80.16	73287	7.00	177.8	2.156	54.8	639	112	1.6	40	999	4446	4.75	120.6	0.500	12.7	9.50	OT	CG	N
3.156	80.16	73293	7.00	177.8	2.094	53.2	842	148	1.4	36	1188	5286	5.04	128.1	0.531	13.5	9.50	OT	CG	N
3.156	80.16	73246	8.00	203.2	2.470	62.7	105	18	3.5	88	363	1616	3.60	91.5	0.343	8.7	10.5	OT	CG	N
3.156	80.16	73252	8.00	203.2	2.432	61.8	133	23	3.2	81	426	1893	3.80	96.6	0.362	9.2	10.5	OT	CG	N
3.156	80.16	73258	8.00	203.2	2.406	61.1	156	27	3.0	77	472	2099	3.94	100.0	0.375	9.5	10.5	OT	CG	N
3.156	80.16	73264	8.00	203.2	2.370	60.2	191	33	2.8	70	529	2351	4.13	104.8	0.393	10.0	10.5	OT	CG	N
3.156	80.16	73270	8.00	203.2	2.344	59.5	218	38	2.7	68	581	2585	4.30	109.3	0.406	10.3	10.6	OT	CG	N
3.156	80.16	73276	8.00																	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
3.156	80.16	73260	12.0	304.8	2.406	61.1	100	17	4.7	120	472	2099	5.72	145.3	0.375	9.5	15.3	OT	CG	N
3.156	80.16	73266	12.0	304.8	2.370	60.2	123	21	4.3	109	529	2351	5.99	152.2	0.393	10.0	15.2	OT	CG	N
3.156	80.16	73272	12.0	304.8	2.344	59.5	140	25	4.1	105	581	2585	6.25	158.9	0.406	10.3	15.4	OT	CG	N
3.156	80.16	73278	12.0	304.8	2.282	58.0	193	34	3.6	92	703	3126	6.77	172.0	0.437	11.1	15.5	OT	CG	N
3.156	80.16	73284	12.0	304.8	2.220	56.4	260	46	3.3	84	858	3814	7.32	186.0	0.468	11.9	15.7	OT	CG	N
3.156	80.16	73290	12.0	304.8	2.156	54.8	349	61	2.9	73	999	4446	7.88	200.1	0.500	12.7	15.8	OT	CG	N
3.156	80.16	73296	12.0	304.8	2.094	53.2	456	80	2.6	66	1188	5286	8.42	213.8	0.531	13.5	15.9	OT	CG	N
3.172	80.57	S-3108	6.00	152.4	2.932	74.5	1.5	27	4.9	125	7.5	33	1.08	27.4	0.120	3.0	8.00	SST	C	N
3.250	82.55	10708	2.13	54.0	2.780	70.6	107	19	1.0	27	112	498	.82	20.9	0.235	6.0	3.50	SPR	CG	Z
3.250	82.55	S-3102	4.25	108.0	2.750	69.9	60	11	1.9	48	113	503	1.25	31.8	0.250	6.4	5.00	SST	CG	N
3.250	82.55	4002	4.50	114.3	2.250	57.2	1234	216	.70	18	866	3850	2.75	69.9	0.500	12.7	5.50	SPR	CG	N
3.250	82.55	4096	12.0	304.8	2.250	57.2	411	72	2.1	53	866	3850	6.25	158.8	0.500	12.7	12.5	SPR	CG	N
3.266	82.96	S-1635	6.75	171.5	2.330	59.2	632	111	.89	23	562	2501	2.96	75.2	0.468	11.9	6.33	SST	CG	N
3.328	84.53	10985	3.13	79.4	2.828	71.8	59	10	1.9	47	111	492	1.22	31.0	0.250	6.4	5.00	SST	CG	N
3.375	85.73	4347	5.25	133.4	2.991	76.0	22	3.9	2.8	71	61	273	.91	23.2	0.192	4.9	4.75	SPR	CG	Z
3.375	85.73	S-3020	5.50	139.7	3.125	79.4	3.0	52	4.8	121	14	63	.75	19.1	0.125	3.2	5.00	SST	C	N
3.375	85.73	4090	14.0	355.6	2.501	63.5	207	36	2.8	72	588	2614	5.24	133.2	0.437	11.1	12.0	SPR	CG	N
3.406	86.51	73297	6.00	152.4	2.720	69.1	121	21	2.8	71	338	1504	2.65	67.3	0.343	8.7	7.72	OT	CG	N
3.406	86.51	73303	6.00	152.4	2.682	68.1	152	27	2.6	66	396	1763	2.81	71.3	0.362	9.2	7.76	OT	CG	N
3.406	86.51	73309	6.00	152.4	2.656	67.5	177	31	2.5	63	440	1955	2.91	74.0	0.375	9.5	7.77	OT	CG	N
3.406	86.51	73315	6.00	152.4	2.620	66.5	209	37	2.4	60	492	2191	3.14	79.8	0.393	10.0	8.00	OT	CG	N
3.406	86.51	73321	6.00	152.4	2.594	65.9	241	42	2.2	57	542	2410	3.25	82.5	0.406	10.3	8.00	OT	CG	N
3.406	86.51	73327	6.00	152.4	2.532	64.3	341	60	1.9	49	656	2916	3.44	87.4	0.437	11.1	7.87	OT	CG	N
3.406	86.51	73333	6.00	152.4	2.470	62.7	473	83	1.7	43	800	3560	3.63	92.1	0.468	11.9	7.75	OT	CG	N
3.406	86.51	73339	6.00	152.4	2.406	61.1	637	112	1.5	37	934	4154	3.87	98.4	0.500	12.7	7.75	OT	CG	N
3.406	86.51	73345	6.00	152.4	2.344	59.5	855	150	1.3	33	1111	4943	4.05	102.8	0.531	13.5	7.63	OT	CG	N
3.406	86.51	73351	6.00	152.4	2.282	58.0	1103	193	1.2	30	1292	5746	4.30	109.2	0.562	14.3	7.65	OT	CG	N
3.406	86.51	73357	6.00	152.4	2.220	56.4	1465	257	1.0	26	1477	6571	4.42	112.2	0.593	15.1	7.45	OT	CG	N
3.406	86.51	73298	8.00	203.2	2.720	69.1	89	16	3.8	97	338	1504	3.35	85.2	0.343	8.7	9.78	OT	CG	N
3.406	86.51	73304	8.00	203.2	2.682	68.1	109	19	3.6	92	396	1763	3.63	92.2	0.362	9.2	10.0	OT	CG	N
3.406	86.51	73310	8.00	203.2	2.656	67.5	127	22	3.5	88	440	1955	3.76	95.6	0.375	9.5	10.0	OT	CG	N
3.406	86.51	73316	8.00	203.2	2.620	66.5	152	27	3.2	82	492	2191	4.03	102.3	0.393	10.0	10.2	OT	CG	N
3.406	86.51	73322	8.00	203.2	2.594	65.9	175	31	3.1	79	542	2410	4.17	105.9	0.406	10.3	10.3	OT	CG	N
3.406	86.51	73328	8.00	203.2	2.532	64.3	243	43	2.7	69	656	2916	4.48	113.7	0.437	11.1	10.2	OT	CG	N
3.406	86.51	73334	8.00	203.2	2.470	62.7	340	60	2.4	60	800	3560	4.68	118.8	0.468	11.9	10.0	OT	CG	N
3.406	86.51	73340	8.00	203.2	2.406	61.1	457	80	2.0	52	934	4154	5.01	127.1	0.500	12.7	10.0	OT	CG	N
3.406	86.51	73346	8.00	203.2	2.344	59.5	608	106	1.8	46	1111	4943	5.26	133.7	0.531	13.5	9.91	OT	CG	N
3.406	86.51	73352	8.00	203.2	2.282	58.0	779	136	1.7	42	1292	5746	5.62	142.8	0.562	14.3	10.0	OT	CG	N
3.406	86.51	73358	8.00	203.2	2.220	56.4	1037	182	1.4	36	1477	6571	5.75	146.1	0.593	15.1	9.70	OT	CG	N
3.406	86.51	73299	10.0	254.0	2.720	69.1	71	12	4.8	121	338	1504	4.03	102.4	0.343	8.7	11.8	OT	CG	N
3.406	86.51	73305	10.0	254.0	2.682	68.1	85	15	4.7	118	396	1763	4.45	113.1	0.362	9.2	12.3	OT	CG	N
3.406	86.51	73311	10.0	254.0	2.656	67.5	100	18	4.4	112	440	1955	4.58	116.3	0.375	9.5	12.2	OT	CG	N
3.406	86.51	73317	10.0	254.0	2.620	66.5	119	21	4.1	105	492	2191	4.93	125.1	0.393	10.0	12.5	OT	CG	N
3.406	86.51	73323	10.0	254.0	2.594	65.9	138	24	3.9	100	542	2410	5.07	128.7	0.406	10.3	12.5	OT	CG	N
3.406	86.51	73329	10.0	254.0	2.532	64.3	191	33	3.4	87	656	2916	5.46	138.6	0.437	11.1	12.5	OT	CG	N
3.406	86.51	73335	10.0	254.0	2.470	62.7	265	46	3.0	77	800	3560	5.74	145.7	0.468	11.9	12.3	OT	CG	N
3.406	86.51	73341	10.0	254.0	2.406	61.1	353	62	2.6	67	934	4154	6.19	157.1	0.500	12.7	12.4	OT	CG	N
3.406	86.51	73347	10.0	254.0	2.344	59.5	469	82	2.4	60	1111	4943	6.51	165.3	0.531	13.5	12.3	OT	CG	N
3.406	86.51	73353	10.0	254.0	2.282	58.0	608	106	2.1	54	1292	5746	6.89	174.9	0.562	14.3	12.3	OT	CG	N
3.406	86.51	73359	10.0	254.0	2.220	56.4	798	140	1.9	47	1477	6571	7.12	180.9	0.593	15.1	12.0	OT	CG	N
3.406	86.51	73300	12.0	304.8	2.720	69.1	59	10	5.7	146	338	1504	4.71	119.7	0.343	8.7	13.7	OT	CG	N
3.406	86.51	73306	12.0	304.8	2.682	68.1	71	12	5.6	142	396	1763	5.19	131.7	0.362	9.2	14.3	OT	CG	N
3.406	86.51	73312	12.0	304.8	2.656	67.5	82	14	5.4	136	440	1955	5.42	137.6	0.375	9.5	14.5	OT	CG	N
3.406	86.51	73318	12.0	304.8	2.620	66.5	98	17	5.0	128	492	2191	5.81	147.7	0.393	10.0	14.8	OT	CG	N
3.406	86.51	73324	12.0	304.8	2.594	65.9	112	20	4.8	123	542	2410	6.06	153.8	0.406	10.3	14.9	OT	CG	N
3.406	86.51	73330	12.0	304.8	2.532	64.3	157	27	4.2	106	656	2916	6.45	163.8	0.437	11.1	14.8	OT	CG	N
3.406	86.51	73336	12.0	304.8	2.470	62.7	218	38	3.7	93	800	3560	6.77	172.0	0.468	11.9	14.5	OT	CG	N
3.406	86.51	73342	12.0	304.8	2.406	61.1	290	51	3.2	82	934	4154	7.31	185.7	0.500	12.7	14.6	OT	CG	N
3.406	86.51	73348	12.0	304.8	2.344	59.5	385	67	2.9	73	1111	4943	7.69	195.4	0.531	13.5	14.5	OT	CG	N
3.406	86.51	73354	12.0	304.8	2.282	58.0	494	87	2.6	66	1292	5746	8.22	208.7	0.562	14.3	14.6	OT	CG	N
3.406	86.51	73360	12.0	304.8	2.220	56.4	652	114	2.3	58	1477	6571	8.45	214.6	0.593	15.1	14.2	OT	CG	N
3.406	86.51	73301	14.0	355.6	2.720	69.1	49	8.6	6.9	175	338	1504	5.53	140.5	0.343	8.7	16.1	OT	CG	N
3.406	86.51	73307	14.0	355.6	2.682	68.1	59	10	6.7	171	396	1763	6.09	154.8	0.362	9.2	16.8	OT	CG	N
3.406	86.51	73313	14.0	355.6	2.656	67.5	69	12	6.4	162	440	1955	6.30	160.0	0.375	9.5	16.8	OT	CG	N
3.406	86.51	73319	14.0	355.6	2.620	66.5	84	15	5.9	149	492	2191	6.65	168.9	0.393	10.0	16.9	OT	CG	N
3.406																				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
3.406	86.51	73350	16.0	406.4	2.344	59.5	283	50	3.9	100	1111	4943	10.1	256.2	0.531	13.5	19.0	OT	CG	N
3.406	86.51	73356	16.0	406.4	2.282	58.0	361	63	3.6	91	1292	5746	10.8	275.1	0.562	14.3	19.3	OT	CG	N
3.406	86.51	73362	16.0	406.4	2.220	56.4	477	84	3.1	79	1477	6571	11.1	282.3	0.593	15.1	18.7	OT	CG	N
3.421	86.89	1879	3.84	97.6	2.921	74.2	50	8.8	2.5	63	124	552	1.38	34.9	0.250	6.4	5.50	HD	CG	Z
3.500	88.90	4085	4.00	101.6	1.750	44.5	23293	4079	.14	3.6	3298	14671	3.50	88.9	0.875	22.2	4.00	HD	CG	N
3.500	88.90	S-1652	4.13	104.8	3.010	76.5	44	7.8	2.2	57	99	441	1.23	31.1	0.245	6.2	5.00	SST	CG	N
3.500	88.90	4081	5.38	136.5	2.976	75.6	19	3.3	2.1	53	40	177	3.28	83.2	0.262	6.7	12.5	SPR	CG	Z
3.500	88.90	4084	8.00	203.2	2.000	50.8	3240	567	.67	17	2162	9616	6.56	166.7	0.750	19.1	8.75	HD	CG	N
3.500	88.90	S-3169	8.50	215.9	3.064	77.8	14	2.4	5.4	136	75	332	1.91	48.5	0.218	5.5	7.75	SST	C	N
3.500	88.90	4050	10.0	254.0	2.250	57.2	1191	209	1.3	32	1491	6631	6.09	154.8	0.625	15.9	9.75	SPR	CG	N
3.656	92.86	73363	6.00	152.4	2.932	74.5	138	24	2.7	68	371	1649	2.53	64.4	0.362	9.2	7.00	OT	CG	N
3.656	92.86	73369	6.00	152.4	2.906	73.8	161	28	2.6	65	411	1829	2.62	66.7	0.375	9.5	7.00	OT	CG	N
3.656	92.86	73375	6.00	152.4	2.870	72.9	197	35	2.3	59	461	2050	2.75	69.9	0.393	10.0	7.00	OT	CG	N
3.656	92.86	73381	6.00	152.4	2.844	72.2	228	40	2.2	57	507	2256	2.84	72.2	0.406	10.3	7.00	OT	CG	N
3.656	92.86	73387	6.00	152.4	2.782	70.7	299	52	2.1	52	614	2731	3.17	80.5	0.437	11.1	7.25	OT	CG	N
3.656	92.86	73393	6.00	152.4	2.720	69.1	405	71	1.9	47	750	3337	3.39	86.2	0.468	11.9	7.25	OT	CG	N
3.656	92.86	73399	6.00	152.4	2.656	67.5	544	95	1.6	41	876	3896	3.63	92.1	0.500	12.7	7.25	OT	CG	N
3.656	92.86	73405	6.00	152.4	2.594	65.9	713	125	1.5	37	1043	4640	3.85	97.8	0.531	13.5	7.25	OT	CG	N
3.656	92.86	73411	6.00	152.4	2.532	64.3	922	161	1.3	33	1214	5398	4.07	103.5	0.562	14.3	7.25	OT	CG	N
3.656	92.86	73417	6.00	152.4	2.470	62.7	1207	211	1.2	29	1389	6178	4.23	107.3	0.593	15.1	7.13	OT	CG	N
3.656	92.86	73364	8.00	203.2	2.932	74.5	99	17	3.8	95	371	1649	3.26	82.8	0.362	9.2	9.01	OT	CG	N
3.656	92.86	73370	8.00	203.2	2.906	73.8	117	20	3.5	90	411	1829	3.34	84.8	0.375	9.5	8.90	OT	CG	N
3.656	92.86	73376	8.00	203.2	2.870	72.9	143	25	3.2	82	461	2050	3.50	88.9	0.393	10.0	8.90	OT	CG	N
3.656	92.86	73382	8.00	203.2	2.844	72.2	165	29	3.1	78	507	2256	3.61	91.8	0.406	10.3	8.90	OT	CG	N
3.656	92.86	73388	8.00	203.2	2.782	70.7	217	38	2.8	72	614	2731	4.04	102.7	0.437	11.1	9.25	OT	CG	N
3.656	92.86	73394	8.00	203.2	2.720	69.1	292	51	2.6	65	750	3337	4.35	110.5	0.468	11.9	9.30	OT	CG	N
3.656	92.86	73400	8.00	203.2	2.656	67.5	389	68	2.3	57	876	3896	4.68	118.8	0.500	12.7	9.35	OT	CG	N
3.656	92.86	73406	8.00	203.2	2.594	65.9	506	89	2.1	52	1043	4640	4.99	126.8	0.531	13.5	9.40	OT	CG	N
3.656	92.86	73412	8.00	203.2	2.532	64.3	657	115	1.8	47	1214	5398	5.27	133.8	0.562	14.3	9.38	OT	CG	N
3.656	92.86	73418	8.00	203.2	2.470	62.7	853	149	1.6	41	1389	6178	5.49	139.3	0.593	15.1	9.25	OT	CG	N
3.656	92.86	73365	10.0	254.0	2.932	74.5	78	14	4.7	120	371	1649	3.91	99.4	0.362	9.2	10.8	OT	CG	N
3.656	92.86	73371	10.0	254.0	2.906	73.8	93	16	4.4	113	411	1829	4.01	101.9	0.375	9.5	10.7	OT	CG	N
3.656	92.86	73377	10.0	254.0	2.870	72.9	112	20	4.1	104	461	2050	4.25	107.9	0.393	10.0	10.8	OT	CG	N
3.656	92.86	73383	10.0	254.0	2.844	72.2	129	23	3.9	100	507	2256	4.38	111.4	0.406	10.3	10.8	OT	CG	N
3.656	92.86	73389	10.0	254.0	2.782	70.7	169	30	3.6	92	614	2731	4.94	125.4	0.437	11.1	11.3	OT	CG	N
3.656	92.86	73395	10.0	254.0	2.720	69.1	226	40	3.3	84	750	3337	5.34	135.5	0.468	11.9	11.4	OT	CG	N
3.656	92.86	73401	10.0	254.0	2.656	67.5	304	53	2.9	73	876	3896	5.70	144.8	0.500	12.7	11.4	OT	CG	N
3.656	92.86	73407	10.0	254.0	2.594	65.9	394	69	2.6	67	1043	4640	6.11	155.1	0.531	13.5	11.5	OT	CG	N
3.656	92.86	73413	10.0	254.0	2.532	64.3	507	89	2.4	61	1214	5398	6.49	164.9	0.562	14.3	11.6	OT	CG	N
3.656	92.86	73419	10.0	254.0	2.470	62.7	660	116	2.1	53	1389	6178	6.75	171.3	0.593	15.1	11.4	OT	CG	N
3.656	92.86	73366	12.0	304.8	2.932	74.5	64	11	5.8	147	371	1649	4.62	117.3	0.362	9.2	12.8	OT	CG	N
3.656	92.86	73372	12.0	304.8	2.906	73.8	76	13	5.4	138	411	1829	4.74	120.3	0.375	9.5	12.6	OT	CG	N
3.656	92.86	73378	12.0	304.8	2.870	72.9	92	16	5.0	128	461	2050	5.01	127.3	0.393	10.0	12.8	OT	CG	N
3.656	92.86	73384	12.0	304.8	2.844	72.2	106	19	4.8	122	507	2256	5.18	131.5	0.406	10.3	12.8	OT	CG	N
3.656	92.86	73390	12.0	304.8	2.782	70.7	139	24	4.4	113	614	2731	5.83	148.2	0.437	11.1	13.3	OT	CG	N
3.656	92.86	73396	12.0	304.8	2.720	69.1	185	32	4.1	103	750	3337	6.32	160.5	0.468	11.9	13.5	OT	CG	N
3.656	92.86	73402	12.0	304.8	2.656	67.5	249	44	3.5	90	876	3896	6.75	171.5	0.500	12.7	13.5	OT	CG	N
3.656	92.86	73408	12.0	304.8	2.594	65.9	323	57	3.2	82	1043	4640	7.22	183.4	0.531	13.5	13.6	OT	CG	N
3.656	92.86	73414	12.0	304.8	2.532	64.3	412	72	2.9	75	1214	5398	7.73	196.3	0.562	14.3	13.8	OT	CG	N
3.656	92.86	73420	12.0	304.8	2.470	62.7	538	94	2.6	66	1389	6178	8.01	203.3	0.593	15.1	13.5	OT	CG	N
3.656	92.86	73367	14.0	355.6	2.932	74.5	54	9.5	6.8	174	371	1649	5.34	135.6	0.362	9.2	14.7	OT	CG	N
3.656	92.86	73373	14.0	355.6	2.906	73.8	64	11	6.5	164	411	1829	5.49	139.4	0.375	9.5	14.6	OT	CG	N
3.656	92.86	73379	14.0	355.6	2.870	72.9	78	14	5.9	151	461	2050	5.78	146.8	0.393	10.0	14.7	OT	CG	N
3.656	92.86	73385	14.0	355.6	2.844	72.2	90	16	5.7	144	507	2256	5.97	151.6	0.406	10.3	14.7	OT	CG	N
3.656	92.86	73391	14.0	355.6	2.782	70.7	118	21	5.2	132	614	2731	6.71	170.4	0.437	11.1	15.4	OT	CG	N
3.656	92.86	73397	14.0	355.6	2.720	69.1	158	28	4.8	121	750	3337	7.26	184.3	0.468	11.9	15.5	OT	CG	N
3.656	92.86	73403	14.0	355.6	2.656	67.5	210	37	4.2	106	876	3896	7.80	198.2	0.500	12.7	15.6	OT	CG	N
3.656	92.86	73409	14.0	355.6	2.594	65.9	272	48	3.8	97	1043	4640	8.36	212.5	0.531	13.5	15.8	OT	CG	N
3.656	92.86	73415	14.0	355.6	2.532	64.3	349	61	3.5	88	1214	5398	8.92	226.6	0.562	14.3	15.9	OT	CG	N
3.656	92.86	73421	14.0	355.6	2.470	62.7	454	80	3.1	78	1389	6178	9.27	235.3	0.593	15.1	15.6	OT	CG	N
3.656	92.86	73368	16.0	406.4	2.932	74.5	47	8.2	7.9	201	371	1649	6.07	154.1	0.362	9.2	16.8	OT	CG	N
3.656	92.86	73374	16.0	406.4	2.906	73.8	56	9.7	7.4	188	411	1829	6.19	157.2	0.375	9.5	16.5	OT	CG	N
3.656	92.86	73380	16.0	406.4	2.870	72.9	68	12	6.8	173	461	2050	6.53	165.9	0.393	10.0	16.6	OT	CG	N
3.656	92.86	73386	16.0	406.4	2.844	72.2	78	14	6.5	166	507	2256	6.75	171.4	0.406	10.3	16.6	OT	CG	N
3.656	92.86	73392	16.0	406.4	2.782	70.7	102	18	6.0	153	614	2731	7.61	193.2	0.437	11.1	1			

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH		
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm						
3.906	99.21	73441	6.00	152.4	3.032	77.0	258	45	2.2	57	577	2568	3.00	76.2	0.437	11.1	6.87	OT	CG	N		
3.906	99.21	73447	6.00	152.4	2.970	75.4	339	59	2.1	53	706	3139	3.28	83.3	0.468	11.9	7.01	OT	CG	N		
3.906	99.21	73453	6.00	152.4	2.906	73.8	455	80	1.8	46	824	3667	3.50	88.9	0.500	12.7	7.00	OT	CG	N		
3.906	99.21	73459	6.00	152.4	2.844	72.2	595	104	1.7	42	982	4370	3.71	94.4	0.531	13.5	7.00	OT	CG	N		
3.906	99.21	73465	6.00	152.4	2.782	70.7	767	134	1.5	38	1144	5087	3.93	99.9	0.562	14.3	7.00	OT	CG	N		
3.906	99.21	73471	6.00	152.4	2.720	69.1	978	171	1.3	34	1310	5827	4.15	105.4	0.593	15.1	7.00	OT	CG	N		
3.906	99.21	73477	6.00	152.4	2.656	67.5	1307	229	1.2	30	1525	6782	4.22	107.2	0.625	15.9	6.75	OT	CG	N		
3.906	99.21	73424	8.00	203.2	3.156	80.2	99	17	3.9	99	386	1718	3.20	81.2	0.375	9.5	8.52	OT	CG	N		
3.906	99.21	73430	8.00	203.2	3.120	79.2	122	21	3.5	90	433	1926	3.33	84.7	0.393	10.0	8.48	OT	CG	N		
3.906	99.21	73436	8.00	203.2	3.094	78.6	136	24	3.5	89	477	2120	3.53	89.7	0.406	10.3	8.70	OT	CG	N		
3.906	99.21	73442	8.00	203.2	3.032	77.0	186	33	3.1	79	577	2568	3.82	97.1	0.437	11.1	8.75	OT	CG	N		
3.906	99.21	73448	8.00	203.2	2.970	75.4	242	42	2.9	74	706	3139	4.22	107.1	0.468	11.9	9.01	OT	CG	N		
3.906	99.21	73454	8.00	203.2	2.906	73.8	325	57	2.5	64	824	3667	4.50	114.2	0.500	12.7	9.00	OT	CG	N		
3.906	99.21	73460	8.00	203.2	2.844	72.2	425	74	2.3	59	982	4370	4.78	121.3	0.531	13.5	9.00	OT	CG	N		
3.906	99.21	73466	8.00	203.2	2.782	70.7	548	96	2.1	53	1144	5087	5.06	128.4	0.562	14.3	9.00	OT	CG	N		
3.906	99.21	73472	8.00	203.2	2.720	69.1	699	122	1.9	48	1310	5827	5.33	135.5	0.593	15.1	8.99	OT	CG	N		
3.906	99.21	73478	8.00	203.2	2.656	67.5	920	161	1.7	42	1525	6782	5.47	138.9	0.625	15.9	8.75	OT	CG	N		
3.906	99.21	73425	10.0	254.0	3.156	80.2	78	14	5.0	126	386	1718	3.85	97.9	0.375	9.5	10.3	OT	CG	N		
3.906	99.21	73431	10.0	254.0	3.120	79.2	96	17	4.5	115	433	1926	4.02	102.2	0.393	10.0	10.2	OT	CG	N		
3.906	99.21	73437	10.0	254.0	3.094	78.6	107	19	4.5	113	477	2120	4.27	108.4	0.406	10.3	10.5	OT	CG	N		
3.906	99.21	73443	10.0	254.0	3.032	77.0	143	25	4.0	103	577	2568	4.71	119.7	0.437	11.1	10.8	OT	CG	N		
3.906	99.21	73449	10.0	254.0	2.970	75.4	189	33	3.7	95	706	3139	5.14	130.5	0.468	11.9	11.0	OT	CG	N		
3.906	99.21	73455	10.0	254.0	2.906	73.8	253	44	3.3	83	824	3667	5.49	139.5	0.500	12.7	11.0	OT	CG	N		
3.906	99.21	73461	10.0	254.0	2.844	72.2	330	58	3.0	76	982	4370	5.85	148.5	0.531	13.5	11.0	OT	CG	N		
3.906	99.21	73467	10.0	254.0	2.782	70.7	420	74	2.7	69	1144	5087	6.26	158.9	0.562	14.3	11.1	OT	CG	N		
3.906	99.21	73473	10.0	254.0	2.720	69.1	536	94	2.4	62	1310	5827	6.59	167.5	0.593	15.1	11.1	OT	CG	N		
3.906	99.21	73479	10.0	254.0	2.656	67.5	710	124	2.1	55	1525	6782	6.72	170.6	0.625	15.9	10.7	OT	CG	N		
3.906	99.21	73426	12.0	304.8	3.156	80.2	65	11	5.9	151	386	1718	4.48	113.7	0.375	9.5	11.9	OT	CG	N		
3.906	99.21	73432	12.0	304.8	3.120	79.2	79	14	5.5	139	433	1926	4.72	119.9	0.393	10.0	12.0	OT	CG	N		
3.906	99.21	73438	12.0	304.8	3.094	78.6	88	15	5.4	138	477	2120	5.01	127.4	0.406	10.3	12.4	OT	CG	N		
3.906	99.21	73444	12.0	304.8	3.032	77.0	120	21	4.8	122	577	2568	5.45	138.4	0.437	11.1	12.5	OT	CG	N		
3.906	99.21	73450	12.0	304.8	2.970	75.4	154	27	4.6	116	706	3139	6.09	154.8	0.468	11.9	13.0	OT	CG	N		
3.906	99.21	73456	12.0	304.8	2.906	73.8	207	36	4.0	101	824	3667	6.49	164.9	0.500	12.7	13.0	OT	CG	N		
3.906	99.21	73462	12.0	304.8	2.844	72.2	270	47	3.6	92	982	4370	6.91	175.5	0.531	13.5	13.0	OT	CG	N		
3.906	99.21	73468	12.0	304.8	2.782	70.7	345	60	3.3	84	1144	5087	7.37	187.2	0.562	14.3	13.1	OT	CG	N		
3.906	99.21	73474	12.0	304.8	2.720	69.1	439	77	3.0	76	1310	5827	7.79	197.8	0.593	15.1	13.1	OT	CG	N		
3.906	99.21	73480	12.0	304.8	2.656	67.5	578	101	2.6	67	1525	6782	7.97	202.3	0.625	15.9	12.7	OT	CG	N		
3.906	99.21	73427	14.0	355.6	3.156	80.2	54	9.5	7.2	182	386	1718	5.23	132.9	0.375	9.5	14.0	OT	CG	N		
3.906	99.21	73433	14.0	355.6	3.120	79.2	66	12	6.6	167	433	1926	5.50	139.6	0.393	10.0	14.0	OT	CG	N		
3.906	99.21	73439	14.0	355.6	3.094	78.6	74	13	6.4	164	477	2120	5.81	147.6	0.406	10.3	14.3	OT	CG	N		
3.906	99.21	73445	14.0	355.6	3.032	77.0	100	18	5.8	147	577	2568	6.36	161.6	0.437	11.1	14.6	OT	CG	N		
3.906	99.21	73451	14.0	355.6	2.970	75.4	131	23	5.4	137	706	3139	7.00	177.8	0.468	11.9	15.0	OT	CG	N		
3.906	99.21	73457	14.0	355.6	2.906	73.8	175	31	4.7	120	824	3667	7.50	190.4	0.500	12.7	15.0	OT	CG	N		
3.906	99.21	73463	14.0	355.6	2.844	72.2	229	40	4.3	109	982	4370	7.96	202.1	0.531	13.5	15.0	OT	CG	N		
3.906	99.21	73469	14.0	355.6	2.782	70.7	289	51	4.0	101	1144	5087	8.58	218.0	0.562	14.3	15.3	OT	CG	N		
3.906	99.21	73475	14.0	355.6	2.720	69.1	369	65	3.6	90	1310	5827	9.04	229.7	0.593	15.1	15.2	OT	CG	N		
3.906	99.21	73481	14.0	355.6	2.656	67.5	487	85	3.1	80	1525	6782	9.22	234.2	0.625	15.9	14.8	OT	CG	N		
3.906	99.21	73428	16.0	406.4	3.156	80.2	47	8.2	8.2	209	386	1718	5.90	149.9	0.375	9.5	15.7	OT	CG	N		
3.906	99.21	73434	16.0	406.4	3.120	79.2	57	10	7.6	193	433	1926	6.24	158.5	0.393	10.0	15.9	OT	CG	N		
3.906	99.21	73440	16.0	406.4	3.094	78.6	64	11	7.4	189	477	2120	6.59	167.4	0.406	10.3	16.2	OT	CG	N		
3.906	99.21	73446	16.0	406.4	3.032	77.0	87	15	6.6	169	577	2568	7.18	182.4	0.437	11.1	16.4	OT	CG	N		
3.906	99.21	73452	16.0	406.4	2.970	75.4	113	20	6.2	159	706	3139	7.96	202.3	0.468	11.9	17.0	OT	CG	N		
3.906	99.21	73458	16.0	406.4	2.906	73.8	152	27	5.4	138	824	3667	8.48	215.4	0.500	12.7	17.0	OT	CG	N		
3.906	99.21	73464	16.0	406.4	2.844	72.2	198	35	5.0	126	982	4370	9.03	229.5	0.531	13.5	17.0	OT	CG	N		
3.906	99.21	73470	16.0	406.4	2.782	70.7	251	44	4.6	116	1144	5087	9.71	246.6	0.562	14.3	17.3	OT	CG	N		
3.906	99.21	73476	16.0	406.4	2.720	69.1	321	56	4.1	104	1310	5827	10.2	259.5	0.593	15.1	17.2	OT	CG	N		
3.906	99.21	73482	16.0	406.4	2.656	67.5	421	74	3.6	92	1525	6782	10.5	265.9	0.625	15.9	16.8	OT	CG	N		
3.968	100.79	S-1596	3.50	88.9	3.728	94.7		41	07	1.9	49		.80	3.5	1.56	39.6	0.120	3.0	13.0	SST	CG	N
4.000	101.60	4052	4.25	108.0	2.000	50.8	26620	4662		.14	3.5	3645	16214	4.00	101.6	1.000	25.4	4.00	HD	CG	Z	
4.000	101.60	4030	6.00	152.4	3.338	84.8	116	20	2.0	52	238	1057	1.66	42.0	0.331	8.4	5.00	SPR	CG	N		
4.000	101.60	4082	6.25	158.8	2.812	71.4	2265	397	.51	13	1145	5095	2.38	60.4	0.594	15.1	4.00	HD	CG	N		
4.000	101.60	4020	6.25	158.8	2.750	69.9	1201	210	1.1	28	1327	5903	4.22	107.2	0.625	15.9	6.75	SPR	CG	N		
4.000	101.60	4048	10.0	254.0	2.500	63.5	2208	387	.88	22	1939	8625	6.00	152.4	0.750	19.1	8.00	SPR	CG	N		
4.125	104.78	4406	4.00	101.6	3.713	94.3	17	3.0	3.1	78	52	231	.92	23.4	0.206	5.2	4.50	SPR	CG	Z		
4.125	104.78	11302	4.00	101.6	3.375	85.7	127	22	1.7	42	210	934	2.34									




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
4.156	105.56	73520	8.00	203.2	3.094	78.6	380	67	2.4	62	928	4129	4.41	112.1	0.531	13.5	8.31	OT	CG	N
4.156	105.56	73526	8.00	203.2	3.032	77.0	485	85	2.2	57	1081	4809	4.71	119.6	0.562	14.3	8.38	OT	CG	N
4.156	105.56	73532	8.00	203.2	2.970	75.4	616	108	2.0	51	1239	5511	4.97	126.2	0.593	15.1	8.38	OT	CG	N
4.156	105.56	73485	10.0	254.0	3.406	86.5	70	12	5.2	132	364	1620	3.56	90.5	0.375	9.5	9.50	OT	CG	N
4.156	105.56	73491	10.0	254.0	3.370	85.6	86	15	4.8	121	408	1816	3.73	94.8	0.393	10.0	9.50	OT	CG	N
4.156	105.56	4099-F	10.0	254.0	3.344	84.9	129	23	3.1	79	400	1777	3.15	79.9	0.406	10.3	7.75	SPR	CG	N
4.156	105.56	73497	10.0	254.0	3.344	84.9	93	16	4.9	123	449	1999	4.06	103.1	0.406	10.3	10.0	OT	CG	N
4.156	105.56	73503	10.0	254.0	3.282	83.4	127	22	4.3	109	545	2423	4.37	111.0	0.437	11.1	10.0	OT	CG	N
4.156	105.56	73509	10.0	254.0	3.220	81.8	172	30	3.9	98	666	2963	4.68	118.9	0.468	11.9	10.0	OT	CG	N
4.156	105.56	73515	10.0	254.0	3.156	80.2	216	38	3.6	91	778	3463	5.25	133.4	0.500	12.7	10.5	OT	CG	N
4.156	105.56	73521	10.0	254.0	3.094	78.6	295	52	3.1	80	928	4129	5.38	136.6	0.531	13.5	10.1	OT	CG	N
4.156	105.56	73527	10.0	254.0	3.032	77.0	377	66	2.9	73	1081	4809	5.73	145.6	0.562	14.3	10.2	OT	CG	N
4.156	105.56	73533	10.0	254.0	2.970	75.4	476	83	2.6	66	1239	5511	6.08	154.4	0.593	15.1	10.3	OT	CG	N
4.156	105.56	73486	12.0	304.8	3.406	86.5	58	10	6.3	161	364	1620	4.17	106.0	0.375	9.5	11.1	OT	CG	N
4.156	105.56	73492	12.0	304.8	3.370	85.6	71	12	5.8	147	408	1816	4.37	111.1	0.393	10.0	11.1	OT	CG	N
4.156	105.56	73498	12.0	304.8	3.344	84.9	76	13	5.9	150	449	1999	4.77	121.1	0.406	10.3	11.7	OT	CG	N
4.156	105.56	73504	12.0	304.8	3.282	83.4	105	18	5.2	132	545	2423	5.14	130.5	0.437	11.1	11.8	OT	CG	N
4.156	105.56	73510	12.0	304.8	3.220	81.8	141	25	4.7	120	666	2963	5.50	139.7	0.468	11.9	11.8	OT	CG	N
4.156	105.56	73516	12.0	304.8	3.156	80.2	175	31	4.4	113	778	3463	6.25	158.8	0.500	12.7	12.5	OT	CG	N
4.156	105.56	73522	12.0	304.8	3.094	78.6	240	42	3.9	98	928	4129	6.37	161.8	0.531	13.5	12.0	OT	CG	N
4.156	105.56	73528	12.0	304.8	3.032	77.0	309	54	3.5	89	1081	4809	6.74	171.3	0.562	14.3	12.0	OT	CG	N
4.156	105.56	73534	12.0	304.8	2.970	75.4	388	68	3.2	81	1239	5511	7.19	182.6	0.593	15.1	12.1	OT	CG	N
4.156	105.56	73487	14.0	355.6	3.406	86.5	49	8.6	7.4	189	364	1620	4.78	121.5	0.375	9.5	12.8	OT	CG	N
4.156	105.56	73493	14.0	355.6	3.370	85.6	60	10	6.8	173	408	1816	5.02	127.4	0.393	10.0	12.8	OT	CG	N
4.156	105.56	73499	14.0	355.6	3.344	84.9	65	11	6.9	175	449	1999	5.43	137.9	0.406	10.3	13.4	OT	CG	N
4.156	105.56	73505	14.0	355.6	3.282	83.4	89	16	6.1	156	545	2423	5.90	149.9	0.437	11.1	13.5	OT	CG	N
4.156	105.56	73511	14.0	355.6	3.220	81.8	120	21	5.6	142	666	2963	6.32	160.5	0.468	11.9	13.5	OT	CG	N
4.156	105.56	73517	14.0	355.6	3.156	80.2	150	26	5.2	132	778	3463	7.12	181.0	0.500	12.7	14.2	OT	CG	N
4.156	105.56	73523	14.0	355.6	3.094	78.6	204	36	4.5	115	928	4129	7.30	185.4	0.531	13.5	13.7	OT	CG	N
4.156	105.56	73529	14.0	355.6	3.032	77.0	260	46	4.2	106	1081	4809	7.80	198.1	0.562	14.3	13.9	OT	CG	N
4.156	105.56	73535	14.0	355.6	2.970	75.4	328	57	3.8	96	1239	5511	8.30	210.9	0.593	15.1	14.0	OT	CG	N
4.156	105.56	73488	16.0	406.4	3.406	86.5	43	7.5	8.5	216	364	1620	5.35	135.8	0.375	9.5	14.3	OT	CG	N
4.156	105.56	73494	16.0	406.4	3.370	85.6	52	9.0	7.9	201	408	1816	5.70	144.7	0.393	10.0	14.5	OT	CG	N
4.156	105.56	73500	16.0	406.4	3.344	84.9	56	9.9	8.0	202	449	1999	6.14	156.0	0.406	10.3	15.1	OT	CG	N
4.156	105.56	73506	16.0	406.4	3.282	83.4	77	13	7.1	180	545	2423	6.67	169.3	0.437	11.1	15.3	OT	CG	N
4.156	105.56	73512	16.0	406.4	3.220	81.8	104	18	6.4	163	666	2963	7.14	181.4	0.468	11.9	15.3	OT	CG	N
4.156	105.56	73518	16.0	406.4	3.156	80.2	129	23	6.0	153	778	3463	8.13	206.4	0.500	12.7	16.3	OT	CG	N
4.156	105.56	73524	16.0	406.4	3.094	78.6	176	31	5.3	134	928	4129	8.28	210.4	0.531	13.5	15.6	OT	CG	N
4.156	105.56	73530	16.0	406.4	3.032	77.0	225	39	4.8	122	1081	4809	8.85	224.9	0.562	14.3	15.8	OT	CG	N
4.156	105.56	73536	16.0	406.4	2.970	75.4	283	50	4.4	111	1239	5511	9.42	239.1	0.593	15.1	15.9	OT	CG	N
4.250	107.95	4021	10.8	273.1	2.250	57.2	6979	1222	.50	13	3492	15531	8.00	203.2	1.000	25.4	8.00	SPR	CG	N
4.375	111.13	4022	8.00	203.2	2.499	63.5	6091	1067	.47	12	2863	12733	6.10	154.9	0.938	23.8	6.50	SPR	CG	N
4.406	111.91	73537	6.00	152.4	3.532	89.7	197	34	2.6	66	515	2293	2.73	69.4	0.437	11.1	6.26	OT	CG	N
4.406	111.91	73543	6.00	152.4	3.470	88.1	266	47	2.4	60	631	2805	2.92	74.2	0.468	11.9	6.25	OT	CG	N
4.406	111.91	73549	6.00	152.4	3.406	86.5	355	62	2.1	53	737	3280	3.12	79.3	0.500	12.7	6.25	OT	CG	N
4.406	111.91	73555	6.00	152.4	3.344	84.9	462	81	1.9	48	879	3912	3.32	84.3	0.531	13.5	6.25	OT	CG	N
4.406	111.91	73561	6.00	152.4	3.282	83.4	594	104	1.7	44	1025	4558	3.51	89.2	0.562	14.3	6.25	OT	CG	N
4.406	111.91	73567	6.00	152.4	3.220	81.8	754	132	1.6	40	1175	5226	3.71	94.2	0.593	15.1	6.25	OT	CG	N
4.406	111.91	73573	6.00	152.4	3.156	80.2	955	167	1.4	36	1369	6089	3.91	99.2	0.625	15.9	6.25	OT	CG	N
4.406	111.91	73538	8.00	203.2	3.532	89.7	143	25	3.6	92	515	2293	3.44	87.3	0.437	11.1	7.86	OT	CG	N
4.406	111.91	73544	8.00	203.2	3.470	88.1	188	33	3.4	85	631	2805	3.75	95.2	0.468	11.9	8.01	OT	CG	N
4.406	111.91	73550	8.00	203.2	3.406	86.5	251	44	2.9	75	737	3280	4.00	101.7	0.500	12.7	8.01	OT	CG	N
4.406	111.91	73556	8.00	203.2	3.344	84.9	327	57	2.7	68	879	3912	4.25	108.0	0.531	13.5	8.01	OT	CG	N
4.406	111.91	73562	8.00	203.2	3.282	83.4	421	74	2.4	62	1025	4558	4.49	114.2	0.562	14.3	8.00	OT	CG	N
4.406	111.91	73568	8.00	203.2	3.220	81.8	534	94	2.2	56	1175	5226	4.75	120.6	0.593	15.1	8.01	OT	CG	N
4.406	111.91	73574	8.00	203.2	3.156	80.2	676	118	2.0	51	1369	6089	5.00	127.0	0.625	15.9	8.00	OT	CG	N
4.406	111.91	73539	10.0	254.0	3.532	89.7	112	20	4.6	117	515	2293	4.15	105.3	0.437	11.1	9.49	OT	CG	N
4.406	111.91	73545	10.0	254.0	3.470	88.1	146	26	4.3	110	631	2805	4.56	115.7	0.468	11.9	9.73	OT	CG	N
4.406	111.91	73551	10.0	254.0	3.406	86.5	195	34	3.8	96	737	3280	4.87	123.6	0.500	12.7	9.73	OT	CG	N
4.406	111.91	73557	10.0	254.0	3.344	84.9	253	44	3.5	88	879	3912	5.18	131.7	0.531	13.5	9.76	OT	CG	N
4.406	111.91	73563	10.0	254.0	3.282	83.4	326	57	3.1	80	1025	4558	5.48	139.1	0.562	14.3	9.74	OT	CG	N
4.406	111.91	73569	10.0	254.0	3.220	81.8	414	72	2.8	72	1175	5226	5.78	146.8	0.593	15.1	9.75	OT	CG	N
4.406	111.91	73575	10.0	254.0	3.156	80.2	524	92	2.6	66	1369	6089	6.09	154.7	0.625	15.9	9.74	OT	CG	N
4.406	111.91	73540	12.0	304.8	3.532	89.7	93	16	5.5	141	515	2293	4.81	122.3	0.437	11.1	11.0	OT	CG	N
4.406	111.91	73546	12.0	304.8	3.470	88.1														

COMPRESSION SPRINGS



O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
4.406	111.91	73560	16.0	406.4	3.344	84.9	151	26	5.8	148	879	3912	7.97	202.4	0.531	13.5	15.0	OT	CG	N
4.406	111.91	73566	16.0	406.4	3.282	83.4	194	34	5.3	134	1025	4558	8.44	214.3	0.562	14.3	15.0	OT	CG	N
4.406	111.91	73572	16.0	406.4	3.220	81.8	246	43	4.8	121	1175	5226	8.92	226.4	0.593	15.1	15.0	OT	CG	N
4.406	111.91	73578	16.0	406.4	3.156	80.2	306	54	4.5	114	1369	6089	9.54	242.3	0.625	15.9	15.3	OT	CG	N
4.500	114.30	4023	4.00	101.6	3.250	82.6	1675	293	.71	18	1194	5310	2.66	67.5	0.625	15.9	4.25	SPR	CG	Z
4.500	114.30	4041	6.00	152.4	3.376	85.8	522	91	1.7	43	893	3973	3.65	92.8	0.562	14.3	6.50	SPR	CG	Z
4.500	114.30	4046	6.50	165.1	3.564	90.5	263	46	2.1	53	550	2444	2.81	71.3	0.468	11.9	6.00	SPR	CG	Z
4.500	114.30	10940	9.00	228.6	3.820	97.0	63	11	3.6	91	225	999	2.13	54.0	0.340	8.6	6.25	SPR	CG	N
4.500	114.30	4087	10.5	266.7	2.500	63.5	5588	979	.82	21	4580	20380	8.00	203.2	1.000	25.4	8.00	HD	CG	N
4.687	119.05	4079	6.00	152.4	4.187	106.3	21	3.8	4.4	112	94	419	1.25	31.8	0.250	6.4	5.00	SPR	CG	N
4.687	119.05	73579	6.00	152.4	3.901	99.1	124	22	2.9	75	364	1620	2.16	54.9	0.393	10.0	5.50	OT	CG	N
4.687	119.05	73585	6.00	152.4	3.875	98.4	137	24	2.9	74	401	1783	2.28	58.0	0.406	10.3	5.63	OT	CG	N
4.687	119.05	73591	6.00	152.4	3.813	96.9	182	32	2.7	68	486	2162	2.51	63.8	0.437	11.1	5.75	OT	CG	N
4.687	119.05	73597	6.00	152.4	3.751	95.3	245	43	2.4	62	595	2646	2.69	68.4	0.468	11.9	5.75	OT	CG	N
4.687	119.05	73603	6.00	152.4	3.687	93.6	326	57	2.1	54	696	3095	2.88	73.0	0.500	12.7	5.75	OT	CG	N
4.687	119.05	73609	6.00	152.4	3.625	92.1	398	70	2.1	53	830	3693	3.19	80.9	0.531	13.5	6.00	OT	CG	N
4.687	119.05	73615	6.00	152.4	3.563	90.5	511	89	1.9	48	968	4305	3.37	85.7	0.562	14.3	6.00	OT	CG	N
4.687	119.05	73621	6.00	152.4	3.501	88.9	648	113	1.7	44	1110	4938	3.56	90.4	0.593	15.1	6.00	OT	CG	N
4.687	119.05	73627	6.00	152.4	3.437	87.3	818	143	1.6	40	1294	5756	3.75	95.3	0.625	15.9	6.00	OT	CG	N
4.687	119.05	73580	8.00	203.2	3.901	99.1	89	16	4.1	104	364	1620	2.70	68.6	0.393	10.0	6.88	OT	CG	N
4.687	119.05	73586	8.00	203.2	3.875	98.4	100	17	4.0	102	401	1783	2.84	72.2	0.406	10.3	7.00	OT	CG	N
4.687	119.05	73592	8.00	203.2	3.813	96.9	130	23	3.7	95	486	2162	3.17	80.5	0.437	11.1	7.25	OT	CG	N
4.687	119.05	73598	8.00	203.2	3.751	95.3	175	31	3.4	86	595	2646	3.39	86.2	0.468	11.9	7.25	OT	CG	N
4.687	119.05	73604	8.00	203.2	3.687	93.6	233	41	3.0	76	696	3095	3.63	92.1	0.500	12.7	7.25	OT	CG	N
4.687	119.05	73610	8.00	203.2	3.625	92.1	283	50	2.9	75	830	3693	4.05	102.9	0.531	13.5	7.63	OT	CG	N
4.687	119.05	73616	8.00	203.2	3.563	90.5	363	64	2.7	68	968	4305	4.29	108.8	0.562	14.3	7.63	OT	CG	N
4.687	119.05	73622	8.00	203.2	3.501	88.9	461	81	2.4	61	1110	4938	4.52	114.8	0.593	15.1	7.63	OT	CG	N
4.687	119.05	73628	8.00	203.2	3.437	87.3	574	101	2.3	57	1294	5756	4.81	122.2	0.625	15.9	7.70	OT	CG	N
4.687	119.05	73581	10.0	254.0	3.901	99.1	69	12	5.3	133	364	1620	3.24	82.4	0.393	10.0	8.25	OT	CG	N
4.687	119.05	73587	10.0	254.0	3.875	98.4	78	14	5.1	130	401	1783	3.40	86.4	0.406	10.3	8.37	OT	CG	N
4.687	119.05	73593	10.0	254.0	3.813	96.9	101	18	4.8	122	486	2162	3.82	97.1	0.437	11.1	8.75	OT	CG	N
4.687	119.05	73599	10.0	254.0	3.751	95.3	136	24	4.4	111	595	2646	4.10	104.0	0.468	11.9	8.75	OT	CG	N
4.687	119.05	73605	10.0	254.0	3.687	93.6	181	32	3.8	97	696	3095	4.38	111.1	0.500	12.7	8.75	OT	CG	N
4.687	119.05	73611	10.0	254.0	3.625	92.1	220	38	3.8	96	830	3693	4.91	124.8	0.531	13.5	9.25	OT	CG	N
4.687	119.05	73617	10.0	254.0	3.563	90.5	282	49	3.4	87	968	4305	5.20	132.0	0.562	14.3	9.25	OT	CG	N
4.687	119.05	73623	10.0	254.0	3.501	88.9	351	62	3.2	80	1110	4938	5.56	141.2	0.593	15.1	9.38	OT	CG	N
4.687	119.05	73629	10.0	254.0	3.437	87.3	444	78	2.9	74	1294	5756	5.86	148.8	0.625	15.9	9.38	OT	CG	N
4.687	119.05	73582	12.0	304.8	3.901	99.1	58	10	6.3	160	364	1620	3.74	94.9	0.393	10.0	9.51	OT	CG	N
4.687	119.05	73588	12.0	304.8	3.875	98.4	64	11	6.2	159	401	1783	3.96	100.6	0.406	10.3	9.75	OT	CG	N
4.687	119.05	73594	12.0	304.8	3.813	96.9	83	14	5.9	149	486	2162	4.48	113.8	0.437	11.1	10.2	OT	CG	N
4.687	119.05	73600	12.0	304.8	3.751	95.3	111	19	5.3	136	595	2646	4.80	121.8	0.468	11.9	10.3	OT	CG	N
4.687	119.05	73606	12.0	304.8	3.687	93.6	148	26	4.7	119	696	3095	5.12	130.1	0.500	12.7	10.2	OT	CG	N
4.687	119.05	73612	12.0	304.8	3.625	92.1	179	31	4.6	118	830	3693	5.77	146.7	0.531	13.5	10.9	OT	CG	N
4.687	119.05	73618	12.0	304.8	3.563	90.5	230	40	4.2	107	968	4305	6.11	155.2	0.562	14.3	10.9	OT	CG	N
4.687	119.05	73624	12.0	304.8	3.501	88.9	288	50	3.9	98	1110	4938	6.52	165.7	0.593	15.1	11.0	OT	CG	N
4.687	119.05	73630	12.0	304.8	3.437	87.3	362	63	3.6	91	1294	5756	6.91	175.4	0.625	15.9	11.1	OT	CG	N
4.687	119.05	73583	14.0	355.6	3.901	99.1	49	8.5	7.5	190	364	1620	4.27	108.6	0.393	10.0	10.9	OT	CG	N
4.687	119.05	73589	14.0	355.6	3.875	98.4	54	9.4	7.5	189	401	1783	4.57	116.0	0.406	10.3	11.3	OT	CG	N
4.687	119.05	73595	14.0	355.6	3.813	96.9	70	12	6.9	176	486	2162	5.14	130.5	0.437	11.1	11.8	OT	CG	N
4.687	119.05	73601	14.0	355.6	3.751	95.3	94	16	6.3	160	595	2646	5.50	139.7	0.468	11.9	11.7	OT	CG	N
4.687	119.05	73607	14.0	355.6	3.687	93.6	126	22	5.5	141	696	3095	5.88	149.3	0.500	12.7	11.8	OT	CG	N
4.687	119.05	73613	14.0	355.6	3.625	92.1	152	27	5.5	139	830	3693	6.64	168.6	0.531	13.5	12.5	OT	CG	N
4.687	119.05	73619	14.0	355.6	3.563	90.5	195	34	5.0	126	968	4305	7.02	178.4	0.562	14.3	12.5	OT	CG	N
4.687	119.05	73625	14.0	355.6	3.501	88.9	244	43	4.6	116	1110	4938	7.49	190.2	0.593	15.1	12.6	OT	CG	N
4.687	119.05	73631	14.0	355.6	3.437	87.3	304	53	4.3	108	1294	5756	7.97	202.4	0.625	15.9	12.8	OT	CG	N
4.687	119.05	73584	16.0	406.4	3.901	99.1	42	7.4	8.6	219	364	1620	4.81	122.2	0.393	10.0	12.2	OT	CG	N
4.687	119.05	73590	16.0	406.4	3.875	98.4	47	8.3	8.5	215	401	1783	5.08	128.9	0.406	10.3	12.5	OT	CG	N
4.687	119.05	73596	16.0	406.4	3.813	96.9	61	11	8.0	203	486	2162	5.79	147.1	0.437	11.1	13.3	OT	CG	N
4.687	119.05	73602	16.0	406.4	3.751	95.3	82	14	7.3	185	595	2646	6.20	157.5	0.468	11.9	13.3	OT	CG	N
4.687	119.05	73608	16.0	406.4	3.687	93.6	109	19	6.4	162	696	3095	6.63	168.3	0.500	12.7	13.3	OT	CG	N
4.687	119.05	73614	16.0	406.4	3.625	92.1	131	23	6.3	161	830	3693	7.50	190.5	0.531	13.5	14.1	OT	CG	N
4.687	119.05	73620	16.0	406.4	3.563	90.5	169	30	5.7	146	968	4305	7.94	201.6	0.562	14.3	14.1	OT	CG	N
4.687	119.05	73626	16.0	406.4	3.501	88.9	209	37	5.3	135	1110	4938	8.53	216.5	0.593	15.1	14.4	OT	CG	N
4.687	119.05	73632	16.0	406.4	3.437	87.3	263	46	4.9	125	1294	5756	9.03	229.4	0.625	15.9	14.4	OT	CG	N
4.750	120.65	4049	5.50	139.7	3.814	96.9	251	44												



COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
4.906	124.61	73647	10.0	254.0	3.844	97.6	202	35	3.9	100	796	3539	4.65	118.1	0.531	13.5	8.76	OT	CG	N
4.906	124.61	73653	10.0	254.0	3.782	96.1	250	44	3.7	94	928	4126	5.06	128.4	0.562	14.3	9.00	OT	CG	N
4.906	124.61	73659	10.0	254.0	3.720	94.5	328	57	3.2	82	1064	4734	5.19	131.9	0.593	15.1	8.76	OT	CG	N
4.906	124.61	73665	10.0	254.0	3.656	92.9	399	70	3.1	79	1241	5520	5.63	143.0	0.625	15.9	9.01	OT	CG	N
4.906	124.61	73636	12.0	304.8	3.970	100.8	96	17	5.9	151	570	2534	4.78	121.5	0.468	11.9	10.2	OT	CG	N
4.906	124.61	73642	12.0	304.8	3.906	99.2	127	22	5.2	133	667	2965	5.14	130.4	0.500	12.7	10.3	OT	CG	N
4.906	124.61	73648	12.0	304.8	3.844	97.6	165	29	4.8	122	796	3539	5.45	138.5	0.531	13.5	10.3	OT	CG	N
4.906	124.61	73654	12.0	304.8	3.782	96.1	206	36	4.5	114	928	4126	5.90	149.8	0.562	14.3	10.5	OT	CG	N
4.906	124.61	73660	12.0	304.8	3.720	94.5	268	47	4.0	101	1064	4734	6.09	154.6	0.593	15.1	10.3	OT	CG	N
4.906	124.61	73666	12.0	304.8	3.656	92.9	329	58	3.8	96	1241	5520	6.56	166.7	0.625	15.9	10.5	OT	CG	N
4.906	124.61	73637	14.0	355.6	3.970	100.8	81	14	7.0	179	570	2534	5.49	139.6	0.468	11.9	11.7	OT	CG	N
4.906	124.61	73643	14.0	355.6	3.906	99.2	108	19	6.2	157	667	2965	5.86	148.9	0.500	12.7	11.7	OT	CG	N
4.906	124.61	73649	14.0	355.6	3.844	97.6	140	25	5.7	144	796	3539	6.24	158.4	0.531	13.5	11.7	OT	CG	N
4.906	124.61	73655	14.0	355.6	3.782	96.1	175	31	5.3	135	928	4126	6.74	171.2	0.562	14.3	12.0	OT	CG	N
4.906	124.61	73661	14.0	355.6	3.720	94.5	222	39	4.8	122	1064	4734	7.10	180.4	0.593	15.1	12.0	OT	CG	N
4.906	124.61	73667	14.0	355.6	3.656	92.9	273	48	4.5	115	1241	5520	7.65	194.3	0.625	15.9	12.2	OT	CG	N
4.906	124.61	73638	16.0	406.4	3.970	100.8	70	12	8.1	207	570	2534	6.21	157.7	0.468	11.9	13.3	OT	CG	N
4.906	124.61	73644	16.0	406.4	3.906	99.2	93	16	7.2	182	667	2965	6.65	168.8	0.500	12.7	13.3	OT	CG	N
4.906	124.61	73650	16.0	406.4	3.844	97.6	121	21	6.6	167	796	3539	7.05	179.1	0.531	13.5	13.3	OT	CG	N
4.906	124.61	73656	16.0	406.4	3.782	96.1	152	27	6.1	155	928	4126	7.59	192.8	0.562	14.3	13.5	OT	CG	N
4.906	124.61	73662	16.0	406.4	3.720	94.5	193	34	5.5	140	1064	4734	7.99	203.0	0.593	15.1	13.5	OT	CG	N
4.906	124.61	73668	16.0	406.4	3.656	92.9	238	42	5.2	132	1241	5520	8.59	218.2	0.625	15.9	13.7	OT	CG	N
5.000	127.00	4053	5.00	127.0	3.000	76.2	11230	1967	.4	10	4200	18690	4.00	101.6	1.000	25.4	4.00	HD	CG	N
5.000	127.00	4083	8.00	203.2	3.812	96.8	465	81	2.0	51	934	4155	3.86	98.1	0.594	15.1	6.50	HD	CG	N
5.000	127.00	4031	12.0	304.8	4.000	101.6	123	22	4.7	120	582	2589	5.00	127.0	0.500	12.7	10.0	SPR	CG	N
5.000	127.00	4088	12.0	304.8	3.124	79.3	2767	485	1.3	33	3600	16000	7.50	190.6	0.938	23.8	8.00	HD	CG	N
5.250	133.35	4022-A	4.00	101.6	4.926	125.1	4.1	.73	3.4	87	14	63	.56	14.2	0.162	4.1	3.50	SST	CG	N
5.500	139.70	4036	12.0	304.8	4.438	112.7	162	28	3.9	100	635	2824	4.12	104.5	0.531	13.5	7.75	SPR	CG	N
5.500	139.70	4000-A	18.8	476.3	4.500	114.3	78	14	6.8	174	532	2365	5.63	142.9	0.500	12.7	11.3	SPR	CG	N
5.750	146.05	4097	12.0	304.8	4.000	101.6	1818	318	1.4	36	2550	11350	5.25	133.4	0.875	22.2	6.00	HD	CG	N
6.000	152.40	4034	3.50	88.9	4.626	117.5	2135	374	.6	15	1220	5430	2.06	52.3	0.687	17.4	3.00	SPR	CG	N
6.000	152.40	4094	8.75	222.3	4.250	108.0	1669	292	1.5	38	2440	10860	5.03	127.8	0.875	22.2	5.75	HD	CG	N
6.000	152.40	4091	24.0	609.6	4.624	117.4	175	31	7	178	1210	5380	9.80	249.0	0.688	17.5	14.3	HD	CG	N
6.060	153.92	4099-A	17.0	431.8	5.490	139.4	4.9	.86	13	338	65	291	3.71	94.1	0.285	7.2	12.0	HD	C	GI
6.125	155.58	4078	14.0	355.6	5.687	144.4	3.5	.61	12	317	44	193	1.53	38.9	0.219	5.6	6.00	SST	C	N
6.250	158.75	4099-B	5.38	136.5	5.250	133.4	291	51	1.8	46	529	2354	1.81	46.1	0.500	12.7	3.63	OT	CG	N
6.250	158.75	4095	12.0	304.8	4.750	120.7	547	96	2.7	69	1500	6670	5.25	133.4	0.750	19.1	7.00	HD	CG	N
6.500	165.10	4089	5.00	127.0	4.500	114.3	4320	757	.8	20	3460	15400	4.00	101.6	1.000	25.4	4.00	HD	CG	N
6.500	165.10	4098	8.00	203.2	4.500	114.3	2033	356	1.6	41	3360	14950	6.25	158.8	1.000	25.4	6.25	HD	CG	N
6.500	165.10	4092	10.0	254.0	5.376	136.6	211	37	3.0	76	632	2811	2.95	74.9	0.562	14.3	5.25	HD	CG	N
7.250	184.15	4024-B	13.0	330.2	5.500	139.7	591	104	3.5	89	2060	9170	6.56	166.7	0.875	22.2	7.50	HD	CG	N
7.250	184.15	4099	29.0	736.6	6.126	155.6	34	6.0	17	422	569	2532	8.99	228.4	0.562	14.3	16.0	HD	CG	N
7.500	190.50	4022-C	6.50	165.1	6.000	152.4	370	65	2.0	51	739	3289	4.50	114.3	0.750	19.1	6.00	HD	CG	N
7.750	196.85	4044	10.0	254.0	6.938	176.2	39	6.9	5.6	141	219	975	1.83	46.4	0.406	10.3	4.50	SPR	CG	N
8.000	203.20	4024	10.0	254.0	6.250	158.8	717	126	2.6	66	1880	8360	4.59	116.7	0.875	22.2	5.25	SPR	CG	N
9.000	228.60	4027	32.0	812.8	7.876	200.1	28	4.9	16	418	462	2055	5.90	149.9	0.562	14.3	10.5	SPR	CG	N
9.250	234.95	4024-A	15.8	400.1	6.626	168.3	2004	351	2.7	69	5370	23890	8.20	208.3	1.312	33.3	6.25	HD	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

ENDS: C - Closed
G - Ground
O - Open

FINISH: Z - Zinc
BO - Black Oxide
GI - Gold Iridite
T - Tinned Wire

N -

