

FLASH FREE[®] ELECTRICAL DEGREASER



ELTM 848



For use on Energized Equipment



NSF[®] Registered; K2 Rated (Solvents for cleaning electronic instruments) (Registration # 115070)




Dielectric strength value 37,000 Volts



Non-Flammable



Evaporation Rate: Fast



KB Solvency Strength (higher value, stronger the solvent): 129



HMIS Hazard Rating:
Health (2) • Flammability (0) • Reactivity (0)

- Non-flammable, non-corrosive
- Replaces 1,1,1 Trichloroethene
- Leaves no residue



PRESERVE. PROTECT. PREVENT.TM

Sprayon[®] ELTM 848 Flash Free[®] Electrical Degreaser is a non-flammable, fast evaporating cleaner that penetrates instantly to remove the dirt, oil, grease, wax and other foreign materials that can decrease the life of electrical components & cause costly downtime. Degreases more thoroughly & several times faster than alkaline cleaners. Excellent for degreasing aluminum, cleaning sheet & strip steel prior to galvanizing. Equipped with a high delivery valve for cleaning efficiency, extension tubes are also included for hard-to-reach areas.

ELECTRICAL & ELECTRONIC

USES

- Electric motors
- Generators
- Air tools
- Brakes
- Clutches
- Chains
- Sprockets
- Wire rope
- Dies • Molds
- Relays • Locks
- Radar equipment
- Material handling equipment
- Air conditioners

APPLICATION

Product should be sprayed in a well ventilated area. Shake well before using. Sprays best at room temperature (70°F). Hold can in upright position for best spray pattern. Use extension tube for pinpoint application. NOTE: May harm certain plastics, elastomers and air-dry painted surfaces. Test product on non-essential similar material prior to application.

PERFORMANCE

- EVAPORATION RATE: Fast
KB VALUE (Cleaning Power): 129
DIELECTRIC STRENGTH: 37,000
PLASTIC SAFE: Most plastics, but test substrate first
- NSF Registration Number 115070, K2 Rated
 - No residue
 - Non-corrosive
 - Replacement for 1,1,1 Trichloroethene
 - Equipped with an extension tube for hard-to-reach areas

PACKAGING

- Stock #: S00848
UPC Code: 0-75577-90848-6
Fill Wt: 13 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 8"

- Stock #: S20848
UPC Code: 0-75577-20848-7
Fill Wt: 17 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 9-5/8"

RESOURCES

- MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486

PROPERTIES

- APPEARANCE: Clear Volatile Liquid
ODOR: Mild Solvent
PROPELLANT: CO₂
WT./GAL.: 14.04
SPECIFIC GRAVITY: 1.45
H.A.P.S. (Hazardous Air Pollutants): No
VOC AEROSOL: 98%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: No
FLASH POINT: N/A
HAZARD RATING: 2,0,0
SHELF LIFE: 3 years from date of manufacture

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



EL848



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-EL848