

High Pressure Full-Bore 3-Way Ball Valves

Features

- Rugged construction
- Black oxide coating

Materials

- FKM seals
- POM (Polyacetal) ball seats
- Nickel plated ball

Specification

- Temperature range: -20°F to 215° F (-29°C to 102°C)

| Female NPT | PSI | Carbon Steel Part # |
|------------|------|---------------------|
| 1/2" | 5145 | HPBV12-3WAY |
| 3/4" | | HPBV34-3WAY |
| 1" | | HPBV10-3WAY |



Standard L 90°

High Pressure Clear Zinc Ball Valves

Materials

- Nitrile rubber O-rings
- POM (Polyacetal) ball seats

Approval

- RoHS compliant

| Female NPT | PSI | Carbon Steel | | PSI |
|------------|------|--------------|---------------|------|
| | | Part # | SAE Part # | |
| 1/4" | 7350 | HPBV25ZPL | HPBV25SAEZPL | 7350 |
| 3/8" | | HPBV38ZPL | HPBV38SAEZPL | |
| 1/2" | | HPBV12ZPL | HPBV12SAEZPL | |
| 3/4" | 6000 | HPBV34ZPL | HPBV34SAEZPL | 6000 |
| 1" | | HPBV10ZPL | HPBV10SAEZPL | |
| 1-1/4" | | HPBV125ZPL | HPBV125SAEZPL | |
| 1-1/2" | | HPBV150ZPL | HPBV150SAEZPL | |
| 2" | | HPBV200ZPL | HPBV200SAEZPL | |



High Pressure Full-Bore Ball Valves

Features

- Blow-out proof stem
- Rugged construction

Materials

- FKM/FPM seals
- POM (Polyacetal) ball seats

| Female NPT | PSI | Carbon Steel | | PSI | 316 Stainless Steel Part # |
|------------|------|--------------|------------|------|----------------------------|
| | | Part # | SAE Part # | | |
| 1/4" | 7350 | HPBV25 | HPBV25SAE | 5880 | HPBV25SS |
| 3/8" | | HPBV38 | HPBV38SAE | | HPBV38SS |
| 1/2" | | HPBV12 | HPBV12SAE | | HPBV12SS |
| 3/4" | 6000 | HPBV34 | HPBV34SAE | 5145 | HPBV34SS |
| 1" | | HPBV10 | HPBV10SAE | | HPBV10SS |
| 1-1/4" | | HPBV125 | HPBV125SAE | --- | --- |
| 1-1/2" | | HPBV150 | HPBV150SAE | --- | --- |
| 2" | | HPBV200 | HPBV200SAE | --- | --- |

