



“E” dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Domestically Manufactured
excluding:
11GI
11GIFL
11HDGI



LISTED
excluding:
11RR



APPROVED
excluding:
11SS, 11SX & 11RR

| | | |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Materials/Finishes: | Plain Carbon Steel (11B) | Electro-Galvanized (11G) |
| | Hot-Dip Galvanized (11HDG) | T-304 Stainless (11SS) |
| | T-316 Stainless (11SX) | |
| Variants: | Pipe Gard (11PG) - Please contact factory for details. | |
| | Electro-Galvanized, Imported: 1/2" - 12" (11GI) | |
| | Electro-Galvanized, 3/16" thick Felt-Lined, Imported: 1/2" - 8" (11GIFL) | |
| | Hot-Dip Galvanized, Imported: 2"-3", 4"-6", 8"-12" (11HDGI) | |
| Service: | Designed for the suspension of non-insulated, stationary pipe lines. | |
| Approvals: | U.L. - U.L.C. listed (sizes 2-1/2" - 8" excluding 7") and FM approved (3/4" - 2" galv only, 2-1/2" - 8" plain and galv.). Complies with Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 1). | |
| Ordering: | Specify figure number, material, finish type and pipe size. | |
| Notes: | For sizes 20" and larger a spacer sleeve is added over the cross bolt. Upper locknut must be tightened securely to assure proper hanger performance. Stainless steel hangers are recommended for applications where protection from a corrosive environment is required. | |

| PIPE SIZE | PIPE OD | BOLT | A | B | C | E | F | WGT EACH (LBS) | MAX REC LOAD (LBS) |
|-----------|---------|-------|-------|----------|----------|----------|---------|----------------|--------------------|
| 1/2 | 0.840 | 1/4 | 3/8 | 1-11/16 | 2-1/16 | 5/16 | 7/16 | 0.18 | 730 |
| 3/4 | 1.050 | 1/4 | 3/8 | 1-11/16 | 2-9/16 | 1-5/16 | 7/16 | 0.18 | 730 |
| 1 | 1.315 | 1/4 | 3/8 | 2-1/16 | 2-11/16 | 1-1/4 | 5/8 | 0.22 | 730 |
| 1-1/4 | 1.660 | 1/4 | 3/8 | 2-1/2 | 3-3/16 | 1-11/16 | 7/8 | 0.26 | 730 |
| 1-1/2 | 1.900 | 1/4 | 3/8 | 2-7/8 | 3-11/16 | 2-1/16 | 1-1/16 | 0.34 | 730 |
| 2 | 2.375 | 1/4 | 3/8 | 3-5/16 | 4-7/16 | 2-1/2 | 1-1/4 | 0.38 | 730 |
| 2-1/2 | 2.875 | 5/16 | 1/2 | 4-1/2 | 5-7/8 | 3-3/8 | 1-15/16 | 0.86 | 1130 |
| 3 | 3.500 | 5/16 | 1/2 | 4-3/4 | 6-1/2 | 3-11/16 | 1-3/4 | 0.96 | 1130 |
| 3-1/2 * | 4.000 | 5/16 | 1/2 | 5-7/8 | 7-15/16 | 4-13/16 | 2-9/16 | 1.14 | 1350 |
| 4 | 4.500 | 3/8 | 5/8 | 5-15/16 | 8-3/16 | 4-9/16 | 2-1/8 | 1.26 | 1430 |
| 5 | 5.563 | 1/2 | 5/8 | 5-11/16 | 8-7/16 | 4-5/16 | 1-7/16 | 2.04 | 1430 |
| 6 | 6.625 | 1/2 | 3/4 | 6-13/16 | 10-1/8 | 5-3/16 | 1-3/4 | 2.80 | 1940 |
| 7 * | 7.625 | 1/2 | 3/4 | 7-13/16 | 11-5/8 | 6-3/16 | 2 | 3.24 | 2000 |
| 8 | 8.625 | 5/8 | 3/4 | 8-1/16 | 12-7/16 | 6-1/4 | 1-7/8 | 4.46 | 2000 |
| 10 | 10.750 | 3/4 | 7/8 | 10 | 15-7/16 | 8 | 2-1/4 | 8.06 | 3600 |
| 12 | 12.750 | 3/4 | 7/8 | 11-9/16 | 18 | 9-9/16 | 2-13/16 | 10.34 | 3800 |
| 14 | 14.000 | 7/8 | 1 | 12-9/16 | 19-9/16 | 10-9/16 | 2-9/16 | 14.80 | 4200 |
| 16 | 16.000 | 1 | 1 | 13-15/16 | 21-15/16 | 11-15/16 | 2-13/16 | 21.00 | 4600 |
| 18 | 18.000 | 1 | 1 | 16 | 25 | 13-7/8 | 3-3/4 | 24.40 | 4800 |
| 20 | 20.000 | 1-1/4 | 1-1/4 | 17-1/2 | 27-1/2 | 15-1/8 | 3-3/4 | 47.00 | 4800 |
| 24 | 24.000 | 1-1/4 | 1-1/4 | 19-3/4 | 31-3/4 | 17-3/8 | 4 | 54.00 | 4800 |
| 30 | 30.000 | 1-1/4 | 1-1/4 | 24-1/8 | 39-1/8 | 21-1/2 | 4-3/4 | 69.50 | 6000 |

* NOT AVAILABLE IN T-304 STAINLESS STEEL

| PROJECT INFORMATION | APPROVAL STAMP |
|---------------------------------------------------|----------------|
| Project: | Notes: |
| Address: | |
| Contractor: | |
| Engineer: | |
| Date: | |
| Approved Approved as Noted Not Approved | |