

PRODUCT SPECIFICATIONS

7007, 7007XL, 7007XX, 70073X FT Basic Standard Non-belted Harness

FT Basic harnesses are a compliance-grade, entry-level fall protection component for occasional use in Fall Arrest applications. Available only in a Dorsal D-ring configuration and with 3 points of body adjustment (legs and chest).

Features:

- Dorsal D-ring for Fall Arrest applications
- Mating Buckle chest and leg closures
- Includes single lanyard parking keeper
- Available in sizes UniFit (S, M, L) up to 3XL



Material Specifications	
Webbing:	Polyester, 5,000 lbs. Min. Static Strength
D-ring:	Plated Alloy Steel, 5,000 lbs. Min. Static Strength
Buckles/Adjusters:	Plated Alloy Steel, 3,375 lbs. Min. Static Strength

ANSI Performance Specifications	
Static Strength:	3,600 lbs. Min.
ANSI User Capacity:	310 lbs. Max.
OSHA User Capacity:	310 lbs. Max.

Part #	Size
7007	UniFit (S, M, L)
7007XL	XL
7007XX	2XL
70073X	3XL

Relevant Standards	
ANSI:	Z359.11-2014
OSHA:	1926.502 and 1910.66

WARNINGS

- Read, understand and follow all labels and instruction manual prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.