

# PRODUCT SPECIFICATIONS

## Hinged, Self-Tracking Rope Grab

## #7479

### Material Specifications

**Ring/body:** Alloy Steel; Min. 3,600 lbs. tensile strength

### Performance Specifications

**Tensile Strength:** Min. 3,600 lbs.  
**Max. Capacity:** 310 lbs.  
**Max. Freefall:** 6 feet  
**Max. Arrest Force:** Less than 1,800 lbs.  
**Max. Elongation:** 54 inches

### Relevant Standards

**OSHA:** CFR1926.502, CFR1910.66  
**ANSI:** Z359.1-2007

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



*This product must be used in conjunction with a 3' Shock-Absorbing Lanyard and rigged to allow a 6' max. free-fall.*

*Rope grab meets the requirements of ANSI Z359.1-2007 for strength and dynamic performance*

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.