

PRODUCT SPECIFICATIONS

SteelGrip Beam Anchor - Single Ratchet

#7531

Features

- Alloy steel jaws with nylon sliders.
- Lightweight aluminum flange bar.
- Easy ratcheting adjustment for quick installation and removal.
- Fits flange widths from 4" - 12" and up to 1" thick.
- Rated at over 5,000 lbs..
- Meets the requirements of OSHA 1926 and ANSI Z359.

Material Specifications

Jaws: *Alloy steel, min.5,000 lbs.*

D-ring: *Alloy steel, min. 5,000 lbs.*

Flange Bar: *Aluminum alloy, SAE 6066*

Performance Specifications

Tensile Strength: *Min. 5,000 lbs.*

Max. Capacity: *425 lbs.*
To maintain ANSI Z359 compliance, limit total user weight to 310lbs

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*

ANSI: *A10.32-2004, Z359.1-2007*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.