PRODUCT SPECIFICATIONS



ClearPack 6' Shock Absorbing Lanyard

#8256

Features

- · Single-leg lanyard for fall arrest.
- ClearPack shock absorber is designed to limit arrest forces to an average of 900 lbs.
- Clear PVC cover protects shock absorber and allows for easy inspection.
- \cdot 1" polyester webbing has a tensile strength of 9,800 lbs.
- Double-locking snap hooks at the attachment and anchorage ends.

Material Specifications

Webbing: Polyester; Min. 6,000 lbs. tensile strength
Energy Absorber: Polyester; activation greater than 450 lbs.
Connectors: Alloy Steel; Min. 5,000 lbs. tensile strength
Alloy Steel; Min. 3,600 lbs. front and side

load

Performance Specifications

Tensile Strength: Min. 5,000 lbs.

Max. Capacity: 310 lbs.
Max. Freefall: 6 feet

Average Arrest

Force: Less than 900 lbs.

Max. Elongation: 42 inches

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*

ANSI: *Z359.13-2009*

(Z359.13-2009 supercedes Z359.1-2007 for Shock Absorbing Lanyards)

Warnings

- \cdot Read, understand and follow all labels and $\,$ instructions prior to use.
- · Inspect before each use.
- \cdot Remove from service if there is evidence of damage or excessive wear.
- · Remove from service if there is any signs of activation.
- · Never attach a Shock Absorbing Lanyard to the front or side D-rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com