785.392.3017 FAX 785.392.2845




EXCEEDS 72 HR SALT SPRAY. 6,000 PSI MAX PRESSURE.

6,000 PSI

Button head fittings are popular in rugged applications such as on conveyors, mining equipment and agricultural equipment. The flat head design minimizes damage from flying debris.

H1184Z3

Button Head - Standard 1/8"-27 PTF Spl Short **Ball Check**




1 5701

* AVAILABLE IN STAINLESS

H1184N


Button Head - Standard 1/8"-27 NPTF No Ball Check



NO BALL CHECK

HC69

Button Head - Standard 1/8"-27 NPTF **Ball Check**




A C69

FEMALE THREADS

H1186Z3

Button Head - Standard 1/4"-18 PTF SAE Short **Ball Check**




L 5706

* AVAILABLE IN STAINLESS

H1188Z3

Button Head - Standard 3/8"-18 NPTF **Ball Check**




L 5711

* AVAILABLE IN STAINLESS

H119@Z3

Button Head - Standard 1/2"-14 PTF Spl. Short **Ball Check**



ltem#	Thread	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Thread Diameter (F)	Hex (H)	Valve System
H1184Z3 💥	1/8"-27	.75"	.34"	.18"	.39"	5/8"	Ball Check
H1184N	1/8"-27	.75"	.34"	.18"	.39"	5/8"	No Ball Check
HC69	1/8"-27	.97"	.41"	.28"	.39"	5/8"	Ball Check
H1186Z3 💥	1/4"-18	.85"	.44"	.31"	.52"	5/8"	Ball Check
H1188Z3 💥	3/8"-18	1.06"	.59"	.41"	.64"	3/4"	Ball Check
H1190Z3	1/2"-14	1.09"	.56"	.36"	.82"	7/8"	Ball Check

