

1/8"-27 PTF

EXCEEDS 72 HR SALT SPRAY,
8,000 PSI MAX PRESSURE


SAE J534

1/8"-27 PTF pipe threads, which have 27 threads per inch, are sometimes generically referred to as 1/8" NPT, and may be threaded into NPT and NPTF threaded holes. Thread sealant is recommended for use with NPT threaded holes. The primary difference between the HA1684 and H1684Z3 is the hex size.

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

H1607Z3


Straight
1/8"-27 PTF SAE Short
Extra Long Shank



1607-B AVAILABLE IN STAINLESS
 5003
 JD7771

H1669Z3


Straight
1/8"-27 PTF SAE Short
Super Long Shank



1669-B
 JD7782

HA1684


Straight
1/8"-27 NPTF
Super Long Shank



1684-B

H1684Z3

Straight
1/8"-27 PTF Spl. Short
Super Long Shank



369599
 5009
 JD7779

Item #	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H1607Z3	1/8"-27	Straight	1.25"	.75"	.22"	—	.39"	—	7/16"
H1669Z3	1/8"-27	Straight	1.75"	1.28"	.22"	—	.39"	—	7/16"
HA1684	1/8"-27	Straight	2.62"	2.16"	.22"	—	.39"	—	3/8"
H1684Z3	1/8"-27	Straight	2.62"	2.16"	.22"	—	.39"	—	7/16"

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed. Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2019