

INSTANT START FLUORESCENT LAMPS

SLIMLINE SUPERSAVER® Instant Start Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
32	T12	48	46	Single Pin	24823	F48T12/CW/SS	30	9000	4200	60	2450 (2200)	☞,3,9,12,13,17

SLIMLINE SUPERSAVER® Instant Start Lamps; Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
60	T12	96	94	Single Pin	23503	F96T12CWXSSUPC	15	12000	4100	87	3850 (3400)	☞,3,9,12,13,17
					29828	F96T12/DX/SS	15	12000	6500	88	3860 (3400)	☞,3,9,12,13,17

SLIMLINE Standard Instant Start Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
21	T12	24	22	Single Pin	22403	F24T12/CW	30	7500	4200	60	1150 (1000)	☞,3,12,13,17
25	T12	42	40	Single Pin	24270	F42T6/WW	24	7500	3032	52	1825 (1605)	☞,3,12,13,17
					24266	F42T6/CW	24	7500	4200	60	1750 (1540)	☞,3,12,13,17
30	T12	36	34	Single Pin	23618	F36T12/CW	30	7500	4200	60	1970 (1735)	☞,3,12,13,17
38	T12	64	62	Single Pin	26466	F64T6/CW	24	7500	4200	60	2800 (2465)	☞,3,12,13,17
38	T12	72	70	Single Pin	27270	F72T8/WW	24	7500	3000	52	3100 (2730)	☞,3,12,13,17
					27266	F72T8/CW	24	7500	4200	60	3050 (2685)	☞,3,12,13,17
					27200	F72T8/D	24	7500	6500	76	2600 (2290)	☞,3,12,13,17
39	T12	48	46	Single Pin	24832	F48T12/D35	30	9000	3500	70	3000 (2760)	☞,3,12,13,17
					24827	F48T12/CW/ECO	30	9000	4200	60	2820 (2480)	☞,3,12,13,17
					24830	F48T12/CW	30	9000	4200	60	2820 (2480)	☞,3,12,13,17
50	T12	60	58	Single Pin	26001	F60T12/CW	30	12000	4200	60	3700 (3255)	☞,3,12,13,17
					26002	F60T12/D	30	12000	6500	76	3000 (2640)	☞,3,12,13,17
52	T12	64	62	Single Pin	26403	F64T12/CW	30	12000	4200	60	3900 (3430)	☞,3,12,13,17
					26404	F64T12/D	30	12000	6500	76	3300 (2905)	☞,3,12,13,17
55	T12	72	71	Single Pin	27255	F72T12/D830	15	12000	3000	80	4800 (4510)	☞,3,12,13,17
					27250	F72T12/D35	15	12000	3500	70	4700 (4325)	☞,3,12,13,17
					27256	F72T12/CW	15	12000	4200	60	4500 (3960)	☞,3,12,13,17
					27259	F72T12/D	15	12000	6500	76	3800 (3345)	☞,3,12,13,17
70	T12	84	82	Single Pin	28417	F84T12/CW	15	12000	4200	60	5300 (4665)	☞,3,12,13,17

SLIMLINE Standard Instant Start Lamps; Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
75	T12	96	94	Single Pin	23504	F96T12/WX	15	12000	3500	87	4200 (3695)	☞,3,12,13,17
					29478	F96T12/CWX	15	12000	4100	87	4400 (3870)	☞,3,12,13,17
					29833	F96T12/DSGN50	15	12000	5000	90	4400 (3870)	☞,3,12,13,17
					29500	F96T12/DX	15	12000	6500	88	4360 (3835)	☞,3,12,13,17