



MORRIS CAT#'s: 23284-23486

Wing Connectors



Features:

- Swept wing fits into your hand naturally to give extra torque leverage and reduce the effort required for connecting even large wire combinations, yet compact, with narrow profile to take up less space in junction boxes
- Ribbed cap on color coded wire connectors provide more secure grip and faster fingertip starts even when hands become slippery
- Deep Skirt Entry Provides Protection From FlashOver or Shorting and Keeps Strands from Splaying
- Live Action Square Wire Spring Draws Wires Deep into Spring Provides a More Secure Grip
- No pre-twisting of conductors is required – spring creates its own thread
- Connector Will Bite and Hold on Single Conductor when Capping Isolated Conductor
- Reusable connector threads on or off splice for fast and easy circuit changes and additions
- Tough, Heavy Duty Thick Wall UL 94V-2 Flame Retardant Housing will not crack or break, even when applied to maximum wire combinations under extreme pressure
- Temperature rated at 221°F (105°C) maximum
- 600V, 1000V fixtures & signs



MORRIS CAT#: 23284-23486

Wing Connectors



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE COMBINATIONS	A	B	C	D	E	BOX/BAG QTY	CASE QTY	
HANGING BAG SMALL PACK										
23284	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	25	1,250	
23285	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	25	1,250	
23286	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	354	.531	.906	.378	1.252	25	1,250	
23288	GRAY	MAX: 4 #12 MIN: 2 #10	394	587	1.000	.394	1.311	6	1,250	
23290	BLUE	MAX: 2 #12 & 3 #10 MIN: 2 #10	472	.740	1.260	.516	1.575	6	1,250	
BOXED										
23084	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	100	10,000	
23085	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	100	10,000	
23086	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	354	.531	.906	.378	1.252	100	8,000	
23088	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	394	587	1.000	.394	1.311	50	5,000	
23090	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	50	4,000	
BAGGED BULK PACK										
23184	YELLOW	MAX: 3 #12 MIN: 2 #18	252	386	.717	.354	1.016	500	5,000	
23185	TAN	MAX: 3 #10 MIN: 3 #22	283	457	.720	.362	1.142	500	5,000	
23186	RED	MAX: 5 #12 MIN: 3 #16	354	.531	.906	.378	1.252	500	5,000	
23188	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	394	587	1.000	.394	1.311	100	2,500	
23190	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	100	1,500	
BULK PAIL										
NEW	23194	YELLOW	MAX: 3 #12 MIN: 2 #18	252	386	.717	.354	1.016	-	4,000
NEW	23195	TAN	MAX: 3 #10 MIN: 3 #22	283	457	.720	.362	1.142	-	3,500
NEW	23196	RED	MAX: 5 #12 MIN: 3 #16	354	.531	.906	.378	1.252	-	2,300
NEW	23197	GRAY	MAX: 3 #10 MIN: 3 #14 & 1 #18	394	587	1.000	.394	1.311	-	1,500
NEW	23198	BLUE	MAX: 1 #8 & 3 #10 MIN: 2 #10 & 1 #12	472	.740	1.260	.516	1.575	-	1,000
SMALL JAR										
23384	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	200	6,400	
23385	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	150	4,800	
23386	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	354	.531	.906	.378	1.252	100	3,200	
LARGE JAR										
23484	YELLOW	MAX: 4 #16 & 2 #18 MIN: 2 #18	252	386	.717	.354	1.016	550	6,600	
23485	TAN	MAX: 3 #12 & 3 #18 MIN: 2 #18	283	457	.720	.362	1.142	450	5,400	
23486	RED	MAX: 2 #12 & 4 #14 MIN: 1 #16 & 1 #14	354	.531	.906	.378	1.252	300	3,600	