


# Copper Split Bolt Connectors - Direct Burial



UL467 LISTED  
SUITABLE FOR  
DIRECT BURIAL &  
GROUNDING/BONDING




- UL listed for Copper and Copper Weld Stranded Wires Only
- Manufactured from Compact, High Strength, High Copper Content Alloy
- Free Running Threads and Easy To Grip Wrench Flats
- Highly Resistant to Cracking and Corrosion
- Provides a Maximum Pressure and Ensures a Secure Connection on all Combinations of Connectors
- UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Rated 600 Volts

DIMENSIONS = INCHES

CAT. NO.	AWG	MAX RUN TO MAX TAP	MIN RUN TO MIN TAP	MAX RUN TO MIN TAP	MIN EQUAL TAP & RUN	TORQUE IN-LB	B	C	L	R	V	W	BOX QTY
90314	8	8-8	10-16	8-16	10-10	88	.472	.562	.854	.413	.145	.650	100
90316	6	4-4	8-14	4-14	8-8	165	.492	.625	.906	.413	.165	.722	100
90318	4	4-4	6-14	4-14	8-8	165	.709	.812	1.16	.579	.268	.938	50
90320	2	2-2	6-14	2-14	6-6	275	.748	.812	1.26	.614	.326	.938	50
90322	1/0	1/0-1/0	2-14	1/0-14	4-4	385	.787	.937	1.54	.708	.374	1.08	50
90324	2/0	2/0-2/0	1-14	2/0-14	2-2	385	.866	1.06	1.69	.807	.421	1.28	25
90326	3/0	3/0-3/0	2/0-8	3/0-8	1-1	500	1.10	1.25	2.09	.976	.531	1.45	25
90328	4/0-250	250-250	4/0-8	250-8	1-1	500	1.10	1.25	2.09	1.06	.579	1.45	25
90330	350	350-350	350-1/0	350-1/0	2/0-2/0	650	1.22	1.50	2.36	1.18	.700	1.73	12
90332	500	500-500	500-2/0	500-2/0	300-300	825	1.34	1.75	2.84	1.34	.815	2.10	12
90334	750	750-750	750-350	750-#8	350-350	1000	1.94	2.31	3.51	1.94	1.02	2.31	1

# Copper Split Bolt Connectors - With Spacer - Direct Burial



- UL listed for Copper and Copper Weld Stranded Wires Only
- Manufactured from Compact, High Strength, High Copper Content Alloy
- Uniform Bright Electro-Tin Plating Resists Corrosion, Reduces Contact Resistance for Maximum Conductivity
- Spacer Separates Dissimilar Conductors and Provides Enhanced Surface Contact Area Preventing Intermittent Contact Between Run & Tap Connectors
- Free Turning Threads and Easy To Grip Wrench Flats
- Highly Resistant to Cracking and Corrosion
- UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Rated for 600 Volts

DIMENSIONS = INCHES

CAT. NO.	AWG	MAX RUN TO MAX TAP	MIN RUN TO MIN TAP	MAX RUN TO MIN TAP	MIN EQUAL TAP & RUN	TORQUE IN-LB	B	C	H	L	R	V	W	BOX QTY
90360	3/0	3/0-3/0	2/0-8	3/0-8	1-1	500	1.10	1.25	1.520	2.20	.976	.531	1.45	25
90362	4/0-250	250-250	4/0-8	250-8	1-1	500	1.10	1.25	1.574	2.22	1.06	.579	1.45	25
90364	350	350-350	350-1/0	350-1/0	2/0-2/0	650	1.22	1.50	1.771	2.56	1.18	.700	1.73	12
90366	500	500-500	500-2/0	500-2/0	300-300	825	1.34	1.75	1.968	2.95	1.34	.815	2.10	12