

UNDERCOUNTER CUBE

UF310



W 30" D 28.5" H 38.5"  
W 76.2 D 72.4 H 97.8 cm

\*290lbs/132 kg daily at 70/50°F  
\*235 lbs/107 kg daily at 90/70°F

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
<b>URF0310A-161B</b>	Regular	Air	115v/60Hz/1	208 lbs / 94 kg	<b>UR0310A-161B</b>
<b>UDF0310A-161B</b>	Dice	Air	115v/60Hz/1	208 lbs / 94 kg	<b>UD0310A-161B</b>
<b>UDF0310A-261Z</b>	Dice	Air	208-230v/60hz/1	208 lbs / 94 kg	<b>UD0310A-261Z</b>
<b>UDF0310W-161B</b>	Dice	Water	115v/60Hz/1	211 lbs / 96 kg	<b>UD0310W-161B</b>
<b>UYF0310A-161B</b>	1/2 Dice	Air	115v/60Hz/1	209 lbs / 95 kg	<b>UY0310A-161B</b>
<b>UYF0310W-161B</b>	1/2 Dice	Water	115v/60Hz/1	211 lbs / 96 kg	<b>UY0310W-161B</b>
<b>URF0310A-251Z</b>	Regular	Air	230v/50hz/1	208 lbs / 94 kg	<b>UR0310A-251Z</b>
<b>UDP0310A-251Z</b>	Dice	Air	230v/50hz/1	208 lbs / 94 kg	<b>UD0310A-251Z</b>
<b>UYP0310A-251Z</b>	1/2 Dice	Air	230v/50hz/1	209 lbs / 95 kg	<b>UY0310A-251Z</b>

Application ice storage capacity 119 lbs/54 kg. Cubic Volume 3.99. Storage Capacity is AHRI Certified.  
Includes 6"/1.8 m power cord with NEMA 5-15P plug ("B" Plug).  
Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.  
Not compatible with iAuCS. LuminIce® II compatible as accessory.  
Application storage capacity measured 90% of total volume in cu. ft. x 33 lbs/ft3.

SQUARE CUBE

USP0100A



W 19.68" D 22.83" H 37.5"

\*100 lbs / 45.5 kgs at 70/50  
\*85 lbs / 38.5 kgs at 90/70

Model	Ice type	Cooling	Electrical	Shipping Weight	Suggested List Price	Replaces Model
<b>USP0100A-161</b>	Square	Air	115v/60Hz/1	209 lbs / 49 kg		<b>N/A</b>

Application storage capacity 38 lbs/17.2 kgs. Measured cubic volume is 2. Storage Capacity is AHRI certified.  
Includes 6 ft / 1.8m power cord with NEMA 5-15 plug  
Refer to Install Use and Care manual for proper cleaning instructions.  
Not compatible with iAuCS or LuminIce II.

MODULAR CUBE

iT300 Series



W 30" D 24.5" H 16.50"  
W 76.2 D 62.2 H 41.9 cm

\*310 lbs /141 kg daily at 70/50°F  
\*230 lbs /104 kg daily at 90/70°F

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
<b>IDT0300A-161</b>	dice	air	115v/60Hz/1	142 lbs/ 64kg	<b>IDF0300A-161</b>
<b>IDT0300A-161X</b>	dice	air	115v/60Hz/1	147 lbs/ 67kg	<b>IDF0300A-161X</b>
<b>IDT0300A-261</b>	dice	air	208-230/60Hz/1	142 lbs/ 64kg	<b>IDF0300A-261</b>
<b>IDT0300W-161</b>	dice	water	115v/60Hz/1	139 lbs/ 63kg	<b>IDF0300W-161</b>
<b>IYT0300A-161</b>	1/2 dice	air	115v/60Hz/1	147 lbs/ 67kg	<b>IYF0300A-161</b>
<b>IYT0300A-161X</b>	1/2 dice	air	115v/60Hz/1	152 lbs/ 69kg	<b>IYF0300A-161X</b>
<b>IYT0300A-261</b>	1/2 dice	air	208-230/60Hz/1	147 lbs/ 67kg	<b>IYF0300A-261</b>
<b>IYT0300W-161</b>	1/2 dice	water	115v/60Hz/1	144 lbs/ 65kg	<b>IYF0300W-161</b>
<b>IYT0300W-161X</b>	1/2 dice	water	115v/60Hz/1	149 lbs/ 68kg	<b>IYF0300W-161X</b>
<b>IDT0300A-251</b>	dice	air	230v/50Hz/1	142 lbs/ 64kg	<b>IDF0300A-251</b>
<b>IYT0300A-251</b>	1/2 dice	air	230/50Hz/1	147 lbs/ 67kg	<b>IYF0300A-251</b>

If factory installed LuminIce II not offered, use aftermarket kit found on page 24.



**Recommended Bins:** D400 (see page 19).

See pages 22-23 for required adapters, deflectors, and dispenser baffles.

Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.

**Not Stackable**

★ ENERGY STAR® Qualified Model

Air filter standard on self-contained air-cooled ice cube machines.

\*Daily ice production based on Half-Dice air-cooled condenser model at air temperature/water temperature.