

NORTON

SAINT-GOBAIN®



ABRASIVE PRODUCT SOLUTIONS FOR THE

EFFECTIVE | 2015

WELDING AND METAL FABRICATION MARKET

TABLE OF CONTENTS

GENERAL INFORMATION		COATED ABRASIVES		NON-WOVEN ABRASIVES	
Products by Machine Index	3	 Fiber Discs	48	 Depressed Center Discs	142
How to Use this Catalog	4	 Flap Discs	54	 Standard Back-up Pad Discs	145
Coated Abrasive Basics	138	 Paper Discs	61	 Speed-Change and AVOS Discs	146
Non-Woven Abrasive Basics	174	 Film and Foam Finishing Discs	72	 Quick-Change Discs	147
Safety Guidelines	184	 Cloth PSA Discs	74	 Hook & Loop Discs	154
Wheel Speed Conversion Table	185	 Quick-Change Discs	77	 Arbor Hole (Gangable) Discs	156
Trademarks	186	 Paper Sheets and Rolls	86	 Brushes	157
Contact Information	187	 Cloth Sheets and Rolls	93	 Hand Pads, Rolls, and Sponges	158
BONDED ABRASIVES		 Abrasive Sponges	95	 Surface Stripping, Unified, and Convoluted Wheels	160
 Depressed Center Wheels	8	 File Belts	97	 Belts	169
 Small Diameter Cut-Off Wheels	18	 Portable Belts	100	 Flap Wheels	171
 High Speed Cut-Off Wheels	25	 Narrow Belts	102	NON-ABRASIVE PRODUCTS	
 Walk-Behind Cut-Off Wheels	27	 NORaX Belts	108	 Wire Brushes	178
 Chop Saw Cut-Off Wheels	28	 FastTrack Belts	109	 Micro-Fiber Cloths	182
 Stationary Saw Cut-Off Wheels	31	 Flap Wheels, Sand-O-Flex Wheels	111	 Masking Tape	183
 Portable Snagging Wheels, Cones, and Plugs	32	 Specialties	123		
 Bench & Pedestal Wheels	35				
 Mounted Points	37				
 Rubbing Bricks	42				
 Sharpening Stones	43				

MACHINE INDEX

RIGHT ANGLE/VERTICAL SHAFT PORTABLE GRINDERS

	Depressed Center Grinding Wheels, Notchers, 8-17
	Saucers and Type 29 Wheels
	Right Angle Grinder Reinforced Cut-off Wheels, 22-23
	Type 01 and Type 27
	Coated Abrasive Fiber Discs 48-53
	Coated Abrasive Flap Discs 54-60
	Coated Abrasive Paper Discs 61-71
	Film and Foam Finishing Discs 72-73
	Coated Abrasive Quick-Change Discs 77-85
	Non-Woven Depressed Center Discs 142-144
	Non-Woven Discs 145-155
	Non-Woven Abrasive Brushes 157
	Wire Brushes 180

HORIZONTAL/STRAIGHT SHAFT PORTABLE GRINDERS

	Small Diameter Reinforced Cut-off 18-21
	Wheels (1-1/2"-6" wheels)
	Cones and Plugs 32-34
	Snagging Straight Wheels 32-33
	Mounted Points 37-41
	Coated Abrasive Flap Wheels with
	Arbor Holes (3-1/2"-5" wheels) 118
	Non-Woven Disc Wheels 156
	Non-Woven Unified Wheels 160-164
	Non-Woven Flap Wheels 171-173
	Wire Brushes 180

RIGHT ANGLE/VERTICAL SHAFT PORTABLE CUP GRINDERS

	Snagging Cup Wheels 33
	Wire Cup Brushes 178-179

PORTABLE CIRCULAR SAWS

	Circular Saw Reinforced Cut-off Wheels 24
---	---

HAND-HELD GAS OR ELECTRIC SAWS

	High-Speed Reinforced Cut-off Wheels 25-26
---	--

WALK-BEHIND SAWS

	Reinforced Cut-off Wheels 27
	Wire Brushes 180

CHOP SAW MACHINES

	Chop Saw Reinforced Cut-off Wheels 28-30
---	--

STATIONARY CHOP STROKE MACHINES

	Large Diameter Reinforced Cut-off Wheels 31
---	---


FLEXIBLE SHAFT MOTORS

	Non-Woven Rapid Strip Wheels 160-161
	Non-Woven Unified Wheels 160-164

DRILLS

	Small Diameter Reinforced Cut-off Wheels 18-21
	(2" and 3" wheels with mandrel)
	Coated Abrasive Small Diameter Flap Wheels 111-117
	Sand-O-Flex Wheels 122
	Non-Woven Surface Stripping & Unified Wheels . 160-164

DIE AND PENCIL GRINDERS

	Mounted Points 37-41
	Coated Abrasive Small Diameter Flap Wheels 111-117, 121
	Coated Abrasive Specialties 123-137
	Non-Woven Disc Wheels 156
	Non-Woven Flap Wheels (2"-4" wheels) 171-172
	Non-Woven Surface Stripping and 160-164
	Unified Wheels (1"-4" wheels)
	Wire Brushes 180-181

BENCH AND PEDESTAL GRINDERS

	Bench and Pedestal Wheels 35-36
	Coated Abrasive Large Diameter Flap Wheels ... 118-121
	Sand-O-Flex Wheels 122
	Non-Woven Discs (6"-12" discs) 156
	Non-Woven Unified Wheels (6" wheels) 160-164
	Non-Woven Convolute Wheels (6"-14" wheels) .. 165-168
	Non-Woven Flap Wheels (6"-8" wheels) 171, 173
	Wire Brushes 179

ORBITAL SANDERS

	Coated Abrasive Paper Discs 61-71
	Film and Foam Finishing Discs 72-73
	Coated Abrasive Small Diameter Cloth PSA Discs ... 74-75

JITTERBUG SANDERS

	Coated Abrasive Sheets and Rolls 86-94
	Non-Woven Rolls 158-159

STATIONARY DISC SANDERS

	Coated Abrasive Large Diameter Cloth 74, 76
	PSA Discs (10"-24" discs)

PORTABLE FILE BELT SANDERS

	Coated Abrasive File Belts 97-99, 108
	Non-Woven File Belts 169-170


PORTABLE BELT SANDERS

	Coated Abrasive Portable Belts 100-101
	Non-Woven Portable Belts 169-170

IN-LINE DRUM SANDERS

	Coated Abrasive Portable Belts 101
	Non-Woven Portable Belts 169-170

BENCHSTAND GRINDERS

	Coated Abrasive Benchstand Belts. 102-107, 109-110
	Non-Woven Benchstand Belts 169-170

BACKSTAND BELT GRINDERS

	Coated Abrasive Backstand Belts .. 102-103, 107, 109-110
	Non-Woven Backstand Belts 169-170

HAND FINISHING APPLICATIONS

	Rubbing Bricks and Sharpening Stones 42-44
	Coated Abrasive Paper Discs 71
	Coated Abrasive Sheets, Rolls and Sponges. 86-96
	Non-Woven Hand Pads, Rolls and Sponges 158-159
	Wire Brushes 181
	Micro-Fiber Cloths, Masking Tape 182-183

SANDING BOARDS

	Sanding Boards and Coated Abrasive File Strips. 90
---	---

What are the Leading Products by Tier?

- J Features and benefits
- K New and/or improved
- L Unique and/or innovative

DEPRESSED CENTER WHEELS

MACHINE USED



FEATURED PRODUCTS



NORTON METAL/MASONRY

GOOD CHOICE FOR STEEL/FERROUS METAL AND MASONRY APPLICATIONS WITH LOW INITIAL PRICE


FEATURES	BENEFITS
- Low initial price point - Metal – aluminum oxide - Masonry – sharp silicon carbide	- Best starting specification for end user unable to measure performance - Engineered for all steel/ferrous materials - Engineered for all masonry materials such as concrete, brick and asphalt



NORTON DIALAST DIAMOND WHEELS

BEST FOR METAL PLATE, PIPE, TUBING, CAST IRON, CARBON AND MILD STEEL, FOUNDRY AND WELDING APPLICATIONS, AND CERAMICS

FEATURES	BENEFITS
- A combination of high-quality diamond and advanced brazed single-layer bonding technology - Environmentally friendly grinding	- Extra-long life vs. conventional abrasives or other vacuum-brazed diamond tools - Retains the diamond grains and wheel shape for full life with low spark, while keeping a continuous grinding depth - Less blade changes reduce downtime and labor costs - Generate minimal dust



Norton Fine, Hard Back Depressed Center Wheels Boost Productivity and Wheel Life

Versus Competitors' Monolithic Design (2 coarse layers)

Our fine, hard back (a finer-grit mixture in the top half of the grinding wheel) limits premature shedding or "spalling" and allows for a smoother grinding action from the periphery to the hub.

- At the proper grinding angle, a sharp bevel is produced at the wheel periphery
- As the wheel wears, this thin edge becomes susceptible to stress
- A coarse grit back is much more likely to break away prematurely resulting in unnecessary wheel loss and quite possibly an injury to operator and others



Norton Depressed Center Adapter Kit

This reusable adapter kit contains everything you need to mount depressed center wheels and saucers with 7/8" center holes on to portable right angle or vertical shaft grinders. Adapter hubs are threaded for mounting on to standard 5/8"-11 NCRH spindles.

KIT NO.	WHEEL DIAMETER	WHEEL THICKNESS	PART #	STD. PKG.
114	6" thru 9"	1/16" thru 1/4"	0760789275	1

FIBER DISCS

MACHINES USED



AVAILABILITY

SIZE (D x H)	GRIT	STD. PKG.	PART #	PART #	PART #	STD. PKG.	PART #
4-1/2 x 7/8	24	25	6957298000	77096008400	77096008462	25	66261138457
	36	25	6957298001	77096008401	77096008465	25	66261138456
	50	25	6957298002	77096008402	77096008466	50	6623377276
	50	25	6957298003	77096008403	77096008467	50	6623377277
	60	25	6957298004	77096008404	77096008470	25	66261138453
	80	25				25	66261138452
	100	25				50	6623377279
5 x 7/8	120	25	66254402332	77096008406			
	24	25	6957298005	77096008407	77096008480	25	66261138563
	24	50	66254404822				
	36	25	6957298006	77096008412	77096008481	25	66261138562
	36	50	66254404821			50	6623377283
	50	25	6957298007	77096008413	77096008482	50	6623377284
	50	25				25	66261138561
	50	50	66254404820				
	60	25	6957298008	77096008414	77096008483	25	66261138601
	80	25				50	6623377285
	80	25				50	6623377286
	100	25	6957298009	77096008422	77096008484	25	66261138600
	100	25					
	120	25	66254405084	77096008423			
7 x 7/8	24	25	6957298010	77096010018	77096010005	25	66261138594
	36	25				50	6623377287
	36	25	6957298011	77096008429	77096010007	25	66261138593
	50	25				50	6623377289
	50	25	6957298012	77096008430	77096010008	25	66261138592
	60	25	6957298013	77096008431	77096010009	25	66261138591
	80	25	6957298014	77096008432	77096010011	50	6623377291
	80	25				25	66261138590
	100	25	66254411528	77096008433			
9 x 1/8 x 7/8	24	25	6957298015	77096008437	77096010012	25	66261138594
	36	25	6957298016	77096008440	77096010013	25	66261138583
	50	25	6957298017	77096008444	77096010017	25	66261138582
	60	25					
	80	25					
	100	25					

NOTE: FIBER DISCS MUST BE USED WITH BACK-UP PADS SHOWN ON THE LAST PAGE OF THIS SECTION.
SHOWN/STANDARD FOR PACK: 10 DISCS PER PACK, 5 PACKS PER STANDARD PACKAGE.
V = VENDOR PACKAGE, IDEAL FOR VENDING MACHINES & SMALL JOBS. 10 DISC PACKAGE, 5 PACKS PER CARTON. ORDER IN MULTIPLES OF 50.

The Perfect Product for Every Performance/Price Level

L



NORTON BLAZE

Latest generation ceramic alumina abrasive provides the industry's fastest cutting discs and 50-200% longer life on stainless, titanium, and super alloys.



NORTON BLUEFIRE

Durable ceramic/zirconia abrasive blend for an increased cut rate and longer life over conventional zirconia products on high pressure applications.



NORTON NEON

New aluminum oxide and ceramic blend provides the best starting specification (and performance) when initial price is the primary purchasing consideration.

Professionals Want Choices

already provide the best wheels in the industry. Invented and made in America, now proved and expanded. The **Norton NorZon Plus** ceramic alumina BEST tier (highest productivity/lowest total cost) line has a wheel for all your right angle grinder applications: NorZon Plus Fast Cut wheels - for your applications requiring the fastest cut rate and quickest project completion. NorZon Plus Long Life wheels - for your most demanding applications. The Original NorZon Plus All Purpose wheels - for the lowest overall cost.

The Choice is Yours!

How Do I Find What I Want Now That I Know What I Want?

- M Visual identification
- N Key product attributes
- O Full specification and product number



a technology leader **FOCUSED ON INNOVATION**

For stock removal, rough blending, grinding and cutting, bonded abrasive products are constructed to tackle the heavy-duty dimensioning work of all material types.



Professionals Want Choices

Norton NorZon Plus is the highest performance line in the industry. Invented and made in America, now improved and expanded. Fastest cutting (FastCut), lowest total cost (All Purpose), and longest lasting (Long Life).



Performance on Fire

Engineered with a proprietary NorZon grain upgrade, the Norton BlueFire design offers faster removal rate, longer product life and increased productivity for better performance value.



The Right Choice Every Time

The re-engineered Norton Gemini RightCut 100% aluminum oxide wheels provide thinner, faster cutting with a burr-free, precision cut and improved operator comfort.






CATEGORY DEFINITION

Depressed center wheels may also be referred to as raised hub wheels or by their shape designation of “Type”, with Type 27 being the most popular. The depressed center design allows the flange/lock nut to recess within the wheel so that it can be used for various grinding and cutting applications. Depressed center wheels are designed to handle the most severe right angle grinding applications from heavy stock removal to rough blending. More recently, depressed center wheels have been designed to increase the utility of the tool for cut-off applications. While large right angle grinders (7" & 9") have been around for many years, small or mini grinders that handle 4", 4-1/2" and 5" wheels have made this machine, and wheel category, the most popular in power tools.

APPLICATIONS:	Grinding, stock removal, edge chamfering, beveling, weld blending, and cutting-off
SIZE RANGE:	2" – 9"
THICKNESS RANGE:	.040 – 1/4"
GRIT RANGE:	24 – 46 grits for stock removal; 60, 80 grits for blending and finishing
ABRASIVE GRAIN:	Ceramic Alumina, Diamond, Zirconia Alumina, Aluminum Oxide, Silicon Carbide
MOUNTING OPTIONS:	Plain hole (3/8", 5/8" and 7/8") and discard mount (5/8"-11)
SHAPE:	Type 27, Type 28, Type 29

TYPE-TO-APPLICATION RECOMMENDATION GUIDE

WHEEL TYPE/THICKNESS	APPLICATIONS		
TYPE 27 	Type 27 wheels are essentially straight wheels that have a “depressed center/raised hub”. Different types of fiberglass reinforcement mesh give the product stability for use on the periphery, on the face, or a combination of the two.		
.040", .045", and 1/16" Type 27/42 RightCut	Cutting only, where fast cutting and low kerf loss are desired	■	
.3/32" and .125" Type 27/42	For tough cutting and notching applications where stability is important; cutting and cleaning burr-free narrow root pass welds	■	
1/8" Type 27	For multiple applications ranging from cutting-off, notching and light-duty side grinding	■	■
1/8" Pipe Notcher Type 27	2-1/2 pieces of reinforcement; durable face grinding; root pass grinding without removing pipe material	■	■
1/8" Type 27 Flexible	For light stock/blending/finishing/polishing		■
1/8" Type 27 Foundry Notchers	Triple-reinforced for grinding steel and dirty/scale-covered castings; removing and cleaning gates and risers	■	■
1/4" Type 27	For heavy-duty to light grinding on the bottom/face of the wheel		■
1/4" Type 27 Foundry Snaggers	Designed for cleaning parting lines, pads and slag		■
1/4" Type 27 Heavy-Duty Foundry	Triple-reinforced for the most aggressive foundry applications		■
TYPE 28 	Type 28 wheels are constructed with a downward angle built into the grinding section to facilitate a flatter grinding angle. These wheels can only be used on the face and never on the periphery for cutting-off.		
1/4" Type 28 Saucers	Smooth, gouge-free grinding at shallow angles		■
TYPE 29 	Type 29 wheels are constructed with an upward angle built into the grinding section to provide full face contact for light stock removal and blending operations. These wheels can only be used on the face and never on the periphery for cutting-off.		
1/8" Type 29 Flexible, AVOS	Polishing and blending applications		■



MATERIAL/APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE

	BEST HIGHEST PRODUCTIVITY LOWEST TOTAL COST	BETTER EXCELLENT BLEND OF PERFORMANCE & PRICE	GOOD CONSISTENT PERFORMANCE LOW INITIAL PRICE
Cutting			
Mild Carbon / High Tensile Steel	Norton NorZon Plus	Norton BlueFire	Norton Metal
Stainless Steel / Alloys	Norton NorZon Plus	Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Contaminate Free		Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Cast Iron	Norton NorZon Plus	Norton BlueFire	Norton Gemini
Gray Iron		Norton BlueFire Foundry	
Aluminum / Bronze / Brass			Norton Gemini Aluminum
Asphalt / Brick / Concrete			Norton Masonry
Fiberglass / Plastic			Norton Masonry
Notching			
Mild Carbon / High Tensile Steel	Norton NorZon Plus	Norton BlueFire	Norton Metal
Stainless Steel / Alloys	Norton NorZon Plus	Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Contaminate Free		Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Cast Iron	Norton NorZon Plus	Norton BlueFire	Norton Gemini
Grinding			
Mild Carbon / High Tensile Steel	Norton NorZon Plus	Norton BlueFire	Norton Metal
Stainless Steel / Alloys	Norton NorZon Plus	Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Contaminate Free		Norton BlueFire FC/INOX/SS	Norton Gemini INOX/SS
Cast Iron	Norton NorZon Plus	Norton BlueFire	Norton Gemini
Gray Iron	Norton NorZon Plus Foundry	Norton BlueFire Foundry	Norton Gemini
Aluminum / Bronze / Brass			Norton Gemini Aluminum
Asphalt / Brick / Concrete			Norton Masonry
Blending			
Mild Carbon / High Tensile Steel			Norton Gemini Flexible
Stainless Steel / Alloys			Norton Gemini Flexible
Aluminum / Bronze / Brass			Norton Gemini Flexible
Fiberglass / Plastic			Norton Gemini Flexible


TYPICAL STEEL, STAINLESS STEEL, CAST IRON PRODUCTS: ANGLE IRON, BAR STOCK, DUCTILE PIPE, CHANNEL IRON, DECKING, REBAR, I-BEAMS, RAIL STEEL, STUDS, TUBING, AND WELDS

HOW TO PICK THE RIGHT BOND TYPE

Standard	Unmarked	Where an excellent blend of cut rate and life is needed
Fast Cut	FC	Where fast stock removal is needed, or the application only allows for low-pressure or under-horsepowered grinders
Long Life	LL	Where durability is needed due to severe application, and when horsepower of the grinder allows for heavy pressure
Contaminate Free	INOX/SS	Contain <0.1% iron, sulfur or chlorine for rust-free and corrosion-free results. Will not contaminate stainless steel

HOW TO PICK THE RIGHT MOUNT


Most wheel sizes come with a plain hole or a discard mount option. While the plain hole has a small, initial cost advantage, the discard mount can provide a labor cost advantage with the quicker wheel change.

**Mini-Mount Hub**

Our unique, patented mini-mount hub used on 4-1/2" and 5" depressed center wheels provides up to 30% more wheel life because the hub covers just a small surface area, providing maximum grinding area exposure and usage.

STANDARD THROW-AWAY HUB SIZE

WHY CHOOSE DEPRESSED CENTER WHEELS?

**Depressed Center Wheels vs. Flap Discs or Fiber Discs**

- Up to 5X life over flap discs, less downtime
- Up to 100X life over fiber discs, less downtime
- Rigidity for severe operations and high power grinders
- 1/8" wheels can be used for cutting and grinding
- Can be used to grind inside corners at outer edge of wheel



CROSS REFERENCE GUIDES

TYPE 27/42 RIGHTCUT – .040" - 1/16"

	TOTAL PERFORMANCE				INITIAL PRICE		SPECIALTY	
NORTON	BEST NorZon Plus	BETTER BlueFire	GOOD Gemini INOX/SS	Gemini Long Life	Gemini	Metal	GOOD Gemini Aluminum	
Brilliant	—	—	—	Brill-Blade Heavy Duty	Brill-Blade Extra FC	Hornet	—	
Bullard	—	ZA60T	—	TA46T, TA60T TA60U	SGA60U	A46T, A60T Comp.	AL46N	
Camel	—	ZA Quickie Cut	A60-T-BF, WA60R Quickie Cut	Super Quickie Cut	A36-S-BF	—	A46 Quickie Cut	
Flexovit	—	—	—	Razorblade A60SST	Razorblade A24T, 30V, 36T	—	—	
Pearl	—	Redline Max Slimcut	—	Slimcut	—	Slimcut Pro-V, Silverline	—	
Pferd	—	SGP-ZA-Q-INOX	SG-A-R-INOX, SGP-A-S-INOX	SG-A-S, SGP-A-T	—	PSF-A-P	S-G-N-ALU	
Sait	—	Z-tech	XA46R	—	A60S, Saitech	SAIT.M.X	A46N	
Spedecut	—	—	—	—	—	A46, 60 TBXX	—	
Walter	—	—	A-60SS-ZIP	—	A-60-ZIP, A-30-ZIP	—	A-60-ZIP-ALU	

TYPE 27 AND 28 – 1/8" AND 1/4"

	TOTAL PERFORMANCE					INITIAL PRICE				SPECIALTY		
NORTON	BEST NorZon Plus NorZon Plus Long Life		BETTER BlueFire FC/INOX/SS BlueFire BlueFire Foundry			GOOD Gemini Gemini Fast Cut Gemini INOX/SS Metal				GOOD Gemini Aluminum Masonry		
	Brilliant	—	—	Brill-Max Z24R	—	—	Brill-Tex A24UHPXL, A30T	Brill-Tex A24R Super-G	Brill-Tex A30P	Hornet Metal	Brill-Tex 30ALU	Brill-Tex C30P, Hornet Concrete
	Bullard	TA24S	—	ZA24R	ZA24R Competitor	—	A24R	A24N	A46Q	A24R Competitor	AL36N	C24R
	Camel	—	—	ZA24T	—	—	A24R	Ultra A24-N-BF, A24T Super Quickie Cut	WA24S	A24N, R&T Fast Cut	A30N, Fast Cut	C24R
	Flexovit	Flexon ZA20Q	Flexon ZA24P ZA30T	—	Metalhog AXT24S	Flexon ZA16U	High Performance A24/30T	High Performance A30S, Specialist A30Q & R	Free Grind A30Q	—	Specialist A24ALU	High Performance C24/30P
	Metabo	—	—	ZA24T	—	—	A24R & T	A24N	A36Q	—	A36M	C24N
	Pearl	—	—	Z24T	—	Premium Metal A24S, Redline Max A/WA24S	Premium Metal A24R, Redline Max A/WA24R	WA24R, SRT24	Silver Line A24R & S	D.A. Series AL24M	Silver Line C24S	
	Pferd	—	—	ZA R SGP, Z-SG	ZA S GP, ZA T SGP	—	A-PS, A-SG	—	A-SG INOX, A-PS INOX	—	A-SG ALU	S-SG, Masonry
	Sait	Saitech Attacker, Pipeline	Saitech Ultimate Performance	Z24R Z-tech	—	CA24R - Foundry	A24R, A24 Turbo	A24N	XA24Q	—	A46N - Aluminum	C24N
	Tyrolit	—	—	ZA24N-BFX	ZA24P-BFX	ZZA24R-BFX	A30S & Q-BFX	A30R-BFX	A30-BF INOX	A30-BF	A36N-BFX WA46-BF	C30-BF
Walter	—	—	Double-X, Allsteel	Allsteel XX	—	HP	—	Stainless	—	Aluminum	Concrete	

TYPE 27 – FLEXIBLE 1/8"

NORTON	GOOD Gemini Flex
Brilliant	Brill-Flex
Bullard	Flexlite AC
Camel	FGF, Special Wheel
Flexovit	Flexcel
Metabo	Z-Plus
Pearl	Flexible AC
Pferd	SG-Flex
Sait	Challenger II
Walter	Flexcut



FEATURED PRODUCTS



EXPANDED OFFERING

NORTON NORZON PLUS

BEST/HIGHEST PRODUCTIVITY FOR STEEL, STAINLESS STEEL AND ALL OTHER FERROUS METALS

FEATURES

- Combination of Norton SG ceramic alumina and NorZon (zirconia alumina) with an advanced bond system
- NEW! Fast Cut – fastest cutting
- The original All Purpose – lowest total cost and best overall value
- Long Life – longest lasting
- Foundry Snagger
- RightCut wheels for cutting only

BENEFITS

- 50 to 200% better overall performance versus competitive zirconia and ceramic wheels
- Lowest total grinding cost; highest productivity
- Up to 10X the performance of aluminum oxide wheels
- Easy on the operator and equipment
- Best option when speed of completion is primary concern, cost of labor is high, heavy grinder is used, and grinding is difficult, or performed in hard-to-reach areas
- Best option when the best combination of life, cut rate, and lowest heat generation is primary concern, and able to measure total cost
- Best option when longest possible life is primary concern, rough grinding conditions require wheel durability, using high cycle, high horsepower grinders and lower labor cost are key
- Designed to withstand the most aggressive foundry application
- Noticeably longer life and faster cut rate
- Less pressure required for first cut

**NORTON BLUEFIRE**

BETTER CHOICE FOR STAINLESS STEEL, CARBON STEEL, ALLOYS AND GRAY IRON

FEATURES

- A blend of R&D advanced chemistry and shaped zirconia alumina abrasive and premium aluminum oxide grain
- Contaminate-free BlueFire **FC** (FastCut/Inox/SS)
- BlueFire Foundry
- RightCut wheels for cutting only

BENEFITS

- 2-3 times the life of aluminum oxide wheels
- Up to 20% increase in performance and life over our former zirconia alumina wheels
- Broad utility from light-to heavy-pressure applications, on a wide range of materials
- Excellent performance-to-price ratio for lower total grinding costs
- Contain <0.1% iron, sulfur, or chlorine for rust-free and corrosion-free results; will not contaminate stainless steel
- Zirconia alumina/silicon carbide abrasive blend and an exceptionally strong reinforcement structure
- The ideal choice for aggressive, foundry applications
- Noticeably longer life and faster cut rate
- Less pressure required for first cut



EXPANDED OFFERING

NORTON GEMINI

GOOD CHOICE FOR STEEL AND FERROUS METALS AS WELL AS SPECIALTY APPLICATIONS IN ALUMINUM AND FOUNDRIES

FEATURES

- Quality aluminum oxide
- Gemini Contaminate Free **INOX/SS**
- NEW! 1/8" and 1/4" thick Gemini XXL grinding wheels
- UPGRADED! .045 ultra-thin Gemini RightCut wheels for cutting only
- Gemini Aluminum

BENEFITS

- Consistent performance at a competitive price
- Contain <0.1% iron, sulphur or chlorine for rust-free and corrosion-free results; will not contaminate stainless steel
- Fastest 100% aluminum oxide grinding wheels in the market today
- 50% more life and metal removal than standard aluminum oxide wheels
- Best on hard-grade carbon steel applications, weld repairs, flashing, and any job that requires, a quick turnaround
- Precise cutting; more stability and a narrower pass
- Up to 70% longer life and 20% faster cut rate than standard aluminum oxide wheels – for substantial savings
- Require less pressure, providing increased operator comfort
- Grind aluminum and soft metals without loading
- Contain no wax or rubber fillers



FEATURED PRODUCTS

**NORTON METAL/MASONRY**

GOOD CHOICE FOR STEEL/FERROUS METAL AND MASONRY APPLICATIONS WITH LOW INITIAL PRICE

FEATURES

- Low initial price point
- Metal – aluminum oxide
- Masonry – sharp silicon carbide

BENEFITS

- Best starting specification for end user unable to measure performance
- Engineered for all steel/ferrous materials
- Engineered for all masonry materials such as concrete, brick and asphalt

**NORTON DIALAST DIAMOND WHEELS**


BEST FOR METAL PLATE, PIPE, TUBING, CAST IRON, CARBON AND MILD STEEL, FOUNDRY AND WELDING APPLICATIONS, AND CERAMICS

FEATURES

- A combination of high-quality diamond and advanced brazed single-layer bonding technology

BENEFITS

- Extra-long life vs. conventional abrasives or other vacuum-brazed diamond tools
- Retains the diamond grains and wheel shape for full life with low spark, while keeping a continuous grinding depth
- Less blade changes reduce downtime and labor costs
- Environmentally friendly grinding
- Generate minimal dust

Norton Fine, Hard Back Depressed Center Wheels Boost Productivity and Wheel Life*Versus Competitors' Monolithic Design (2 coarse layers)*

Our fine, hard back (a finer-grit mixture in the top half of the grinding wheel) limits premature shedding or “spalling” and allows for a smoother grinding action from the periphery to the hub.

- At the proper grinding angle, a sharp bevel is produced at the wheel periphery
- As the wheel wears, this thin edge become susceptible to stress
- A coarse grit back is much more likely to break away prematurely resulting in unnecessary wheel loss and quite possibly an injury to operator and others

**Norton Depressed Center Adapter Kit**

This reusable adapter kit contains everything you need to mount depressed center wheels and saucers with 7/8" center holes on to portable right angle or vertical shaft grinders. Adapter hubs are threaded for mounting on to standard 5/8"-11 NCRH spindles.

KIT NO.	WHEEL DIAMETER	WHEEL THICKNESS	PART #	STD. PKG.
114	6" thru 9"	1/16" thru 1/4"	07660789275	1

DEPRESSED CENTER WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE	FC = FAST CUT	HD = HEAVY DUTY	INOX/SS = CONTAMINANT FREE	LL = LONG LIFE	1-2-3 = CUTTING/NOTCHING/GRINDING
■ = ALUMINUM	■ = FOUNDRY	■ = MASONRY	■ = STAINLESS	■ = STEEL / METAL	

**Professionals Want Choices**

We already provide the best wheels in the industry. Invented and made in America, now improved and expanded. The **Norton NorZon Plus** ceramic alumina BEST tier (highest productivity/lowest total cost) line has a wheel for all your right angle grinder applications:

- NorZon Plus Fast Cut wheels - for your applications requiring the fastest cut rate and quickest project completion
- NorZon Plus Long Life wheels - for your most demanding applications
- The Original NorZon Plus All Purpose wheels - for the lowest overall cost

The Choice is Yours!



AVAILABILITY



TIER:

TRADENAME:

SHAPE:

ABRASIVE:

MATERIAL:

**BEST****NORTON NORZON PLUS**

Type 27/42

Ceramic Alumina/
Zirconia Alumina**STAINLESS****STEEL/METAL****BETTER****NORTON BLUEFIRE**

Type 27/42

Zirconia Alumina/
Aluminum Oxide**STAINLESS****STEEL/METAL****GOOD****NORTON GEMINI**

Type 27/42

Aluminum Oxide

STAINLESS**STEEL/METAL****GOOD****NORTON METAL**

Type 27/42

Aluminum Oxide

STAINLESS**STEEL/METAL**

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #
.040, .045, 1/16" – RightCut Cut-off – Type 27/42						
4 x .045 x 5/8	15,280	25			66252842180	07660705249
4-1/2 x .040 x 5/8-11	13,580	10		66252843227		
4-1/2 x .045 x 5/8-11	13,580	10	66252842006	66252843223	66252842025	
	13,580	10			66252841913 INOX/SS	
4-1/2 x .045 x 7/8	13,580	25	66252843320	66252843219	66252842026	66252843604
	13,580	25			66252841912 INOX/SS	
	13,580	25*			66252842161 5-Pk	
	13,580	250			66253370065 250-Pk	
5 x .040 x 5/8-11	12,225	10		66252843228	66252841939	
5 x .045 x 5/8-11	12,225	10			66252841915 INOX/SS	
	12,225	10			66252842036	66252843849
5 x .045 x 7/8	12,225	25	66252843329	66252843220	66252841914 INOX/SS	
	12,225	25			66252842171 5-Pk	
	12,225	25*			66253370066 250-Pk	
	12,225	250			66252830587	
6 x .045 x 5/8-11	10,185	10	66252842007		66252841917 INOX/SS	
	10,185	10			66252842202	66252842015
6 x .045 x 7/8	10,185	25	66252842009	66252843221	66252841916 INOX/SS	
	10,185	25			66252842176 5-Pk	
	10,185	25*			66253370067 250-Pk	
	10,185	250			66252841919 INOX/SS	
7 x .045 x 5/8-11	8,600	10			66252912626	
7 x .045 x 7/8	8,600	20			66252841918 INOX/SS	
	8,600	20				07660705251
7 x 1/16 x 7/8	8,600	10				
9 x 1/16 x 5/8-11	6,600	10			66253019115	

RIGHTCUT WHEELS ARE TO BE USED FOR CUTTING ONLY.

3/32", .125" – Cut-off – Type 27/42						
4 x .125 x 3/8	15,280	25	66252842001			
4 x .125 x 5/8	15,280	25				66252842014
4-1/2 x 3/32 x 5/8-11	13,580	10			66252841903	
	13,580	10			66252842027 INOX/SS	
4-1/2 x 3/32 x 7/8	13,580	25			66252841940	
	13,580	25			66252842028 INOX/SS	
	13,580	25			66252843582 1-2-3	
4-1/2 x .125 x 5/8-11	13,580	10	66252843321		66252843588	66252843609
4-1/2 x .125 x 7/8	13,580	25	66252843322		66252843589	66252843611
5 x 3/32 x 5/8-11	12,225	10			66252841904	
5 x 3/32 x 7/8	12,225	25			66252842037 INOX/SS	
	12,225	25			66252843587 LL	
	12,225	25			66252843583 1-2-3	
5 x .125 x 5/8-11	12,225	10				66252843615
5 x .125 x 7/8	12,225	25			66252843595	66252843616
6 x 3/32 x 5/8-11	10,185	10			66252841905	
6 x 3/32 x 7/8	10,185	25			66252841906	
	10,185	25			66252832487 INOX/SS	
6 x .125 x 5/8-11	10,185	10			66252841192	
6 x .125 x 7/8	10,185	25			66252842021	
7 x 3/32 x 5/8-11	8,600	10			66252841907	
7 x 3/32 x 7/8	8,600	20			66252841908	
	8,600	20			66252914638 INOX/SS	
7 x .125 x 5/8-11	8,600	10	66252912625			
7 x .125 x 7/8	8,600	20	66252912624		66252900619	
	8,600	25*				07660775956 5-Pk
9 x 3/32 x 5/8-11	6,600	10		66252842378		
9 x 3/32 x 7/8	6,600	20		66252842343		

THESE WHEELS ARE TO BE USED FOR CUTTING ONLY.

* 5-WHEEL JOB PACKS; WHEELS ARE PACKED 5 WHEELS/PACK, WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.

See .045" RightCut Wheels for Aluminum on page 17.



AVAILABILITY

							
				BEST	BETTER	GOOD	GOOD
TIER:							
TRADENAME:				NORTON NORZON PLUS	NORTON BLUEFIRE	NORTON GEMINI	NORTON METAL
SHAPE:				Type 27/42	Type 27/42	Type 27/42	Type 27/42
ABRASIVE:				Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
MATERIAL:				STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
1/8", 5/32" – Pipe Notching – Type 27							
4-1/2 x 1/8 x 5/8-11	13,580	10				66253370272 XXL	
4-1/2 x 1/8 x 7/8	13,580	25				66253370271 XXL	
5 x 1/8 x 5/8-11	12,225	10				66253370273 XXL	
5 x 1/8 x 7/8	13,580	25				66252842038 XXL	
6 x 1/8 x 5/8-11	10,185	10				66252841193 XXL	
6 x 1/8 x 7/8	10,185	20				66252835580 XXL	
7 x 1/8 x 5/8-11	8,600	10	66252939184			66253370274 XXL	
7 x 1/8 x 7/8	8,600	20				66252835581 XXL	
9 x 1/8 x 5/8-11	6,600	10	66253049066			66253370275 XXL	
9 x 1/8 x 7/8	6,600	20				66253370276 XXL	

PIPE NOTCHERS ARE TO BE USED FOR CUTTING/NOTCHING ONLY.

AVAILABILITY

							
				BEST	BETTER	GOOD	GOOD
TIER:							
TRADENAME:				NORTON NORZON PLUS	NORTON BLUEFIRE	NORTON GEMINI	NORTON METAL
SHAPE:				Type 27 and Type 28	Type 27 and Type 28	Type 27 and Type 28	Type 27
ABRASIVE:				Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
MATERIAL:				STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
1/8" – Cutting / Notching / Light Grinding – Type 27							
3 x 1/8 x 3/8	18,000	25	66252842177				
4 x 1/8 x 3/8	15,280	25	66252842004		66252843178	66252842016	
4 x 1/8 x 5/8	15,280	25	66252842005		66252843176	66252842017	
4-1/2 x 1/8 x 5/8-11	13,580	10	66252843323		66252843211	66252843590	
	13,580	10			66252843191 FC/INOX/SS		
	13,580	10 V				66252842166 2-Pk	
4-1/2 x 1/8 x 7/8	13,580	25	66252843324		66252843212	66252843591	
	13,580	25			66252843190 FC/INOX/SS		
	13,580	10 V				66252842167 2-Pk	
5 x 1/8 x 5/8-11	12,225	10	66252843330		66252843215		
	12,225	10			66252843195 FC/INOX/SS		
5 x 1/8 x 7/8	12,225	25	66252843331		66252843216	66252843596	
	12,225	25			66252843194 FC/INOX/SS		
6 x 1/8 x 5/8-11	10,185	10	66252841891		66252843199 FC/INOX/SS	66252833965	
6 x 1/8 x 7/8	10,185	20			66252843202	66252801864	
	10,185	20			66252843198 FC/INOX/SS		
7 x 1/8 x 5/8-11	8,600	10	66252938855		66252843233	66252939259	07660702678
	8,600	10			66252843183 FC/INOX/SS		
7 x 1/8 x 7/8	8,600	20	66252938854		66252843234	66252939207	
	8,600	20			66252843182 FC/INOX/SS		
	8,600	25*					
9 x 1/8 x 5/8-11	6,600	10	66253048897		66252843244	66253048983	
	8,600	10			66252843187 FC/INOX/SS		
9 x 1/8 x 7/8	6,600	20	66253048896		66252843245	66253048994	
	6,600	20			66252843186 FC/INOX/SS		

* 5-WHEEL JOB PACKS; WHEELS ARE PACKED 5 WHEELS/PACK, WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.

V NEW! VENDIBLE 2-WHEEL PACKAGE. IDEAL FOR VENDING MACHINES AND SMALL JOBS. 5 PACKS/CARTON. ORDER IN MULTIPLES OF 10.



AVAILABILITY

**BEST****BETTER****GOOD****GOOD**

TIER:
TRADENAME:
SHAPE:
ABRASIVE:
MATERIAL:

NORTON NORZON PLUS**NORTON BLUEFIRE****NORTON GEMINI****NORTON METAL**

Type 27 and Type 28

Type 27 and Type 28

Type 27 and Type 28

Type 27

Ceramic Alumina/
Zirconia AluminaZirconia Alumina/
Aluminum Oxide

Aluminum Oxide

Aluminum Oxide

STAINLESS**STAINLESS****STAINLESS****STAINLESS****STEEL/METAL****STEEL/METAL****STEEL/METAL****STEEL/METAL**

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #
1/4" – Grinding – Type 27						
3 x 1/4 x 3/8	18,000	25	66252842178		66252842179	
4 x 1/4 x 3/8	15,280	25	66252842002	66252843179	66252842018	
4 x 1/4 x 5/8	15,280	25	66252842003	66252843177	66252842020 FC	66252842011
	15,280	25			66252842019	
4-1/2 x 3/16 x 7/8	13,580	25	66252843325		66252843592	
4-1/2 x 1/4 x 5/8-11	13,580	10	66252843326	66252843213	66252843593	66252843605
	13,580	10	66252843327 LL	66252843193 FC/INOX/SS	66252843585 FC	
	13,580	10	66252843796 FC		66252842032 INOX/SS	
	13,580	10			66252843785 XXL	
	13,580	40				66252819559
	13,580	10 V	66252829541 2-Pk	66252842162 2-Pk	66252842163 2-Pk	
4-1/2 x 1/4 x 7/8	13,580	25	66252843328	66252843214	66252843594	66252843607
	13,580	25	66252843795 FC	66252843192 FC/INOX/SS	66252843584 FC	
	13,580	25			66252842033 INOX/SS	
	13,580	25			66252843784 XXL	
	13,580	50				66252836796
	13,580	10 V	66252829540 2-Pk	66252842164 2-Pk	66252842165 2-Pk	
5 x 1/4 x 5/8-11	12,225	10	66252843332	66252843217	66252843597	66252843613
	12,225	10	66252843333 LL	66252843197 FC/INOX/SS	66252843787 XXL	
	12,225	10	66252843798 FC			
5 x 1/4 x 7/8	12,225	25	66252843334	66252843218	66252843598	66252843614
	12,225	25	66252843797 FC	66252843196 FC/INOX/SS	66252843586 FC	
	12,225	25			66252842040 INOX/SS	
	12,225	25			66252843786 XXL	
	12,225	10 V			66252842172 2-Pk	
6 x 1/4 x 5/8-11	10,185	10	66252841920	66252843224	66252832390	
	10,185	10	66252843800 FC	66252843201 FC/INOX/SS	66252843789 XXL	
6 x 1/4 x 7/8	10,185	20	66252809376	66252843203	66252801865	
	10,185	20	66252843799 FC	66252843200 FC/INOX/SS	66252843788 XXL	
7 x 1/4 x 5/8-11	8,600	10	66252917881	66252843235	66252940147 FC	66252912633
	8,600	10	66252835578 LL	66252843185 FC/INOX/SS	66252940148 LL	
	8,600	10	66252843802 FC		66252843791 XXL	
	8,600	25*				07660775940 5-Pk
7 x 1/4 x 7/8	8,600	20	66252917880	66252843236	66252940099 FC	
	8,600	20	66252843801 FC	66252843184 FC/INOX/SS	66252940098 LL	
	8,600	20			66252843790 XXL	
	8,600	25*				07660775936 5-Pk
9 x 1/4 x 5/8-11	6,600	10	66253021634	66252843246	66253049105 FC	
	6,600	10	66252830728 LL	66252843189 FC/INOX/SS	66253049104 LL	
	6,600	10	66252843804 FC		66252843793 XXL	
	6,600	25*				07660775938 5-Pk
9 x 1/4 x 7/8	6,600	20	66253021633	66252843247	66253049077 FC	
	6,600	20	66252843803 FC	66252843188 FC/INOX/SS	66253048991 LL	
	6,600	20			66252843792 XXL	

* 5-WHEEL JOB PACKS; WHEELS ARE PACKED 5 WHEELS/PACK. WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.


V NEW! VENDIBLE 2-WHEEL PACKAGE. IDEAL FOR VENDING MACHINES AND SMALL JOBS. 5 PACKS/CARTON. ORDER IN MULTIPLES OF 10.

DEPRESSED CENTER WHEEL DESCRIPTION CODES


BLANK = ALL PURPOSE **FC** = FAST CUT **HD** = HEAVY DUTY **INOX/SS** = CONTAMINANT FREE **LL** = LONG LIFE **1-2-3** = CUTTING/NOTCHING/GRINDING
ALUMINUM **FOUNDRY** **MASONRY** **STAINLESS** **STEEL / METAL**



AVAILABILITY

									
TIER:		BEST		BEST		BETTER		GOOD	
TRADENAME:		NORTON NORZON PLUS		NORTON DIALAST		NORTON BLUEFIRE		NORTON GEMINI	
SHAPE:		Type 28		Type 29 and Reversible		Type 28		Type 28	
ABRASIVE:		Ceramic Alumina/ Zirconia Alumina		Diamond		Zirconia Alumina/ Aluminum Oxide		Aluminum Oxide	
MATERIAL:		STAINLESS		STAINLESS		STAINLESS		STAINLESS	
		STEEL/METAL		STEEL/METAL		STEEL/METAL		STEEL/METAL	
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #		PART #		PART #		PART #
1/4" – Grinding – Type 28 Saucer 									
7 x 1/4 x 5/8-11	8,600	10	66252905369			66252843229		66252940149	
	8,600	10	66252844345 FC						
7 x 1/4 x 7/8	8,600	20	66252905368					66252940095	
9 x 1/4 x 5/8-11	6,600	10	66253006335			66252843237		66253049106	
	6,600	10	66252844346 FC						
9 x 1/4 x 7/8	6,600	20	66253370137 FC					66253049081	
Light Grinding – Type 29 									
4-1/2 x 5/8-11	13,600	1			66253370009				
5 x 5/8-11	12,225	1			66253370010				
6 x 5/8-11	10,200	1			66253370011				
7 x 5/8-11	8,600	1			66253370012				
9 x 5/8-11	6,600	1			66253370013				
1/4" – Grinding – Reversible Grinding Disc 									
4-1/2 x 1/4 x 5/8-11	13,600	1			66253370019				
7 x 1/4 x 5/8-11	8,600	1			66253370020				

AVAILABILITY

											
TIER:		BEST		BEST		BEST		BETTER		GOOD	
TRADENAME:		NORTON NORZON PLUS		NORTON NORZON III		NORTON DIALAST		NORTON BLUEFIRE		NORTON FOUNDRY X	
SHAPE:		Type 27		Type 27		Type 29		Type 27		Type 27	
ABRASIVE:		Ceramic Alumina/ Zirconia Alumina		Ceramic Alumina/ Zirconia Alumina		Diamond		Zirconia Alumina/ Silicon Carbide		Aluminum Oxide	
MATERIAL:		FOUNDRY		FOUNDRY		FOUNDRY		FOUNDRY		FOUNDRY	
		FOUNDRY		FOUNDRY		FOUNDRY		FOUNDRY		FOUNDRY	
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #		PART #		PART #		PART #		PART #
.140", 1/8", 1/4", – Cutting / Notching / Grinding – Type 27 and Type 29 											
4 x 1/4 x 3/8	15,280	25						66252843181			
4 x 1/4 x 5/8	15,280	25						66252843180			
4-1/2 x 1/8 x 5/8-11	13,580	10						66252843206			
4-1/2 x 1/8 x 7/8	13,580	25						66252843204			
4-1/2 x 1/4 x 5/8-11	13,580	10						66252843207			
4-1/2 x 1/4 x 7/8	13,580	25						66252843205			
7 x .140 x 5/8-11	8,600	1				66253370014					
7 x 1/8 x 5/8-11	8,600	10						66252843232			
7 x 1/8 x 7/8	8,600	20						66252915526			
7 x 1/4 x 5/8-11	8,600	10						66252843231			
7 x 1/4 x 7/8	8,600	20						66252843230			
9 x .140 x 5/8-11	6,600	1				66253370015					
9 x 1/8 x 5/8-11	6,600	10						66252843240			
9 x 1/8 x 7/8	6,600	20						66252843238			
9 x 1/4 x 5/8-11	6,600	10	66253007014					66252843241			
	6,600	10						66252843261 HD			
9 x 1/4 x 7/8	6,600	20	66253007013		66253049069			66252843239		66252842776	
	6,600	20						66252843260 HD			

DEPRESSED CENTER WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE	FC = FAST CUT	HD = HEAVY DUTY	INOX/SS = CONTAMINANT FREE	LL = LONG LIFE	1-2-3 = CUTTING/NOTCHING/GRINDING
 = ALUMINUM	 = FOUNDRY	 = MASONRY	 = STAINLESS	 = STEEL / METAL	



AVAILABILITY



TIER: **GOOD**
 TRADENAME: **NORTON GEMINI**
 SHAPE: Type 27
 ABRASIVE: Aluminum Oxide
 MATERIAL: ALUMINUM

SIZE (D x T x H)	MAX. RPM	STD. PKG.	GRIT	PART #
1/8", 1/4" – Cutting / Grinding / Blending – Type 27				
4-1/2 x .045 x 7/8	13,580	25	36	66252841909
4-1/2 x 1/8 x 5/8-11	13,580	10	46	66252842029
4-1/2 x 1/8 x 7/8	13,580	25	46	66252842030
4-1/2 x 1/4 x 5/8-11	13,580	10	46	66252842031
4-1/2 x 1/4 x 7/8	13,580	25	46	66252842034
5 x .045 x 7/8	12,225	25	36	66252841910
5 x 1/4 x 7/8	12,225	25	46	66252842039
6 x .045 x 7/8	10,185	25	36	66252841911
7 x 1/4 x 5/8-11	8,600	10	24	66252940514
	8,600	10	46	66252940515
7 x 1/4 x 7/8	8,600	20	24	66252940516
9 x 1/4 x 5/8-11	6,600	10	24	66253049045

AVAILABILITY



TIER: **GOOD**
 TRADENAME: **NORTON MASONRY**
 SHAPE: Type 27
 ABRASIVE: Silicon Carbide
 MATERIAL: MASONRY

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #
1/8", 1/4" – Cutting / Grinding – Type 27			
4 x 1/8 x 5/8	15,280A	25	66252842013
4 x 1/4 x 5/8	15,280	25	66252842010
4-1/2 x 1/8 x 7/8	13,580	25	66252843601
4-1/2 x 1/4 x 5/8-11	13,580	10	66252843599
4-1/2 x 1/4 x 7/8	13,580	25	66252843600
5 x 1/4 x 7/8	12,225	25	66252843602
7 x 1/4 x 5/8-11	8,600	5	07660775942
9 x 1/4 x 5/8-11	6,600	5	07660775937

AVAILABILITY



TIER: **BETTER**
 TRADENAME: **NORTON AVOS GEMINI**
 SHAPE: Type 29
 ABRASIVE: Aluminum Oxide
 MATERIAL: ALUMINUM



GOOD
 NORTON GEMINI FLEXIBLE

Type 27
 Aluminum Oxide

ALUMINUM
 STEEL/METAL

PART #



GOOD
 NORTON GEMINI FLEXIBLE

Type 29
 Aluminum Oxide

ALUMINUM
 STEEL/METAL

PART #

SIZE (D x T x H)	MAX. RPM	STD. PKG.	GRIT	PART #	PART #	PART #
1/8", 1/4" Flexible – Blending – Type 27 and 29						
2 x 1/8 x 3/8	30,560	25	60		66252835632*	
	30,560	25	80		66252835633*	
4 x 1/8 x 5/8	15,280	20	36		66243529721#	
	15,280	20	60		66243529722#	
4-1/2 x 1/8 x 5/8-11	12,000	10	36	66252842208		66252842203
4-1/2 x 1/8 x 7/8	12,000	25	36	66252842209	66252830424#	66252842204
	12,000	25	46	66252842210		
	12,000	25	60	66252842211	66252830425#	
5 x 1/8 x 7/8	12,225	25	36	66252842212		66252842205
7 x 1/8 x 5/8-11	8,600	10	36		66252939024	66252917052
7 x 1/8 x 7/8	8,600	20	36		66252939028#	66252917051

*5 WHEELS PER DISPLAY PACK; 5 DISPLAY PACKS PER STANDARD PACKAGE.

THESE WHEELS ARE PACKED 20 PER BOX, AND MUST BE USED WITH A BACK PLATE. TWO BACK PLATES ARE INCLUDED IN EACH BOX.

DEPRESSED CENTER WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE **FC** = FAST CUT **HD** = HEAVY DUTY **INOX/SS** = CONTAMINANT FREE **LL** = LONG LIFE **1-2-3** = CUTTING/NOTCHING/GRINDING
 ■ = ALUMINUM ■ = FOUNDRY ■ = MASONRY ■ = STAINLESS ■ = STEEL / METAL



CATEGORY DEFINITION

The Norton small diameter cut-off wheel line consists of Type 01, Type 01/41 straight and Type 27/42 depressed center cut-off wheels from 1-1/2" to 9" diameters. These wheels come in ultra thin .035 for quick burn-free and burr-free cutting to .125" for more durable applications. All are reinforced for the demanding nature of portable cut-off.


APPLICATIONS:	Cutting sheet metal, cutting pipe, and metal plate dimensioning (metal fabrication)
SIZE RANGE:	1-1/2" - 9" diameter
THICKNESS RANGE:	.035, .040, .045, .060, .090, and .125
ABRASIVE GRAIN:	Ceramic Alumina/Zirconia Alumina, Zirconia Alumina/Aluminum Oxide, Aluminum Oxide, Silicon Carbide, Diamond
SHAPE:	Type 01, Type 01/41 Straight and Type 27/42 Depressed Center




TYPE-TO-APPLICATION RECOMMENDATION GUIDE

WHEEL TYPE/THICKNESS APPLICATIONS

TYPE 01



Type 01 straight cut-off wheels are designed for traditional cut-off applications. All are supplied with full fiberglass reinforcing.



.035, .040, 1/16

Where fast cutting and low kerf loss are desired



.125

For tough cutting and notching applications where stability is important



TYPE 01/41 RIGHT CUT



Type 01/41 straight cut-off wheels are designed for use on right angle grinder cut-off applications. All are supplied with full fiberglass reinforcing.



90° ANGLE

.035, .040, .045, .050, 1/16

Where fast cutting and low kerf loss are desired



3/32

For tough cutting and notching applications where stability is important



TYPE 27/42 RIGHT CUT



Type 27/42 cut-off wheels are designed for use on right angle grinder cut-off applications. Their depressed center shape provides a recess for the hub, which allows flush cutting. All are supplied with full fiberglass reinforcing.



90° ANGLE

.040, .045, 1/16

Where fast cutting and low kerf loss are desired



3/32, .125

For tough cutting and notching applications where stability is important



HOW TO PICK THE RIGHT BOND TYPE

All Purpose	Unmarked	Where an excellent blend of cut rate and life is needed
Free Cut	FC	Where fast stock removal is needed, or the application only allows low-pressure or under-horsepowered grinders
Long Life	LL	Where durability is needed due to severe application, and when horsepower of the grinder allows heavy pressure
Contaminate Free	INOX/SS	Contain <0.1% iron, sulfur or chlorine for rust-free and corrosion-free results; will not contaminate stainless steel
Aluminum	ALU	Specially formulated bond for reduced loading/surface contamination cutting aluminum/soft materials



MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	BEST HIGHEST PRODUCTIVITY LOWEST TOTAL COST	BETTER EXCELLENT BLEND OF PERFORMANCE & PRICE	GOOD CONSISTENT PERFORMANCE LOW INITIAL PRICE
Cutting			
Mild Carbon / High Tensile Steel	Norton NorZon Plus	Norton BlueFire	Norton Metal
Stainless Steel / Alloys	Norton NorZon Plus	Norton BlueFire <i>INOX/SS</i>	Norton Gemini <i>INOX/SS</i>
Contaminate Free		Norton BlueFire <i>INOX/SS</i>	Norton Gemini <i>INOX/SS</i>
Cast Iron	Norton NorZon Plus	Norton BlueFire	Norton Gemini
Aluminum / Bronze / Brass			Norton Gemini <i>ALU</i>
Asphalt / Brick / Concrete			Norton Masonry

CROSS REFERENCE GUIDES

TYPE 01 .035 - .125 CUT-OFF WHEELS FOR DIE GRINDERS

	TOTAL PERFORMANCE			INITIAL PRICE		SPECIALTY	
NORTON	BEST NorZon Plus	BETTER BlueFire	GOOD Gemini <i>Free Cut</i>	Gemini	Metal	GOOD Gemini <i>INOX</i>	
Brilliant	—	Brill-Max ZA	—	—	Safe-Tex FC, LL	—	
Bullard	—	ZA46T, ZA60T	TA36T	TA46T, TA60T	A36T, A60T Comp.	—	
Camel	—	ZA60-TBF	A36 RBF	A60 RBF	Fast Cut RBF	—	
Flexovit	Flexon Fast Cut A46, 60	—	High Perf Fast Grind A36	High Perf Fast Cut A36, 46, 60	—	—	
Pearl	—	SRT, Zirconia	—	Premium	Silver Line	—	
Pferd	—	—	—	—	PSF-A	SG-A-R-INOX	
Sait	Saittech	—	A60S	A24R, A36T, A60T	—	—	
Spedecut	—	—	—	—	A46, 60 TBXX	—	
Walter	—	—	A24 ZIP	A60 ZIP	—	—	

TYPE 01/41 AND TYPE 27/42 .035 - .125 CUT-OFF WHEELS FOR RIGHT ANGLE GRINDERS

NORTON	TOTAL PERFORMANCE				INITIAL PRICE			SPECIALTY		
	BEST		BETTER		GOOD			GOOD		
	NorZon Plus Free Cut	NorZon Plus	BlueFire Free Cut	BlueFire	Gemini Free Cut	Gemini	Metal	Gemini ALU	Gemini INOX/SS	Masonry
Brilliant	—	—	—	—	Brill-Blade Extra FC	Brill-Blade Heavy Duty	Hornet Stinger	—	—	—
Bullard	—	—	—	ZA60T	SGA60U	TA46T, TA60T, TA60U	A46T, A60T Comp.	AL46N	—	C24R
Camel	—	—	—	ZA Quickie Cut	A36-S-BF	Super Quickie Cut	Quickie Cut	A46 Quickie Cut	A60-T-BF, WA60R Quickie Cut	—
Flexovit	—	—	—	—	Razorblade A60SST	Razorblade A24T, 30V, 36T	—	Razorblade A30Q	—	C30U
Metabo	—	—	—	A 60 XP Super Slicer	—	A 60 TX Slicer-Plus	A 60 TZ Slicer	—	—	—
Pearl	—	—	—	Redline Max Slimcut	—	Slimcut	Slimcut Pro-V, Sliverline	—	—	—
Pferd	—	—	—	SGP-ZA-Q- INOX	—	SG-A-S, SGP-A-T	PSF-A-P	S-G-N-ALU	SG-A-R- INOX, SGP-A- S-INOX	SG-C-R
Sait	—	Saittech	—	Z-tech	SAIT.M.X	A60S	—	A46N	XA46R	—
SpedeCut	—	—	—	—	—	—	A46, 60 TBXX	—	—	—
Walter	—	—	—	—	A-30-ZIP	A-60-ZIP	—	A-60-ZIP-ALU	A60-SS-ZIP	C-30 -ZIP



FEATURED PRODUCTS



EXPANDED
OFFERING

NORTON NORZON PLUS CUT-OFF / RIGHTCUT

BEST CHOICE FOR HIGHEST PRODUCTIVITY FOR STEEL, STAINLESS STEEL AND ALL FERROUS METALS

FEATURES

- Norton SG (ceramic alumina) / NorZon (zirconia alumina) grain combination
- Highly-advanced bond system
- RightCut right angle grinder wheels

BENEFITS

- Fastest cutting wheel available on the market, up to 3X faster cutting versus aluminum oxide
- 3X – 10X life versus aluminum oxide wheels on carbon steel, stainless and cast iron
- Noticeably longer life and faster cut rate
- Less pressure required for first cut



NORTON BLUEFIRE CUT-OFF / RIGHTCUT

BETTER CHOICE FOR STAINLESS STEEL, CARBON STEEL, ALLOYS AND GRAY IRON

FEATURES

- A blend of R&D advanced chemistry and shaped zirconia alumina abrasive and premium aluminum oxide grain
- RightCut right angle grinder wheels

BENEFITS

- 2-3 times the life of aluminum oxide wheels
- Broad utility from light-to heavy-pressure applications
- Excellent performance-to-price ratio for lower total grinding costs
- Noticeably longer life and faster cut rate
- Less pressure required for first cut



IMPROVED

NORTON GEMINI CUT-OFF / RIGHTCUT

GOOD, VERSATILE CHOICE FOR STEEL AND FERROUS METALS

FEATURES

- Quality, versatile aluminum oxide
- Gemini Contaminate-Free **INOX/SS**
- .045 ultra-thin Gemini RightCut right angle grinder Type 01/41 straight and T27/42 depressed center cut-off wheels

BENEFITS

- Consistent performance at a competitive price
- Contain <0.1% iron, sulfur or chlorine for rust-free and corrosion-free results; will not contaminate stainless steel
- Precise cutting; more stability and a narrower pass
- Up to 70% longer life and 20% faster cut rate than standard aluminum oxide wheels – for substantial savings
- Require less pressure, providing increased operator comfort



NORTON METAL CUT-OFF / RIGHTCUT


GOOD CHOICE FOR GRINDING ALLOYS, METALS, STEELS, AND FERROUS METALS

FEATURES

- Quality aluminum oxide
- Low initial cost per wheel

BENEFITS

- Consistent performance at a competitive price
- Ideal for on-site and small-unit jobs



NEW

NORTON DIALAST DIAMOND CUT-OFF


BEST FOR PIPE, TUBING, CAST IRON, CARBON AND MILD STEEL AND CERAMIC APPLICATIONS

FEATURES

- A combination of high-quality diamond and advanced brazed single-layer bonding technology
- Environmentally friendly grinding

BENEFITS

- Extra-long life vs. conventional abrasives or other vacuum-brazed diamond tools
- Retains the diamond grains and wheel shape for full life with low spark, while keeping a continuous grinding depth
- Less blade changes reduce downtime and labor costs
- Generate minimal dust



AVAILABILITY

TIER:	BEST	BETTER	BETTER	GOOD	GOOD	GOOD
TRADENAME:	NORTON NORZON PLUS	NORTON BLUEFIRE	NORTON A60-0BNA2	NORTON GEMINI	NORTON GEMINI LONG LIFE	NORTON METAL
SHAPE:	Type 01	Type 01	Type 01	Type 01	Type 01	Type 01
ABRASIVE:	Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
MATERIAL:	STAINLESS	STAINLESS	STAINLESS	STAINLESS	STAINLESS	STAINLESS
	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #
.035", .040", .060", 1/16" and .125" Type 01 – Cut-off								
1-1/2 x .035 x 1/16	40,745	25			66243427764			
1-1/2 x .035 x 1/8	40,745	25			66243427831			
1-1/2 x .035 x 1/4	40,745	25			66243427875			
2 x .035 x 1/8	30,560	25				66243411392 FC		
2 x .035 x 1/4	30,560	25			66243428014	66243411393 FC		
2 x .035 x 3/8	30,560	25				66243411394 FC		
2 x .060 x 1/8	30,560	25			66243428041			
2 x 1/16 x 1/4	30,560	25			66243427993	66243411395 FC		
2 x 1/16 x 3/8	30,560	25				66243411396 FC		
2 x .125 x 1/4	30,560	25				66243411402 FC		
2 x .125 x 3/8	30,560	25				66243411403 FC		
2-1/2 x .035 x 1/8	30,560	25			66243528476			
2-1/2 x .035 x 1/4	30,560	25			66243528425			
2-1/2 x 1/16 x 1/4	30,560	25				66243510640 FC		
2-1/2 x 1/16 x 3/8	30,560	25				66243510641 FC		
3 x .035 x 1/4	25,465	25	66243510668		66243528573	66243510627 FC		
	25,465	25*	66243531753 5-Pk					
3 x .035 x 3/8	25,465	25	66243510669	66252843174	66243528574	66243510628 FC	66243537271 LL	07660789451
	25,465	25*	66243534828 5-Pk	66243534821 5-Pk				
3 x 1/16 x 1/4	25,465	25	66243510670		66243528471	66243510645 FC	66243510649 LL	
3 x 1/16 x 3/8	25,465	25	66243510671	66252843175	66243528552	66243510647 FC	66243510648 LL	66252835553
	25,465	25*	66243510835 LL					07660747767 5-Pk
	25,465	100						07660789012
	25,465	1						66252843624 5-Pk with Mandrel
3 x .125 x 1/4	25,465	25				66243510650 FC	66243510652 LL	
3 x .125 x 3/8	25,465	25	66243510673			66243510651 FC	66243510653 LL	07660789384
4 x .035 x 1/4	15,300	25			66243529606			
	19,100	25				66243510629 FC		
4 x .035 x 3/8	19,100	25	66243510675	66252843173	66243529621	66243510630 FC	66243537273 LL	07660789453
	19,100	250*						66252836496 250-Pk
4 x .035 x 1/2	19,100	25			66243529622			
4 x .035 x 3/4	19,100	25			66243529609			
4 x .040 x 3/8	19,100	25			66243529516			
4 x 1/16 x 1/4	19,100	25	66243510676			66243510654 FC		
4 x 1/16 x 3/8	19,100	25	66243510677	66252843171		66243510655 FC	66243510657 LL	66252843848
4 x 1/16 x 5/8	19,100	100			66243527827 FabTech			
	19,100	100			66243527826 FabTech LL			
4 x .125 x 1/4	19,100	25				66243510658 FC		
4 x .125 x 3/8	19,100	25	66243510841	66252843172		66243510659 FC	66243510661 LL	
	19,100	25	66243510680 LL					
5 x .035 x 3/8	12,225	25			66252830653			
6 x .035 x 3/8	10,185	25			66252835064			
6 x .035 x 1/2	10,185	25			66252835053			
6 x .035 x 5/8	10,185	25			66252835054	66252809714		
Drill Mount Mandrel		5						07660747769+

+ FOR MOUNTING 2" AND 3" X 3/8" HOLE CUT-OFF WHEELS ON TO A DRILL

* 5-WHEEL JOB PACKS; WHEELS ARE PACKED 5 WHEELS/PACK, WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.

• BULK PACKED 250/CARTON; 5 INNER BOXES OF 50 WHEELS EACH. ORDER IN MULTIPLES OF 250 WHEELS.

WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE	FC = FREE CUT	INOX/SS = CONTAMINANT FREE	LL = LONG LIFE
■ = MASONRY	■ = STAINLESS	■ = STEEL / METAL	



AVAILABILITY



TIER:

TRADENAME:

SHAPE:

ABRASIVE:

MATERIAL:

BEST	BEST	BETTER	GOOD	GOOD
NORTON NORZON PLUS RIGHTCUT	NORTON DIALAST RIGHTCUT	NORTON BLUEFIRE RIGHTCUT	NORTON GEMINI RIGHTCUT	NORTON METAL RIGHTCUT
Type 01/41	Type 01/41	Type 01/41	Type 01/41	Type 01/41
Ceramic Alumina/ Zirconia Alumina	Diamond	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
STAINLESS	STAINLESS	STAINLESS	STAINLESS	STAINLESS
STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #

.035", .040", .045", .050", 1/16, and 3/32" Type 01/41 – RightCut Cut-off					800-665-2200		www.norton.com	
4 x .040 x 5/8	15,280	25						07660701616
4 x .045 x 5/8	15,280	25				66243527956		
4 x 3/32 x 5/8	15,280	25				66243527955		
4-1/2 x .035 x 7/8	13,580	25						66252843846
4-1/2 x .040 x 7/8	13,580	25			66252843225			07660701617
	13,580	50						66253370222
	13,580	250•						66252840001 250-Pk
	13,580	25*						66252842158 5-Pk
4-1/2 x .045 x 7/8	13,580	25	66252830730		66252843208	66252823602		
	13,580	25				66252841994 ALU		
	13,580	25				66252841997 INOX/SS		
	13,580	250•				66252841213 250-Pk		
	13,580	25*			66252842159 5-Pk	66252842160 5-Pk		
4-1/2 x .050 x 7/8	13,580	1		66253370016				
4-1/2 x 1/16 x 7/8	13,580	25						66252843845
4-1/2 x 3/32 x 7/8	13,580	25				66252823599		
5 x .040 x 5/8	12,225	25						66252843847
5 x .040 x 7/8	12,225	25			66252843226			07660701618
	12,225	25*						66252842168 5-Pk
5 x .045 x 7/8	12,225	25	66252830731		66252843209	66252823603		
	12,225	25				66252841995 ALU		
	12,225	25				66252841998 INOX/SS		
	12,225	250•				66252841214 250-Pk		
	12,225	25*			66252842169 5-Pk	66252842170 5-Pk		
5 x .050 x 7/8	12,225	25	66252809829					
	12,225	1		66253370017				
5 x 3/32 x 7/8	12,225	25				66252823600		
6 x .040 x 7/8	10,185	25						07660702757
	10,185	50						66253370223
	10,185	250•						66252841212 250-Pk
	10,185	25*						66252842173 5-Pk
6 x .045 x 7/8	10,185	25	66252842008		66252843210	66252823604		
	10,185	25				66252841996 ALU		
	10,185	25				66252841999 INOX/SS		
	10,185	250•				66252841215 250-Pk		
	10,185	25*			66252842174 5-Pk	66252842175 5-Pk		
6 x .050 x 7/8	10,185	1		66253370018				
6 x .060 x 5/8	10,185	25				66252809718		
6 x 3/32 x 7/8	10,185	25				66252823601		
7 x .045 x 7/8	8,600	25				66252832323		
	8,600	20				66252842000 INOX		
7 x 1/16 x 5/8	8,600	25				66252905957		
7 x 1/16 x 7/8	8,600	25	66252900652					07660704732
	8,600	1		70184694055				
9 x .060 x 7/8	6,600	1		70184694056				

RIGHTCUT WHEELS ARE TO BE USED FOR CUTTING ONLY

* 5-WHEEL JOB PACKS: WHEELS ARE PACKED 5 WHEELS/PACK, WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.

• BULK PACKED 250 WHEELS/CARTON; 5 INNER BOXES OF 50 WHEELS EACH. ORDER IN MULTIPLES OF 250 WHEELS.

Gemini RightCut Right Angle Grinder Cut-off Wheels

THINNER! FASTER! STRONGER! Our 100% aluminum oxide abrasive has been infused with a new bond technology and processed to outlast and out-cut competitive aluminum oxide blades. Operators will notice and appreciate the low kerf loss and added comfort.

Available in Type 01/41 straight and Type 27/42 depressed center wheels.

We Make the Right Choice More Comfortable





AVAILABILITY



TIER:
TRADENAME:
SHAPE:
ABRASIVE:
MATERIAL:

	BEST	BETTER	GOOD	GOOD
TRADENAME:	NORTON NORZON PLUS	NORTON BLUEFIRE	NORTON GEMINI	NORTON METAL
SHAPE:	Type 27/42	Type 27/42	Type 27/42	Type 27/42
ABRASIVE:	Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
MATERIAL:	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL	STAINLESS STEEL/METAL
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #

.040, .045, 1/16", - RightCut Cut-off - Type 27/42

4 x .045 x 5/8	15,280	25			66252842180	07660705249
4-1/2 x .040 x 5/8-11	13,580	10		66252843227		
4-1/2 x .045 x 5/8-11	13,580	10	66252842006	66252843223	66252842025	
	13,580	10			66252841913 INOX/SS	
4-1/2 x .045 x 7/8	13,580	25	66252843320	66252843219	66252842026	66252843604
	13,580	25			66252841912 INOX/SS	
	13,580	25*			66252842161 5-Pk	
	13,580	250			66253370065 250-Pk	
5 x .040 x 5/8-11	12,225	10		66252843228	66252841939	
5 x .045 x 5/8-11	12,225	10			66252841915 INOX/SS	
	12,225	10			66252842036	66252843849
5 x .045 x 7/8	12,225	25	66252843329	66252843220	66252841914 INOX/SS	
	12,225	25			66252842171 5-Pk	
	12,225	25*			66253370066 250-Pk	
	12,225	250			66252830587	
6 x .045 x 5/8-11	10,185	10	66252842007		66252841917 INOX/SS	
	10,185	10			66252842202	66252842015
6 x .045 x 7/8	10,185	25	66252842009	66252843221	66252841916 INOX/SS	
	10,185	25			66252842176 5-Pk	
	10,185	25*			66253370067 250-Pk	
	10,185	250			66252841919 INOX/SS	
7 x .045 x 5/8-11	8,600	10			66252912626	
7 x .045 x 7/8	8,600	20			66252841918 INOX/SS	
	8,600	20				07660705251
7 x 1/16 x 7/8	8,600	10				
9 x 1/16 x 5/8-11	6,600	10			66253019115	

RIGHTCUT WHEELS ARE TO BE USED FOR CUTTING ONLY.

3/32", .125" - Cut-off - Type 27/42

4 x .125 x 3/8	15,280	25	66252842001		66252841903	
4-1/2 x 3/32 x 5/8-11	13,580	10			66252842027 INOX/SS	
	13,580	10			66252841940	
4-1/2 x 3/32 x 7/8	13,580	25			66252842028 INOX/SS	
	13,580	25			66252843582 1-2-3	
	13,580	25			66252843588	
4-1/2 x .125 x 5/8-11	13,580	10	66252843321		66252843589	
4-1/2 x .125 x 7/8	13,580	25	66252843322		66252841904	
5 x 3/32 x 5/8-11	12,225	10			66252842037 INOX/SS	
5 x 3/32 x 7/8	12,225	25			66252843587 LL	
	12,225	25			66252843583 1-2-3	
	12,225	25			66252843595	
5 x .125 x 7/8	12,225	25			66252841905	
6 x 3/32 x 5/8-11	10,185	10			66252841906	
6 x 3/32 x 7/8	10,185	25			66252832487 INOX/SS	
	10,185	25			66252841192	
6 x .125 x 5/8-11	10,185	10			66252842021	
6 x .125 x 7/8	10,185	25			66252841907	
7 x 3/32 x 5/8-11	8,600	10			66252841908	
7 x 3/32 x 7/8	8,600	20			66252914638 INOX/SS	
	8,600	20				
7 x .125 x 5/8-11	8,600	10	66252912625		66252900619	
7 x .125 x 7/8	8,600	20	66252912624			
9 x 3/32 x 5/8-11	6,600	10		66252842378		
9 x 3/32 x 7/8	6,600	20		66252842343		

THESE WHEELS ARE TO BE USED FOR CUTTING ONLY.

* 5-WHEEL JOB PACKS; WHEELS ARE PACKED 5 WHEELS/PACK, WITH 5 JOB PACKS/CARTON. ORDER PER EACH WHEEL IN STANDARD PACKAGE QUANTITIES OF 25. ORDER IN MULTIPLES OF 25.

See .045" RightCut Wheels for Aluminum on page 17.

WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE	FC = FREE CUT	INOX/SS = CONTAMINANT FREE	LL = LONG LIFE
= MASONRY	= STAINLESS	= STEEL / METAL	



AVAILABILITY

TIER:
TRADENAME:
SHAPE:
ABRASIVE:
MATERIAL:



BEST

BETTER

GOOD

GOOD

GOOD

NORTON DIALAST

NORTON CHARGER

NORTON GEMINI

NORTON METAL

NORTON MASONRY

Type 01

Type 01

Type 01

Type 01

Type 01

Diamond

Zirconia Alumina/
Aluminum Oxide

Aluminum Oxide

Aluminum Oxide

Silicon Carbide

STAINLESS

STEEL/METAL

STEEL/METAL

STEEL/METAL

MASONRY

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
Type 01 – Circular Saw							
6 x .035 x 5/8	10,185	25			66252809714		
6 x .060 x 5/8	10,185	25			66252809718		
6-1/2 x .125 x DM-5/8	9,405	10				07660789098	07660789089
7 x .060 x 5/8	8,730	25			66252905957		
7 x .060 x 7/8	8,730	1	70184694055				
7 x .125 x DM-5/8	8,730	25				07660789097	07660789088
8 x 1/16 x 5/8	7,640	25		66253017771 LL	66253007025		
	7,640	10			66253017795		
8 x 1/8 x DM-5/8	7,640	10				07660789096	07660789086
9 x .060 x 7/8	6,600	1	70184694056				

DM DENOTES DIAMOND MOUNT; 5/8" HOLE BUSHINGS INCLUDED

WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE

FC = FREE CUT

INOX/SS = CONTAMINANT FREE

LL = LONG LIFE

■ = MASONRY

■ = STAINLESS

■ = STEEL / METAL

DiaLast Diamond: Introducing The Last Cut-Off and Depressed Center Wheels Standing!

Metal working demands tools that will cut or grind fast, throw a minimum of spark, and above all, LAST.

Thve new Norton DiaLast diamond cutting and grinding wheels give the operator everything needed to get the job done right, the very first time:

- Right angle grinder, circular saw, and chop saw blades for cutting steel, metal studs, stainless steel, nonferrous materials, tile, brick, plastic, and much more.
- DiaLast depressed center cutting and grinding wheels are an excellent choice on steel, cast iron, ductile pipe, tubing, and metal plate when high stock removal is desired

To learn more, see DiaLast depressed center (page 12) and cut-off wheel Features and Benefits (page 20).





CATEGORY DEFINITION

Norton high-speed cut-off abrasive wheels provide the industry's leading performance in all high-speed gas and electric-powered applications.

APPLICATIONS:	Metalworking: steel, stainless, ductile, cast iron, rail steel and metal decking Non-Metal Building Materials: concrete, brick, masonry, asphalt aggregate, stone and schedule 40 and 80 PVC pipe Rescue and Demolition: steel, acrylic, fiberglass, rubber, glass, wood, concrete, brick and asphalt
SIZE RANGE:	12" – 16" diameter
THICKNESS RANGE:	1/8"
ABRASIVE GRAIN:	Aluminum Oxide, Silicon Carbide, Silicon Carbide/Aluminum Oxide Blend
SHAPE:	Type 01 Straight
REINFORCEMENT:	Wheels are offered in standard two layer reinforcement as well as three layer reinforcement for higher-speed saws and heavy-duty applications
ARBOR:	Wheels are offered with patented universal arbor that accommodates both 20mm and all other machines with 1" arbors

MATERIAL / APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE

ICON		APPLICATION
	Metal	High-performance aluminum oxide grain wheels designed for general purpose cutting of all steel and stainless parts including rebar, steel pipe, structural steel, sheet metal, cable and small to medium diameter solid pieces.
	Metal Decking	High-performance aluminum oxide abrasive combined with a thicker wheel that stands up to the sharp edges of sheet metal and roof decking.
	Rail Steel	A finer grit, harder grade aluminum oxide wheel designed for straight, fast cuts on all sizes of rail track. Additional high-performance lines of rail cut wheels are available for production applications.
	Ductile/Cast Iron	A special blend of silicon carbide abrasive for cutting and aluminum oxide abrasive for life, designed to cut ductile and cast iron pipe, concrete-lined water pipes, sewer construction and heavy duty PVC.
	Rescue	For ventilation, forcible entry, rescue and demolition. A versatile abrasive formula that can be used on a wide range of materials including all types of metals and masonry.
	Concrete	Coarse grit silicon carbide abrasive provides a low initial cost solution for cutting brick, block, concrete or other masonry materials. For higher-production applications that require optimum speed of cut and product life, please see our complete selection of high-speed diamond wheels in our Norton Construction diamond product line.
	Asphalt	A special blend of extra coarse silicon carbide abrasive grains provides a low initial cost solution for cutting asphalt, green concrete, asphalt over concrete, a wide range of aggregates and abrasive materials. For higher-production applications that require optimum speed of cut and product life, please see our Norton Construction diamond product line.


HOW TO PICK THE RIGHT REINFORCEMENT



Two full layers of reinforcing are offered for lower power machines, and light to medium applications where speed of cut is the primary selection criterion.



Three full layers of reinforcing are recommended for high speed, high horsepower machines where the application is heavy-duty, and durability is the primary selection criterion.



Universal Arbor

Two Blade Sizes in One

Our Norton patented 1"/20mm knock-out arbor fits all gas and electric high-speed saws. A 20mm bushing is pre-mounted into the 1" molded arbor hole. The wheel, with the 20mm bushing, can be mounted directly on any 20mm arbor high-speed saw. With the bushing removed, exposing the 1" arbor hole, the wheel can be mounted on any 1" arbor high-speed saw. Combining this arbor, with heavy-duty triple reinforcing results in a higher performing, extra strong, longer lasting cutting wheel. Once the 20mm bushing is removed, it cannot be replaced.



CROSS REFERENCE GUIDE

SPECIALTY

NORTON

	GOOD Gemini Metal	Gemini Metal Decking	Rail Steel	Gemini Ductile	Gemini Concrete	Gemini Asphalt
Abmast	A 24 R, Kompetitor Metal	A 24 T	Rail-Kut A 24 Z	AC 24 R, Kompetitor Ductile Iron	C 24 R, Kompetitor Concrete	C 16 T, Kompetitor Asphalt
Brilliant	Metal/Stainless	—	A24PB	—	Concrete/Masonry	—
Bullard Blaze & Road Warrior	A24R, ZA24Q, The Competitor	TA24R	A30R	AC24R	C24R, The Competitor	CC20R
Camel	A24-R	A24-T	—	AC24-R	C24-R	C16-U
Flexovit	A24/30SB	A24TB	A30PB	AC24SB	C30UB	C16UB
Husqvarna	Blue XHS, Blue QMS- CM, Blue EHS	Grey QMS-CM	Yellow QMS-CM	Green QMS-CM, Green EHS	Red XHS, Red QHS-CM, Red EHS	Black QMS-AS
Pearl	SRT, Premium A36S, Silver Line A30R	—	—	AC30S	Premium C36S, Silver Line C24R	—
Pferd	A 24 R SG	A 24 Q SG-RAIL	A 24 Q SG-RAIL	AC 24 Q SG	C 24 R SG	—
Sait	A24R, A30S, XFC	Brute	Hobo	Ductile	C24R	Big M.A.C, XFC
Tyrolit	A30P, A30BF	—	—	AC24, AC30BF	1C24, C30BF	—
Virginia Abrasives	Metal	—	—	Ductile	Concrete	Asphalt
Walter	A-24	—	—	—	—	—

AVAILABILITY

TIER:
BRAND:
TRADENAME:
SHAPE:
ABRASIVE:
REINFORCING:
MATERIAL:

GOOD	GOOD	GOOD	GOOD	GOOD
Norton	Norton	Norton	Norton	Norton
GEMINI METAL HD	GEMINI METAL	GEMINI METAL DECKING	RAIL STEEL	GEMINI RESCUE
Type 01	Type 01	Type 01	Type 01	Type 01
Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
3 Layers	2 Layers	2 Layers	2 Layers	2 Layers

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
Type 01 Cut-off – for Gas & Electric-Powered Saws							
12 x 1/8 x 1" / 20mm	6,300	10	66252836708	66252837838			
14 x 1/8 x 1" / 20mm	5,400	10	66252835386	66252837841			66243578262
14 x 1/8 x 1"	5,400	10				66253260462	
14 x 5/32 x 1" / 20mm	5,400	10			66252832521		
16 x 1/8 x 1" / 20mm	4,800	10		66252830886			
16 x 1/8 x 1"	4,800	10				66253259935	

AVAILABILITY

TIER:
BRAND:
TRADENAME:
SHAPE:
ABRASIVE:
REINFORCING:
MATERIAL:

GOOD	GOOD	GOOD	GOOD	GOOD
Norton	Norton	Norton	Norton	Norton
GEMINI DUCTILE HD	GEMINI DUCTILE	GEMINI CONCRETE HD	GEMINI CONCRETE	GEMINI ASPHALT
Type 01	Type 01	Type 01	Type 01	Type 01
Silicon Carbide / Aluminum Oxide Blend	Silicon Carbide / Aluminum Oxide Blend	Silicon Carbide	Silicon Carbide	Silicon Carbide
3 Layers	2 Layers	3 Layers	2 Layers	2 Layers

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
Type 01 Cut-off – for Gas & Electric-Powered Saws							
12 x 1/8 x 1" / 20mm	6,300	10		66252837840	66252836709	66252837839	70184670243
14 x 1/8 x 1" / 20mm	5,400	10	66252835388	66252837843	66252835387	66252837842	70184672877
16 x 1/8 x 1" / 20mm	4,800	10				70184623029	



CATEGORY DEFINITION

These powerful, self-propelled machines are designed to cut concrete slabs and asphalt and are normally fitted with diamond blades. For inexperienced operators or small jobs, the machines can accommodate these low initial cost, conventional abrasives wheels.

APPLICATIONS:	Cutting straight sections of concrete surfaces
SIZE RANGE:	14" and 18" diameter
THICKNESS RANGE:	3/16" – 3/8"
ABRASIVE GRAIN:	Silicon Carbide
BOND:	Hot Pressed (HP) – for higher-horsepower machine applications where additional durability is needed, may be used wet or dry Cold Pressed (CP) – for lower-horsepower machines, which need a free-cutting wheel
SHAPE:	Type 01 Straight
ARBOR:	All are 1" with a drive pin

CROSS REFERENCE GUIDE

NORTON

Abmast
Bullard Blaze & Road Warrior
Camel
Flexovit
Husqvarna
Pearl
Pferd
Sait
Tyrolit
Virginia Abrasives
Walter

SPECIALTY		
BETTER Gemini Asphalt / Green Concrete – HP	GOOD Gemini Asphalt - CP	GOOD Gemini Concrete - CP
—	C 16 T. Kompetitor Asphalt/Concrete	C 24 R
—	C16R & T, C16R3	—
—	C16-U	C24-R
HPC16AG	C16 G.P. C16UB	C20SB/C16TB
Red GC-7A	Black EWC	Gold RTC, Blue RTC, Blue EWC
—	—	Premium C36S, Silver Line C24R
—	C 24 R SG ASP	C 24 R SG GP
Street Runner	C16	C24R, Street Walker
Concrete/Asphalt CHP	Asphalt CP	Concrete CP
—	GC/Asphalt	Concrete
—	—	C-24

AVAILABILITY

TIER:
BRAND:
TRADENAME:
SHAPE:
ABRASIVE:
BOND:
MATERIAL:

BETTER	GOOD	GOOD
Norton	Norton	Norton
GEMINI ASPHALT - HP	GEMINI ASPHALT - CP	GEMINI CONCRETE - CP
Type 01	Type 01	Type 01
Silicon Carbide	Silicon Carbide	Silicon Carbide
Hot Pressed	Cold Pressed	Cold Pressed

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #
Type 01 Cut-off – For Walk-Behind Saws					
14 x 3/16 x 1 Pin Hole	4,365	10	70184670100	70184680324	70184680323
14 x 1/4 x 1 Pin Hole	4,365	5	70184670099	70184670535	70184670533
18 x 1/4 x 1 Pin Hole	4,250	5	70184670103	70184670098	
18 x 3/8 x 1 Pin Hole	4,250	5	70184648998		



For higher-production applications, optimum speed of cut and product life, please see our complete selection of walk-behind diamond blades in our Diamond, Abrasives and Equipment for the Construction Market Catalog #7719 found on www.nortonconstructionproducts.com.



CATEGORY DEFINITION

A chop saw is a light, low-horsepower portable machine. Although very similar to a compound miter saw, it is designed for cutting denser materials, like metal bar, tubing or pipe. Chop saw cut-off wheels are designed specifically for this machine with finer grit, softer grades, and reinforcement layers that match the application.

APPLICATIONS:	Cutting small-diameter metal pieces, bar stock, metal pipe, tubing, decking, cable, drywall studs, and metal plate dimensioning
SIZE RANGE:	10" - 16" diameter
THICKNESS RANGE:	7/64"
ABRASIVE GRAIN:	Zirconia Alumina/Aluminum Oxide Blend, Aluminum Oxide, Silicon Carbide
SHAPE:	Type 01 Straight
REINFORCEMENT TYPE:	Side reinforced, centrally reinforced

CROSS REFERENCE GUIDE

	TOTAL PERFORMANCE			INITIAL PRICE			SPECIALTY		
NORTON	BETTER BlueFire Free Cut	BlueFire Rapid Cut	BlueFire Long Life	GOOD Gemini Free Cut	Gemini Rapid Cut	Gemini Long Life	GOOD Stud Cutter	Gemini Aluminum	Masonry
Brilliant	—	—	—	Super-G	Tube/Pipe	—	Drywall Stud	Aluminum	—
Bullard	ZA36T	—	—	TA36T A46T The Competitor	A36R The Competitor	A36R Ironmaster	A46T Studmaster	AL36R	—
Camel	—	—	ZA24-S	A36-P, WA36-P	—	A36-S	A30-R Mr. Stud	A30-N	—
Dewalt	—	—	XP	GP, Stainless Fabrication	—	—	Stud Cutting	—	—
Flexovit	—	—	—	A30R Fast Cut A30-Q Free Cut	—	A30S Long Life	A30T Drywall Stud	—	—
Makita	—	—	—	—	General Purpose	—	—	—	—
Pearl	SRT36	—	—	A36P Premium	A30P Silver Line	—	A46S Stud Cutting	—	—
Pferd	—	—	—	A 36 K SG CHOP	PSF CHOP	—	A 36 K SG-STUD	—	C 36 K SG-CHOP
Sait	Saitech Steel Worker	Z-tech	—	EZ-Chop	EZ-Chop Attacker	Iron Worker	Stud King	Aluminum	—
Walter	—	—	—	—	A-30	A-30-HC+	—	A30-ALU	—

APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE


WHEEL TYPE/REINFORCEMENT

TYPE 01 STRAIGHT SIDE REINFORCED CUT-OFF WHEEL



Side reinforced wheels have two full layers of reinforcing and are designed for a fast cut and the most aggressive applications. All Purpose, Free Cut, and Long Life are side reinforced.

TYPE 01 STRAIGHT CENTRALLY REINFORCED CUT-OFF WHEEL



Centrally reinforced wheels have a single layer of reinforcing with exposed rough sides for free-cutting, non-binding applications where minimal burr and burn are the key requirements. Rapid Cut wheels are centrally reinforced.

HOW TO PICK THE RIGHT BOND TYPE

All Purpose	Unmarked	Where an excellent blend of cut rate and life is needed
Free Cut	FC	Used when fast, burn-free cutting is desired or when cutting pieces with larger cross sections
Long Life	LL	Where durability is needed due to severe application, and when cutting parts with small cross sections
Rapid Cut	RC	Where a free cutting, non-binding wheel is needed for burn-free and burr-free cuts
High-Performance	STUD	High-performance aluminum oxide/resin bond combination designed for cleaner cuts and longer life when cutting steel studs
Aluminum	ALU	Specially formulated bond for reduced loading/surface contamination when cutting aluminum/soft materials



FEATURED PRODUCTS



NORTON BLUEFIRE CHOP SAW REINFORCED CUT-OFF WHEELS

BETTER CHOICE FOR STEEL, STAINLESS STEEL AND ALL OTHER FERROUS METALS

FEATURES

- Durable zirconia alumina / premium aluminum oxide abrasive blend
- Free Cut: side reinforced
- Long Life: side reinforced
- Rapid Cut: centrally reinforced, rough sides

BENEFITS

- 2X the life and cut rate of aluminum oxide
- Engineered for larger cross-sections and/or hard-to-cut materials
- Ideal for small cross-section workpieces
- Free cutting, non-binding; burr- and burn-free cuts



NORTON GEMINI CHOP SAW REINFORCED CUT-OFF WHEELS

GOOD CHOICE FOR ALL STEEL AND FERROUS METALS AS WELL AS SPECIALTY APPLICATIONS IN ALUMINUM

FEATURES

- Free Cut: side reinforced
- Long Life: side reinforced
- Rapid Cut: centrally reinforced, rough sides
- Aluminum: specially formulated bond for aluminum and other soft, nonferrous metals; no wax or rubber fillers

BENEFITS

- Engineered for larger cross-sections and/or hard-to-cut materials
- Ideal for small cross-section workpieces
- Free cutting, non-binding; burr- and burn-free cuts
- Free cutting; resist loading
- No surface contamination



NORTON METAL STUD CUTTER CHOP SAW REINFORCED CUT-OFF WHEELS

GOOD CHOICE FOR DRYWALL STUDS

FEATURES

- Stud Cutter: thin, side-reinforced; with high-performance aluminum oxide abrasive

BENEFITS

- Designed specifically for cutting steel studs



NEW

NORTON DIALAST DIAMOND CHOP SAW REINFORCED CUT-OFF WHEELS

DESIGNED FOR CUTTING STEEL, METAL STUDS, STAINLESS STEEL, NONFERROUS MATERIALS, TILE, BRICK, PLASTIC AND MUCH MORE

FEATURES

- A combination of high-quality diamond and advanced brazed single-layer bonding technology
- Environmentally friendly grinding
- Engineered with sound-dampening technology

BENEFITS

- Extra-long life vs. conventional abrasives or other vacuum-brazed diamond tools
- Retains the diamond grains and wheel shape for full life with low spark, while keeping a continuous grinding depth
- Less blade changes reduce downtime and labor costs
- Generate minimal dust
- Makes the blade environmentally-friendly when cutting indoors or out



AVAILABILITY

									
TIER:			BEST	BETTER	BETTER	GOOD	GOOD	GOOD	GOOD
TRADENAME:			NORTON DIALAST	NORTON BLUEFIRE	NORTON BLUEFIRE	NORTON GEMINI	NORTON GEMINI	NORTON METAL	NORTON MASONRY
SHAPE:			Type 01	Type 01	Type 01	Type 01	Type 01	Type 01	Type 01
ABRASIVE:			Diamond	Zirconia Alumina/ Aluminum Oxide	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Silicon Carbide
REINFORCING:				Side	Central	Side	Central	Side	Side
MATERIAL:				STAINLESS	STAINLESS	STAINLESS	STAINLESS	STAINLESS	
			STAINLESS	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL	STEEL/METAL	MASONRY
SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #
Type 01 Straight Cut-off									
10 x 7/64 x 1	6,110	10				66253106109 LL			
12 x 7/64 x 1	5,095	10		66252843250		66253207554 LL	66253214561 RC		
	5,095	5						07660789400	
14 x 3/32 x 1	4,365	10				66253306627 FC	66253313588 RC	66252835554	
	4,365	10				66253306626 LL		07660789405 STUD	
	4,365	5						07660789399	
14 x 7/64 x 1	4,365	10		66252843252 FC	66252843254 RC				
	4,365	10		66252843253 LL					
	4,365	25							
	4,365	10				66253314816 ALU		07660703970 5 Pk	07660789402
14 x .155 x 1	5,400	1	70184694053						
16 x 3/32 x 1	3,820	10				66253410198 LL			
16 x 7/64 x 1	3,820	10		66252843256 FC					
	3,820	10		66252843257 LL					

CUT-OFF WHEEL DESCRIPTION CODES

BLANK = ALL PURPOSE	ALU = ALUMINUM	FC = FREE CUT	LL = LONG LIFE	RC = RAPID CUT	STUD = STUD CUTTER
■ = MASONRY	■ = STAINLESS	■ = STEEL / METAL			





The Norton stationary saw reinforced cut-off wheel line consists of Type O1 straight 10" - 24" wheels, designed to fit on fixed-base stationary saws that are free-standing or mounted on a workbench.

APPLICATIONS: Primary applications are cutting of all metal parts (flat stock, bars, studs, pipes, tubes, angle iron, cable), wire rope and hydraulic hose used in fabrication, construction and plant maintenance.

SIZE RANGE: 10" – 20" diameter

THICKNESS RANGE: 3/32", 1/8", 5/32", 3/16"

ABRASIVE GRAIN: Zirconia Alumina/Aluminium Oxide Blend, Aluminum Oxide, Silicon Carbide

SHAPE: Type 01 Straight

TOTAL PERFORMANCE

INITIAL PRICE

SPECIALTY

NORTON	BETTER BlueFire	GOOD			GOOD	
	Gemini <i>Free Cut</i>	Gemini <i>Long Life</i>	Gemini <i>Rapid Cut*</i>	Norton <i>Masonry</i>		
Abmast	Z 24 R3	A 30 R	—	—	—	AC 24 R3
Brilliant	—	GP Fast Cut	GPX Long Life	XL , XLX	—	—
Bullard	—	A30-R	A30-T	A300	C20R	—
Camel	ZA24-R	A24-R, A46-T	—	—	C24-R	WA24-S
Flexovit	—	A30RB Multi Purpose	A30SB Long Life, A24TB Long Life	—	C24RB	AC24PB Heavy Duty
Metabo	—	A30N, A30R	A30S, A30V	—	C30S	—
Pearl	SRT36	A30P Premium, A30Q Silver Line	A30S Premium, A36R Premium	—	C24 Silver Line	—
Pferd	ZA 24 Q/R SG-HD	A 24 N/P SG-HD	A 24 Q/S SG-HD	—	C 24 0 SG	—
Sait	—	A24N, A36R	A24R	—	C24R	—
Tyrolit	—	A30BF	—	—	C30BF	—
Walter	—	A-24-FC	A-24-RIP	—	—	—


* FOR BURR-FREE APPLICATIONS, PLEASE SEE CENTRALLY-REINFORCED BLUEFIRE RAPID CUT AND GEMINI RAPID CUT WHEELS IN CHOP SAW CUT-OFF WHEEL SECTION OR AT WWW.NORTONABRASIVES.COM

** FOR FOUNDRY AND OTHER PRODUCTION CUT-OFF WHEELS, PLEASE REFER TO THAT SECTION OF THIS NORTON FULL LINE CATALOG #7362 OR AT WWW.NORTONABRASIVES.COM

AVAILABILITY

				
TIER:	BETTER	GOOD	GOOD	GOOD
TRADENAME:	NORTON BLUEFIRE	NORTON GEMINI FREE CUT	NORTON GEMINI LONG LIFE	NORTON MASONRY
SHAPE:	Type 01	Type 01	Type 01	Type 01
ABRASIVE:	Zirconia Alumina/ Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Silicon Carbide
MATERIAL:	STAINLESS	STAINLESS	STAINLESS	
	STEEL/METAL	STEEL/METAL	STEEL/METAL	MASONRY
STD. PKG.	PART #	PART #	PART #	PART #
10	66252843248	66253106101 <i>FC</i>	66253106102 <i>LL</i>	
5				07660789391
10	66252843249		66253207548 <i>LL</i>	
5				07660789350
10	66252843251	66253306609 <i>FC</i>	66253306611 <i>LL</i>	
5				07660789353
10		66253422942		70184623029
10	66252843255	66253410183 <i>FC</i>	66253410184 <i>LL</i>	
10		66253410185 <i>FC</i>		
5	66252843258 <i>FC</i>	69078609031 <i>FC</i>	69078609032 <i>LL</i>	
5	66252843259 <i>LL</i>			
5		69078609033 <i>FC</i>	69078609034 <i>LL</i>	

BLANK = ALL PURPOSE **FC** = FREE CUT **LL** = LONG LIFE = STAINLESS = STEEL / METAL = MASONRY



CATEGORY DEFINITION

For consistent, quality performance in foundries, welding shops, fabrication facilities, steel mills and shipyards, Norton snagging wheels maximize your productivity. Used on horizontal/straight shaft grinders or right angle cup portable grinders.

APPLICATIONS:	Removing flaws, cracks, gates, risers and parting lines, smoothing weld seams, cleaning castings, and rough beveling
SIZE RANGE:	Type 01 Straight Wheels: 2-1/2" – 8" diameter Type 06 and 11 Cup Wheels: 4" – 6" diameter Cones and Plugs: Type 16, 17, 17R, 18 and 18R
GRIT RANGE:	14 – 24
ABRASIVE TYPES:	Zirconia Alumina NZ and NV; Zirconia Alumina/Silicon Carbide Blend NVC; Aluminum Oxide 57A and Metal; Aluminum Oxide/Silicon Carbide Blend 57AC, Silicon Carbide 37C

MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

		BEST HIGHEST PRODUCTIVITY LOWEST TOTAL COST	BETTER EXCELLENT BLEND OF PERFORMANCE & PRICE	GOOD CONSISTENT PERFORMANCE LOW INITIAL PRICE
Iron	Gray Ductile/Malleable Dirty/Scale-covered	NorZon Plus NZ14-R NorZon Plus NZ14-R	BlueFire NV16-Q BlueFire NV16-Q BlueFire NVC16-Q	Gemini 57A16-Q, Metal Gemini 57A16-Q, Metal Gemini 57AC16-Q
Steel	Carbon and Low Alloy Stainless and High Alloy	NorZon Plus NZ16-Q NorZon Plus NZ16-P	BlueFire NV16-Q BlueFire NV16-Q	Gemini 57A16-Q, Metal Gemini 57A16-Q, Metal
Aluminum, Copper, Brass, & Bronze Alloys			BlueFire NVC16-Q	Gemini 57AC16-Q

NOTE: GRADE, GRIT AND ABRASIVE TUNING MAY BE NECESSARY TO OBTAIN OPTIMUM PERFORMANCE

CROSS REFERENCE GUIDE FOR TYPE 01, 06 AND 11

	TOTAL PERFORMANCE			INITIAL PRICE		
NORTON	BEST NorZon Plus NZ	BETTER BlueFire NV	BlueFire NVC	GOOD Gemini 57A	Gemini 57AC	Gemini 37C
Brilliant	—	ZA16QB	—	A16QB	—	C16QB
Bullard	—	ZA16PB	—	A16R	AC16	C16P
Camel	—	—	—	A	CA	C
Flexovit	ZA16PB	—	—	A16QB	AC16QB	C16PB
Gulf States	Zirconium	—	—	A16	—	C16
Pacific	Z, Z-GPC	—	—	A	CA	—
Pearl	—	—	—	A16Q	—	C16-Q
Pferd	ZA 16 Q SG	—	—	A 16 Q SG	—	C 16 Q SG
Sait	—	Z16	—	A16, 20	CA16	C16
Tyrolit	—	—	—	A16PB	—	C16PB
Walter	—	—	—	A	—	C

FEATURED PRODUCTS



NORTON NORZON PLUS WHEELS, CONES AND PLUGS

BEST CHOICE FOR HEAVY-DUTY STOCK REMOVAL ON HIGH-HORSEPOWER GRINDERS

FEATURES

- NZ Plus (NorZon) – premium zirconia alumina grain

BENEFITS

- Engineered for high-powered machines 10X life, 50% faster grinding versus aluminum oxide products



NORTON BLUEFIRE SNAGGING WHEELS, CONES AND PLUGS



BETTER CHOICE FOR STOCK REMOVAL ON HIGH- AND MEDIUM-HORSEPOWER GRINDERS

FEATURES

- More friable zirconia alumina grain and durable resin bond technologies
- NVC – zirconia alumina/silicon carbide blend

BENEFITS

- Higher metal removal rates, faster, freer-cutting than standard zirconia alumina blends
- Up to 5X the life of aluminum oxide products; better grinding action
- Highly effective on dirty, scale-covered castings



FEATURED PRODUCTS



VENDIBLE

NORTON GEMINI

GOOD CHOICE FOR STEEL AND FERROUS METALS AS WELL AS SPECIALTY APPLICATIONS IN ALUMINUM AND FOUNDRIES

FEATURES

- Quality aluminum oxide

BENEFITS

- Consistent performance at a competitive price



NEW

NORTON METAL/MASONRY

GOOD CHOICE FOR STEEL/FERROUS METAL AND MASONRY APPLICATIONS WITH LOW INITIAL PRICE

FEATURES

- Aluminum oxide abrasive
- Low initial price point

BENEFITS

- Engineered for all steel/ferrous materials
- Best starting specification for end user unable to measure performance

AVAILABILITY

TIER:
TRADENAME:
SHAPE:
ABRASIVE:



BEST

NORTON NORZON PLUS

Type 01

Zirconia Alumina



BETTER

NORTON BLUEFIRE

Type 01

Zirconia Alumina NV
Zirconia Alumina/Silicon Carbide NVC



GOOD

NORTON GEMINI

Type 01

Aluminum Oxide 57A, Silicon Carbide 37C,
Aluminum Oxide/Silicon Carbide 57AC

SIZE (D x T x H)	MAX. RPM	STD. PKG.	SPEC	PART #	SPEC	PART #	SPEC	PART #
Type 01 Straight								
2-1/2 x 1/2 x 3/8	21,700	20					57A24-R	66243522381
3 x 1/4 x 3/8	20,370	25			NV20-T	66253343872**	57A24-T	66243528831
3 x 3/8 x 3/8	18,080	10					57A24-R	66243522415
3 x 1/2 x 3/8	18,080	10					57A24-P	66243522417
4 x 1/4 x 3/8	15,280	10			NV20-T	66253344098	57A24-R	66243522221
6 x 1 x 5/8	8,000	5	NZ14-Q	66252838075	NV14-R	66253198589	57A16-QS	66252809563
S Webs	8,000	5	NZ14-R	66252837961				
8 x 3/4 x 5/8	6,000	10			NV14-S	66253344347		
S Webs								
8 x 1 x 5/8	6,000	5	NZ16-Q	66253030778	NV16-Q	66253198590		
S Webs	6,000	5	NZ16-Q	66253044532				
	6,000	10			NV14-R	66253 344355		
	6,000	10			NV14-T	66253344365		
	6,000	10			NVC16-Q	66253198592		
Type 06 Straight Cup								
6 x 2 x 5/8-11	6,000	5	NZ16-R	66252838577				
Rim 2" Back 3/4"								
Type 11 Flaring Cup								
4/3 x 2 x 5/8-11	9,070	10	NZ16-Q	66243530761	NV16-Q	66253198583	57A16-Q	66243510512
Rim 3/4" Back 3/4"								
5/3-3/4 x 2 x 5/8-11	7,260	5			NV16-Q	66253146918	57A16-Q	66252809598
Rim 1" Back 3/4"								
6/4-3/4 x 2 x 5/8-11	6,000	5	NZ16-Q	66252838568	NV16-Q	66253146925	57A16-Q	66252825201
Rim 1" Back 3/4"	6,000	5	NZ16-R	66252838566				
6/4-3/4 x 2 x 5/8-11	6,000	5	NZ16-P	66252830765	NV16-Q	66253198584	37C16-P	66252809609
Rim 1-1/2" Back 3/4"	6,000	5			NVC16-Q	66253146922	57A16-Q	66252809618
	6,000	5					57AC16-Q	66252809608
Type 11 Flaring Cup with Steel Back								
4/3 x 2 x 5/8-11	9,070	10			NV16-Q	66253146917		
Rim 3/4" Back 3/4"								
5/3-13/16 x 2 x 5/8-11	7,260	10			NV16-Q	66253146920		
Rim 1" Back 3/4"								
6/4-13/16 x 2 x 5/8-11	6,000	5			NV14-R	66253344373	57A16-Q	66252809599
Rim 1-1/2" Back 3/4"	6,000	5			NV16-Q	66253198586	57AC16-Q	66252809600
	6,000	5			NVC16-Q	66253146929		

** STD. PKG. = 50

BEST	BETTER	GOOD	GOOD
--	--	--	---

GOOD
NORTON METAL
Aluminum Oxide

V = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES & SMALL JOBS.

GOOD
NORTON
Silicon Carbide

NORTON




CATEGORY DEFINITION

The Norton bench and pedestal wheel line consists of all wheel diameters and arbor sizes, abrasive types and grit sizes. Our offering answers all metal removal, deburring, shaping and sharpening needs: white aluminum oxide for high-speed tool steels, brown aluminum oxide for carbon steel, and silicon carbide for non-ferrous metals and carbide tooling.

APPLICATIONS:	Offhand deburring and sharpening of parts and tools
SIZE RANGE:	5" – 18"
GRIT RANGE:	24 – 150
ABRASIVE TYPES:	Aluminum Oxide (Alundum), Silicon Carbide (Crystolon)
BUSHINGS:	Telescopic arbor bushings to fit all popular grinders are packaged with the wheel

APPLICATION/GRIT RECOMMENDATION GUIDE



FEATURED PRODUCTS



PREMIUM WHITE ALUMINUM OXIDE

BETTER CHOICE FOR LIGHT METAL REMOVAL AND SHARPENING OF HIGH-SPEED TOOL STEELS (55 RC AND HIGHER)

FEATURES

- White aluminum oxide in a premium vitrified bond

BENEFITS

- Maximum cut rate and cool grinding action on hardened or high-speed tool steels



NORTON GEMINI ALUMINUM OXIDE

GOOD CHOICE FOR ALL GENERAL-PURPOSE BENCH AND PEDESTAL APPLICATIONS

FEATURES

- Quality, brown aluminum oxide

BENEFITS

- Economical prices; ideal for small job shops and numerous general-purpose applications



NORTON GEMINI SILICON CARBIDE

GOOD CHOICE FOR ALL GENERAL-PURPOSE BENCH AND PEDESTAL APPLICATIONS ON NONFERROUS MATERIALS AND CARBIDE TOOLING

FEATURES

- Sharp, green silicon carbide

BENEFITS

- Economical prices; ideal for small job shops and numerous general-purpose applications

TECHtip

- Unsecured machines can move, causing grinding breakage and injury. Fixed-based bench and pedestal grinders MUST be secured.
- Do not grind wood, plastic, or any other non-metallic material on a bench or pedestal grinder.
- All bench and pedestal wheels must be dressed to prevent loading. Loading can cause excessive heat, damage to the workpiece, and wheel breakage. Dressing exposes new cutting edges and provides chip clearance.
- Recommended starting dressing stick: 1 x 1 x 6 37C24-SVK Part # 61463610462.



It is the user's responsibility to refer to and comply with ANSI B7.1



AVAILABILITY

**BETTER**

Norton

TIER:
BRAND:
TRADENAME:
ABRASIVE:

PREMIUM ALUNDUM

White Aluminum Oxide

**GOOD**

Norton

GEMINI ALUNDUM

Brown Aluminum Oxide

**BETTER**

Norton

GEMINI CRYSTOLON

Green Silicon Carbide

SIZE (D x T x H)	MAX. RPM	MIN./STD. PKG.	SPEC	PART #	MIN./STD. PKG.	SPEC	PART #	MIN./STD. PKG.	SPEC	PART #
5 x 1/2 x 1	4,965				1/5	Medium 60/80	07660788202			
	4,965				1/5	Fine 100/120	07660788201			
5 x 3/4 x 1	4,965				1/5	Coarse 36/46	07660788215			
	4,965				1/5	Medium 60/80	07660788210			
	4,965				1/5	Fine 100/120	07660788205			
5 x 1 x 1	4,965				1/5	Coarse 36/46	07660788230			
	4,965				1/5	Medium 60/80	07660788225			
6 x 1/2 x 1	4,140				1/5	Coarse 36/46	66252836132	1/5	Medium 60	66252836571
	4,140				1/5	Medium 60/80	66252836131	1/5	Fine 80	66252836572
	4,140				1/5	Fine 100/120	66252836133	1/5	Extra Fine 120	66252836573
6 x 3/4 x 1	4,140	1/5	Medium 60	07660788246	1/5	Coarse 36/46	07660788245	1/5	Medium 60	66252837190
	4,140	1/5	Fine 100	07660788247	1/5	Medium 60/80	07660788240	1/5	Fine 80	66252837191
	4,140	1/5	Very Fine 150	07660788248	1/5	Fine 100/120	07660788235	1/5	Extra Fine 120	66252837192
6 x 1 x 1	4,140	1/5	Medium 60	07660788261	1/5	Coarse 36/46	07660788260	1/5	Medium 60	66252837187
	4,140	1/5	Fine 100	07660788262	1/5	Medium 60/80	07660788255	1/5	Fine 80	66252837193
	4,140	1/5	Very Fine 150	07660788263	1/5	Fine 100/120	07660788250	1/5	Extra Fine 120	66252837194
7 x 1 x 1	3,600				1/5	Coarse 36/46	07660788275	1/5	Medium 60	66252942300
	3,600				1/5	Medium 60/80	07660788270	1/5	Fine 80	66252942301
	3,600				1/5	Fine 100/120	07660788265	1/5	Extra Fine 120	66252942302
8 x 3/4 x 1	3,600				1/5	Coarse 36/46	07660788278			
	3,600				1/5	Medium 60/80	07660788277			
	3,600				1/5	Fine 100/120	66253042317			
8 x 1 x 1	3,600	1/5	Medium 60	07660788281	1/5	Very Coarse 24	66253044454	1/5	Medium 60	66253044087
	3,600	1/5	Fine 100	07660788282	1/5	Coarse 36/46	07660788286	1/5	Fine 80	66253044534
	3,600	1/5	Very Fine 150	07660788283	1/5	Medium 60/80	07660788285	1/5	Extra Fine 120	66253044535
	3,600				1/5	Fine 100/120	07660788280			
10 x 1 x 1-1/4	2,485				1/2	Very Coarse 24	66253160788	1/2	Medium 60	66253144536
	2,485				1/2	Coarse 36/46	07660788295	1/2	Fine 80	66253160366
	2,485				1/2	Medium 60/80	07660788290			
	2,485				1/2	Fine 100/120	66253160350			
10 x 1-1/4 x 1-1/4	2,485				1/2	Coarse 36/46	66253161250			
	2,485				1/2	Medium 60/80	66253161251			
10 x 1-1/2 x 1-1/4	2,485				1/2	Coarse 36/46	66253161393			
	2,485				1/2	Medium 60/80	66253161395			
12 x 1-1/2 x 1-1/2	2,070				1/2	Coarse 36/46	66253263052			
	2,070				1/2	Medium 60/80	66253263053			
12 x 2 x 1-1/4	2,070							1/2	Medium 60	66253263359
	2,070							1/2	Fine 80	66253263360
12 x 2 x 1-1/2	2,070				1/2	Very Coarse 24	66253263054			
	2,070				1/2	Coarse 36/46	66253263055			
	2,070				1/2	Medium 60/80	66253263056			

Bench and Pedestal Wheel Arbor Bushings

WHEEL DIAMETER	WHEEL CENTER HOLE	1/2"	5/8"	3/4"	7/8"	1"	1-1/4"
5", 6", 7"	1"	•	•	•	•		
8"	1"		•	•	•		
10"	1-1/4"			•	•	•	
12" x 2"	1-1/4"					•	
12" and 14"	1-1/2"					•	•

THESE SIZE BUSHINGS SHIPPED FREE OF CHARGE WITH YOUR WHEEL ORDER.



CATEGORY DEFINITION

Resin bond, vitrified bond, center lap, and cotton fiber mounted points are available in a wide range of shapes.

INDUSTRIES:

Aerospace
Tool and Die
Construction
Metal Fabrication
Automotive
Cutlery
Mold Shops
Stainless Steel Equipment
Foundries



ABRASIVE GRAIN:

Ceramic Alumina, Zirconia Alumina, Zirconia Alumina/Aluminum Oxide Blend, Aluminum Oxide, Silicon Carbide

SHAPE AVAILABILITY:

A, B, and W

MEASUREMENT GUIDE



DESCRIPTION OF OVERHANG

Overhang is the distance between the grinder chuck and the abrasive on the spindle. The larger the overhang, the lower the maximum safe operating speed.

SIZE

Measured by diameter (D) x thickness (T)

FEATURED PRODUCTS

COTTON FIBER MOUNTED POINTS
GOOD FOR BLENDING AND POLISHING

FEATURES

- 80 grit
- 120 grit

BENEFITS

- For most materials
- For polishing and stainless steel applications


AVAILABILITY

TIER:	GOOD
BRAND:	Norton
TRADENAME:	COTTON FIBER
ABRASIVE:	Aluminum Oxide

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #
Cotton Fiber Mounted Points						
A11	7/8 x 2	1/4	19,860	5/25	A80-HBF3	61463622664
B52	3/8 x 3/4	1/8	45,370	5/25	A120-HBF3	61463620242
B121	1/2" Ball	1/8	45,370	5/25	A80-HBF3	61463622657
W163	1/4 x 1/2	1/8	60,000	5/25	A80-HBF3	61463622655
			60,000	5/25	A120-HBF3	61463622656
W176	3/8 x 1/2	1/8	45,370	5/25	A80-HBF3	61463622654
W185	1/2 x 1/2	1/8	34,500	5/25	A80-HBF3	61463622649
W187	1/2 x 1	1/8	20,620	5/25	A80-HBF3	61463622651
W220	1 x 1	1/4	25,500	5/25	A80-HBF3	61463622646

† SPINDLE LENGTH IS 1-1/2"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG



W SHAPES

**CENTER LAP MOUNTED POINTS**

FOR EXCELL-O CENTER LAP AND SIMILAR MACHINES

FEATURES

- Specially formulated wheel treatment (#5 wood resin)
- Larger diameter spindle
- Precise dimensional tolerances

BENEFITS

- Adds lubricity to the wheel, minimizing risk of metallurgical damage
- Minimum deflection, rigid support
- Ensure accurate location of part centers

AVAILABILITY

TIER:	BETTER
BRAND:	Norton
TRADENAME:	CENTER LAP
ABRASIVE:	Aluminum Oxide

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #
Center Lap Mounted Points						
—	1/2 x 2**	1/2	65,000	5/25	A80-VVM	61463621421
—	1 x 2**	1/2	15,900	5/25	A80-VVM	61463622926

** POINTED 60°

† SPINDLE LENGTH IS 1-1/4"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG

TECHtip

Dress the center lap mounted points frequently to ensure accurate and smooth center holes.



It is the user's responsibility to refer to and comply with ANSI B7.1

**NORTON NORZON – RESIN BOND MOUNTED POINTS**

BEST CHOICE FOR FAST STOCK REMOVAL

FEATURES

- NZ (NorZon) zirconia alumina self-sharpening abrasive and durable organic bond

BENEFITS

- 2X faster stock removal than competitive aluminum oxide products
- Last 4X longer



VENDIBLE

NORTON CHARGER – RESIN BOND MOUNTED POINTS

BETTER CHOICE FOR FAST STOCK REMOVAL AND LONG LIFE

FEATURES

- Zirconia alumina/aluminum oxide abrasive blend
- Specially formulated organic bond
- NEW! Charger mounted point pre-packed in small packages

BENEFITS

- 35% faster cut rate than standard aluminum oxide
- An aggressive, free cut
- More parts cleaned in less time to substantially increase productivity
- 2X greater life than ordinary aluminum oxide
- Reduces vibration and wheel chatter
- Ideal for vending machines, pegboards, small jobs, and carrying to job site

AVAILABILITY


TIER:	BEST	BETTER
BRAND:	Norton	Norton
TRADENAME:	NORZON	CHARGER
ABRASIVE:	Zirconia Alumina	Zirconia Alumina/Aluminum Oxide

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #	SPEC	PART #
Resin Bond Mounted Points								
A1	3/4 x 2-1/2	1/4	19,800	5/25	NZ24-UBXR1	61463616457	Charger	61463616458
			19,800	4 ✓			Charger	66253325922
A3	1 x 2-3/4	1/4	16,100	5/25	NZ24-UBXR1	61463616459	Charger	61463616460
			16,100	2 ✓			Charger	66253325924
A5	3/4 x 1-1/8	1/4	45,000	5/25			Charger	61463616462
			45,000	5 ✓			Charger	66253325926
A11	7/8 x 2	1/4	19,860	5/25	NZ24-UBXR1	61463616463	Charger	61463616464
W189	1/2 x 2	1/4	24,000	5/25	NZ24-UBXR1	61463616465	Charger	61463616466
			24,000	5 ✓			Charger	66253325928
W197	5/8 x 2	1/4	21,000	5/25	NZ24-UBXR1	61463616467		
W207	3/4 x 1-1/2	1/4	24,000	5/25			Charger	61463616470
W208	3/4 x 2	1/4	18,750	5/25	NZ24-UBXR1	61463616471	Charger	61463616472
W220	1 x 1	1/4	25,500	5/25	NZ24-UBXR1	61463617520	Charger	61463617521
			25,500	5 ✓			Charger	66253325930
W221	1 x 1-1/2	1/4	19,120	5/25	NZ24-UBXR1	61463616473	Charger	61463616474
W222	1 x 2	1/4	15,900	5/25	NZ24-UBXR1	61463616475	Charger	61463616476

† SPINDLE LENGTH IS 1-1/2"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG

✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES AND SMALL JOBS. MIN. PKG. QTY = NUMBER OF MOUNTED POINTS PER VENDIBLE PACK. ORDER IN MULTIPLES OF MIN QTY.



**NORTON QUANTUM – VITRIFIED BOND MOUNTED POINTS**

BEST CHOICE FOR HIGH VOLUME OPERATIONS

FEATURES

- Unique, engineered ceramic grain shape and chemistry with proven bond technology

BENEFITS

- Ideal for high-volume foundry operations – grinding Inconel and similar alloy turbine blade components
- Minimal loading and heat build-up
- 33% + longer life versus competitive ceramic products
- 30% + higher metal removal rates
- Versatile, optimized for all low-, medium- and high-force applications
- Exceptional productivity and life

- Oil and Gas 36 grit mounted points

- Specifically engineered to efficiently grind the carbide matrix material of oilfield drill heads

**NORTON GEMINI – VITRIFIED BOND MOUNTED POINTS**

GOOD VALUE FOR GENERAL PURPOSE, SMALL JOB SHOP APPLICATIONS

FEATURES

- 38A abrasive
- Diverse shapes and sizes

BENEFITS

- Cool cutting, less burn
- Ideal when initial price is the main purchasing consideration


AVAILABILITY

TIER:	BEST	GOOD
BRAND:	Norton	Norton
TRADENAME:	QUANTUM	GEMINI
ABRASIVE:	Ceramic Alumina	38A

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #	SPEC	PART #
Vitrified Bond Mounted Points – A Shapes								
A1	3/4 x 2-1/2	1/4	19,800	25/250	Oil & Gas 36	61463686139		
A1	3/4 x 2-1/2	1/4	19,800	5/25	3NQ80	69083149139	38A36-T	61463624374
A1	3/4 x 2-1/2	1/4	19,800	5/25			38A60-P	61463624375
A3	1 x 2-3/4	1/4	16,100	25/250	Oil & Gas 36	61463686138		
A3	1 x 2-3/4	1/4	16,100	5/25	3NQ80	69083160166	38A36-T	61463624377
A3	1 x 2-3/4	1/4	16,100	5/25			38A60-P	61463624378
A4	1-1/4 x 1-1/4	1/4	30,560	5/25			38A60-P	61463624380
A5	3/4 x 1-1/8	1/4	45,000	5/25	3NQ80	69083149140	38A36-T	61463624381
A5	3/4 x 1-1/8	1/4	45,000	5/25			38A60-P	61463624382
A11	7/8 x 2	1/4	19,860	5/25	3NQ80	69083149141	38A36-T	61463624384
A11	7/8 x 2	1/4	19,860	5/25			38A60-P	61463624385
A12	11/16 x 1-1/4	1/4	48,000	5/25	3NQ60	61463677679	38A60-P	61463624388
A13	1-1/8 x 1-1/8	1/4	33,950	5/25			38A60-P	61463624389
A14	11/16 x 7/8	1/4	55,560	5/25			38A60-P	61463624390
A15	1/4 x 1-1/16	1/4	72,750	5/25			38A60-P	61463624391
A21	1 x 1	1/4	34,500	5/25	3NQ80	69083149144	38A60-P	61463624392
A23	3/4 x 1	1/4	39,370	5/25	3NQ80	69083149143	38A60-P	61463624394
A24	1/4 x 3/4	1/4	76,500	5/25			38A60-P	61463624395
A25	1" Ball	1/4	35,620	5/25	3NQ80	61463677680	38A60-P	61463624396
A26	5/8" Ball	1/4	61,120	5/25	3NQ80	69083149145	38A60-P	61463624397
A31	1-3/8 x 1	1/4	27,780	5/25			38A60-P	61463624399
A34	1-1/2 x 3/8	1/4	25,470	5/25			38A60-P	61463624402
A36	1-5/8 x 3/8	1/4	23,520	25/250	Oil & Gas 36	66253145562		
A36	1-5/8 x 3/8	1/4	23,520	5/25	3NQ80	69083149146	38A60-P	61463624404
A37	1-1/4 x 1/4	1/4	30,560	5/25			38A60-P	61463624405
A38	1 x 1	1/4	34,500	5/25	3NQ80	61463677682	38A60-P	61463624406
A39	3/4 x 3/4	1/4	47,250	5/25	3NQ80	69083149147	38A60-P	61463624407
A40	3/4" Ball	1/4	47,250	5/25			38A60-P	61463624408

† STANDARD SPINDLE SIZE IS 1/4" X 1-1/2"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG











AVAILABILITY

TIER:	BEST	GOOD
BRAND:	Norton	Norton
TRADENAME:	QUANTUM	GEMINI
ABRASIVE:	Ceramic Alumina	38A

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #	SPEC	PART #
Vitrified Bond Mounted Points – B Shapes								
B41	5/8 x 5/8	1/8	33,570	5/25			38A60-P	61463624410
B42	1/2 x 3/4	1/8	33,570	5/25	3NQ80	69083149045	38A60-P	61463624412
B43	1/4 x 5/16	1/8	81,370	5/25			38A60-P	61463624413
B44	7/32 x 3/8	1/8	68,400	5/25			38A60-P	61463624414
B45	3/16 x 5/16	1/8	104,250	5/25			38A60-P	61463624415
B46	1/8 x 5/16	1/8	105,000	5/25			38A60-P	61463624416
B51	7/16 x 3/4	1/8	45,370	5/25			38A60-P	61463624418
B52	3/8 x 3/4	1/8	45,370	5/25	3NQ80	69083149046	38A60-P	61463624420
B52	3/8 x 3/4	1/4	81,000	5/25			38A60-P	61463624419
B52	3/8 x 3/4	1/8	45,370	5/25			38A90-Q	61463624422
B53	5/16 x 5/8	1/8	60,000	5/25			38A60-P	61463624423
B54	1/4 x 1/2	1/8	60,000	5/25			38A60-P	61463624424
B55	1/8 x 1/4	1/8	105,000	5/25			38A60-P	61463624425
B81	3/4 x 3/16	1/8	50,930	5/25			38A60-P	61463624437
B91	1/2 x 5/8	1/8	34,500	5/25			38A60-P	61463624443
B96	1/8 x 1/4	1/8	105,000	5/25			38A60-P	61463624448
B96	1/8 x 1/4	1/8	105,000	5/25			38A90-Q	61463624449
B97	1/8 x 3/8	1/8	105,000	5/25	3NQ80	69083149048	38A60-P	61463624451
B98	3/32 x 1/4	1/8	105,000	5/25			38A60-P	61463624452
B121	1/2" Ball	1/8	45,370	5/25			38A60-P	61463624466
B122	3/8" Ball	1/8	61,650	5/25	3NQ80	69083149050	38A60-P	61463624470
B122	3/8" Ball	1/8	61,650	5/25			38A90-Q	61463624471
B123	3/16" Ball	1/8	104,250	5/25			38A60-P	61463624472
B124	1/8" Ball	1/8	105,000	5/25			38A90-Q	61463624474
B131	1/2 x 1/2	1/8	34,500	5/25	3NQ80	69083149049	38A60-P	61463624475
B132	3/8 x 1/2	1/8	45,370	5/25			38A60-P	61463624479
B133	3/8 x 3/8	1/8	54,000	5/25			38A60-P	61463624481
B134	5/16 x 3/8	1/8	61,650	5/25			38A60-P	61463624482
B135	1/4 x 1/2	1/8	60,000	5/25			38A60-P	61463624484
B136	1/4 x 5/16	1/8	77,250	5/25			38A60-P	61463624485

† STANDARD SPINDLE SIZE IS 1/8" OR 1/4" X 1-1/2"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG





AVAILABILITY

TIER:	BEST	GOOD
BRAND:	Norton	Norton
TRADENAME:	QUANTUM	GEMINI
ABRASIVE:	Ceramic Alumina	38A

SHAPE	SIZE (D x T)	SPINDLE DIA.†	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #	SPEC	PART #
Vitrified Bond Mounted Points – W Shapes								
W144	1/8 x 1/4	1/8	105,000	5/25			38A60-P	61463624488
W145	1/8 x 3/8	1/8	105,000	5/25			38A60-P	61463624489
W146	1/8 x 1/2	1/8	105,000	5/25			38A60-P	61463624491
W152	3/16 x 1/4	1/8	105,000	5/25			38A60-P	61463624495
W153	3/16 x 3/8	1/8	80,850	5/25			38A60-P	61463624496
W154	3/16 x 1/2	1/8	70,500	5/25	3NQ80	69083149133	38A60-P	61463624497
W160	1/4 x 1/4	1/8	81,370	5/25			38A60-P	61463624501
W162	1/4 x 3/8	1/8	64,800	5/25			38A60-P	61463624503
W163	1/4 x 1/2	1/8	60,000	5/25			38A60-P	61463624504
W164	1/4 x 3/4	1/8	45,900	5/25	3NQ80	69083149135	38A60-P	61463624505
W170	5/16 x 1/2	1/8	52,500	5/25			38A60-P	61463624511
W175	3/8 x 3/8	1/8	54,000	5/25			38A60-P	61463624516
W176	3/8 x 1/2	1/8	45,370	5/25			38A60-P	61463624517
W177	3/8 x 3/4	1/8	33,750	5/25			38A60-P	61463624518
W179	3/8 x 1-1/4	1/8	20,415	25/250	Oil & Gas 36	69083154055		
W185	1/2 x 1/2	1/8	34,500	5/25	3NQ80	69083149137	38A60-P	61463624525
W185	1/2 x 1/2	1/4	61,500	5/25			38A60-P	61463624526
W186	1/2 x 3/4	1/4	51,000	5/25			38A60-P	61463624528
W188	1/2 x 1-1/2	1/4	30,370	5/25			38A60-P	61463624530
W189	1/2 x 2	1/4	24,000	25/250	Oil & Gas 36	61463686137		
W189	1/2 x 2	1/4	24,000	5/25	3NQ80	61463677683	38A60-P	61463624531
W196	5/8 x 1	1/4	35,250	5/25			38A60-P	61463624539
W200	3/4 x 1/8	1/8	50,930	5/25			38A60-P	61463624543
W200	3/4 x 1/8	1/8	50,930	5/25			38A90-Q	61463624544
W204	3/4 x 3/4	1/4	42,750	5/25			38A60-P	61463624549
W205	3/4 x 1	1/4	34,500	5/25			38A60-P	61463624550
W208	3/4 x 2	1/4	18,750	5/25	3NQ80	61463677684	38A60-P	61463624553
W215	1 x 1/8	1/8	38,200	5/25	3NQ80	69083149138	38A60-P	61463624560
W216	1 x 1/4	1/4	38,200	5/25			38A60-P	61463624562
W218	1 x 1/2	1/4	38,200	25/250	Oil & Gas 36	69083154061		
W218	1 x 1/2	1/4	38,200	5/25			38A60-P	61463624564
W220	1 x 1	1/4	25,500	5/25	3NQ80	61463677685	38A60-P	61463624566
W221	1 x 1-1/2	1/4	19,120	5/25			38A60-P	61463624567
W222	1 x 2	1/4	15,900	5/25			38A60-P	61463624569
W230	1-1/4 x 1-1/4	1/4	20,400	5/25			38A60-P	61463624578
W235	1-1/2 x 1/4	1/4	25,470	5/25			38A60-P	61463624583
W236	1-1/2 x 1/2	1/4	25,470	5/25	3NQ80	61463677686	38A60-P	61463624585
W237	1-1/2 x 1	1/4	22,500	5/25			38A60-P	61463624587
W238	1-1/2 x 1-1/2	1/4	15,600	5/25			38A60-P	61463624588
W242	2 x 1	1/4	19,100	5/25	3NQ80	69083149148	38A60-P	61463624592

† STANDARD SPINDLE SIZE IS 1/8" OR 1/4" X 1-1/2"

* MAXIMUM OPERATING SPEED BASED ON 1/2" OVERHANG

W SHAPES

TECHtip

- For best mounted point performance, always run the mounted point at the maximum allowable speed according to ANSI B7.1. Refer to the speed chart included in each shipment for proper operating speeds.
- Use "A" shapes for medium- to heavy-duty blending.
- Use "B" shapes for light deburring and finishing/polishing.
- Use "W" shapes for offhand and precision grinding of medium to heavy stock.
- Use 36 grit and coarser for rough grinding.
- Use 60 and 90 grits for imparting fine finishes or when grinding on narrow surfaces.

! It is the user's responsibility to refer to and comply with ANSI B7.1

50-Piece Mounted Point Kits

- Each kit contains 5 each of 10 of our best selling mounted point shapes and specifications
- The 1/4" spindle kits contain "A"-shaped points that are ideal for general maintenance and metalworking applications
- The 1/8" spindle kits contain "B"-shaped points for light deburring machine parts or finishing/polishing dies
- The "W"-shaped points in all of these kits work well for precision grinding of medium to heavy stock

TIER:	BEST	GOOD
BRAND:	Norton	Norton
TRADE NAME:	QUANTUM	GEMINI

SHAPE	SPINDLE DIA.†	MIN./STD. PKG.	PART #	PART #
Mounted Point Kits				
Assorted	1/4	1	50 piece Premium Norton Quantum 1/4" Spindle Mounted Point Kit contains 5 each of Norton Quantum A1, A5, A11, A21, A23, A26, A36, A39, W242, and A80-HBF3 W220	69083147810
Assorted	1/8	1	50 piece Premium Norton Quantum 1/8" Spindle Mounted Point Kit contains 5 each of Norton Quantum B42, B52, B97, B122, B131, W154, W164, W185, W215, and A80-HBF3 W163	69083147806
Assorted	1/4	1	50 piece Norton Gemini 1/4" Spindle Mounted Point Kit contains 5 each of 38A60-P A1, A5, A11, A21, A23, A26, A36, A39, W242, and A80-HBF3 W220	69083147789
Assorted	1/8	1	50 piece Norton Gemini 1/8" Spindle Mounted Point Kit contains 5 each of 38A60-P B42, B52, B97, B122, B131, W154, W164, W185, W215, and A80-HBF3 W163	69083147669

† STANDARD SPINDLE SIZE IS 1/8" OR 1/4" X 1-1/2"



CATEGORY DEFINITION

Hard silicon carbide rubbing bricks are used for heavy-duty applications such as rubbing floors, cleaning and scouring castings, rubbing down concrete, and removing mold marks.

APPLICATIONS:

Floor Rubbing Bricks – are used to rub down concrete and remove mold marks. These are designed to fit the chucks of common concrete floor grinding equipment. Reusable wooden wedges anchor the bricks to the equipment chucks.

Plain Hand Rubbing Bricks – are the choice of mechanics and foundry workers for dressing grinding wheels and cleaning or scouring castings.

Fluted Hand Rubbing Bricks – are used by masons and stone workers for rubbing down concrete and removing mold marks. The diagonal flutes provide sharp edges, a clean shearing action, and carry away debris.

Fluted Hand Rubbing Bricks with Handle – make quick work of removing mold marks and rubbing down concrete. The firmly attached handle reduces fatigue and facilitates overhead, wall, and floor work.

GRIT RANGE:

6 – 120

ABRASIVE TYPE:

Silicon Carbide



SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PART #
Plain Floor Rubbing Bricks with Wooden Wedges					
4 x 2 x 2	1	6	C6-R	Silicon Carbide	61463653292
	1	6	C10-R	Silicon Carbide	61463653293
	1	6	C24-R	Silicon Carbide	61463653294
	1	6	C80-R	Silicon Carbide	61463653295

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PART #
Griddle Brick					
4-1/2 x 3 x 2	1	5	Medium	Alundum	61463687870

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PART #
Floor Rubbing Brick with Center Score					
8 x 2 x 2	1	6	C120-R*	Silicon Carbide	61463685296*
*8" BRICK HAS A CENTER SCORE TO FACILITATE DIVIDING THE BRICK IN HALF – AN ECONOMICAL ALTERNATIVE TO BUYING TWO 4" BRICKS.					

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	PART #
Wooden Wedges			
6	6		61463685297

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PRODUCT #	PART #
Plain Hand Rubbing Bricks						
8 x 2 x 2	1	5	C24	Silicon Carbide	BP28	61463687830

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PRODUCT #	PART #
Fluted Hand Rubbing Bricks						
6 x 2 x 2	1	5	C20	Silicon Carbide	BF26	61463687840
8 x 2 x 2	1	5	C20	Silicon Carbide	BF28	61463687845

SIZE (L x W x H)	QTY./ PKG.	QTY./ CASE	SPEC.	ABRASIVE	PRODUCT #	PART #
Fluted Hand Rubbing Bricks with Handle						
6 x 3 x 1	1	5	C20	Silicon Carbide	BFH6	61463687800
8 x 3-1/2 x 1-1/2	1	5	C20	Silicon Carbide	235	61463687795



Retail Packaged Sharpening Products

Our retail-packaged line brings Norton quality to your distributor showroom, vending machine, tool crib, and your tool box. Each stone is specifically designed for a popular sharpening application and packaged to sell or carry to the job site.



AVAILABILITY

TIER:

BETTER

SIZE (L x W x H)	SPEC.	QTY./CASE	PART #
Axe and Hatchet Sharpener			
3 x 5/8 round	Coarse/Fine Crystolon (Silicon Carbide)	10	07660785316
Pocket Knife Sharpener			
3 x 7/8 x 3/8	Fine Crystolon (Silicon Carbide)	5	07660787600
3 x 7/8 x 3/8 with case	Medium India (Aluminum Oxide)	5	07660787937
3 x 1-1/2 x 1/2 with case	Coarse/Fine India (Aluminum Oxide)	5	07660787630
Economy Tool & Knife Benchstone			
6 x 2 x 3/4	Coarse/Fine Crystolon (Silicon Carbide)	5	07660787933
8 x 2 x 3/4	Coarse/Fine India (Aluminum Oxide)	10	07660787934
8 x 2 x 1	Coarse/Fine India (Aluminum Oxide)	10	61463685755
High Quality Tool & Knife Benchstone			
6 x 2 x 3/4	Coarse/Fine Crystolon (Silicon Carbide)	5	07660787935
Chisel & Planer Blade Sharpener			
8 x 2 x 3/4	Coarse/Fine India (Aluminum Oxide)	10	07660787936
Household Knife & Tool Sharpener			
7-1/2	Fine Crystolon (Silicon Carbide)	5	07660787939
Farm Tool Sharpener			
10 x 1-1/4 x 3/4	Coarse Crystolon (Silicon Carbide)	10	07660787730
Lawn & Garden Tool Sharpener			
9-1/2 x 1-3/8 x 1/2	Medium Crystolon (Silicon Carbide)	10	07660787938
Sharpening Stone Oil			
4-1/2 oz.	Oil	5	07660787940
Sharpening Steel			
1/2 x 10	Round file with rubber handle	8	66253240433



Knife and Scissor Sharpener

The knife and scissor mechanical sharpener is a quick and portable tool for hundreds of sharpening applications.


SPECIFICATION	QTY./CASE	PART #
Knife and Scissor Sharpener		
Carbide	6	07660787520

Norton Professional Sharpening Products and Dressing Sticks

See the "Norton Professional Sharpening Products and Dressing Sticks Catalog #200" on www.nortonstones.com to view the complete list and descriptions of our many sharpening products.



Bulk Sharpening Products



Stackable Diamond Benchstones


Made in the USA, these benchstones have unique stackable, non-skid rubber feet designed to keep the diamond plate steady while you sharpen, and efficiently stacked for space-saving storage when not in use. The simple grit-size color-coding makes them easy to differentiate: 220 (red), 325 (blue), 600 (green), and 2 sizes: 6" and 8". The flat diamond surface is plated onto a nickel-coated steel bar precision ground to a tolerance of .0001" which provides excellent sharpening performance across entire surface of stone. Faster and 100X the life of regular abrasives, stackable diamond benchstones provide quick, exceptional sharpening.

AVAILABILITY

TIER: **BETTER**
BRAND: Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PART #
Stackable Diamond Benchstones			
6 x 2 x 1/4	D220	5	66253268082
	D325	5	66253268081
	D600	5	66253268080
8 x 2 x 1	D220	5	66253268087
	D325	5	66253268086
	D600	5	66253268083

6" STONES COME RETAIL PACKAGED



India (Aluminum Oxide) Benchstones

Smooth cutting aluminum oxide abrasive provides a long-lasting cutting edge. Our best product for a fine finish, these stones are the choice of artisans, craftsmen, and mechanics. Ideal for clean deburring, generating keen edges, and quality finishes. Available in single grit and combination grit.

AVAILABILITY

TIER: **BETTER**
BRAND: Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PRODUCT #	PART #
India (Aluminum Oxide) Single Grit Benchstones				
4 x 1 x 1/4	Coarse	5	CB14	61463685580
	Medium	5	MB14	61463685575
	Fine	5	FB14	61463685570
	Fine	5 ✓	FB14-V	66253325919
4 x 1 x 1/2	Coarse	5	CB24	61463685595
	Medium	5	MB24	61463685590
	Fine	5	FB24	61463685585
5 x 2 x 5/8	Medium	5	MB35	61463685605
	Fine	5	FB35	61463685600
6 x 2 x 1	Coarse	5	CB6	61463685620
	Medium	5	MB6	61463685615
	Fine	5	FB6	61463685610
8 x 2 x 1	Coarse	5	CB8	61463685635
	Medium	5	MB8	61463685630
	Fine	5	FB8	61463685625
8 x 3 x 1/2	Coarse	5 ✓	CB83-V	61463654462*
	Medium	5 ✓	MB83-V	61463654461*
	Fine	5 ✓	FB83-V	61463654460*
11-1/2 x 2-1/2 x 1/2	Coarse	1	IM6	61463654214#
	Medium	1	IM9	61463685970#
India (Aluminum Oxide) Combination Grit Benchstones				
4 x 1 Round	Coarse/Fine	5	IB64	61463685545
4 x 1-3/4 x 5/8	Coarse/Fine	5	IB134	61463685550
5 x 2 x 3/4	Coarse/Fine	5	IB45	61463685555
6 x 2 x 1	Coarse/Fine with Anniversary Box	5	IB6	61463685560
8 x 2 x 1	Coarse/Fine with Anniversary Box	5	IB8	61463685565
11-1/2 x 2-1/2 x 1	Coarse/Fine	2	IM2	61463685851


✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES, SMALL JOBS, AND CARRYING TO JOB SITE. PRE-PACKED IN STURDY BOXES OF 5 PER PACK. ORDER BY TOTAL NUMBER OF STONES NEEDED; NOT BY QUANTITY OF PACKS.

* MAY BE USED AS REPLACEMENT STONE FOR IM-83 SHARPENING SYSTEM.

MAY BE USED AS REPLACEMENT STONE FOR IM-313 SHARPENING STONE SYSTEM.



Bulk Sharpening Products CONTINUED

**Crystolon (Silicon Carbide) Benchstones**

Premium silicon carbide abrasive produces a fast cutting stone, ideal for general sharpening of cutting tools. Fast stock removal for quick edge shaping with minimal loading when the speed of sharpening is more important than the fineness of the cutting edges.

AVAILABILITY

TIER:

BETTER

BRAND:

Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PRODUCT #	PART #
Crystolon (Silicon Carbide) Combination Grit Benchstones				
4 x 1 Round	Coarse/Fine	5	JB64	61463685435
4 x 1-3/4 x 5/8	Coarse/Fine	5	JB134	61463685440
5 x 2 x 3/4	Coarse/Fine	5	JB45	61463685445
6 x 2 x 1	Coarse/Fine	5	JB6	61463685450
8 x 2 x 1	Coarse/Fine	5	JB8	61463685455
11-1/2 x 2-1/2 x 1	Coarse/Fine	2	JUM3	61463685840
12 x 2-1/2 x 1-1/2	Coarse/Fine	2	JUM4	61463685855

**Arkansas Benchstones**

Arkansas benchstones are made of natural premium Novaculite quarried in Arkansas. Used for finer honing after India stone, Arkansas benchstones create the sharpest possible razor edges and near mirror finishes. White in color; they may contain shades of red, yellow and gray.

AVAILABILITY

TIER:

BETTER

BRAND:

Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PRODUCT #	PART #
Arkansas Single Grit Benchstones				
4 x 2 x 3/4-1	Extra Fine Soft Arkansas	5	SB4	61463685670
6 x 2 x 3/4-1	Extra Fine Soft Arkansas	5	SB6	61463685675
8 x 2 x 3/4-1	Extra Fine Soft Arkansas	5	SB8	61463685680
4 x 2 x 3/4-1	Ultra Fine Hard Arkansas	5	HB4	61463685655
6 x 2 x 3/4-1	Ultra Fine Hard Arkansas	5	HB6	61463685660
8 x 2 x 3/4-1	Ultra Fine Hard Arkansas	5	HB8	61463685665
8 x 3 x 1/2	Ultra Fine Hard Arkansas	5 ✓	HTB83-V	61463654464*

✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES, SMALL JOBS, AND CARRYING TO JOB SITE. PRE-PACKED IN STURDY BOXES OF 5 PER PACK. ORDER BY TOTAL NUMBER OF STONES NEEDED; NOT BY QUANTITY OF PACKS.

* MAY BE USED AS REPLACEMENT STONE FOR IM-83 SHARPENING SYSTEM.

**Sharpening Stone Oil**

Norton Oil is a highly refined lubricating oil specially formulated for sharpening stone use. It will not load or "gum-up" sharpening stones, and is equally ideal for all lubricating jobs. Meets U.S. Pharmacopoeia standards for mineral oil purity, and may be used around food preparation operations.

AVAILABILITY


TIER:

BETTER

BRAND:

Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PRODUCT #	PART #
Norton Oil				
4-1/2 oz.	Oil	20	XB1	61463687760
1 Pint	Oil	20	XB5	61463687770
1 Quart	Oil	5	XB2	61463687775

**Tradesmen's Stone and Utility File**

Tradesmen's Utility Stones are used for sharpening trimming knives and as abrasive files in many different industries. Both have wooden handles.

The Norton Utility File is a long wedge-shaped stone with four flat sides designed for sharpening coarse cutting edges on cutting implements and edged garden tools. Wooden handle makes it easy to use. It will out-last out-sharpen metal files.

AVAILABILITY

TIER:

BETTER

BRAND:


Norton

SIZE (L X W X H)	SPECIFICATION	QTY./ CASE	PRODUCT #	PART #
Tradesmen's Utility Stones – Crystolon (Silicon Carbide)				
14-3/4 including handle	Coarse/Fine	10	JT930	61463687675
14-3/4 including handle	Medium	10	JT920	61463687670
Utility File – Crystolon (Silicon Carbide)				
14 including handle	Coarse	10	JD2	61463687750



the brightest product solutions from **A TOTAL SPECTRUM OF INNOVATION**

For everything from heavy-to-medium stock removal, to fine finishing, to light blending and polishing, coated abrasive products are available in unique abrasive grains, specialty coatings and backing configurations to meet many application needs.



Blaze Your Way to Greater Productivity

The latest-generation, cooler cutting ceramic abrasive grain of Norton Blaze delivers highest productivity on the toughest jobs without the added operator pressure or heavy tool.



Performance On Fire

Infused with a proprietary NorZon grain upgrade, Norton BlueFire products enhance performance in faster removal rate, longer product life and smoother finish. True Blue, Reinvented.



Power Up Affordable Versatility

The proprietary grain technology and improved resin bond in our Norton Neon products deliver up to 3X the life and cut rate at an economical initial price.



CATEGORY DEFINITION

The most heavy-duty of coated abrasive discs with resin over resin construction on heavy-duty vulcanized fiber backing. Designed for applications ranging from heavy stock removal to surface blending. Used with back-up pads on portable angle grinders.


APPLICATIONS:	Stock removal, edge chamfering, weld blending, deburring/deflashing, rust removal, cleaning and finishing
SIZE RANGE:	4" x 5/8" hole, 4-1/2" – 9-1/8" x 7/8" hole
GRIT RANGE:	16 – 120
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, and Aluminum Oxide
PRODUCT OPTIONS:	Speed-Change hubs (5/8-11"), AVOS technology
ACCESSORIES:	Air-cooled, smooth-faced, and AVOS back-up pads

MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity – Lowest Total Cost	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Low Initial Price
Stainless Steel / Titanium / Super Alloys*	Norton Blaze F980	Norton BlueFire F826P	Norton Neon F726
Mild Carbon Steel / Welds	Norton Red Heat F981	Norton BlueFire F826P	Norton Neon F726
Ferrous Metals / Cast Iron	Norton Red Heat F981	Norton BlueFire F826P	Norton Neon F726
Brass / Bronze / Aluminum	—	—	Norton Neon F726

*NICKEL/COBALT BASED – HASTELLOY, INCONEL, Waspalloy

APPLICATION/GRIT RECOMMENDATION GUIDE



CROSS REFERENCE GUIDE

	TOTAL PERFORMANCE		INITIAL PRICE	
	BEST		BETTER	GOOD
NORTON	Blaze F980	Red Heat F981	BlueFire F826P	Neon F726 Metal
3M	985C, 982C	988C, 983C	785C	501C
Camel	—	—	Ceramic Blend	—
Flexovit	—	—	Flexon CG	Flexon
GemTex	—	—	X, PMD	—
Hermes	CB844X	CB444X/J	—	RB414X/J
Klingspor	CS661	—	—	CS570
Metabo	—	—	—	—
Mirka	—	—	—	Blue A/Z
Pearl	—	—	—	Gold A/Z
Pferd	CO Cool	CO	CO-PMD	Z Cool
Sait	9S	8S	—	3Z
SIA	—	4515	—	4815
Standard	—	—	Ceramic	—
VSM	XF870	XF750	ZF844	ZF713, ZF714
Walter	—	—	—	Topcut, Inox
Weiler	—	—	—	Zirconium



FEATURED PRODUCTS

**NORTON BLAZE F980**

BEST CHOICE FOR STAINLESS STEEL, TITANIUM, AND SUPER ALLOYS

FEATURES

- Micro-fracturing ceramic alumina grain
- 100% ceramic alumina grain
- Self-lubricating, advanced supersize treatment
- Improved resin bond system
- Extra heavy-duty backing on 50 grit and coarser
- Foil-packed availability

BENEFITS

- Constantly exposing sharper grain edges and improved grain life
- Significant cut rate and life over competitive blended/low-ratio ceramic alumina discs
- Minimizes heat, loading and glazing on stainless, titanium and super alloys
- Improved grain retention for longer life
- Increased life and durability
- Improved humidity and prevention against curl
- Fully recyclable for reduced landfill waste



NEW

NORTON RED HEAT F981 AND F981S

BEST CHOICE/HIGHEST PRODUCTIVITY FOR MILD CARBON STEEL (F981), STAINLESS (F981S), AND FERROUS METALS

FEATURES

- Premium, self-sharpening full-ratio ceramic abrasive grain
- F981: durable, long lasting
- F981S: supersized grinding aid

BENEFITS

- Faster initial cut rate, longer life and improved finishes versus competitive ceramic discs
- Great performance to price ratio
- Excellent starting specifications when the performance of ceramic is needed
- Excellent performance on carbon steel
- Minimizes heat and loading on stainless and aluminum



VENDIBLE

NORTON BLUEFIRE F826P

BETTER CHOICE FOR STAINLESS, SUPER ALLOYS, STEEL, CAST IRON AND HIGH-PRESSURE APPLICATIONS

FEATURES

- High-performance blend of ceramic alumina and zirconia alumina abrasive
- NEW! Vendible 10-disc package

BENEFITS

- 15% faster cut and longer life with less power draw
- Broad utility on a wide range of materials
- Ideal for vending machines, small jobs, or carrying to a job site



NEW

VENDIBLE

NORTON NEON F726

GOOD CHOICE FOR CARBON STEEL AND ALUMINUM APPLICATIONS

FEATURES

- Proprietary blend of aluminum oxide/ceramic grain
- Upgrade from former Norton Metalite F226 discs at a low initial price
- NEW! Vendible 10-disc package

BENEFITS

- Delivers up to 3X the life and cut rate at an economical price point
- Improved resin bond system and heavy-duty fiber backing extend grain adhesion
- Ideal for vending machines, small jobs, or carrying to a job site



NEW

NORTON METAL F240

GOOD STARTING SPECIFICATION FOR ALL METALS

FEATURES

- High-performance aluminum oxide

BENEFITS

- Low initial price with consistent performance



AVAILABILITY

TIER:
BRAND:
TRADENAME:

			
BEST	BEST	BEST	BETTER
Norton	Norton	Norton	Norton
BLAZE F980	RED HEAT F981	RED HEAT F981S	BLUEFIRE F826P
Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina/ Zirconia Alumina Blend

OTHER:

SIZE (D x H)	GRIT	STD. PKG.	PART #	PART #	PART #	STD. PKG.	PART #
4-1/2 x 7/8	24	25	69957398000	77696008400	77696008462	25	66261138457
	36	25	69957398001	77696008401	77696008465	25	66261138456
	36					50 ✓	66623377276
	50	25	69957398002	77696008402	77696008466	25	66261138454
	50					50 ✓	66623377277
	60	25	69957398003	77696008403	77696008467	25	66261138453
						50 ✓	66623377278
	80	25	69957398004	77696008404	77696008470	25	66261138452
	80					50 ✓	66623377279
	100	25		77696008405			
	120	25	66254425332	77696008406			
5 x 7/8	24	25	69957398005	77696008407	77696008480	25	66261138563
	24	50#	66254464822				
	36	25	69957398006	77696008412	77696008481	25	66261138562
	36	50#	66254464821			50 ✓	66623377283
	50	25	69957398007	77696008413	77696008482	50 ✓	66623377284
	50	25				25	66261138561
	50	50#	66254464820				
	60	25	69957398008	77696008414	77696008483	25	66261138601
	60					50 ✓	66623377285
	80					50 ✓	66623377286
	80	25	69957398009	77696008422	77696008484	25	66261138600
	100	25		77696008423			
7 x 7/8	120	25	66254409084	77696008425			
	24	25	69957398010	77696010018	77696010006	25	66261138594
	36					50 ✓	66623377287
	36	25	69957398011	77696008429	77696010007	25	66261138593
	50					50 ✓	66623377289
	50	25	69957398012	77696008430	77696010008	25	66261138592
	60					50 ✓	66623377290
	60	25	69957398013	77696008431	77696010009	25	66261138591
	80					50 ✓	66623377291
	80	25	69957398014	77696008432	77696010011	25	66261138590
	100	25		77696008433			
	120	25	66254411528	77696008436			
9-1/8 x 7/8	24	25	69957398015	77696008437	77696010012	25	66261138584
	36	25	69957398016	77696008440	77696010013	25	66261138583
	50	25	69957398017	77696008444	77696010017	25	66261138582
	60	25		77696008449			
	80	25		77696008452			
	100	25		77696008453			

NOTE: FIBER DISCS MUST BE USED WITH BACK-UP PADS SHOWN ON THE LAST PAGE OF THIS SECTION.

SHRINK-WRAP FOIL PACK: 10 DISCS PER PACK, 5 PACKS PER STANDARD PACKAGE.

✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES & SMALL JOBS. 10 DISC PACKAGE, 5 PACKS PER CARTON. ORDER IN MULTIPLES OF 50.

The Perfect Product for Every Performance/Price Level

**NORTON BLAZE**

Latest generation ceramic alumina abrasive provides the industry's fastest cutting discs and 50-200% longer life on stainless, titanium, and super alloys.

**NORTON BLUEFIRE**

Durable ceramic/zirconia abrasive blend for an increased cut rate and longer life over conventional zirconia products on high pressure applications.


**NORTON NEON**

New aluminum oxide and ceramic blend provides the best starting specification (and performance) when initial price is the primary purchasing consideration.



AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
OTHER:

**GOOD**

Norton

NEON F726Aluminum Oxide/
Ceramic Alumina Blend**GOOD**

Norton


METAL F240

Aluminum Oxide

SIZE (D x H)	GRIT	STD. PKG.	PART #	STD. PKG.	PART #
4 x 5/8	24	50 ✓	66623395000	25	5539510595
	36	50 ✓	66623395001	25	5539510594
	50	50 ✓	66623395002	25	5539510593
	60	50 ✓	66623395003	25	5539510592
	80	50 ✓	66623395004	25	5539510591
	100	50 ✓	66623395005		
	120	50 ✓	66623395006		
4-1/2 x 7/8	24	50 ✓	66623395007	25	66623353309
	36	50 ✓	66623395008	25	66623353306
	50	50 ✓	66623395009	25	66623353310
	60	50 ✓	66623395010	25	66623353311
	80	50 ✓	66623395011	25	66623353312
	100	50 ✓	66623395012	25	66623353313
	120	50 ✓	66623395013	25	66623353314
5 x 7/8	16			25	05539510684
	24	50 ✓	66623395016	25	66623357276
	36	50 ✓	66623395017	25	66623357277
	50	50 ✓	66623395018	25	66623357278
	60	50 ✓	66623395019	25	66623357279
	80	50 ✓	66623395020	25	66623357280
	100	50 ✓	66623395021	25	66623357281
7 x 7/8	120	50 ✓	66623395022	25	66623357282
	16			25	05539510693
	24	50 ✓	66623395029	25	66623357283
	36	50 ✓	66623395030	25	66623357284
	50	50 ✓	66623395031	25	66623357285
	60	50 ✓	66623395032	25	66623357286
	80	50 ✓	66623395033	25	66623357287
9-1/8 x 7/8	100	50 ✓	66623395034	25	66623357288
	120	50 ✓	66623395035	25	66623357289
	24	50 ✓	66623395036	25	05539510702
	36	50 ✓	66623395037	25	05539510701
	50	50 ✓	66623395038	25	05539510700
	60	50 ✓	66623395039	25	05539510699
	80	50 ✓	66623395040		
	100	50 ✓	66623395041		
	120	50 ✓	66623395042	25	05539510695

NOTE: FIBER DISCS MUST BE USED WITH BACK-UP PADS SHOWN ON THE LAST PAGE OF THIS SECTION.

✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES & SMALL JOBS : 10 DISC PACKAGE, 5 PACKS PER CARTON. ORDER IN MULTIPLES OF 50.



Corner Store Convenience – Right on the Floor

Metal Fabrication Vending Solutions

See the many popular products conveniently pre-packed in small quantity packages

- Perfect for vending machines, pegboards, new test orders, small orders and jobs, and carrying cleanly to job site
- Pre-selected product assortment for optimal coverage of popular applications
- Available in fiber, flap, paper, and quick-change discs, belts, hand pads, depressed center, cut-off and bench wheels, mounted points, cones and plugs, and sharpening stones

Industry's best selection of vendible abrasive solutions



Speed-Change Fiber Discs

These fiber discs feature Norton quick, tool-free, twist-on and -off Speed-Change fasteners. Discs lock to standard back-up pads with a unique nut design and are easily removed, increasing your productivity with more time to grind.

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
OTHER:

BEST	BEST	BETTER	GOOD
Norton	Norton	Norton	Norton
BLAZE F980	RED HEAT F981	BLUEFIRE F826P	NEON F726
Ceramic Alumina	Ceramic Alumina	Ceramic Zirconia	Aluminum Oxide/ Ceramic Alumina
Supersize			
PART #	PART #	PART #	STD. PKG. PART #
66261023269	77696009735		10 77696009702
66261185294	77696009737		10 77696009703
	77696009739		10 77696009704
	77696009740		10 77696009712
	77696009741		10 77696009715
	77696009746		10 77696009716
	77696009747		10 77696009723
66254425336	77696009748	66261138797	10 77696009725
66261185801	77696009749	66261138796	10 66623395014
	77696009750		10 77696009727
	77696009752		10 66623395015
	77696009753		10 77696009728
	77696009754		
	77696009755		10 77696009729
69957349782	77696009759	66261138819	10 66623395023
66261029863	77696009760	66261138818	10 66623395024
	77696009761	66261138817	10 66623395025
	77696009762	66261138816	
	77696009767		10 66623395026
	77696009771		10 66623395027
	77696009772		10 66623395028



NOTE: SPEED CHANGE FIBER DISCS MUST ALWAYS BE USED WITH SMOOTH FACE BACK-UP PADS, SEE NEXT PAGE FOR DETAILS.

AVOS Fiber Discs

- Patented, see-through design allows interrupted cut which reduces heat up to 30% over standard discs
- The scooped holes create air flow to pull swarf away from grinding zone; cool cutting and extended product life
- 15° back-up pad for full utilization of discs – no gouging
- Quick, tool-free, twist-on and -off Speed-Lok fasteners

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:

		
BEST	BEST	BETTER
Norton	Norton	Norton
BLAZE F980	RED HEAT F981S	BLUEFIRE F826P
Ceramic Alumina	Ceramic Alumina	Ceramic Zirconia
PART #	PART #	PART #
66254468389	77696008454	66261129718
66254468390	77696008456	66261129719
66254468391	77696008457	66261129720
66254468392	77696008459	66261129721
66254468393	77696008460	66261129722
66254468385	77696008471	66261126556
66254468386	77696008474	66261126557
66254468387	77696008475	66261126558
66254468388	77696008477	66261126559
	77696008478	66261126560
66254468381	77696008485	66261137454
66254468382	77696010001	66261137455
66254468383	77696010002	66261137456
66254468384	77696010003	66261137457
	77696010005	66261137458

NOTE: AVOS FIBER DISCS MUST BE USED WITH AVOS SPEED-LOK BACK-UP PADS, SEE NEXT PAGE FOR DETAILS.





Fiber Disc Accessories



Air-Cooled Standard Back-up Pad

Slotted hub design and curved ribs draw heat away from the grinding zone, reducing disc loading and increasing life. All pads have a 5/8"-11 threaded female hub for mounting. We also offer a no-nose for shorter-shafted right angle grinders.



Smooth Face Speed-Change Back-up Pad

Molded rubber back-up pads with a smooth face.

- Hard density pads are for aggressive cutting action
- Medium density pads are for all-purpose applications



AVOS Fiber Discs

- Patented, see-through design allows interrupted cut which reduces heat up to 30% over standard discs
- The scooped holes create air flow to pull swarf away from grinding zone; cool cutting and extended product life
- 15° back-up pad for full utilization of discs – no gouging
- Quick, tool-free, twist-on and -off Speed-Lok fasteners

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Rubber Back-up Pads			
Air-Cooled Standard			
4" Medium	12,000	5	63642504918
4-1/2" Medium	11,000	5	63642502122
5" Medium	10,000	5	63642543421
7" Hard	8,600	5	63642543425
7" Medium	8,600	5	63642543422
9" Hard	6,600	5	63642543426
9" Medium	6,600	5	63642543423
NOTE: RETAINER NUTS ARE NOT INCLUDED WITH BACK-UP PADS. THESE MUST BE ORDERED SEPARATELY.			
Air-Cooled No-Nose			
4-1/2" Medium	11,000	5	63642504872
5" Medium	10,000	5	63642503000
7" Medium	8,600	5	66254487375
Smooth Face / Speed-Change			
4-1/2" Medium	20,000	5	66254492277
5" Medium	12,000	5	63642543235
7" Hard	8,600	5	63642543240
7" Medium	8,600	5	63642543245
9" Medium	7,000	5	63642543270
AVOS Speed-Lok Back-up Pads			
AVOS Triangular Speed-Lok Back-up Pads			
4-1/2" x 5/8-11	13,000	5	63642502985
5" x 3/8-24 Pistol Grip*	20,000	5	63642503029
5" x 5/8-11	13,000	5	63642502517
5" x 7/16-20 Pistol Grip*	20,000	5	63642503030
AVOS Round Speed-Lok Back-up Pads			
7" x 5/8-11 Medium	8,600	5	63642504874
*USE ON AIR PNEUMATIC AND HIGH-SPEED PISTOL GRIP SANDERS			
Tools			
#103 Retainer Nut	—	10	63642543463
Spanner Wrench	—	5	63642543005
66NS Short Retainer Nut	—	10	63642543461



CATEGORY DEFINITION

Flap discs are versatile grinding and finishing tools, consisting of three main components: a backing plate, adhesive, and abrasive cloth flaps. The rectangular flaps are overlapped and glued to the backing plate. Flap discs are designed for right angle grinder applications ranging from heavy stock removal to surface blending.

APPLICATIONS:	Grinding, stock removal, edge chamfering/beveling, weld blending, deburring/deflashing, rust removal, blending, cleaning and finishing
SIZE RANGE:	4": 5/8" hole 4-1/2" - 7": 5/8"-11 discard mount, 7/8" hole, and 2" - 3" quick-change
GRIT RANGE:	24 - 120
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide,
ABRASIVE FLAPS:	Polyester or cotton
FLAP DISC SHAPE:	Type 27 Flat and Type 29 Conical
ABRASIVE FLAP DENSITY:	Standard or high
BACKING PLATE MATERIAL:	Fiberglass and plastic

FLAP DISC SHAPES



GRIND AT FLATTER ANGLES:
0° - 15°

Type 27 Flat – The Best Choice for Finishing

- Used primarily on flat surfaces
- The best choice for blending and smooth finishing



GRIND AT STEEPER ANGLES:
15° - 25°

Type 29 Conical – The Best Choice for Aggressive Stock Removal

- Conical flap discs have angled flaps and may be used on both contoured and edge work
- The angle provides greater surface contact for stock removal on flat surfaces
- The best choice when speed and stock removal are primary considerations

ABRASIVE FLAP DENSITIES



Standard Density

- Excellent for heavy-duty applications and rapid stock removal




High Density

- Ideal when working on uneven or curved surfaces, as well as finer grit blending


BACKING PLATE MATERIALS

All flap discs are a combination of abrasive flaps adhered to a rigid backing plate. It is the backing plate that provides stability during operation. There are two main materials used: fiberglass and plastic. The fiberglass backing plate, along with the flap shape, helps to absorb vibration and is consumed during use with no smearing. Fiberglass is the most popular material because of its high strength and light weight. The plastic backing plate offers some additional conformability and is trimmable.





WHY CHOOSE FLAP DISCS?

Flap discs replace both grinding wheels and fiber discs. The same flap disc can be used for applications ranging from stock removal to blending.




Flap Discs vs. Grinding Wheels

- Faster stock removal
- Smoother finish, no gouging
- Cooler cutting, less glazing
- Lightweight, easier to control
- Less vibration, less operator fatigue
- Reduced noise



Flap Discs vs. Fiber Discs

- 20X longer life, reduced abrasive cost
- Fewer disc changes, reduced labor cost
- More consistent finish
- No back-up pad required
- Easier storage, no curling
- Reduced loading
- Use flap discs one grit size coarser than fiber discs, except in 36 grit.






MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity – Lowest Total Cost	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Lowest Total Cost
Type 29 for Stock Removal			
Stainless Steel / Titanium / Super Alloys	Norton Blaze R980P	Norton BlueFire R884P	Norton Neon R766
Mild Carbon Steel / Welds	Norton Red Heat R961	Norton BlueFire R884P	Norton Neon R766
Ferrous Metals / Cast Iron	Norton Red Heat R961	Norton BlueFire R884P	Norton Neon R766
Brass / Bronze / Aluminum	–	Norton BlueFire R884P	
Type 27 for Blending and Finishing			
Stainless Steel / Titanium / Super Alloys	Norton Blaze R980P	Norton BlueFire R884P	Norton Neon R766
Mild Carbon Steel / Welds	Norton Red Heat R961	Norton BlueFire R884P	Norton Neon R766
Ferrous Metals / Cast Iron	Norton Red Heat R961	Norton BlueFire R884P	Norton Neon R766
Brass / Bronze / Aluminum	–	Norton BlueFire R884P	Norton Neon R766

APPLICATION/GRIT RECOMMENDATION GUIDE



CROSS REFERENCE GUIDE

	TOTAL PERFORMANCE		INITIAL PRICE	
	BEST Blaze R980P	Red Heat R961	BETTER BlueFire R884P	GOOD Neon R766
NORTON				
3M	947D	747D	563D, 546D	–
DeWalt	–	–	–	Z/A
Camel	–	C3	Z-Stainless	Z3, A3
Flexovit	–	–	–	Zircotex Premium, Zircotex HP
Garryson	–	–	Zirc+, Zirconium	Aluminum Oxide
GemTex	–	Ceramic	–	Zirconia, A/O
Hermes	–	–	–	–
Klingspor	–	–	SMT 630	SMT 618, 619, 624, 626, 627, 628, 640
Metabo	–	–	–	Z/A
Pearl	–	Stainless Max	Zirconia Premium, TuffMax	Z/A Silver Line, Premium A/O Classic, Silver Line
Pferd	–	Ceramic	Cool Zirconia, CO-COOL	Zirconia, Cool Aluminum Oxide, Aluminum Oxide
Sait	–	–	Z	2A, 3A
SIA	–	–	–	Z/A
Standard	–	Ceramic Oxide	Zirconia Pro	Zirconia
Tyrolit	–	–	Z/A	A/O
Walter	–	–	Enduro Flex	–
Weiler	–	Saber Tooth Ceramic	–	Tiger Zirconium, A/O, Vortec



FEATURED PRODUCTS



EXPANDED OFFERING

NORTON BLAZE R980P

BEST/HIGHEST PRODUCTIVITY FOR STAINLESS STEEL, TITANIUM, AND SUPER ALLOYS

FEATURES

- Latest-generation ceramic alumina abrasive grain
- Y-weight polyester flaps with a supersize grinding aid
- Durable fiberglass back on Type 29 and Type 27 HD
- Orange, flexible plastic backing plate on Type 27 Quick Trim
- NEW! 2" and 3" quick-change mini flap discs

BENEFITS

- Last 50% – 200% longer than any flap discs on stainless steel, cobalt, chrome, Inconel, titanium and other hard-to-grind materials
- Significantly improve life, grain retention, and fray resistance while providing a cool, noticeably fast cut rate
- High strength, lightweight, absorbs vibration
- The industry standard for trimmability
- Ideal for tight spaces



NORTON RED HEAT R961

BEST/HIGH PRODUCTIVITY FOR MILD CARBON STEEL, AND FERROUS METALS

FEATURES

- Premium ceramic and zirconia alumina abrasive blend
- Durable, fiberglass back on Type 29
- Red, flexible plastic backing plate on Type 27 Quick Trim

BENEFITS

- Excellent performance and efficiencies on mild carbon steel and ferrous metal/cast iron applications
- High strength, lightweight, absorbs vibration
- The industry standard for trimmability



EXPANDED OFFERING

NORTON BLUEFIRE R884P

BETTER CHOICE FOR MILD CARBON STEEL, AND WELDS

FEATURES

- High performance zirconia alumina plus abrasive
- Polyester flaps with semi-open coat
- Durable, fiberglass back on Type 29 and NEW Type 27 HD
- Blue, flexible plastic backing plate on Type 27 Quick Trim
- NEW! Vendible 2-disc package
- NEW! 2" and 3" quick-change mini flap discs

BENEFITS

- Aggressive cut and long life
- Up to 30% longer life than competitive zirconia alumina products
- Improved durability and retards loading on aluminum
- High strength, lightweight, absorbs vibration
- The industry standard for trimmability
- ideal for vending machines, small jobs, or carrying to a job site
- Ideal for tight spaces



NORTON NEON R766

GOOD CHOICE FOR ALUMINUM, BRASS, BRONZE, STAINLESS, CARBON STEEL, AND TITANIUM

FEATURES

- Alternating aluminum oxide (black) and zirconia alumina (blue) flaps
- New resin system and alternating Y-weight polyester and cotton flaps
- Unique grain coating
- Fiberglass back on Type 29 and Type 27 HD
- Green, flexible plastic backing plate on Type 27 Quick Trim

BENEFITS

- Ideal when purchasing criteria is a good-performing, economically-priced, general purpose disc
- Improved base adhesion and 30%+ improvement in life over key competitors' aluminum oxide flap discs
- Stand up on light- to moderately-demanding applications
- Longer life and faster cut rate
- High strength, lightweight, absorb vibration
- The industry standard for trimmability



NEW

NORTON METAL R828

GOOD CONSISTENT PERFORMANCE WITH LOW INITIAL PRICE

FEATURES

- Durable zirconia alumina abrasive

BENEFITS

- Maximum cut rate and life with consistent finish



AVAILABILITY

TIER:
BRAND
TRADENAME:
SHAPE:
FLAP DENSITY
ABRASIVE:
BACKING PLATE:
OTHER:

BEST	BEST	BETTER	GOOD	GOOD
Norton	Norton	Norton	Norton	Norton
BLAZE R980P	RED HEAT R961	BLUEFIRE R884P	NEON R766	METAL R828
Type 29 Conical	Type 29 Conical	Type 29 Conical	Type 29 Conical	Type 29 Conical
Standard	Standard	Standard	Standard	Standard
Ceramic Alumina	Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina Plus	Aluminum Oxide/ Zirconia Alumina	Zirconia Alumina
Fiberglass	Fiberglass	Fiberglass	Fiberglass	Fiberglass
Supersize				

SIZE (D x H)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
Type 29 Conical								
4 x 5/8	36	15,300	10			66623399049		
	40	15,300	10			66623399050		
	60	15,300	10			66623399051		
	80	15,300	10			66623399052		
4-1/2 x 5/8-11	36	13,300	10	66261183490	66623399053*	66254461165	66623399028	66254419991
	36	13,300	10			66623341104 2-Pack		
	40	13,300	10	66261183491	63642536156*	66254461167	66623399029	66254419994
	60	13,300	10	66261183492	63642536157*	66254461170	66623399030	66254419996
	60	13,300	10			66623341105 2-Pack		
	80	13,300	10	66261183493	63642536158*	66254461173	66623399173	66254419997
	80	13,300	10			66623341106 2-Pack		
	120	13,300	10		63642597115*		66623399174	
4-1/2 x 7/8	24	13,300	10			66623399204		
	36	13,300	10	66261183486	63642504329	66254461155	66623399032	66254419963
	36	13,300	10			66623341107 2-Pack		
	40	13,300	10	66261183487	63642504330	66254461161	66623399033	66254419978
	60	13,300	10	66261183488	63642504331	66254461163	66623399034	66254419984
	60	13,300	10			66623341108 2-Pack		
	80	13,300	10	66261183489	63642504332	66254461164	66623399035	66254419987
	80	13,300	10			66623341109 2-Pack		
5 x 5/8-11	120	13,300	10		63642504333		66623399175	
	36	12,000	10		66623399197*	66623399189	66623399176	
	36	12,000	10			66623341110 2-Pack		
	40	12,000	10		66623399198*	66623399190	66623399177	
	60	12,000	10		66623399199*	66623399191	66623399178	
	60	12,000	10			66623341111 2-Pack		
	80	12,000	10		66623399200*	66623399192	66623399179	
	80	12,000	10			66623341112 2-Pack		
5 x 7/8	120	12,000	10		66623399201*		66623399180	
	24	12,000	10			66623399206		
	36	12,000	10	66261190001	66623399054	66254461174	66623399036	66254419998
	36	12,000	10			66623341113 2-Pack		
	40	12,000	10	66261190002	66623399055	66254461176	66623399037	66254420001
	60	12,000	10	66261190003	66623399056	66254461177	66623399038	66254420002
	60	12,000	10			66623341114 2-Pack		
	80	12,000	10	66261190004	66623399057	66254461178	66623399039	66254420003
6 x 5/8-11	80	12,000	10			66623341115 2-Pack		
	120	12,000	10		66623399202		66623399181	
	40	10,200	10				66623399040	66254491779
	60	10,200	10				66623399041	66254491780
6 x 7/8	80	10,200	10				66623399042	66254491781
	24	10,200	10			66623399066		
	36	10,200	10			66623399298		
	40	10,200	10		63642541406	66623399193	66623399182	66254491776
	60	10,200	10		63642541407	66623399194	66623399183	66254491777
	80	10,200	10		63642541408	66623399195	66623399184	66254491778
7 x 5/8-11	120	10,200	10					
	36	8,600	10	66261183498	66623399058*	66254461188	66623399185	66254420009
	36	8,600	10			66623341116 2-Pack		
	40	8,600	10	66261183499	63642536159*	66254461190	66623399043	66254420010
	60	8,600	10	66261183500	63642536160*	66254461192	66623399044	66254420012
	60	8,600	10			66623341117 2-Pack		
	80	8,600	10	66261183501	63642536161*	66254461193	66623399045	66254420013
	80	8,600	10			66623341118 2-Pack		
7 x 7/8	120	8,600	10		66623399203*		66623399186	
	24	8,600	10			66623399196		
	36	8,600	10	66261183494	63642504334	66254461180	66623399187	66254420004
	36	8,600	10			66623341119 2-Pack		
	40	8,600	10	66261183495	63642504335	66254461183	66623399046	66254420006
	60	8,600	10	66261183496	63642504336	66254461185	66623399047	66254420007
	60	8,600	10			66623341120 2-Pack		
	80	8,600	10	66261183497	63642504337	66254461186	66623399048	
120	8,600	10			63642504338	66623341121 2-Pack	66623399188	

* 5/8-11 (HUBBED) RED HEAT FLAP DISC STD. PKG. QUANTITY = 5 = VENDIBLE PACKAGE. 2 DISCS/PACK; 5 PACKS/CARTON. ORDER IN MULTIPLES OF 10.



AVAILABILITY

TIER:	BEST	BEST	BEST	BETTER	BETTER
BRAND	Norton	Norton	Norton	Norton	Norton
TRADENAME:	BLAZE R980P	BLAZE R980P	RED HEAT R961	BLUEFIRE R884P	BLUEFIRE R884P
SHAPE:	Type 27 Flat	Type 27 Flat	Type 27 Flat	Type 27 Flat	Type 27 Flat
FLAP DENSITY	Standard	High	Standard	Standard	High
ABRASIVE:	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina/ Zirconia Alumina	Zirconia Alumina Plus	Zirconia Alumina Plus
BACKING PLATE:	Quick Trim Plastic	Fiberglass	Quick Trim Plastic	Quick Trim Plastic	Fiberglass
OTHER:	Supersize	Supersize			

SIZE (D x H)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
Type 27 Flat								
4 x 5/8	40	15,300	10			63642536153		
	60	15,300	10			63642536154		
	80	15,300	10			63642536155		
4-1/2 x 5/8-11	36	13,300	10		66254499894	66623399163*	66623399136	
	36	13,300	10 V	66254400257	66261098290	63642536147*	66623399137	77696090086
	40	13,300	10	66254400258	66261096435	63642536148*	66623399138	77696090087
	60	13,300	10 V				66623341087 2-Pack	
	80	13,300	10	66254400259	66261096436	63642536149*	66623399139	77696090088
	80	13,300	10 V				66623341088 2-Pack	
	120	13,300	10	66254400261		66623399164*		
				63642501865	66261097678	63642504876	66623399140	77696090081
4-1/2 x 7/8	36	13,300	10 V				66623341089 2-Pack	
	40	13,300	10	66254400253	66261020628	63642504877	66623399141	77696090082
	60	13,300	10	66254400254	66261020633	63642504878	66623399142	77696090083
	60	13,300	10 V				66623341090 2-Pack	
	80	13,300	10	66254400255	66261020634	63642504879	66623399143	77696090084
	80	13,300	10 V				66623341091 2-Pack	
	120	13,300	10	66254400256		63642505279		77696090085
						66623399165*	66623399144	
5 x 5/8-11	36	12,000	10				66623341092 2-Pack	
	36	12,000	10 V	77696090141		66254491941*	66623399145	
	40	12,000	10	77696090142		66254491942*	66623399146	
	60	12,000	10				66623341093 2-Pack	
	60	12,000	10 V				66623399147	
	80	12,000	10	77696090143		66254491943*	66623341094 2-Pack	
	80	12,000	10 V					
	120	12,000	10	77696090144		66623399166*		
5 x 7/8	36	12,000	10			63642505281	66623399148	
	36	12,000	10 V				66623341095 2-Pack	
	40	12,000	10	66254400262		63642505282	66623399149	
	60	12,000	10	66254400264		63642505283	66623399150	
	60	12,000	10 V				66623341096 2-Pack	
	80	12,000	10	66254400265		63642505284	66623399151	
	80	12,000	10 V				66623341097 2-Pack	
	120	12,000	10	66254400519		63642505285		
6 x 5/8-11	40	10,200	10			66623399167*		
	60	10,200	10			66623399168*		
	80	10,200	10			66623399169*		
6 x 7/8	36	10,200	10			66623399024	66623399152	
	40	10,200	10			66623399025	66623399153	
	60	10,200	10			66623399026	66623399154	
	80	10,200	10			66623399027		
	120	10,200	10			66623399170*	66623399155	
7 x 5/8-11	36	8,600	10				66623341098 2-Pack	
	36	8,600	10 V	66254461066		63642536150*	66623399156	77696090092
	40	8,600	10	66254461067		63642536151*	66623399157	77696090093
	60	8,600	10				66623341099 2-Pack	
	60	8,600	10 V	66254461068		63642536152*	66623399158	77696090094
	80	8,600	10				66623341100 2-Pack	
	80	8,600	10 V	66254461069		66623399171*		
	120	8,600	10	63642501866		63642504880	66623399159	
7 x 7/8	36	8,600	10				66623341101 2-Pack	
	36	8,600	10 V	66254461059		63642504881	66623399160	77696090089
	40	8,600	10	66254461060		63642504882	66623399161	77696090090
	60	8,600	10 V				66623341102 2-Pack	
	80	8,600	10	66254461061		63642504883	66623399162	77696090091
	80	8,600	10 V				66623341103 2-Pack	
	120	8,600	10	66254461063		66623399172		

* 5/8-11 (HUBBED) RED HEAT FLAP DISC STD. PKG. QUANTITY = 5

V = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES & SMALL JOBS. 2 FLAP DISCS/PACK, 5 PACKS/CARTON. ORDER IN MULTIPLES OF 10.



AVAILABILITY

TIER:			
BRAND:	Norton	Norton	Norton
TRADENAME:	NEON R766	NEON R766	METAL R828
SHAPE:	Type 27 Flat	Type 27 Flat	Type 27 Flat
FLAP DENSITY:	Standard	High	Standard
ABRASIVE:	Aluminum Oxide/ Zirconia Alumina	Aluminum Oxide/ Zirconia Alumina	Zirconia Alumina
BACKING PLATE:	Quick Trim Plastic	Fiberglass	Fiberglass
OTHER:			

SIZE (D x H)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #
Type 27 Flat (continued)						
4 x 5/8	40	15,300	10			
	60	15,300	10			
	80	15,300	10			
4-1/2 x 5/8-11	36	13,300	10	66623399125	66623399205	66254472655
	40	13,300	10	66623399000	66623399059	66254437013
	60	13,300	10	66623399001	66623399060	66254472656
	80	13,300	10	66623399002	66623399061	66254472657
	120	13,300	10	66623399003		
4-1/2 x 7/8	36	13,300	10	66623399126	66623399062	66254472653
	40	13,300	10	66623399004	66623399063	66254437004
	60	13,300	10	66623399005	66623399064	66254448989
	80	13,300	10	66623399006	66623399065	66254448990
	120	13,300	10	66623399007		
5 x 5/8-11	36	12,000	10	66623399127	66623399207	
	40	12,000	10	66623399128	66623399208	
	60	12,000	10	66623399130	66623399209	
	80	12,000	10	66623399131	66623399210	
	120	12,000	10	66623399132		
5 x 7/8	36	12,000	10	66623399133	66623399211	66254472659
	40	12,000	10	66623399008	66623399212	66254472660
	60	12,000	10	66623399009	66623399213	66254472661
	80	12,000	10	66623399010	66623399214	66254472662
	120	12,000	10	66623399011		
6 x 5/8-11	40	10,200	10		66623399219	66254491773
	60	10,200	10		66623399220	66254491774
	80	10,200	10		66623399221	66254491775
6 x 7/8	36	10,200	10		66623399215	
	40	10,200	10	66623399012	66623399216	66254491770
	60	10,200	10	66623399013	66623399217	66254491771
	80	10,200	10	66623399014	66623399218	66254491772
	120	10,200	10	66623399015		
7 x 5/8-11	36	8,600	10	66623399134	66623399222	66254472669
	40	8,600	10	66623399016	66623399067	66254472670
	60	8,600	10	66623399017	66623399068	66254472671
	80	8,600	10	66623399018	66623399069	66254472672
	120	8,600	10	66623399019		
7 x 7/8	36	8,600	10	66623399135	66623399070	66254472664
	40	8,600	10	66623399020	66623399071	66254472665
	60	8,600	10	66623399021	66623399072	66254472666
	80	8,600	10	66623399022	66623399073	66254472667
	120	8,600	10	66623399023		

When You Want Fast and Tough, You Want Norton

Whether you want maximum productivity or simply the lowest initial cost solution, Norton has the product for all your right angle grinding and blending applications.



BEST Norton Blaze

Highest Productivity – Lowest Total Cost



BETTER Norton BlueFire

Exceptional Blend of Performance and Price



GOOD Norton Neon

Good Performance – Low Initial Price



NORTON BLUEFIRE 20X R884P

PACKAGED FOR RETAIL / WALK-IN SELLING / SMALL JOBS

FEATURES & BENEFITS

- Zirconia alumina abrasive for aggressive cut and long life
- Individual hang card provides product selling points
- Product ships in merchandisable display case of small quantities
- Available wire rack (with header card) allows merchandising of 4 and 4-1/2 product three ways: hung on pegboard, mounted on an upright, or placed on a shelf/counter

AVAILABILITY

TIER:	BETTER
BRAND:	Norton
TRADENAME:	BLUEFIRE 20X R884P
SHAPE:	Type 29
FLAP DENSITY:	Standard
ABRASIVE:	Zirconia Alumina Plus
BACKING PLATE:	Fiberglass

SIZE (D x H)	GRIT	MAX. RPM	STD. PKG.	PART #
4 x M-10	40	15,300	5	07660703214
	60	15,300	5	07660703215
	80	15,300	5	07660703216
4-1/2 x 5/8-11	40	13,300	5	07660703211
	60	13,300	5	07660703212
	80	13,300	5	07660703213
7 x 5/8-11	40	8,600	5	07660703205
	60	8,600	5	07660703206
	80	8,600	5	07660703207
Wire Rack			2	07660704157



WIRE RACK (WITH HEADER CARD) ALLOWS MERCHANDISING OF 4" AND 4-1/2" PRODUCT THREE WAYS: HUNG ON PEGBOARD, MOUNTED ON AN UPRIGHT, OR PLACED ON A SHELF/COUNTER



NORTON MINI FLAP DISCS

PACKAGED FOR RETAIL / WALK-IN SELLING / SMALL JOBS

FEATURES & BENEFITS

- High performance ceramic and zirconia alumina abrasive provide maximum cut rate and life
- Layered flaps wear away evenly, producing a high quality and consistent finish



AVAILABILITY

TIER:	BEST	BETTER	BEST	BETTER
BRAND:	Norton	Norton	Norton	Norton
TRADENAME:	BLAZE R980P	BLUEFIRE R884P	BLAZE R980P	BLUEFIRE R884P
ABRASIVE:	Ceramic Alumina	Zirconia Alumina	Ceramic Alumina	Zirconia Alumina
FLAP:	Polyester	Polyester	Polyester	Polyester
BACKING MATERIAL:	Extra Heavy-Duty Plastic	Extra Heavy-Duty Plastic	Extra Heavy-Duty Plastic	Extra Heavy-Duty Plastic
ATTACHMENT:	TR (Type III)	TR (Type III)	TS (Type II)	TS (Type II)



SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #
2	36	10	77696090145	77696090165	77696090155	77696090175
	40	10	77696090146	77696090166	77696090156	77696090176
	60	10	77696090147	77696090167	77696090157	77696090177
	80	10	77696090148	77696090168	77696090158	77696090178
	120	10	77696090149	77696090169	77696090159	77696090179
3	36	10	77696090150	77696090170	77696090160	77696090180
	40	10	77696090151	77696090171	77696090161	77696090181
	60	10	77696090152	77696090172	77696090162	77696090182
	80	10	77696090153	77696090173	77696090163	77696090183
	120	10	77696090154	77696090174	77696090164	77696090184

DESCRIPTION	STD. PKG.	MAX. RPM	PART #
Mini Flap Disc Back-up Pads			
2" and 3" TS (Type II) Back-up Pads	1	30,000	08834168539
2" and 3" TR (Type III) Back-up Pads	1	30,000	08834164922

TR (TYPE III)

TS (TYPE II)



CATEGORY DEFINITION


For use on random orbital and rotary sanders. The industry's highest performing and broadest selection of paper discs in PSA (pressure sensitive adhesive) disc rolls and individual discs, and hook and loop discs.

APPLICATIONS:	Stripping and preparing primed and painted surfaces for finishing, sanding of plastics, fiberglass and composites, bare wood sanding, light weld blending, preparing and finishing metal, and sanding of all gel coat and body filler compounds
SIZE RANGE:	3" – 8"
GRIT RANGE:	36 – 1500
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide, Silicon Carbide
ATTACHMENT SYSTEMS:	PSA (pressure-sensitive adhesive), hook and loop
PAPER WEIGHTS:	Heavyweight – E and F; Lightweight – B and C
VACUUM HOLES:	See product availability charts

MATERIAL/APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity – Lowest Total Cost		BETTER Excellent Blend of Performance & Price		GOOD Consistent Performance – Low Initial Price
	Heavy-Medium Stock Removal	Light Stock Removal-Finishing	Heavy-Medium Stock Removal	Light Stock Removal-Finishing	Light Stock Removal-Finishing
Primed, Painted Surfaces		A975	H875P	A275	PB273
Fiberglass / Composites / Gel Coats		A975	H875P	A275	PB273
Wood		A975	H875P	A275	PB273
Metal	H920	A975	H822	A275	PB273
Body Fillers / Compounds / Plastics		A975	H875P	A275	PB273

APPLICATION/GRIT RECOMMENDATION GUIDE



CROSS REFERENCE GUIDE

TOTAL PERFORMANCE								INITIAL PRICE	
NORTON MERIT	BEST		BETTER					GOOD	
	F-Wt.	B- & C-Wt.	F-Wt.	E-Wt.	B-Wt.	B-Wt.	B-Wt.	C-Wt.	B-Wt.
	Norton SG H920	Dry Ice A975	BlueFire H822	BlueFire H875P	Adalox A275	Adalox A270	Durite A475	Adalox A290	PB273
	763U, 751I	734U, 735U, 765L	—	750U, 751U, 740I, 745I	216U, 255L, 260L, 334U	210U, 268L, 360L	414N, 415N, 405N, 415U, 435U	236U	214U, 316U Red. NX
	CB115	—	BW 115	—	VC154-LL	VC152	PSF-LL, SF168	HCAB-LL, HC135, VC151-LL	—
	—	—	—	—	RedLine	—	—	—	WhiteLine
	—	PS36	PS20, PS21, PS22	—	PS33	—	PL35	PS33	PL36
	—	—	—	Royal Coarse Cut	Q-Silver, Royal, Royal Micro	Silver	CaratFlex, PolarStar	Bulldog Gold, Basecut	Carat (B), Basecut
	—	1950	1820, 1919	1820, 1919	1940, 1950	—	1748	1947	—
	—	—	—	KP510E, KP709	MPG	—	CP131A	KP911	MP10



FEATURED PRODUCTS

Light-Weight Paper Discs

**NO-FIL NORTON DRYICE A975**

BEST CHOICE FOR THE MOST DEMANDING SANDING APPLICATIONS

FEATURES

- P-graded Norton SG ceramic alumina abrasive
- Unique fiber-reinforced, flexible B- and C-weight latex-saturated backing
- Water-based No-Fil stearate, non-pigmented
- NEW Multi-Air Cyclonic A975 Hook and Loop Discs now available

BENEFITS

- Fastest cut rate; longest life of any paper disc
- 50-60% improvement in tear strength, longer life in all applications
- Flexible
- Provides maximum load resistance and extended life
- No color transfer
- Revolutionary desing for maximum vacuum assist (see page 87 for more details and product availability)

**NO-FIL NORTON ADALOX A275**

BETTER CHOICE FOR HIGH-PERFORMANCE DRY FINISHING ON ALL MATERIALS

FEATURES

- Premium P-graded, heat-treated aluminum oxide abrasive
- Unique fiber-reinforced, flexible B-weight latex-saturated backing
- Water-based stearate, non-pigmented, No-Fil coating
- 5" and 6" individual PSA discs in fine grits have a tabbed, white translucent liner

BENEFITS

- Superior life, fast cut rate, consistent finish
- 50-60% improvement in tear strength
- Flexible
- Provides maximum load resistance and extended life
- No color transfer to work
- The PSA adhesive is protected from airborne contaminants
- The tab allows easier removal of the paper liner

**NO-FIL NORTON DURITE A475**

BETTER CHOICE FOR HARD-TO-SAND SURFACES AND WOOD APPLICATIONS

FEATURES

- P-graded, hard, silicon carbide abrasive
- Water-based stearate, non-pigmented, No-Fil coating
- Durable, fiber-reinforced, B-weight latex paper

BENEFITS

- Easy penetration of the hardest surfaces
- Resists loading for the longest usable product life
- No color transfer to work
- Provides flexibility and resistance to tearing

**MERIT NO-LOAD PB273**


GOOD CHOICE FOR SANDING PAINT, PRIMER, PLASTICS, FIBERGLASS, AND WHITEWOOD AT A LOW INITIAL PRICE

FEATURES

- P-graded, aluminum oxide abrasive
- Flexible latex B-weight backing, with a full resin bond and open coat
- Water-based stearate, non-pigmented, No-Fil coating

BENEFITS

- Fast cutting action and extended life with consistent finish
- Improved resistance to delamination; no delamination to back-up pad
- Provides improved load resistance
- No color transfer to work



FEATURED PRODUCTS

Heavy-Weight Paper Discs



NORTON SG H920

BEST CHOICE FOR MORE DEMANDING STOCK REMOVAL APPLICATIONS

FEATURES

- Durable and friable Norton SG ceramic alumina abrasive
- Strong, heavy F-weight paper, synthetically-coated

BENEFITS

- Maximum life; fast aggressive cutting action, yet cool cutting
- Maximum durability and chip resistance, ideal for soldered and welded areas, and unpainted metal applications



NORTON BLUEFIRE H875P

BETTER CHOICE FOR SOFT MATERIAL APPLICATIONS

FEATURES

- Next-generation zirconia alumina abrasive
- Strong, heavy, E-weight paper
- Open coat design

BENEFITS

- Extended life over original zirconia alumina products
- Improved cut rate
- Increased durability and chip resistance, flexible
- Reduced loading; ideal for body-filler, fiberglass and composites

AVAILABILITY
STICK AND SAND (PSA)
HEAVY-WEIGHT DISC ROLLS
NON-VACUUM



TIER:

BRAND:

CAP CODE:

ABRASIVE:

PAPER BACKING WEIGHT:

SIZE	GRIT	ROLLS/STD. PKG.	DISCS/ ROLL	PART #	PART #	PART #
5	60	4	100	66261149873	66261137310	66261124977
	80	4	100	66261149872	66261137309	
	100	4	100	66261149871	66261137308	
	120	4	100	66261149870	66261137307	
6	60	4	100	66261149876 66261149874 66261149879	66261137323	66261125573
	80	4	100		66261137322	
	120	4	100			
8	100	4	50		66261137333	
	120	4	50			

Refer to the end of this section for back-up pads and accessories.



AVAILABILITY
STICK AND SAND (PSA)
LIGHT-WEIGHT DISC ROLLS
NON-VACUUM

TIER:

BRAND:

CAP CODE:

ABRASIVE:

PAPER BACKING WEIGHT:


OTHER:

BEST	BETTER	BETTER	GOOD	GOOD
Norton	Norton	Norton	Norton	Merit
A975 NO-FIL	A275 NO-FIL	A475 NO-FIL	A290 NO-FIL	PB273 NO-LOAD
Ceramic Alumina	Aluminum Oxide	Silicon Carbide	Aluminum Oxide	Aluminum Oxide
B- & C-Weight	B-Weight	B-Weight	C-Weight	B-Weight
P-Graded	P-Graded	P-Graded	P-Graded	P-Graded

SIZE	GRIT	ROLLS/ STD. PKG.	DISCS/ ROLL	PART #	PART #	PART #	PART #	PART #
3-1/2	80	4	100		66261136376			
	120	4	100		66261136375			
	180	4	100		66261136373			
	220	4	100		66261136372			
	280	4	100		66261136370			
	320	4	100		66261136369			
	400	4	100		66261136368			
5	60	4	100				66261149831	
	80	4	100	66261140502	66261131464*	66254487415	66261149830	66623362930
	100	4	100	66261140501	66261131463*	66254487417	66261149829	
	120	4	100	66261140500	66261131462*	66254487418	66261149828	66623362929
	150	4	100	66261140499	66261131461*	66254487440	66261149827	66623362928
	180	4	100	66261140498	66261131460*	66254487441	66261149826	66623362927
	220	4	100	66261142474	66261131459*	66254487442	66261149825	66623362926
	240	4	100	66261155380	66261131458*	66254487443	66261149824	66623362925
	280	4	100	66261155379	66261131457*		66261149823	
	320	4	100	66261155378	66261131456*	66254487444	66261149822	66623362924
	400	4	100	66261155377	66261131454*	66261065293	66261149821	66623362923
	500	4	100	66254480231	66261131453*			
	600	4	100	66623305608	66261131452*	66254421217		66623362922
	800	4	100	66254480230	66261131451*	66254401221		66623362921
6	60	4	100				66261149847	
	80	4	100	66261140512	66261131481*	66254487446	66261149842	66623362940
	100	4	100	66261140511	66261131480*		66261149841	69957352447
	120	4	100	66261140510	66261131479*	66254487447	66261149840	66623362939
	150	4	100	66261140509	66261131478*		66261149839	66623362938
	180	4	100	66261140508	66261131477*	66254487448	66261149838	66623362937
	220	4	100	66261148340	66261131476*	66254487449	66261149837	66623362936
	240	4	100	66261155376	66261131475*		66261149836	66623362935
	280	4	100	66261155375	66261131474*		66261149835	
	320	4	100	66261155374	66261131473*	66254487450	66261149834	66623362934
	400	4	100	66261155373	66261131471*		66261149833	66623362933
	500	4	100	63642506198	66261131470*			
	600	4	100	63642506199	66261131469*			66623362932
	800	4	100	63642506200	66261131468*			66623362931
8	80	4	100		66261131617			
	120	4	100		66261131615			
	150	4	100		66261131614			
	180	4	100		66261131613			
	220	4	100		66261131612			
	320	4	100		66261131609			

* PACKAGING STANDARDS A275 = 6/100

Refer to the end of this section for back-up pads and accessories.



AVAILABILITY
STICK AND SAND (PSA)
LIGHT-WEIGHT DISC ROLLS
VACUUM



TIER:

BETTER

BRAND:

Norton

CAP CODE:

A275 NO-FIL

ABRASIVE:

Aluminum Oxide

PAPER BACKING WEIGHT:

B-Weight

OTHER:

P-Graded



GOOD

Norton

A290 NO-FIL

Aluminum Oxide

C-Weight

P-Graded

SIZE	GRIT	ROLLS/STD. PKG.	DISCS/ROLL	PART #	ROLLS/STD. PKG.	DISCS/ROLL	PART #	
				 5 IN. X 5 HOLE DIE #3329				 5 IN. X 5 HOLE DIE #3329
5"	60				4	100	66261130266	
	80	6	100	66261131498	4	100	66261130265	
	100	6	100	66261131497	4	100	66261130264	
	120	6	100	66261131496	4	100	66261130263	
	150	6	100	66261131495	4	100	66261130262	
	180	6	100	66261131494	4	100	66261130261	
	220	6	100	66261131493	4	100	66261130260	
	240	6	100	66261131492	4	100	66261130259	
	320	6	100	66261131490	4	100	66261130258	
	400	6	100	66261131488				
500	6	100	66261131487					
				 6 IN. X 6 HOLE DIE #3333				 6 IN. X 6 HOLE DIE #3333
6"	80	6	100	66261131515	4	100	66261130276	
	100	6	100	66261131514	4	100	66261130275	
	120	6	100	66261131513	4	100	66261130274	
	150	6	100	66261131512	4	100	66261130273	
	180	6	100	66261131511	4	100	66261130272	
	220	6	100	66261131510	4	100	66261130271	
	240	6	100	66261131509				
	280	6	100	66261131508				
	320	6	100	66261131507	4	100	66261130268	
	400	6	100	66261131505				
	600	6	100	66261131503				


Refer to the end of this section for back-up pads and accessories.



PSA Disc Roll Dispenser

- Norton disc roll dispensers feature heavy-duty construction and a rubberized finish to protect your product, as well as the finish on your workpiece
- These versatile dispensers are designed to accommodate any 5" or 6" disc roll or sheet roll
- They can be attached to a wall or stacked for multi-grit or multi-diameter operations
- Discs are individually dispensed and removed from the roll by a cutter bar

DESCRIPTION	STD. PKG.	PART NO
PSA Disc Roll Dispenser		
Single Disc Roll Dispenser	1	63642542772
Double Disc Roll Dispenser (shown)	1	63642502981



AVAILABILITY STICK AND SAND (PSA) INDIVIDUAL DISCS

TIER:

BRAND:


CAP CODE:



ABRASIVE:

PAPER BACKING WEIGHT:

FASTENING:

OTHER:



SIZE	GRIT	MIN./ STD PKG.	PART #	PART #	PART #	PART #
5"	36	50/200	66261125436	 6" X 6 HOLE DIE #3371		
	40	50/200	66261125307			
	80	50/200	66261125244			
	100	100/400				
	120	100/400				
	150	100/400				
	180	100/400				
	220	100/400				
	240	100/400				
	320	100/400				
	400	100/400				
	600	100/400				
	800	100/400				
	1000	100/400				
	1200	100/400				
6"	36	50/200	66261123575	 8" X 8 HOLE DIE #3370		
	40	50/200	66261123574			
	80	50/200	66261123573			
	1000	100/400				
	1200	100/400				
	1500	100/400				
8"	36	25/100	66261123578	66261123584		
	40	25/100	66261123577			
	80	25/100	66261123576			

PACKAGING STANDARDS:

MIN. / STD. PKG.

‡ PB273 = 100/400

Refer to the end of this section for back-up pads and accessories.



FEATURED PRODUCTS



MULTI-AIR CYCLONIC HOOK AND LOOP VACUUM
LESS DUST; MORE PRODUCTIVITY

FEATURES

- Precision laser-cut, spiral-hole design based on the Golden Ratio
- Norton SG ceramic alumina grain
- Unique fiber-reinforced latex/paper backing
- Water-based stearate coating (No-Fil)

BENEFITS


- Maximum dust extraction for cleaner work environment and less potential for contamination
- Consistent cut throughout the life of the disc
- Superior cut on difficult to sand surfaces
- Substantially longer life and faster cut than conventional abrasives
- Quick/cool cut
- Flexible, strong and tear resistant
- Load resistant for extended product life

AVAILABILITY

TIER:	BEST
BRAND:	Norton
TRADENAME:	A975 NO-FIL
ABRASIVE:	Ceramic Alumina
PAPER BACKING WEIGHT:	B- & C-Weight
OTHER:	P-Graded



SIZE	GRIT	MIN./ STD PKG.	PART #
5" x 11/16"	80	50/200	77696007745
	120	50/200	77696007753
	150	50/200	77696007755
	180	50/200	77696007756
	220	50/200	77696007757
	240	50/200	77696007760
	280	50/200	77696007762
	320	50/200	77696007763
	400	50/200	77696007765
	500	50/200	77696007768
	600	50/200	77696007791
6" x 11/16"	80	50/200	77696007770
	120	50/200	77696007773
	150	50/200	77696007774
	180	50/200	77696007775
	220	50/200	77696007776
	240	50/200	77696007777
	280	50/200	77696007778
	320	50/200	77696007781
	400	50/200	77696007784
	500	50/200	77696007785
	600	50/200	77696007786
	800	50/200	77696007787
	1000	50/200	77696007788




Refer to the end of this section for back-up pads and accessories for Norton Multi-Air Cyclonic Discs.

Improved Dust Extraction / Increased Productivity

The upgrade to precise, flat, laser-cut holes instead of die-punched holes, dramatically increases surface area contact allowing Multi-Air Cyclonic discs to improve productivity by 32% versus conventional multi-hole sanding and by 60% versus non-vacuum sanding.

The end result is more holes for dust extraction, more abrasive coverage for a better cut and no deformation – for full surface contact utilizing all the cutting power of the premium ceramic grain.





AVAILABILITY HOOK AND LOOP INDIVIDUAL DISCS NON-VACUUM

TIER:




BRAND:

CAP CODE:

ABRASIVE:

PAPER BACKING WEIGHT:

OTHER:

									
			BEST	BEST	BETTER	BETTER	BETTER	GOOD	GOOD
			Norton	Norton	Norton	Norton	Norton	Norton	Merit
			H920	A975 NO-FIL	H875P	A275 NO-FIL	A475 NO-FIL	A290 NO-FIL	PB273 NO-LOAD
			Ceramic Alumina	Ceramic Alumina	Zirconia Alumina	Aluminum Oxide	Silicon Carbide	Aluminum Oxide	Aluminum Oxide
			F-Weight	B- & C-Weight	E-Weight	B-Weight	B-Weight	C-Weight	B-Weight
				P-Graded		P-Graded	P-Graded	P-Graded	P-Graded
SIZE	GRIT	MIN./ STD PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #
3"	80	50/200		63642505990		66261131532			
	100	50/200				66261144926			
	120	50/200		63642505991		66261128688			
	150	50/200		63642505992		66261140385			
	180	50/200		63642505993		66261131528			
	220	50/200		63642505994		66261131527			
	240	50/200		63642505995		66261131526			
	320	50/200		63642505996		66261131524			
	400	50/200		63642505997		66261136995			
	500	50/200		63642505998		66261131521			
	600	50/200		63642505999		66261136996			
	800	50/200		63642506000		66261131519			
	1000	50/200		63642506001		66261135900			
	1200	50/200							
	1500	50/200		63642506002		66261147434			
5"	40	25/100			66261125684				
	60	100/400	66261149864*					66261130224	
	80	100/400	66261149865*	66261140522‡	66261125444•	66261131549		66261149907	66623362950
	100	100/400	66261149866*	66261140521‡		66261131548		66261149906	66623365788
	120	100/400	66261149867*	66261140520‡		66261131547		66261149905	66623362949
	150	100/400		66261140519‡		66261131546		66261149904	66623362948
	180	100/400		66261140518‡		66261131545		66261149903	66623362947
	220	100/400		66261149541‡		66261131544		66261149902	66623362946
	240	100/400		66261149540‡		66261131543			66623362945
	280	100/400				66261131542			
	320	100/400		66261149538‡		66261131541		66261149900	66623362944
	400	100/400		66261149537‡		66261131539	66261052270	66261149899	66623362943
	500	100/400		66254480233‡		66261131538			
	600	100/400				66261131537	66254421221		66623362942
	800	100/400		66254480232‡		66261131536	66261052267		66623362941
	1000	100/400				66261131535	66261052254		
	1200	100/400				66261131534			
	1500	100/400				66261131533			
6"	36	25/100			66261123590				
	40	25/100			66261123589				
	80	100/400		66261140532‡	66261123588•	66261131566		66261149916	66623362960
	100	100/400		66261140531‡		66261131565		66261149915	66623365789
	120	100/400		66261140530‡		66261131564		66261149914	66623362959
	150	100/400		66261140529‡		66261131563		66261149913	66623362958
	180	100/400		66261140528‡		66261131562		66261149912	66623362957
	220	100/400		66261149546‡		66261131561		66261149911	66623362956
	240	100/400				66261131560			66623362955
	280	100/400				66261131559		66261149910	
	320	100/400		66261149543‡		66261131558		66261149909	66623362954
	400	100/400		66261149542‡		66261131556		66261149908	66623362953
	500	100/400		63642506202‡		66261131555			
	600	100/400		63642506203‡		66261131554			66623362952
	800	100/400		63642506204‡		66261131553	66261052268		66623362951
	1000	100/400		63642506375‡		66261131552	66261052255		
	1200	100/400		63642506376‡		66261131551			
	1500	100/400		63642506377‡		66261131550			
8"	36	25/100			66261123593				
	40	25/100			66261123592				
	60	50/250							
	80	50/250			66261123591•				
	100	50/250							
	120	100/400				66261131662			
	180	100/400				66261131661			

PACKAGING STANDARDS: MIN. / STD. PKG.

* H920 = 50/250

‡ A975 = 50/200

• H875P = 25/100

Refer to the end of this section for back-up pads and accessories.



AVAILABILITY HOOK AND LOOP INDIVIDUAL DISCS VACUUM

TIER:

BRAND:

CAP CODE:

ABRASIVE:

PAPER BACKING WEIGHT:

OTHER:



BEST

BETTER

BETTER

GOOD

GOOD

GOOD

Norton

Norton

Norton

Norton

Norton

Merit

A975 NO-FIL

H875P

A275 NO-FIL

A290 NO-FIL

A290 NO-FIL

PB273 NO-LOAD

Ceramic Alumina

Zirconia Alumina

Aluminum Oxide

Aluminum Oxide

Aluminum Oxide

Aluminum Oxide

B- & C-Weight

E-Weight

B-Weight

C-Weight

C-Weight

B-Weight


P-Graded

P-Graded

P-Graded

P-Graded

P-Graded


SIZE	GRIT	MIN./ STD PKG.	PART #	PART #	PART #	PART #	PART #	PART #			
											
			5 IN. X 5 HOLE DIE #3328		5 IN. X 5 HOLE DIE #3328	5 IN. X 5 HOLE DIE #3328	5 IN. X 8 HOLE DIE #3392	5 IN. X 8 HOLE DIE #3392			
5	60	100/400	66261140517‡		66261131583	66261130236‡	66261130245‡	66623366071			
	80	100/400		66261131582	66261130235‡	66261130244‡					
	100	100/400		66261131581	66261130234‡	66261130243‡					
	120	100/400		66261140515‡	66261130233‡	66261130242‡	66623369778				
	150	100/400		66261131580	66261130232‡	66261130241‡	66623366073				
	180	100/400		66261131579	66261130231‡	66261130240‡	66623366074				
	220	100/400		66261131578	66261130230‡	66261130239‡	66623366075				
	240	100/400		66261131577							
	320	100/400		66261131575	66261130227‡	66261130238‡	66623366077				
	400	100/400		66261131573	66261130226‡						
600	100/400		66261131571								
											
			6 IN. X 6 HOLE DIE #3371		6 IN. X 6 HOLE DIE #3371	6 IN. X 6 HOLE DIE #3371	6 IN. X 6 HOLE DIE #3371				
6	80	100/400	66261140527‡		66261131600	66261130255‡		66623367394			
	100	100/400		66261131599							
	120	100/400		66261131598	66261130253‡						
	150	100/400		66261131597			66623367397				
	180	100/400		66261131596	66261130251‡		66623367398				
	220	100/400		66261131595	66261130250‡		66623367399				
	280	100/400		66261131593							
	320	100/400		66261131592			66623367400				
	400	100/400		66261131590			66623367401				
	600	100/400		66261131588							
	800	100/400		66261131587							
	1000	100/400		66261131586							
	1200	100/400		66261131585							
	1500	100/400			66261131584						
											
				8 IN. X 8 HOLE DIE #3370							
	8	36		25/100		66261123598					
80		25/100		66261123596							

PACKAGING STANDARDS: ‡ A975, A975 VACUUM, A290 VACUUM = 50/200



For Fein/Festo Sanders

High-performance abrasives for high performance sanders. Now available: No-Fil Norton Drylce A975 discs with center vacuum hole for Fein and Festo random orbital sanders.



6 IN. X 9 HOLE
DIE #3408-2

TIER:

BRAND:

CAP CODE:

ABRASIVE:

PAPER BACKING WEIGHT:

OTHER:

BEST

Norton

A975 NO-FIL

Ceramic Alumina

B- & C-Weight

P-Graded


SIZE	GRIT	STD. PKG.	PART #
6	80	50/200	07660705489
	100	50/200	07660705488
	120	50/200	07660705487
	150	50/200	07660705486
	220	50/200	07660705484



Multi-Air Foam Interface Pads

- Designed for use with fine grit Multi-Air Cyclonic Hook and Loop sanding discs to improve both surface finish and cut rate
- Use with Multi-Air Hook & Loop Disc Back-Up Pads
- Align the interface pad with the Multi-Air back up pad then simply attach the disc to the interface pad because the holes do not have to be lined up.

DESCRIPTION	STD. PKG.	PART #
Multi-Air Foam Interface Pads		
5" Diameter x 1/2" Thick Pad	8	63642585864
6" Diameter x 1/2" Thick Pad	12	07660719359



Multi-Air Hook & Loop Back-up Pads with Vacuum Holes

- Innovative design optimized for maximum air flow and powerful dust extraction
- Pads are engineered with a durable urethane foam, heat-resistant plastic, a molded-in 5/16"-24 spindle, and hooked face.
- Holes in the disc do not have to be matched up with the holes in the pad, so changeover is fast and easy.

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Multi-Air Hook & Loop Back-Up Pads with Vacuum Holes			
5" (125mm) with 5/16"-24 Shank, Medium-Density Urethane Pad	15,000	5	66623376000
6" (150mm) with 5/16"-24 Shank, Medium-Density Urethane Pad	15,000	5	63642506160



Low-Profile Pads for Dual Action / Random Orbital Sanders

- Soft density low-profile pads utilize 1/2" thick foam for fine finish sanding and offer moderate conformability
- Medium low-profile pads have 1/2" thick urethane foam for intermediate and finish sanding
- Available with PSA or hook and loop faces; both designs are shock resistant and have a fiberglass backing plate with a riveted 5/16"-24 threaded shank for added strength and increased heat resistance
- Available with standard hole patterns for vacuum-assist sanding

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Low Profile Pads for DA/Random orbital Sanders			
3" Hook & Loop Soft Low-Profile	12,000	10*	63642506128
3" x 7/8" Hook & Loop Pad		10	63642541947
3-1/4" Hook & Loop Buffing Pad		5*	66261085302
5" PSA Soft Low-Profile	12,000	5*	63642506126
5" PSA Medium Low-Profile	15,000	5*	63642506131
5" PSA Medium Low-Profile with 5 vacuum holes	15,000	5*	63642506132
5" Hook & Loop Soft Low-Profile	12,000	5*	63642506129
5" Hook & Loop Medium Low-Profile	15,000	5*	63642506135
5" Hook & Loop Medium Low-Profile with 5 vacuum holes	15,000	5*	63642506136
6" PSA Soft Low-Profile	12,000	5*	63642506127
6" PSA Medium Low-Profile	15,000	5*	63642506133
6" PSA Medium Low-Profile with 6 vacuum holes	15,000	5*	63642506134
6" Hook & Loop Soft Low-Profile	12,000	5*	63642506130
6" Hook & Loop Medium Low-Profile	15,000	5*	63642506137
6" Hook & Loop Medium Low-Profile with 6 vacuum holes	15,000	5*	63642506138
8" Hook & Loop Medium Low-Profile with 8 vacuum holes, 5 screw	1,500	5*	63642543712
8" Hook & Loop Medium Low-Profile with 8 vacuum holes, 6 screw	1,500	5*	63642543714

* PACKED IN INDIVIDUAL CLAMSHELL



Tapered Pads for Dual Action / Random Orbital Sanders

- Designed with medium density polyurethane foam and a tapered edge for conformability, these pads are firm enough for flat surfaces, yet soft enough for severe curves and contours
- Available with either PSA (vinyl) or hook and loop faces in vacuum or non-vacuum
- The 5" and 6" pads are shock resistant and have a fiberglass backing plate with a riveted 5/16"-24 threaded shank for use on random orbital or dual action sanders
- The 8" pads have a 5/8"-11 threaded female hub

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Tapered Pads for DA/Random Orbital Sanders			
5" PSA Medium Tapered	15,000	5*	63642506139
5" PSA Medium Tapered with 5 vacuum holes	15,000	5*	63642506140
5" Hook & Loop Medium Tapered	15,000	5*	63642506143
5" Hook & Loop Medium Tapered with 5 vacuum holes	15,000	5*	63642506144
6" PSA Medium Tapered	15,000	5*	63642506141
6" PSA Medium Tapered with 6 vacuum holes	15,000	5*	63642506142
6" Hook & Loop Medium Tapered	15,000	5*	63642506145
6" Hook & Loop Medium Tapered with 6 vacuum holes	15,000	5*	63642506146
8" PSA Medium Tapered	6,000	5*	63642543112
8" Hook & Loop Medium Tapered	3,200	5*	63642543704

* PACKED IN INDIVIDUAL CLAMSHELL



Hook & Loop Foam Interface Pads

- Designed for use with our fine grit hook and loop sanding discs
- Improve both surface finish and cut rate
- Use with hook and loop back-up pads

DESCRIPTION	STD. PKG.	PART #
Foam Hook & Loop Interface Pads		
3" Diameter, 1/2" Thick Interface	10	63642505457
6" Diameter, 1/2" Thick Interface	5	63642542089
5" Diameter, 3/4" Thick Interface	2	63642502161
6" Diameter, 3/4" Thick Interface	2	63642502162



Half Moon Hand Pad

- The unique half moon pad uses a standard 5" hook and loop disc folded in half, which adheres to the hooks on the pad face
- The straight edge of the pad allows the operator to sand corners, contours, narrow crevices and minute imperfections without over-sanding

DESCRIPTION	STD. PKG.	PART #
Half Moon Hand Pad		
5" Hook and Loop	10	63642502768



Polishing Adapter Pad

- Converts your standard hook and loop pad into a soft polishing pad
- The foam adapter is 3/8" thick and is excellent for fine grits where minimal removal is required
- It is ideal for either flat or contour surfaces

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Polishing Adapter Pad			
5" Hook and Loop Adapter Pad	3,786	10	63642503121



Ergonomic Hand Sanders

- The ergonomic palm sander is uniquely designed to be user-friendly, with finger indentations for the operator
- It quickly converts standard 5" and 6" hook and loop discs into hand sanders for finishing flat surfaces

DESCRIPTION	STD. PKG.	PART #
Ergonomic Hand Sander		
5" Hook and Loop	5	63642503147
6" Hook and Loop	5	63642503726



Disc Hand Pads

- Hand pads eliminate finger sanding
- The ultra-thin 3/16" thick pad is composed of a single layer of neoprene foam and is designed for maximum flexibility – producing excellent finishes
- The 1" thick pad is composed of two layers, neoprene and polyester foam, for excellent conformability and softness, resulting in fine finishes
- Each pad has an elastic hand strap to hold it firmly in place.
- Available with either PSA (vinyl) faces or hook and loop face

DESCRIPTION	STD. PKG.	PART #
Disc Hand Pads		
5" x 3/16" Thick Soft Foam PSA	10	63642503111
5" x 1" Thick Soft Foam PSA	10	63642502842
5" x 1" Thick Soft Foam Hook and Loop	10	63642503117



Panel and Adhesive Cleaner

- Removes adhesives, tar, grease, wax, body sealers, undercoating sprays, and silicone from most surfaces
- Aggressive cleaner is safe to use on most paint applications
- Packaged with squirt dispenser
- Use as directed

DESCRIPTION	STD. PKG.	PART #
Panel and Adhesive Cleaner		
Quart Can	12	07660782780



CATEGORY DEFINITION

For use on random orbital and rotary sanders. The industry's highest performing film and foam finishing discs are engineered for composite, automotive, and other fine finishing applications. Norton microfinishing film discs produce superior finishes dry without sacrificing cut rate while Norton foam finishing discs are used moist to produce a semi-polished surface to reduce buffing time.

APPLICATIONS:	Film discs: final dry finishing of primed and painted surfaces, varnishes, composites, and gel coats before buffing Foam finishing discs: final moist finishing of clear coat, varnishes, composites, and gel coats before buffing Compounds and buffing pads: removes swirl marks and sand scratches
SIZE RANGE:	3", 5" and 6"
GRIT RANGE:	Film Discs: P800-P1500 Foam Discs: P1500, P2000, P3000

FEATURED PRODUCTS



NORTON PURE ICE FINISHING FILM Q175

BEST CHOICE FOR FINAL DRY FINISHING OF PRIMED AND PAINTED SURFACES, VARNISHES, COMPOSITES, AND GEL COATS

FEATURES	BENEFITS
■ White aluminum oxide grain and new patented resin system	■ Better life, cut rate, and finish
■ 3 mil polyester backing	■ Better flexibility and flatness of discs
■ Hook and loop attachment system	■ Quick, easy mounting and removal
■ Color-coded backprint by grit size	■ Easy grit identification



NORTON ICE FINISHING FOAM Q255

BEST CHOICE FOR MOIST FINISHING OF CLEAR COATS, VARNISHES, COMPOSITES, AND GEL COATS

FEATURES	BENEFITS
■ Integrated foam backing	■ Eliminate pigtails and costly re-work
■ Open mesh design	■ Conformable to contours
	■ Equal pressure distribution for quicker sanding
	■ Uniform scratch pattern
■ Produces a semi-polished finish	■ Quick and easy to buff out

AVAILABILITY

TIER:	BEST
BRAND:	Norton
TRADENAME:	PURE ICE Q175
ABRASIVE:	Aluminum Oxide
BACKING WEIGHT:	3 mil Polyester Film
OTHER:	P-Graded



TIER:	BEST
BRAND:	Norton
TRADENAME:	ICE Q255
ABRASIVE:	Aluminum Oxide
BACKING WEIGHT:	Foam
OTHER:	P-Graded

SIZE	GRIT	COLOR	MIN./STD. PKG.	PART #	MIN./STD. PKG.	PART #
3	P800	Black	50/200	77696088701	6/24 6/24	63642506022 63642506020
	P1000	Red	50/200	77696088702		
	P1200	Green	50/200	77696088703		
	P1500	Blue	50/200	77696088704		
	P3000	Green	50/200	77696088710		
5	P800	Black	50/200	77696088707		
	P1000	Red	50/200	77696088708		
	P1200	Green	50/200	77696088709		
	P1500	Blue	50/200	77696088710		
	P3000	Green	50/200	77696088711		
6	P800	Black	50/200	77696088713	15/60 15/60 15/60	63642506015 63642506014 63642506013
	P1000	Red	50/200	77696088714		
	P1200	Green	50/200	77696088715		
	P1500	Blue	50/200	77696088716		
	P2000	Magenta	50/200			
	P3000	Green	50/200			

Refer to the following page for back-up pads and accessories.



Norton Liquid Ice Extra-Cut Compound

- Water soluble; easy to use and easy to clean up
- Engineered to be used with a selection of 3 pads, depending on the finish required.

DESCRIPTION	STD. PKG.	STD. CASE	PART #
Quart – Norton Liquid Ice Extra-Cut Compound	1	4	63642597116



Norton Liquid Ice Ultra-Fine Machine Glaze

- Use on its own for fine scratch removal or as Step 3 in place of Norton Liquid Ice Extra-Cut to eliminate swirl marks and produce a high gloss finish
- Ideal for dark-colored vehicles

DESCRIPTION	STD. PKG.	STD. CASE	PART #
Quart – Norton Liquid Ice Ultra-Fine Machine Glaze	1	4	63642506092



8" and 9" Hook and Loop Buffing/Polishing Pads

- These pads can be used with Norton Liquid Ice Extra-Cut following the step numbers

DESCRIPTION	STD. PKG.	STD. CASE	PART #
8" Super Cut Wool Pad - Step 1	1	6	63642542077
9" Blue Cutting Foam Pad - Step 2	1	6	63642542078
9" White Finishing Foam Pad - Step 3	1	6	63642542079



Low-Profile Back-up Pads for Dual Action / Random Orbital Sanders

- Soft density low-profile pads utilize 1/2" thick foam for fine finish
- Shock-resistant and have a fiberglass backing plate with a riveted 5/16"-24 threaded shank for added strength/increased heat resistance.

DESCRIPTION	MAX. RPM	STD. CASE	PART #
3" Hook and Loop Soft Low-Profile	12,000	10	63642506128
6" Hook and Loop Soft Low-Profile	12,000	5	63642506130



Norton Liquid Ice Clean-up/ Detailer Spray

- The spray detailer easily cleans up excess buffing residue and produces paint protection
- Spray it on and wipe off with a Norton Microfiber cloth (see page 212)

DESCRIPTION	STD. PKG.	STD. CASE	PART #
32 oz. Spray Bottle Clean-up Detailer	1	4	63642542082



8" Hook and Loop Buffing/Polishing Waffle Pads

- These pads can be used with Norton Liquid Ice Extra-Cut.

DESCRIPTION	STD. PKG.	STD. CASE	PART #
8" Orange Waffle Foam pad - Step 1	1	6	63642506379
8" Blue Waffle Foam Pad - Step 2	1	6	63642506380
8" White Waffle Foam Pad - Step 3	1	6	63642506381



3" Hook and Loop Buffing/Polishing Pads

- For small spot repair.

DESCRIPTION	STD. PKG.	STD. CASE	PART #
3" Super Cut Wool Pad - Step 1	10	40	63642543832
3" Blue Cutting Foam Pad - Step 2	10	40	63642505459
3" White Finishing Foam Pad - Step 3	10	40	63642505460



Black Lamb'swool Hook and Loop Polishing Pads

- Distributing and applying material evenly and consistently, these dense, durable, lamb'swool pads are designed to repair clearcoat finishes.

DESCRIPTION	STD. CASE	PART #
3" Pad with Loop – 3/4" nap	40	63642503670
4" Pad with Loop – 3/4" nap	250	63642503671



Hook and Loop Back-up Pads for 8" and 9" Buffing Pads

- Black plastic back-up plate with hook and loop face. Moulded in 5/8"-11 threaded female hub.

DESCRIPTION	STD. PKG.	STD. CASE	PART #
8" and 9" Hook and Look Back-up Pad	1	3	63642542080



CATEGORY DEFINITION

Norton PSA (pressure sensitive adhesive) individual cloth discs and disc rolls are used on three different types of machines and the application changes depending on which two they are used on.

APPLICATIONS:	Electric Random Orbital Sanders – for use on contours or flat surfaces for light- to medium-pressure grinding, blending, leveling, and finishing applications Stationary Disc Sanders – used in woodworking and metalworking for stock removal, sanding/grinding flat surfaces, dimensioning and finishing
SIZE RANGE:	5" – 24" diameter
GRIT RANGE:	24 – 320
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide
BACK-UP PADS:	Rubber, with hardness variations for different applications, for portable machines. Steel for stationary disc sanders

FEATURED PRODUCTS



NORTON BLAZE R980P

BEST CHOICE FOR ALL HARD-TO-GRIND HIGH ALLOY STEELS

FEATURES

- Norton SG ceramic alumina abrasive
- Durable resin bond
- Self-lubricating supersize treatment
- Strong Y-weight polyester backing

BENEFITS

- Coolest cut; significantly faster cut rate
- Better grain adhesion, edge-fray resistance
- Cool cut on harder-to-grind materials
- Long life and consistent cut



NORTON BLUEFIRE R821P

BETTER CHOICE FOR GRINDING AND DEBURRING STAINLESS STEEL

FEATURES

- Self-sharpening, zirconia alumina abrasive
- Heavy Y-weight backing

BENEFITS

- Cooler cut, extended life over aluminum oxide discs
- Durable; reduced edge wear



NORTON METALITE R228

GOOD CHOICE FOR GENERAL PURPOSE METALWORKING

FEATURES

- Premium aluminum oxide abrasive
- Heavy X-weight backing

BENEFITS

- Long life
- Durable
- Ideal for aggressive stock removal applications
- Resistant to heat



Cloth PSA Discs for Random Orbital Sanders

AVAILABILITY

TIER:

BRAND:

TRADENAME:

ABRASIVE:

ATTACHMENT



BEST

Norton

BLAZE R980P

Ceramic Alumina

PSA Discs



GOOD

Norton

METALITE R228

Aluminum Oxide

PSA Discs



GOOD

Norton

METALITE R228

Aluminum Oxide

PSA Discs Roll

SIZE (D)	GRIT	MIN. / STD. PKG.	PART #	PART #	ROLLS/PKG / DISCS/ROLL	PART #
5	36	50/250	66254461506	66261136589		
	40	50/250	66254461507	66261136588		
	50	50/250	66254461508	66261136587	4/100	66261133252
	60	50/250	66254461509	66261136586	4/100	66261133253
	80	50/250	66254461510	66261136585	4/100	66261133254
	100	50/250		66261136584		
	120	50/250	66254461512	66261136583		
	150	50/250		66261136582		
6	180	50/250		66261136581		
	60	50/250		66261136596		
	80	50/250		66261136595		
	100	50/250		66261136594		
	120	50/250		66261136593		
8	180	50/250		66261136592		
	36	50/250		66261136350		
	40	50/250		66261136351		
	50	50/250		66261136352		
	60	50/250		66261136356		
	80	50/250		66261136354		
	120	50/250		66261136355		

Back-up Pads for Cloth PSA Discs

DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Back-up Pads for Cloth PSA Discs			
5" Diameter – Low Profile – Soft	12,000	5	63642506126
5" Diameter – Low Profile – Medium	12,000	5	63642506131
5" Diameter – Tapered – Medium	12,000	5	63642506139
6" Diameter – Low Profile – Soft	10,000	5	63642506127
6" Diameter – Low Profile – Med	10,000	5	63642506133
6" Diameter – Tapered – Medium	10,000	5	63642506141
8" Diameter – Tapered – Medium	6,000	5	63642543112





Large Diameter Cloth PSA Discs

Used on stationary disc machines for dimensioning and finishing metal workpieces and woodworking. Pressure sensitive adhesive offers fast, convenient mounting. Made without center holes for full-face usage.

AVAILABILITY



TIER:

BRAND

TRADENAME:

ABRASIVE:

ATTACHMENT:

			BEST	BETTER	GOOD
			Norton	Norton	Norton
			BLAZE R980P	BLUEFIRE R821P	METALITE R228
			Ceramic Alumina	Zirconia Alumina	Aluminum Oxide
			PSA	PSA	PSA
SIZE (D)	GRIT	MIN./STD. PKG.	PART #	PART #	PART #
10	36	25/50		66261138314	66261136606
	40	25/50			66261136604
	50	25/50			66261136607
	60	25/50			66261136602
	80	25/50			66261136601
	100	25/50			66261136600
12	24	25/50	66254416171 66254416172 66254416173 66254416174 66254416175 66254416176	66261138318	66261136635
	36	25/50		66261138319	66261136630
	40	25/50		66261138320	66261136625
	50	25/50		66261138321	66261136620
	60	25/50		66261138322	66261136615
	80	25/50		66261138323	66261136614
	100	25/50			66261136613
	120	25/50			
15	36	25/50			66261136666
	40	25/50			66261136665
	50	25/50			66261136714
	60	25/50			66261136663
	80	25/50			66261136662
16	36	25/50		66261138333 66261138334 66261109128	66261136700
	40	25/50			66261136685
	50	25/50			66261136684
	60	25/50			66261136683
	80	25/50			66261136701
18	36	25/50			66261136720
	60	25/50			66261136696
	80	25/50			66261136723
20	36	25/50	66254416165	66261138343	66261136710
	40	25/50	66254416167 66254416168 66254416169 66254416170	66261138344	66261136709
	50	25/50		66261138346	66261136711
	60	25/50			66261136712
	80	25/50			66261136706
	120	25/50			
24	36	10/10			66261136718
	40	10/10			66261136717
	50	10/10			66261136725
	60	10/10			66261136726
	80	10/10			66261136727



CATEGORY DEFINITION

Tool-free, twist-on and -off fastening systems make fast work of disc changes to maximize productivity by minimizing downtime.

APPLICATIONS:	Fiber and NorKut trimmable hard plastic discs: welding, grinding and blending; heavy metal removal; light deburring and finishing Cloth discs: light- to medium-pressure grinding; blending, leveling and finishing applications; for use on contours or flat surfaces
SIZE RANGE:	3/4" – 4" diameter
GRIT RANGE:	24 – 320
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide, Silicon Carbide
BACKING:	Fiber or cloth
CLOTH FLEX:	3-ply (more aggressive), 2-ply (standard), or 1-ply (more flexible) lamination
ATTACHMENT:	Type TS (II), Type TR (III), and Type TP (I)
BACK-UP PADS:	Rubber with hardness variations for different applications

COATED ABRASIVE QUICK-CHANGE DISC AVAILABILITY



Fiber

- The most heavy-duty discs with resin over resin construction on heavy-duty vulcanized fiber backing
- Premium grain for applications from heavy stock removal to surface blending



NorKut

- Unique polymer backing resists cracking and breakage and can be cut down up to the 1" core
- Use the cores to grind "pinch" welds and other hard-to-reach areas



Cloth 3-Ply

- These heavy-duty, 3-ply polyester laminate construction discs are the most aggressive and durable cloth discs on the market



Cloth 2-Ply

- Our standard 2-ply laminate construction creates an aggressive and durable cloth disc for flat surfaces



Cloth 1-Ply

- The flexible, 1-ply cotton laminate construction offers added conformability on contoured surfaces or any application where added flexibility is needed

QUICK-CHANGE ATTACHMENT SYSTEMS AND CROSS REFERENCE GUIDE

Each system enables quick, safe disc changes, reducing downtime and operating expenses.


Type TS (Type II)

- Features a turn-on/turn-off style fastener
- Fastener is made of metal
- Equivalent to Standard Abrasives' SocAtt® locking system



Type TR (Type III)

- Features a roll-on/roll-off style fastener
- Fastener is made of plastic
- Equivalent to 3M™ Roloc™ fastening system



Type TP (Type I)

- Features a snap-on/snap-off style fastener
- Fastener is made of nylon



NORTON

TS

TR

TP

MERIT

Type II

Type III

Type I


3M	Roloc TS/TSM	Roloc TR	Roloc TP
Standard	TS (SocAtt)	TR (Lockit)	TP (ClickOn)
Superior	Type S	Type R	—
Arc	Type S	Type R	Type P
Pferd	Type CD	Type CDR	—
Sait	SAIT-LOK	SAIT-LOK-R	—
Camel	Turn On	Roll On	—
Klingspor	QMC	QRC	—
Garryson	Type S	Type R	—



MATERIAL/APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity – Lowest Total Cost	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Low Initial Price
Stainless Steel / Titanium / Super Alloys	Norton Blaze R980P	Norton BlueFire R884P	Norton Neon R766
Mild Carbon Steel / Welds	Norton Blaze R980P	Norton BlueFire R884P	Norton Neon R766
Ferrous Metals / Cast Iron	Norton Blaze R980P	Norton BlueFire R884P	Norton Neon R766
Brass / Bronze / Aluminum	–	Norton BlueFire R884P	Norton Neon R766
Paint / Glue / Adhesive	–	–	Norton Neon R766
Concrete / Stone / Fiberglass	–	–	Merit Silicon Carbide

APPLICATION/GRIT RECOMMENDATION GUIDE



CROSS REFERENCE GUIDE

	TOTAL PERFORMANCE		INITIAL PRICE			
Abrasive	BEST Ceramic Alumina Full Ratio	Ceramic Alumina Full Ratio	BETTER Zirconia Alumina	GOOD Aluminum Oxide	Aluminum Oxide	Silicon Carbide
Backing	Fiber	Cloth	Cloth	Cloth	Cloth	Cloth
NORTON	Blaze F980	Blaze R980P	BlueFire R884P	Neon R766	–	–
MERIT	–	–	–	–	Aluminum Oxide	Silicon Carbide
3M	983C, 988C	963G, 977F, 785C, 777F	–	–	361F	461F
Standard	–	Ceramic Pro, Ceramic	Zirconia	A/O Extra, A/O Pro	A/O	Silicon Carbide
Superior	–	Ceramic G.A.	Premium Zirc	A/O with Grinding Aid	Premium A/O, Rigid Kut A/O	–
Arc	–	–	Zirconia/ Y Standard	A/O/X Plus Coolant	A/O/Y Premium	–
Pferd	Ceramic Oxide CO	Ceramic	ZA Z	Aluminum Oxide A-Plus, Aluminum Oxide A-INOX-FORTE	Aluminum Oxide A, A/O A-FORTE	Silicon Carbide SiC
Sait	–	–	Z	3A	2A-H, 2A	–
Camel	–	–	Zirconia A0	–	Aluminum Oxide	–
Klingspor	–	Ceramic	Alumina Zirconia	–	Aluminum Oxide	–
Garryson	–	Ceramic	–	–	Aluminum Oxide	–



FEATURED PRODUCTS



NORTON BLAZE F980 CERAMIC FIBER DISCS

BEST CHOICE FOR TOUGH APPLICATIONS AND STAINLESS STEEL

FEATURES AND BENEFITS

- Norton SG ceramic grain with self-lubricating, supersize treatment provides coolest cut with significantly faster cut rates
- Heaviest fiber backing, greater durability, longest life, and edge-fray resistance

AVAILABILITY

TIER:	BEST
BRAND:	Norton
TRADENAME:	BLAZE F980
ABRASIVE:	Ceramic Alumina
BACKING:	Fiber – Heavy Duty
OTHER:	Supersized
ATTACHMENT:	TR (Type III)



SIZE (D)	GRIT	STD. PKG.	PART #
2	24	25	77696090139
	36	25	66261058704
	50	25	66261058705
	60	25	66261058706
	80	25	66261058707
3	24	25	77696090140
	36	25	66261058708
	50	25	66261058709
	60	25	66261058711
	80	25	66261058712



NORTON NORKUT ZIRCONIA DISCS

BETTER CHOICE FOR HARD-TO-GROUND AREAS WHERE FLEXIBILITY IS NOT REQUIRED

FEATURES AND BENEFITS

- Zirconia alumina grain is resin bonded to a unique polymer backing which resists cracking and breaking and can be trimmed to the 1" core
- Use the cores to grind "pinch" welds and other hard-to-reach areas
- Used with a quick change mandrel: 7/16"-20 threaded for hand-held pneumatic grinders or 1/4" mandrel for automotive drills

AVAILABILITY

TIER:	BETTER
BRAND:	Norton
TRADENAME:	NORKUT
ABRASIVE:	Zirconia Alumina
BACKING:	Extra HD Polymer
ATTACHMENT:	Threaded Hole

SIZE (D)	GRIT	STD. PKG.	PART #
3	24	20	63642503656
	36	20	63642503657
	50	20	63642503658
7/16-20 Mandrel	-	5	63642503659
1/4" Mandrel	-	5	63642503660



NORTON BLAZE R980P CERAMIC CLOTH DISCS

BEST CHOICE FOR TOUGH APPLICATIONS AND STAINLESS STEEL (3-PLY) OR CONTOURED SURFACES (1-PLY)

FEATURES AND BENEFITS

- Next-generation, Norton SG ceramic alumina grain with self-lubricating, supersize treatment provides coolest cut and significantly faster cut rates
- 3-ply heavy-duty laminate discs (Y-weight polyester yellow backing) are more aggressive; for greatest durability, longest life, and edge-fray resistance on tough applications and stainless steel
- NEW! 1-ply laminate discs (black backing) provide durability and long life, but are more conformable and flexible; ideal on contoured surfaces or any application where added flexibility is needed. Used in aircraft and aerospace manufacturing for structural hand polishing.

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
BACKING:
OTHER:
ATTACHMENT:

	BEST	BEST	BEST	BEST	BEST	BEST	BEST
	Norton	Norton	Norton	Norton	Norton	Norton	Norton
	BLAZE R980P	BLAZE R980P	BLAZE R980P	BLAZE R980P	BLAZE R980P	BLAZE R980P	BLAZE R980P
	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina
	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester
	3-Ply Heavy Duty	1-Ply Conformable	3-Ply Heavy Duty	3-Ply Heavy Duty	3-Ply Heavy Duty	1-Ply Conformable	1-Ply Conformable
	Supersized	Supersized	Supersized	Supersized	Supersized	Supersized	Supersized
	TS (Type II)	TS (Type II)	TR (Type III)	TR (Type III)	TR (Type III)	TR (Type III)	TR (Type III)

SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #
1-1/2	36	100	66261162307	77696088201	66261162308	
	50	100	66261162309	77696088202	66261162310	
	60	100	66261162311	77696088203	66261162312	
	80	100	66261162313	77696088204	66261162314	
	120	100	66261043379	77696088206	66261043380	
2	36	25	66261162317	77696088207	66261162318	77696088219
	50	25	66261162319	77696088208	66261162320	77696088220
	60	25	66261162321	77696088209	66261162322	77696088221
	80	25	66261162323	77696088210	66261162324	77696088222
	100	25	66261043382	77696088211	66261043383	77696088223
3	120	25	66261043384	77696088212	66261043386	77696088224
	36	25	66261162327	77696088213	66261162328	77696088225
	50	25	66261162329	77696088214	66261162330	77696088226
	60	25	66261162331	77696088215	66261162332	77696088227
	80	25	66261162333	77696088216	66261162334	77696088228
	100	25	66261043389	77696088217	66261043390	77696088229
	120	25	66261043391	77696088218	66261043392	77696088230





NORTON BLUEFIRE R884P ZIRCONIA CLOTH DISCS

BETTER CHOICE FOR SOFT METALS, WOOD, STAINLESS STEEL, AND CARBON

FEATURES AND BENEFITS

- Premium, versatile, self-sharpening zirconia alumina plus grain provides aggressive cut and up to 30% longer life than competitive zirconia alumina product
- Strong resin bond improves base adhesion and reduces grain shedding
- Advanced grain coating results in longer life and faster cut rate
- Semi-open coat retards loading on soft metals (aluminum, brass, and bronze) and wood, as well as stainless steel and carbon steel
- Durable, Y-wt, 2-ply polyester backing stands up to demanding applications: high-pressure and hard-to-grind exotic alloy

AVAILABILITY

TIER:	BETTER	BETTER
BRAND:	Norton	Norton
TRADENAME:	BLUEFIRE R884P	BLUEFIRE R884P
ABRASIVE:	Zirconia Alumina	Zirconia Alumina
BACKING:	Polyester Standard	Polyester Standard
ATTACHMENT:	TS (Type II) 	TR (Type III) 

SIZE (D)	GRIT	STD. PKG.	PART #	PART #
1	50	100	66261138609	
	60	100	66261138608	
	80	100	66261138607	
1-1/2	36	100	66261138624	66261121041
	50	100	66261138622	
	60	100	66261138621	66261121043
	80	100	66261138620	66261121044
2	24	25	66261138638	66261138672
	36	25	66261138637	66261138671
	50	25	66261138635	66261138670
	60	25	66261138634	66261121048
	80	25	66261138633	66261121049
3	24	25	66261138665	66261138675
	36	25	66261138664	66261138674
	50	25	66261138662	66261138673
	60	25	66261138661	66261121053
	80	25	66261138660	66261121054
4	36	25	66261138683	
	50	25	66261138681	
	60	25	66261137343	
	80	25	66261138679	



Merit Quick-Change Test Kit "D"

- Part # 08834165001
- Includes 150 discs, assorted grits, in 1", 2", and 3" diameters and 3" back-up pads
- Primarily aluminum oxide cloth quick-change discs
- Several zirconia alumina and FlexEdge discs are included



VENDIBLE

NORTON NEON R766 ALUMINUM OXIDE CLOTH DISCS


GOOD CHOICE FOR DIFFICULT-TO-GRIND MATERIALS THAT REQUIRE AN ECONOMICAL OPTION

FEATURES AND BENEFITS

- Premium abrasive and aluminum oxide blend for aggressive cut and longer life than competitive aluminum oxide discs
- Durable Y-weight 2-ply polyester backing and new grain coating for longer life and faster cut rate on moderately-demanding applications
- Great for difficult-to-grind materials (aluminum, brass, bronze, stainless, carbon steel, and titanium) and applications requiring an economical option
- NEW! vendible packs, ideal for vending machines, small jobs, or carrying to a job site

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
BACKING:
ATTACHMENT:



GOOD

Norton

NEON R766

Aluminum Oxide

Polyester Standard

TS (Type II)



GOOD

Norton

NEON R766

Aluminum Oxide

Polyester Standard

TR (Type III)



GOOD

Norton

NEON R766

Aluminum Oxide

Polyester Standard

TP (Type I)



SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #
3/4	36	100			66623318933
	50	100			66623318935
	80	100			66623318937
1	36	100	66623318957		66623318950
	40	100			66623318951
	50	100	66623318959		66623318952
	60	100	66623318960		66623318953
	80	100	66623318961		66623318956
1-1/2	36	100	66623318972	66623318977	66623318967
	40	100	66623318973	66623318978	66623318968
	50	100	66623318974	66623318979	66623318969
	60	100	66623318975	66623318980	66623318970
	80	100	66623318976	66623318981	66623318971
2	24	100	66623319011	66623319013	66623319010
	36	100	66623318999	66623319005	66623318993
	40	100	66623319000	66623319006	66623318994
	50	100	66623319001	66623319007	66623318995
	60	100	66623319003	66623319008	66623318996
	80	100	66623319004	66623319009	66623318997
2	36	40 ✓	66623341058	66623341059	
	40	40 ✓	66623341060	66623341061	
	50	40 ✓	66623341062	66623341063	
	60	40 ✓	66623341064	66623341065	
	80	40 ✓	66623341066	66623341067	
3	24	50	66623319020	66623319026	66623319014
	36	50	66623319021	66623319027	66623319015
	40	50	66623319022	66623319028	66623319016
	50	50	66623319023	66623319029	66623319017
	60	50	66623319024	66623319030	66623319018
	80	50	66623319025	66623319031	66623319019
3	36	20 ✓	66623341072	66623341073	
	40	20 ✓	66623341074	66623341075	
	50	20 ✓	66623341076	66623341077	
	60	20 ✓	66623341078	66623341079	
	80	20 ✓	66623341080	66623341081	
4	36	50		66623319036	
	60	50			66623319033

✓ = VENDIBLE PACKAGE. 2" DISCS: 10 DISCS PER PACK / 4 PACKS PER CARTON. ORDER IN MULTIPLES OF 40.

✓ = VENDIBLE PACKAGE. 3" DISCS: 5 DISCS PER PACK / 4 PACKS PER CARTON. ORDER IN MULTIPLES OF 20.



MERIT ALUMINUM OXIDE CLOTH DISCS

GOOD CHOICE WHEN INITIAL PRICE IS THE PRIMARY CONSIDERATION

FEATURES AND BENEFITS

- Premium abrasive and aluminum oxide blend for aggressive cut and longer life than competitive aluminum oxide discs
- Durable Y-weight 2-ply polyester backing and new grain coating for longer life and faster cut rate on moderately-demanding applications
- Great for difficult-to-grind materials (aluminum, brass, bronze, stainless, carbon steel, and titanium) and applications requiring an economical option

AVAILABILITY

TIER:
BRAND:
ABRASIVE:
BACKING:
ATTACHMENT:

SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #
3/4	24	100	69957399601	69957399669	69957399737
	36	100	69957399602	69957399670	69957399738
	40	100	69957399603	69957399671	69957399739
	50	100	69957399604	69957399672	69957399740
	60	100	69957399605	69957399673	69957399741
	80	100	69957399606	69957399674	69957399742
	100	100	69957399607	69957399675	69957399743
	120	100	69957399608	69957399676	69957399744
	150	100	69957399609	69957399677	69957399745
	180	100	69957399610	69957399678	69957399746
	240	100	69957399611	69957399679	69957399747
	320	100	69957399612	69957399680	69957399748
1	24	100	69957399613	69957399681	69957399749
	36	100	69957399614	69957399682	69957399750
	40	100	69957399615	69957399683	69957399751
	50	100	69957399616	69957399684	69957399752
	60	100	69957399617	69957399685	69957399753
	80	100	69957399618	69957399686	69957399754
	100	100	69957399619	69957399687	69957399755
	120	100	69957399620	69957399688	69957399756
	150	100	69957399621	69957399689	69957399757
	180	100	69957399622	69957399690	69957399758
	240	100	69957399623	69957399691	69957399759
	320	100	69957399624	69957399692	69957399760
1-1/2	24	100	69957399625	69957399693	69957399761
	36	100	69957399626	69957399694	69957399762
	40	100	69957399627	69957399695	69957399763
	50	100	69957399628	69957399696	69957399764
	60	100	69957399629	69957399697	69957399765
	80	100	69957399630	69957399698	69957399766
	100	100	69957399631	69957399699	69957399767
	120	100	69957399632	69957399700	69957399768
	150	100	69957399633	69957399701	69957399769
	180	100	69957399634	69957399702	69957399770
	240	100	69957399635	69957399703	69957399771
	320	100	69957399636	69957399704	69957399772
2	24	100	69957399637	69957399705	69957399773
	36	100	69957399638	69957399706	69957399774
	40	100	69957399639	69957399707	69957399775
	50	100	69957399640	69957399708	69957399776
	60	100	69957399641	69957399709	69957399777
	80	100	69957399642	69957399710	69957399778
	100	100	69957399643	69957399711	69957399779
	120	100	69957399644	69957399712	69957399780
	150	100	69957399645	69957399713	69957399781
	180	100	69957399646	69957399714	69957399782
	240	100	69957399647	69957399715	69957399783
	320	100	69957399648	69957399716	69957399784

CONTINUED



AVAILABILITY
CONTINUED

TIER:
BRAND:
ABRASIVE:
BACKING:
ATTACHMENT:



GOOD	GOOD	GOOD
Merit	Merit	Merit
Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
Polyester Standard	Polyester Standard	Polyester Standard

TS (Type II)	TR (Type III)	TP (Type I)

SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #
3	24	50	69957399649	69957399717	69957399785
	36	50	69957399650	69957399718	69957399786
	40	50	69957399651	69957399719	69957399787
	50	50	69957399652	69957399720	69957399788
	60	50	69957399653	69957399721	69957399789
	80	50	69957399654	69957399722	69957399790
	100	50	69957399655	69957399723	69957399791
	120	50	69957399656	69957399724	69957399792
	150	50	69957399657	69957399725	69957399793
	180	50	69957399658	69957399726	69957399794
	240	50	69957399659	69957399727	69957399795
	320	50	69957399660	69957399728	69957399796
4	36	50	69957399661	69957399729	69957399797
	40	50	69957399662	69957399730	69957399798
	50	50	69957399663	69957399731	69957399799
	60	50	69957399664	69957399732	69957399800
	80	50	69957399665	69957399733	69957399801
	100	50	69957399666	69957399734	69957399802
	120	50	69957399667	69957399735	69957399803
	180	50	69957399668	69957399736	69957399804



MERIT SILICON CARBIDE CLOTH DISCS
GOOD CHOICE FOR NON-FERROUS MATERIALS

FEATURES AND BENEFITS

- Sharp, silicon carbide abrasive
- X-weight 2-ply backing
- High initial cut and penetration for nonferrous materials

AVAILABILITY

TIER:
BRAND:
ABRASIVE:
BACKING:
ATTACHMENT:





GOOD	GOOD	GOOD
Merit	Merit	Merit
Silicon Carbide	Silicon Carbide	Silicon Carbide
Cotton Standard	Cotton Standard	Cotton Standard

TS (Type II)	TR (Type III)	TP (Type I)

SIZE (D)	GRIT	STD. PKG.	PART #	PART #	PART #
2	40	100	08834165252	08834164275	08834162166
	60	100	08834165254	08834164163	08834162168
	80	100	08834165255	08834166155	08834162169
	120	100	08834165257	08834164837	08834162171
	180	100	08834165259	08834167313	08834162173
3	40	50	08834165267	08834164277	
	60	50	08834165269	08834164850	
	80	50	08834165270	08834166159	08834162188
	120	50	08834165272	08834166160	08834162190
	180	50	08834165274	08834168177	08834164971



Quick-Change Back-up Pads



- Hard density pads are for aggressive cutting action
- Medium density pads are for all-purpose applications
- Soft density pads are used for contours and fine finishing work

DIAMETER/RPM	DENSITY	TS (TYPE II)	TR (TYPE III)	TP (TYPE I)
Quick-Change Back-up Pads				
9/16"		66261054014		66261054013
40,000 RPM				
3/4"	Medium	08834164206	08834164038	08834164001
40,000 RPM				
1"	Medium	08834164651	08834164037	08834164002
40,000 RPM				
1-1/2"	Hard	08834164622	08834164640	08834163996
30,000 RPM	Medium	08834164146	08834161174	08834164003
2"	Hard	08834164624	08834164643	08834163997
30,000 RPM	Medium	08834164198	08834164922	08834164004
	Soft	08834161625	08834164641	08834163949
3"	Hard	08834161626	08834164036	08834163998
20,000 RPM	Medium	08834164113	08834164949	08834164005
	Soft	08834164626	08834164644	08834163948
4"	Medium	08834164135	08834164655	08834164006
15,000 RPM				
Vendible Quick-Change Back-up Pads				
2" Vendible	Medium	66623341082	66623341083	
30,000 RPM				
3" Vendible	Medium	66623341084	66623341085	
20,000 RPM				




ALL QUICK-CHANGE BACK-UP PADS HAVE A 1/4" SOLID STEEL SHANK. STD. PKG. = 1
VENDIBLE 2" 10 DISCS/PACK; 3" 5 DISCS/PACK; 2" AND 3" 4 PACKS PER CARTON
TO ORDER NORTON QUICK-CHANGE BACK-UP PADS, SEE PAGE 183 (NON-WOVEN DISC SECTION)

Replacement Medium Density Rubber Pads for Quick-Change Back-up Pads

DIAMETER	MODEL #	TP (TYPE I)
Quick-Change Replacement Rubber Back-up Pads		
3/4"	RR75	08834164008
1"	RR10	08834164009
2"	RR20	08834164011
3"	RR30	08834164012
4"	RR40	08834164013

WHEN THE RUBBER PAD HAS WORN AWAY, BUT THE STEEL COMPONENTS OF YOUR QUICK-CHANGE BACK-UP ARE STILL SERVICEABLE, ORDER THESE REPLACEMENT RUBBER PADS. STD. PKG. = 1


Replacement Assemblies and Shanks for Quick-Change Back-up Pad



DESCRIPTION	STD. PKG.	PART #
Replacement Mandrels and Nut Assembly		
TP (Type I) Assembly RMN1 for 3/4 - 2	1	08834164015
TP (Type I) Assembly RMN3 for 3 - 4	1	08834164016
TS (Type II) & TR (Type III) Replacement 1/4" Shank	1	08834164303


ASSEMBLIES REPLACE ALL THE STEEL COMPONENTS OF A QUICK-CHANGE BACK-UP PAD. THIS SHANK REPLACES THE SCREW-IN 1/4" SOLID STEEL SHANK ONLY.

Extension Mandrels and Assembly



DIAMETER	MODEL #	LENGTH	STD. PKG.	PART #
Extension Mandrels and Assembly – TP (Type I)				
3/4 - 2"	EMN-14	4"	1	08834164017
3/4 - 2"	EMN-16	6"	1	08834164018
3/4 - 2"	EMN-18	8"	1	08834164019
3 - 4"	EMN-34	4"	1	08834164020
3 - 4"	EMN-36	6"	1	08834164026
3 - 4"	EMN-38	8"	1	08834164021


MNA-1 Pad Adapters



DISC DIAMETER	MODEL #	STD. PKG.	PART #
MNA-1 Pad Adapters – TP (Type I)			
3/4 - 2"	MNA 1/4-20 THD.	1	08834161176
3/4 - 2"	MNA 3/8-24	1	08834164055
3/4 - 2"	MNA 5/8-11	1	08834163001
3 - 4"	MNA 1/4-20	1	08834163002
3 - 4"	MNA 3/8-24	1	08834164041
3 - 4"	MNA 5/8-11	1	08834164028

CONVERT A TP (TYPE I) BACK-UP PAD 1/4" DIAMETER SOLID SHANK TO A THREADED SHANK


MNA-23 Pad Adapters



DISC DIAMETER	MODEL #	STD. PKG.	PART #
MNA-23 Pad Adapters – TS (Type II) and TR (Type III)			
3/4 - 4"	MNA-23 3/8-24 5/8"-11 THD.	1	08834162764

FOR USE ON A RIGHT ANGLE GRINDER: CONVERT TS (TYPE II) AND TR (TYPE III) BACK-UP PAD 1/4" DIAMETER SOLID SHANKS TO THREADED SHANKS. THE LARGER 5/8-11 ADAPTER (FOR 4-1/2" DISCS) IS USED ALONE TO CONVERT TO A 5/8-11 THREAD. THE 3/8-24 INSERT (FOR 4" DISCS) IS SCREWED INTO THE 5/8-11 ADAPTER TO CREATE A 3/8-24 THREAD ADAPTER.

1/4" Diameter Extension Mandrel



MODEL NO.	LENGTH	STD. PKG.	PART #
1/4" Diameter Extension Mandrel 1/4-20 Thread			
EM-144	4"	1	08834154185
EM-146	6"	1	08834154186
EM-148	8"	1	08834154187



CATEGORY DEFINITION


Paper sheets and rolls are engineered for optimum performance when sanding metal, wood, composites and painted surfaces. The sheets are packed in protective packaging to eliminate waste and permit easy, neat storage.

CATEGORIES:	All purpose, wood sanding, steartated (non-loading), waterproof, and heavyweight
APPLICATIONS:	Light-duty metal sanding, primer sanding, defect removal from painted surfaces, filler sanding, sanding and finishing of composites and fiberglass, bare wood sanding, sanding between sealer coats
SIZE RANGE:	Full Sheets, Cut Sheets, File Strips and Rolls
GRIT RANGE:	36 – 2500
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide, Silicon Carbide, and Garnet
PAPER WEIGHTS:	Heavy-weight – E; Light-weight – A and D


MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity – Lowest Total Cost	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Low Initial Price
Unfinished Metal	A275	–	PB273
Primed / Painted Surfaces / Between Coats	A275	A475	PB273
Fiberglass / Composites	A275	A475	PB273
Bare Wood	A275	–	A511, A513, A514
Clear Coat Sanding	T214, T401	–	T461
Sealer Sanding	A275	A475	PB273
Lacquer Sanding	T214, T401	T414	T461
Wet Sanding	T214, T401	T414	T461
Paint Stripping	A275, A259 (3X)	A475	A290
All Purpose Dry Sanding	A275, A259 (3X)	–	A212, A213, A211

APPLICATION/GRIT RECOMMENDATION GUIDE



RECOMMENDED BACKING WEIGHT





CROSS REFERENCE GUIDE

NORTON	3M	Hermes	Klingspor	Mirka	SIA	VSM
Stearated (Non-Loading)						
A975	734U, 735U, 765L, 334U	—	—	—	1950 siaspeed	—
A275 / A259 (3X)	216U, 334U	HC133	PS33	Royal, Royal Micro	1950 siaspeed	—
A475	405N, 414N, 415N/U	PSF-LL, SA168	PL35	Carat Flex, FineFlex	1701 sialac 1748 siarexx fine	CP131A
A290	236U	HCAB-LL	PS33, PL36	Bulldog Gold	1960 siarexx cut	KP911
PB273	Red, NX	—	PL36	GoldFlex	—	—
Waterproof						
T214	213Q	WAFlex28B	PS12	—	1913 siawat	—
T401	401Q	WSFlex16	PS11, PS14	Waterproof (A)	—	CP918A
T414	413Q	WSFlex16	PS11, PS14	Waterproof (A)	—	CP918A
T461	438Q, 431Q	WSFlex18C	PS11, PS14	—	1727 siawat	CP918C
All Purpose/Wood						
A211	230U, 240N, 346U	—	—	—	—	KP31C
A212	210N	HFB	PL31	—	—	—
A213	230N	HFB	PL31	—	—	KP31B
A511	110N	—	—	—	1400 sianor	—
A513	130N	GCAB	—	—	—	—
A514	140N	GCAB	—	—	—	—
Heavyweight Paper						
H875P	750U, 751U, 740I, 745I	—	—	Royal Coarse Cut	—	KP510E, KP709

Aluminum Oxide All-Purpose Sanding and Garnet Wood Sanding 9" x 11" Paper Sheets

AVAILABILITY
9 X 11
PAPER SHEETS

				GOOD	GOOD	GOOD	GOOD	GOOD	GOOD	GOOD
TIER:				Norton	Norton	Norton	Norton	Norton	Norton	Norton
BRAND:				A211	A213	A212	A213/A212 MULTISAND	A513	A511	A513/A511 WOODSAND
TRADENAME:				Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Garnet	Garnet	Garnet
ABRASIVE:				D-Weight	C-Weight	A-Weight	D-, C- & A-Weight	D- & C-Weight	A-Weight	D-, C- & A-Weight
BACKING WEIGHT:				P-Graded	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded
OTHER:										
SIZE (W x L)	GRIT	MIN./ STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #	PART #
9 x 11	36	25/125	66261100335							
	40	25/125	66261100330							
	50	50/250	66261100325							
	60	50/250		66261100320				66261101560		
	80	50/250		66261100315				66261101555	66261101505	07660701584*
	100	100/500		66261100295			07660700358*	66261101535	66261101500	07660701583*
	120	100/500		66261100290			07660700357*	66261101530	66261101495	07660701582*
	150	100/500		66261100285			07660700356*	66261101525	66261101490	07660701581*
	180	100/500			66261100245		07660700355*		66261101489	07660701580*
	220	100/500			07660700156		07660700354*		66261101488	07660701579*
	240	100/500								
	280	100/500								
	Asst•	100/500					07660700365*			

* PACKAGING STANDARDS: JOB PACKS: 25 SHEETS PER PACK / 10 PACKS PER STANDARD PACKAGE FOR A TOTAL OF 250 SHEETS

• ASSORTED CONTAINS 6 EACH OF 60, 100, 150 GRIT AND 7 EACH OF 220 GRIT



Stearated (Non-Loading) Aluminum Oxide and Silicon Carbide 9" x 11" Sheets

FEATURED PRODUCTS



NO-FIL NORTON ADALOX A275

THE BEST CHOICE FOR SANDING PAINTED SURFACES, COMPOSITES, PLASTICS OR ANY MATERIAL THAT TENDS TO LOAD

FEATURES

- Premium P-graded, heat-treated aluminum oxide abrasive
- Unique fiber-reinforced, B-weight latex-saturated backing
- Water-based stearate, non-pigmented, No-Fil coating
- Full resin adhesive bond

BENEFITS

- Superior life, fast cut rate, consistent finish
- 50-60% improvement in tear strength
- Exceptional flexibility, can be folded without cracking
- Provides maximum load resistance and extended life: no color transfer to work
- Provides exceptional resistance to abrasive grain shedding especially when folding to sand into corners; long life



NO-FIL NORTON DURITE A475

THE BETTER CHOICE FOR GEL COATS, HARD COMPOSITE SUBSTRATES, ABRASION-RESISTANT COATINGS, AND WOODWORKING APPLICATIONS

FEATURES

- P-graded, silicon carbide abrasive
- Water-based stearate, non-pigmented, No-Fil coating
- Fiber-reinforced, latex paper backing

BENEFITS

- Easy penetration of the hardest surfaces
- Resists loading for longest usable product life, no color transfer to work
- Provides flexibility and resistance to tearing

AVAILABILITY 9 X 11 PAPER SHEETS



BEST

Norton

A275 NO-FIL

Aluminum Oxide

B-Weight

P-Graded



BEST

Norton

A259 (3X) NO-FIL

Aluminum Oxide

B-Weight

P-Graded



BETTER

Norton

A475 NO-FIL

Silicon Carbide

B-Weight

P-Graded



GOOD

Merit

PB273 NO-FIL

Aluminum Oxide

B-Weight

P-Graded


SIZE (W x L)	GRIT	MIN./ STD. PKG.	PART #	PART #	PART #	PART #
9 x 11	60	50/250		07660702642*		
	80	50/250	66261131634	07660702641*	66254487393	66623311878
	100	100/500	66261131633	07660702640*	66254487394	66623311877
	120	100/500	66261131632	07660702639*	66254487395	66623311876
	150	100/500	66261131631	07660702638*	66254487396	66623311875
	180	100/500	66261131630	07660702637*	66254487397	66623311874
	220	100/500	66261131629	07660702636*	66254487398	66623311873
	240	100/500	66261131628		66254487399	66623311879
	280	100/500	66261131627			
	320	100/500	66261131626	07660702633*	66254487400	66623311871
	400	100/500	66261131624	07660702632*		66623311870
	500	100/500	66261131623			
	600	100/500	66261131622			
	800	100/500	66261131621			
	1000	100/500	66261131620			
	1200	100/500	66261131619			
	1500	100/500	66261131618			

* PACKAGING STANDARDS: A259 (3X) JOB PACKS: 20 SHEETS PER PACK / 10 PACKS PER STANDARD PACKAGE FOR A TOTAL OF 200 SHEETS



Waterproof Aluminum Oxide and Silicon Carbide 9" x 11" Sheets

FEATURED PRODUCTS



NORTON BLACK ICE T214 AND T401 WATERPROOF

BEST CHOICE FOR ALL WET APPLICATIONS


FEATURES

- T214: Premium, P-graded, heat-treated aluminum oxide abrasive
- T401: Premium, ultra fine (1000 – 2500 JIS graded) silicon carbide abrasive
- Improved resin bond system
- High-strength B-weight high-latex, waterproof paper backing

BENEFITS

- Ultimate cut and life in wet applications
- Ultimate finish in wet applications
- Long life in wet applications
- Ultimate flexibility, with wet-curl resistance
- Environmentally stable, resists humidity-caused curling

AVAILABILITY
9 X 11
PAPER SHEETS



TIER:

BRAND:

CAP CODE:

ABRASIVE:

BACKING WEIGHT:

OTHER:

SIZE (W x L)	GRIT	MIN./STD. PKG.	PART #	PART #	PART #	PART #
9 x 11	60	50/250				66261101175
	80	50/250				66261101170
	100	50/250				66261101165
	120	50/250				66261101160
	150	50/250				66261101155
	180	50/250				66261101150
	220	50/250	66261139389		66261139367	
	240	50/250	66261139388		66261139366	66261130331
	280	50/250			66261139365	
	320	50/250	66261139386		66261139364	66261130332
	360	50/250			66261139363	
	400	50/250	66261139385		66261139362	66261130333
	500	50/250	66261139384		66261139361	
	600	50/250	66261139383		66261139360	66261130334
	800	50/250	66261139382			
	1000	50/250		66261139381		
	1200	50/250		66261139380		
	1500	50/250		66261139379		
	2000	50/250		66261139378		
	2500	50/250		66261139377		

Waterproof Sanding Blocks – with “grabbing” power


Dual Density Wet Sanding Block

- No adhesive required: simply wrap a 5-1/2" x 9" (9" x 11" cut in half) sheet around the block
- The dense side is for more aggressive blocking, while the soft side is for color sanding
- Equalizes sanding pressure for fine grit applications

Holey Block

- No adhesive required: simply wrap a 5-1/2" x 9" (9" x 11" cut in half) sheet around the block
- A rugged, semi-rigid, multi-purpose sanding block engineered for flat to medium curved surfaces
- A tactical hole pattern side provides numerous cutting edges to create a 30% faster cut rate
- The plain side provides firmness and a comfortable, easy-to-hold surface


DESCRIPTION	STD. PKG.	PART #
Wet Sanding Block	12	63642503728
Holey Block	8	63642503729





File Strips / Hand Sanding Cut Sheets / Rolls

FEATURED PRODUCTS



NORTON BLUEFIRE H875P

EXCELLENT FOR SOFT MATERIAL APPLICATIONS

FEATURES

- Patented zirconia abrasive
- Strong E-weight paper, latex impregnated
- Open coat design

BENEFITS

- Extended life over original NorZon products
- Increased durability and chip resistance, flexible
- Reduced loading; ideal for body filler, fiberglass, composite sanding


AVAILABILITY PAPER FILE STRIPS

TIER:
BRAND:
CAP CODE:
ABRASIVE:
BACKING WEIGHT:
BACKING ATTACHMENT:
OTHER:



BEST

Norton




BEST

Norton



BEST

Norton




BEST

Norton




BEST

Norton



BETTER

Norton



BETTER

Norton



BETTER

Norton

SIZE (W x L)	GRIT	MIN/ STD. PKG.	PART #	PART #	PART #	PART #	MIN/ STD PKG	PART #	PART #	MIN/ STD PKG	PART #
2-3/4 x 16	100	50/500				66261131657					
	120	50/500				66261131656					
	180	50/500				66261131654					
2-3/4 x 16-1/2	36						50/250		66261123610	25/125	66261123616
	40						50/250		66261123609	25/125	66261123615
	80	50/500		66261131640	66261131646		50/250		66261123608	25/125	66261123614
	100	50/500		66261131639	66261131645						
	120	50/500			66261131644						
	150	50/500		66261131637	66261131643						
	180	50/500		66261131636	66261131642						
2-3/4 x 17-1/2	36						50/250	66261123622			
	40						50/250	66261123621			
	80	50/500	66261131652				50/250	66261123620			
	100	50/500	66261131651				50/250	66261126512			
	120	50/500	66261131650								
	150	50/500	66261131649								
	180	50/500	66261131648				50/250	66261126511			
	220	50/500	66261131647								



VACUUM HOLE PATTERN FOR
2-3/4 X 16 FILE STRIPS

Sanding Boards

PSA/Non-PSA Sanding Board

- This sanding board has a cushioned surface
- Spring clips mounted at each end securely hold 2-3/4" x 16-1/2" PSA file strips and 2-3/4" x 17-1/2" non-PSA file strips

Hook and Loop and Non-PSA Sanding Board

- Lightweight, rugged design for easy sanding of plastic fillers
- Spring clips mounted at each end securely hold 2-3/4" x 16-1/2" hook and loop file strips and 2-3/4" x 17-1/2" non-PSA file strips
- Air file shoe eliminates the need for clips. The quick-change backing positively locks and unlocks for fast use.

DESCRIPTION	STD. PKG.	PART #
Hook and Loop/Non-PSA File Strip Sanding Board	5	63642552836
Hook and Loop Air File Shoe	5	63642552835
PSA/Non-PSA File Strip Sanding Board	6	63642542724



AVAILABILITY PAPER CUT SHEETS



TIER:	GOOD	GOOD
BRAND:	Norton	Norton
CAP CODE:	A290 NO-FIL	A213
ABRASIVE:	Aluminum Oxide	Aluminum Oxide
BACKING WEIGHT:	C-Weight	C-Weight
OTHER:	P-Graded	P-Graded

SIZE (W x L)	GRIT	MIN./STD. PKG.	PART #	PART #
3-2/3 x 9	60	100/1000		66261102925
	80	100/1000	66261101119	66261102920
	100	100/1000		66261102900
	120	100/1000		66261102895
	180	100/1000	66261101124	
	220	100/1000	66261101123	



Rubber Hand Sanding Blocks


- Resilient rubber blocks that conform well to mild contours and flat surfaces

DESCRIPTION	STD. PKG.	PART #
2-3/4 x 5	5	07660701889

AVAILABILITY PSA AND HOOK AND LOOP PAPER ROLLS



TIER:	BEST	BEST	BEST	BETTER	BETTER	BETTER	BETTER
BRAND:	Norton	Norton	Norton	Norton	Norton	Norton	Norton
CAP CODE:	A975 NO-FIL	A975 NO-FIL	A975 NO-FIL	A275 NO-FIL	A275 NO-FIL	A275 NO-FIL	A275 NO-FIL
ABRASIVE:	Ceramic Alumina	Ceramic Alumina	Ceramic Alumina	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
BACKING WEIGHT:	C-Wt.	C-Wt.	B-Wt.	B-Wt.	B-Wt.	B-Wt.	B-Wt.
BACKING ATTACHMENT:	PSA	PSA	PSA	PSA	PSA	PSA	PSA
OTHER:	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded
SIZE:	2-3/4" x 25yd	2-3/4" x 30yd	2-3/4" x 45yd	2-3/4" x 25yd	2-3/4" x 30yd	2-3/4" x 45yd	4-1/2" x 10 yd



TIER:	BEST	GOOD
BRAND:	Norton	Merit
CAP CODE:	A975 NO-FIL	PB273 NO-LOAD
ABRASIVE:	Ceramic Alumina	Aluminum Oxide
BACKING WEIGHT:	B-Wt.	B-Wt.
BACKING ATTACHMENT:	Hook & Loop*	Hook & Loop•
OTHER:	P-Graded	P-Graded
SIZE:	2-3/4" x 13 yd	3" x 12 yd

GRIT	MIN./STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #	MIN/STD PKG	PART #	PART #
80	1/5	66261149566			66261131691			66261131697	1/4	63642506261	66623345609
100	1/5					66261131690		66261131696			
120	1/5		66261149564			66261131689		66261131695	1/4	63642506259	66623334493
150	1/5			66261149563				66261131688	1/4	63642506258	66623334494
180	1/5			66261149562				66261131687	1/4	63642506257	66623334495
220	1/5			66261149561				66261131686	1/4	63642506256	66623334561
240	1/5							66261131685			
320	1/5			66261149558				66261131683	1/4	63642506255	66623335601
400	1/5			66261149557				66261131681	1/4	66623329518	666233345612
500									1/4	66623329547	
600	1/5							66261131679	1/4	66623329548	

* THE 2-3/4" WIDE HOOK AND LOOP PAPER ROLL IS PERFORATED AT 2-3/4" WHICH ALLOWS USE ON ALL STANDARD LENGTHS OF HAND BLOCKS AND FILE BOARDS.

• THE 3" WIDE HOOK AND LOOP PAPER ROLL IS PERFORATED AT 4-1/4" TO ALLOW FOR USE ON DYNABRADE® "DYNABUG II®" TOOL.

Roll Accessories



PSA Roll Dispenser

- Heavy-duty wire dispenser has a vinyl coating to protect the work surface
- Accommodates two 2-3/4" PSA rolls; stackable for multi-grit operations. Attach to wall or mount on cabinet



PSA/Hook & Loop Sanding Blocks

- Ergonomically-shaped flexible foam blocks used with 2-3/4" rolls, fit comfortably in your hand
- Firm block produces a truly flat surface
- The soft block is designed for flat surfaces and contours


DESCRIPTION	STD. PKG.	PART #
PSA Roll Dispenser	1	63642542773

BACKING ATTACHMENT:			PSA	HOOK & LOOP
SIZE	DESCRIPTION	STD. PKG.	PART #	PART #
2-3/4 x 5	Soft	5	63642542090	63642542092
2-3/4 x 5	Firm	5	63642542091	63642542093
2-3/4 x 7-3/4	Soft	5		63642542095
2-3/4 x 7-3/4	Firm	5	63642542094	



Rotolo Foam Sanding Pads

APPLICATION/GRIT RECOMMENDATION GUIDE



FEATURED PRODUCTS



NO-FIL NORTON ADALOX A275 ROTOLO FOAM ROLLS

THE BETTER CHOICE FOR FINE SANDING FLAT AND CURVED SURFACES

FEATURES

- A275 (premium P-graded, aluminum oxide grain with No-Fil coating) on Rotolo foam backing
- 4-1/2" wide x 82' long roll perforated every 5-1/2"
- Convenient dispensing box

BENEFITS

- Perfect for hand sanding without leaving finger marks
- Provides outstanding finish on wood, metal, composites, primers, sealers, and top coats
- Fast cut and long life without loading
- Compatible with all coatings
- 50% – 60% improvement in tear strength
- Standard 1/4 sheet size for hand or machine sanding
- 178 sheets per roll
- Protects A275 Rotolo foam from damage

AVAILABILITY

TIER:	BETTER
BRAND:	Norton
TRADENAME:	ROTOLO
ABRASIVE:	Aluminum Oxide

SIZE (W x L)	GRIT SIZE	ROLLS/STD. PKG.	PART #
4-1/2" x 82'	P120	2	63642535316
	P150	2	63642557584
	P180	2	63642557599
	P220	2	63642557600
	P240	2	63642557602
	P280	2	63642557604
	P320	2	63642557606
	P400	2	63642557608
	P500	2	63642557611
	P600	2	63642557612
	P800	2	63642557613
	P1000	2	63642557616





CATEGORY DEFINITION

Engineered for flexibility and fast cutting, cloth sheets and rolls have a longer life than paper. They tear cleanly and straight without shedding and are packed in a protective dispenser to eliminate waste and damage.

CATEGORIES:	All purpose, fine finishing, and screen-back
APPLICATIONS:	Scouring and light deburring, scale and rust removal, blending and fine sanding, polishing lathe turnings, rolls and cylinders, and blending machine tool marks
SIZE RANGE:	Sheets: 9" x 11" Rolls: 1" x 10 yds., 1-1/2" – 2" x 25 yds., 1" – 4" x 50 yds.
GRIT RANGE:	40 – 600, extra coarse, coarse, medium, fine
ABRASIVE GRAIN:	Aluminum Oxide, Silicon Carbide, Emery

CROSS REFERENCE GUIDE

	GOOD Metalite K224/K225	Metalite K227	Emery K622	Screen-Bak Q421
NORTON				
3M	311T Three-M-lte BG 211K Electrocut	211K Three-M-lte 311K Three-M-lte	011k Crystal Bay	481Q
Hermes	RB317LX	RB232J	–	–
Klingspor	CS310X	KL361	KL371	–
Sait	DA-F	EA-F	–	Saitscreen
SIA	–	2947J	C680J	–
VSM	KK504X	KK504J, KK504X	–	–

APPLICATION/STARTING RECOMMENDATION GUIDE

Durability/Stock Removal	Conformability	Slower Cut	Waterproof
Fast Cut	Excellent Finish	Fine Finish	Load Resistant
Metalite K224/K225	Metalite K227	Emery K622	Screen-Bak Durite Q421

AVAILABILITY
CLOTH SHEETS

		GOOD		GOOD		GOOD		GOOD	
		Norton		Norton		Norton		Norton	
		METALITE K224/K225		METALITE K227		EMERY K622		SCREEN-BAK Q421	
		Aluminum Oxide		Aluminum Oxide		Emery		Silicon Carbide	
		P-Graded		P-Graded				P-Graded/Waterproof	
SIZE (W x L)	GRIT	MIN./STD. PKG.	PART #	PART #	PART #	PART #	MIN./STD. PKG.	PART #	PART #
9 x 11	40	25/125	66261058713						
	50	25/125	66261101862						
	60	25/125	66261101861						
	80	25/125	66261126340	66261101750			25/125	66261100960	
	100	50/250	66261126339	66261101745			25/125	66261100955	
	120	50/250	66261126338	66261101740			25/125	66261100950	
	150	50/250	66261126337	66261101735			25/125	66261100945	
	180	50/250	66261126336	66261101730			25/125	66261100940	
	220	50/250	66261126335				25/125	66261100935	
	240	50/250	66261126334						
	280	50/250	66261126333	66261101720					
	320	50/250	66261126332	66261101710			25/125	66261100920	
	400	50/250	66261126331	66261101705			25/125	66261100915	
	500	50/250		66261101700					
	600	50/250	66261126330						
	Extra Coarse	25/125			66261101255				
	Coarse	25/125			07660701307				
	Medium	50/250			07660701309				
	Fine	50/250			07660701308				



AVAILABILITY CLOTH ROLLS

TIER:	GOOD				
BRAND:	Norton				
TRADENAME:	METALITE K224/K225	METALITE K224/K225	METALITE K224/K225	METALITE K224/K225	METALITE K224/K225
ABRASIVE:	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
SIZE:	1" x 10 yds	1" x 50 yds	1-1/2" x 50 yds	2" x 50 yds	4" x 50 yds
OTHER:	P-Graded	P-Graded	P-Graded	P-Graded	P-Graded
GRIT	MIN./STD. PKG.	PART #	PART #	PART #	PART #
40	1/5		66261058716	66261058715	66261058714
50	1/5		66261127728	66261127730	66261127732
60	1/5		66261127729	66261127731	66261127733
80	1/5	66261134298	66261126276	66261126288	66261126299
100	1/5	66261134299	66261126275	66261126287	66261126298
120	1/5	66261134300	66261126274	66261126286	66261126297
150	1/5	66261134301	66261126273	66261126285	66261126296
180	1/5	66261134302	66261126272	66261126284	66261126295
220	1/5		66261126271	66261126283	66261126294
240	1/5	66261134303	66261126270	66261126282	66261126293
280	1/5		66261126269	66261126281	66261126292
320	1/5	66261134304	66261126268	66261126280	66261126291
400	1/5		66261126267	66261126279	66261126290
600	1/5		66261126266	66261126278	66261126289

* PACKAGING STANDARDS: 4" ROLL MIN. /STD. PKG.: 6

AVAILABILITY CLOTH ROLLS

TIER:	GOOD				
BRAND:	Norton				
TRADENAME:	METALITE K227	METALITE K227	METALITE K227	SCREEN-BAK Q421	SCREEN-BAK Q421
ABRASIVE:	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Silicon Carbide	Silicon Carbide
SIZE:	1" x 50 yds	1-1/2" x 50 yds	2" x 50 yds	1-1/2" x 25 yds	2" x 25 yds
OTHER:	P-Graded	P-Graded	P-Graded	P-Graded Waterproof	P-Graded Waterproof
GRIT	MIN./STD. PKG.	PART #	PART #	PART #	PART #
80	1/5	66261109180	66261109255	66261109335	66261107275*
100	1/5	66261058721	66261058719	66261109330	
120	1/5	66261109170	66261109245	66261109325	66261107270*
150	1/5	66261058720	66261058717	66261109320	
180	1/5	66261109160	66261109235	66261109315	66261107265*
280	1/5	66261109150	66261109225	66261109305	
320	1/5	66261109140	66261109215	66261109295	

* PACKAGING STANDARDS: MIN. /STD. PKG.: (Q421) 1/10

FastTrack Service – Cloth Rolls


FastTrack delivery is available on made-to-order aluminum oxide R228 and K225 50-yard rolls with 5-day lead-time. Contact your local distributor for details and prices.

Availability

- Width: 2" – 12"
- Length: 50 yards

FastTrack Roll Quantity Availability

WIDTH	MINIMUM QTY.	MAXIMUM QTY.
2" to 9"	5 Rolls	10 Rolls
> 9" to 11"	4 Rolls	8 Rolls
>11" to 12"	3 Rolls	6 Rolls



CATEGORY DEFINITION


Flexible, abrasive sanding sponges for a wide variety of curved, contoured or flat surface applications on wood, metal, paint, plastic, ceramics and drywall.

APPLICATIONS: Light stock removal, sanding sealer and wash-coats, touch-up or repair of primer, sanding contours and intricate shapes, and finishing

BENEFITS:

- Can be used wet or dry
- Clog resistant, washable, reusable
- Easy to use, can be folded without cracking
- Conformable
- Generate a consistent surface finish

WHY CHOOSE ABRASIVE SPONGES VERSUS CONVENTIONAL SHEETS?



Eliminate Clogging

- The combination of flexible foam backing material and abrasive grit adhesion continually releases sanded material
- Any clogging can be washed out


Pressure Control

- Foam backing allows optimum pressure distribution to prevent sanding through surfaces
- Pressure spots are eliminated providing even surface pattern


Adapt to Contours

- Flexible foam allows adaptability to contours, shapes or areas of limited access
- No folding or buckling results in an even pattern without scratching

SURFACE FINISHING CHART – CONTOUR SPONGES VERSUS SHEETS



SURFACE FINISHING CHART – SPONGE PADS VERSUS SHEETS




CROSS REFERENCE GUIDE

	BETTER SoftTouch	GOOD Contour	GOOD Small Area	GOOD Profile	GOOD Sealer Sanding	GOOD Flexible
NORTON						
3M	Softback	Contour	Full Size	High Flexibility	Woodworking	Pro Pads
Hermes	Single Side	—	Four Sided	—	Two Sided	—
Klingspor	—	—	—	—	Foam Sanding Pad	—
SIA	Flat Pad	—	Standard Block	—	Standard Pad	—



FEATURED PRODUCTS AND AVAILABILITY



BETTER SOFTTOUCH CONTOUR SPONGES – COATED 1 SIDE

- Superior flexibility; for hand-sanding or finishing flat, curved, contoured and hard-to-reach areas on wood, metal, composites, paint and solid surfaces
- Premium foam substrate provides for an extremely smooth and uniform sanded surface

SIZE (W x L x T)	GRIT	STD. PKG.	PART #
4-1/2 x 5-1/2 x 3/16	60 Medium	80	07660703074
	100 Fine	80	07660703075
	180 Super Fine	80	07660703076
	220 Ultra Fine	80	07660703077
	280 Micro Fine	80	07660703078



GOOD CONTOUR SPONGES – COATED 1 SIDE

- Thin, flexible; good for sanding small diameters and contours such as ceramics, spindles, turnings and railings

SIZE (W x L x T)	GRIT	STD. PKG.	PART #
4-1/2 x 5-1/2 x 3/16	100 Fine	100	07660702257
	150 Extra Fine	100	07660702256
	220 Ultra Fine	100	07660702255



GOOD SMALL AREA GENERAL PURPOSE SPONGES – COATED 4 SIDES

- Good for a wide variety of materials and sanding applications where moderate flexibility is needed
- Medium to firm density open cell polyurethane foam provides uniform support and moderately aggressive cutting action while generating a smooth surface


SIZE (W x L x T)	GRIT	STD. PKG.	PART #	BULK PKG.	PART #
4 x 2-3/4 x 1	36/80	24	07660749505	250	07660704735
	Ex. Coarse/Med				
	80/80	24	07660749507	250	07660701875
	Med/Med				
	80/120	24	07660749504	250	07660702600
	Med/Fine				
	120/120	24	07660749506		
	Fine/Fine				



GOOD PROFILE SPONGES – COATED 3 SIDES

- Good for corners and flat surfaces on wood, metal, plastic and paint
- Ideal for cabinet sanding of raised profile doors

SIZE (W x L x T)	GRIT	STD. PKG.	PART #
4 x 2-3/4 x 1/2	100 Medium	500	63642536313



GOOD SEALER SANDING SPONGES – COATED 2 SIDES

- Very flexible; silicon carbide abrasive for sanding primers, sealers and between coats on furniture and cabinets

SIZE (W x L x T)	GRIT	BULK PKG.	PART #
4-3/4 x 3-3/4 x 1/2	80 Medium	250	63642502538
	100 Medium	250	63642552870
	150 Fine	250	63642552869
	220 Very Fine	250	63642552868



GOOD FLEXIBLE ABRASIVE SPONGES – COATED 1 SIDE

- Ideal for final sanding of surfaces, primer sanding, and between coats sanding
- Best initial price point for abrasive sponges

SIZE (W x L x T)	GRIT	STD. PKG.	PART #	BULK PKG.	PART #
3 x 4 x 1/2	60 Coarse	48	07660704068	108	07660701110
	80 Medium	48	07660704067	108	07660704070
	100 Medium	48	07660704066	108	07660700950
	150 Fine	48	07660704065	108	07660700949
	220 Very Fine			108	07660704069



CATEGORY DEFINITION

Portable file belt sanders have replaced tedious hand filing and sanding. First introduced in pneumatic, they are now available in electric. Increasingly, tool manufacturers are introducing additional fixtures for an increasing number of applications. The belts listed are popular stock sizes, but additional sizes, specifications, backing materials, and edge scallops are available made-to-order.

APPLICATIONS:	Light weld removal and blending, shape and contour sanding, surface preparation prior to coating and plating, removing cutting tool marks from molds and dies, general clean-up and finishing
SIZE RANGE:	1/8" to 1" wide, 12" to 30" long
GRIT RANGE:	40 – 120
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide

CROSS REFERENCE GUIDE

	BEST Blaze R980P	BEST Norton SG R981	BETTER BlueFire R887P/R823P	GOOD Metalite R283	GOOD Neon R766
NORTON					
3M	984F, 977F	963G, 967F	577F, 777F	241E	363F
Hermes	CR456	—	RB486 44 Z	RB317J, RB316EJ RB303 Flex	SB 378 YR
Klingspor	CS610YY	—	CS411YX, CS 409Y	CS310XF	CS412
SIA	—	—	—	933A, 936A	—
VSM	SK840X, SK750X	—	KK715X	KK711T, KK511J	KK711

MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	HEAVY-DUTY		GENERAL-DUTY	
	BEST Highest Productivity – Lowest Total Cost.	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Low Initial Price	
Carbon Steel	Norton Blaze R980P	Norton BlueFire R887P/R823P	Norton Neon R766	
Stainless Steel / Alloys	Norton Blaze R980P	Norton BlueFire R887P/R823P	Norton Neon R766	
Cast Iron	Norton Blaze R980P	Norton BlueFire R887P/R823P	Norton Neon R766	
Brass/Bronze	—	Norton BlueFire R887P/R823P	Norton Neon R766	
Aluminum	—	Norton BlueFire R887P/R823P	Norton Neon R766	

FEATURED PRODUCTS

**NORTON BLAZE R980P**

BEST FOR STAINLESS, COBALT, CHROME, INCONEL, TITANIUM, MILD AND CARBON STEEL

FEATURES

- Next-generation cooler cutting Norton SG ceramic alumina grain
- Y-weight polyester waterproof cloth backing
- Improved resin bond system
- Advanced "supersize" grinding lubricant

BENEFITS

- Lasts 50% to 200% longer on mild and carbon steel, stainless, cobalt, chrome, Inconel and titanium
- Better metal integrity
- Edge-fray resistance
- Improved body-retention during use for more consistent grinding throughout belt life
- Significantly improved belt life due to exceptional grain adhesion
- Cooler cutting during the life of the belt
- Improved part finish and integrity



FEATURED PRODUCTS

**NORTON BLUEFIRE R887/R823P**

THE BETTER CHOICE FOR STAINLESS AND CARBON STEEL

FEATURES

- High-performance, self-sharpening zirconia alumina abrasive
- High-performance resin bond
- Strong Y-weight polyester backing - R887P
- Flexible X-weight polyester backing - R823P

BENEFITS

- Industry-leading cut rate and life
- Strong grain adhesion, longer life
- For heavy-duty stock removal applications
- For moderate- to light-pressure applications

**NORTON NEON R766**

THE BETTER CHOICE FOR DIFFICULT-TO-GROUND MATERIALS (ALUMINUM, BRASS, BRONZE, STAINLESS, CARBON STEEL, TITANIUM, ETC.)

FEATURES

- Premium abrasive and aluminum oxide blend
- Resin bond system
- Y-weight waterproof polyester backing

BENEFITS

- Ideal when purchasing criteria is a good-performing, economically priced, general purpose belt
- Improved edge retention and 30% + improvement in life vs. key competitors
- Withstands light- to moderately-demanding applications
- Extended life on dry grinding applications

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
BACKING:
OTHER:



BEST	BEST	BETTER	GOOD	GOOD
Norton	Norton	Norton	Norton	Norton
BLAZE R980P	NORTON SG R981	BLUEFIRE R887/R823P	METALITE R283	NEON R766
Ceramic Alumina	Ceramic Alumina	Zirconia Alumina	Aluminum Oxide	Premium A/O Blend
Y-wt. Polyester	Y-wt. Polyester	Y-wt./X-wt. Polyester	X-wt. Rayon	Y-wt. Polyester
Supersize				

SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #
12" Belts							
1/8 x 12	40	50	66254491518	66254491521	66254492520	66254491536	66623390000
	60	50	66254405345	66254491522	66261093029		66623390001
	80	50	66261089479	66254491523	66261093030	66254491537	66623390002
	120	50	66254491519	66254491524	66254491533	66254491538	
1/4 x 12	40	50	66254491520	66254491525		66254491539	66623390003
	60	50	66261196480	78072760823			66623390004
	60	25 ✓			78072758896		
	80	50	66261063617	66254491526	78072782621	78072766143	66623390005
	8	25 ✓			66623373744		
	120	50	66261063632	66254491527	78072782622	78072763175	
1/2 x 12	40	50	69957398018	66254491528	66254492522	78072727557	66623390006
	50	50	66261043759	78072718700	66254492523	66254491540	66623390007
	60	50	69957398019	78072718701	78072728745	78072727555	66623390008
	60	25 ✓			66623373753		
	80	50	69957398020	78072718702	78072728744	78072727554	66623390009
	80	25 ✓			66623373754		
	100	50	66261081180	66254491529	66254491534	78072727553	
	120	50	66261042909	78072700518	78072728742	78072727552	
1 x 12	60	50	66261063641		66623373755		
					78072753073	78072773813	66623390010
13" Belts							
3/8 x 13	60	50	69957345359	78072745459	78072740295	78072732112	66623390011
	80	50	69957392150	78072774916	78072736062	78072771323	66623390012
18" Belts							
1/8 x 18	40	50	66254475211		66254492524	66254491541	66623390013
	60	50	66261080010		66254491535		66623390014
	80	50	66261089120	78072789083	78072760595	63642594761	66623390015
	120	50	66254475215	78072789084	63642595221	66254491542	

CONTINUED



AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:
BACKING:
OTHER:



BEST	BEST	BETTER	GOOD	GOOD
Norton	Norton	Norton	Norton	Norton
BLAZE R980P	NORTON SG R981	BLUEFIRE R887/R823P	METALITE R283	NEON R766
Ceramic Alumina	Ceramic Alumina	Zirconia Alumina	Aluminum Oxide	Premium A/O Blend
Y-wt. Polyester	Y-wt. Polyester	Y-wt./X-wt. Polyester	X-wt. Rayon	Y-wt. Polyester
Supersize				

SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #
18" Belts (continued)							
1/4 x 18	40	50	66261027923	66261198953	66254492525	66254491543	66623390016
	60	50	69957347249	78072774684	78072743583	78072771000	66623390017
	60	25 ✓			66623373747		
	80	50	69957346155	78072703284	78072753075	78072773921	66623390018
	80	25 ✓			66623373748		
	120	50	66261085071	78072785655	78072773764		
	120	25 ✓			66623373749		
1/2 x 18	40	50	69957398021	78072766018	66254444193	78072727561	66623390019
	60	50	69957398022	78072718704	78072728569	78072727560	66623390020
	60	25 ✓			66623373756		
	80	50	69957398023	78072718705	78072728568	78072727559	66623390021
	80	25 ✓			66623373757		
	120	50	66261041384	78072718706	78072728567	78072727558	
	120	25 ✓			66623373758		
3/4 x 18	40	50	69957398027	78072762476	66254492526	78072781797	66623390022
	60	50	69957398028	78072745691	78072709590	78072739966	66623390023
	60	25 ✓			66623373762		
	80	50	69957398029	78072756309	78072758953	78072732289	66623390024
	80	25 ✓			66623373763		
	120	25 ✓			66623373764		
20-1/2" Belts							
3/4 x 20-1/2	40	50	69957398030	78072714398	66254457869	78072727573	66623390025
	50	50	69957344982	78072718714	66254492527	66254491544	66623390026
	60	50	69957398031	78072718715	78072728560	78072727571	66623390027
	60	25 ✓			66623373765		
	80	50	69957398032	78072718716	78072728559	78072727570	66623390028
	80	25 ✓			66623373766		
	100	50	66261055516	78072771151	66261038911	78072727569	
	120	50	66261044755	78072727380	78072728557	78072727575	
	120	25 ✓			66623373767		
24" Belts							
1/4 x 24	40	50	66261198631	78072747823	66254473499	66254401929	66623390029
	60	50	69957345451	78072756534	78072728552	78072727548	66623390030
	60	25 ✓			66623373750		
	80	50	63642596940	78072718340	78072767713	66261085068	66623390031
	80	25 ✓			66623373751		
	120	50	66261080367	78072770718	78072728550	66261085069	
	120	25 ✓			66623373752		
1/2 x 24	40	50	69957398024	78072760092	66254492528	78072727568	66623390032
	50	50	66261043757	78072718707	66254452237	78072727567	66623346910
	60	50	69957398025	78072718708	78072728564	78072727566	66623390033
	60	25 ✓			66623373759		
	80	50	69957398026	78072718709	78072728566	78072727565	66623390034
	80	25 ✓			66623373760		
	100	50	66261042203	78072745021	78072753076	66254491545	
	120	50	66261042565	78072718710	78072728565	78072727564	
	120	25 ✓			66623373761		
1 x 24	40	50	69957350019	66254491531	66254492529	66254491546	66623390035
	50	50	69957344889	78072710374	66254492530	66254491547	66623390036
	60	50	69957353375	78072737318	78072798720	66254491548	66623390037
	80	50	69957345419	78072772209	78072776498	66261085068	66623334206
	120	50	66261085067	66254491532	78072730029	66261085069	
30" Belts							
1 x 30	40	50	66261053470	78072765229	66254478257	66261189958	66623390038
	60	50	69957345985		78072728583	66254491549	66623390039
	80	50	69957346105	78072764439	78072728582	78072727579	66623390040
	120	50	66261193676	78072781197	78072766992	78072727577	

ADDITIONAL SIZES, GRITS AND SCALLOPED EDGE BELTS ARE AVAILABLE MTO (MADE-TO-ORDER). PLEASE CONTACT YOUR LOCAL NORTON DISTRIBUTOR TO CHECK AVAILABILITY.

40 AND 50 GRIT BLUEFIRE BELTS ARE FURNISHED IN BLUEFIRE R887 (Y-WT POLYESTER); 60-120 GRITS ARE SUPPLIED IN BLUEFIRE R823P (X-WT. POLYESTER).

JOINTS AND FLEXES – ALL BELTS ARE PG JOINTED; A BUTT JOINT JOINED WITH FLEXIBLE TAPE FOR CONTOUR GRINDING.

✓ = VENDIBLE PACKAGE. IDEAL FOR VENDING MACHINES AND SMALL JOBS. 5 BELTS PER PACK / 5 PACKS PER CARTON. ORDER IN MULTIPLES OF 25.



CATEGORY DEFINITION

Portable belts are ideal for all your metal and woodworking applications. Choose 36 – 50 grits for rough/heavy-duty applications, 60 – 100 for intermediate, and 100 – 220 for finishing/polishing applications.

APPLICATIONS:	Grinding and finishing all metals, blending welds, sanding and finishing wood, glass seaming, and polishing
SIZE RANGE:	3" to 4" wide, 15-1/2" to 24" long
GRIT RANGE:	36 – 220
ABRASIVE GRAIN:	Ceramic Alumina, Zirconia Alumina, Aluminum Oxide

CROSS REFERENCE GUIDE

	BEST Norton SG R981	BETTER BlueFire R831	GOOD Metalite R215/R228/R255
NORTON			
3M	977F, 967F, 963G	777F, 577F	241D, 340D
Hermes	RB346MX	RB484Z	RB316XOP
Klingspor	CS610YY	CS411Y	CS311YX, CS310X, LS309XH
Sait	–	ZH	AOX, IAX
SIA	–	–	2903XO, 2905X, 2920X
VSM	SK855X	ZK713X	KK511X, KK711X, KK504X

MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	HEAVY-DUTY		GENERAL-DUTY
	BEST Highest Productivity – Lowest Total Cost	BETTER Excellent Blend of Performance & Price	GOOD Consistent Performance – Low Initial Price
Wood	–	Norton NorZon R831	Norton Metalite R215/R255
Stainless Steel / Carbon Steel	Norton SG R981	Norton NorZon R831	Norton Metalite R228
Brass / Bronze / Aluminum	–	Norton NorZon R831	Norton Metalite R215/R255

FEATURED PRODUCTS

**NORTON SG R981**

EXCEPTIONAL PERFORMANCE, ESPECIALLY ON HARD-TO-GRIND ALLOYS

FEATURES

- Norton SG ceramic abrasive
- Grinding-aid enhanced
- Strong Y-weight polyester, waterproof cloth backing

BENEFITS

- Exceptional life and value, especially on hard-to-grind alloys
- Longer life, cooler cut
- Improved grain adhesion, reduced edge-fray, and better body retention result in longer life and product consistency

**NORTON BLUEFIRE R831**

THE BETTER CHOICE FOR STAINLESS STEEL AND WOOD

FEATURES

- Premium, self-sharpening zirconia alumina
- Reversible butt splice
- Open-coat design, strong Y-weight cotton backing
- Packaged in convenient job packs

BENEFITS

- Aggressive abrasive, rapid cut rate, long life
- Use in either direction for longer life
- Reduced loading, extended life
- Ideal for small jobs, carrying cleanly to job sites, and mounting on showroom displays



Portable Belts for Belt Sanders

Portable electric belt sanders are used on wood, metal, and other materials, for applications ranging from stock removal to finishing. They consist of an electrical motor that turns a pair of drums on which an abrasive belt is mounted.

Belt sanders can be either hand-held, where the sander is moved over the material, or stationary (fixed), where the material is brought to the sanding belt.

AVAILABILITY



		JOBPACK		JOBPACK		JOBPACK	
		BETTER	GOOD	GOOD	GOOD	GOOD	GOOD
TIER:		Norton	Norton	Norton	Norton	Norton	Norton
BRAND:		BLUEFIRE R831	METALITE R255	METALITE R255	METALITE R255	METALITE R255	METALITE R255
TRADENAME:		Zirconia Alumina	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
ABRASIVE:		Plyweld	Plyweld	Plyweld	Plyweld	Plyweld	Plyweld
JOINT:		Open Coat	Open Coat	Open Coat	Open Coat	Open Coat	Open Coat
GRAIN COATING:							
OTHER:							UPC Bar Coded
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	STD. PKG.	PART #	PART #
3 x 18	36				5	78072780447	
	50	5*	07660749259	07660700964	10	78072727994	
	80	5*	07660749258	07660700968	10	78072727993	
	120	5*	07660749256	07660700969	10	78072727992	
3 x 21	36	5*	07660749266	07660701741			
	40				10	78072727927	
	50	5*	07660749265	07660701740	10	78072727926	
	60				10	78072727925	
	80	5*	07660749264	07660702064	10	78072727924	
	100	5*	07660749263		10	78072727923	
	120	5*	07660749262	07660702062	10	78072727922	
	220	5*		07660705287			
3 x 24	36	5*	07660749272	07660701743	5	78072781847	
	40				10	78072727937	
	50	5*	07660749271	07660701742	10	78072727936	
	60				10	78072727935	
	80	5*	07660749270	07660702067	10	78072727934	
	100	5*	07660749269	07660702066	10	78072727933	
	120	5*	07660749268	07660702065	10	78072727932	
4 x 24	36	5*	07660749278	07660701745	5	78072780438	
	40				10	78072727947	
	50	5*	07660749277	07660701744	10	78072727946	
	60				10	78072727945	
	80	5*	07660749276	07660702069	10	78072727944	
	100	5*	07660749275		10	78072727943	
	120	5*	07660749274	07660702068	10	78072727942	
	180	5*		07660705285			

*JOB PACK PACKING STANDARDS: 5 BELTS/JOB PACK; 5 JOB PACKS PER CARTON. ORDER BY NUMBER OF PACKS, IN MULTIPLES OF 5 PACKS.

Portable Belts for Pneumatic In-Line Drum Sanders

AVAILABILITY



		BEST		BETTER		GOOD		GOOD	
TIER:		Norton	Norton	Norton	Norton	Norton	Norton	Norton	Norton
BRAND:		SG R981	BLUEFIRE R823P	METALITE R215	METALITE R215	METALITE R215	METALITE R215	METALITE R228	METALITE R228
TRADENAME:		Ceramic Alumina	Zirconia Alumina	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
ABRASIVE:		Plyweld	Plyweld	Plyweld	Plyweld	Plyweld	Plyweld	Plyweld	Plyweld
JOINT:		Close Coat/Supersize	Close Coat	Open Coat	Open Coat	Open Coat	Open Coat	Closed Coat	Closed Coat
GRAIN COATING:									
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #
3-1/2 x 15-1/2	36	10	78072700783			78072721997			
	60	10	78072718750			78072722000			
	80	10	78072718751	78072753074				78072721995	
	120	10	78072718753						



CATEGORY DEFINITION

A wide selection of sizes and grits for most dimensioning, intermediate grinding and polishing applications.

APPLICATIONS: Benchstand and Backstand Belts: grinding and deburring of all metals, heavy stock removal, blending, dimensioning and shaping, polishing.

Centerless, Conveyor and Platen Belts: intermediate grinding stainless and carbon, moderate-pressure applications, dimensioning and finishing.

SIZE RANGE: 1" to 10" wide, 36" to 132" long

GRIT RANGE: 36 – 320

ABRASIVE GRAIN: Ceramic Alumina, Zirconia Alumina, Aluminum Oxide

CROSS REFERENCE GUIDE

	BEST Blaze R980P	BEST Norton SG R981	BETTER BlueFire R887P	BETTER BlueFire R821P	BETTER BlueFire R823P	BETTER BlueFire R884P	GOOD Metalite R228
NORTON 3M	987F1, 977F, 777F, 967F, 963G, 963H, 984F	987F1, 977F, 777F, 967F, 963G, 963H	577F, 567G, 777F 977F	561D	561F Y, 551E XE 741A, 741E, 761D	561D, 561F, 563F 741A, 741E, 761D 761F	240DZ OPK, 270DZ OPK, 241D, 248D, 251D, 341I Imperial, 351D
Hermes	CR456	CR456	RB486X, RB486Y RB426-23MX	—	RB486 X, RB346-23MX, RB426-23MX, RB484TY RB486XF	RB484TY, RB486Y, RB346-23MX, RB426-23MX, RB480-21MX, CB440Y, RB486XY	RB3160P RB317LX RB346MX
Klingspor	CS612YY, CS610YY	CS612YY, CS610YY	CS409Y	CS411Y	CS411X	CS411Y	CS311X, CS310, CS410
SIA	—	—	—	—	—	2800, 2803, 2929	2903XO, 2905X, 2920X
VSM	SK840X, SK750X	SK840X, SK750X	KK815Y, ZK744X	—	KK715X	KK716Y, ZK713X	KK511X, KK711

MATERIAL-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity. Lowest Total Cost.	BETTER Excellent Blend of Performance & Price.	GOOD Consistent Performance. Low Initial Price.
Aluminum	—	Norton BlueFire R884P/R823P	Norton Neon R766
Cast Iron	Norton Blaze R980P	Norton BlueFire R823P	Norton Neon R766
Brass / Bronze	—	Norton BlueFire R884P/R823P	Norton Neon R766
Die Castings	Norton Blaze R980P	Norton BlueFire R823P	Norton Neon R766
Carbon Steel	Norton Blaze R980P	Norton BlueFire R823P	Norton Neon R766
Glass / Ceramics	Norton Blaze R980P	Norton BlueFire R821P	Norton Neon R766
Stainless Steel and Alloys	Norton Blaze R980P	Norton BlueFire R823P/R887P	Norton Neon R766
Wood	—	Norton BlueFire R831/R884P	Norton Neon R766

GRIT SELECTION RECOMMENDATION GUIDE

STOCK REMOVAL	INTERMEDIATE	FINISHING
36 – 50 grit	60 – 100 grit	120 – 320 grit



FEATURED PRODUCTS

**NORTON BLAZE R980P**

BEST FOR MILD AND CARBON STEEL, STAINLESS, COBALT, CHROME, INCONEL, TITANIUM

FEATURES

- Cooler cutting Norton SG ceramic abrasive grain
- Y-weight polyester waterproof cloth backing
- Durable resin bond system
- Advanced "supersize" grinding lubricant

BENEFITS

- Lasts 50% to 200% longer on mild and carbon steel, stainless, cobalt, chrome, Inconel and titanium versus aluminum oxide belts
- Cuts 20% faster than the current generation of grinding belts
- Longer belt life
- Better metal integrity
- Greater productivity; lowest total grinding costs
- Edge-fray resistance
- Excellent body retention during use for more consistent grinding throughout belt life
- Significantly improved belt life due to better grain adhesion
- Cooler cutting during the life of the belt
- Improved part finish and integrity

**NORTON SG R981**

EXCEPTIONAL PERFORMANCE, ESPECIALLY ON HARD-TO-GRIND ALLOYS

FEATURES

- Norton SG ceramic abrasive
- Grinding-aid enhanced
- Strong Y-weight polyester, waterproof cloth backing

BENEFITS

- Exceptional life and value, especially on hard-to-grind alloys
- Longer life, cooler cut
- Improved grain adhesion, reduced edge-fray and better body retention, result in longer life and product consistency



EXPANDED OFFERING

NORTON BLUEFIRE R884P/R823P

BETTER CHOICE FOR HEAVIEST-PRESSURE APPLICATIONS

FEATURES

- Premium self-sharpening zirconia alumina abrasive
- R884P – Durable Y-weight polyester, waterproof cloth backing
- R823P – Strong X-weight polyester backing; waterproof

BENEFITS

- Aggressive, rapid cut rate
- Excellent grain adhesion, reduced edge-fray and better body retention, result in longer life and product consistency
- More flexible than R884P
- Available in finer grit sizes

**NORTON NEON R766**

THE BETTER CHOICE FOR DIFFICULT-TO-GRIND MATERIALS (ALUMINUM, BRASS, BRONZE, STAINLESS, CARBON STEEL, TITANIUM, ETC.)

FEATURES

- Premium abrasive and aluminum oxide blend
- New resin bond system
- Y-weight waterproof polyester backing

BENEFITS

- Ideal when purchasing criteria is a good-performing, economically priced, general purpose belt
- Improved edge retention and 30% + improvement in life versus key competitors
- Withstands light- to moderately-demanding applications
- Extended life on dry grinding applications

TECHtip

TROUBLESHOOTING GUIDE

PROBLEM**Loading****Shedding****Belt breakage****CORRECTION**

Decrease infeed pressure or belt speed

Reduce applied pressure

Use a less aggressive contact wheel

Dress contact wheel if worn or damaged

Use entire surface of belt

Reduce belt tension

Use less aggressive contact wheel

Check tracking mechanism for belts tracking erratically



1" to 6" wide, 36" to 72" long

AVAILABILITY

											
		BEST		BETTER		BETTER		GOOD		GOOD	
TIER:		Norton		Norton		Norton		Norton		Norton	
BRAND:		Norton		Norton		Norton		Norton		Norton	
TRADENAME:		BLAZE R980P		BLUEFIRE R821P		BLUEFIRE R823P		NEON R766		METALITE R228	
ABRASIVE:		Ceramic Alumina		Zirconia Alumina		Zirconia Alumina		Premium A/O Blend		Aluminum Oxide	
BACKING:		Y-wt. Polyester		Y-wt. Cotton		X-wt. Polyester		Y-wt. Polyester		X-wt. Cotton	
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #	PART #	PART #	PART #
1 x 42	36	50	66254476825							78072791710	
	40	50	69957345887	78072726905				66623390041		78072720910	
	50	50	66254476826	78072726904				66623390042		78072720905	
	60	50	69957345486	78072726903	78072728596			66623334502		78072720900	
	80	50	66261041539	78072726902	78072728594			66623390043		78072720895	
	100	50	66261043462		78072728592					78072720890	
	120	50	66261038660		78072728590					78072720885	
	150	50			78072728588					78072720880	
	180	50			78072728586					78072720875	
	220	50			78072700001					78072720871	
	240	50								78072720870	
	320	50								78072720865	
1-1/2 x 60	36	10	69957345578							78072721060	
	40	10	63642595003								
	50	10	69957345664					66623390044		78072787807	
	60	10	69957345631					66623390045			
	80	10	69957345579					66623390046			
	100	10			78072765077					69957351736	
	120	10	66261056493		78072726984						
	180	10			78072758464						
2 x 48	220	10			78072708871					78072756615	
	24	10								78072726130	
	36	10	63642592057	78072727103				66623390047		78072721255	
	40	10	69957345193	78072727102				66623390048		78072721250	
	50	10	69957346716	78072727101				66623390049		78072721245	
	60	10	69957344423	78072727100	78072728621			66623390050		78072721240	
	80	10	69957345100	78072727099	78072728619			66623390051		78072721235	
	100	10	66261052522		78072728617					78072721230	
	120	10	66261052520		78072728615					78072721225	
	150	10			78072728613					78072723246	
	180	10			78072728611					78072721223	
	220	10			78072728609					78072763677	
2 x 60	320	10								78072746387	
	24	10								66261054787	
	36	10	69957345196					66623390052		78072701170	
	40	10	69957394425	78072727124				66623390053		78072721300	
	50	10	69957346149					66623390054		78072762537	
	60	10	69957344901	78072727122				66623390055		78072721290	
	80	10	63642592574	78072727121				66623390056		78072721285	
	100	10	66261052222			66261082976				78072721280	
	120	10	66261042738			78072761958					
	150	10								78072744018	
	180	10				78072702695				78072720441	
	220	10				78072706282				78072744020	
2 x 72	240	10								78072761862	
	320	10								78072702825	
	24	10	66254433969								
	36	10	69957345460	78072727147				66623390057		78072721335	
	40	10	69957346729	78072727146				66623390058		78072721332	
	50	10	69957344966	78072727145				66623390059		78072784894	
	60	10	69957345157	78072727144	78072728645			66623390060		78072721325	
	80	10	69957344961	78072727142	78072728643			66623334237		78072721320	
	100	10	66261041897		66261025537					78072723235	
	120	10	66261044095		78072728639					78072721318	
	150	10			78072761770					78072761973	
	180	10			78072763853					78072718488	
	220	10			78072728633					78072765601	
	320	10								78072721308	

CONTINUED...



1" to 6" wide, 36" to 72" long CONTINUED

AVAILABILITY

			BEST	BETTER	BETTER	BETTER	GOOD	GOOD
TIER:			Norton	Norton	Norton	Norton	Norton	Norton
BRAND:			BLAZE R980P	BLUEFIRE R821P	BLUEFIRE R823P	BLUEFIRE R884P	NEON R766	METALITE R228
TRADENAME:			Ceramic Alumina	Zirconia Alumina	Zirconia Alumina	Zirconia Alumina	Premium A/O Blend	Aluminum Oxide
ABRASIVE:			Y-wt. Polyester	Y-wt. Cotton	X-wt. Polyester	Y-wt. Polyester	Y-wt. Polyester	X-wt. Cotton
BACKING:								
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #
2-1/2 x 48	36	10					66623390061	78072721540
	40	10					66623390062	
	50	10					66623390063	78072721530
	60	10		78072727213			66623390064	78072721525
	80	10					66623390065	78072721520
2-1/2 x 60	24	10				78072737759		78072708296
	36	10	69957344963	78072727235			66623390066	78072721610
	40	10	69957346523	78072727234			66623390067	78072721605
	50	10	69957345300	78072727233			66623390068	78072721600
	60	10	69957345002	78072727232	78072728692	78072721383	66623390069	78072721595
	80	10	69957346095	78072727231	78072728690		66623390070	78072721590
	100	10			78072768991			78072721585
	120	10	66261041380		78072728686			78072721580
	150	10						78072710118
	180	10			78072728682			78072721570
	220	10			78072778217			78072721565
4 x 36	36	10					66623390071	78072722110
	40	10					66623390072	78072722105
	50	10		78072727475			66623390073	78072722100
	60	10			78072728827		66623390074	78072722095
	80	10		78072727473	78072728825		66623390075	78072722090
	100	10			78072728823			78072722085
	120	10			78072728821			78072722080
	150	10						78072722079
	180	10						78072722075
	240	10						78072722926
	320	10						78072722071
4 x 54	36	10	69957346358				66623390076	78072722185
	40	10	63642594113				66623390077	78072722180
	50	10	66254469595				66623390078	78072722175
	60	10	66261063419	78072727518	78072725116		66623390079	78072722170
	80	10	69957345139		78072782996		66623390080	78072722165
	100	10						78072722160
	120	10			78072728847			78072722155
	150	10	66261088705					78072728381
	180	10						78072759243
	220	10						78072762536
4 x 60	24	10	66254461488					78072772342
	36	10	69957345298			78072737955		78072705189
	40	10	69957391732					78072744693
	50	10	69957346715					78072761630
	60	10	63642594485		78072774790			78072762861
	80	10	69957345099		78072765086			78072784685
	100	10						78072763161
	120	10	66254416188		78072766229			78072787840
	150	10						78072704878
	180	10			78072709820			78072728393
	220	10			78072702594			78072790168
4 x 72	36	10				78072725984		
6 x 48	36	10	69957345143	78072727698			66623390081	78072722590
	40	10		78072727697			66623390082	
	50	10		78072727696			66623390083	78072722580
	60	10	69957344422	78072727695*	78072728937*		66623390084	
	80	10		78072727694*	78072728935*		66623390085	78072722570
	100	10			78072728933*			78072722565
	120	10			78072728931*			78072722560
	150	10			78072770042			78072722555
	180	10						78072722550
	220	10						78072722546
	240	10						78072722545
	320	10						78072722543

* STD. PKG. = 20 BELTS

CONTINUED...




1" to 6" wide, 36" to 72" long CONTINUED

AVAILABILITY

TIER:	BEST	BETTER	BETTER	BETTER	GOOD	GOOD
BRAND:	Norton	Norton	Norton	Norton	Norton	Norton
TRADENAME:	BLAZE R980P	BLUEFIRE R821P	BLUEFIRE R823P	BLUEFIRE R884P	NEON R766	METALITE R228
ABRASIVE:	Ceramic Alumina	Zirconia Alumina	Zirconia Alumina	Zirconia Alumina	Premium A/O Blend	Aluminum Oxide
BACKING:	Y-wt. Polyester	Y-wt. Cotton	X-wt. Polyester	Y-wt. Polyester	Y-wt. Polyester	X-wt. Cotton
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #
6 x 54	60	10			78072746982	
6 x 60	36	10				66623343751
	40	10				66623390086
	60	10	69957345149	78072727762		66623390087
	80	10		78072728957*		66623390088
	100	10	66254477452		78072728955	
	120	10				
						78072726680
						78072722679
						78072722665*
						78072722660*
						78072763882

* STD. PKG. = 20 BELTS

Belt Cleaning Stick



- This solid, rubber cleaning stick is designed to remove wood and other non-metallic materials that build up on belt surface during use.
- Apply it to the face of the belt, while running, to remove unwanted materials and prolong the overall life of the belt up to 10 times.

DESCRIPTION	STD. PKG.	PART #
1-3/8 x 1-3/8 x 6	10	07660701717

TECHtip

A light bodied grease applied to a benchstand belt surface will reduce loading and greatly enhance the belt life and performance when grinding soft, malleable nonferrous materials such as aluminum, brass, bronze and copper.

FastTrack Belt Service



For non-stock belts, FastTrack Service Centers offer all the benefits of an ISO 9001 quality manufacturer and the advantages of a coated abrasives express belt service. As the industry's leading producer of abrasive material and backings, our FastTrack service offers an extensive range of Norton made-to-order belts including Norton SG ceramic alumina, BlueFire zirconia alumina, and versatile aluminum oxide and silicon carbide belts.

Manufacturing lead-time is two days for narrow belts (1/2"- 12" widths) and three days for wide belts =>14" width. Please see the FastTrack Service belt section for complete availability and lead-times.



2" to 10" wide, over 70" Long

AVAILABILITY

TIER:

BRAND:

TRADENAME:

ABRASIVE:

BACKING:

								
			BEST	BEST	BETTER	BETTER	GOOD	GOOD
			Norton	Norton	Norton	Norton	Norton	Norton
			BLAZE R980P	SG R981	BLUEFIRE R884P	BLUEFIRE R823P	NEON R766	METALITE R228
			Ceramic Alumina	Ceramic Alumina	Zirconia Alumina	Zirconia Alumina	Premium A/O Blend	Aluminum Oxide
			Y-wt. Polyester	Y-wt. Polyester	Y-wt. Polyester	X-wt. Polyester	Y-wt. Polyester	X-wt. Cotton
SIZE (W x L)	GRIT	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #
2 x 132	36	10		78072753086	78072750016		66623347337●	
	40	10			78072750015		66623390089●	
	50	10		78072740771	78072750013		66623390090●	
	60	10			78072750011		66623390091‡	78072721445
	80	10		78072701958	78072750008		66623390092‡	78072721440
	120	10				78072728662		
3 x 79	50	10	66261090276					
	60	10			78072748280			
3 x 90	24	10			78072731833			
	36	10	69957346319					78072785831
3 x 132	24	10	69957344962●		78072750140			
	36	10	69957344710●	78072753087	78072750138 RR		66623390093	78072721900
	36	10			78072750139 L			
	40	10	69957344964●	78072701614			66623390094●	
	50	10	69957344763●	78072703709	78072750135		66623390095●	78072721890
	60	10	69957344958‡			78072728794	66623390096‡	78072721885
	80	10	69957344764‡			78072728792	66623390097‡	78072721880
	100	10				78072728790		
	120	10				78072728789		78072721870
	150	10						78072721865
4 x 79	36	10		66261022622		78072728785		78072721860
	40	10			78072774955			
4 x 100	80	10			78072731327			
	36	10			78072768679			
4 x 132	24	10			78072750289			
	36	10	69957343852●	78072739662	78072750287		66623326093	
	40	10					66623390098	
	60	10			78072750281		66623335394‡	
	80	10			78072750279		66623343488‡	78072722385
	120	10						78072722375
6 x 78-3/4	40	10			78072725150			
6 x 79	36	10			78072738105			
	40	10			78072760469			
	80	10			78072779322			
8 x 107	36	10					66623390099	78072722795
	50	10					66623390100	78072749887
	60	10					66623347341	78072722780*
	80	10					66623329182	78072722775*
	100	10						
10 x 70-1/2	36	10					66623347342	78072722840
	40	10					66623347343	78072722835
	50	10					66623347344	78072722830
	60	10					66623347345	78072722825
	80	10					66623347346	78072722820

* STD. PKG. = 20 BELTS

● STD. PKG. = 25 BELTS

‡ STD. PKG. = 50 BELTS



CATEGORY DEFINITION

NORaX layered belts outlast conventional abrasive belts with 2 - 5 times longer life. Longer life, higher quality finishes, faster cut rates, and the ability to skip finishing steps all drive down the costs of your finishing processes.

APPLICATIONS:	Polishing and finishing
SIZE RANGE:	Stock: 1/4" to 1" wide, 12" to 30" long
GRIT RANGE:	Stock: X200 and X100
ABRASIVE GRAIN:	Stock: Ceramic Alumina

FEATURED PRODUCTS



NORaX U936 BELTS

BEST FOR HIGH-PRESSURE PRECISION APPLICATIONS

FEATURES

- Unique, engineered quad surface pattern
- 100% high-performance, micron-graded, cool-cutting Norton SG ceramic alumina abrasive grain
- Improved resin bond system
- Premium, Y-weight polyester waterproof backing
- Fray-resistant backing

BENEFITS

- More abrasive contact area
- Higher cut rates while maintaining more consistent finishes
- Up to more than 2X the life vs. competitive engineered ceramic belts
- Lower specific grinding energy
- Increased durability
- Durable; stands up to high-pressure, coolant applications
- Shred-free

AVAILABILITY

AVAILABILITY	TIER:	BEST	BEST
	BRAND:	Norton	Norton
	TRADENAME:	NORaX U936	NORaX U936
	ABRASIVE:	Ceramic Alumina	Ceramic Alumina
	BACKING:	Y-wt. Polyester W/P	Y-wt. Polyester W/P
	JOINT/FLEX:	Plyweld, TF	Plyweld, TF
	GRIT SIZE:	X200 (80)	X100 (150)
SIZE (W x L)	STD. PKG.	PART #	PART #
1/4 x 12	50	66623300249	66623300261
1/2 x 12	50	66623300245	66623300258
1 x 12	50	66623300240	66623300255
1/4 x 18	50	66623300250	66623300262
1/2 x 18	50	66623300247	66623300259
3/4 x 18	50	66623300253	66623300264
3/4 x 20-1/2	50	66623300254	66623300265
1/4 x 24	50	66623300252	66623300263
1/2 x 24	50	66623300248	66623300260
1 x 24	50	66623300243	66623300256
1 x 30	50	66623300244	66623300257

Call your local Norton distributor or sales representative for information on additional NORaX belt sizes and specifications.

NORaX VERSUS FEPA GRADING

NORaX engineered abrasives perform over a wider range of traditional grit sequences.





CATEGORY DEFINITION

For many non-stock belts, our FastTrack belt service centers offer all the benefits of an ISO 9001 quality manufacturer and the advantages of a coated abrasives express belt service. As the industry leader of abrasive belts, our FastTrack belt service has an extensive range of Norton made-to-order belts including Norton SG ceramic alumina, BlueFire zirconia alumina, versatile aluminum oxide, and silicon carbide belts.

Manufacturing lead-time is two days for narrow belts (1/2" – 12" wide) and three days for wide belts (14 – 52" wide). Please see the FastTrack belt service chart below for complete details on availability and lead-times.

FASTTRACK AVAILABILITY AND LEAD-TIME INFORMATION

WIDTH*	GRIT SIZE	MINIMUM ORDER QUANTITY	CASE QUANTITY	MAXIMUM ORDER QUANTITY (EQUALS 2 CASES)	CONVERSION LEAD-TIMES
Narrow Belts					
1/2" through 1"	All	50	200	400	2
Over 1" through 5"	All	10	50	100	2
Over 5" through 9"	All	10	20	40	2
Over 9" through 14"	All	10	10	20	2
Wide Belts					
Over 14" through 20"	All	5	10	20	3
Over 20" through 52"	36 & coarser	2	2	4	3
Over 20" through 52"	40-80	3	3	6	3
Over 20" through 52"	100 & finer	5	5	10	3

* FASTTRACK BELT SERVICE APPLIES TO BELTS 25" AND GREATER IN LENGTH

HOW TO PLACE A FASTTRACK BELT ORDER

- Check the FastTrack belt availability
- Include a full description of belt: quantity, size, Norton CAP code, and grit size
- Send order electronically, fax, or phone to customer service
- When ordering a belt that does not have an existing part number, please call Customer Service to expedite part number creation




BELT SPECIFICATIONS AND AVAILABILITY

TIER	PRODUCT CAP CODE	SHAPE AVAILABILITY	GRIT SIZE	ABRASIVE GRAIN	BACKING	APPLICATIONS
Metalworking						
Norton						
Best	R980P	Narrow, Wide	24-120	Norton Blaze Ceramic Alumina	Y-wt. Polyester	Latest-generation Norton SG grain, supersized and designed for high-performance grinding on stainless and other alloys
Best	R984	Narrow, Wide	36-120	Norton SG Ceramic Alumina	Y-wt. Polyester	Norton SG grain for medium-pressure grinding and finishing heat-sensitive alloys
Better	R884P	Narrow, Wide	24, 36-80	Norton BlueFire Zirconia Alumina	Y-wt. Polyester	High-performance zirconia alumina grain designed for medium- to high-pressure grinding
 Better	R887D	Narrow, Wide	24, 36-120	Norton BlueFire Zirconia Alumina	Y-wt. Polyester	NEW! Significantly improved-performance zirconia alumina grain, supersized and designed for medium- to high-pressure grinding of heat-sensitive alloys
Better	R823P	Narrow, Wide	60-220	Norton BlueFire Zirconia Alumina	X-wt. Polyester	High-performance zirconia alumina grain on lighter backing designed for light to medium grinding
Good	R766	Narrow	P24-80	Aluminum Oxide Blend	Y-wt. Polyester	Premium aluminum oxide blend product designed for a variety of applications including soft metals to hard-to-grind stainless and carbon steel
 Good	R766X	Narrow, Wide	P60-P400	Norton Neon Aluminum Oxide	X-wt. Polyester	NEW! Quality, P-graded aluminum oxide and broad grit range for stock removal to finer finishing
Good	MX240	Narrow, Wide	P60-P150	Aluminum Oxide	X-wt. Poly/Cotton	P-graded, heat-treated aluminum oxide X-weight cloth with strong, but flexible, cotton/ polyester backing making it an ideal multi-purpose product
Good	R245	Narrow	P80-P240, P320, P400	Aluminum Oxide	J-wt. Polyester	Aluminum oxide on flexible, lightweight polyester backing for moderate- to light- pressure applications on mild steel
Good	KF376	Narrow	P80-P320, P400, P600	Aluminum Oxide	J-wt. Cotton	P-graded, heat-treated aluminum oxide with ceramic coating on a very flexible backing for use wherever flexibility and conformability are needed
Good	R445	Narrow	60-220	Silicon Carbide	X-wt. Polyester	Sharp, silicon carbide grain on medium polyester backing for grinding very hard materials – glass, stone, solid surface
Good	U243	Narrow, Wide to 12"	X80, X65, X45, X30, X22, X16	NORaX Aluminum Oxide	J-wt. Cotton	High-performance, multi-layered NORaX grain on very flexible backing for dry polishing applications

TIER	PRODUCT CAP CODE	SHAPE AVAILABILITY	GRIT SIZE	ABRASIVE GRAIN	BACKING	APPLICATIONS
Woodworking						
Norton						
Best	R963	Narrow, Wide	24-60, P80 100-150	Norton SG Ceramic Alumina	Y-wt. Polyester	Norton SG ceramic alumina grain with anti-static coating for forest product applications (MDF, particleboard, plywood)
Best	R955	Narrow	P36-P120	Norton Red Heat Ceramic Alumina	Y-wt. Cotton	100% ceramic alumina abrasive with Y-weight cloth backing for dimensioning, intermediate sanding of wood
Better	R831	Narrow, Wide	24, 36-120	Norton BlueFire Zirconia Alumina	Y-wt. Cotton	Norton BlueFire open-coat product recommended for dry low-pressure applications or where loading is a problem
Good	R215	Narrow, Wide	50-180	Aluminum Oxide	X-wt. Cotton	Initial starting specification for all woodworking applications where loading is a problem
Good	R490	Narrow, Wide	P36-P150	Silicon Carbide	Y-wt. Polyester	Anti-static product for forest product applications (MDF, particle board, plywood) where loading is an issue
Good	R422	Narrow	50-120	Silicon Carbide	X-wt. Cotton	Initial starting specification for all woodworking applications where loading is not an issue
 Best	H975	Narrow, Wide	60-220	Norton Red Heat Ceramic Alumina	F-wt. Paper	NEW! Ceramic alumina grain, antistatic coating, and open coat; the best choice for applications where loading is a problem (soft woods, etc.)
 Better	H831	Narrow, Wide	24,36-120	Norton BlueFire Zirconia Alumina	F-wt. Paper	NEW! Durable zirconia alumina grain, antistatic coating, and open coat: the better choice for applications where loading is a problem (soft woods, etc.)
 Good	H275B	Narrow, Wide	P60-P220	Norton Adalox Aluminum Oxide	F-wt. Paper	NEW! Quality aluminum oxide grain, antistatic coating, and open coat make these an economical choice for all heavy-weight paper belt jobs
 Better	H475	Narrow, Wide	P120-P400	Norton Onyx Silicon Carbide	F-wt. Paper	NEW! Sharp silicon carbide and antistatic coating create finer finishes on hard materials and veneers where finish is critical



CATEGORY DEFINITION


Flap wheels are an ideal choice for a wide variety of blending, deburring and finishing applications common in the metal fabrication, welding and polishing industries. Flap wheels are conformable to intricate shapes and contours. Designed to deliver a consistent finish with a uniform rate of cut, flap wheels wear away, continually exposing fresh abrasives.

- APPLICATIONS:** Used for a wide range of metal fabrication and welding applications including stock removal, blending, deburring, cleaning, finishing, and polishing
- SIZE RANGE:** Flap wheels with mounted steel shanks: 3/8" - 3" diameter
Flap wheels with mounted 1/4"-20 thread: 1" - 3" diameter
Flap wheels with arbor holes: 3-1/2" - 16" diameter
- GRIT RANGE:** 40 - 320
- ABRASIVE GRAIN:** Ceramic Alumina/Aluminum Oxide Blend, Aluminum Oxide

SHAPE RECOMMENDATION GUIDE

SHAPE

DESCRIPTION/APPLICATION



Flap Wheels with Mounted Steel Shanks

Wheels are designed with a 1/8" or 1/4" steel shank as an integral part of each wheel. These shanks run through the wheel creating better balance, a reduction of chatter, and reduced operator fatigue. They also permit quick changes on air tools when using other abrasive products.



Flap Wheels with Mounted 1/4-20 Thread


Wheels are designed with a 1/4"-20 thread and flange as an integral part of the wheel. These threads facilitate the quickest changes on air tools using flap wheels exclusively, as there are no special tools needed to change the flap wheel. Also allow extended reach with accessory mandrels.




Flap Wheels with Arbor Holes

For use on larger portable and fixed-base tools where the wheel must fit on an existing arbor.

APPLICATION/GRIT RECOMMENDATION GUIDE



SEE NON-WOVEN FLAP WHEEL SECTION FOR INTERLEAF FLAP WHEELS



FEATURED PRODUCTS



MERIT HIGH PERFORMANCE

GOOD CHOICE FOR MORE DURABLE FLAP WHEEL APPLICATIONS WHERE AGGRESSIVE CUT AND SUPERIOR LIFE ARE REQUIRED

FEATURES

- Long-lasting ceramic alumina/aluminum oxide abrasive grain blend
- Heavy cotton backing

BENEFITS

- Aggressive cut and 2 to 3 times longer life
- Extended durability for added life and reduced edge wear



MERIT SUPER FINISH

GOOD CHOICE WHERE SUPERIOR FINISH IS REQUIRED, OR ON LOW-PRESSURE APPLICATIONS

FEATURES

- Long-lasting premium aluminum oxide abrasive blend
- Premium flexible cotton backing

BENEFITS

- Excellent cut rate on low-pressure finishing operations
- Softer acting with more flexibility for improved finishing



MERIT METAL

GOOD CHOICE WHEN INITIAL PRICE IS THE MAIN CONSIDERATION


FEATURES

- Quality aluminum oxide abrasive
- Engineered, low-cost cotton backing
- Competitive initial price point

BENEFITS

- Good cut rate and life
- Longer life and wear resistance
- Best starting specification for end-user unable to measure total performance





Micro-Mini Flap Wheels with 1/8" Mounted Steel Shanks

- The smallest flap wheels, ranging from 3/8" to 1-3/16" diameter, mounted on a 1/8" diameter steel shank
- Provide fast polishing and light deburring of internal workpieces with holes or grooves as small as 1/2"

AVAILABILITY

TIER: GOOD				
BRAND: Merit				
TRADENAME: MICRO-MINI				
ABRASIVE: Aluminum Oxide				
SIZE (D x W x SK.)	GRIT	MAX. RPM	STD. PKG.	PART #
3/8 x 3/8 x 1/8	60	40,000	10	08834137470
	80	40,000	10	08834137471
	120	40,000	10	08834137472
	180	40,000	10	08834137473
	240	40,000	10	08834137474
5/8 x 5/8 x 1/8	320	40,000	10	08834137475
	60	37,000	10	08834137480
	80	37,000	10	08834137481
	120	37,000	10	08834137482
	180	37,000	10	08834137483
5/8 x 3/4 x 1/8	240	37,000	10	08834137484
	320	37,000	10	08834137485
	80	37,000	10	08834137541
	120	37,000	10	08834137542
	180	37,000	10	08834137543
3/4 x 3/16 x 1/8	240	37,000	10	08834137544
	320	37,000	10	08834137545
	60	35,000	10	08834137550
	80	35,000	10	08834137551
	120	35,000	10	08834137552
3/4 x 3/8 x 1/8	180	35,000	10	08834137553
	240	35,000	10	08834137554
	320	35,000	10	08834137555
	60	35,000	10	08834137560
	80	35,000	10	08834137561
3/4 x 1/2 x 1/8	120	35,000	10	08834137562
	180	35,000	10	08834137563
	240	35,000	10	08834137564
	320	35,000	10	08834137565
	60	35,000	10	08834137570
	80	35,000	10	08834137571
	120	35,000	10	08834137572
	180	35,000	10	08834137573
	240	35,000	10	08834137574
	320	35,000	10	08834137575

TIER: GOOD				
BRAND: Merit				
TRADENAME: MICRO-MINI				
ABRASIVE: Aluminum Oxide				
SIZE (D x W x SK.)	GRIT	MAX. RPM	STD. PKG.	PART #
3/4 x 5/8 x 1/8	60	35,000	10	08834137580
	80	35,000	10	08834137581
	120	35,000	10	08834137582
	180	35,000	10	08834137583
	240	35,000	10	08834137584
3/4 x 3/4 x 1/8	320	35,000	10	08834137585
	60	35,000	10	08834137590
	80	35,000	10	08834137591
	120	35,000	10	08834137592
	180	35,000	10	08834137593
1-3/16 x 1/8 x 1/8	240	35,000	10	08834137594
	320	35,000	10	08834137595
	80	30,000	10	08834137491
	120	35,000	10	08834137492
	180	35,000	10	08834137493
1-3/16 x 3/16 x 1/8	240	35,000	10	08834137494
	320	35,000	10	08834137495
	60	30,000	10	08834137508
	80	35,000	10	08834137501
	120	35,000	10	08834137502
1-3/16 x 3/8 x 1/8	180	35,000	10	08834137503
	240	35,000	10	08834137504
	320	35,000	10	08834137505
	80	30,000	10	08834137511
	120	35,000	10	08834137512
	180	35,000	10	08834137513
	240	35,000	10	08834137514
	320	35,000	10	08834137515

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



Flap Wheel Test Kits


Micro-Mini Test Kit "MMC"

- Part # 08834131493
- Includes five wheels, 3/8" to 1-3/16" diameter in various grits, mounted on a 1/8" diameter hardened steel shank
- The "MMC" kit is ideal for fast polishing and light deburring of internal holes or grooves as small as 1/2"



Shank-Mounted Mini Test Kit "CMM"

- Part # 08834138004
- Includes ten wheels, 1" to 3" diameter in various grits mounted on a 1/4" diameter hardened steel shank



Mini Flap Wheels with 1/4" Mounted Steel Shanks

- Small flap wheels, ranging from 1" to 3" diameter, mounted on a 1/4" diameter steel shank
- Very durable, long-lasting mini flap wheels for demanding, heavy stock removal applications


AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:



SIZE (D x W x SK.)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #
1 x 1/2 x 1/4	60	30,000	10			08834149800
	80	30,000	10			08834149801
	120	30,000	10			08834149802
1 x 5/8 x 1/4	40	30,000	10	08834137105		
	60	30,000	10	08834137100	08834130754	
	80	30,000	10	08834137101	08834130755	
	120	30,000	10	08834137102	08834130756	
	180	30,000	10	08834131536	08834130757	
	240	30,000	10	08834137104	08834130758	
	320	30,000	10	08834137357	08834130759	
1 x 1 x 1/4	40	30,000	10	08834131259		08834149803
	50	30,000	10	08834137309		
	60	30,000	10	08834137310	08834130760	08834149804
	80	30,000	10	08834137311	08834130761	08834149805
	120	30,000	10	08834137312	08834130762	08834149806
	180	30,000	10	08834137313	08834130763	08834149807
	240	30,000	10	08834137114	08834130764	08834149808
	320	30,000	10	08834137315	08834130765	08834149809
1-3/16 x 1/4 x 1/4	60	25,000	10		08834137600	
	80	25,000	10		08834137601	
	120	25,000	10		08834137602	
1-3/16 x 1/2 x 1/4	60	25,000	10		08834137810	
	80	25,000	10		08834137811	
	120	25,000	10		08834137812	
1-3/8 x 5/8 x 1/4	60	30,000	10	08834137320		
	80	30,000	10	08834137321		
	120	30,000	10	08834137322		
	180	30,000	10	08834137323		
	240	30,000	10	08834137324		
1-1/2 x 1/2 x 1/4	60	25,000	10		08834137130	08834149810
	80	25,000	10		08834137131	08834149811
	120	25,000	10		08834137132	08834149812
	180	25,000	10		08834137133	
	240	25,000	10		08834137134	
1-1/2 x 1 x 1/4	40	25,000	10	08834135140		
	60	25,000	10	08834137340	08834130766	08834149816
	80	25,000	10	08834137141	08834130767	08834149817
	120	25,000	10	08834137142	08834130768	08834149818
	180	25,000	10	08834137343	08834130769	08834149819
	240	25,000	10	08834132101	08834130770	
	320	25,000	10	08834137145	08834130771	
1-1/2 x 1-1/2 x 1/4	40	25,000	10	08834130642		
	60	25,000	10	08834130643		
	80	25,000	10	08834130644		
	120	25,000	10	08834130641		
	180	25,000	10	08834130695		
2 x 1/2 x 1/4	40	25,000	10			08834149820
	60	25,000	10		08834137350	08834149821
	80	25,000	10		08834137151	08834149822
	120	25,000	10		08834137152	08834149823
	180	25,000	10		08834137353	
	240	25,000	10		08834137354	
	320	25,000	10		08834137355	

CONTINUED




Mini Flap Wheels with 1/4" Mounted Steel Shanks CONTINUED

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:

				  		
				GOOD	GOOD	GOOD
				Merit	Merit	Merit
				HIGH PERFORMANCE	SUPER FINISH	METAL
				Ceramic Alumina/ Aluminum Oxide Blend	Aluminum Oxide	Aluminum Oxide
SIZE (D x W x SK.)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #
2 x 3/4 x 1/4	40	25,000	10	08834137158		
	60	25,000	10	08834137160	08834130772	
	80	25,000	10	08834137161	08834130773	
	120	25,000	10	08834137162	08834130774	
	180	25,000	10	08834137163	08834130775	
2 x 1 x 1/4	40	25,000	10	08834137377		08834149824
	50	25,000	10	08834137169		
	60	25,000	10	08834137370	08834130778	08834149825
	80	25,000	10	08834137371	08834130779	08834149826
	120	25,000	10	08834137372	08834130780	08834149827
	180	25,000	10	08834137373	08834130781	08834149828
	240	25,000	10	08834137374	08834130782	
	320	25,000	10	08834137375	08834130783	
2 x 1-1/2 x 1/4	40	25,000	10	08834137183		
	60	25,000	10	08834137380	08834130784	
	80	25,000	10	08834137381	08834130785	
	120	25,000	10	08834137382	08834130786	
	180	25,000	10	08834137383		
	240	25,000	10	08834137384		
	320	25,000	10	08834137319		
2-1/2 x 1 x 1/4	40	20,000	10	08834137408		
	60	20,000	10	08834137410	08834130790	
	80	20,000	10	08834137411	08834130791	
	120	20,000	10	08834137412	08834130792	
	180	20,000	10	08834137413	08834130793	
	240	20,000	10	08834137633	08834130794	
	320	20,000	10	08834137415	08834130795	
2-1/2 x 1-1/2 x 1/4	60	20,000	10	08834137420		
	80	20,000	10	08834137421		
	120	20,000	10	08834137422		
3 x 1/2 x 1/4	40	20,000	10			08834149833
	60	20,000	10		08834137230	08834149834
	80	20,000	10		08834137231	08834149835
	120	20,000	10		08834131610	
	180	20,000	10		08834137433	
	240	20,000	10		08834137235	
	320	20,000	10		08834137287	
3 x 3/4 x 1/4	60	20,000	10	08834137440	08834130796	
	80	20,000	10	08834137441	08834130797	
	120	20,000	10		08834130798	
3 x 1 x 1/4	40	20,000	10	08834137456		08834149836
	60	20,000	10	08834137450	08834130802	08834149837
	80	20,000	10	08834137451	08834130803	08834149838
	120	20,000	10	08834137252	08834130804	08834149839
	180	20,000	10	08834137253	08834130805	08834149840
	240	20,000	10	08834135339	08834130806	
	320	20,000	10	08834135341	08834130807	
3 x 2 x 1/4	40	12,000	10	08834137460		
	60	12,000	10	08834137260		
	80	12,000	10	08834137261		
	120	12,000	10	08834137262		
	180	12,000	10	08834137263		
3 x 2 x 3/8	60	12,000	10	08834135050		
	80	12,000	10	08834135051		
	120	12,000	10	08834135052		

SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



Mini Flap Wheels with 1/4"-20 Thread

- Mini flap wheels ranging from 1" to 3" diameter, mounted on a 14-20 thread that allows you to quickly spin the wheels on and off with no tools
- Designed for polishing and finishing intricate surfaces; cost-effective replacement for brushes, rubber points, and felt bobs

AVAILABILITY

TIER:	GOOD	GOOD
BRAND:	Merit	Merit
TRADENAME:	HIGH PERFORMANCE	SUPER FINISH
ABRASIVE:	Ceramic Alumina/ Aluminum Oxide Blend	Aluminum Oxide




SIZE (D x W x THD.)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #
1 x 5/8 x 1/4-20	60	30,000	10	08834131001	08834130814
	80	30,000	10	08834131002	08834130701
	120	30,000	10	08834131003	08834130702
	180	30,000	10		08834130703
1 x 1 x 1/4-20	40	30,000	10	08834131027	
	60	30,000	10	08834131008	08834130706
	80	30,000	10	08834131009	08834130707
	120	30,000	10	08834131010	08834130708
	180	30,000	10	08834131011	08834130709
	240	30,000	10	08834131012	08834130710
1-3/8 x 5/8 x 1/4-20	60	30,000	10	08834132001	
	80	30,000	10	08834132002	08834130834
	120	30,000	10	08834132003	
1-5/8 x 1/2 x 1/4-20	60	25,000	10		08834132008
	80	25,000	10		08834132009
	120	25,000	10		08834132010
	180	25,000	10		08834132011
1-5/8 x 1 x 1/4-20	40	25,000	10	08834132051	
	60	25,000	10	08834132015	08834130712
	80	25,000	10	08834132016	08834130713
	120	25,000	10	08834132017	08834130714
	180	25,000	10	08834132018	08834130715
	320	25,000	10	08834132020	
2 x 1/2 x 1/4-20	60	25,000	10		08834133001
	80	25,000	10		08834133002
	120	25,000	10		08834133003
	180	25,000	10		08834133004
	320	25,000	10		08834133006
2 x 3/4 x 1/4-20	60	25,000	10	08834133008	08834130718
	80	25,000	10	08834133009	08834130719
	120	25,000	10	08834133010	08834130720
	180	25,000	10	08834133011	
2 x 1 x 1/4-20	40	25,000	10	08834133044	
	60	25,000	10	08834133015	08834130724
	80	25,000	10	08834133016	08834130725
	120	25,000	10	08834133017	08834130726
	180	25,000	10	08834133018	08834130727
	240	25,000	10	08834133019	08834130728
2 x 1-1/2 x 1/4-20	60	25,000	10	08834133020	08834130729
	80	25,000	10	08834135201	08834130730
	120	25,000	10	08834135202	08834130731
	180	25,000	10	08834135203	08834130732
2-1/2 x 1/4 x 1/4-20	60	20,000	10	08834135204	
	80	20,000	10		08834134001
	120	20,000	10		08834134002
	180	20,000	10		08834134003
	240	20,000	10		08834134004
2-1/2 x 3/8 x 1/4-20	60	20,000	10		08834134005
	80	20,000	10		08834134008
	120	20,000	10		08834134009
2-1/2 x 1/2 x 1/4-20	60	20,000	10		08834134010
	80	20,000	10		08834134015
	120	20,000	10		08834134016
	180	20,000	10		08834134017
					08834134018

FOR ADAPTERS FOR FLAP WHEELS WITH 1/4"-20 THREAD, SEE THE END OF THIS SECTION

SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

CONTINUED



Mini Flap Wheels with 1/4"-20 Thread CONTINUED

AVAILABILITY

TIER:	GOOD	GOOD
BRAND:	Merit	Merit
TRADENAME:	HIGH PERFORMANCE	SUPER FINISH
ABRASIVE:	Ceramic Alumina/ Aluminum Oxide Blend	Aluminum Oxide

SIZE (D x W x THD.)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #
2-1/2 x 1 x 1/4-20	40	20,000	10	08834134061	
	60	20,000	10	08834134022	08834130736
	80	20,000	10	08834134023	08834130737
	120	20,000	10	08834134024	08834130738
	180	20,000	10	08834134025	
3 x 1/2 x 1/4-20	60	20,000	10		08834135001
	80	20,000	10		08834135002
	120	20,000	10		08834135003
	180	20,000	10		08834135004
3 x 3/4 x 1/4-20	60	20,000	10	08834135008	08834130742
	80	20,000	10	08834135009	
	120	20,000	10	08834135010	08834130744
3 x 1 x 1/4-20	40	20,000	10	08834135230	
	60	20,000	10	08834135015	08834130748
	80	20,000	10	08834135016	08834130749
	120	20,000	10	08834135017	08834130750
	180	20,000	10	08834135018	08834130751
	240	20,000	10	08834135019	08834130752
	320	20,000	10		08834130753

FOR ADAPTERS FOR FLAP WHEELS WITH 1/4"-20 THREAD, SEE THE END OF THIS SECTION
SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



Cup-Type Mini Flap Wheels with 1/4" Mounted Steel Shanks

- Primarily used for bottom or side-wall type sanding where conventional tools do not reach
- Cup-type mini flap wheels will not mar your workpiece while reaching flush into areas where other wheels cannot reach

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide

SIZE (D x W x SK.)	MAX. RPM	GRIT	STD. PKG.	PART #
2-1/2 x 1-1/2 x 1/4	20,000	60	10	08834144463



Flap Wheel Test Kits

Merit Mini 1/4"-20 Thread Test Kit "CQ"


- Part # 08834138001
- Includes ten, 1" to 3" diameter, 1/4"-20 thread mini flap wheels
- Each kit includes a 1/4"-20 QC-4 quick-change adapter

Merit Mini Grind-O-Flex Test Kit "CMM"

- Part # 08834138004
- Includes ten wheels, 1" to 3" diameter in various grits
- Each wheel comes with a 1/4" steel mandrel permanently mounted

Merit Micro Mini GOF Test Kit "MMC"

- Part # 08834131493
- Includes 5 wheels, 3/8" to 1-3/16" in diameter
- The flap wheels are mounted on a 1/8" diameter hardened steel shank
- Ideal for fast polishing and light deburring of holes or grooves



3-1/2" – 8" Flap Wheels with Arbor Holes

- Flap wheels ranging from 3-12" to 8" diameter with arbor holes
- Heavy cotton backing and premium abrasive grains combine to provide superior life with aggressive cut on a wide range of polishing and finishing applications

AVAILABILITY

TIER:

BRAND:

TRADENAME:

ABRASIVE:



GOOD

Merit

HIGH PERFORMANCE

Ceramic Alumina/
Aluminum Oxide Blend

SIZE (D x W x H)	GRIT	MAX. RPM	STD. PKG.	PART #
3-1/2 x 1 x 5/8	40	12,000	10	08834122001
	50	12,000	10	08834122002
	60	12,000	10	08834122003
	80	12,000	10	08834122004
	120	12,000	10	08834122006
	180	12,000	10	08834122007
	240	12,000	10	08834122008
3-1/2 x 1-1/2 x 5/8	320	12,000	10	08834122009
	40	12,000	10	08834122011
	50	12,000	10	08834122012
	60	12,000	10	08834122013
	80	12,000	10	08834122014
	120	12,000	10	08834122016
	150	12,000	10	08834122017
3-1/2 x 2 x 5/8	180	12,000	10	08834122018
	320	12,000	10	08834122020
	40	12,000	10	08834122022
	60	12,000	10	08834122024
	80	12,000	10	08834122025
	120	12,000	10	08834122027
	180	12,000	10	08834122028
4 x 1 x 5/8	40	12,000	10	08834122032
	50	12,000	10	08834122033
	60	12,000	10	08834122034
	80	12,000	10	08834122035
	120	12,000	10	08834122037
	180	12,000	10	08834122038
	240	12,000	10	08834122039
4 x 1-1/2 x 5/8	320	12,000	10	08834122040
	40	12,000	10	08834122042
	50	12,000	10	08834122043
	60	12,000	10	08834122044
	80	12,000	10	08834122045
	120	12,000	10	08834122047
	240	12,000	10	08834122050
4 x 2 x 5/8	40	12,000	10	08834122053
	50	12,000	10	08834122054
	60	12,000	10	08834122055
	80	12,000	10	08834122056
	120	12,000	10	08834122058
	180	12,000	10	08834122059
	240	12,000	10	08834122060
5 x 1-1/2 x 5/8	320	12,000	10	08834122061
	40	12,000	10	08834122063
	50	12,000	10	08834122064
	60	12,000	10	08834122065
	80	12,000	10	08834122066
	120	12,000	10	08834122068
	180	12,000	10	08834122070
	240	12,000	10	08834122071
	320	12,000	10	08834122072

FOR FLAP WHEEL WITH ARBOR HOLE ADAPTERS AND BUSHINGS, SEE THE END OF THIS SECTION

A SET OF REDUCING BUSHING WILL BE INCLUDED FOR 1" CENTER HOLE WHEELS AT NO CHARGE WHEN PURCHASED WITH FLAP WHEELS AND SPECIFIED ON THE ORDER. REFER TO REDUCING BUSHING FOR ADDITIONAL INFORMATION.

SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

CONTINUED



3-1/2" – 8" Flap Wheels with Arbor Holes CONTINUED

AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:

				  		
				GOOD	GOOD	GOOD
				Merit	Merit	Merit
				HIGH PERFORMANCE	SUPER FINISH	METAL
				Ceramic Alumina/ Aluminum Oxide Blend	Aluminum Oxide	Aluminum Oxide
SIZE (D x W x H)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #
6 x 1/2 x 1	40	6,000	10	08834123001		
	60	6,000	10	08834123003		
	80	6,000	10	08834123004		
	120	6,000	10	08834123005		
	150	6,000	10	08834122198		
	180	6,000	10	08834123006		
	240	6,000	10	08834123007		
	320	6,000	10	08834122137		
6 x 1 x 1	40	6,000	5	08834123009		08834120167
	50	6,000	5	08834123010		08834120168
	60	6,000	5	08834123011	08834121002	08834120169
	80	6,000	5	08834123012	08834121003	08834120170
	100	6,000	5			08834120171
	120	6,000	5	08834123014	08834121005	08834120172
	150	6,000	5	08834123015	08834121006	
	180	6,000	5	08834123016	08834121007	08834120174
	240	6,000	5	08834123017	08834121008	08834120176
	320	6,000	5	08834123018	08834121009	08834120177
6 x 1-1/2 x 1	40	6,000	5	08834123020		
	50	6,000	5	08834123021		
	60	6,000	5	08834123022	08834121023	
	80	6,000	5	08834123023	08834121024	
	120	6,000	5	08834123025	08834121025	
	150	6,000	5	08834123026	08834121106	
	180	6,000	5	08834123027	08834121026	
	240	6,000	5	08834123028		
	320	6,000	5	08834123029	08834121109	
6 x 2 x 1	40	6,000	5	08834123031		08834120189
	50	6,000	5	08834123032		
	60	6,000	5	08834123033	08834121030	08834120191
	80	6,000	5	08834123034	08834121031	08834120192
	100	6,000	5			08834120198
	120	6,000	5	08834123036	08834121032	08834120194
	180	6,000	5	08834123038	08834121033	08834120197
	240	6,000	5	08834123039	08834121034	08834120199
	320	6,000	5	08834123040	08834121035	08834120493
6 x 3 x 1	40	6,000	3	08834123053		
	50	6,000	3	08834123054		
	60	6,000	3	08834123055		
	80	6,000	3	08834123056		
	120	6,000	3	08834123058		
	150	6,000	3	08834122544		
	180	6,000	3	08834123060		
	240	6,000	3	08834123061		
	320	6,000	3	08834122329		
8 x 1 x 1	40	4,500	3	08834123070		
	50	4,500	3	08834123071		
	60	4,500	3	08834123072		
	80	4,500	3	08834123073		
	120	4,500	3	08834123075		
	180	4,500	3	08834123077		
	240	4,500	3	08834123078		
	320	4,500	3	08834123079		
8 x 2 x 1	40	4,500	3	08834123092		
	50	4,500	3	08834123093		
	60	4,500	3	08834123094		
	80	4,500	3	08834123095		
	120	4,500	3	08834123097		
	180	4,500	3	08834123099		
	240	4,500	3	08834123100		
	320	4,500	3	08834123101		

FOR FLAP WHEEL WITH ARBOR HOLE ADAPTERS AND BUSHINGS, SEE THE END OF THIS SECTION

A SET OF REDUCING BUSHING WILL BE INCLUDED FOR 1" CENTER HOLE WHEELS AT NO CHARGE WHEN PURCHASED WITH FLAP WHEELS AND SPECIFIED ON THE ORDER. REFER TO REDUCING BUSHING FOR ADDITIONAL INFORMATION.

SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



10" – 16" Large Flap Wheels with Arbor Holes

Wide range of applications:

- For polishing/grinding jobs in production work as well as clean-up and maintenance jobs
- Work on metals, plastic, rubber and wood

Easy to operate:

- No adjustments, dressing, or preparation required before or during operation

Fewer rejected parts:

- More forgiving than other abrasive products
- Reduce the possibility of flattening, gouging and surface deformation

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
TRADENAME:	HIGH PERFORMANCE
ABRASIVE:	Ceramic Alumina/ Aluminum Oxide Blend

SIZE (D x W x H)	GRIT	MAX. RPM	STD. PKG.	PART #
10 x 1 x 1-3/4	40	4,000	4	08834122223
	60	4,000	4	08834124002
	80	4,000	4	08834124003
	120	4,000	4	08834124005
	150	4,000	4	08834124006
	180	4,000	4	08834124007
	240	4,000	4	08834122889
10 x 1-1/2 x 1-3/4	320	4,000	4	08834124009
	60	4,000	4	08834124022
	80	4,000	4	08834124023
	120	4,000	4	08834124025
10 x 2 x 1-3/4	180	4,000	4	08834124027
	60	4,000	2	08834124042
	80	4,000	2	08834124043
	120	4,000	2	08834124045
10 x 3 x 1-3/4	180	4,000	2	08834124047
	60	4,000	2	08834124077
	80	4,000	2	08834122316
	120	4,000	2	08834122131
12 x 1 x 1-3/4	180	4,000	2	08834122132
	60	3,000	4	08834124085
	80	3,000	4	08834122349
	120	3,000	4	08834122311
12 x 2 x 1-3/4	180	3,000	4	08834122315
	40	3,000	2	08834122248
	50	3,000	2	08834122249
	60	3,000	2	08834122250
12 x 4 x 1-3/4	80	3,000	2	08834122267
	120	3,000	2	08834122269
	150	3,000	2	08834122270
	180	3,000	2	08834122271
	240	3,000	2	08834122273
	320	3,000	2	08834122275
	50	2,400	1	08834120013
	80	2,400	1	08834120015
14 x 1 x 1-3/4	120	2,400	1	08834120016
	180	2,400	1	08834120017
	240	2,400	1	08834120019
14 x 1-1/2 x 1-3/4	60	2,400	1	08834120020
	120	2,400	1	08834120022
14 x 1-1/2 x 1-3/4	60	2,400	1	08834120024
	80	2,400	1	08834120025
	120	2,400	1	08834120026
	180	2,400	1	08834120027


AVAILABILITY

TIER:	GOOD
BRAND:	Merit
TRADENAME:	HIGH PERFORMANCE
ABRASIVE:	Ceramic Alumina/ Aluminum Oxide Blend

SIZE (D x W x H)	GRIT	MAX. RPM	STD. PKG.	PART #
14 x 2 x 1-3/4	60	2,400	1	08834120028
	80	2,400	1	08834123215
	120	2,400	1	08834122907
	240	2,400	1	08834120032
14 x 3 x 1-3/4	60	2,400	1	08834120033
	80	2,400	1	08834120034
	120	2,400	1	08834120035
	240	2,400	1	08834120036
14 x 4 x 1-3/4	60	2,000	1	08834120037
	80	2,000	1	08834122829
	120	2,000	1	08834122502
	240	2,000	1	08834120041
16 x 1 x 1-3/4	60	2,400	1	08834120042
	80	2,400	1	08834120043
	120	2,400	1	08834120044
	180	2,400	1	08834120045
16 x 2 x 1-3/4	240	2,400	1	08834120046
	60	2,400	1	08834120047
	80	2,400	1	08834120049
	120	2,400	1	08834120050
16 x 3 x 1-3/4	180	2,400	1	08834120051
	240	2,400	1	08834120052
	60	2,400	1	08834120053
	80	2,400	1	08834120054
16 x 4 x 1-3/4	120	2,400	1	08834120055
	180	2,400	1	08834120056
	240	2,400	1	08834120057
	60	2,000	1	08834120058
16 x 6 x 1-3/4	120	2,000	1	08834120060
	240	2,000	1	08834122435
	80	2,000	1	08834120068
	120	2,000	1	08834120069
16 x 6 x 1-3/4	180	2,000	1	08834120070
	240	2,000	1	08834120071

FOR FLAP WHEEL WITH ARBOR HOLE ADAPTERS AND BUSHINGS, SEE THE END OF THIS SECTION FOR ADDITIONAL INFORMATION.

SOME FLAP WHEEL PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



Adapter and Bushings for Flap Wheels with Arbor Holes

WHEEL DIAMETER	ADAPTERS	PART #
Shank Adapters		
3-1/2	1/4 Shank	08834125001
3-1/2	3/8 Shank	08834125007
4 – 8	1/4 Shank	08834125003
Threaded Mounting Adapters		
4 – 8	5/8-11 Thread	08834125027
Reducing Bushings		
6 – 8	1 to 3/8	08834125016
	1 to 1/2	08834125017
	1 to 5/8	08834125018
	1 to 3/4	08834125019
	1 to 7/8	08834125020
10 – 16	1 to 5/8	08834122069

STANDARD PACKAGES = 1 ADAPTER, 1 PAIR OF BUSHINGS
FOR ADDITIONAL ALUMINUM REDUCING BUSHINGS SEE NON-WOVEN CONVOLUTE WHEEL
SECTION PAGE 198



08834125001



08834125007



08834125003



08834125027



08834125016


Adapters for 1/4"-20 Thread Mini and Arbor Hole Flap Wheels

MODEL #	DESCRIPTION	PART #
Adapters		
ADAPT C	Fits 3 x 2 x 3/8 arbor flap wheel	08834137009
MA-100	Fits A.H. Mini Wheel	08834137007
QC-8	1/8 x 5/8	08834137002
QC-4	1/4 SK. Dia. x 5/8 SK. L.	08834137001
QC-44	1/4 x 4	08834137003
QC-46	1/4 x 6	08834137004
QC-48	1/4 x 8	08834137005
QC-T	1/4-20 Thread	08834137012
QC-T	3/8-24 Thread	08834137010


STANDARD PACKAGE = 1 ADAPTER
OTHER THREAD SIZES AVAILABLE FOR QUOTATION



QC-4



QC-46



QC-T



Sand-O-Flex Wheels

With their firm cushioning brushes, Sand-O-Flex's abrasive strips are forced into, around and over corners, hollow and fluted surfaces, and small openings. Pressure is distributed evenly over the surface to prevent loss of detail and the flattening of rounded areas; for sanding metals, woods, plastics, rubber and ceramic.

Sand-O-Flex wheels eliminate the need to hand-sand and are designed to fit most standard equipment. They load quickly and easily by turning the index knob as needed, allowing you to change grit size in minutes. Sand-O-Flex refills are available both scored (for finer, less aggressive work) and unscored. And, with the use of Merit adapters, Sand-O-Flex wheels will fit most electric bench grinders.



Sand-O-Flex Wheel – Model 350-RP

- Diameter: 6-1/2" overall, 4" diameter high-impact plastic body
- 1" wide abrasive strips backed by 8 cushioning brushes
- 1/4" diameter steel shank
- Weight: 9-1/2 oz.
- Maximum operating speed: 2,400 RPM
- Special adapter required for bench grinder use
- Some assembly required



AVAILABILITY

TIER:	GOOD
BRAND:	Merit
TRADENAME:	SAND-O-FLEX
ABRASIVE:	Aluminum Oxide

MODEL #	GRIT	STD. PKG.	PART #
Sand-O-Flex Wheel			
350-RP		1	08834111051
Comes assembled with 80 grit A/O resin bond scored refill and brushes			
Sand-O-Flex Accessories			
Bench Grinder Adapter 350-RP 1/4 shank to 1/2 shank		1	08834111055
Replacement Brushes for 350-RP; 8 per set		1 set	08834113003
Resin Bond Refills			
350-RP SCORED	60	10	08834111052
	80	10	08834111053
	100	10	08834112114
	120	10	08834111054
	180	10	08834111057
Glue Bond Refills			
350-RP SCORED	80	10	08834112054
	100	10	08834112055
	120	10	08834112056
	180	10	08834112058
	80	10	08834112044
350-RP UNSCORED	180	10	08834112048





CATEGORY DEFINITION

Best product for blending and polishing contours when smooth running is a primary concern. Used for finishing hard-to-reach areas, removing parting lines, imperfections, and burrs on all surfaces.

BENEFITS:	Spiral construction avoids shadow marks and provides smooth, chatter-free cutting action
	Achieves close tolerances when finishing curved, contoured, and hard-to-reach areas
	Fast cutting and removes toughest metal
	Bands are easily removed and replaced
GRIT RANGE:	24 - 320
ABRASIVE GRAIN:	Aluminum Oxide
OTHER:	Use with rubber expanding drum

APPLICATION/GRIT RECOMMENDATION GUIDE

	COARSER (GRINDING)					FINER (FINISHING)				
GRIT:	24	36	40	50	60	80	120	180	240	320
	HEAVY STOCK REMOVAL		BLENDING OUT HEAVY MACHINE MARKS					REMOVING HEAVY BURRS		
			APPLYING HEAVY SCRATCH PATTERN					REMOVING FLASH/PARTING LINES		
			REMOVING RUST/SCALE/PIT MARKS					PREPARING METAL FOR PAINTING		
			BLENDING OUT MEDIUM MACHINE MARKS					BLENDING METAL SURFACES		
			APPLYING LIGHT SCRATCH PATTERN					FINE BLENDING AND CLEANING		
								METAL FINISHING AND POLISHING		

AVAILABILITY

GOOD								
Merit								
Aluminum Oxide								
GRIT	1/4 x 1/2	1/4 x 1	3/8 x 1/2	3/8 x 1	1/2 x 1/2	1/2 x 1	1/2 x 1-1/2	1/2 x 2
24	-	-	-	-	-	08834196712	-	-
36	-	-	-	08834197674	08834196619	08834196591	08834196237	08834196758
40	08834196614	-	-	-	08834196234	08834196174	-	08834196825
50	08834196292	08834196785	08834196386	-	08834196228	08834196214	08834197111	08834196548
60	08834196342	08834196886	08834196829	08834196999	08834196068	08834196212	08834196053	08834196549
80	08834196269	08834196733	08834196512	08834196645	08834196179	08834196215	08834196646	08834196669
100	08834196511	08834196734	08834196513	-	08834196189	08834196534	08834196540	08834196735
120	08834196217	08834197004	08834196747	08834196218	08834196069	08834196210	08834196324	08834196736
150	08834196327	-	-	-	08834196211	08834196772	-	-
180	08834196490	-	08834196504	-	08834196209	08834196713	-	-
240	-	-	08834196481	-	08834196564	08834196814	-	-
320	08834196865	-	08834196830	-	08834196505	08834196487	-	-
PKG. QTY. STOCK	100/box	100/box	100/box	100/box	100/box	100/box	100/box	100/box
MOQ NON-STOCK	400	400	300	300	300	300	300	200
Expanding Rubber Drums								
	1/8 Shank	NA	1/8 Shank	1/8 Shank	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank
	30,000 RPM		30,000 RPM	18,000 RPM	30,000 RPM	15,000 RPM	12,000 RPM	10,000 RPM
	08834196030		08834196944	08834196011	08834196904	08834196906	08834196907	08834196908

SOME MERIT SPECIALTY PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



AVAILABILITY

GOOD								
Merit								
Aluminum Oxide								
GRIT	3/4 x 1/2	3/4 x 3/4	3/4 x 1	3/4 x 1-1/2	3/4 x 2	1 x 1/2	1 x 1	1 x 1-1/2
24	-	08834196613	08834196776	08834196596	-	-	08834196563	08834196708
36	08834196769	08834196609	08834196261	08834196238	08834196953	08834196058	08834196072	08834196525
40	08834196605	08834196236	08834196517	08834196227	08834196826	-	08834196073	08834196546
50	08834196608	08834196183	08834196515	08834196500	08834196757	-	08834196184	08834196078
60	08834196578	08834196168	08834196070	08834196554	08834196745	08834196580	08834196075	08834196060
80	08834196255	08834196161	08834196071	08834196249	08834196756	08834196647	08834196074	08834196162
100	08834196567	08834196230	08834196502	08834196501	08834196766	08834196157	08834196167	08834196257
120	08834196579	08834196226	08834196219	08834196057	08834196746	08834197592	08834196177	08834196677
150	08834196631	08834196231	08834196822	-	08834197283	-	08834196686	08834197639
180	08834197116	08834196056	08834196565	08834196851	-	-	08834196059	08834196790
240	08834196603	08834196859	08834196668	-	66254410751	08834197287	08834196178	08834196526
320	08834196806	-	08834196624	08834199664	-	-	08834196789	08834197700
PKG. QTY. STOCK	100/box	100/box	100/box	100/box	100/box	100/box	100/box	100/box
MOQ NON-STOCK	300	300	300	300	200	200	300	200
Expanding Rubber Drums								
	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank	1/4 Shank
	27,000 RPM	24,000 RPM	17,000 RPM	10,000 RPM	10,000 RPM	20,000 RPM	18,000 RPM	10,000 RPM
	08834196909	08834196910	08834196911	08834196912	08834196913	08834196914	08834196916	08834196917

SOME MERIT SPECIALTY PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

GOOD								
Merit								
Aluminum Oxide								
GRIT	1 x 2	1 x 3	1-1/2 x 1	1-1/2 x 1-1/2	1-1/2 x 2	1-1/2 x 3	2 x 1	2 x 1-1/2
24	08834196709	08834197806	08834196684	08834196220	08834196539	-	08834196841	08834196700
36	08834196267	08834196665	08834196222	08834196164	08834196657	08834197063	08834196233	08834196509
40	08834196689	-	08834196223	08834196171	08834196598	-	08834196109	08834196514
50	08834196588	08834197688	08834196185	08834196176	08834196252	-	08834196186	08834196527
60	08834196506	08834196676	08834196503	08834196091	08834196067	08834196703	08834196232	08834196978
80	08834196268	08834196195	08834196254	08834196165	08834196533	08834196809	08834196166	08834196259
100	08834196750	08834196445	08834196216	08834196182	08834196543	08834196522	08834196508	08834196521
120	08834196507	08834196197	08834196707	08834196066	08834196079	08834196343	08834196595	08834196586
150	08834197664	-	08834196989	08834197750	08834197376	-	-	-
180	08834196987	08834196356	-	08834196535	-	08834197869	08834196661	08834196536
240	-	-	08834196491	08834196260	08834197709	-	08834197983	-
320	-	-	08834196063	08834197647	-	-	-	-
PKG. QTY. STOCK	100/box	100/box	100/box	100/box	100/box	100/box	100/box	100/box
MOQ NON-STOCK	200	100	300	200	200	100	200	200
Expanding Rubber Drums								
	1/4 Shank	NA	1/4 Shank	1/4 Shank	1/4 Shank	NA	1/4 Shank	1/4 Shank
	8,000 RPM		12,000 RPM	10,000 RPM	8,000 RPM		11,000 RPM	8,000 RPM
	08834196918		08834196921	08834196922	08834196923		08834196926	08834196927

SOME MERIT SPECIALTY PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

GOOD							
Merit							
Aluminum Oxide							
GRIT	2 x 2	2 x 3	2-1/4 x 3	3 x 1	3 x 1-1/2	3 x 2	3 x 3
24	08834196516	08834197903	-	08834196795	-	08834196263	08834196256
36	08834196110	08834196827	08834197140	08834196717	08834196802	08834196545	08834196262
40	08834196172	08834196151	08834197158	08834196755	-	08834196090	08834196555
50	08834196187	08834196152	08834196620	-	-	08834196264	08834196253
60	08834196173	08834196175	-	08834196150	08834196719	08834196530	08834196188
80	08834196181	08834196198	08834196270	08834196524	08834196633	08834196265	08834196159
100	08834196193	08834196199	-	08834196831	-	-	08834196250
120	08834196585	08834196200	08834196729	08834196089	-	08834196531	08834196572
150	08834196629	-	08834195857	-	-	-	08834196452
180	08834196306	-	-	-	-	-	08834196131
240	08834196375	-	-	-	-	-	08834196574
320	08834196628	-	08834195825	-	-	-	08834197968
PKG. QTY. STOCK	100/box	100/box	100/box	100/box	100/box	100/box	100/box
MOQ NON-STOCK	200	100	100	200	200	100	100
Expanding Rubber Drums							
	1/4 Shank	NA	NA	3/8 Shank	NA	3/8 Shank	3/8 Shank
	6,000 RPM			3,000 RPM		3,000 RPM	3,000 RPM
	08834196928			08834196929		08834196930	08834196931

SOME MERIT SPECIALTY PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



CATEGORY DEFINITION

Cartridge, spiral rolls and cone points are strips of abrasive cloth rolled and glued to form a solid shape that is designed to break down during use and reveal the next layer of abrasive.

APPLICATIONS: Used on inside surfaces and inside corners where other abrasive shapes cannot reach. Typically these are used on high-speed air grinders and are always mounted on a mandrel. Ideal for flash removal, polishing, or removing machine tool marks, and edge breaking.

SHAPES: Cartridge rolls, spiral rolls (full taper, half taper, and sidewall taper), and tapered cone points

GRIT RANGE: 36 - 320

ABRASIVE GRAIN: Ceramic Alumina, Aluminum Oxide, Silicon Carbide


BACKING: Cotton Cloth

MAXIMUM RPM: 1/8" to 1/2" – 23,000
5/8" to 1" – 18,000
1" to 1-1/2" – 15,000

APPLICATION/GRIT RECOMMENDATION GUIDE

	COARSER (GRINDING)			FINER (FINISHING)				
GRIT:	36	40	50	60	80	120	180	240 320
	BLENDING OUT HEAVY MACHINE MARKS							
	REMOVING HEAVY BURRS							
	APPLYING HEAVY SCRATCH PATTERN							
	REMOVING FLASH/PARTING LINES							
	REMOVING RUST/SCALE/PIT MARKS							
		PREPARING METAL FOR PAINTING						
		BLENDING OUT MEDIUM MACHINE MARKS						
			BLENDING METAL SURFACES					
			APPLYING LIGHT SCRATCH PATTERN					
				FINE BLENDING AND CLEANING				
						METAL FINISHING AND POLISHING		

Cartridge Rolls



- Effective for flash removal
- Polishing or removing machine tool marks
- Edge breaking
- Valuable abrasive tool for reaching into corners, where larger diameter tools cannot work
- All cartridge roll part numbers shown are resin bond, half-glued
- Quarter and full glue are also available for quotation as made-to-order products

Refer to the back of this section for mandrels.



FEATURED PRODUCTS



MERIT CERAMIC ALUMINA CARTRIDGE ROLLS

BEST CHOICE FOR HARD-TO-GROUND MATERIALS – STAINLESS STEEL, COBALT, INCONEL, AND TITANIUM

FEATURES

- Next-generation ceramic alumina abrasive grain
- Advanced grinding aid
- Improved resin bond system
- Strong X-weight cotton backing

BENEFITS

- Greatest productivity with significantly faster cut rates
- Resists wear, resulting in 50% – 300% longer life
- Cooler cutting, longer life
- Exceptional grain retention and longer life
- Durability and even wear

AVAILABILITY

TIER:	BEST
BRAND:	Merit
ABRASIVE:	Ceramic Alumina
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/4 x 1-1/2 x 1/8	60	100	66261194384
Use M-9 Mandrel	80	100	66261194394
	120	100	66261194397
3/8 x 1-1/2 x 1/8	60	100	66261194392
Use M-9 Mandrel	80	100	66261194395
	120	100	66261194398

CONTINUED

AVAILABILITY

TIER:	BEST
BRAND:	Merit
ABRASIVE:	Ceramic Alumina
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	66261194393
Use M-9 Mandrel	80	100	66261194396
	120	100	66261194399



NEW

MERIT CERAMIC ALUMINA BLEND CARTRIDGE ROLLS

BETTER CHOICE FOR STAINLESS STEEL AND OTHER HARD-TO-GROUND MATERIALS

FEATURES

- Sharp ceramic alumina abrasive blend
- Durable X-weight cotton backing
- Grinding aid

BENEFITS

- Delivers cooler cut
- Ensures even wear
- Promotes cooler cut on stainless steel

AVAILABILITY

TIER:	BETTER
BRAND:	Merit
ABRASIVE:	Ceramic Alumina Blend
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/4 x 1-1/2 x 1/8	60	100	66261040477
Use M-9 Mandrel	80	100	69957300001
3/8 x 1-1/2 x 1/8	60	100	66261041270
Use M-9 Mandrel	80	100	08834187134

CONTINUED

AVAILABILITY

TIER:	BETTER
BRAND:	Merit
ABRASIVE:	Ceramic Alumina Blend
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	08834184221
Use M-9 Mandrel	80	100	66261012798



NEW

MERIT ALUMINUM OXIDE PLUS CARTRIDGE ROLLS

EFFECTIVE STARTING SPECIFICATION FOR FLASH REMOVAL, POLISHING, OR REMOVING MACHINE TOOL MARKS AND EDGE BREAKING ON ALL TYPES OF METAL

FEATURES

- Premium aluminum oxide abrasive
- Advanced, full resin bond system

BENEFITS

- Controls aggressiveness while cool cutting
- Ensures edge adhesion and long life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Premium Aluminum Oxide
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/4 x 1-1/2 x 1/8	60	100	77696089001
Use M-9 Mandrel	80	100	77696089002
	120	100	77696089003
3/8 x 1-1/2 x 1/8	60	100	77696089004
Use M-9 Mandrel	80	100	77696089005
	120	100	77696089006

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Premium Aluminum Oxide
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	77696089007
Use M-9 Mandrel	80	100	77696089008
	120	100	77696089009

Refer to the back of this section for mandrels.



MERIT ALUMINUM OXIDE CARTRIDGE ROLLS

GOOD STARTING SPECIFICATION FOR FLASH REMOVAL, POLISHING, OR REMOVING MACHINE TOOL MARKS AND EDGE BREAKING ON ALL TYPES OF METAL

FEATURES

- Quality aluminum oxide abrasive
- Strong X-weight cotton backing construction
- Durable resin bond system

BENEFITS

- Tough and durable
- For extended durability and even wear
- Provides longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton Cloth

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/16 x 3/4 x 3/32	80	100	08834180005
3/16 x 1 x 3/32	60	100	08834180023
Use M-2E Mandrel	80	100	08834180024
	100	100	08834180025
	120	100	08834180026
	150	100	08834180027
	180	100	08834180028
	240	100	08834180030
	320	100	08834180032
1/4 x 3/4 x 1/8	60	100	08834180042
Use M-3 or M-7 Mandrel	80	100	08834180043
	120	100	08834180045
1/4 x 1 x 1/8	50	100	08834180060
Use M-4 or M-8 Mandrel	60	100	08834180061
	80	100	08834180062
	100	100	08834180063
	120	100	08834180064
	150	100	08834180065
	180	100	08834180066
	240	100	08834180068
	320	100	08834180070
1/4 x 1-1/2 x 1/8	50	100	08834180079
Use M-9 Mandrel	60	100	08834180080
	80	100	08834180081
	100	100	08834180082
	120	100	08834180083
	150	100	08834180084
	180	100	08834180085
	320	100	08834180089
1/4 x 2 x 1/8	80	100	08834180100
Use M-10 Mandrel	100	100	08834180101
	120	100	08834180102
5/16 x 1 x 1/8	60	100	08834180137
use M-4 or M-8 Mandrel	80	100	08834180138
	120	100	08834180140
5/16 x 1-1/2 x 1/8	60	100	08834180156
use M-9 Mandrel	80	100	08834180157
	120	100	08834180159
3/8 x 3/4 x 1/8	60	100	08834180194
use M-7 Mandrel	80	100	08834180195
	120	100	08834180197
3/8 x 1 x 1/8	40	100	08834180211
use M-8 Mandrel	50	100	08834180212
	60	100	08834180213
	80	100	08834180214
	100	100	08834180215
	120	100	08834180216
	150	100	08834180217
	180	100	08834180218
	240	100	08834180220

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/8 x 1-1/2 x 1/8	36	100	08834180228
use M-9 Mandrel	40	100	08834180229
	50	100	08834180230
	60	100	08834180231
	80	100	08834180232
	100	100	08834180233
	120	100	08834180234
	150	100	08834180235
	180	100	08834180236
	240	100	08834180238
	320	100	08834180240
3/8 x 2 x 1/8	60	100	08834180250
use M-10 Mandrel	80	100	08834180251
	100	100	08834180252
	120	100	08834180253
1/2 x 3/4 x 1/8	80	100	08834180270
use M-7 Mandrel			
1/2 x 1 x 1/8	40	100	08834180286
use M-8 Mandrel	50	100	08834180287
	60	100	08834180288
	80	100	08834180289
	100	100	08834180290
	120	100	08834180291
	150	100	08834180292
	180	100	08834180293
	240	100	08834180295
	320	100	08834180297
1/2 x 1-1/2 x 1/8	36	100	08834180304
use M-9 Mandrel	40	100	08834180305
	50	100	08834180306
	60	100	08834180307
	80	100	08834180308
	100	100	08834180309
	120	100	08834180310
	150	100	08834180311
	180	100	08834180312
	240	100	08834180314
	320	100	08834180316
1/2 x 1-1/2 x 3/16	120	100	08834180919
use M-16 Mandrel			
1/2 x 2 x 1/8	60	100	08834180326
use M-10 Mandrel	80	100	08834180327
	100	100	08834180328
	120	100	08834180329
	180	100	08834180331
	240	100	08834180333
	320	100	08834180335
1/2 x 2 x 3/16	60	100	08834180350
use M-17 Mandrel	80	100	08834180653
	120	100	08834180338
1/2 x 2 x 1/4	40	100	08834183168
use M-22 Mandrel	80	100	08834180351
5/8 x 1 x 3/16	80	100	08834180364
use M-15 Mandrel			

CONTINUED

Refer to the back of this section for mandrels.



AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
5/8 x 1-1/2 x 1/8	36	100	08834180395
use M-9 Mandrel	40	100	08834180392
	50	100	08834180393
	60	100	08834180275
	80	100	08834180789
	120	100	08834180394
5/8 x 1-1/2 x 3/16	50	100	08834180381
use M-16 Mandrel	60	100	08834180382
	80	100	08834180383
5/8 x 2 x 1/8	60	100	08834182505
use M-10 Mandrel	80	100	08834181080
5/8 x 2 x 3/16	50	100	08834180400
use M-10 Mandrel	60	100	08834180401
	80	100	08834180402
	100	100	08834180403
3/4 x 1 x 1/8	80	100	08834180469
use M-8 Mandrel	120	100	08834181543
3/4 x 1 x 3/16	40	100	08834180456
use M-15 Mandrel	80	100	08834180459
	120	100	08834180461
3/4 x 1-1/2 x 1/8	40	100	08834180069
use M-9 Mandrel	60	100	08834180490
	80	100	08834180527
	120	100	08834180487
3/4 x 1-1/2 x 3/16	36	100	08834180474
use M-16 Mandrel	40	100	08834180475
	50	100	08834180476
	60	100	08834180477
	80	100	08834180478
	100	100	08834180479
	120	100	08834180480
	180	100	08834180482

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/4 x 1-1/2 x 1/4	36	100	08834180907
100/box 400/case	60	100	08834180489
use M-21 Mandrel	80	100	08834180358
	100	100	08834180523
	120	100	08834180488
	150	100	08834182807
3/4 x 2 x 1/8	60	100	08834180791
use M-10 Mandrel			
3/4 x 2 x 3/16	40	100	08834180494
use M-17 Mandrel	60	100	08834180496
	80	100	08834180497
	100	100	08834180498
	120	100	08834180499
3/4 x 2 x 1/4	60	100	08834180506
use M-22 Mandrel	80	100	08834181297
	100	100	08834180509
	120	100	08834180507
1 x 1-1/2 x 1/8	60	100	08834180580
use M-9 Mandrel	80	100	08834180584
1 x 1-1/2 x 1/4	36	100	08834181195
use M-21 Mandrel	60	100	08834180587
	80	100	08834180583
1 x 2 x 3/16	40	100	08834180589
use M-17 Mandrel	60	100	08834180591
	80	100	08834180592
1 x 2 x 1/4	60	100	08834180603
use M-22 Mandrel	80	100	08834180606
	120	100	08834180585

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



MERIT SILICON CARBIDE CARTRIDGE ROLLS

GOOD CHOICE FOR TOUGH, DIFFICULT-TO-GRIND MATERIALS, AS WELL AS SOFT, LOADING MATERIALS

FEATURES

- Sharp silicon carbide abrasive
- Durable resin bond system

BENEFITS

- Provides high initial cut on non-ferrous and soft-loading materials such as titanium, masonry, composites, plastic, and rubber
- Exceptional grain retention and longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Silicon Carbide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/4 x 1-1/2 x 1/8	60	100	08834183274
Use M-9 Mandrel	80	100	08834182359
	120	100	08834189131
3/8 x 1-1/2 x 1/8	60	100	08834181309
Use M-9 Mandrel	80	100	08834180710
	120	100	66261042229

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Silicon Carbide
BACKING:	Cotton


SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	08834189233
Use M-9 Mandrel	80	100	08834180712
	120	100	66261086969

Refer to the back of this section for mandrels.




Spiral Rolls

- All spiral roll part numbers shown are full tapered, resin bond, half glued
- Half-tapered and sidewall-tapered are available for quotation as made-to-order products
- Quarter and full glue are also available for quotation as made-to-order products
- Ceramic Alumina blend spiral rolls are also available for quotation as made-to-order products



Full Taper

- Especially useful for grinding/polishing of channels, fillets and radii, and deburring small holes
- Full taper used when the area to finished is hard to reach with a full cartridge roll
- The tapered roll conforms to smaller areas
- Fits into irregular concaves, contours, channels



Half Taper

- Used when the area to be finished is not narrow but a beginning point on the roll is needed
- The portion of the roll that is not tapered is then used to finish off the sides



Sidewall Taper

- The portion of the roll that is tapered guides the roll down to the area to be finished
- The sidewall then finishes off the sides

FEATURED PRODUCTS



MERIT CERAMIC ALUMINA SPIRAL ROLLS – FULL TAPER

BEST CHOICE FOR HARD-TO-GROUND MATERIALS – STAINLESS STEEL, COBALT, INCONEL, AND TITANIUM

FEATURES

- Next-generation ceramic alumina abrasive grain
- Advanced grinding aid
- Improved resin bond system
- Strong X-weight cotton backing

BENEFITS

- Greatest productivity with significantly faster cut rates
- Resists wear, resulting in 50% – 300% longer life
- Cooler cutting, longer life
- Exceptional grain retention and longer life
- Durability and even wear

AVAILABILITY

TIER:	BEST
BRAND:	Merit
ABRASIVE:	Ceramic Alumina
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/8 x 1-1/2 x 1/8	60	100	66261194481
Use M-9 Mandrel	80	100	66261194490
	120	100	66261194491

CONTINUED

AVAILABILITY

TIER:	BEST
BRAND:	Merit
ABRASIVE:	Ceramic Alumina
BACKING:	Cotton
OTHER:	Supersized

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	66261194484
Use M-9 Mandrel	80	100	66261194492
	120	100	66261194495



NEW

MERIT ALUMINUM OXIDE PLUS SPIRAL ROLLS – FULL TAPER

ESPECIALLY USEFUL FOR COOLER GRINDING/POLISHING OF CHANNELS, FILLETS AND RADII, AND DEBURRING SMALL HOLES..

FEATURES

- Premium aluminum oxide abrasive
- Strong X-weight cotton backing construction
- Advanced, full resin bond system

BENEFITS

- Runs cooler and more efficiently; ideal for grinding exotic alloys
- For extended durability and even wear
- Provides exceptional grain retention and longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Premium Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/8 x 1-1/2 x 1/8	60	100	77696089010
use M-9 Mandrel	80	100	77696089011
	120	100	77696089012

CONTINUED

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Premium Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	77696089013
use M-9 Mandrel	80	100	77696089014
	120	100	77696089015

Refer to the back of this section for mandrels.



MERIT ALUMINUM OXIDE SPIRAL ROLLS – FULL TAPER

ESPECIALLY USEFUL FOR COOLER GRINDING/POLISHING OF CHANNELS, FILLETS AND RADII, AND DEBURRING SMALL HOLES..

FEATURES

- Quality aluminum oxide abrasive
- Strong X-weight cotton backing construction
- Durable resin bond system

BENEFITS

- For the buyer whose major purchasing criterion is low initial price
- Durability and even wear
- Exceptional grain adhesion and longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/8 x 1 x 1/8	60	100	08834181714
use M-8 Mandrel	80	100	08834181715
	120	100	08834181717
	180	100	08834181719
3/8 x 1-1/2 x 1/8	50	100	08834181723
use M-9 Mandrel	60	100	08834181724
	80	100	08834181708
	120	100	08834181727
	150	100	08834181728
	180	100	08834181709
1/2 x 1 x 1/8	60	100	08834181734
use M-8 Mandrel	80	100	08834181735
	120	100	08834181737
	180	100	08834181739
1/2 x 1-1/2 x 1/8	36	100	08834181230
use M-9 Mandrel	40	100	08834181742
	50	100	08834181743
	60	100	08834181744
	80	100	08834181745
	100	100	08834181746
	120	100	08834181747
	180	100	08834181749
	240	100	08834181750

CONTINUED

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 2 x 1/8	60	100	08834181754
use M-10 Mandrel	80	100	08834181755
	120	100	08834181757
5/8 x 1-1/2 x 1/8	100	100	08834181776
use M-9 Mandrel	120	100	08834181777
	240	100	08834183313
	320	100	08834181781
5/8 x 1-1/2 x 3/16	80	100	08834181444
use M-16 Mandrel			
3/4 x 1-1/2 x 1/8	60	100	08834181286
use M-9 Mandrel	80	100	08834180886
3/4 x 1-1/2 x 3/16	50	100	08834181807
use M-16 Mandrel	60	100	08834181808
	80	100	08834181809
	120	100	08834181811
3/4 x 2 x 3/16	60	100	08834181820
use M-17 Mandrel			
1 x 1-1/2 x 1/8	60	100	08834181240
use M-9 Mandrel			
1 x 2 x 3/16	36	100	08834181875
use M-17 Mandrel	60	100	08834181878
	80	100	08834181879

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



MERIT SILICON CARBIDE SPIRAL ROLLS – FULL TAPER

GOOD CHOICE FOR TOUGH, DIFFICULT-TO-GRIND MATERIALS, AS WELL AS SOFT, LOADING MATERIALS

FEATURES

- Sharp silicon carbide abrasive
- Durable resin bond system

BENEFITS

- Provides high initial cut on non-ferrous and soft-loading materials such as titanium, masonry, composites, plastic, and rubber
- Exceptional grain retention and longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Silicon Carbide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
3/8 x 1-1/2 x 1/8	60	100	08834189901
use M-9 Mandrel	80	100	08834189904
	120	100	66261046936

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Silicon Carbide
BACKING:	Cotton

SIZE (D x L x H)	GRIT	STD. PKG.	PART #
1/2 x 1-1/2 x 1/8	60	100	66261185977
use M-9 Mandrel	80	100	08834183460
	120	100	08834183448

Refer to the back of this section for mandrels.



Tapered Cone Points



- Tapered cone points are similar to cartridge rolls but their shape lends greater accessibility to many difficult-to-reach work areas
- They are used for deburring holes and in close tolerance work areas
- Popular sizes and mandrels are listed, with additional sizes available upon request as made-to-order products
- Ceramic alumina, ceramic alumina blend, aluminum oxide plus, and silicon carbide cone points are available upon request as made-to-order products

FEATURED PRODUCTS



MERIT ALUMINUM OXIDE TAPERED CONE POINTS

GOOD STARTING SPECIFICATION FOR FLASH REMOVAL, POLISHING, OR REMOVING MACHINE TOOL MARKS AND EDGE BREAKING ON ALL TYPES OF METAL IN DIFFICULT-TO-REACH WORK AREAS.

FEATURES

- Quality aluminum oxide abrasive
- Strong X-weight cotton backing construction
- Durable resin bond system

BENEFITS

- Tough and durable
- For extended durability and even wear
- Provides longer life

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton
TD. PKG.	PART #
00	08834180873
00	08834182043
00	08834182717
00	08834186890
00	08834182535
00	08834182044
00	08834182537

CONTINUED

AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	Cotton
STD. PKG.	PART #
500	08834186892
500	08834186893
500	08834180918
500	08834182197
500	08834182199
500	08834182200
500	08834186894
500	08834186895
500	08834182855

Test Kits



Merit Ceramic Alumina Cartridge Roll Test Kit

- Part # 66261066726
- Kit includes a variety of our Merit ceramic alumina cartridge rolls, spiral rolls and mandrels in popular sizes and grits.

Merit Aluminum Oxide Cartridge Roll Test Kit "CR"

- Part # 08834181061
- Includes over 120 pieces of our most popular sizes, grits and shapes with their appropriate mandrels.

Merit General Purpose Test Kit "GP"

- Part # 08834169025
- Includes samples of various Merit abrasive specialties. One of these kits could be worth the cost of the entire kit by solving your problems in deburring, polishing and grinding.

Merit Porting Test Kit "APK-M0"

- Part # 08834169032
- The samples in this kit highlight Merit specialties for general metal and wood working polishing and finishing applications.




Cartridge and Spiral Roll Mandrels

MODEL #	PILOT DIA.	PILOT LENGTH	SHANK DIA.	SHANK LENGTH	OVERALL LENGTH	PART #
Cartridge and Spiral Roll Mandrels						
M-2E	3/32	3/4	1/4	1	3	08834183799
M-2	3/32	1	1/8	1	3	08834181202
M-3	1/8	1/2	1/8	1	2-1/2	08834181203
M-4	1/8	3/4	1/8	1	2-1/2	08834181204
M-5	1/8	1	1/8	1	2-3/4	08834181205
M-6	1/8	1-1/2	1/8	1	2-1/2	08834181206
M-7	1/8	1/2	1/4	1-1/4	2-1/4	08834181207
M-8	1/8	3/4	1/4	1-1/4	2-1/2	08834181208
M-9	1/8	1	1/4	1-1/4	2-3/4	08834181209
M-10	1/8	1-1/2	1/4	1-1/4	3-1/4	08834181210
M-11	1/8	2	1/4	1-1/4	4	08834181211
M-12	3/16	1/2	1/8	1-1/4	2-1/4	08834181212
M-13	3/16	3/4	1/8	1-1/4	2-1/2	08834181213
M-14	3/16	1/2	1/4	1-1/4	2-1/2	08834181214
M-15	3/16	3/4	1/4	1-1/4	2-3/4	08834181215
M-16	3/16	1	1/4	1-1/4	3	08834181216
M-17	3/16	1-1/2	1/4	1-1/4	3-1/2	08834181217
M-18	3/16	2	1/4	1-1/4	4	08834181218
M-19	1/4	1/2	1/4	1-1/4	2-1/2	08834181219
M-20	1/4	3/4	1/4	1-1/4	2-3/4	08834181220
M-21	1/4	1	1/4	1-1/4	3	08834181221
M-22	1/4	1-1/2	1/4	1-1/4	3-1/2	08834181222
M-23	1/4	2	1/4	1-1/4	4	08834181223
M-24	5/16	3/4	1/4	1-1/4	2-3/4	08834181224
M-25	5/16	1	1/4	1-1/4	3	08834181225
M-26	5/16	1-1/2	1/4	1-1/4	3-1/2	08834181226
M-27	5/16	2	1/4	1-1/4	4	08834181227

STANDARD PACKAGE = 1

Recommended Pilot Length for Mandrels

3/4 Roll Length	use 1/2 Pilot
1 Roll Length	use 3/4 Pilot
1-1/2 Roll Length	use 1 Pilot
2 Roll Length	use 1-1/2 Pilot



Extra Shank Length Mandrels

MODEL #	SHANK LENGTH	OVERALL LENGTH	PART NO.
Extras Shank Length Mandrels			
M-8-4	4	5-1/4	08834180116
M-8-6	6	7-1/4	08834180122
M-9-2.5	2-1/2	4	08834180096
M-9-3	3	4-1/2	08834180129
M-9-4	4	5-1/2	08834180074
M-9-6	6	7-1/2	08834180131
M-9-8	8	9-1/2	08834180133
M-10-4	1-3/4	4	08834180092
M-10-6	3-3/4	6	08834180145

ALL EXTRA SHANK LENGTH MANDRELS ARE 1/4" DIAMETER


STANDARD PACKAGE = 1

Tapered Cone Point Mandrels

DESCRIPTION	SHANK	PART #
Cone Point Mandrels		
A-10	1/4	08834181300
B-20	1/4	08834181301
C-30	1/4	08834181302
D-40	1/4	08834181303
E-50	A1/4	08834181304
F-60	1/4	08834181305
G-70	1/4	08834181306
H-80	1/4	08834181307
I-90	1/4	08834181308
K-110	1/8	08834181310

STANDARD PACKAGE = 1






CATEGORY DEFINITION

Square pads, cross pads and overlap slotted discs are all used on high-speed pneumatic tools for deburring, blending, cleaning, and polishing applications. All of these abrasive specialties are designed for applications in small, tight, hard-to-access locations on parts that are being finished.

BENEFITS:	Variety of shapes and sizes to fit application and part geometry Shapes provide flexibility for the application, while eliminating aggressiveness of the sanding action Cross pads allow visibility of the surface while sanding, to ensure correct amount of material is removed
GRIT RANGE:	50 – 180
ABRASIVE GRAIN:	Ceramic Alumina, Aluminum Oxide
BACKING:	Cotton
MAXIMUM RPM:	1" Diameter – 25,000 1-1/2" to 2" Diameter – 18,000 to 23,000 2-1/2" Diameter – 14,000 to 18,000 3" Diameter – 12,000 to 14,000 4" Diameter – 8,000 to 12,000 5" to 6" Diameter – 5,500 to 7,500

APPLICATION/GRIT RECOMMENDATION GUIDE



FEATURED PRODUCTS



MERIT CERAMIC ALUMINA


BEST FOR HARD-TO-GROUND MATERIALS – STAINLESS STEEL, COBALT, INCONEL, AND TITANIUM

FEATURES

- Next-generation ceramic alumina abrasive grain
- Advanced grinding aid
- Improved resin bond system

BENEFITS

- Significantly faster cut rates versus any other abrasive
- Resists wear, resulting in 50%-300% longer life
- Greatest productivity; lowest total cost
- Cooler cutting, longer life
- Improved grain retention and longer life



MERIT ALUMINUM OXIDE

GOOD FOR MOST ID DEBURRING AND POLISHING APPLICATIONS

FEATURES

- Quality aluminum oxide abrasive grain
- Resin bond system
- Standard quick-change eyelet for easy mounting and removal on quick-change mandrel

BENEFITS

- Versatile; ideal for deburring, chamfering, and polishing most radii, holes, recesses, and cylinder walls
- Good grain retention and life
- Minimal downtime
- Mandrel use increases range and versatility




Merit Square Pads

- Corners wear down consistently exposing fresh abrasive; the pad becomes round for less aggressive stock removal
- Grind almost as fast as hard wheels, but are much smoother and easier to control
- For quick blending of channels, fillets, corners, or spotting flat surfaces

Square Pads

AVAILABILITY



SIZE (L x W x T)	EYELET	GRIT	STD. PKG.	TIER: ABRASIVE: OTHER:	PART #	PART #
1 x 1 x 6 ply	8-32	80	100			08834184826
1 x 1 x 8 ply	8-32	60	100			08834184828
		80	100			08834184124
		120	100			08834184994
1-1/2 x 1-1/2 x 1/2	1/4-20	60	100			08834184463
		80	100			08834184125
2 x 2 x 1/2	1/4-20	60	100		66261194520	08834184334
		80	100		66261194552	08834184397
		120	100		66261194554	
2 x 2 x 3/4	1/4-20	50	100			08834184487
		80	100			08834184394
3 x 3 x 1/4	1/4-20	60	100		66261194531	
		80	100		66261194555	08834184882
		120	100		66261194556	
3 x 3 x 1/2	1/4-20	50	100			08834182152
		60	100		66261194528	08834182057
		80	100		66261194557	08834184336
		120	100		66261194558	

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

CERAMIC ALUMINA BLEND AND ALUMINUM OXIDE PLUS SQUARE PADS ARE ALSO AVAILABLE UPON REQUEST AS MADE-TO-ORDER PRODUCTS.




Merit Cross Pads

- The shape of Merit cross pads enables you to see through to the contact area, and provides greater flexibility than square pads to conform to variable internal diameters
- Used for close-tolerance polishing of small radii and channels, deburring, and finishing of bell-mouth configurations
- All pads are furnished with standard quick-change eyelet, as listed
- Plain hole sizes must be specified and are available for quotation as made-to-order products

Cross Pads

AVAILABILITY



SIZE (L x W x T)	PLY	EYELET	GRIT	STD. PKG.	TIER: ABRASIVE: OTHER:	PART #	PART #
3/4 x 3/4 x 3/8	8	3-48	80	100			08834185578
1 x 1 x 3/8	8	3-48	60	100			08834184943
			80	100			08834185519
			100	100			08834184195
			120	100			08834185164
1-1/2 x 1-1/2 x 1/2	8	8-32	60	100		66261194496	08834184258
			80	100		66261194508	08834184465
			100	100			08834182196
			120	100		66261194511	08834182148
2 x 2 x 1/2	8	8-32	60	100			08834182156
			80	100			08834182157
			120	100			08834182132
2 x 2 x 3/4	8	8-32	60	100		66261194502	08834184128
			80	100		66261194513	08834184194
			120	100		66261194516	08834184285
2 x 2 x 1	8	8-32	120	100			08834184805
2-1/4 x 2-1/4 x 1/2	8	8-32	80	100			08834184402
2-1/2 x 2-1/2 x 3/4	8	8-32	80	100			08834184206
			120	100			08834184074
3 x 3 x 1	8	1/4-20	60	100		66261194504	08834182135
			80	100		66261194549	08834184119
			120	100		66261194551	08834184116
3 x 3 x 1	10	1/4-20	80	100			08834182140
3 x 3 x 1-1/2	10	1/4-20	80	100			08834182184
4 x 4 x 1	8	1/4-20	60	100			08834184142
			80	100			08834184135
			120	100			08834184377
4 x 4 x 1-1/2	8	1/4-20	80	100			08834184129
			120	100			08834184370

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.


CERAMIC ALUMINA BLEND AND ALUMINUM OXIDE PLUS CROSS PADS ARE ALSO AVAILABLE UPON REQUEST AS MADE-TO-ORDER PRODUCTS.

Refer to the back of this section for mandrels.



Overlap Slotted Discs

AVAILABILITY




TIER:

BRAND:

ABRASIVE:

OTHER:



BEST

Merit

Ceramic Alumina

Supersized, 2-Ply



GOOD

Merit

Aluminum Oxide

2 Per Set



GOOD

Merit

Aluminum Oxide

4 Per Set

SIZE (DIA.)	EYELET	GRIT	STD. PKG.	PART #	PART #	PART #
1	8-32	60	100		08834184346	
		80	100		08834184019	08834184085
		100	100		08834184224	
		120	100		08834184151	08834184236
		180	100		08834185078	
1-1/4	8-32	60	100		08834184270	
		80	100		08834184065	
		100	100		08834184291	
		120	100		08834184084	
		180	100			
1-1/2	8-32	60	100	66261195051	08834184066	
		80	100	66261195368	08834184079	
		100	100		08834184279	08834184023
		120	100	66261195367	08834186035	
		180	100		08834184498	
1-3/4	8-32	60	100		08834184655	
		80	100		08834184042	
		120	100			
2	8-32	60	100	66261195054		
		80	100	66261195055	08834184076	
		100	100		08834184145	
2-1/2	8-32	60	100	66261195056	08834184055	
		80	100		08834184444	
		120	100		08834184818	
3	1/4-20	50	100		08834184041	
		60	100	66261195057	08834184077	
		80	100	66261195058	08834184082	
		100	100		08834184344	
		120	100	66261195059	08834184000	
4	1/4-20	60	100		08834184159	
		80	100		08834185155	
		120	100		08834184431	
4-1/2	1/4-20	100	100		08834184302	
5	1/4-20	100	100			

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

ALL OVERLAP SLOTTED DISCS ARE AVAILABLE (MADE-TO-ORDER) REINFORCED WITH A FIBER WASHER

CERAMIC ALUMINA BLEND AND ALUMINUM OXIDE PLUS OVERLAP SLOTTED DISCS ARE ALSO AVAILABLE UPON REQUEST AS MADE-TO-ORDER PRODUCTS.


Merit Overlap Slotted Discs

- Used for deburring and polishing radii, holes and cylinder walls
- Our "2 to a set" configuration cuts on the inward motion only
- The "4 to a set" configuration, assembled back to back, cuts on both the inward and outward motions
- All discs are furnished with standard quick-change eyelet
- Plain hole sizes must be specified and are available for quotation as made-to-order products


Quick-Change Mandrels for Overlap Slotted Discs, Square and Cross Pads

CROSS PAD SIZE DIA.	SQUARE PAD SIZE DIA.	OAL	MODEL NO.	THD. SIZE	PART #
1/4, 3/8, and 1/2 wide		2-1/2	MM48-4	3-48	08834183162
3/4, 1 wide	Up thru 1-1/2 sq. x 1/2 thick 2 sq. x 1/4 or 3/8 thick	3	MM32-4	8-32	08834183163
		4	MM-32-4-4	8-32	08834121680
		6	MM-32-4-6	8-32	08834121681
All pads 2-1/2 x 1-1/2 and larger	2 sq. x 1/4 or 1/2 thick and larger	3	MM20-4	1/4-20	08834183164

FOR OVERLAP SLOTTED DISCS, CHOOSE A MANDREL WITH THE SAME THREAD SIZE AS THE DISC



EXTENDED MANDREL



CATEGORY DEFINITION

Flaps of abrasive cloth are stacked, inserted into a holder, and then attached to a mandrel. The flaps are designed to break down during use and reveal the next layer of abrasive.

Cloth flaps are mixed with non-woven flaps to create an interleaf bore polisher.

APPLICATIONS: For deburring, sizing, cleaning and polishing the interior diameters of cylinders, tubes and hydraulic fittings. Flaps adjust automatically to inside diameter, polishing the entire surface area with each pass.

Bore polishers are self-centering, so they apply equal pressure to full wall of inside diameter. Spring action design gives faster inside diameter cleaning, deburring and polishing to cylinders, deep bores and tubes.

Interleafed bore polishers are designed to polish and finish in one easy application. The abrasive flaps cut, while the non-woven flaps apply a fine finish.


GRIT RANGE: 60 - 240

ABRASIVE GRAIN: Aluminum Oxide

APPLICATION-TO-PRODUCT SHAPE RECOMMENDATION GUIDE

SHAPE	APPLICATION
 Bore Polisher Solid Flaps B-3 Series	- For 5/8" to 1" interior diameter bores 3 abrasive packs 1-1/2" wide, bonded to hub - Use with QC-5 mandrel Part # 08834154182
 Bore Polisher Solid Flaps B-4 Series	- For 1" to 4" interior diameter bores 4 abrasive packs 1-1/2" wide, bonded to hub - Use with BPM-4 mandrel Part # 08834154183
 Bore Polisher Solid Flaps B-8 Series	- For 2" to 5-7/8" interior diameter bores 8 abrasive packs 1-1/2" wide, bonded to hub - Use with BPM-8 mandrel Part # 08834154184
 Bore Polisher Scored Flaps	Available upon request as made-to-order products
 Bore Polisher Interleaf	Cloth flaps are mixed with non-woven flaps. Merit interleaf bore polishers do double duty. Designed to polish and finish in one easy application, they are the ideal choice when close tolerances must be maintained, while giving an interior a polished finish.

APPLICATION/GRIT RECOMMENDATION GUIDE





Merit Aluminum Oxide Bore Polishers


AVAILABILITY

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	X-wt. Cotton/Poly

DESCRIPTION	GRIT	MAX. RPM	STD. PKG.	PART #
Bore Polishers – Solid Flap B-3 and B-4 Series				
B-305	60	25,000	10	08834154190
Fits ID 5/8 to 1	80	25,000	10	08834154191
	120	25,000	10	08834154193
	180	25,000	10	08834154195
	240	25,000	10	08834154197
B-405	60	22,000	10	08834154091
Fits ID 1 to 1-1/2	80	22,000	10	08834154092
	120	22,000	10	08834154093
	180	22,000	10	08834154094
B-410	60	20,000	10	08834154100
Fits ID 1-1/2 to 2	80	20,000	10	08834154101
	120	20,000	10	08834154102
	180	20,000	10	08834154103
	240	20,000	10	08834154104
B-415	60	16,000	10	08834154109
Fits ID 2-1/8 to 2-1/2	80	16,000	10	08834154110
	120	16,000	10	08834154111
	180	16,000	10	08834154112
	240	16,000	10	08834154113
B-420	60	15,000	10	08834154118
Fits ID 2-1/2 to 3	80	15,000	10	08834154119
	120	15,000	10	08834154120
	180	15,000	10	08834154121
	240	15,000	10	08834154122
B-425	60	10,000	10	08834154127
Fits ID 3-1/8 to 4	80	10,000	10	08834154128
	120	10,000	10	08834154129
	180	10,000	10	08834154130
	240	10,000	10	08834154131

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

Mandrels for Bore Polishers



DESCRIPTION	MODEL NO.	THREAD	PART #
For B-3 Series	QC-5	5/16-18	08834154182
For B-4 Series	BPM-4	1/2-20	08834154183
For B-8 Series	BPM-8	1/4-20	08834154184
QC-5 Ext.	QC-5 Ext.	5/16-18	08834150573

STANDARD PACKAGE = 1

TIER:	GOOD
BRAND:	Merit
ABRASIVE:	Aluminum Oxide
BACKING:	X-wt. Cotton/Poly

DESCRIPTION	GRIT	MAX. RPM	STD. PKG.	PART #
Bore Polishers – Solid Flap B-8 Series				
B-810	60	16,000	10	08834154136
Fits ID 2 to 2-1/2	80	16,000	10	08834154137
	120	16,000	10	08834154138
	180	16,000	10	08834154139
	240	16,000	10	08834154140
B-815	60	15,000	10	08834154145
Fits ID 2-5/8 to 3	80	15,000	10	08834154146
	120	15,000	10	08834154147
	180	15,000	10	08834154148
	240	15,000	10	08834154149
B-820	60	10,000	10	08834154154
Fits ID 3-1/8 to 4	80	10,000	10	08834154155
	120	10,000	10	08834154156
	180	10,000	10	08834154157
	240	10,000	10	08834154158
B-825	60	8,000	10	08834154163
Fits ID 4-1/4 to 5-1/4	80	8,000	10	08834154164
	120	8,000	10	08834154165
	180	8,000	10	08834154166
	240	8,000	10	08834154167
B-830	60	8,000	10	08834154172
Fits ID 5-1/4 to 5-7/8	80	8,000	10	08834154173
	120	8,000	10	08834154174
	180	8,000	10	08834154175
	240	8,000	10	08834154176


Bore Polishers – Scored Flaps

Available on request as made-to-order products

Bore Polishers – Interleaf

B-405 Interleaf	80	22,000	10	08834150271
Fits ID 1 to 1-1/2	180	22,000	10	08834150273
B-410 Interleaf	80	20,000	10	08834150275
Fits ID 1-1/2 to 2				

Extension Mandrels for Bore Polishers



DIAMETER X LENGTH	MODEL NO.	THREAD	PART #
1/4 x 4	EM-144	1/4-20	08834154185
1/4 x 6	EM-146	1/4-20	08834154186
1/4 x 8	EM-148	1/4-20	08834154187

To extend a B-3 series bore polisher, attach the QC-5 Ext. to the bore polisher, then attach the desired length extension mandrel above to the QC-5 Ext. To extend a B-4 series bore polisher, attach the adapter piece of the BPM-4 mandrel to the bore polisher, then attach the desired length extension mandrel above to the BPM-4 adapter piece. To extend a B-8 series bore polisher, attach the desired length extension mandrel above directly to the bore polisher. Standard package = 1.

Test Kit

Merit Bore Polisher Test Kit “BP”

- Part # 08834154181
- Contains ten bore polishers and two mini 1/4"-20 thread flap wheels in assorted sizes and grits for finishing 1" to 5" interior diameters, and mandrel for 1/4" chuck.



Coated Abrasives

A coated abrasive product is made up of three basic raw materials: an abrasive mineral, the backing onto which the abrasive is applied, and an adhesive bond.

Abrasive Types

Emery (6)

Emery is a dark gray, round-shaped grain which tends to polish rather than abrade a work surface.

- For polishing and cleaning metal only

Garnet (5)

Garnet is reddish brown in color. This natural abrasive is medium hard and relatively sharp, but not as durable as synthetic abrasives.

- For use on wood only
- Particularly good for soft woods such as pine
- Produces an excellent finish

Silicon Carbide (4)



Silicon carbide is the hardest and sharpest of the manufactured abrasives. Because of its extreme sharpness, this bluish-black abrasive grain permits fast stock removal and cool cut.

- Cast iron
- Non-ferrous metals, i.e. brass, aluminum and bronze
- Non-metallics, i.e. glass, rubber, plastic and stone
- Final finish on wood and stainless steel
- Abrasive planing particleboard

Light Brown Aluminum Oxide (2)

Light brown aluminum oxide is a tough, yet sharp synthetic abrasive characterized by cool cut, long life and the ability to break down under pressure, producing new cutting edges.

- Production wood sanding
- Non-ferrous metal finishing



Brown Aluminum Oxide (2)

Brown aluminum oxide is a tough, durable, synthetic abrasive characterized by the long life and wear resistance of its cutting edges. It offers enormous penetrating strength, even at high speeds.

- Ferrous metals
- Aluminum
- Hardwood



Heat-treated Aluminum Oxide (2)

Heat-treated aluminum oxide is a tough but cool cutting abrasive which gives both long life and freeness of cut on a wide range of materials.

- Ferrous metals
- Wood sanding



Zirconia Alumina (8)

Zirconia alumina is an ultra-tough, synthetic abrasive which provides a free, cool cut for high stock removal applications. It is tougher and sharper than aluminum oxide. It has a micro-crystalline structure which allows for controlled breakdown and self-sharpening.


- Heavy-duty snagging and grinding of all ferrous and non-ferrous metals
- Abrasive planing of wood, plywood and particleboard
- Grinding fiberglass, rubber and plastics



Ceramic Alumina (9)

The sub-micron structure of ceramic alumina allows each grain to continually expose sharp cutting points, resulting in a cooler cutting action and an extended life.

- All ferrous/non-ferrous metals, carbon steel and exotic alloys



How to Read a Coated Abrasive Specification

The Norton coated abrasive marking system includes both a generic and a technical marking, which identifies the actual components which make up the product. The markings identify the tradename, abrasive type, bond, backing, and any special features. An example would be: Norton Blaze R980P.

R 9 8 0 P				
BACKING / BOND	PRINCIPAL ABRASIVE	COATING	RANDOM	MODIFIER
A = Lightweight Paper (A-D wts.) excluding Waterproof	1 = Aluminum Oxide	1 = Openkote	Designates different products within the same product group.	Additional description, often indicative of a product upgrade, i.e. "P" = Plus
F = Fiber	2 = Aluminum Oxide	2 = Closekote		
H = Heavy Paper / Resin Bond (E and F wts.)	3 = Layered Aluminum Oxide	3 = Openkote		
K = Cloth / Glue Bond (J and X wts.)	4 = Silicon Carbide	4 = Closekote		
PB = B-wt. Paper with Resin Bond and Latex	5 = Garnet	5 = Openkote		
Q = Various (e.g. Screen-Bak, Film, and Foam)	6 = Crocus & Emery	6 = Closekote	6 = Closekote	
R = Cloth / Resin Bond (H, J, X and Y wts.)	8 = Zirconia Alumina	7 = Openkote	7 = Openkote	
T = Waterproof Paper (A, C wts.)	9 = Norton SG Ceramic Alumina	8 = Closekote	8 = Closekote	
U = Lightweight Waterproof Paper/ NORaX Engineered Abrasive Resin Bond		9 = Openkote	9 = Openkote	
		0 = Closekote	0 = Closekote	

Backing Types

Backings are the base for the abrasive minerals and, combined with the adhesive bond, support and anchor the abrasive mineral. The backings used in the manufacture of coated abrasives are:

Paper

Due to the fine surface of paper, a consistent finish is produced. Paper weights include *A, B, C, D, E* and *F* weights with *A* being the lightest and most flexible and *F* being the heaviest and least flexible. *A, B, C* and *D* weight papers are used for hand sanding and light mechanical operations in the form of sheets, PSA (pressure sensitive adhesive) and hook and loop discs and sheet rolls. *E* and *F* weight papers are primarily used for more aggressive mechanical operations in the form of belts and discs.

Cloth

Cloth backings used for coated abrasives are identified by weight. Cloth backings are filled or “finished” with a variety of materials (glues or resins) to create various backing characteristics, most notably flexibility. Several cloth types are used: cotton, polyester, polyester/nylon and polyester/cotton blends, and rayon.

There are three basic weights of cloth: J-weight or “jeans” is the lightest and most flexible. X-weight or “drills” is a heavier cloth that ranges in flexibility, strength and durability and is used on the broadest range of applications. Y-weight is a heavyweight drills cloth used on heavy-duty, high stock removal operations.

Fiber

Vulcanized fiber (cotton fibers which are chemically treated and then pressed under temperature and pressure to form a very durable backing) is used exclusively as the backing for resin fiber discs.

Film

Polyester film backing comes in 3 mil. and 5 mil. thicknesses, which have high strength and surface smoothness. They are used primarily in disc and roll applications requiring consistent surface finish.

Bond Types

An adhesive bond system is required to secure the abrasive mineral to the backing. All coated abrasive products are made with a two stage bonding process, the *make coat* and the *size coat*.

The *make coat* is the first layer of bond applied to the backing. The make coat provides the adhesive base between the abrasive mineral and the backing.

The *size coat* is the second coat, which is applied over the abrasive mineral and make coat to anchor the abrasive mineral and provide the desired physical strength of the finished product.


Glue, urea resin, and phenolic resin are the three basic bonding agents most commonly used. There are many size coat and make coat combinations, such as *glue over glue, urea over glue, and resin over resin*. *Glue over glue* is the most flexible bond while *resin over resin bond* is moisture-resistant, harder, less flexible, heat-resistant and has superior grain retention.

Coating Types

There are two types of abrasive coatings used in the manufacturing of coated abrasives: *open coat* and *closed coat*.

Open Coat


With an open coat, 50% to 75% of the surface is covered by abrasive grain. There are evenly spaced voids between the particles of grain, helping reduce the effect of loading caused by wood dust or metal particles.



OPEN COAT
(1/3 LESS GRAIN THAN CLOSED)

Closed Coat

With a closed coat, the entire surface is covered with abrasive grain, with no voids between the particles. This is the most typical coating, permitting the greatest degree of stock removal and longest product life.



CLOSED COAT

Coated Abrasive Grit Comparison Chart

AVERAGE PARTICLE SIZE IN MICRONS	GRADING SYSTEMS (OTHER THAN EMERY)			EMERY PRODUCTS
	CAMI	FEPA	JIS	
5.0	—	—	—	—
6.0	—	—	3000	—
6.5	1200	—	2500	4/0
8.4	—	P2500	—	—
8.5	—	—	2000	—
9.2	1000	—	—	3/0
10.3	—	P2000	—	—
10.5	—	—	1500	—
12.2	800	—	1200	—
12.6	—	P1500	—	—
15.0	—	—	—	—
15.3	—	P1200	1000	—
16.0	600	—	—	2/0
18.3	—	P1000	800	—
19.7	500	—	—	0
20.0	—	—	—	—
21.8	—	P800	—	—
23.6	400	—	600	—
25.0	—	—	—	—
25.75	—	P600	—	—
28.8	360	—	500	—
30.0	—	P500	—	—
35.0	—	P400	400	—
36.0	320	—	—	—
40.0	—	—	360	—
40.5	—	P360	—	—
44.0	280	—	—	1
45.0	—	—	—	—
46.2	—	P320	320	—
50.0	—	—	—	—
52.5	—	P280	280	—
53.5	240	—	—	—
55.0	—	—	—	—
58.5	—	P240	—	—
60.0	—	—	240	—

AVERAGE PARTICLE SIZE IN MICRONS	GRADING SYSTEMS (OTHER THAN EMERY)			EMERY PRODUCTS
	CAMI	FEPA	JIS	
64.0	—	—	—	2
65.0	—	P220	220	—
66.0	220	—	—	—
78.0	180	P180	180	—
79.0	—	—	—	3
93.0	150	—	150	—
95.0	—	—	—	FINE
97.0	—	P150	—	—
116.0	120	—	120	—
127.0	—	P120	100	—
136.0	—	—	—	MEDIUM
141.0	100	—	—	—
156.0	—	P100	—	—
189.0	—	—	—	COARSE
192.0	80	—	80	—
197.0	—	P80	—	—
260.0	—	P60	—	—
268.0	60	—	60	—
326.0	—	P50	50	—
341.0	—	—	—	EX. COARSE
351.0	50	—	—	—
412.0	—	P40	40	—
428.0	40	—	—	—
524.0	—	P36	—	—
535.0	36	—	36	—
622.0	—	P30	—	—
638.0	30	—	30	—
715.0	24	—	—	—
740.0	—	P24	24	—
905.0	20	—	—	—
984.0	—	P20	20	—
1320.0	16	—	16	—
1324.0	—	P16	—	—
1764.0	—	P12	—	—
1842.0	12	—	—	—



®

we've surfaced faster solutions **THAT WORK HARD AND PAY BETTER**

For stripping, deburring, finishing, blending or polishing surfaces and coatings, Norton Bear-Tex non-woven innovations reduce steps and improve surface finish.

**CLEAN
BOND[®]**
TECHNOLOGY

Our patented Clean Bond Technology eliminates smearing.



NORTON ***Rapid***
STRIP[™]

Strip Away Old Ideas

Quick and easy rough cleaning and stripping of scale and heavy stock on a variety of materials while maintaining its non-loading feature.



NORTON ***Rapid***
PREP[™]

Prep for the Future

Cleaning and surface conditioning Norton Rapid Prep products deliver higher material removal, longer life and consistent, smear-free finishes - even on high nickel content alloys



NORTON ***Rapid***
BLEND[™]

Blending In is Easy

Polishing and finishing with Norton Rapid Blend discs leaves a smear-free final finish in fewer steps.



CATEGORY DEFINITION

Non-woven depressed center discs have three components: strong synthetic fiber mesh and quality abrasives, bonded together by a smear-resistant adhesive. Rapid Strip discs have an open web construction that enables aggressive cutting action while maintaining a cool, non-loading surface. Rapid Blend discs have a unitized construction with varying weave – from open to tighter – for deburring and finishing. Rapid Prep discs have a more open weave that excels in preparation and cleaning of a surface. Each product provides excellent cutting action while improving surface finish.

APPLICATIONS: Medium-to-light material removal, deburring, blending, cleaning, finishing, and polishing





SIZE RANGE: 4-1/2" - 7"

GRIT RANGE: X-Coarse, Coarse, Medium, Fine, Very Fine

ABRASIVE GRAIN: Ceramic Alumina, Silicon Carbide, Aluminum Oxide



WHY CHOOSE NON-WOVEN DEPRESSED CENTER DISCS?



Non-Woven Right Angle Discs vs. Fiber Discs, Wire Wheels, and Depressed Center Wheels

- Deburring, blending and finishing done with one product to reduce the number of steps
- To provide a controlled, sustained finish
- To prevent undercutting and gouging
- To provide a cooler grinding action to lessen the chance of warping or discoloration
- When loading is an issue with fiberglass, adhesives and soft metals
- For stripping coatings and paint off of hard materials like concrete, cement and stone
- Less vibration and quieter for high operator acceptance
- To provide an alternative to wire brushes

MATERIAL/APPLICATION-TO-PRODUCT RECOMMENDATION GUIDE

	BEST Highest Productivity. Lowest Total Cost.	BETTER Excellent Blend of Performance & Price.	GOOD Consistent Performance. Low Initial Price.
Removing scale and coarse welding marks	Blaze Rapid Strip Ceramic X/Coarse	–	Rapid Strip S/C X-Coarse
Removing coatings, epoxy/glue, paint and other clogging material			
Removing rust, oxidation, corrosion and residue			
Removing parting lines and seams on fiberglass parts			
Removing paint/graffiti from concrete/stone			
Removing weld marks and weld splatter	–	Vortex Rapid Blend A/O Coarse	Rapid Blend A/O Coarse
Stainless steel deburring and cleaning			
Removing small flashings and parting lines			
Surface preparation before coatings/plating	–	Vortex Rapid Prep A/O Medium	Rapid Prep A/O Medium
Light cleaning			
Cleaning and prepping welds	–	Vortex Rapid Prep A/O Fine	Rapid Prep A/O Fine
Removing blemishes after welding stainless			
Blending and finishing all metal parts	–	Vortex Rapid Blend A/O Very Fine	Rapid Blend S/C Very Fine
Creating decorative finishes on stainless steel			
Final finishing and polishing			
Final finishing/polishing where high conformability is needed	–	–	Rapid Prep A/O Very Fine



APPLICATION/PRODUCT RECOMMENDATION GUIDE

	MOST AGGRESSIVE / LEAST CONFORMABLE			LEAST AGGRESSIVE / MOST CONFORMABLE	
DEPRESSED CENTER	BLAZE RAPID STRIP	VORTEX RAPID BLEND A/O MED. RAPID BLEND A/O COARSE	RAPID BLEND A/O MEDIUM	RAPID BLEND S/C FINE	RAPID PREP VERY FINE
DISCS WITH BACK-UP PAD		RAPID PREP A/O COARSE	RAPID PREP A/O MEDIUM	RAPID PREP A/O FINE	
SCALE REMOVAL	BEST CHOICE				
STOCK REMOVAL	BEST CHOICE	SECOND CHOICE			
HEAVY DEBURRING	SECOND CHOICE	BEST CHOICE			
LIGHT DEBURRING		BEST CHOICE	SECOND CHOICE		
LIGHT FINISHING		SECOND CHOICE	BEST CHOICE		
BLENDING			BEST CHOICE	SECOND CHOICE	
FINISHING			SECOND CHOICE	BEST CHOICE	
POLISHING				BEST CHOICE	SECOND CHOICE

CROSS REFERENCE GUIDE

	STRIPPING EXTRA COARSE	SURFACE FINISHING COARSE – MEDIUM – FINE				SURFACE PREP VERY FINE
	BEST Blaze Rapid Strip	GOOD Rapid Strip	BETTER Vortex Rapid Blend	GOOD Rapid Blend	BETTER Vortex Rapid Prep	GOOD Rapid Prep
NORTON						
3M	–	Clean & Strip	–	–	–	SL Surface Conditioning
Bibielle	–	SDR Strip-It/Red	–	Unitized	–	–
Camel	–	EZ Strip Black/Red	–	–	–	–
Flexovit	–	Clean & Strip	–	–	–	–
Hermes	–	Webrax	–	–	–	–
Pearl	–	S/C Stripping	–	–	–	Surface Preparation
Pferd	–	Policlean	–	Poliflex PUR	–	–
Sait	–	Sait-Strip	–	Unitized	–	–
Standard	–	Cleaning	–	Unitized	–	–
Superior	–	Stripping	–	Unitized	–	–
Walter	–	FX Cleaning	–	–	–	Blendex Surface Conditioning



Norton Blaze Rapid Strip Type 27 Depressed Center Discs

Strip/blend cast iron, steels, aluminum, fiberglass and composites

- Open structure; will not load on sticky coatings, adhesives, and soft metals (e.g. aluminum), or snag and shed like a cloth or fiber disc
- Norton Blaze ceramic alumina grain provides 2X cut rate and life over silicon carbide
- Will not shed on heavily rust-encrusted pieces
- Extremely versatile; use one disc; stiff enough to stand abuse, but soft enough to prevent gouging and rework
- Use on edge for blending weld root forms
- Apply some pressure to strip or remove coatings; lighter pressure finishes like a surface finishing disc
- Fewer safety, ergonomic, and environmental issues due to fewer change-outs, less downtime, and less production waste/landfill scrap



FEATURED PRODUCTS



NORTON BLAZE RAPID STRIP NON-WOVEN DEPRESSED CENTER DISCS – TYPE 27

BEST CHOICE FOR QUICK AND EASY ROUGH CLEANING AND STRIPPING OF ALL MATERIALS

FEATURES

BENEFITS

■ Blaze ceramic alumina grain	■ 2x cut rate, 2x life over silicon carbide products
■ Advanced resin bond	■ Does not shed on rust-encrusted pieces, and prevents gouging and rework
	■ Does not snag when used for deburring
■ Uniform coating process	■ Abrasive coating covers the entire disc providing a consistent cut rate
■ Open structure	■ Sticky coating, adhesives and soft metals will not clog the disc

AVAILABILITY

TIER:	BEST	GOOD
BRAND:	Norton	Norton
TRADENAME:	BLAZE RAPID STRIP	RAPID STRIP
ABRASIVE:	Ceramic Alumina	Silicon Carbide
GRIT SIZE:	36-50	36-50
GRADE:	X-Coarse	X-Coarse
TYPE/BACKING:	Type 27/Fiberglass	Type 27/Fiberglass

SIZE (D x H)	MAX. RPM	STD. PKG.	PART #	PART #
4-1/2 x 5/8-11	12,000	10	66254498101	66261009585
4-1/2 x 7/8	12,000	10	66623303783	66261009649
5 x 5/8-11	11,000	10	66623303915	
5 x 7/8	11,000	10	66623303916	
7 x 5/8-11	8,000	10	66623303919	66261009650
7 x 7/8	8,000	10	66623303920	66261009586



NORTON VORTEX RAPID BLEND DEPRESSED CENTER DISCS – TYPE 27

REVOLUTIONARY TECHNOLOGY FOR HEAVY DEBURRING AND FINISHING

FEATURES

BENEFITS

■ Proprietary high-performance, engineered aluminum oxide aggregate grain	■ Aggressive, fast stock removal cut rate while providing a fine finish
■ New bond technology	■ Twice the wheel life over conventional unified wheels, with minimal shedding
■ Controlled porosity	■ Consistent performance with no smearing
	■ Cooler and improved cut rate

AVAILABILITY

TIER:	BETTER	GOOD	GOOD	GOOD	GOOD
BRAND:	Norton	Norton	Norton	Norton	Norton
TRADENAME:	VORTEX RAPID BLEND	RAPID BLEND	RAPID BLEND	RAPID BLEND	RAPID BLEND
ABRASIVE:	Engineered A/O	Aluminum Oxide	Aluminum Oxide	Silicon Carbide	Aluminum Oxide
GRIT SIZE:	100-120	150-180	220-280	320-400	150-180
SPECIFICATION:	Medium	NEX-2AM	NEX-2AF	NEX-2SVF	High Strength Medium
TYPE/BACKING:	Type 27/Fiberglass	Type 27/Fiberglass	Type 27/Fiberglass	Type 27/Fiberglass	Type 27/Fiberglass

SIZE (D x H)	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #	PART #
4-1/2 x 5/8-11	12,000	10	66254429243	66261023947	66261023946	66261023943	66261023949
4-1/2 x 7/8	12,000	10	66254429268	66261020548	66261020547	66261020546	66261020549



BEAR-TEX®



FEATURED PRODUCTS



NORTON VORTEX RAPID PREP NON-WOVEN DISCS

BETTER CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

- Proprietary, engineered Vortex aluminum oxide abrasive grain, new coating method, and smear-free Clean-Bond technology

BENEFITS

- Most consistent cutting and finishing surface conditioning products on the market
- Combine maximum cutting speed with the finish of fine grits
- Reduce process times by 50+% by eliminating 2 to 5 grit sequences to 1 step in your technical blending operations
- More resistant to edge wear; up 4X life vs. competitive products
- Friable grain structure keeps Ra specs throughout disc life and reduces scrap and rework

7/8" Center Hole AVAILABILITY

TIER:
BRAND:
TRADENAME:
ABRASIVE:

		BETTER	GOOD
		Norton	Norton
		VORTEX RAPID PREP	RAPID PREP
		Aluminum Oxide	Aluminum Oxide
SIZE (DIAMETER)	STD. PKG.	PART #	PART #
EXTRA COARSE			
4-1/2	25	66623334973	66623326070
5	25	66623334975	66261090645
6	25	66623341359	66623326076
7	25	66623341360	66623326085
COARSE			
4-1/2	25	66623334944	66254473868
5	25	66623334946	66261008293
6	25	66623341361	66623325136
7	25	66623341362	66623325138
MEDIUM			
4-1/2	25	66623333612	66623325915
5	25	66623334963	66261017124
6	25	66623341363	66623325918
7	25	66623341364	66623325919
FINE			
4-1/2	25	66623333608	66623325153
5	25	66623334954	66254469132
6	25	66623341365	66623325159
7	25	66623341366	66623325897
VERY FINE			
4-1/2	25	66623333616	66623325938
5	25	66623333618	66623325943
6	25	66623341367	66623325958
7	25	66623341368	66623325959



DESCRIPTION	MAX. RPM	STD. PKG.	PART NO.
Rapid Prep Disc Back-up Pads			
4-1/2" Medium	11,000	5	63642502122
5" Medium	10,000	5	63642543421
7" Medium	8,600	5	63642543422



Norton Rapid Prep Surface Conditioning Products

The Perfect Abrasive, Coating, and Bond Built into Every Disc and Belt

- Available in premium Vortex aluminum oxide aggregate grain and Norton aluminum oxide grain ideal for many aerospace, metal and stainless steel fabrication, and MRO applications
- Our proprietary coating method extends life and delivers consistent finishes by creating a thick layer of grain throughout the product. Grain does not sit on top of fibers as other competitive products can.
- Our new Clean Bond resin system guarantees smear-free finishes, even on high nickel content alloys; will not load on aluminum and soft metals, as competitive products can



FEATURED PRODUCTS



AVOS RAPID PREP SPEED-LOK DISCS

GOOD CHOICE FOR LIGHT DEBURRING, CLEANING AND FINISHING


FEATURES

BENEFITS

- Patented hole design
- Allows interrupted cut, reducing heat up to 30% over standard surface preparation discs
- Scooped holes
- Cool cutting results in longer disc life
- 15 degree angle back-up pad
- Provides complete vision into the grinding zone
- Operators can grind more accurately with less re-work
- Create air flow to pull loose abrasive and swarf away from work surface grinding zone – resulting in extended disc life
- Grinding at 5°-15° angle allows greater utilization of disc surface
- Eliminates gouging of workpiece

AVOS Speed-Lok AVAILABILITY

TIER:	BETTER		GOOD	
BRAND:	Norton		Norton	
TRADENAME:	VORTEX RAPID PREP		RAPID PREP	
ABRASIVE:	Aluminum Oxide		Aluminum Oxide	
SIZE (DIAMETER)	STD. PKG.	PART #	PART #	
EXTRA COARSE				
4-1/2	10	66623374800	66623374815	
5	10	66623374801	66623374816	
7	10	66623374802	66623374817	
COARSE				
4-1/2	10	66623374803	66261010447	
5	10	66623374804	66623374818	
7	10	66623374805		
MEDIUM				
4-1/2	10	66623374806	66261010448	
5	10	66623374807	66623374819	
7	10	66623374808		
FINE				
4-1/2	10	66623374809	66623374820	
5	10	66623374810	66623374821	
7	10	66623374811	66623374822	
VERY FINE				
4-1/2	10	66623374812	66623374823	
5	10	66623374813	66623374824	
7	10	66623374814		



DESCRIPTION	MAX. RPM	STD. PKG.	PART #
AVOS Speed-Lok Back-up Pads – Triangular			
4-1/2 x 5/8-11	13,000	5	63642502985
5 x 3/8-24 Pistol Grip*	20,000	5	63642503029
5 x 5/8-11 Thicker	13,000	5	63642502517
5 x 5/8-11	13,000	5	63642503663
5 x 7/16-20 Pistol Grip*	20,000	5	63642503030
AVOS Speed-Lok Back-up Pads – Round			
7 x 5/8-11 Hard	8,600	5	63642504873
7 x 5/8-11 Medium	8,600	5	63642504874

* USE ON AIR PNEUMATIC AND HIGH-SPEED PISTOL GRIP SANDERS.

Speed Change 5/8"-11 AVAILABILITY

TIER:	BETTER		GOOD	
BRAND:	Norton		Norton	
TRADENAME:	VORTEX RAPID PREP		RAPID PREP	
ABRASIVE:	Aluminum Oxide		Aluminum Oxide	
SIZE (DIAMETER)	STD. PKG.	PART #	PART #	
EXTRA COARSE				
4-1/2	25	66623373667	66623373690	
5	25	66623373669	66623373691	
7	25	66623373670	66623373692	
COARSE				
4-1/2	25	66623373671	66623373693	
5	25	66623373674	66254498516	
7	25	66623373675	66261192908	
MEDIUM				
4-1/2	25	66623373678	66623308157	
5	25	66623373679	66623373694	
7	25	66623373680	66261192913	
FINE				
4-1/2	25	66623373681	66623373696	
5	25	66623373682	66623373695	
7	25	66623373684	66623373697	
VERY FINE				
4-1/2	25	66623373685	66623373698	
5	25	66623373686	66623373699	
7	25	66623373687	66623373700	



DESCRIPTION	MAX. RPM	STD. PKG.	PART #
Smooth-Face Back-up Pads for 5/8-11 Speed-Change Discs			
4-1/2" Medium	20,000	5	66254492277
5" Medium	12,000	5	63642543235
7" Hard	8,600	5	63642543240
7" Medium	8,600	5	63642543245
7" Soft	8,600	5	63642543250
9" Medium	7,000	5	63642543270



CATEGORY DEFINITION

Norton and Merit non-woven quick-change discs are a combination of strong synthetic mesh and quality abrasives, bonded together by a smear-resistant adhesive. They are ideal for use on portable tools to clean and remove imperfections on metal surfaces, clean, deburr or finish a variety of surfaces, blend weld seams, or create decorative finishes. The open construction of the non-woven material enables aggressive cutting action and improved surface finish while maintaining its non-loading feature.

APPLICATIONS:	Medium-light stock removal, beveling, deburring/deflashing, rust removal, blending, cleaning and finishing, polishing
SURFACE FINISHING MATERIALS:	Surface stripping, surface deburring and blending, surface preparation, buffing, and polishing
SIZE RANGE:	3/4" – 8" diameter
GRIT RANGE:	X-Coarse, Coarse, Medium, Fine, Very Fine, Super Fine
ABRASIVE GRAIN:	Ceramic Alumina, Aluminum Oxide, Silicon Carbide
ATTACHMENT:	Quick-Change Type TR (Type III), Type TS (Type II), and Type TP (Type I)
BACK-UP PADS:	Rubber with hardness variations for different applications

QUICK-CHANGE ATTACHMENT SYSTEMS AND CROSS REFERENCE GUIDE

Each system enables quick, safe disc changes, reducing downtime and operating expenses.

Type TS (Type II)

- Features a turn-on/turn-off style fastener
- Fastener is made of metal
- Equivalent to Standard Abrasives SocAtt® locking system



Type TR (Type III)

- Features a roll-on/roll-off style fastener
- Fastener is made of plastic
- Equivalent to 3M™ Roloc™ fastening system



Type TP (Type I)

- Features a snap-on/snap-off style fastener
- Fastener is made of nylon



NORTON

TS

TR

TP

3M	Roloc TS/TSM	Roloc TR	Roloc TP
Standard	TS (SocAtt)	TR (Lockit)	TP (ClickOn)
Superior	Type S	Type R	—
Arc	Type S	Type R	Type P
Pferd	Type CD	Type CDR	—
Sait	SAIT-LOK	SAIT-LOK-R	—
Camel	Turn On	Roll On	—
Klingspor	QMC	QRC	—
Garryson	Type S	Type R	—

APPLICATION/GRIT RECOMMENDATION GUIDE

	MOST AGGRESSIVE				LEAST AGGRESSIVE	
	RAPID STRIP	VORTEX RAPID BLEND	VORTEX RAPID PREP	RAPID PREP		
NORTON						
MERIT	DEBURRING & BLENDING					HS BUFFING, BUFFING
SCALE REMOVAL	BEST CHOICE					
STOCK REMOVAL	BEST CHOICE	SECOND CHOICE				
HEAVY DEBURRING	SECOND CHOICE	BEST CHOICE				
LIGHT DEBURRING		BEST CHOICE	SECOND CHOICE			
LIGHT FINISHING			BEST CHOICE	SECOND CHOICE		
BLENDING			BEST CHOICE	SECOND CHOICE		
CLEANING			SECOND CHOICE	BEST CHOICE		
FINISHING				BEST CHOICE	SECOND CHOICE	



CROSS REFERENCE GUIDE

	STRIPPING			HEAVY/LIGHT DEBURRING		LIGHT DEBURRING/BLENDING/CLEANING/FINISHING	
	BEST	GOOD	BETTER	GOOD	BETTER	GOOD	GOOD
NORTON	Blaze Rapid Strip	Rapid Strip	Vortex Rapid Blend	Rapid Blend	Vortex Rapid Prep	Rapid Prep	HS Buffing, Buffing
MERIT				Deburring & Blending			
3M	—	Clean & Strip Clean Strip XT	—	EXL Unitized	—	Surf Cond, SL, SE	—
Standard	—	Cleaning Disc	—	500-900 Series Unitized	—	FE, GP, RC	Buff & Blend - HS, Buff & Blend
Fiberal/SIA	—	—	—	—	—	Meteor, Type B & C	—
Superior	—	Type R	—	XL Unitized	—	FD, GD, CC	HS, HD A/O
Arc	—	Arcstrip	—	—	—	Surface Cond	Blend & Finish
Pferd	—	Policlean	—	—	—	Finishing Disc - Hard & Soft	—
Sait	—	SAIT-Strip	—	—	—	HD, GP	Sand-Light Blending
Camel	—	EZ Strip - Black	—	—	—	—	—
Klingspor	—	Strip-It Black	—	—	—	—	—
Garryson	—	—	—	—	—	Surface Cond	—
Bibielle	—	—	—	BUR Unitized	—	DCR	—

ABRASIVE/GRIT/DENSITY KEY

ABRASIVE	SILICON CARBIDE			ALUMINUM OXIDE		CERAMIC ALUMINA
	SHARPER, FINER/BRIGHTER SCRATCH PATTERN			MORE DURABLE, LONGER LASTING, POLISHED FINISH		
GRIT SIZE	XC (24-36)	C (50-80)	M (100-150)	F (180-220)	VF (240-360)	SF (400-600)
	FASTER, AGGRESSIVE CUT, ROUGHER FINISH			REDUCED CUT RATE, FINER FINISH		
DENSITY	2					9
	SOFT, OPEN, CONFORMABLE, LESS BURNING/LOADING			HARDER, MORE DURABLE, FASTER CUTTING, BETTER FINISH		

FEATURED PRODUCTS

Quick-Change Rapid Strip Discs



NORTON BLAZE RAPID STRIP AND NORTON RAPID STRIP DISCS

IDEAL FOR REMOVING COATINGS ON A VARIETY OF SUBSTRATES, SUCH AS WOOD, METAL AND PLASTICS

FEATURES	BENEFITS
- Manufactured with extruded nylon fibers, flexible resin technology, and extra-coarse abrasive grains - Blaze Rapid Strip	- Provide a unique combination of aggressive performance, long life, improved finish - Outperform traditional coated abrasive products, leaving a thoroughly cleaned surface, ensuring excellent adhesion in subsequent processes such as coating, painting and soldering - Great alternative to wire brushes - Will not load on sticky coatings, adhesives, and soft metals, or snag and shed like a fiber disc 2X faster cutting than competitive discs; lasts 2X (plus) as long - Stiff enough to stand abuse; soft enough to prevent gouging and rework. Apply some pressure to strip/remove coatings; lighter pressure finishes like a surface finishing disc

AVAILABILITY

TIER:	BEST	GOOD	GOOD		
BRAND::	Norton	Norton	Norton		
TRADENAME:	BLAZE RAPID STRIP	RAPID STRIP	RAPID STRIP		
ABRASIVE:	Ceramic Alumina	Silicon Carbide	Silicon Carbide		
GRADE:	XC	XC	XC		
ATTACHMENT:	TR (Type III)	TR (Type III)	TS (Type II)		
					
STD. PKG.	PART #	STD. PKG.	PART #	STD. PKG.	PART #
25	66623303912	10	66261013402	25	66623333374
25	66261096557	10	66261013403		
5	66623303921	5	66261016580		



FEATURED PRODUCTS

Deburring & Blending Discs



NEW

NORTON BLAZE RAPID BLEND DISCS

REVOLUTIONARY TECHNOLOGY FOR HEAVY DEBURRING AND FINISHING

FEATURES

- Norton Blaze SG ceramic alumina grain
- Special resin chemistry
- New construction: abrasive is distributed throughout the entire disc (top, bottom and side)

BENEFITS

- Quickest cut rate and up to 8X longer life than competitive aluminum oxide discs
- Resists shedding when used on sharp edges, making it ideal for deburring
- All three faces can be used – versus competitive discs' one bottom layer of abrasive
- 3 - 8 times the life of competitive surface blending discs
- Fewer safety, ergonomic, and environmental issues due to fewer change-outs, less downtime, and less production waste/landfill scrap
- No smearing



EXPANDED OFFERING

NORTON VORTEX RAPID BLEND DISCS

REVOLUTIONARY TECHNOLOGY FOR HEAVY DEBURRING AND FINISHING

FEATURES

- Proprietary Vortex aluminum oxide aggregate grain
- Special resin chemistry
- New construction: abrasive is distributed throughout the entire disc (top, bottom and side)

BENEFITS

- Performs the medium to fine grit steps of traditional discs in an easy one-step operation
- Resists shedding when used on sharp edges, making it ideal for deburring
- All three faces can be used – versus competitive discs' one bottom layer of abrasive
- 3 - 8 times the life of competitive surface blending discs
- Fewer safety, ergonomic, and environmental issues due to fewer change-outs, less downtime, and less production waste/landfill scrap
- No smearing



NORTON RAPID BLEND DISCS

GOOD CHOICE FOR LIGHT DEBURRING, BLENDING, AND CLEANING

FEATURES

- Open mesh construction
- New construction: abrasive is distributed throughout the entire disc (top, bottom and side)

BENEFITS

- Waterproof, washable, conformable, and non-loading
- Designed for surface generation where stock removal is not required
- All three faces can be used – versus competitive discs' one bottom layer of abrasive
- 3 - 8 times the life of competitive surface blending discs
- Fewer safety, ergonomic, and environmental issues due to fewer change-outs, less downtime, and less production waste/landfill scrap
- No smearing

AVAILABILITY

TIER:		
BRAND::	Norton	Norton
TRADENAME:	BLAZE RAPID BLEND	VORTEX RAPID BLEND
ABRASIVE:	Ceramic Alumina	Aluminum Oxide
ATTACHMENT:	TS (Type II)	TS (Type II)

SIZE (D x T)	ABRASIVE	GRIT	DENSITY	MAX. RPM	STD. PKG.	PART #	PART #
1 x 1/4	Ceramic Alumina	XC	1	35,100	100	66623313920	
1-1/2 x 1/4	Ceramic Alumina	XC	1	35,100	80	66623313922	
2 x 1/4	Ceramic Alumina	XC	1	12,100	25	66623313925	
	Aluminum Oxide	M	1	12,100	25		66254497070
3 x 1/4	Ceramic Alumina	XC	1	12,100	25	66623313931	
	Aluminum Oxide	M	1	12,100	25		66254497069


Refer to the end of this section for a list of quick-change back-up pads.



Deburring & Blending Discs CONTINUED

AVAILABILITY

TIER:
BRAND:.
TRADENAME:
ABRASIVE:
ATTACHMENT:

			
BEST	BETTER	GOOD	GOOD
Norton	Norton	Norton	Merit
BLAZE RAPID BLEND	VORTEX RAPID BLEND	RAPID BLEND	DEBURR/BLEND
Ceramic Alunima	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
TR (Type III)	TR (Type III)	TR (Type III)	TR (Type III)
			

SIZE (D x T)	ABR.	GRIT	DENSITY	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #
1 x 1/4	C/A	XC	1	35,100	100	66623313919			
	A/O	M	1	35,100	100		66254497806		
1-1/2 x 1/4	C/A	XC	1	35,100	80	66623313921			
	A/O	M	1	35,100	80		66254497807		
2 x 1/8	A/O	M	4-6	22,000	60		66254425632		
	A/O	M	7-9	22,000	60		66254433509		
2 x 3/16	A/O	M	2-3	22,000	60		66254428236		
2 x 1/4	C/A	XC	1	35,100	25	66623313923			
	A/O	C	7-9	22,000	60			66261014921	66261054187
	A/O	M	1	12,100	25		66254497067		
	A/O	M	2-3	22,000	60		66254428237	66261014897	66261054183
	A/O	M	4-6	22,000	60		66254413660	66261014911	66261054185
	A/O	M	7-9	22,000	60		66254433510	66261014935	66261054186
	S/C	F	2	22,000	60			66261014889	
	S/C	F	3	22,000	60			66261017306	
	S/C	F	2-3	22,000	60				66261054182
	S/C	F	4-6	22,000	60			66261014906	66261054184
3 x 1/8	A/O	C	7-9	15,000	40			66261014922	
	A/O	M	2-3	15,000	40			66261014898	
	A/O	M	4-6	15,000	40		66261093556	66261014912	
	A/O	M	7-9	15,000	40		66261090909	66261014936	
	A/O	F	2-3	15,000	40				
	A/O	F	4	15,000	40				
	A/O	F	6	15,000	40			66261015419	
3 x 3/16	A/O	M	7-9	15,000	40		66254428239		
3 x 1/4	C/A	XC	1	12,100	25	66623313930			
	A/O	C	7-9	15,000	40				66261054198*
	A/O	M	1	12,100	25		66254497068		
	A/O	M	2-3	15,000	40		66254428238		66261054193*
	A/O	M	4-6	15,000	40		66254413661		66261054196*
	A/O	M	7-9	15,000	40		66254406395		66261054197*
	A/O	F	2-3	15,000	40				66261054192*
	A/O	F	4-6	15,000	40				66261054194*
	S/C	F	2	15,000	40			66261014890	
	S/C	F	3	15,000	40			66261016005	
	S/C	F	4-6	15,000	40				66261054195*

* STD. PKG. = 20 DISCS

Refer to the end of this section for a list of quick-change back-up pads.



BEAR-TEX®



FEATURED PRODUCTS

Surface Preparation Discs



NORTON VORTEX RAPID PREP

BETTER CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

- Proprietary Vortex aluminum oxide abrasive grain and coating method
- Clean Bond resin system, aerospace-tailored
- Extended form holding

BENEFITS

- Combines maximum cutting speed with the consistent finish of finer grits
- Reduce process times by 50+% by combining multiple grit sequences to 1 step
- More resistant to edge wear; up 4X life versus competitive products
- Friable grain structure keeps Ra specs throughout disc life, reducing scrap/rework
- Smear-free, even on high nickel content alloys
- Will not load on aluminum and soft metals, as competitive products may
- Lowest total cost of consumable tooling per workpiece



NORTON RAPID PREP

GOOD CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

- Clean Bond resin system, aerospace-tailored
- Proprietary coating method

BENEFITS

- Smear-free, even on high nickel content alloys
- Will not load on aluminum and soft metals, as competitive products may
- Thick layer of grain throughout the product extends life; grain does not sit on top of fibers as other competitive products may

TIER:
BRAND:
TRADENAME:
ABRASIVE:
ATTACHMENT:

BETTER	GOOD	BETTER	GOOD	BETTER	GOOD
Norton	Norton	Norton	Norton	Norton	Norton
VORTEX RAPID PREP	RAPID PREP	VORTEX RAPID PREP	RAPID PREP	VORTEX RAPID PREP	RAPID PREP
Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
TR (Type III)	TR (Type III)	TS (Type II)	TS (Type II)	TP (Type I)	TP (Type I)

SIZE (DIAM.)	STD. PKG.	PART #	PART #	PART #	PART #	PART #	PART #
EXTRA COARSE							
3/4	50	66623325001	66623340002	66623335324	66261022401	66623325000	66623340000
1	50	66623325004	66623340007	66623325003	66623340006	66623325002	66623340004
1-1/2	50	66623325007	66623340011	66623325006	66623340010	66623325005	66623340008
2	50	66623335326	66261016373	66623335325	66261017819	66623325008	66623340012
3	25	66623335327	66261016994	66623325010	66261017818	66623325009	66623340015
4	25	66623335329	66261016374	66623335328	66623310706	66623325011	66623340018
COARSE							
3/4	50	66623325013	66623340021	66623335410	66261095015	66623325012	66623340020
1	50	66623325015	66623340023	66623335537	66261024310	66623325014	66623340022
1-1/2	50	66623335411	66261047579	66623325017	66623340026	66623325016	66623340024
2	50	66623335414	66261009191*	66623335413	66261009183	66623335412	66254498593
3	25	66623335417	66261009194	66623335416	66261009186	66623335415	66254498596
4	25	66623335419	66261008822	66623335418	66261055349	66623325018	66623340030
MEDIUM							
3/4	50	66623325020	66623340032	66623335420	66254428059	66623325019	66623340031
1	50	66623335422	66254482331	66623335421	66254482327	66623325021	66623340033
1-1/2	50	66623335424	66254482332	66623335423	66254482328	66623325022	66623340034
2	50	66623335427	66261009190*	66623335426	66261009182	66623335425	66254498520
3	25	66623335430	66261017522	66623335429	66261009185	66623335428	66254498595
4	25	66623335432	66261008821	66623335431	66261055350	66623325023	66623340039
FINE							
3/4	50	66623325026	66623340058	66623325025	66623340056	66623325024	66623340054
1	50	66623325029	66623340064	66623325028	66623340062	66623325027	66623340060
1-1/2	50	66623325032	66623340070	66623325031	66623340068	66623325030	66623340066
2	50	66623325035	66623340077	66623325034	66623340074	66623325033	66623340072
3	25	66623325038	66623340085	66623325037	66623340082	66623325036	66623340080
4	25	66623325041	66623340092	66623325040	66623340090	66623325039	66623340088
VERY FINE							
3/4	50	66623325044	66623340044	66623325043	66623340042	66623325042	66623340041
1	50	66623325047	66254482339	66623325046	66254482335	66623325045	66623340045
1-1/2	50	66623325050	66254482340	66623325049	66254482336	66623325048	66623340046
2	50	66623335433	66261009189*	66623325052	66254482337	66623325051	66254498594
3	25	66623335437	66261009192	66623335436	66261009184	66623325053	66254498597
4	25	66623325056	66623340053	66623325055	66623340052	66623325054	66623340051
SUPER FINE							
2	50		66261091459				
3	25		66261091460				

* 25 PER STANDARD PACKAGE



FEATURED PRODUCTS

Surface Preparation Stars



MERIT SURFACE PREPARATION STARS

THE PERFECT ITEM FOR ID WORK

FEATURES	BENEFITS
■ Star shape	■ Penetrates the ID and polishes or cleans the surface without disturbing any tolerances
■ 1/4-20 eyelets	■ Attach to Merit MM20-4 mandrel, Part # 08834183164 (See description at end of Overlap Slotted Disc Section.)

AVAILABILITY

TIER:	GOOD
BRAND::	Merit
TRADENAME:	SURFACE PREP
ABRASIVE:	Aluminum Oxide
ATTACHMENT:	1/4-20 Eyelet

SIZE (D x EYELET)	GRIT	STD. PKG.	PART #
1-1/2" x 1/4-20	C	100	08834185923
	M	100	08834185924
	VF	100	08834185925
2" x 1/4-20	C	100	08834185926
	M	100	08834185927
	VF	100	08834485928
3" x 1/4-20	C	100	08834185929
	M	100	08834185678
	VF	100	08834185931
4" x 1/4-20	C	100	08834185932
	M	100	08834185933
	VF	100	08834185934

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

FEATURED PRODUCTS

Cross Buffs



MERIT CROSS BUFFS

EXCELLENT FOR BLENDING, POLISHING AND ID USAGE

FEATURES	BENEFITS
■ Unique design	■ Durable non-woven construction that delivers longer life and cool running
■ 8-32 eyelets	■ Attach to Merit MM32-4 mandrel. Part No. 08834183163 (See description at end of Overlap Slotted Disc Section)

AVAILABILITY

TIER:	BETTER	GOOD
BRAND::	Merit	Merit
TRADENAME:	HIGH STRENGTH	BUFFING
ABRASIVE:	Aluminum Oxide	Aluminum Oxide
ATTACHMENT:	8-32 Eyelet	8-32 Eyelet

SIZE (D x W)	GRIT	PLY	STD. PKG.	PART #	PART #
1-1/2 x 1/2	Coarse	2	100		08834188761
	Medium	2	100	08834189306	08834187312
	Very Fine	2	100	08834189307	08834188585
1-1/2 x 1/2	Coarse	3	100		66623301763
	Medium	3	100	08834189308	08834187311
	Very Fine	3	100	08834189309	08834188586

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



FEATURED PRODUCTS

Buffing/Polishing Discs



BUFFING/POLISHING DISCS

DESIGNED FOR LIGHT REMOVAL OF PAINT OR RUST

FEATURES

- High-strength discs
- For light removal of paint or rust

BENEFITS

- Tough, yet conformable, and resist tearing on burrs and sharp edges
- Smear-proof
- Does not affect the base product

AVAILABILITY

TIER:	BEST
BRAND::	Norton
TRADENAME:	HIGH-STRENGTH
ABRASIVE:	Aluminum Oxide
ATTACHMENT:	TR (Type III)




BETTER	BETTER	GOOD	GOOD	GOOD
Merit	Merit	Merit	Merit	Merit
HIGH-STRENGTH	HIGH-STRENGTH	BUFFING	BUFFING	BUFFING
Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
TR (Type III)	TS (Type II)	TR (Type III)	TS (Type II)	TP (Type I)
				
PART #	PART #	PART #	PART #	PART #
		08834166368 08834166369	08834166392	08834166292 08834166332
08834164064	08834164244	08834161649 08834166303 08834166304	08834166394 08834166395 08834166396	08834161627 08834166280 08834166281
08834163987	08834164245	08834166305	08834166405	08834166282
08834164065	08834164252	08834161651 08834166308 08834166309	08834166397 08834166398 08834166399	08834166293 08834166284 08834166285
08834163559	08834164255	08834166310	08834166403 08834166401	08834166286


SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

Quick-Change Back-up Pads


- Hard density pads are for aggressive cutting action
- Medium density pads are for all-purpose applications
- Soft density pads are used for contours and fine finishing work



TR (TYPE III)



TS (TYPE II)



TP (TYPE I)

AVAILABILITY

BRAND::	Norton	Merit	Norton	Merit	Merit
ATTACHMENT:	TR (Type III)	TR (Type III)	TS (Type II)	TS (Type II)	TP (Type I)

SIZE (DIAMETER)	MAX. RPM	DENSITY	PART #	PART #	PART #	PART #	PART #
Quick-Change Back-up Pads							
3/4"	40,000	Medium		08834164038		08834164206	08834164001
1"	40,000	Medium		08834164037		08834164651	08834164002
1-1/2"	30,000	Hard		08834164640		08834164622	08834163996
	30,000	Medium	66261047580	08834161174		08834164146	08834164003
2"	30,000	Hard		08834164643	63642543205	08834164624	08834163997
	30,000	Medium	66261055103	08834164922	63642543210	08834164198	08834164004
	30,000	Soft		08834164641		08834161625	08834163949
3"	20,000	Hard	63642504900	08834164036	63642543220	08834161626	08834163998
	20,000	Medium	66261055105	08834164949	63642543225	08834164113	08834164005
	20,000	Soft		08834164644		08834164626	08834163948
4"	15,000	Medium	66261047581	08834164655	63642543232	08834164135	08834164006
4" TR+	8,000	Medium	66261016581	63642555106			

ALL QUICK-CHANGE BACK-UP PADS HAVE A 1/4" DIAMETER SHANK. STD. PKG. = 1

Refer to the end of the Coated Abrasive Quick-Change Discs section for a complete list of back-up pads and mandrels.



FEATURED PRODUCTS

Non-Woven Hook and Loop Discs



NORTON VORTEX RAPID PREP

BETTER CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

■ Proprietary Vortex aluminum oxide abrasive grain and coating method

■ Clean Bond resin system, aerospace-tailored

■ Improved hook and loop backing

BENEFITS

■ Most consistent cutting and finishing of surface conditioning products on the market
 ■ Combines maximum cutting speed with the finish of finer grits
 ■ Reduce process times by 50+% by combining multiple grit sequences to 1 step in a blending operation
 ■ More resistant to edge wear; up 4X life vs. competitive products
 ■ Friable grain structure keeps Ra specs throughout disc life and reduces scrap and rework

■ Smear-free, even on high nickel content alloys
 ■ Will not load on aluminum and soft metals, as competitive products may

■ Will not fly off rotary sanders
 ■ Discs sit flatter on back-up pads, resulting in a more consistent finish on DA applications

AVAILABILITY

TIER:

BRAND:

TRADENAME:

ABRASIVE:

		BETTER	GOOD
		Norton	Norton
		VORTEX RAPID PREP	RAPID PREP
		Aluminum Oxide	Aluminum Oxide
SIZE (DIAMETER)	STD. PKG.	PART #	PART #
EXTRA COARSE			
1-1/2	50	66623325061	66623340098
2	50	66623334970	66261017900
3	25	66623333620	66623326059
4	25	66623334971	66261017382
4-1/2	25	66623334972	66261017906
5	25	66623334974	66261017215
6	25	66623333621	66623326077
7	25	66623334976	66261192846
8	25	66623334977	66261017531
COARSE			
1-1/2	50	66623325057	66623340099
2	50	66623334882	66261004431*
3	25	66623334883	66261055015
4	25	66623334884	66261055018
4-1/2	25	66623334943	66261017806
5	25	66623334945	66261004435
6	25	66623334949	66261006910
7	25	66623334951	66261055027
8	25	66623334953	66261006913
MEDIUM			
1-1/2	50	66623325059	66623338571
2	50	66623334958	66261004441
3	25	66623334956	66261004442
4	25	66623334959	66261055019
4-1/2	25	66623334961	66261004444
5	25	66623334962	66261055022
6	25	66623334964	66261006911
7	25	66623334965	66261017813
8	25	66623334966	66261017815
FINE			
1-1/2	50	66623325058	66623340101
2	50	66623333604	66623325141
3	25	66623333605	66623325143
4	25	66623333606	66623325145
4-1/2	25	66623333607	66623325147
5	25	66623333609	66623325154
6	25	66623333610	66623325160
7	25	66623334955	66261199465
8	25	66623333611	66623325907

* STANDARD PACKAGE = 80

CONTINUED



Non-Woven Hook and Loop Discs CONTINUED

AVAILABILITY

AVAILABILITY		TIER:	BETTER	GOOD
		BRAND:	Norton	Norton
		TRADENAME:	VORTEX RAPID PREP	RAPID PREP
		ABRASIVE:	Aluminum Oxide	Aluminum Oxide
SIZE (DIAMETER)	STD. PKG.	PART #	PART #	
VERY FINE				
1-1/2	50	66623325060	66623340100	
2	50	66623333613	66623325926	
3	25	66623333614	66623325934	
4	25	66623334967	66261055020	
4-1/2	25	66623333615	66623325936	
5	25	66623333617	66623325941	
6	25	66623334968	66261055026	
7	25	66623334969	66261019990	
8	25	66623333619	66623325972	
SUPER FINE				
4-1/2	25		66261094948	
5	25		66261019962	
7	25		66261094949	




Back-Up Pads for Hook And Loop Discs

AVAILABILITY

AVAILABILITY					TIER:	GOOD	GOOD
					BRAND:	Norton	Merit
PAD DIAMETER	SPINDLE OR HOLE SIZE	MAX. RPM	3M EQUIVALENT	STD. PKG.	PART #	PART #	
Back-Up Pads for Hook And Loop Discs							
2	1/4 Steel Shank	23,000	922	5	66261059352	08834168025*	
3	1/4 Steel Shank	20,000	923	5	66261059354	08834168026*	
4	1/4 Steel Shank	18,000	924	5	66261059356	08834168027*	
	1/2-13	13,000	914	5	66261059303	05539562714	
	5/8-11	13,000	914	5	66261059304	08834168984*	
	M10 x 1.250	13,000		5	66261059305		
4-1/2	5/8-11	10,000	9145	5	66261006948	05539562718	
5	5/16-24 Male	10,000	905	5	66261059360	08834168993**	
	3/8-24 Male	10,000	905	5	66261059308	08834168028*	
	5/8-11	10,000	915	5	66261059310	08834168967*	
6	5/8-11	8,000	916	5	66261059312	05539562723	
7	5/8-11	6,000	917	5	66261059368	08834168032*	
8	5/8-11	4,500	918	5	66261059372		

* = 1 PER PKG, ** = 2 PER STD PKG.



FEATURED PRODUCTS

Non-Woven High Strength Discs



HIGH STRENGTH AND FASTCUT DISCS

BETTER CHOICE FOR LIGHT DEBURRING AND FINISHING

FEATURES

- Firm, durable web
- Tough, yet conformable
- Strong, smear-proof resin binders

BENEFITS

- High resistance to tearing on burrs and sharp edges
- Can be "ganged" together and used as a wheel
- Produce light satin finishes

Applications include rust/oxide or coating removal, pipe ID and OD polishing, casting cleaning, highlighting (antiquing), contaminant removal, removal of handling marks, gasket removal, cleaning and blending of surface imperfections, prepping prior to soldering, removal of filling materials, cleaning angles and odd shapes. Will not stretch or shed. Ganging increases versatility.

AVAILABILITY

TIER:				GOOD			
BEST				BETTER			
Norton				Norton			
FAST CUT				HIGH STRENGTH			
Aluminum Oxide				Aluminum Oxide			
SIZE (D x H)	GRIT	MAX. RPM	STD. PKG.	PART #	PART #	STD. PKG.	PART #
6 x 1/4	VF	4,000	70	66261000601	66261007628		
6 x 1/2	M	4,000	70		66261005073	25	08834162410
	F	4,000	70			25	08834167735
	VF	4,000	70		66261004980	25	08834162411
8 x 1/2	M	3,000	50		66261005491	25	08834162412
	VF	3,000	50		66261004506	25	08834162413
12 x 1-1/4	VF	1,900	25		66261008723		



FITS HOLE	FOR DISC WIDTH	FOR DISC DIAMETER	SHANK DIAMETER	OVERALL LENGTH	WASHER DIAMETER	STD. PKG.	PART #
Mandrel Assemblies for using Discs on Edge							
1/4"	1/2" (Standard)	up to 6"	1/4"	2-1/2"	1-1/2"	1	66261009502
1/2"	1/2" (Standard)	Up to 8"	1/4"	3-1/8"	2-1/4"	1	66261059420

FEATURED PRODUCTS

Non-Woven Disc Wheels



MERIT DISC WHEELS

GOOD CHOICE FOR LIGHT DEBURRING AND FINISHING



FEATURES

- Discs are "ganged" together to form a wheel

BENEFITS

- Mounted on a 1/4" steel mandrel embedded in an epoxy core
- Strong and durable

MACHINES USED



AVAILABILITY

TIER:					GOOD	
Norton					Merit	
FAST CUT					HIGH STRENGTH	
Aluminum Oxide					Aluminum Oxide	
SIZE (D x W x 1/4 SHANK)	GRIT	PLY	MAX. RPM	STD. PKG.	PART #	
2 x 1/2	Medium	2 Ply	12,000	10	08834131551	
2 x 1	Medium	4 Ply	12,000	10	08834131554	
3 x 1/2	Medium	2 Ply	8,000	10	08834131558	
	Very Fine	3 Ply	8,000	10	08834131560	
3 x 1	Medium	4 Ply	8,000	10	08834131496	
	Fine	5 Ply	8,000	10	08834131557	
	Very Fine	5 Ply	8,000	10	08834131497	
4 x 1/2	Fine	3 Ply	6,000	10	08834131562	
4 x 1	Medium	4 Ply	6,000	10	08834131564	
5 x 1/2	Medium	2 Ply	4,000	10	08834131567	
5 x 1	Medium	4 Ply	4,000	10	08834131570	
	Fine	5 Ply	4,000	10	08834131571	

DISC WHEELS ARE CONSTRUCTED BY NUMBER OF PLYS. THE ACTUAL FACE WIDTH WILL VARY AND WILL NOT MATCH THE LISTED WIDTH EXACTLY. FACE WIDTH IS GIVEN FOR REFERENCE ONLY. SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



FEATURED PRODUCTS

Non-Woven Abrasive Brushes



NON-WOVEN ABRASIVE BRUSHES



BACK-UP PAD

NON-WOVEN ABRASIVE BRUSHES – TYPE 27

USE WHERE MAXIMUM CONFORMABILITY IS NEEDED

FEATURES

- Feature tough, flexible nylon filaments embedded with abrasive grain

BENEFITS

- Provide finishing and polishing where maximum conformability is needed

AVAILABILITY

TIER:	GOOD	GOOD
BRAND:	Norton	Norton
ABRASIVE:	Silicon Carbide	Silicon Carbide
GRIT SIZE:	80	120

SIZE (D x T x H)	MAX. RPM	STD. PKG.	PART #	PART #
Abrasive Brush				
7 x 1 x 7/8	6,000	5	66261058830	66261058834
USE WITH AIR-COOLED RUBBER BACK-UP PAD AND RETAINER NUT				
Abrasive Brush Back-up Pads				
7" Medium	8,600	5	63642543422	



THIN and FLEXIBLE: Perfect for Tight Spots

Norton Bear-Tex Thin-Flex High-Performance Hand Pads

- Achieve performance benefits of a Coarse and Fine grain product in one hand pad: fast cut and definitively better finish than competing pads.
- Extremely thin and conformable; ideal for cleaning, blending, finishing and deburring contoured surfaces and tight spaces
- Special coated web design for superior and constant cutting action without added effort from user
- Versatile; ideal for woodworking, metalworking, maintenance operations, and synthetics fabrication



CATEGORY DEFINITION

Surface finishing hand pads and rolls are made of a non-woven nylon web impregnated with abrasive grain and resin bond.

- APPLICATIONS:** Light- to heavy-duty cleaning, deburring, blending, polishing, and finishing of metal, wood, composite, plastics, stone, solid surface and painted surfaces.
- ABRASIVE GRAIN:** Aluminum Oxide, Silicon Carbide
- GRIT RANGE:** Medium (M), Fine (F), Very Fine (VF), Ultra Fine (UF), Micro Fine (MF), Non-Abrasive (–)
- HAND PAD FEATURES:**
- Flexible; conform to work surface
 - Gentle action easily removes flashing or burrs without affecting dimension of workpiece
 - Non-loading; constant supply of new cutting edges
 - Non-rusting; no workpiece contamination
 - Resilient construction; long life, increased productivity; solvent resistant; waterproof
- SPONGE PAD FEATURES:**
- Non-woven material is laminated to a long-lasting sponge for the convenience of 2 pads in one
 - Superior replacement for steel wool
- ROLL FEATURES:**
- Economical alternative to cut pads
 - Can be cut to specific sizes

APPLICATION/GRIT RECOMMENDATION GUIDE

MORE AGGRESSIVE, ROUGHER FINISH

LESS AGGRESSIVE, FINER FINISH

PRODUCT #:
COLOR:
DESCRIPTION:

ABRASIVE:

GRIT SIZE:

STEEL WOOL
EQUIVALENT:

APPLICATIONS:

									
#740 DARK TAN HEAVY DUTY	#746 GRAY BLENDING	#644 MAROON GP – FINE	#747 MAROON) GP PLUS – VERY FINE	#796 GREEN SCOURING	#635 GRAY CLEAN & FINISH	#748 GRAY FINAL SHINE	THIN-FLEX VF MAROON CLEANING	THIN-FLEX UF GRAY CLEANING	#456 WHITE CLEANING
AO	SC	AO	AO	AO	SC	SC	AO	SC	Non-Abrasive
Medium 100 - 150	Medium 100 - 150	Fine 180 - 220	Very Fine 240 - 360	Very Fine 240 - 360	Ultra Fine 400 - 600	Micro Fine 800 - 1200	Very Fine 240 - 360	Ultra Fine 400 - 600	Non-Abrasive - - - -
4 Extra Coarse	3 Coarse	2 Medium Coarse	1 Medium	0 Fine	00 Very Fine	00 Very Fine	00 Very Fine	000 Extra Fine	0000 SuperFine
• Smear-free Clean Bond technology • 2X life • Most durable and aggressive cutting pad • Heavy-duty removal - rust - oxidation • Deburring	• Blending and deburring - welds - aluminum - stainless	• Cleaning and deburring - machinery - metal parts - plastic - solid surface - stone	• Light cleaning, deburring and finishing - machinery - metal parts - plastic - solid surface - stone	• Removing stains, marks, rust, corrosion or oxidation from stainless equipment • Light cleaning of metal surfaces	• Light cleaning and finishing of most surfaces - steel, - aluminum - denibbing plastic - scuffing acrylics	• Final finishing - final rub on wood - final blend on metal - final finish on plastics and acrylics	• Maximum flexibility for consistent finishes • Cleaning blending, finishing, and deburring in woodwork, metalwork, MRO, and synthetic applications	• Maximum flexibility for consistent finishes • Cleaning blending, finishing, and deburring in woodwork, metalwork, MRO, and synthetic applications	• Scratch-free cleaning - metal - fiberglass - stone - solid surface - ceramic • Wood - highlighting - rubbing

CROSS REFERENCE GUIDE

COARSER

FINER

	#740	#746	#644	#747	#796	#635	#748	Thin-Flex VF	Thin Flex UF	#456
NORTON	7440	7446	64659	7447/8447 Production Hand Pad	96	64660	7448	Multi-Flex Maroon	Multi-Flex Gray	7445
Camel	Tan	–	–	Maroon	Green	–	Grey	–	–	White
Mirka	–	–	–	Maroon/Red VF	–	–	–	Mirlon Total Maroon	Mirlon Total Gray	–
Sait	Brown	–	–	Maroon	Green	–	Gray	–	–	–
SIA	6912 Brown	6712 Grey	–	6912 Maroon	6312 Green	–	–	–	–	–
Standard	HD-Tan AO	–	–	GP-Maroon VF	Green-AO	HP-VF	UF Gray	–	–	Cleaning White



AVAILABILITY

						TIER:	BEST	BETTER	GOOD
						BRAND::	Norton	Norton	Norton
SIZE (W x L)	COLOR	DESCRIPTION	ABRASIVE	GRIT SIZE	STD. PKG.	PART #	PART #	PART #	PART #
Hand Pads									
4-1/2 x 9	Maroon	Thin Flex Cleaning Pad	A/O	VF	25	66623398062			
	Grey	Thin Flex Cleaning Pad	S/C	UF	25	66623398063			
6 x 9	Dark Tan	740 Heavy-Duty Pad IMPROVED!	A/O	Med	40				66261074000
	Gray	746 Blending Pad	S/C	Med	40				66261074600
	Maroon	777 General Purpose Very Fine Pad	A/O	VF	60				66261077700
	Maroon	747 General Purpose Plus Pad	A/O	VF	60		66261074700		
	Maroon	747 General Purpose Plus Perforated Pad	A/O	VF	60		66261084700		
	Green	796 Scouring Pad	A/O	VF	60				66261079600
	Lt. Green	696 Food Pro Pad	A/O	VF	60				66261069600
	Gray	851 General Cleaning Pad	S/C	VF	40				66261085100
	Gray	635 Clean & Finish Pad	S/C	UF	60				66261063500
	Gray	748 Final Shine Pad	S/C	MF	60				66261074800
	White	456 Cleaning Pad	None	—	60				66261045600
Hand Pad Holder									
3-1/4 x 5-1/2	N/A	Hand Pad Holder			10				66261047583
Rolls									
4" x 30 Ft.	Maroon	High Strength Roll	A/O	M	3		66261006358		
	Dark Tan	740 Heavy-Duty Roll IMPROVED!	A/O	M	3				66261010081
	Maroon	644 General Purpose Fine Roll	A/O	F	4				66261058364
	Maroon	777 General Purpose Very Fine Roll	A/O	VF	4		66261006373		66261058361
	Maroon	747 General Purpose Plus Roll	A/O	VF	4		66261051701		
	Gray	851 General Cleaning Roll	S/C	VF	4				66261058360
	Gray	635 Clean & Finish Roll	S/C	UF	5				66261058357
6" x 30 Ft.	Maroon	High Strength Roll	A/O	M	2		66261005182		
	Maroon	747 General Purpose Plus Roll	A/O	VF	3		66261016430		
	Maroon	777 General Purpose Very Fine Roll	A/O	VF	3		66261004281		66261058376
	Gray	851 General Cleaning Roll	S/C	VF	3				66261058377
2" x 15 Ft. Handy Roll Pack	Assorted	1 each A/O Fine, A/O VF, SC MF	—	—	1				66261008108
Scouring Pads/Sponges									
3-1/4 x 6-1/4 x 3/4	Green/Yellow	893 Scour-N-Sponge Pad	A/O	VF	40				66261059403
3-1/4 x 6-1/4 x 3/4	White/Yellow	875 Clean-N-Sponge Pad	None	—	40				66261059402



Put Our Technology To Work!

UPGRADED PERFORMANCE Norton Bear-Tex 740 Hand Pad


Revolutionize your operation with our technological breakthrough for aggressive and rough metalworking applications. Our Clean Bond resin technology makes 740 heavy-duty hand pads more aggressive and durable than ever before.

FEATURES & BENEFITS

- Up to two times more life vs. competitive and former Norton products
- Increased grain retention for increased cutting capabilities
- Ultra flexible resin for added user comfort
- Ultra conformable for superior surface finish consistency

Our 740 series of products are available in non-stock sizes and shapes. Contact your Norton sales representative for samples.





CATEGORY DEFINITION

Made from non-woven synthetic fiber mesh, which is impregnated with abrasives and bound with resins, non-woven wheels are designed to create desired surface finish where little or no stock removal is required. The industry's broadest offering is available for light stock removal, deburring, blending, finishing and polishing. Non-woven wheels have an open mesh construction that is waterproof, washable, conformable and non-loading.

APPLICATIONS: Cleaning and removing imperfections on metal surfaces, cleaning built-up residue, deburring or finishing a variety of surfaces, blending weld seams or creating decorative finishes. Non-woven surface finishing products have excellent versatility.

ABRASIVE GRAIN: Aluminum Oxide, Silicon Carbide

GRIT RANGE: Extra Coarse (XC), Coarse (C), Medium (M), Fine (F),

APPLICATION/GRIT RECOMMENDATION GUIDE

	MOST AGGRESSIVE → LEAST AGGRESSIVE						
	RAPID STRIP WHEELS	RAPID BLEND UNIFIED WHEELS	SERIES 4000 & 1000 CONVOLUTE WHEELS	METAL FINISHING CONVOLUTE WHEELS	CLEAN & FINISH CONVOLUTE WHEELS	LIGHT FINISHING CONVOLUTE WHEELS	NON-WOVEN / INTERLEAF FLAP WHEELS
NORTON							
SCALE REMOVAL	BEST CHOICE						
STOCK REMOVAL		BEST CHOICE	2ND CHOICE				
HEAVY DEBURRING		BEST CHOICE	2ND CHOICE				
DECORATIVE FINISHING				BEST CHOICE	2ND CHOICE		
BLENDING			BEST CHOICE	2ND CHOICE			
CLEANING				2ND CHOICE	BEST CHOICE		
LIGHT DEBURRING			2ND CHOICE			BEST CHOICE	
LIGHT FINISHING			2ND CHOICE			BEST CHOICE	
POLISHING						BEST CHOICE	2ND CHOICE
BUFFING							BEST CHOICE


SURFACE FINISH VARIABLES

Changes in any one of many factors can affect the surface finish on the workpiece. This chart shows the effect on surface finish by changes in single factors of product specifications. Arrows have been used to signify the trend direction. The arrow length does not signify that the effect of each factor is equal.

Variable Factor	Rough Finish High Rms Reading	Smooth Surface Lower Rms Reading		
1. Wheel Speed	Slow	Fast		
2. Feed Speed	Faster (Long Scratch)	Slower (Short Scratch)		
3. Oscillation	No Oscillation	Oscillation		
4. Lubricants	Dry	Water	Soluble Oil	Straight Oil
		Compounds		

NON-WOVEN MARKING SYSTEM

ABRASIVE	S/C			A/O
	SHARPER, FINER/BRIGHTER SCRATCH PATTERN		MORE DURABLE, LONGER LASTING, POLISHED FINISH	
GRIT SIZE	XC (24-36)	C (50-80)	M (100-150)	F (180-220)
	FASTER, AGGRESSIVE CUT, ROUGHER FINISH		REDUCED CUT RATE, FINER FINISH	
DENSITY	2			9
	SOFT, OPEN, CONFORMABLE, LESS BURNING/LOADING		HARDER, MORE DURABLE, FASTER CUTTING, BETTER FINISH	



CROSS REFERENCE GUIDE

	STRIPPING	HEAVY/LIGHT DEBURRING		LIGHT DEBURRING/BLENDING/POLISHING			CLEANING/FINISHING		
NORTON	GOOD Rapid Strip	BEST Vortex Rapid Blend	GOOD NEX Rapid Blend	BEST Series 4000	BETTER Series 1000	BEST Light Finishing	BEST Metal Finishing	BEST Clean & Finish	GOOD Non-Woven / Interleaf Flap Wheels
	3M Clean Strip	Cut & Polish Unitized	EXL Unitized	EX2 & EX3	EXL Deburring	Light Deburring	Metal Finishing	Multi Finishing	Finishing Flap Brush
Standard	Britestrip	800 & 900 Series	500 - 700 Series	GP Plus	Deburring Convolute	LDW	Metal Finishing	Multi Finishing	Buff & Blend Flap Brush

Rapid Strip Wheels



NORTON RAPID STRIP WHEELS

IDEAL FOR REMOVING COATINGS ON A VARIETY OF SUBSTRATES, SUCH AS WOOD, METAL AND PLASTICS

FEATURES

- Extruded nylon fibers, flexible resin technology, and extra-coarse silicon carbide mineral

BENEFITS

- Provide a unique combination of aggressive performance, long life, and improved finish while outperforming traditional coated abrasives
- Leave a thoroughly cleaned surface that ensures excellent adhesion for subsequent processes such as coating, painting and soldering.

AVAILABILITY

TIER:	GOOD
BRAND:	Norton
TRADENAME:	RAPID STRIP WHEELS
GRIT:	Extra Coarse

SIZE	MAX. RPM	STD. PKG.	PART #
Arbor Hole			
4 x 1/4	8,000	25	66261008008
4 x 1/2	8,000	25	66261007916
6 x 1/2	5,500	15	66261008051

Rapid Blend Unified Wheels

Designed for maintenance operations needing an efficient and cost-effective method of deburring, polishing, cleaning or finishing metals and composites. Easily preformed for use on a wide variety of shapes/contours. Hold shape well; less wheel dressing. Non-metallic so no contamination of workpiece. Uniform construction maintains part tolerance; prevents cutting or gouging.



NORTON VORTEX RAPID BLEND UNIFIED WHEELS

BETTER CHOICE FOR LIGHT WELD BEAD AND WELD SPLATTER REMOVAL, HEAVY DEBURRING AND FINISHING APPLICATIONS

FEATURES

- High-performance engineered grain and improved resin bond system
- Thick nylon web
- Controlled porosity


BENEFITS

- Aggressive, fast, stock removal, reduced cycle times, and increased part quality
- 2X longer life and faster finishing – with minimal shedding
- Cool cutting and improved cut rate

AVAILABILITY

TIER:	BETTER
BRAND:	Norton
TRADENAME:	VORTEX RAPID BLEND UNIFIED WHEELS

SIZE (D x T x H)	ABRASIVE	GRIT SIZE	STD. PKG.	MAX. RPM	3 DENSITY PART #	MAX. RPM	5 DENSITY PART #	MAX. RPM	7 DENSITY PART #	MAX. RPM	9 DENSITY PART #
2 x 1/8 x 1/8	A/O	M	60			22,000	66254425657	20,000	66254410849		
2 x 1/8 x 1/4	A/O	M	60			22,000	66254406346	22,000	66261191446		
2 x 1/4 x 1/4	A/O	M	60	18,000	66254428456	22,000	66254433504	22,000	66261080270		
2 x 1 x 1/4	A/O	M	15					22,000	66261080269		
3 x 1/8 x 1/4	A/O	M	40			18,000	66261093448	18,000	66261191445		
3 x 1/8 x 3/8	A/O	M	40			18,000	66254433503	18,000	66254401131		
3 x 1/4 x 1/4	A/O	M	40	12,000	66254428454	18,000	66254414832	18,000	66261199696		
3 x 1/4 x 3/8	A/O	M	40	12,000	66254433505	12,000	66254433506	18,000	66261199697		
3 x 1/2 x 1/4	A/O	M	20			18,000	66254432925	18,000	66261080267	18,000	66254433507
3 x 1/2 x 3/8	A/O	M	20			18,000	66254433508	18,000	66261080266	18,000	66254420696



Rapid Blend Unified Wheels CONTINUED



NORTON NEX RAPID BLEND WHEELS
GOOD CHOICE FOR LIGHT DEBURRING AND BLENDING

FEATURES

- Uniform construction
- Smear-resistant formula

BENEFITS

- Extra long life
- Excellent, consistent, smear-free finishes

AVAILABILITY

TIER:

BRAND:

TRADENAME:

GOOD


Norton

NEX RAPID BLEND UNIFIED WHEELS


SIZE (D x T x H)	ABRASIVE	GRIT	MAX. RPM	STD. PKG.	2 DENSITY PART #	3 DENSITY PART #	4 DENSITY PART #	6 DENSITY PART #	7 DENSITY PART #	8 DENSITY PART #
1 x 1 x 3/16	A/O	C	30,000	50						66261014915
	A/O	M	18,000	50	66261014891					
	A/O	M	30,000	50				66261014908		66261014924
	A/O	F	30,000	50				66261014900		
	S/C	F	18,000	50	66261014883					
	S/C	F	30,000	50				66261014904		66261014923
2 x 1/8 x 1/4	A/O	M	22,000	60						66261014927
2 x 1/4 x 1/4	A/O	C	22,000	60						66261014916
	A/O	M	18,000	60	66261014892					
	A/O	M	22,000	60						66261014926
	A/O	F	22,000	60				66261014901		
	S/C	M	22,000	60						66261014964
	S/C	F	18,000	60	66261014884					
2 x 1/2 x 1/4	A/O	M	22,000	30						66261014925
3 x 1/8 x 1/4	A/O	M	18,000	40						66261014934
3 x 1/4 x 1/4	A/O	C	18,000	40						66261014919
	A/O	M	12,000	40	66261014894					
	A/O	M	18,000	40				66261014909		66261014930
	A/O	F	18,000	40			66261015565	66261014902		
	S/C	M	18,000	40						66261014937
	S/C	F	12,000	40	66261014886	66261016392				
3 x 1/4 x 3/8	A/O	C	18,000	40						66261014920
	A/O	M	12,000	40	66261014895					
	A/O	M	18,000	40				66261014910		66261014933
	A/O	F	12,000	40			66261014899			
	S/C	M	18,000	40						66261014965
	S/C	F	12,000	40	66261014887	66261016006				
3 x 1/2 x 1/4	S/C	F	18,000	40				66261014905		
	A/O	C	18,000	20						66261014917
	A/O	M	12,000	20	66261014893					
	A/O	M	18,000	20				66261014928		
3 x 1/2 x 3/8	S/C	F	12,000	20	66261014885					
	A/O	C	18,000	20						66261014918
	A/O	M	18,000	20						66261014929
	S/C	XC	14,000	20						
3 x 1 x 3/8	S/C	XC	14,000	10					66261014914	
6 x 1/2 x 1	A/O	M	7,500	4						66261014931
6 x 1 x 1	A/O	M	5,000	2	66261014896					
	S/C	F	5,000	2	66261014888					



BEAR-TEX®



Rapid Blend Unified Wheels CONTINUED



AVAILABILITY

NORTON RAPID BLEND DEBURRING UNIFIED WHEELS

GOOD STARTING SPECIFICATION FOR HIGH-SPEED DEBURRING APPLICATIONS

FEATURES

■ Controlled density range

BENEFITS

■ More durable than General Duty Wheels

TIER: **GOOD**

BRAND: Norton

TRADENAME: **RAPID BLEND DEBURRING
UNIFIED WHEELS**

SIZE (D x T x H)	ABRASIVE	GRIT	MAX. RPM	STD. PKG.	PART #
2 x 1/4 x 1/4	A/O	220	20,000	60	66261052200
2 x 1/2 x 1/4	A/O	120	20,000	40	66261058876
	S/C	220	20,000	40	66261058782
3 x 1/4 x 1/4	A/O	220	18,000	40	66261058877
	S/C	220	18,000	40	66261058854
3 x 1/2 x 1/4	S/C	220	18,000	20	66261058859
3 x 3/4 x 1/4	A/O	220	18,000	20	66261058881



AVAILABILITY

NORTON RAPID BLEND GENERAL DUTY DEBURRING UNIFIED WHEELS

GOOD CHOICE FOR GENERAL PURPOSE LIGHT DEBURRING APPLICATIONS

FEATURES

■ Outstanding resistance to snagging

BENEFITS


■ For general purpose light deburring applications

TIER: **GOOD**

BRAND: Norton

TRADENAME: **RAPID BLEND
GENERAL DUTY UNIFIED WHEELS**

SIZE (D x T x H)	ABRASIVE	GRIT	DENSITY	MAX. RPM	STD. PKG.	PART #
1 x 1 x 3/16	A/O	C	8	15,000	50	66261000938
2 x 1/4 x 1/4	A/O	C	8	11,000	60	66261052275
2 x 1/2 x 1/4	A/O	F	4	11,000	40	66261058764
3 x 1/4 x 1/4	A/O	C	8	8,000	40	66261052276
	A/O	F	4	8,000	40	66261058816
	S/C	F	4	8,000	40	66261000745
3 x 1/2 x 1/4	A/O	F	4	8,000	20	66261054046
	S/C	F	4	8,000	20	66261054048
3 x 3/4 x 1/4	A/O	F	4	8,000	20	66261058769
	S/C	M	4	8,000	20	66261058773
	S/C	F	4	8,000	20	66261058771
6 x 1/2 x 1/2	S/C	M	4	4,800	8	66261058779
6 x 1 x 1/2	S/C	M	4	4,800	4	66261058792
	S/C	F	4	4,800	4	66261058790
6 x 1 x 1	S/C	F	4	4,800	4	66261058797



Mandrels for Unified Wheels

FITS WHEEL CENTER HOLE	FOR WHEEL WIDTH	FOR WHEEL DIAMETER	SHANK DIAMETER	OVERALL LENGTH	WASHER DIAMETER	3M EQUIVALENT	STD. PKG.	PART #
Mandrel Assemblies for Unified Wheels and Discs on Edge								
1/8 – 3/16	Up to 1/2	Up to 2	1/8	1-3/4	7/16	931	1	66261009849
3/16	1/8 – 1/2	1 – 2	1/4	2	7/16	994	1	66261009852
1/4 – 5/16	Up to 1/2	Up to 2	1/4	2	5/8	932	1	66261015146
1/4 – 5/16	Up to 1	Up to 2	1/4	2-1/2	5/8	932	1	66261059422
	Up to 1	2 – 3	1/4	2-1/2	1	933	1	66261059421
3/8	Up to 1/2	2 – 4	1/4	2-1/2	1	990	1	66261009851
1/2	Up to 1	3 – 6	1/4	3-1/8	1-5/8	934	1	66261009850

FOR CENTER HOLE	USE WITH UNIFIED WHEEL	SHANK DIAMETER	SHANK LENGTH	3M EQUIVALENT	STD. PKG.	PART #
Threaded Mandrel for Unified Wheels						
3/16	1 x 1 x 3/16	1/4"	1-3/4"	948	5	66261047584



MANDREL ASSEMBLY 66261059421



MANDREL ASSEMBLY 66261059422



THREADED MANDREL 66261047584





Convolute Wheels

Formed by wrapping and bonding web material impregnated with abrasive grain and resin around a center core. Convolute wheels offer a wide range of uses:.

- Burr and flashing removal
- Surface roughness reduction
- Blending weld areas on stainless steel
- Blending scratch patterns
- Weld polishing
- Removing rust and oxides
- Applying decorative finishes including antique patterns

TECHtip

- Convolute wheels must always run in the direction indicated by the arrow printed on the side of each wheel.
- Light to medium pressure is recommended. Excessive pressure may result in part damage.
- Lubricants such as water-soluble oil and straight oil will decrease the heat and improve the surface finish and lustre.



It is the user's responsibility to refer to and comply with all safety regulations.

FEATURED PRODUCTS



SERIES 4000 RAPID FINISH CONVOLUTE WHEELS BEST CHOICE FOR HEAVY DEBURRING APPLICATIONS

FEATURES

- Advanced resin bond system
- High quality synthetic web

BENEFITS

- Free cutting
- Use both wet and dry
- Long life for heavy deburring, edge breaking and removing parting lines on exotic metals

AVAILABILITY

TIER:

BRAND:

TRADENAME:

BEST

Norton

SERIES 4000 RAPID FINISH CONVOLUTE WHEELS

SIZE (D x T x H)	ABRASIVE	GRIT	MAX. RPM	STD. PKG.	8 DENSITY PART #	9 DENSITY PART #
Series 4000 Rapid Finish Convolute Wheels						
6 x 1/2 x 1	S/C	F	6,000	4		66261004021
6 x 1 x 1	A/O	M	6,000	3	66261004208	
	S/C	F	6,000	3	66261004142	66261004141
8 x 1 x 3	A/O	M	4,500	3	66261004165	
	S/C	F	4,500	3	66261004123	66261004135
12 x 1 x 5	S/C	F	3,000	2	66261004284	66261004148
12 x 2 x 5	S/C	F	3,000	1		66261004011



BEAR-TEX®



Convolute Wheels CONTINUED



SERIES 1000 LONG LIFE RAPID FINISH CONVOLUTE WHEELS

BETTER CHOICE FOR GENERAL DEBURRING, BLENDING, AND FINAL FINISHING

FEATURES

- Smear and heat-resistant formula
- Dense web construction (9 density)
- More open web construction (7 density)
- Waterproof
- Non-metallic
- Optimum grain/resin formulation
- Conformable and flexible

BENEFITS

- Consistent, high quality results
- Starting point for deburring, blending, polishing and finishing applications
- Smear-resistant and cool cutting on light deburring applications
- Use dry, wet or with oil
- No contamination of workpiece
- Durable, long life construction with versatile application range and improved cut rate and shed resistance
- Less operator fatigue

AVAILABILITY

TIER:

BRAND:

TRADENAME:

BETTER

Norton

SERIES 1000 LONG LIFE RAPID FINISH CONVOLUTE WHEELS

SIZE (D x T x H)	ABRASIVE	GRIT	MAX. RPM	STD. PKG.	7 DENSITY PART #	8 DENSITY PART #	9 DENSITY PART #
Series 1000 Long Life Rapid Finish Convolute Wheels							
6 x 1/2 x 1	A/O	M	6,000	4	66261018857	66261018789	66261018650
	S/C	M	6,000	4			66261019540
	S/C	F	6,000	4	66261018628		66261018629
6 x 1 x 1	A/O	M	6,000	3	69957397884	66261018636	66261019337
	S/C	M	6,000	3	69957397882	69957397883	66261018630
	S/C	F	6,000	3	66261018631	66261018774	66261018632
8 x 1 x 3	A/O	M	4,500	3	69957397885	66261018855	66261018633
	S/C	M	4,500	3	69957394610	66261018673	66261018997
	S/C	F	4,500	3	66261018639	66261018640	66261018641
12 x 1 x 5	A/O	M	3,000	2	69957397887		66261018896
	S/C	M	3,000	2		66261018786	66261018908
	S/C	F	3,000	2			66261018626



LIGHT FINISHING CONVOLUTE WHEELS

BEST CHOICE FOR LIGHT DEBURRING, POLISHING, AND FINE FINISHING APPLICATIONS

FEATURES

- Controlled cut rate
- Very conformable
- Superior form holding
- Durable resin bond system
- Advanced manufacturing process

BENEFITS

- Prevents "over benching"
- Deburrs and polishes without altering geometry
- Operator friendly, reduces fatigue
- Consistent, reliable edge breaking and finishing with minimal wheel dressing and reshaping
- Less dust and shedding with more uniform wear
- Substantial extended wheel life in a soft, conformable wheel
- Improved web forming and grain distribution produce consistent finish on intricate polishing applications

AVAILABILITY

TIER:

BRAND:

TRADENAME:

BEST

Norton

LIGHT FINISHING CONVOLUTE WHEELS

SIZE (D x T x H)	ABRASIVE	GRIT	MAX. RPM	STD. PKG.	6 DENSITY PART #	7 DENSITY PART #	8 DENSITY PART #
Light Finishing Convolute Wheels							
6 x 1/2 x 1	S/C	F	6,000	4	66261092322	66261092324	66254421572
6 x 1 x 1	S/C	F	6,000	3	66254403708	66254403709	66254421573
8 x 1/2 x 3	S/C	F	4,500	4	66254403707	66254409698	66254421575
8 x 1 x 3	S/C	F	4,500	3	66261095702	66254409924	66254421577



Convolute Wheels CONTINUED



METAL FINISHING CONVOLUTE WHEELS

BEST CHOICE FOR DECORATIVE FINISHING, BLENDING, AND FINAL FINISHING

FEATURES

- Premium, medium grit aluminum oxide grain
- Dense, very durable web
- Strongest resin binders
- Uniform grain dispersion and coating
- Available in 5 and 6 densities

BENEFITS

- Generates uniform distinct satin and antique finishes
- Can be used for blending applications
- Resilient, long life construction
- Clean and condition without gouging or changing dimensions of workpiece
- Ideal for blending and matching #3 and 4 mil. finishes, and surface prep for buffing, polishing and applying decorative finishes

AVAILABILITY

TIER: **BEST**

BRAND: Norton

TRADENAME: **METAL FINISHING
CONVOLUTE WHEELS**

SIZE (D x T x H)	ABRASIVE	GRIT	DENSITY	MAX. RPM	STD. PKG.	PART #
Metal Finishing Convolute Wheels						
6 x 1 x 1	A/O	M	5	6,000	3	66261007936
		M	6	6,000	3	66261010148
6 x 2 x 1	A/O	M	5	6,000	2	66261007957
		M	6	6,000	2	66261009635
8 x 1 x 3	A/O	M	5	4,500	3	66261007831
8 x 2 x 3	A/O	M	5	4,500	2	66261007904
		M	6	4,500	2	66261012971
12 x 1 x 5	A/O	M	5	3,000	2	66261007434
		M	6	3,000	2	66261009481
12 x 2 x 5	A/O	M	5	3,000	1	66261007212
14 x 2 x 8	A/O	M	5	2,550	1	66261007817
		M	6	2,550	1	66261012041



CLEAN & FINISH CONVOLUTE WHEELS

BEST CHOICE FOR FINE FINISHING WITH LIGHT PRESSURE

FEATURES

- Silicon carbide grain
- Open mesh construction

BENEFITS

- Good for blending, rust removal, applying decorative, contrast finishes and low- to moderate-speed applications
- Not used for deburring
- Used with light to moderate pressure, low speed

AVAILABILITY

TIER: **BEST**

BRAND: Norton

TRADENAME: **CLEAN & FINISH
CONVOLUTE WHEELS**

SIZE (D x T x H)	ABRASIVE	GRIT	DENSITY	MAX. RPM	STD. PKG.	PART #
Clean & Finish Convolute Wheels						
4 x 1 x 1	S/C	M	4	4,000	10	66261058502
		F	4	4,000	10	66261058501
6 x 1 x 1	S/C	M	4	3,000	4	66261058507
		F	4	3,000	4	66261058506
6 x 2 x 1	S/C	M	4	3,000	2	66261058510
		F	4	3,000	2	66261058509
6 x 3 x 1	S/C	M	4	3,000	1	66261058512
6 x 4 x 1	S/C	M	4	3,000	1	66261058514
8 x 1 x 3	S/C	M	4	2,500	3	66261058518
8 x 2 x 3	S/C	M	4	2,500	2	66261058521
8 x 3 x 3	S/C	M	4	2,500	1	66261058524
8 x 4 x 3	S/C	M	4	2,500	1	66261058526






Aluminum Reducing Bushings for Flap and Convolute Wheels



- Durable, aluminum one-piece-design flanges with integrated “contact washer”
- Snug fit; extended usable life
- Available in stock and non-stock sizes: 3" up to 10" in many combinations of ID hole reduction

WHEEL CENTER HOLE	BUSHING REDUCES HOLE SIZE TO	FOR WHEEL DIAMETER	STD. PKG.	PART #
Aluminum Reducing Bushing for Flap and Convolute Wheels				
1	3/8	4 - 6	1 Pair	66261080522
	1/2	4 - 6	1 Pair	66261080523
	5/8	4 - 6	1 Pair	66261080524
	3/4	4 - 6	1 Pair	66261080525
	7/8	4 - 6	1 Pair	66261080526
2	1/2	6	1 Pair	66261080527
	5/8	6	1 Pair	66261080528
	1	6	1 Pair	66261080529
	1-1/4	6	1 Pair	66261080530
3	1	8	1 Pair	66261080531
	1-1/4	8	1 Pair	66261080532
	1-1/2	8	1 Pair	66261080383
	2	8	1 Pair	66261080514
5	1	10 and 12	1 Pair	66261080533
	1-1/4	10 and 12	1 Pair	66261080534
	3	10 and 12	1 Pair	66261080535
8	1-1/4	14	1 Pair	66261080536
10	1-1/4	16	1 Pair	66261080520





CATEGORY DEFINITION

Norton non-woven belts are a combination of strong synthetic mesh and quality abrasive, bonded together by a smear-resistant adhesive. The open construction of non-woven material enables aggressive cutting action and improved surface finish while maintaining its non-loading feature.

APPLICATIONS: Removing surface defects, light edge burrs, parting lines, flashing, rust, oxides, corrosion, paints, and scale; blending mill marks, tool marks, uneven edges, and applying decorative finishes.

ABRASIVE GRAIN: Aluminum Oxide

GRIT RANGE: Extra Coarse (Black), Coarse (Brown), Medium (Maroon), Fine (Green), Very Fine (Blue)

APPLICATION/GRIT RECOMMENDATION GUIDE

	EXTRA COARSE	COARSE	MEDIUM	FINE	VERY FINE
	BETTER CHOICE - NORTON VORTEX RAPID PREP				
	GOOD CHOICE - NORTON RAPID PREP				
Scale Removal	X				
Stock Removal		X			
Heavy Deburring		X			
Light Deburring			X		
Light Finishing			X		
Blending				X	
Finishing					X

FEATURED PRODUCTS



NORTON VORTEX RAPID PREP NON-WOVEN BELTS

BETTER CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

- Proprietary Vortex aluminum oxide abrasive grain and new coating method

BENEFITS

- Most consistent cutting and finishing of surface conditioning products on the market
- Combine maximum cutting speed with the finish of fine grits
- Reduce process times by 50+% by eliminating 2 to 5 grit sequences to 1 step in your technical blending operations
- More resistant to edge wear; up 4X life vs. competitive products
- Friable grain structure keeps Ra specs throughout disc life and reduces scrap and rework

- Clean Bond resin system, aerospace-tailored

- Smear-free, even on high nickel content alloys
- Will not load on aluminum and soft metals, as competitive products may



NORTON RAPID PREP

GOOD CHOICE FOR FINISHING AND BLENDING APPLICATIONS

FEATURES

- Clean Bond resin system, aerospace-tailored

BENEFITS

- Smear-free, even on high nickel content alloys
- Will not load on aluminum and soft metals, as competitive products may
- Thick layer of grain throughout the product extends life; grain does not sit on top of fibers as other competitive products may
- Extended form holding
- Lowest total cost of consumable tooling per workpiece
- 50% better life than competitive aluminum oxide products



Norton Vortex Rapid Prep

AVAILABILITY

TIER:	BETTER	BETTER	BETTER	BETTER	BETTER
BRAND:	Norton	Norton	Norton	Norton	Norton
TRADENAME:	VORTEX RAPID PREP	VORTEX RAPID PREP	VORTEX RAPID PREP	VORTEX RAPID PREP	VORTEX RAPID PREP
ABRASIVE:	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
GRIT/COLOR:	EXTRA COARSE	COARSE	MEDIUM	FINE	VERY FINE
WIDTH	LENGTH	STD. PKG.	PART #	PART #	PART #
2	18-15/16	12	66623313274	66623335031	66623333675
2-3/4	15-1/2	10	66623333718	66623333628	66623333676
3	10-11/16	12	66623333719	66623335039	66623335110
	18	10	66623335149	66623335040	66623335112
	21	10	66623333720	66623333629	66623335113
	24	10	66623335150	66623333630	66623335114
3-1/2	15-1/2	8	66623333725	66623335042	66623335118
4	24	8	66623333726	66623335043	66623335119
					66623333649
					66623333655
					66623333656
					66623333657
					66623333658
					66623333659
					66623335135
					66623333696
					66623335136
					66623335139
					66623333700

Norton Rapid Prep

AVAILABILITY

TIER:	GOOD	GOOD	GOOD	GOOD	GOOD
BRAND:	Norton	Norton	Norton	Norton	Norton
TRADENAME:	RAPID PREP	RAPID PREP	RAPID PREP	RAPID PREP	RAPID PREP
ABRASIVE:	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide	Aluminum Oxide
GRIT/COLOR:	EXTRA COARSE	COARSE	MEDIUM	FINE	VERY FINE
WIDTH	LENGTH	STD. PKG.	PART #	PART #	PART #
1/4	18	24	66261011420	66261012524	66623333424
	24	24	69957392606	66261097565	66623333425
1/2	12	24	66261003177	66261006465	66623318175
	18	24	66261055309	66261055310	66623333426
	24	24	66261055312	66261008972	66254490859
3/4	18	12	66261002111	66261015808	66254490858
	20-1/2	12	66261083899	66261003260	66623333427
	80	12	66623333411	66623333505	66623333428
1	18	12	66261007023	66261017898	66623333429
	21	12	66623333412	66623336005	66623333430
	30	12	66261019801	66623336006	66623333431
	42	12	66261008317	66254441289	66623333432
	60	12	66623333413	66623333506	66623333433
	64	12	66623333414	66623301513	66623333434
	72	12	66261194240	66261006378	66254493830
	132	10	66623314981	66254436886	66623333525
1-1/2	60	8	66623333415	66261007644	66623333435
2	18-15/16	12	66261018224	66623333507	66623333436
	34	12	66261063309	66623312203	66623333437
	48	10	66261006504	66261006648	66623333438
	60	8	66623333416	66261189669	66623333439
	72	8	66261002571	66261007757	66623333440
	132	6	66261008491	66261008492	66261069525
2-1/2	60	6	66254429365	66254441491	66623333441
2-3/4	15-1/2	10	66623333417	66623333508	66623333442
3	10-11/16	12	66623333580	66261067469	66623333443
	18	10	66254428772	66254428776	66623333444
	21	10	66623333584	66261010870	66623333445
	24	10	66254433359	66623314158	66623333446
	72	6	66623333419	69957396833	66623333447
	80	4	66623333420	66261007149	66623333448
	90	4	66623333421	66623333509	66623333449
	118	4	66623333422	66623333510	66623333450
	132	4	66254490470	66261055322	66623333451
3-1/2	15-1/2	8	66623333595	66261055324	66623333452
4	24	8	66623333596	66254444576	66623333453
	36	6	66254495931	66261031667	66623333454
	132	2	66623333423	66261002321	66623333455
	168	2	66261009056	66261006898	66623333456
	168	2	63642576650	66261009174	66623333457
6	48	4	66261055330	66261055331	66623333457

If you do not see the Rapid Prep belts you need in our stock offering, call your local Norton distributor to check for made-to-order availability.



CATEGORY DEFINITION

Non-woven surface finishing flap wheels are an ideal choice for a wide variety of blending and finishing applications common in the metal fabrication, welding and polishing industries. Flap wheels are conformable to intricate shapes and contours. Designed to deliver a consistent finish with a uniform rate of cut, flap wheels wear away continually exposing fresh abrasives.

There are two types of non woven flap wheels: non-woven only abrasive flaps where finishing is the primary application, and interleaf with alternating cloth and non-woven abrasive flaps (less conformable, more aggressive) for stock removal and finishing. Interleaf flap wheels must always be run in the direction indicated by the arrow.


APPLICATIONS: Used for a wide range of metal fabrication and welding applications including blending, deburring, cleaning, finishing, and polishing


SIZE RANGE: Flap wheels with mounted steel shanks: 2" – 4" diameter
Flap wheels with arbor holes: 3" – 12" diameter

GRIT RANGE: 60 – 320


ABRASIVE GRAIN: Aluminum Oxide, Silicon Carbide

APPLICATION/GRIT RECOMMENDATION GUIDE





1/4" Mounted Steel Shanks



AVAILABILITY

TIER:

BRAND:

TRADENAME:



BETTER

Norton



GOOD

Merit



BETTER

Norton



GOOD

Merit

SIZE (D x W x SK.)	ABRASIVE	CA GRIT	NON-WOVEN GRIT	MAX. RPM	STD. PKG.	INTERLEAF PART #	INTERLEAF PART #	NON-WOVEN PART #	NON-WOVEN PART #
2 x 1 x 1/4	A/O	60	Coarse	12,000	10	66261051720*	08834138122		
	A/O	80	Medium	12,000	10	66261051721*	08834138123		
	A/O	120	Medium	12,000	10	66261051722	08834144457	66261051716*	66261189992*
	A/O	180	Fine	12,000	10		08834144458		
	A/O	320	Very Fine	12,000	10		08834144459	66261051717*	69957399202
2 x 1-1/2 x 1/4	A/O	60	Coarse	12,000	10		08834138124		
	A/O	80	Medium	12,000	10		08834138125		
	A/O	120	Medium	12,000	10		08834138126		
	A/O	180	Fine	12,000	10		08834138127		
	A/O	320	Very Fine	12,000	10		08834138128		
3 x 1 x 1/4	A/O	60	Coarse	12,000	10		08834138129		
	A/O	80	Medium	12,000	10		08834138130		
	A/O	120	Medium	12,000	10	66261051725*	08834138118	66261051718*	08834131921
	A/O	180	Fine	12,000	10		08834138120		
	A/O	320	Very Fine	12,000	10			66261051719*	
3 x 1-3/4 x 1/4	A/O	—	Medium	12,000	10		08834138119		66261026075
3 x 2 x 1/4	A/O	60	Grit	8,000	10		08834131338		
	A/O	80	Coarse	8,000	10		08834138116		
	A/O	120	Medium	8,000	10		08834144460	66261058474	
	A/O	180	Medium	8,000	10		08834144461		
4 x 2 x 1/4	A/O	80	Coarse	12,000	10		08834121115		
	A/O	120	Medium	12,000	10		08834120458		

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.

*STANDARD PACKAGE QUANTITY = 20

Refer to Non-Woven Convolute Wheel section for Flap Wheel Reducing Bushings.



BEAR-TEX®



Arbor Hole Mounts

AVAILABILITY



TIER:

BRAND:

TRADENAME:



SIZE (D x W x SK.)	ABRASIVE	CA GRIT	NON-WOVEN GRIT	MAX. RPM	STD. PKG.	PART #	PART #	PART #	PART #
3 x 2 x 3/8	A/O	60	Coarse	12,000	10		08834139000		
	A/O	120	Medium	12,000	10		08834139001		
	A/O	240	Very Fine	12,000	10		08834139028		
	A/O	320	Very Fine	12,000	10		08834139024		
4 x 2 x 5/8	A/O	60	Coarse	12,000	10		08834126025		
	A/O	240	Very Fine	12,000	10		08834126014		
	A/O	320	Very Fine	12,000	10		08834126027		
6 x 1 x 1	A/O	120	Medium	6,000	10		08834126006		
	A/O	240	Very Fine	6,000	10		08834126030		
6 x 1 x 2	A/O	80	Medium	3,000	4	66261004418			
	A/O	—	Medium	3,000	4			66261058456	
	A/O	180	Fine	3,000	4	66261005387		66261058487	05539562635
	S/C	—	Fine	3,000	4			66261058451	
6 x 2 x 1	A/O	—	Very Fine	3,000	4			66261058450	05539512658
	A/O	80	Medium	6,000	10		08834126009		
6 x 3 x 1	A/O	180	Fine	6,000	10		08834126018		
	A/O	80	Medium	6,000	6		08834126055		
8 x 1 x 3	A/O	120	Medium	2,500	3	66261010711			
	—	—	Fine	2,500	3			66261058491	
8 x 2 x 1	A/O	120	Medium	4,500	6		08834126043		
	A/O	180	Fine	4,500	6		08834126044		
8 x 2 x 3	A/O	—	Medium	2,500	2			66261000889	
	A/O	—	Medium	2,500	2				05539512677
	A/O	—	Fine	2,500	2			66261058493	
12 x 1 x 5	A/O	80	Medium	1,900	2	66261010712			
12 x 2 x 5	A/O	—	Medium	1,900	1				05539528945
	A/O	—	High Strength	1,900	1			66261005070	05539562637

SOME MERIT PART NUMBERS ARE NON-STOCK. ASK YOUR NORTON/MERIT REPRESENTATIVE FOR STOCK/MTO STATUS.



Introduction

Most Norton Bear-Text products consist of a non-woven web of nylon fibers impregnated throughout with abrasive grain and bonded with synthetic resins. This design produces a cushioned, three-dimensional material that is extremely pliable and long lasting. The uniform dispersion of abrasive throughout the web provides a continuous supply of new grain as the old grain and fibers wear away during use.

Norton Bear-Text products, with their open mesh construction, are waterproof, washable, resilient, conformable, non-loading, non-conductive, non-metallic and non-rusting. Norton Bear-Text wheels are easily pre-formed to conform to special-shaped work pieces.

Since Norton Bear-Text products are designed for use where stock removal is not required, they begin where other abrasives leave off. The relatively non-aggressive nature of nylon and grit inherent in the Norton Bear-Text material makes it ideal as a finishing tool. While 60 to 80 grit are considered intermediate sizes in other products, they are considered coarse for Norton Bear-Text items.

Used wet or dry, Norton Bear-Text products offer the following advantages: controlled cut (with little or no stock removal) allows for increased productivity, consistent, uniform finish, ability to automate operations, minimized smearing and reduced operator training. These advantages make Norton Bear-Text products an excellent alternative to bristle brushes, set-up wheels, greaseless compounds and steel wool.

Abrasives


Silicon carbide and aluminum oxide abrasives are offered. Silicon carbide is sharper, cuts faster, and produces finer scratch patterns on most surfaces. Aluminum oxide is more durable and tends to last longer. It causes less discoloration on aluminum, and is more aggressive on certain applications such as hardened steel parts. Norton Bear-Text hand pads are also available in a non-abrasive material.

Grits

Grit refers to the size of the abrasive grain impregnated into the nylon web. The coarser the grit, the more aggressive the cut, the rougher the finish. The finer the grit, the less aggressive the cut and the resulting surface finish will be finer, if all other conditions are equal.

GRIT DESIGNATIONS	GRIT SIZE
Extra Coarse (XC)	24 – 36
Coarse (C)	50 – 80
Medium (M)	100 – 150
Fine (F)	180 – 220
Very Fine (VF)	240 – 360
Super Fine (SF)	400
Ultra Fine (UF)	600
Micro Fine (MF)	800 – 1200

Product Identification System



Densities

The product "density" refers to the number of fibers which have been compressed into the nylon web material. Under identical conditions, harder density wheels cut faster, last longer and produce finer finishes than softer density wheels. Softer density wheels offer greater conformability and have less tendency to load or burn the work piece.

Fiber Sizing

Several nylon fiber sizes are used in the manufacture of Norton Bear-Text web material because the fiber size is a significant factor in the coating process, as each produces distinct cutting characteristics.

Bonding Agents

Waterproof resins are used in the manufacture of Norton Bear-Text web material to bond the nylon fibers together and to firmly anchor the abrasive grains throughout the web.

Conventional Finishing Methods Versus Norton Bear-Text Products

The following chart outlines the advantages achievable when using Norton Bear-Text products as alternatives to other cleaning, blending, deburring and finishing methods.

Norton Bear-Text products are listed in the sequence of normal preference for the application stated. However, because of the numerous variables, only testing can ensure selection of the most cost-effective product.

CONVENTIONAL FINISHING METHOD	KEY APPLICATION	BEAR-TEXT PRODUCT AS AN ALTERNATIVE	ADVANTAGES OF BEAR-TEXT PRODUCT VERSUS ALTERNATE FINISHING METHODS
Bristle Brushes	Cleaning	Clean & Finish Wheels Metal Finishing Wheels Flap Wheels	Superior cleaning performance Higher productivity No slurry or compound required More consistent finish Eliminate compound dust
Greaseless Compounds	Finishing	Flap Wheels Convolute Wheels Unified Wheels	Reduced maintenance No compound, instant set-up Elimination of compound dust More uniform finish More consistent work rate
Set-up Wheels	Blending/ Deburring	Convolute Wheels Unified Wheels	No break-in time required More consistent cut More uniform finish Maintain geometry Safer, no flying wheel pieces
Steel Wool	Cleaning	Rolls Discs Hand Pads	Faster, longer life Less pressure required Non-rusting, cleaner Safer, no splinters

Getting the Most Out of Norton Bear-Text Wheels

Maximum wheel life and best surface conditioning results can be achieved by closely adhering to the following recommendations.

1) Wheel Direction

Convolute wheels and interleaf flap wheels must always run in the direction indicated by the arrow printed on the side of each wheel. Conventional flap wheels and unified wheels can be run in either direction.

2) Wheel Speed

Wheel speed is an important factor in that it affects product finish, rate of cut, and wheel life. In general, fast wheel speeds give harder action and a finer finish; whereas, slower speeds give a softer action and a coarser finish for the same wheel density.

The following are recommended operating speeds for the most common applications.

APPLICATION	RECOMMENDED SPEED
Cleaning and upgrading of surface conditions	2200 to 6000 SFPM
Cut-buffing on metal surfaces	6500 to 8000 SFPM
Deburring	5500 to 8000 SFPM
Decorative finishing	500 to 3000 SFPM
Imparting decorative finishes	900 to 3000 SFPM
Oxide removal	3500 to 6500 SFPM

TESTING MIGHT SHOW THAT A SLOWER OR FASTER SPEED IS DESIRABLE FOR SPECIFIC OPERATIONS. NEVER EXCEED THE MAXIMUM RPM RATING OF THE WHEEL.

3) Pressure

Light to medium pressure is recommended for most operations. Flap wheels require much lighter pressure to perform properly than other Norton Bear-Text wheels; unified wheels can withstand much higher pressures in order to perform deburring jobs. In all cases, avoid excessive pressure which may result in wheel deformation and damage to the work surface.

4) Feed Speed

Low feed speed reduces the number of workpieces completed, while producing a shorter scratch pattern. Slow feed speed allows for longer dwell time and permits more work to be done on each piece. Conversely, a fast feed speed increases the number of workpieces completed, while producing a longer scratch pattern.

5) Oscillation

Oscillation may be used to break up scratch lines and produce a more uniform finish. Additionally, an increase in cut may be experienced. A general starting point for oscillation is 3/8" amplitude at 200 cycles per minute.

6) Lubricants

Lubricants, such as water, water soluble oil, and straight oil, will decrease the heat generated while running, improve the luster, and reduce the surface finish. The higher the viscosity of the lubricant, the lower the surface finish (RMS value) produced.

Factors in Wheel Choice

This chart provides a relative comparison of other Norton Bear-Text wheel variables. It can serve as a useful guide in choosing the most suitable product for a given application. However, as many other factors affect wheel performance, this chart can only be general in nature. The most cost-effective results can always be obtained by wheel testing on the application.

1 Wheel Conformability	MOST CONFORMABLE (SOFT) ←	Flap Wheels	Clean & Finish	Metal Finishing	Series 1000 Long Life 7 Density	Series 1000 Long Life 8 & 9 Density	Series 4000	← LEAST CONFORMABLE (HARD)
2 Wheel Openness	OPEN MESH ←		Clean & Finish	Metal Finishing	Series 1000 Long Life 7 Density	Series 1000 Long Life 8 & 9 Density	Series 4000	→ CLOSED MESH
3 Wheel Aggressiveness	MOST AGGRESSIVE ←		Metal Finishing		Clean & Finish	Series 1000 Long Life	Flap Wheels	→ LEAST AGGRESSIVE
4 Finishing Action	COARSER ←		Metal Finishing	Clean & Finish	Series 4000	Series 1000 Long Life Series 4000	Flap Wheels	→ FINER
5 Pressure for Best Results	LIGHTER ←	Flap Wheels	Clean & Finish	Metal Finishing Series 1000 Long Life 7 Density		Series 1000 Long Life 8 & 9 Density	Series 4000	→ HIGHER

* ON STEEL SURFACES, SILICON CARBIDE WHEELS WILL PRODUCE A BRIGHTER FINISH THAN ALUMINUM OXIDE WHEELS.

Surface Finish Variables

Changes in any one of many factors can affect the surface finish on the work piece. This chart shows the effect on surface finish by changes in single factors of product specifications. Arrows have been used to signify the trend direction. The arrow length does not signify that the effect of each factor is equal.

VARIABLE FACTOR	ROUGH FINISH HIGH RMS READING	SMOOTH SURFACE LOWER RMS READING
1 Grit Size	Coarse ←	→ Very Fine
2 Wheel Grade	Soft ←	→ Hard
3 Wheel Speed	Slow ←	→ Fast
4 Feed Speed	Faster (Long Scratch) ←	→ Slower (Short Scratch)
5 Oscillation	No Oscillation ←	→ Oscillation
6 Lubricants and Compounds	Dry ←	→ Water ← Soluble Oil ← Straight Oil



complementing our **ABRASIVES PORTFOLIO**

To help you finish the job, Norton accessory items let you one-stop shop. Our goal is to get it finished faster, easier and with less hassle of multiple vendors and invoices.



Get Wired

Broad wire brush offering includes the basic shapes and configurations you'll need for heavy - to light-duty brushing applications.




The Right Dose of Fiber

Trap dirt, grime or liquids with microfiber cloths. Whether you are cleaning, dry tacking, or polishing, these cloths make quick work, trapping all unwanted particles.



Unmasking the Mystery

Masking tape choices: Professional High Heat for maximum performance and clean release on multiple surfaces; Blue Core 14-Day Tape for easy on/off. and Pro Contractor Grade for general purpose.



CATEGORY DEFINITION


Our Norton wire brush broad offering includes all the basic shapes and configurations: cups, saucer cups, wheel end brushes and hand brushes. Informative, attractive packaging clearly explains dimensions, structure, safety and machine usage. All brushes are individually clamshell packaged unless otherwise noted. When using wire brushes, be sure to comply with ANSI B165 "Power-Driven Brushing Tools: Safety Requirement for the Design, Care and Use." and safety documents on www.nortonabrasives.com website.

APPLICATIONS:	Cleaning rust, scale and dirt; light deburring; edge blending; roughening for adhesion; finishing for appearance; finish preparation prior to plating or painting
SHAPES:	Cup, saucer cup, wheel, end brush, hand brush
WIRE DESIGN:	Twist knot, crimped, and stringer bead
OTHER:	Color-coded for easy identification:

STAINLESS

STEEL/METAL

FEATURED PRODUCTS AND AVAILABILITY

**BETTER TWIST KNOT WIRE SAUCER CUP BRUSHES**

IDEAL FOR CLEANING CORNERS, RECESSES, AND OTHER HARD-TO-REACH AREAS – FOR STEEL/STAINLESS


FEATURES

- Twist knot style

BENEFITS

- For heavy-duty cleaning

DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
4 x .020 x 5/8-11	15,000	5	Carbon	66252833483
5 x .020 x 5/8-11	12,500	10	Carbon	66252835585
5 x .020 x 5/8-11	12,500	10	Stainless	66252835586

**BETTER HIGH PERFORMANCE (HP) CABLE CRIMPED CUP BRUSHES**

FOR LIGHT- TO MEDIUM-DUTY BRUSHING APPLICATIONS ON FLAT OR IRREGULAR SURFACES, AND BEVEL BUFFING – FOR STEEL


FEATURES

- 12 wires of .009" brass-coated steel are bundled together into a group, then crimped
- Cable crimped wire breaks down in smaller pieces than standard crimped brushes

BENEFITS

- Creates a 50% longer lasting brush compared to standard crimped brushes; better flexibility on irregular surfaces
- Safer wire to use
- Protective guard

DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
Crimped Cup with Protective Guard – Single Row				
3 x (12 x .009) x 5/8-11	15,000	5	Carbon	66252833493
4 x (12 x .009) x 5/8-11	9,000	5	Carbon	66252833494

**BETTER CRIMPED WIRE CUP BRUSHES**

FOR LIGHT- TO MEDIUM-DUTY BRUSHING APPLICATIONS ON FLAT OR IRREGULAR SURFACES, AND BEVEL BUFFING – FOR STEEL


FEATURES

- Highly flexible heavy wire fill


BENEFITS

- Fast cutting

DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
3 x .014 x 5/8-11	15,000	5	Carbon	69936653341
3 x .014 x 5/8-11	20,000	5	Stainless	66252836362
4 x .014 x 5/8-11	9,000	5	Carbon	69936653347
4 x .020 x 5/8-11	9,000	5	Stainless	66252843844
6 x .014 x 5/8-11	6,000	5	Carbon	69936653348
6 x .020 x 5/8-11	6,000	1	Carbon	69936653349



FEATURED PRODUCTS AND AVAILABILITY

**BETTER TWIST KNOT WIRE CUP BRUSHES**

HIGH IMPACT CUTTING AND CLEANING ON MORE DEMANDING APPLICATIONS – FOR STEEL/STAINLESS

FEATURES

- Rigid structure
- Available with or without plastic guard
- Protective guard opens up into a shield
- Single row construction
- Double row construction

BENEFITS

- High impact cutting and cleaning on more demanding applications
- Application-specific
- Prevents wire, dust and/or projection from reaching the end-user
- Provides for a friendly handling of the brush, preventing potential pricking caused by the wire ends
- Limits flaring of the brush on corners and angles
- More aggressive; provides twice the cutting points of a single row cup brush for heavy-duty action in very severe applications

DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
Knotted Cup With Protective Guard – Single Row				
2-3/4 x .020 x 5/8-11	15,000	5	Carbon	66252833492
4 x .020 x 5/8-11	9,000	5	Carbon	66252833496
5 x .020 x 5/8-11	6,500	5	Carbon	66252833497
Knotted Cup – Single Row				
2-3/4 x .020 x 5/8-11	15,000	5	Carbon	69936653336
2-3/4 x .020 x 5/8-11	15,000	5	Stainless	69936653340
4 x .020 x 5/8-11	9,000	5	Carbon	69936653345
4 x .020 x 5/8-11 with bridle	9,000	5	Carbon	66252833947
6 x .020 x 5/8-11	6,000	5	Carbon	69936605965
6 x .035 x 5/8-11	6,000	5	Carbon	69936602003
Knotted Cup – Double Row				
6 x .020 x 5/8-11	6,000	5	Carbon	69936653346

BETTER CRIMPED WIRE WHEEL BRUSHES

EXCELLENT PERFORMANCE FOR DEBURRING, REMOVING RUST, CORROSION AND DIRT – FOR STEEL

FEATURES

- Brushes may be used individually or stacked on a shaft

BENEFITS



- Single-section, narrow-faced brushes are ideal for general-purpose brushing of uneven or difficult-to-reach surfaces
- Single section, medium-faced brushes clean larger surface areas and have longer life

DIAMETER x WIRE THICKNESS x HOLE SIZE	MAX. RPM	STD. PKG.	APPLICATION	PART #
Crimped Narrow 3/4" Face				
6 x .014 x 1/2-2**	6,500	5	Carbon	69936653306
Crimped Medium 1" Face				
4-1/2 x .014 x 5/8-11	13,000	6	Carbon	66253370278
6 x .014 x 1/2-2**	6,500	5	Carbon	69936653324
8 x .014 x 1/2-2**	4,500	5	Carbon	69936653326


** 7 BUSHING SIZES INCLUDED WITH EACH BRUSH (FIT 1/2" - 2")

STAINLESS

STEEL/METAL



FEATURED PRODUCTS AND AVAILABILITY

**BETTER STANDARD TWIST KNOT WIRE WHEEL BRUSHES**

IDEAL FOR TOUGHER WELDING AND METAL FABRICATION APPLICATIONS (REMOVING WELD SCALE SPATTER, EXTRA-HEAVY RUST AND CORROSION, OR SURFACE ROUGHENING) – FOR STEEL/STAINLESS

FEATURES

- Twist knot wire design
- Pipeline: heavy-duty knot construction

BENEFITS

- Provides added rigidity for extra cutting and cleaning power
- Small diameter wheels are used for small- to medium-duty jobs requiring some flexibility and lighter brushing action
- Stiffer, longer-lasting knots for tougher applications / heavy build-up
- Longest life for brushing/cleaning joints and preparing expansion joints for filling and scaling

DIAMETER x WIRE THICKNESS x MOUNT/HOLE	MAX. RPM	STD. PKG.	APPLICATION	PART #
3 x .014 x 5/8-11	20,000	5	Stainless	66252836362
4-1/2 x .020 x 5/8-11	20,000	5	Carbon	69936606275
4 x .020 x 5/8-11	20,000	5	Carbon	66252838300
4-1/2 x .020 x 5/8-11	20,000	6*	Carbon Pipeline	66252840466
4-1/2 x .020 x 5/8-11	20,000	6*	Carbon	69936653331
4-1/2 x .020 x 5/8-11	20,000	5	Stainless	69936653333
5 x .020 x 5/8-11	12,500	5	Carbon	66252833487
5 x .020 x 5/8-11	12,500	5	Stainless	66252833488
6 x .020 x 5/8-11	12,500	5	Carbon	69936653352
6 x .020 x 5/8-1/2	12,500	5	Carbon	69936653327

*BULK PACKED ITEMS



EXPANDED OFFERING

**BETTER STRINGER BEAD KNOT WIRE WHEEL BRUSHES**

DELIVER HIGH-IMPACT CUTTING AND CLEANING FOR TOUGHEST APPLICATIONS – FOR STEEL/STAINLESS

FEATURES

- Stringer bead wire for hard-to-reach areas
- NEW! Heavy-Duty brushes
- Joint/Crack cleaning wire wheel brushes

BENEFITS

- Specially suited for groove and weld bead, corners, and t-connections
- 1/3 more welding points which provide 50% more resistance to side load pressure
- 6-7/8" brushes have 76 knots vs. standard 56 knot brushes, resulting in 40% more cleaning action and up to 2X life, with similar life for the smaller versions of the heavy-duty brushes
- Used for brushing joints, cleaning cracks in concrete and asphalt, and preparing expansion joints for filling and scaling
- Pipeline: longest life for brushing/cleaning joints and preparing expansion joints for filling and scaling


DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
For Right Angle Grinders				
4 x .020 x 5/8-11	20,000	5	Carbon	69936606277
4 x .020 x 5/8-11	20,000	6*	Carbon	66252833489
4 x .020 x 5/8-11	20,000	10*	Carbon	66253370022
4 x .020 x 5/8-11	20,000	6*	Carbon Pipeline	66252840467
4 x .020 x 5/8-11	20,000	5	Stainless	69936606278
4 x .020 x 5/8-11	20,000	6*	Stainless Pipeline	66252842233
4 x .020 x 5/8-11/M14-20	20,000	5	Carbon	66252840889
4-1/2 x .020 x 5/8-11	20,000	6	Carbon Heavy-Duty	66252844886
4-1/2 x .020 x 5/8-11	20,000	6*	Carbon Pipeline	66252842299
5 x .020 x 5/8-11	12,500	10*	Carbon	66252833490
5 x .020 x 5/8-11	12,500	10*	Stainless	66252833491
6 x .020 x 5/8-11	12,500	10*	Carbon	69936653350
6 x .020 x 5/8-11	12,500	10	Carbon Heavy-Duty	66252844887
6 x .020 x 5/8-11	12,500	10*	Carbon Pipeline	66252840469
6 x .020 x 5/8-11	12,500	10	Stainless	69936653351
6-7/8 x .020 x 5/8-11	9,000	10*	Carbon	69936653329
6-7/8 x .020 x 5/8-11	9,000	10*	Carbon Heavy-Duty	66252843919
6-7/8 x .020 x 5/8-11	9,000	10*	Carbon Pipeline	66252840468
9 x .020 x 5/8-11	6,000	6	Carbon	66252837993

For Walk-Behind Machines – Joint/Crack Cleaning Brushes

12 x .035 x 1 - DP	4,500	2	Carbon	69936606280
--------------------	-------	---	--------	-------------

*BULK PACKED ITEMS





FEATURED PRODUCTS AND AVAILABILITY

**BETTER END BRUSHES**

CLEAN AND DEBURR A RECESSED AREA OR THE INSIDE DIAMETER OF A TUBE OR PIPE – FOR STEEL/STAINLESS

FEATURES

- Twist knot wire end brushes
- Crimped wire end brushes

BENEFITS

- For more aggressive cutting
- For lighter brushing action and contoured surfaces

DIAMETER x WIRE THICKNESS x MOUNT	MAX. RPM	STD. PKG.	APPLICATION	PART #
Stem Mounted Knotted				
3/4 x .020 x 1/4 Shank	20,000	10*	Carbon	69936653316
1 x .014 x 1/4 Shank	20,000	10*	Carbon	69936606279
1 x .020 x 1/4 Shank	20,000	10*	Carbon	69936653310
Stem Mounted Crimped				
3/4 x .006 x 1/4 Shank	20,000	10*	Stainless	69936606145
3/4 x .014 x 1/4 Shank	20,000	10*	Carbon	69936653317
1 x .020 x 1/4 Shank	20,000	10*	Carbon	69936653309

*BULK PACKED ITEMS

**BETTER HAND BRUSHES**

FOR STEEL/STAINLESS

FEATURES

- Plastic handle scratch brush
- Long handle and shoe handle brushes

BENEFITS

- Ergonomic handle
- Crimped wire for longer life
- Wires are wrapped up and around the metal post so they never come out
- Curved face for hard-to-reach places
- Narrow brush allows access into tight areas and slots
- Steel scratch brushes are made with a high-carbon, brass-coated steel; stainless steel is made with a 304L stainless

SIZE	STD. PKG.	APPLICATION	PART #
Scratch Brush 3 x 19 Long Handle	12	Carbon	66252833948
Scratch Brush 3 x 19 Long Handle	12	Stainless	66252833950
Scratch Brush 4 x 16 Shoe Handle	12	Carbon	66252833949
Scratch Brush 4 x 16 Shoe Handle	12	Stainless	66252833951
Scratch Brush Plastic Handle	24	Carbon	66252833954
Scratch Brush Plastic Handle	24	Stainless	66252833953
Inspection Brush 3 x 7	36	Stainless	66252833952

STAINLESS

STEEL/METAL



CATEGORY DEFINITION

A micro-fiber is a single fiber with a thickness less than a human hair that has been split 16 times and woven into various products. The surface area of a micro-fiber product is increased over 15 times, creating millions of spaces between the fibers which trap dirt, grime or liquids, making this product one of the most absorbent materials. These cloths save you labor, time, and additional costs of multiple cleaning products and chemicals.

APPLICATIONS: Cleaning Cloth: Used for general-purpose wet or dry applications. Works best when sprayed with a light water mist to deep clean.

Dry Tack Cloth: This woven terry cloth has a low profile to resist snagging and help pick up embedded debris.

Polishing Cloth: Streak-free cleaning of mirrors, optical lens and highly-polished items.

OTHER: Color-coded for easy identification
Cleaning Cloth: Blue
Dry Tack Cloth: Red
Polishing Cloth: Yellow



DESCRIPTION	COLOR	STD. PKG.	PART #
Micro-Fiber Cleaning Cloth			
16" x 16"	Blue	20	07660705300
Micro-Fiber Dry Tack Cloth			
16" x 16"	Red	20	07660704025
Micro-Fiber Polishing Cloth			
16" x 16"	Yellow	20	07660705301

TECH^{tip}

- Use these micro-fiber cloths dry for general cleaning
- To remove spills, stains or grime, lightly dampen the cloth for best results
- All micro-fiber cloths can be used with or without chemicals
- Micro-fiber cloths can be washed up to 300+ times without losing cleaning and trapping abilities
- Clean often for best results



It is the user's responsibility to refer to and comply with all safety regulations.





Norton Premium Tan High Heat Tape

- Designed for maximum performance and clean release on multiple surfaces
- These high quality masking tapes are ideal for conditions that include exposure to the high heat curing temperatures found in automobile, truck, bus and other transportation assembly operations, as well as aerospace manufacturing applications
- Can be baked up to 230°F and be exposed to wet sanding without adhesive transfer
- Conforms easily to contours and irregular surfaces
- No bleed-through or flaking upon removal
- Available in bulk, accordion-wrapped for protection and work site stocking

SIZE (W x L)	STD. PKG.	PART #
Norton Premium Tan High Heat Tape		
18mm x 54.8m (3/4" x 60 yards)	48	63642506183
36mm x 54.8m (1-1/2" x 60 yards)	24	63642506184
48mm x 54.8m (2" x 60 yards)	24	63642506185

PACKED IN SLEEVES, WITH 4 SLEEVES TO A CASE



Norton Pro Contractor Grade Tape

- A general-purpose masking tape that offers both economy and versatility for a variety of materials and applications
- Norton Pro Contractor Grade masking tape provides a clean release up to 3 days
- Use for general paint masking, hanging protective plastic, holding drop cloths in place and other general-purpose masking, bundling, and sealing jobs where the tape will be removed when the job is complete
- Not intended for critical paint applications
- Limit exposure to UV light for extended periods
- Extended exposure to UV light could result in difficult removal from the surface

SIZE (W x L)	STD. PKG.	PART #
Norton Pro Contractor Grade Tape		
18mm x 54.8m (3/4" x 60 yards)	48	07660721944
36mm x 54.8m (1-1/2" x 60 yards)	24	07660721946
48mm x 54.8m (2" x 60 yards)	24	07660721947

BULK PACKED AS INDIVIDUAL ROLLS



Norton Blue Core 14-Day Tape

- Our premium paint masking tape has a specially formulated adhesive system that provides optimum low- to medium-tack adhesion and clean removal from a variety of surfaces, for up to 14 days
- Norton Blue Core masking tape can be used indoors or out
- The crepe paper backing is designed to enable easy unrolling and to minimize slivering
- It delivers very sharp, clean edges on smooth- to moderately-textured surfaces

SIZE (W x L)	STD. PKG.	PART #
Norton Blue Core 14 Day Tape		
18mm x 54.8m (3/4" x 60 yards)	48	07660721952
24mm x 54.8m (1" x 60 yards)	36	07660721953
36mm x 54.8m (1-1/2" x 60 yards)	24	07660721954
48mm x 54.8m (2" x 60 yards)	24	07660721955

BULK PACKED AS INDIVIDUAL ROLLS

Safety Icons

Watch for and obey these safety icons.



WARNING

This warning icon appears on our products and packaging. It is intended to draw your attention to the specific safety warning practices outlined after it.



SPEEDS



FACE PROTECTION




WHEEL GUARD



SAFETY GLOVES



HEARING PROTECTION



FLANGES



SAFETY GUIDES



DUST PROTECTION

Safe Operating Practices

Safe operating practices must be part of every grinding wheel user's operation. The greatest efficiency and lowest overall abrasive cost can be realized only if proven care and use techniques become standard practice.

- Be sure to read any safety material/guidelines provided with the abrasive product.
- Always check the wheel for cracks or damage before use.
- Always properly maintain your machine; especially governors on pneumatic machines and linkage on floorstand machines.
- Never use the incorrect air, hydraulic or electric power supply.
- Never mount grinding wheels directly on electric motors.
- Never mount grinding wheels on the wrong size machine for the grinding wheel.
- Before mounting the wheel, use a tachometer to measure the spindle speed.
- Ensure the mounting flanges, backplate or adapter supplied by the machine manufacturer are used and kept in good condition. ANSI Safety Requirement B7.1 provides wheel mounting requirements. Check mounting flanges for equal and correct diameter and use blotters when supplied.
- Always mount, true and dress the wheel in conformance with the guidelines published in the ANSI Safety Requirements B7.1.
- Ensure the correct wheel guard is in place before starting the wheel. Allow the wheel to come up to full operating speed before starting to grind for a minimum of one minute, and stand out of the plane of rotation.
- NEVER use a high speed air sander as a portable grinder.
- NEVER use grinding wheel with a rated speed less than that of the grinder.

- NEVER exceed the maximum operating speed marked on the wheel being used. The following formula may be used to calculate wheel speed:
 $SFPM = \text{Spindle Speed in RPM} \times \text{Wheel Dia. in inches} \times .262$
- Avoid dropping or bumping the wheel.
- When not using the wheel, store the wheel in its original packing materials. This protects the wheel from chips and cracking, as well as provides easy identification of the wheel.

For more information on product safety, ask your Norton distributor for these publications:

- "Primer on Grinding Wheel Safety" (form 474) (available on www.nortonabrasives.com)
- Portable Grinding Safety (form 1406)
- ANSI B7.1 "Safety Requirements for the Use, Care and Protection of Abrasive Wheels"
- ANSI B7.7 "Safety Requirements for Abrading Materials with Coated Abrasive Systems"
- OSHA and literature provided by the grinding wheel and machine manufacturer
- Material Safety Data Sheets (available on www.nortonabrasives.com)
- Other applicable regulations
- Or contact the Saint-Gobain Product Safety Department at telephone 508-795-2317, fax 508-795-5120, or your Norton representative



A DEADLY EQUATION

Pistol Grip Air Sander + Grinding Wheel = Certain Injury!

- Never use a high speed air sander as a portable grinder
- Use only sanding discs specifically designed for sanders
- Because the speed of these sanders far exceeds the maximum rated speeds for grinding wheels, a potentially lethal wheel breakage may occur

Breakages/Personal Injury

In the event of on-machine breakage of Norton abrasive products, call your local Norton distributor immediately. Whether involving personal injury or not, the abrasive user should leave the equipment and other evidence undisturbed until a Norton sales representative has been notified and conducts an investigation. Prompt action on the part of abrasive users, distributor, and Norton sales personnel is important to ensure swift determination of the breakage cause and to guard against recurrence.



Conversion Table – Wheel Speeds

REVOLUTIONS PER MINUTE FOR VARIOUS DIAMETERS OF GRINDING WHEELS TO GIVE SURFACE SPEED IN FEET PER MINUTE AS INDICATED
(FOR WHEEL MARKING PURPOSES THE CALCULATED RPM FIGURES LISTED BELOW ARE ROUNDED OFF TO THE NEXT 5)

Diameter of Wheel in Inches	Surface Speed in Feet Per Minute (SFPM)															
	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500	9,000	9,500	10,000	12,000	12,500	14,200
	Revolutions Per Minute (RPM)															
1	15,279	17,189	19,098	21,008	22,918	24,828	26,737	28,647	30,558	32,467	34,377	36,287	38,196	45,836	47,745	54,240
2	7,639	8,594	9,549	10,504	11,459	12,414	13,368	14,328	15,278	16,238	17,188	18,143	19,098	22,918	23,875	27,120
3	5,083	5,729	6,366	7,003	7,639	8,276	8,913	9,549	10,186	10,822	11,459	12,096	12,732	15,278	15,915	18,080
4	3,820	4,297	4,775	5,252	5,729	6,207	6,685	7,162	7,640	8,116	8,595	9,072	9,549	11,459	11,940	13,560
5	3,056	3,438	3,820	4,202	4,584	4,966	5,348	5,730	6,112	6,494	6,876	7,258	7,640	9,168	9,550	10,850
6	2,546	2,865	3,183	3,501	3,820	4,138	4,456	4,775	5,092	5,411	5,729	6,048	6,366	7,639	7,960	9,040
7	2,183	2,455	2,728	3,001	3,274	3,547	3,820	4,092	4,366	4,638	4,911	5,183	5,456	6,548	6,820	7,750
8	1,910	2,148	2,387	2,626	2,865	3,103	3,342	3,580	3,820	4,058	4,297	4,535	4,775	5,729	5,970	6,780
9	1,698	1,910	2,122	2,334	2,546	2,758	2,970	3,182	3,396	3,606	3,820	4,032	4,244	5,092	5,305	6,030
10	1,528	1,719	1,910	2,101	2,292	2,483	2,674	2,865	3,056	3,247	3,438	3,629	3,820	4,584	4,775	5,425
12	1,273	1,432	1,591	1,751	1,910	2,069	2,228	2,386	2,546	2,705	2,864	3,023	3,183	3,820	3,980	4,520
14	1,091	1,228	1,364	1,500	1,637	1,773	1,910	2,046	2,182	2,319	2,455	2,592	2,728	3,274	3,410	3,875
16	955	1,074	1,194	1,313	1,432	1,552	1,672	1,791	1,910	2,029	2,149	2,268	2,387	2,865	2,985	3,390
18	849	955	1,061	1,167	1,273	1,379	1,485	1,591	1,698	1,803	1,910	2,016	2,122	2,546	2,655	3,015
20	764	859	955	1,050	1,146	1,241	1,337	1,432	1,528	1,623	1,719	1,814	1,910	2,292	2,390	2,715
22	694	781	868	955	1,042	1,128	1,215	1,302	1,388	1,476	1,562	1,649	1,736	2,084	2,170	2,465
24	637	716	796	875	955	1,034	1,115	1,194	1,274	1,353	1,433	1,512	1,591	1,910	1,990	2,260
26	588	661	734	808	881	955	1,028	1,101	1,176	1,248	1,322	1,395	1,468	1,762	1,840	2,090
28	546	614	682	750	818	887	955	1,023	1,092	1,159	1,228	1,296	1,364	1,637	1,705	1,940
30	509	573	637	700	764	828	891	955	1,018	1,082	1,146	1,210	1,274	1,528	1,595	1,810
32	477	537	597	656	716	776	836	895	954	1,014	1,074	1,134	1,194	1,432	1,495	1,695
34	449	505	562	618	674	730	786	843	898	955	1,011	1,067	1,124	1,348	1,405	1,595
36	424	477	530	583	637	690	742	795	848	902	954	1,007	1,061	1,273	1,330	1,510
38	402	452	503	553	603	653	704	754	804	854	904	955	1,006	1,206	1,260	1,430
40	382	430	478	525	573	620	669	716	764	812	860	908	956	1,146	1,195	1,355
42	366	409	454	500	545	591	636	682	732	775	818	863	908	1,090	1,140	1,295
44	347	390	434	478	521	564	608	651	694	737	780	824	868	1,042	1,085	1,235
46	333	375	416	458	500	541	582	624	666	708	750	791	832	1,000	1,040	1,180
48	318	358	398	438	478	517	558	597	636	676	716	756	796	956	995	1,130
53	288	324	360	395	432	468	503	539	576	612	648	683	720	864	900	1,025
60	255	287	319	350	387	414	446	478	510	542	574	606	638	774	795	905
72	212	239	265	291	318	345	371	398	424	451	477	504	530	637	665	755

For intermediate diameters not listed use the formula listed in Section 1.2.10 of ANSI B7.1 (SFPM = .262 x wheel diameter in inches x RPM.)
To convert meters per second (m/s) to SFPM: m/s x 196.85 = SFPM. To convert SFPM to m/s: SFPM/196.85 = m/s. To convert RPM to SFPM: Wheel Diameter x RPM x 0.262 = SFPM

Product Warranty

WARRANTY – Norton warrants the products in this catalog to be free from defects in material or workmanship for a period of one year from the date of purchase. Norton's sole obligation under this warranty shall be to repair or replace, at Norton's option, any product which is non-conforming provided any such product failure was not caused by a subsequent modification of the product, misuse or a failure to follow any applicable instructions for the product.

EXCEPT FOR THE FOREGOING, NORTON EXPRESSLY DISCLAIMS ALL OTHER GUARANTIES AND/OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Product Quality Complaints

All product quality complaints should be submitted to your local Norton Distributor.

Liability Limitation

NORTON'S LIABILITY FOR ANY LOSS OR DAMAGE ARISING OUT OF OR RESULTING FROM THE USE OF THE PRODUCT SHALL NOT EXCEED THE PURCHASE PRICE THEREOF, REGARDLESS OF WHETHER SUCH LIABILITY ARISES IN CONTRACT, TORT (INCLUDING WITHOUT LIMITATION NEGLIGENCE OR STRICT LIABILITY), OR OTHERWISE, AND IN NO EVENT SHALL NORTON BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY KIND. NO REPRESENTATIVE OF NORTON, NOR ANY OF NORTON'S DISTRIBUTORS OR DEALERS, IS AUTHORIZED TO MODIFY THIS WARRANTY OR ISSUE ANY WARRANTY REGARDING THE PRODUCTS IN THIS CATALOG.

Trademarks

All trademarks used in these pages are trademarks of Saint-Gobain Abrasives unless otherwise indicated.

3X™	Fantastic Tool™	NORaX®	Rapid Prep™
A275 Original Performance™	Fast Cut™	Norbide®	Rapid Strip™
Abrasive Connection Expressx®	FastEco™	NorKut™	Red Heat®
Abrasotex™	FastTrack™	NorGrip®	Rescue Runner™
Adalox®	FlexDrum™	NorLok™	Reshaping Your World™
Alundum®	FlexEdge™	NorPor®	RightCut™
Aero-Jet™	Foundry X™	Norton®	SAABA™
Amplex®	Free Cut®	Norton Clipper™	Sand-O-Flex™
AVOS®	Furioso™	Norton Design® (Parallelogram)	SandWet™
Aztec®	Gemini®	Norton Design® (Triple Stripe Design)	Screen-Bak®
Aztec li®	G-Force™	Norton Ice™	ShurStik™
Bear-Tex®	Green Flipper™	Norton Quantum™	Silver Eagle®
Black Ice®	Greenlyte™	Norton Quantum X™	SoftTouch®
Blaze®	Grind-O-Flex™	Norton SG®	Speed Change™
Blue-Bak™	India®	NorZon®	Speed-Lok®
Blue-Core™	JobPack™	NorZon BlueFire®	Stick & Sand®
BlueFire®	Lightning®	NorZon Plus®	Targa®
BlueFire 20X™	Liquid Ice®	Onyx™	The Absolute Force™
BZX®	Long Life™	Openkote™	The See-Thru System™
Charger™	Merit®	Pacester™	Thin Flex™
Clean Bond®	Metalite®	Paradigm®	TufBak®
Clear Choice™	Mini-Dex™	Plyweld®	U-Dex-It™
Clear Creek™	MSL®	PowerFlex®	Univel®
CloseKote®	Multi-Air®	PowerLock®	USB™
Crystolon®	Multi-Air Cyclonic®	PowerStrip™	Vitrium ³ ®
DiaLast™	Multi-Air® Plus™	Pure Ice™	Vortex®
Dry Ice®	Multi-Oilstone®	PureSand®	Winter®
Duo®	MultiSand™	Quadro-Fit Pro™	WoodSand™
Durite®	The Muscle Behind The Machine®	QuadroFlex™	ZF®
Edger™	Nanozyte™	Rail Cut™	ZS®
Elgin™	Neon®	Rapid Blend™	ZX®
EZ Choice®	NEX™	Rapid Cut™	and others
E-Z Flex®	No-Fil®	Rapid Finish™	
FabCut™			

GET ACCESS TO THE INDUSTRY'S BEST SELECTION OF ABRASIVE SOLUTIONS!

Inside Sales

FOR INFORMATION, contact our inside sales team:

- Product application information/technical assistance
- Competitive product conversions
- Product availability, pricing and delivery information
- Request for on-site "no-risk" product test

PHONE: **800-962-9379** FAX: **508-795-5950**



Norton | Saint-Gobain is so confident of the superior performance of our abrasive products, as recommended for specific applications, that we invite in-plant tests against any other brand of abrasive product on the market.

- 1 The test will be conducted in the user's own plant, on their own machines, using their own workpieces
- 2 Even if the user purchases only a minimum quantity of Norton abrasive products, the user will receive the same quantity discount as would apply to their normal production orders
- 3 If the Norton product tested proves completely unsatisfactory, the user will receive a full refund
- 4 If the Norton product tested performs at a lower level than the product presently in production, the user will receive an adjustment to make up the difference in performance
- 5 The user is the final judge of performance!

Customer Service

TO PLACE AN ORDER, contact our customer service support center with:

- Customer number and contact name
- Any special shipping needs
- Complete product information:
 - 11-digit Part Number
 - Product description
 - Quantity and unit of measure
 - Price by unit of measure

To ensure minimal errors and faster turnaround, using electronic media is preferred. For assistance with www.abrasiveconnection.com or EDI setup, contact us at:

Email: abrasive.connection@saint-gobain.com

Phone: **888-383-2236**

EMAIL: nacustomerservice@saint-gobain.com

U.S. PHONE: **800-551-4413** FAX: **800-551-4416**

CDN. PHONE: **800-263-6565** FAX: **800-561-9490**



Online

This printed catalog is a great starting resource for Norton and Merit product selection. Our website is the ideal resource for a more comprehensive outline of product and application information. It is continually updated with all our most current information and offers more electronic queries for deeper detail, at a click of a button.

www.nortonabrasives.com



RESHAPING THE WORLD FOR METAL FAB MARKETS

For nearly 130 years, Norton products have delivered industry-leading abrasive solutions to consistently improve part quality finish and enhance production capabilities. The Norton brand has you covered for consistent-performing products that offer the highest productivity in the industry while reducing the overall total cost of doing business. **Call, click, or visit us online to learn how.**



The Right Choice Every Time

Our re-engineered Norton Gemini RightCut 100% aluminum oxide wheels provide thinner, faster cutting with a burr-free, precision cut and improved operator comfort.



Corner Store Convenience

Look for the "V" throughout the catalog for the industry's best selection of vendible abrasive solutions: wheels, discs, belts, mounted points, and more.



It's Time to Clear the Air

The precision laser-cut, spiral-hole design of Norton Multi-Air Cyclonic ceramic paper discs maximize dust extraction for a superior surface finish and cleaner work environment.



Power Up Affordable Versatility

The proprietary grain technology and improved resin bond in our Norton Neon products deliver up to 3X the life and cut rate at an economical initial price.



Prep for the Future

Cleaning and surface conditioning Norton Rapid Prep products deliver higher material removal, longer life and consistent, smear-free finishes - even on high nickel content alloys



Professionals Want Choices

Norton NorZon Plus is the highest performance line in the industry. Invented and made in America: fastest cutting (FastCut), lowest total cost (All Purpose), and longest lasting (Long Life).

BEST

Highest Productivity - Lowest Total Cost

BETTER

Excellent Blend of Performance and Price

GOOD

Consistent Performance - Low Initial Price

www.facebook.com/NortonIndustrial | www.youtube.com/NortonIndustrial | www.nortonindustrial.com

USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 551-4413
Toll Free Fax: 1 (800) 551-4416

CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565
Toll Free Fax: 1 (800) 561-9490

FORM #7364 REV. 01/15

© Saint-Gobain January 2015.
Norton is a registered trademark of Saint-Gobain.

