



THE PERFECT SHOP

A product guide
for an efficient, reliable
and safe compressed
air system



PREVOST...
your best source
for premium products
for distributing and treating
compressed air!

Connection contents

PUSH BUTTON QUICK COUPLINGS

→ SAFETY Push button couplings

The coupling that puts safety first

- Venting-action eliminates dangerous «Hose-whip»
- One-hand connection is easy to operate
- Leak-free design reduces energy costs



→ REGULAR push button couplings

The «original» push button coupling

- Light-weight, composite body is non-marring
- One-hand connection is easy to operate
- Impact-resistant design handles tough applications
- Leak-free design reduces energy costs



INTERCHANGE		SAFETY COUPLING PREVO S1			REGULAR COUPLINGS	
INDUSTRIAL INTERCHANGE 1/4", 3/8", 1/2"						
AUTOMOTIVE INTERCHANGE 1/4", 3/8"						
HIGH FLOW INTERCHANGE 3/8", 1/2"						
ARO 210 INTERCHANGE 1/4"						

BLOW GUNS 27202

High performance blow guns for compressed air

- Sturdy construction
- Light weight
- Full pressure performance with variable flow
- Ergonomic design
- Available in OSHA compliant styles



BLOW GUNS PREVO S1

Compact compressed-air blowguns with integrated plug

Users will appreciate the prevo S1 blowguns in their daily operation, for their ease of use.

These blowguns, equipped with PREVOST plugs, are compatible with all major connection profile standards.

The plugs couple directly to the prevo S1 quick safety coupling, which also optimizes the blowguns ergonomics (excellent handling).



Distribution & Treatment contents


PREVOST PIPING SYSTEM

Pipes are held in the fitting using a new system: the « PPS Grip Concept ». The PPS Grip Concept is based on a stainless steel ring with teeth that penetrate the aluminum. Leak tight is achieved via a new contoured and lubricated seal, with optimised design and properties. The seal remains perfectly leaktight even under the harshest conditions.

- **Maximum Working Pressure:** 232 psi
- **Vacuum level:** 0.59 inHg
- **Temperature range:** -4°F to 176°F
- **Body and nut:** 100% aluminum, EN AB 46100
- **PPS Grip Concept:** fastening system using teeth



HOSE REELS




Streamline your workstations

- More efficient work stations
- Automatic hose locking system
- Keep work area safe and neat
- No more cut or broken hoses

SPIRAL HOSES PUS

Flexible and durable polyurethane spiral hose



- Excellent shape memory and extra-long service life
- Very flexible and resists kinking
- Abrasion resistant
- Rotating connector on operator end prevents twisting

AIR HOSES



Flexair

- Hybrid polymer extension hoses, with high flexibility
- Equipped with pressed metal sleeves, non-scratch sheath and quick coupling Prevo S1

Airca automotive hose

- Ideal for automotive applications
- Heavy duty and highly durable hose



Stoflex non-static hose

- Ideal for painting applications
- Very light and flexible, high resistance to oil

AIR TREATMENT UNITS

ALTO

- **Air quality** Preservation and lubrication of pneumatic tools
- **Heavy duty** Sturdy construction. Aluminium alloy body
- **Modular construction** Fast easy installation and maintenance
- **User friendly** «Push to lock» adjusting knob for setting pressure



CYCLONE SEPARATORS - SPC

Specially designed for the efficient separation and elimination of the largest solid particles as well as water droplets in compressed air.



The **prevoS1** range

SAFETY PUSH BUTTON COUPLINGS

- ➔ **Body** : Composite polyester material
- ➔ **Other components** : steel with RoHS* compliant anti-corrosion treatment, or aluminium
- ➔ **Seal** : NBR O-ring for thread seal

PRESSURE AND TEMPERATURES

- ➔ **Service pressure range** : 30 to 175 psi (not suitable for vacuum)
- ➔ **Temperature** : 5°F to 155°F

CONSTRUCTION STANDARDS

- ➔ **Prevo S1 couplings comply with :**
 - the European Pressure Equipment Directive (PED) 97/23/CE
 - the safety requirements of the ISO 4414 standard
 - the European RoHS* directive 2002/95/CE
 - ATE X 2



* Directive RoHS 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE)).

ADVANTAGES EXCLUSIVE TO THE **PREVO S1** COMPOSITE BODY

➔ Ultra-lightweight

2.6 OZ for couplings with 6 mm clearance (hose outlet)
4 OZ for couplings with 8 mm clearance (hose outlet)

➔ Non-scratch

No damage to vulnerable surfaces

➔ Anti-static

Electrically conducting, thus avoiding problems relating to static electricity (e.g. dust attracted to the paint/polish/electronic work surface). - ATE X 2

➔ Ease of coupling

< 80 N at 6 bar for couplings with 6 mm
< 100 N at 6 bar for couplings with 7.2
Unit of measurement N = Newton

➔ Applications


- All connections with or without safety mechanism
- Assembly lines (automotive, household appliances, etc.)
- Mechanical manufacturing, machining workshops
- Paper and printing industries
- Automotive repairs
- Textile industries
- Wood and plastics industries
- Any work involving vulnerable environments or products
- Technical education

For more details : www.prevostusa.com


SAFETY QUICK COUPLING - 1/4" INDUSTRIAL INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ISI 061201
	3/8" FNPT	ISI 061202
	1/2" FNPT	ISI 061203


Tapered male thread coupler

	NPT male thread	Part number
	1/4" MNPT	ISI 061251
	3/8" MNPT	ISI 061252
	1/2" MNPT	ISI 061253


Hose stem coupler

	For hose ID	Part number
	1/4" Hose Barb	ISI 061806
	3/8" Hose Barb	ISI 061810

Threaded swivel coupler


	NPT female thread	Part number
	3/8" FNPT	ISI 061202SW
	Tapped swivel coupler 360° rotation in 2 axes	

Female threaded double wall manifold - 2 couplings and drain - 1/4" Industrial Interchange

	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	ISI 06	ISI 068203WK
	3/4" FNPT	ISI 06	ISI 068204WK

PLUG 1/4" INDUSTRIAL INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	IRP 066201
	3/8" FNPT	IRP 066202

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	IRP 066251
	3/8" MNPT	IRP 066252
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	1/4" Hose Barb	IRP 066806
	3/8" Hose Barb	IRP 066810


SAFETY QUICK COUPLING - 3/8" INDUSTRIAL INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ISI 081201
	3/8" FNPT	ISI 081202
	1/2" FNPT	ISI 081203


Tapered male thread coupler

	NPT male thread	Part number
	1/4" MNPT	ISI 081251
	3/8" MNPT	ISI 081252
	1/2" MNPT	ISI 081253


Hose stem coupler

	For hose ID	Part number
	1/4" Hose Barb	ISI 081810
	3/8" Hose Barb	ISI 081813

Threaded swivel coupler


	NPT female thread	Part number
	3/8" FNPT	ISI 081202SW
	Tapped swivel coupler 360° rotation in 2 axes	

Female threaded double wall manifold - 2 couplings and drain - 1/4" Industrial Interchange

	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	ISI 06	ISI 088203WK
	3/4" FNPT	ISI 06	ISI 088204WK

PLUG 3/8" INDUSTRIAL INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	IRP 086201
	3/8" FNPT	IRP 086202
	1/2" FNPT	IRP 086203

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	IRP 086251
	3/8" MNPT	IRP 086252
	1/2" MNPT	IRP 086253
Teflon-coated thread		


Hose stem plug

	For hose ID	Part number
	3/8" Hose Barb	IRP 086810
	1/2" Hose Barb	IRP 086813
	5/8" Hose Barb	IRP 086816


SAFETY QUICK COUPLING - 1/2" INDUSTRIAL INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	3/8" FNPT	ISI 111202
	1/2" FNPT	ISI 111203
	3/4" FNPT	ISI 111204


Tapered male thread coupler

	NPT male thread	Part number
	3/8" MNPT	ISI 111252
	1/2" MNPT	ISI 111253
	3/4" MNPT	ISI 111254

Hose stem coupler


	For hose ID	Part number
	3/8" Hose Barb	ISI 111810
	1/2" Hose Barb	ISI 111813
	5/8" Hose Barb	ISI 111816
	3/4" Hose Barb	ISI 111819

Female threaded double wall manifold - 2 couplings and drain - 1/2" Industrial Interchange


	Inlet NPT female thread	Outlet: 2 couplings	Part number
	3/4" FNPT	ISI 11	ISI 118204WK

PLUG 1/2" INDUSTRIAL INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	3/8" FNPT	IRP 116202
	1/2" FNPT	IRP 116203
	3/4" FNPT	IRP 116204

Tapered male threaded plug

	NPT male thread	Part number
	3/8" MNPT	IRP 116252
	1/2" MNPT	IRP 116253
	3/4" MNPT	IRP 116254
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	3/8" Hose Barb	IRP 116810
	1/2" Hose Barb	IRP 116813
	5/8" Hose Barb	IRP 116816
	3/4" Hose Barb	IRP 116819


SAFETY QUICK COUPLING - 1/4" AUTOMOTIVE INTERCHANGE




Parallel Female threaded coupler

	NPT female thread	Part number
	1/4" FNPT	USI 061201
	3/8" FNPT	USI 061202
	1/2" FNPT	USI 061203

Male threaded coupler

	NPT male thread	Part number
	1/4" MNPT	USI 061251
	3/8" MNPT	USI 061252
	1/2" MNPT	USI 061253


Hose stem coupler

	For hose ID	Part number
	1/2" Hose Barb	USI 061808
	3/8" Hose Barb	USI 061810

Threaded swivel coupler


	NPT female thread	Part number
	3/8" FNPT	USI 081202SW
	360° rotation in 2 axes	

Female threaded double wall manifold - 2 couplings and drain - 3/8" Automotive interchange


	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	USI 08	USI 068203WK
	3/4" FNPT	USI 08	USI 068204WK

PLUG 3/8" AUTOMOTIVE INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	URP 086201
	3/8" FNPT	URP 086202
	1/2" FNPT	URP 086203

Tapered male threaded plug

	NPT male thread	Part number
	1/4" MNPT	URP 086251
	3/8" MNPT	URP 086252
	1/2" MNPT	URP 086253
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	3/8" Hose Barb	URP 086810
	1/2" Hose Barb	URP 086813


SAFETY QUICK COUPLING - 3/8" AUTOMOTIVE INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	USI 081201
	3/8" FNPT	USI 081202
	1/2" FNPT	USI 081203

Tapered male threaded coupler

	NPT male thread	Part number
	1/4" MNPT	USI 081251
	3/8" MNPT	USI 081252
	1/2" MNPT	USI 081253


Hose stem coupler

	For hose ID	Part number
	1/2" Hose Barb	USI 081813

Threaded swivel coupler


	NPT female thread	Part number
	3/8" FNPT	USI 081202SW
	360° rotation in 2 axes	

Female threaded double wall manifold - 2 couplings and drain - 3/8" Automotive interchange

	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	USI 08	USI 088203WK
	3/4" FNPT	USI 08	USI 088204WK

PLUG 3/8" AUTOMOTIVE INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	URP 086201
	3/8" FNPT	URP 086202
	1/2" FNPT	URP 086203

Tapered male threaded plug

	NPT male thread	Part number
	1/4" MNPT	URP 086251
	3/8" MNPT	URP 086252
	1/2" MNPT	URP 086253
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	3/8" Hose Barb	URP 086810
	1/2" Hose Barb	URP 086813


SAFETY QUICK COUPLING - 1/2" AUTOMOTIVE INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	3/8" FNPT	USI 111202
	1/2" FNPT	USI 111203
	3/4" FNPT	USI 111204


Tapered male threaded coupler

	NPT male thread	Part number
	3/8" MNPT	USI 111252
	1/2" MNPT	USI 111253
	3/4" MNPT	USI 111254

Hose stem coupler


	For hose ID	Part number
	3/8" Hose Barb	USI 111810
	1/2" Hose Barb	USI 111813
	3/4" Hose Barb	USI 111819

Female threaded double wall manifold - 2 couplings and drain - 1/2" Automotive interchange


	Inlet NPT female thread	Outlet: 2 couplings	Part number
	3/4" FNPT	USI 11	USI 118204WK

PLUG 1/2" AUTOMOTIVE INTERCHANGE

Tapered female thread plug

	NPT female thread	Part number
	3/8" FNPT	URP 116202
	1/2" FNPT	URP 116203
	3/4" FNPT	URP 116204


Tapered male threaded plug

	NPT male thread	Part number
	3/8" MNPT	URP 116252
	1/2" MNPT	URP 116253
	3/4" MNPT	URP 116254
	Teflon-coated thread	


SAFETY QUICK COUPLING 3/8" - HIGH FLOW INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ESI 071201
	3/8" FNPT	ESI 071202

Tapered male thread coupler

	NPT male thread	Part number
	1/4" MNPT	ESI 071251
	3/8" MNPT	ESI 071252
	1/2" MNPT	ESI 071253


Hose stem coupler

	For hose ID	Part number
	1/4" Hose Barb	ESI 071806
	3/8" Hose Barb	ESI 071810
	1/2" Hose Barb	ESI 071813

Threaded swivel coupler


	NPT female thread	Part number
	1/4" FNPT	ESI 071201SW
	360° rotation in 2 axes	

Female threaded double wall manifold - 2 couplings and drain - 3/8" High Flow Interchange


	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	ESI 07	ESI 078203WK
	3/4" FNPT	ESI 07	ESI 078204WK

PLUG 3/8" HIGH FLOW INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	ERP 076201
	3/8" FNPT	ERP 076202

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	ERP 076251
	3/8" MNPT	ERP 076252
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	1/4" Hose Barb	ERP 076806
	3/8" Hose Barb	ERP 076810
	1/2" Hose Barb	ERP 076813


SAFETY QUICK COUPLING - 1/2" HIGH FLOW INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	3/8" FNPT	ESI 111202CB
	1/2" FNPT	ESI 111203CB

Tapered male thread coupler

	NPT male thread	Part number
	3/8" MNPT	ESI 111252CB
	1/2" MNPT	ESI 111253CB


Hose stem coupler

	For hose ID	Part number
	3/8" Hose Barb	ESI 111810CB
	1/2" Hose Barb	ESI 111813CB
	5/8" Hose Barb	ESI 111816CB
	3/4" Hose Barb	ESI 111819CB


SAFETY QUICK COUPLING - 1/2" HIGH FLOW INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	3/8" FNPT	ESI 111202
	1/2" FNPT	ESI 111203
	3/4" FNPT	ESI 111204

Tapered male thread coupler


	NPT male thread	Part number
	3/8" MNPT	ESI 111252
	1/2" MNPT	ESI 111253
	3/4" MNPT	ESI 111254

Hose stem coupler


	For hose ID	Part number
	3/8" Hose Barb	ESI 111810
	1/2" Hose Barb	ESI 111813
	5/8" Hose Barb	ESI 111816
	3/4" Hose Barb	ESI 111819

PLUG 1/2" HIGH FLOW INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	3/8" FNPT	ERP 116202
	1/2" FNPT	ERP 116203
	3/4" FNPT	ERP 116204

Tapered male thread plug

	NPT male thread	Part number
	3/8" MNPT	ERP 116252
	1/2" MNPT	ERP 116253
	3/4" MNPT	ERP 116254
	Teflon-coated thread	


Hose stem plug

	For hose ID	Part number
	3/8" Hose Barb	ERP 116810
	1/2" Hose barb	ERP 116813
	5/8" Hose Barb	ERP 116816
	3/4" Hose Barb	ERP 116819


SAFETY QUICK COUPLING - 1/4" ARO 210 INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ASI 061201
	3/8" FNPT	ASI 061202
	1/2" FNPT	ASI 061203


Tapered male thread coupler

	NPT male thread	Part number
	1/4" MNPT	ASI 061251
	3/8" MNPT	ASI 061252
	1/2" MNPT	ASI 061253

Hose stem coupler


	For hose ID	Part number
	1/4" Hose Barb	ASI 061806
	3/8" Hose Barb	ASI 061810
	1/2" Hose Barb	ASI 061813

Female threaded double wall manifold - 2 couplings and drain - 1/4" ARO 210 Interchange


	Inlet NPT female thread	Outlet: 2 couplings	Part number
	1/2" FNPT	ASI 06	ASI 068203WK
	3/4" FNPT	ASI 06	ASI 068204WK

PLUG 1/4" ARO 210 INTERCHANGE


Tapered female thread plug

	NPT female thread	Part number
	1/4" FNPT	ARP 066201
	3/8" FNPT	ARP 066202

Tapered male thread plug

	NPT male thread	Part number
	1/4" FNPT	ARP 066251
	3/8" FNPT	ARP 066252
	Thread : Teflon-coated	

Hose stem plug

	For hose ID	Part number
	1/4" Hose Barb	ARP 066806
	3/8" Hose Barb	ARP 066810

Regular push button **PROLAC**



Prolac couplings are connected simply by pushing the adaptor into the coupling and disconnected instantaneously by pressing the button. Pushing a button to disconnect and cut off the supply is an intuitive action. A straightforward thumb movement makes Prolac couplings comfortable to work with.

COMPACT, LIGHTWEIGHT AND SCRATCH-RESISTANT

➔ Compact

Single-piece composite construction. The perfectly cylindrical single piece construction enables use in all work environments. No parts overhang outside the coupling, avoiding snagging and accidental disconnection. The air circuit opens when the adaptor is in place.

➔ Light

The IRC 06 couplings are designed to allow users ease of movement. Their lightweight and compact construction optimises efficiency and ease of use.

➔ Non-scratch coupling

Their resin body avoids scratching bodywork.

PROXI STAINLESS STEEL COUPLINGS

External construction : composite material compatible with corrosive atmospheres*

Internal construction : high resistance stainless steel*

- Plug: 316 L stainless steel

Fluids carried:

- Compressed air in corrosive atmosphere
- Cold water, hot water up to 140°F
- Inert gases from 5°F to 140°F



SIMPLICITY AND RELIABILITY OF CONNECTION AND DISCONNECTION

➔ When using a quick coupling with a Prevost adaptor, a perfect seal is guaranteed in three areas:


- Adaptor to O-ring
- Valve seal held in place on seat
- Solid seal in check chamber

SWIVEL OPTION

The 360° free rotation ensures easy tool handling.

The swivel fitting eliminates all constraints on the hose (uncontrolled coiling and twisting).

Paint spray guns, pneumatic tools and precision work are all facilitated.



For more details : www.prevostusa.com

REGULAR QUICK COUPLING 1/4" INDUSTRIAL INTERCHANGE




Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	IRC 061201

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	IRP 066251
	3/8" MNPT	IRP 066252
	Teflon-coated thread	

REGULAR QUICK COUPLING - 3/8" INDUSTRIAL INTERCHANGE



Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	IRC 081201
	3/8" FNPT	IRC 081202
	1/2" FNPT	IRC 081203

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	IRP 086251
	3/8" MNPT	IRP 086252
	Teflon-coated thread	

REGULAR QUICK COUPLING HIGH FLOW INTERCHANGE



Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ERC 071201

Tapered male thread plug

	NPT male thread	Part number
	1/4" MNPT	ERP 076251
	3/8" MNPT	ERP 076252
	Teflon-coated thread	

REGULAR QUICK COUPLING - 1/4" AUTOMOTIVE INTERCHANGE



Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	URC 061201

Tapered male threaded plug

	NPT male thread	Part number
	1/4" MNPT	URP 066251
	3/8" MNPT	URP 066252
	Teflon-coated thread	

REGULAR QUICK COUPLING - 3/8" AUTOMOTIVE INTERCHANGE



Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	URC 081201
	3/8" FNPT	URC 081202
	1/2" FNPT	URC 081203

Tapered male threaded plug

	NPT male thread	Part number
	1/4" MNPT	URP 086251
	3/8" MNPT	URP 086252
	1/2" MNPT	URP 086253
	Teflon-coated thread	

REGULAR QUICK COUPLING - 1/4" ARO 210 INTERCHANGE



Tapered female thread coupler

	NPT female thread	Part number
	1/4" FNPT	ARC 061201

Tapered male thread plug

	NPT male thread	Part number
	1/4" FNPT	ARP 066251
	3/8" FNPT	ARP 066252
	Thread : Teflon-coated	

Blow guns



NEW GENERATION BLOW GUNS

Compact compressed-air blowguns with integrated plug
Users will appreciate the **prevo S1** blowguns in their daily operations, for their ease of use. These blowguns, equipped with PREVOST plugs, are compatible with all major connection profile standards. The plugs couple directly to the **prevo S1** quick safety coupling, which also optimizes the blowguns ergonomics (excellent handling).



➔ Construction

- Body and lever: polyamide composite
- Seals: nitrile
- Valves: polyacetal (POM)
- Plug: nitrided steel, scratch and corrosion resistant A II materials are compliant with the RoHS1 directive and REACH2 regulations.

➔ Technical specifications

- Maximum operating pressure: 174 psi
- Recommended pressure: 87 psi
- Operating temperature range: +5°F to 158°F

➔ Use

- Fluid: compressed air
- Applications: blowing, dust removal, cleaning and drying of tools and workstations
- Sectors of activity: industry, automotive, wood working, etc.

➔ Safety

- Reinforced security thanks to the association with the prevo S1 quick coupling



The configurations

The prevo S1 range of blowers consists of:

- Prevo S1 standard blow guns
- Soufflettes prevo S1 pocket

nozzle OSHA

nozzle MTL

nozzle OSHA



IBG 06OSH





IBG 06MTL





IPG 06OSH

PREVO S1 BLOW GUNS - INDUSTRIAL INTERCHANGE



prevo S1 blow gun with OSHA metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	85	IBG 06MTLH
prevo S1 coupler sold separately : ISI 06				



prevo S1 blow gun with metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	390	20	89	IBG 06MTL
prevo S1 coupler sold separately : ISI 06				



prevo S1 blowgun with OSHA polyamid composite nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	87	IBG 060SH
prevo S1 coupler sold separately : ISI 06				



prevo S1 blowgun with OSHA polyamid composite nozzle - Pocket model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	6	8.2	89	IPG 060SH
prevo S1 coupler sold separately : ISI 06				



prevo S1 blow gun with OSHA metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	85	UBG 06MTLH
prevo S1 coupler sold separately : USI 06				



prevo S1 blow gun with metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	14	12	89	UBG 06MTL
prevo S1 coupler sold separately : USI 06				



prevo S1 blowgun with OSHA polyamid composite nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	7	7.7	87	UBG 060SH
prevo S1 coupler sold separately : USI 06				



prevo S1 blowgun with OSHA polyamid composite nozzle - Pocket model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	6	8.2	89	UPG 060SH
prevo S1 coupler sold separately : USI 06				



prevo S1 blow gun with OSHA metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	85	EBG 07MTLH
prevo S1 coupler sold separately : ESI 07				



prevo S1 blow gun with metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	390	20	89	EBG 07MTL
prevo S1 coupler sold separately : ESI 07				

prevo S1 blowgun with OSHA polyamid composite nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	87	EBG 070SH
prevo S1 coupler sold separately : ESI 07				


prevo S1 blow gun with OSHA polyamid composite nozzle - Pocket model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	6	8,2	89	EPG 070SH
prevo S1 coupler sold separately : ESI 07				


PREVO S1 BLOW GUNS

- ARO 210 INTERCHANGE


prevo S1 blow gun with OSHA metal nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	85	ABG 06MTLH
prevo S1 coupler sold separately : ASI 06				


prevo S1 blow gun with metal nozzle - Standard model

	Blowing force (Oz) (at 87 psi)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	390	20	89	ABG 06MTL
prevo S1 coupler sold separately : ASI 06				


prevo S1 blowgun with OSHA polyamid composite nozzle - Standard model

	Blowing force (Oz) (at 87 psi)	Air consumption (at 87 psi) (SCFM)	Noise level (at 6 bar) (dBA)	Part number
	9	7.7	87	ABG 06OSH
prevo S1 coupler sold separately : ASI 06				


prevo S1 blow gun with OSHA polyamid composite nozzle - Pocket model

	Blowing force (Oz) (at 87 psi)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	6	8.2	89	APG 06OSH
prevo S1 coupler sold separately : ASI 06				


prevo S1 blow gun with OSHA polyamid composite nozzle - Standard model

	Blowing force (at 87 psi) (Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	9	7.7	87	CBG 06OSH
prevo S1 coupler sold separately : CSI 06				

prevo S1 blow gun with metal nozzle - Standard model

	Blowing force (at 87 psi)(Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	390	20	89	CBG 06MTL
prevo S1 coupler sold separately : CSI 06				

prevo S1 blow gun with OSHA polyamid composite nozzle - Pocket model

	Blowing force (at 87 psi)(Oz)	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	6	8.2	89	CPG 06OSH
prevo S1 coupler sold separately : CSI 06				

27202 *blow guns*

PROGRESSIVE AND ERGONOMIC BLOW GUNS **27202**



→ Protected mechanism

Design sealed against any external intrusions which might block the mechanism.

→ Use

Smooth trigger action enables flow rate to be precisely adjusted and compressed air circuit to open progressively.

→ Jet

Directional jet. The blowing angle and natural orientation of the air jet ensure accurate work.

→ Technologie material

Robust, anti-scratch, isolating, antislip. High tech composite material.

→ Connection

Inlet connection with brass insert: airtight connections material.

→ Easy to handle

The ergonomic shape fits perfectly in one hand

→ Grip

Two practical hanging systems.



→ Design

Smooth shape avoiding build-up




27202 BLOW GUN


OSHA Venturi Metal Nozzle Blow Gun

 	NPT female thread	Air consumption (at 87 PSI)	Construction	Part number
	1/4" FNPT	6.6	Metal tip blow gun with OSHA nozzle	27202 MTLOSHA


Metal Nozzle Blow Gun

	Noise level (at 87 psi) (dBA)	NPT female thread	Air consumption	Part number
	83 dB	1/4" FNPT	13.5	27202 MTL
	73 dB	1/4" FNPT	5.3	27202 MTLBP3
27202 MTLBP3 : Option : blow gun with flow limiter At 87 PSI inlet, the air jet is equivalent to the one of a standard blow gun with a 43.5 PSI inlet.				



Metal Nozzle Blow Gun

	Nozzle	Construction	Part number
	Bent 4" with Rubber Tip w/ 1/4" FNPT	Metal tip blow gun with non-scratch nozzle	27202 MTLRT



Metal Nozzle Blow Gun

	NPT female thread	Bent tube length (mm)	Part number
	1/4" FNPT	13"	27202 MB13
	1/4" FNPT	20"	27202 MB20
	1/4" FNPT	Straight 13"	27202 MS13
	1/4" FNPT	Straight 20"	27202 MS20



OSHA Metal Nozzle Blow Gun

 	NPT female thread	Bent tube length	Part number
	w/ 1/4" FNPT	Bent 13"	27202 MB13OSHA
	w/ 1/4" FNPT	Bent 20"	27202 MB20OSHA
	w/ 1/4" FNPT	Bent 40"	27202 MB40OSHA


OSHA Venturi Nozzle Blow Gun

 	NPT female thread	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	1/4" FNPT	7.7	90	27202 OSHA
	Complies with OSHA requirements			


OSHA Silent Nozzle

 	NPT female thread	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	1/4" FNPT	7.1	77	27202 SIL
	Complies with OSHA requirements			

Protective Sreen Nozzle

	NPT female thread	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	1/4" FNPT	15.9	82	27202 ECR

Non-Scratch Blow Gun

	NPT female thread	Air consumption (at 87 psi) (SCFM)	Noise level (at 87 psi) (dBA)	Part number
	1/4" FNPT	7.2	84	27202 PRE
	1/4" FNPT	5.8	80	27202 PREBP3
	27202 PREBP3 : Option : blow gun with flow limiter At 87 PSI, bar inlet, the air jet is equivalent to the one of a standard blow gun with a 43.5 PSI inlet.			

PREVOST PIPING SYSTEM

Concept 100 % aluminium

➔ New concept

Pipes are held in the fitting using a new system: the « **PPS Grip Concept** ». The **PPS Grip Concept** is based on a **stainless steel ring** with teeth that penetrate the aluminum. A leak tight connection is achieved via a **new contoured and lubricated seal**, with **optimised design** and properties. The seal remains perfectly leaktight even under the harshest conditions.

➔ IDENTIFICATION

The Prevost logo is engraved on each fitting.



➔ DIAMETER

Pipe external diameter in mm and inches



➔ PRESSURE

Maximum service pressure (bar/psi)



➔ MARKER

to indicate that the pipe is correctly positioned in the fitting

➔ TRACEABILITY

Date of fabrication



➔ Network design


To design a network, **the pipe diameter must be determined, taking into account the desired flow rate and the length of the main pipe.** Data calculated for a service pressure of 116 psi (8 bar) with 5% pressure loss.

COMPRESSOR*					MAIN RING LENGTH									
POWER		FLOW			30 m	76 m	152 m	305 m	610 m	914 m	1219 m	1524 m	1981 m	
kW	HP	Nm ³ /h	NI/min	Scfm	100 ft	250 ft	500 ft	1000 ft	2000 ft	3000 ft	4000 ft	5000 ft	6500 ft	
2,2	3,00	22	367	13	1/2"	1/2"	3/4"	3/4"	1"	1"	1"	1 1/4"	1 1/4"	
3	4,00	30	500	18	1/2"	1/2"	3/4"	1"	1"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	
4	5,00	40	668	24	1/2"	3/4"	3/4"	1"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/2"	
5,5	7,50	50	833	29	1/2"	3/4"	1"	1"	1 1/4"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	
7,5	10,00	70	1167	41	3/4"	1"	1"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	
11	15,00	100	1667	59	1"	1"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	2"	2"	2"	
15	20,00	150	2500	88	1"	1 1/4"	1 1/4"	1 1/2"	2"	2"	2"	2"	2 1/2"	
18	25,00	180	3000	106	1 1/4"	1 1/4"	1 1/2"	1 1/2"	2"	2"	2 1/2"	2 1/2"	2 1/2"	
22	30,00	220	3674	130	1 1/4"	1 1/4"	1 1/2"	2"	2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	
26	35,00	260	4167	147	1 1/2"	1 1/2"	1 1/2"	2"	2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	
30	40,00	350	5833	206	1 1/2"	1 1/2"	2"	2"	2 1/2"	2 1/2"	2 1/2"	3"	3"	
37	50,00	370	6179	218	1 1/2"	1 1/2"	2"	2"	2 1/2"	2 1/2"	3"	3"	3"	
45	60,00	500	8350	294	2"	2"	2"	2 1/2"	2 1/2"	3"	3"	3"	3"	
55	75,00	550	9185	324	2"	2"	2"	2 1/2"	2 1/2"	3"	3"	3"		
75	100	750	12500	441	2 1/2"	2 1/2"	2 1/2"	2 1/2"	3"	3"				
90	125	1000	16667	589	2 1/2"	2 1/2"	2 1/2"	3"	3"					
110	150	1100	18370	649	2 1/2"	2 1/2"	2 1/2"	3"						
132	175	1500	25000	883	3"	3"	3"	3"						
160	215	1750	29167	1030	3"	3"	3"							
200	270	2000	33333	1177	3"	3"	3"							


* These values may vary slightly from compressor data

PPS SYSTEM ALL ALUMINIUM NETWORKS


PPS - Aluminium pipe for compressed air

	Pipe OD (in)	Length (ft)	Part number
	1/2" / 16 mm	13.12 ft / 4 m	PPS TUB16L4
	3/4" / 20 mm	19.70 ft / 6 m	PPS TUB20L6
	1" / 25 mm	19.70 ft / 6 m	PPS TUB25L6
	1 1/4" / 32 mm	19.70 ft / 6 m	PPS TUB32L6
	1 1/2" / 40 mm	19.70 ft / 6 m	PPS TUB40L6
	2" / 50 mm	19.70 ft / 6 m	PPS TUB50L6
	2 1/2" / 63 mm	19.70 ft / 6 m	PPS TUB63L6
	3" / 80 mm	19.70 ft / 6 m	PPS TUB80L6


PPS - Aluminium pipe for vacuum

	Pipe OD (in)	Length (ft)	Part number
	1/2" / 16 mm	13.12 ft / 4 m	PPS TUG16L4
	3/4" / 20 mm	19.70 ft / 6 m	PPS TUG20L6
	1" / 25 mm	19.70 ft / 6 m	PPS TUG25L6
	1 1/4" / 32 mm	19.70 ft / 6 m	PPS TUG32L6
	1 1/2" / 40 mm	19.70 ft / 6 m	PPS TUG40L6
	2" / 50 mm	19.70 ft / 6 m	PPS TUG50L6
	2 1/2" / 63 mm	19.70 ft / 6 m	PPS TUG63L6
	3" / 80 mm	19.70 ft / 6 m	PPS TUG80L6


PPS - Aluminium pipe for nitrogen

	Pipe OD (in)	Length (ft)	Part number
	3/4" / 20 mm	19.70 ft / 6 m	PPS TUV20L6
	1" / 25 mm	19.70 ft / 6 m	PPS TUV25L6


PPS - Aluminium bended link pipe

	Pipe OD (in)	Part number
	1/2"	PPS LMCB16
	3/4"	PPS LMCB20
	1"	PPS LMCB25


PPS1 UN - Aluminum union for pipe

	For pipe OD (in)	Part number
	1/2"	PPS1 UN16
	3/4"	PPS1 UN20
	1"	PPS1 UN25
	1 1/4"	PPS1 UN32
	1 1/2"	PPS1 UN40
	2"	PPS1 UN50
	2 1/2"	PPS1 UN63
	3"	PPS1 UN80


PPS1 UNS - Aluminum female slide union for pipe

	For pipe OD (in)	Part number
	1"	PPS1 UNS25
	1 1/4"	PPS1 UNS32
	1 1/2"	PPS1 UNS40
	2"	PPS1 UNS50
	2 1/2"	PPS1 UNS63
	3"	PPS1 UNS80

PPS1 MR - Aluminium pipe reducing fitting

	For pipe OD (in)	For pipe OD (in)	Part number
	1"	3/4"	PPS1 MR2520
	1 1/4"	1"	PPS1 MR3225
	1 1/2"	1 1/4"	PPS1 MR4032
	2"	1 1/2"	PPS1 MR5040
	2 1/2"	2"	PPS1 MR6350
	3"	2 1/2"	PPS1 MR8063

PPS1 9C - 90° Aluminum union elbow for pipe

	For pipe OD (in)	Part number
	1/2"	PPS1 9C16
	3/4"	PPS1 9C20
	1"	PPS1 9C25
	1 1/4"	PPS1 9C32
	1 1/2"	PPS1 9C40
	2"	PPS1 9C50
	2 1/2"	PPS1 9C63
	3"	PPS1 9C80

PPS SYSTEM ALL ALUMINIUM NETWORKS

PPS1 9CM - 90° aluminum tapered male threaded elbow for pipe

For pipe OD (in)	NPT male thread	Part number
1/2"	3/8" MNPT	PPS1 9CM16252
1/2"	1/2" MNPT	PPS1 9CM16253
3/4"	1/2" MNPT	PPS1 9CM20253
1"	1/2" MNPT	PPS1 9CM25253
1"	3/4" MNPT	PPS1 9CM25254
1 1/4"	1" MNPT	PPS1 9CM32255
1 1/2"	1 1/4" MNPT	PPS1 9CM40256
1 1/2"	1 1/2" MNPT	PPS1 9CM40257

PPS1 4C - 45° Aluminum equal female elbow for pipe

For pipe OD (in)	Part number
1/2"	PPS1 4C16
3/4"	PPS1 4C20
1"	PPS1 4C25
1 1/4"	PPS1 4C32
1 1/2"	PPS1 4C40

PPS1 BO - Aluminum Pipe Cap

For pipe OD (in)	Part number
1/2"	PPS1 B016
3/4"	PPS1 B020
1"	PPS1 B025
1 1/4"	PPS1 B032
1 1/2"	PPS1 B040
2"	PPS1 B050
2 1/2"	PPS1 B063
3"	PPS1 B080

PPS1 TE - Aluminum equal female tee piece for pipe

For pipe OD (in)	Part number
1/2"	PPS1 TE16
3/4"	PPS1 TE20
1"	PPS1 TE25
1 1/4"	PPS1 TE32
1 1/2"	PPS1 TE40
2"	PPS1 TE50
2 1/2"	PPS1 TE63
3"	PPS1 TE80

PPS1 TR - Aluminium reducing branch tee for pipe

For pipe OD (in)	For pipe OD (in)	Part number
3/4"	1/2"	PPS1 TR2016
1"	1/2"	PPS1 TR2516
1"	3/4"	PPS1 TR2520
1 1/4"	1/2"	PPS1 TR3216
1 1/4"	3/4"	PPS1 TR3220
1 1/4"	1"	PPS1 TR3225


PPS1 TT - Aluminum tapered female threaded tee piece for pipe

For pipe OD (in)	NPT female thread	Part number
1/2"	3/8" FNTP	PPS1 TT16202
3/4"	1/2" FNTP	PPS1 TT20203
1"	1/2" FNTP	PPS1 TT25203
1"	3/4" FNTP	PPS1 TT25204
1 1/4"	3/4" FNTP	PPS1 TT32204
1 1/4"	1" FNTP	PPS1 TT32205
1 1/2"	3/4" FNTP	PPS1 TT40204
1 1/2"	1" FNTP	PPS1 TT40205
1 1/2"	1 1/4" FNTP	PPS1 TT40206
2"	1" FNTP	PPS1 TT50205
2"	1 1/4" FNTP	PPS1 TT50206
2"	1 1/2" FNTP	PPS1 TT50207
2 1/2"	1" FNTP	PPS1 TT63205
2 1/2"	1 1/4" FNTP	PPS1 TT63206
2 1/2"	1 1/2" FNTP	PPS1 TT63207
2 1/2"	2" FNTP	PPS1 TT63208
3"	1" FNTP	PPS1 TT80205
3"	1 1/2" FNTP	PPS1 TT80207
3"	2" FNTP	PPS1 TT80208
3"	2 1/2" FNTP	PPS1 TT80209


PPS1 MM - Aluminum tapered male threaded straight fitting for pipe

For pipe OD (in)	NPT male thread	Part number
1/2"	3/8" MNPT	PPS1 MM16252
1/2"	1/2" MNPT	PPS1 MM16253
3/4"	1/2" MNPT	PPS1 MM20253
3/4"	3/4" MNPT	PPS1 MM20254
1"	1/2" MNPT	PPS1 MM25253
1"	3/4" MNPT	PPS1 MM25254
1"	1" MNPT	PPS1 MM25255
1 1/4"	1" MNPT	PPS1 MM32255
1 1/4"	1 1/4" MNPT	PPS1 MM32256
1 1/2"	1 1/4" MNPT	PPS1 MM40256
1 1/2"	1 1/2" MNPT	PPS1 MM40257
2"	1 1/2" MNPT	PPS1 MM50257
2"	2" MNPT	PPS1 MM50258
2 1/2"	2" MNPT	PPS1 MM63258
2 1/2"	2 1/2" MNPT	PPS1 MM63259
3"	2 1/2" MNPT	PPS1 MM80259
3"	3" MNPT	PPS1 MM802510


PPS1 MF - Aluminum female threaded fitting for pipe

	For pipe OD (in)	NPT female thread	Part number
	1/2"	3/8" FNPT	PPS1 MF16202
1/2"	1/2" FNPT	PPS1 MF16203	
3/4"	1/2" FNPT	PPS1 MF20203	
3/4"	3/4" FNPT	PPS1 MF20204	
1"	1/2" FNPT	PPS1 MF25203	
1"	3/4" FNPT	PPS1 MF25204	
1"	1" FNPT	PPS1 MF25205	
1 1/4"	1" FNPT	PPS1 MF32205	
1 1/4"	1 1/4" FNPT	PPS1 MF32206	
1 1/2"	1 1/4" FNPT	PPS1 MF40206	
1 1/2"	1 1/2" FNPT	PPS1 MF40207	
2"	1 1/2" FNPT	PPS1 MF50207	
2"	2" FNPT	PPS1 MF50208	
2 1/2"	2" FNPT	PPS1 MF63208	
2 1/2"	2 1/2" FNPT	PPS1 MF63209	
3"	2 1/2" FNPT	PPS1 MF80209	
3"	3" FNPT	PPS1 MF802010	


PPS1 BP - Aluminum tapping flange for pipe

	For pipe OD (in)	For pipe OD (in)	Part number
	1"	1/2"	PPS1 BP2516
1"	3/4"	PPS1 BP2520	
1 1/4"	1/2"	PPS1 BP3216	
1 1/4"	3/4"	PPS1 BP3220	
1 1/2"	1/2"	PPS1 BP4016	
1 1/2"	3/4"	PPS1 BP4020	
1 1/2"	1"	PPS1 BP4025	
2"	1/2"	PPS1 BP5016	
2"	3/4"	PPS1 BP5020	
2"	1"	PPS1 BP5025	
2 1/2"	3/4"	PPS1 BP6320	
2 1/2"	1"	PPS1 BP6325	
2 1/2"	1 1/4"	PPS1 BP6332	
3"	3/4"	PPS1 BP8020	
3"	1"	PPS1 BP8025	
3"	1 1/4"	PPS1 BP8032	


PPS1 RSIF - Aluminum parallel female threaded valves with fittings for pipe

	For pipe OD (in)	NPT female thread	Part number
	1 1/2"	1 1/4" FNPT	PPS1 RSIF40206
2"	1 1/2" FNPT	PPS1 RSIF50207	
2 1/2"	2" FNPT	PPS1 RSIF63208	
3"	2 1/2" FNPT	PPS1 RSIF80209	
1/2"	1/2" FNPT	PPS1 RSIF16203	
3/4"	1/2" FNPT	PPS1 RSIF20203	
1"	3/4" FNPT	PPS1 RSIF25204	
1 1/4"	1" FNPT	PPS1 RSIF32205	


PPS1 BT - Aluminum threaded tapping flange for pipe

	For pipe OD (in)	NPT female thread	Part number
	1"	3/8" FNPT	PPS1 BT25202
1"	1/2" FNPT	PPS1 BT25203	
1 1/2"	1/2" FNPT	PPS1 BT40203	
1 1/4"	1/2" FNPT	PPS1 BT32203	
1 1/2"	3/4" FNPT	PPS1 BT40204	
1 1/4"	3/4" FNPT	PPS1 BT32204	
1 1/2"	1" FNPT	PPS1 BT40205	
2"	1/2" FNPT	PPS1 BT50203	
2"	3/4" FNPT	PPS1 BT50204	
2"	1" FNPT	PPS1 BT50205	
2 1/2"	1/2" FNPT	PPS1 BT63203	
2 1/2"	3/4" FNPT	PPS1 BT63204	
2 1/2"	1" FNPT	PPS1 BT63205	
3"	1/2" FNPT	PPS1 BT80203	
3"	3/4" FNPT	PPS1 BT80204	
3"	1" FNPT	PPS1 BT80205	


PPS1 RSIM - Aluminum parallel male threaded valves with fittings for pipe

	For pipe OD (in)	NPT male thread	Part number
	1/2"	1/2" MNPT	PPS1 RSIM16253
3/4"	1/2" MNPT	PPS1 RSIM20253	
1"	3/4" MNPT	PPS1 RSIM25254	
1 1/4"	1" MNPT	PPS1 RSIM32255	
1 1/2"	1 1/4" MNPT	PPS1 RSIM40256	
2"	1 1/2" MNPT	PPS1 RSIM50257	


PPS1 NUT - Aluminum nut

	For fitting Ø (in)	Part number
	1/2"	PPS1 NUT16
3/4"	PPS1 NUT20	
1"	PPS1 NUT25	
1 1/4"	PPS1 NUT32	
1 1/2"	PPS1 NUT40	
2"	PPS1 NUT50	
2 1/2"	PPS1 NUT63	
3"	PPS1 NUT80	

PPS1 RSI - Aluminum piping ball valve

	For pipe OD (mm)	Part number
	1/2"	PPS1 RSI16
3/4"	PPS1 RSI20	
1"	PPS1 RSI25	
1 1/4"	PPS1 RSI32	
1 1/2"	PPS1 RSI40	
2"	PPS1 RSI50	
2 1/2"	PPS1 RSI63	
3"	PPS1 RSI80	


PPS1 SEAL - Gasket kit

	Includes	For fitting Ø (in)	Part number
	10	1/2"	PPS1 SEAL16
	20	3/4"	PPS1 SEAL20
	10	1"	PPS1 SEAL25
	10	1 1/4"	PPS1 SEAL32
	5	1 1/2"	PPS1 SEAL40
	5	2"	PPS1 SEAL50
	2	2 1/2"	PPS1 SEAL63
2	3"	PPS1 SEAL80	


PPS1 IP - Internal parts kit

	For fitting Ø (in)	Part number
	1/2"	PPS1 IP16
	3/4"	PPS1 IP20
	1"	PPS1 IP25
	1 1/4"	PPS1 IP32
	1 1/2"	PPS1 IP40
	2"	PPS1 IP50
	2 1/2"	PPS1 IP63
3"	PPS1 IP80	


PPS1 CLE - Spanner wrench

	For fitting Ø (in)	Part number
	1/2"	PPS1 CLE16
	3/4"	PPS1 CLE20
	1"	PPS1 CLE25
	1 1/4"	PPS1 CLE32
	1 1/2"	PPS1 CLE40
	2"	PPS1 CLE50
	2 1/2"	PPS1 CLE63
3"	PPS1 CLE80	

PPS SP - Drill for taping flange


	Drill Ø (in)	Part number
	0.63	PPS SP16
	0.87	PPS SP22
	1.18	PPS SP30
Boring through for flange		

PPS AL - Spray lubricator for assembly


	Capacity (oz)	Part number
	25	PPS AL

ACCESSORIES FOR PPS


PPS1 CI - Piping Clamp (unit of sales = 1 box of 5 clamps)

	For pipe OD (in)	Part number
	1/2"	PPS1 CI16
	3/4"	PPS1 CI20
	1"	PPS1 CI25
	1 1/4"	PPS1 CI32
	1 1/2"	PPS1 CI40
	2"	PPS1 CI50
	2 1/2"	PPS1 CI63
3"	PPS1 CI80	

Metal support bracket


	Description	Part number
	Length 7.09 in	CS 180L
	Length 11.81 in	CS 310L
	Length 16.54 in	CS 420L
	Length 20.08 in	CS 500
	Screw M8 (3) on metal support CS 500	CS VIS
Screw (4) for metal support CS 180L - CS 310L - CS 420L	CS VIS2	

M8 Beam clip

	Panel thickness (in)	Metric thread	Part number
	.11" to .31" (1)		CP 38
	.31" to .55" (1)		CP 814
	.55" to .78" (1)		CP 1420
	up to .63" max. (2)	M6 or cross-piece	CP 016

FLEXIBLE LINKS

Flexible link - Swivel male - male


	NPT male thread	Length (ft)	Part number
	1/2"	4.9	LEM 253
	3/4"	4.9	LEM 254
	1"	4.9	LEM 255
	1 1/4"	7.2	LEM 256
	1 1/2"	8.2	LEM 257
	2"	6.5	LEM 258

INSTALLATION TOOL CASE

PPS CT - Tools case for pipes preparation

	Part number
	Includes : PPS CTU63 / PPS CHE50 / PPS CHERAP / PPS SP16 / PPS SP22 / PPS PEN
	PPS CT1650

PPS CK - Tightening wrenches case

	Part number
	Includes : PPS1 CLE16 / PPS1 CLE20 / PPS1 CLE25 / PPS1 CLE32 / PPS PEN
	PPS CK1632
	Includes : PPS1 CLE40 / PPS1 CLE50 / PPS PEN
	PPS CK4050
	Includes : PPS1 CLE63 / PPS1 CLE80 / PPS PEN
	PPS CK6380

The hose reels range

THE ADVANTAGES THAT MAKE THE DIFFERENCE

Automatic hose reels are essential equipment for an efficient workshop. They save time and enable flexible distribution hoses to be used in total safety and comfort. Available for the following media:

- compressed air,
- cold water and hot water at high and low pressure,
- oil, grease, prevost's comprehensive range of hose reels meets all requirements.

➔ RETURN SPRING

The return spring system effortlessly winds the hose back into the reel housing. This extends the service life of hoses by ensuring that they are not left lying on the floor, where they would be exposed to contaminants, abrasion and a risk of crushing.

➔ CONTROLLED HOSE RETURN SYSTEM

The DRFB range features a braked return system which optimises operator safety and safeguards the work area. The brake ensures that the hose is reeled in smoothly and progressively. This means that users can safely let go of a hose without it being reeled in unexpectedly fast.



➔ QUICK CONNECTION FITTINGS

Compressed air hose reels feature prevo S1 quick safety couplings, offering hose whip protection and enabling single press depressurisation and disconnection of pneumatic tools in total safety. The range features various types of couplings:

- 6 mm, 7.4 mm, 8 mm and 11 mm clearance depending on the hose size and the corresponding air flow,
- various profiles (Automotive interchange, industrial, high flow, ARO, etc.) meeting the needs of international markets.

➔ TWIST PROTECTION

A twist protection system on the outlet connector ensures that the hose will not fold during use. Made from lightweight polyamide, the system prevents impact damage to hoses. Stainless steel reels feature stainless steel twist protection.



➔ DESIGN

Our extensive experience in the methods and techniques used to manufacture our hose reels ensures that they offer longlasting reliability with no premature wear. The reels are fitted with appropriate hoses for the fluids carried:

- compressed air
- cold water and hot water, at high and low pressure
- grease and oil.

The technology and the quality of the materials ensure that the reels are robust and effective.

➔ STOP CATCH

The reel mechanism includes a catch system that locks the hose at the length needed for the operator's work. This avoids the operator being hampered by heavy, cumbersome lengths of hose. Pulling on the hose releases the catch, enabling the return spring to automatically wind the hose back into the reel.

➔ WALL-MOUNTED OR OVERHEAD INSTALLATION

Our hose reels can be mounted on a wall, overhead or fitted on a trolley, depending on the workshop layout, always ensuring good reach. A carefully placed reel reduces workshop clutter and increases productivity and convenience.

ENCLOSED HOSE REELS FOR COMPRESSED AIR / STEEL

DRFB Series - Hose reel w/ safety retraction - PU/PVC hose

ID (in)	Length (ft)	Coupler	Part number
5/16"	40'	ISI 06	DRFB 0812IS
5/16"	40'	ISI 06	DRFB 0815IS
3/8"	33'	ISI 06	DRFB 1010IS
3/8"	40'	ISI 06	DRFB 1012IS

180° swiveling bracket
Inlet : 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 149° F
Pressure : 174 PSI

DRF Series - Medium - Economy type - Outer hose: PU/PVC - Inner: PU ether base

ID (in)	Length (ft)	Coupler	Part number
5/16"	40'	ISI 06	DRF 0812IS
5/16"	50'	ISI 06	DRF 0815IS
3/8"	40'	ISI 06	DRF 1012IS
3/8"	33'	ISI 06	DRF 1010IS
5/16"	40'	USI 06	DRF 0812US
5/16"	50'	USI 06	DRF 0815US
3/8"	33'	USI 06	DRF 1010US
3/8"	40'	USI 06	DRF 1012US

180° swiveling bracket
Inlet : 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 149° F
Pressure : 174 PSI

DSF series - small - Polyurethane hose w/ polyester base

ID (in)	Length (ft)	Coupler	Part number
5/16"	17'	ISI 06	DSF 0805IS
3/8"	10'	ISI 06	DSF 1003IS

180° swiveling bracket
Inlet : 1 m Hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 104° F
Pressure : 174 PSI

DMF Series - Industrial type - Polyurethane hose

ID (in)	Length (ft)	Coupler	Part number
5/16"	33'	ISI 06	DMF 0810IS

180° swiveling bracket
Inlet : 3/8" FBSP + 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 104° F
Pressure : 174 PSI

DPF series - Industrial type - Polyurethane hose

ID (in)	Length (ft)	Coupler	Part number
5/16"	40'	ISI 06	DPF 0812IS
3/8"	33'	ISI 06	DPF 1010IS

180° swiveling bracket
Inlet : 3/8" FBSP + 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 104° F
Pressure : 174 PSI

DGF series - Large industrial type - Rubber hose

ID (in)	Length (ft)	Coupler	Part number
5/16"	33'	ISI 06	DGF 0810IS
5/16"	50'	ISI 06	DGF 0815IS
5/16"	65'	ISI 06	DGF 0820IS
3/8"	33'	ISI 06	DGF 1010IS
3/8"	50'	ISI 06	DGF 1015IS
1/2"	33'	ISI 08	DGF 1310IS

Fixed bracket
Inlet : 3/8" FBSP
Inlet : 1/2" MBSP for DGF 1310
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 104° F
Pressure : 174 PSI

DMO series - medium - Rubber hose

ID (in)	Length (ft)	Coupler	Part number
5/16"	33'	ISI 06	DMO 0810IS
5/16"	50'	ISI 06	DMO 0815IS
5/16"	65'	ISI 06	DMO 0820IS
3/8"	33'	ISI 06	DMO 1010IS
3/8"	50'	ISI 06	DMO 1015IS
3/8"	65'	ISI 06	DMO 1020IS

DVO series - medium - Polyurethane braided hose

ID (in)	Length (ft)	Coupler	Part number
3/8"	82'	ISI 06	DVO 1025IS

Fixed bracket
Inlet : 3/8" FBSP
 + 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 104° F
Pressure : 174 PSI

DGO series - large - rubber hose

ID (in)	Length (ft)	Coupler	Part number
10 x 17	82'	ISI 06	DGO 1025IS
13 x 20	65'	ISI 08	DGO 1320IS
16x23	33'	ISI 11	DGO 1610IS

Fixed bracket
Inlet : 3/8" FBSP
Inlet : 1/2" MBSP for DGO 1320 + DGO 1610
 + 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 149° F
Pressure : 174 PSI

DLO series - extra large - rubber hose

ID (in)	Length (ft)	Coupler	Part number
1/2"	98'	ISI 11	DLO 1330IS
5/8"	82'	ISI 11	DLO 1625IS
3/4"	65'	ISI 11	DLO 1920IS

Fixed bracket
Inlet : 1/2" FBSP
Inlet : 1" MBSP for DLO 1920
 + 1 m hose
Outlet : with prevoS1 safety quick coupling
Temperature : 5° F to 158° F
Pressure : 174 PSI

Air treatment units

ALTO and SPC


FILTRATION AND TREATMENT OF COMPRESSED AIR

Treatment of compressed air

is essential for : Preserving pneumatic tools and equipment

- Obtaining high quality work
- Reducing maintenance costs

ALTO range : the ALTO range ensures that your pneumatic tools work optimally



➔ Alto filter

ALTO filters eliminate contaminants from compressed air (particles, water and oil) by filtration and bleeding. They ensure 95% separation of water, oil and solid particles greater than or equal to the selected filtration threshold.

➔ Alto regulator

ALTO regulators adjust pressure to the values required by each application.

➔ Alto lubricator

ALTO oil mist lubricators preserve your pneumatic tools by injecting precisely metered quantities of lubricant into the filtered air.

➔ Ease of use

Operation of ALTO units

- Tank with bayonet-type mounting system for NPT 3/8, NPT 1/2, NPT 3/4, NPT 1 assemblies
- Threaded tank for NPT 1/4 assemblies
- Oil flow adjusted by set screw
- Oil tank may be filled during use
- Manual bleed of filters by pressing the drain button
- Tank with metallic protection

CYCLONE SEPARATORS - SPC

➔ Condensate separation and draining

Water is one of the main contaminants of compressed air. The cyclone separator is specially designed for the efficient separation and elimination of the largest solid particles as well as water droplets in compressed air. Inside the tank, a fin system drives the compressed air in a rotational movement. Particulate matter is projected against the walls of the tank, under the effect of centrifugal force, then guided towards the base. Condensates are then drained via the automatic float drain.

➔ Advantages

- Sturdy construction
- Efficient separation of air and water
- Cost-effective and dependable operation
- Applications for flow rates from 155 to 1280 Nm³/h and for all industries.

➔ Efficiency

- Greater than 98% at nominal flow rate and at 7 bar, temperature 20°C, particle size from 10 µm to 50 µm. Classification according to ISO 8573-1 Water: Class 8


Typical applications for the SPC separator:

- compressor outlet
- tank outlet
- prefilter for refrigerated dryers
- prefilter for submicron filters




ALTO 3 - 1/2" FNPT LARGE SIZE COMPRESSED AIR TREATMENT UNITS


3-piece-set - Filter-Regulator-Lubricator (gauge included) with wall bracket

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	123.54	25	TT SM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				


3-piece-set - Filter-Regulator-Lubricator (gauge included) with wall bracket and pipe adapters

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	123.54	25	TT PSM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				


Filter-Regulator (gauge included) with wall bracket

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	105.96	25	KTM SM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				


Filter-Regulator (gauge included) with wall bracket and pipe adapters

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	105.96	25	TM PSM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				


2-piece-set - Filter-Regulator-Lubricator (gauge included) with wall bracket, diverter block and pipe adapters

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	105.96	25 and 4 non-lubricated outlets	TB SME203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi 4 outlets for non lubricated aria				

2-piece-set - Microfilter assembly with Regulator (gauge included) and wall bracket

	NPT female thread	Flow rate (Cfm at 87 psi Δp=4psi)	Filtration	Part number
	1/2"	52.95	5 and 0.01	TB CSM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				

Filter-Regulator (gauge included) with wall bracket and pipe adapters

	NPT female thread	Flow rate (Cfm at 100 psi Δp=14psi)	Filtration (μm)	Part number
	1/2"	105.96	25	TM PSM203
Equipped with a pressure gauge : 0 to 145 psi Max operating pressure : 174 psi				


MFM SERIES - MICRONIC FILTER

Micron Filter - Filtration threshold : 1 μm


	Female thread (FNPT)	Flow rate (CFM at 100 psi)	Part number
	1/2"	50	MFM 1203
Filtration threshold : 1 μm			

GAUGES


Square Gauge 1/8" MNPT

	Graduation	Fastening	Part number
	0-58 PSI	Presealed 1/8" MNPT back entry.	MT CA0440T
	0-87 PSI	Presealed 1/8" MNPT back entry.	MT CA0640T
	0-145 PSI	Presealed 1/8" MNPT back entry.	MT CA1040T
	0-232 PSI	Presealed 1/8" MNPT back entry.	MT CA1640T
Presealed 1/8" MNPT back entry. Plexiglas dial			


Square Gauge 1/8" MBSP

	Graduation (psi)	Fastening BSPP male thread	Construction	Part number
	0 - 4	G 1/8	Plexiglas dial	MT CA0440
	0 - 6	G 1/8	Plexiglas dial	MT CA0640
	0 - 10	G 1/8	Plexiglas dial	MT CA1040
	0-232	G 1/8	Plexiglas dial	MT CA1640
Presealed back entry				


Round gauge 1/8" MNPT

	Graduation (psi)	Fastening BSPP male thread	Construction	Part number
	0-174 PSI	1/8" MNPT	Plexiglas dial Gas back entry.	MT RA1023T
	Presealed back entry			

Round gauge MNPT 1/4"


	Graduation (psi)	Construction	Part number
	0-58 PSI	Plexiglas dial	MT RA0450T
	0-145 PSI	Plexiglas dial	MT RA1050T
	0-363 PSI	Plexiglas dial	MT RA2550T
Presealed back entry			

Gauge 1/8" MBSP


	Graduation (psi)	Fastening BSPP male thread	Part number
	0-45	1/8"	MT IA1040V
Presealed back entry. Solvent resistant glass dial			

WATER SEPARATOR (A)

Cyclonic Water Separator w/ Float Drain

	Female thread (NPT)	Flow rate (cfm)	Part number
	1/2"	91	SPC 155T
	3/4"	138	SPC 235T
	1"	215	SPC 365T
	1" 1/2	452	SPC 770T
	2"	753	SPC 1280T

Wall bracket for SPC separator

	Compatible with	Part number
	SPC 155T - SPC 235T	SPC Q1
	SPC 365T - SPC 770T - SPC 1280T	SPC Q2

Drain for SPC

	Description	Part number
	Drain for SPC	SPC D

Hose extensions

HOSE EXTENSIONS FITTED WITH QUICK COUPLING AND ADAPTOR

- Wide range of extensions: choice of hose type, diameter and length
- Couplings perfectly match hose diameter
- Leak-tight, ready to use
- Easy and secure connections
- Easy to use, move and store



TYPES OF EQUIPMENT

➔ Hose extensions with ear clamp



Ear clamps ensure the fixation of hoses, PVC, rubber or other materials, on the cylindrical part of parts intended to receive a pipe (JFT Junction ZS).

- Safety and durability of fixation
- Undesirable products
- Perfect tighten
- To corrosion resistance



Junction JFT ZS

This method can be dismantled by cutting the clamp, so the extension can be modified if necessary.

➔ Rubber protector



Placed on ear clamp, the rubber protector suits perfectly and cover metal elements. This protection avoid scratches and injuries.

➔ Crimped hose extensions



- Hose attached to coupling with industrial crimping
- Encased in steel skirt
- Excellent grip of hose

➔ Extension with swivel couplings avoid




- problems due to twisted hoses
- work stoppages due to broken hoses
- difficult, uncomfortable positions
- Arm and wrist fatigue

They offer operators the freedom of movement needed for quick, highquality work


AIR HOSE EXTENSION

Airca Hose Assembly with swivel


	Diameter (ID) (mm)	Coupler	Length (ft)	Part number
	3/8"	IRP 06-ISC 06SW	50'	SIAIR 63850S
	3/8"	IRP 08-ISC 08SW	50'	SIAIR 83850S
	3/8"	ERP 07-ESC 07SW	35'	SEAIR 73835S
	3/8"	ERP 07-ESC 07SW	50'	SEAIR 73850S
	3/8"	ARP 06-ASC 06SW	50'	SAAIR 63835S
	3/8"	ARP 06-ASC 06SW	50'	SAAIR 63850S

PVC HOSE EXTENSION EQUIPPED WITH SAFETY COUPLINGS AND PLUG

FLEXAIR hybrid polymer extension hoses with pressed metal sleeves, non-scratch shield / bend protector and Prevo S1 quick couplings


	ID (in)	Coupler	Length (ft)	Part number
	3/8"	ISI 06	50	RST RISB3850
	3/8"	USI 06	50	RST RUSB3850
	3/8"	ESI 07	50	RST RESB3850
	3/8"	ASI 06	50	RST RASB3850

Stoflex Hose Assembly / non static

	Thread (MNPT)	Diameter (ID (in))	Length (ft)	Part number
	1/4"	3/8"	4.5'	USTO 3804FA
	1/4"	3/8"	35'	USTO 3835FA
	1/4"	3/8"	50'	USTO 3850FA
	3/8"	3/8"	4.5'	ESTO 3804FA
	3/8"	3/8"	35'	ESTO 3835FA
	3/8"	3/8"	50'	ESTO 3850FA


Outlet :
 - USTO* = equipped with URC coupler
 - ESTO* = equipped with ERC coupler

Stoflex- Non static hose

	Thread (MNPT)	Diameter (ID (in))	Coil (Length (Ft))	Part number
	1/4"	3/8"	35'	STOFLEX 3835
	1/4"	3/8"	50'	STOFLEX 3850
	NA	3/8"	500' Bulk hose	STOFLEX 38500

Hose assemblies available in custom lengths

Airca Rubber Air Hose

	Thread (MNPT)	Diameter (ID (in))	Coil (Length (Ft))	Part number
	1/4"	3/8"	25'	AIRCA 3825
	1/4"	3/8"	50'	AIRCA 3850
	NA	3/8"	500' Bulk hose	AIRCA 38500

Hose assemblies available in custom lengths

Spirals with swivel coupling

GUARANTEED FREEDOM OF MOVEMENT

In the workshop, spiral tubing offer the flexibility to supply quick connectors, blow guns and various pneumatic tools.

Their length adapts to the use and allows the operator to use the tool easily connected in its perimeter of work, without constraint of weight and of bulk, avoiding any risk of kinks.



PUS POLYURETHANE VERSION

➔ PUS SPIRAL TUBES POLYURETHANE

- Pipes delivered assembled ready for use
- Male connection threads


Prefabricated for easy and safe installation

- Nickel plated brass fittings

- Good elasticity
- Return to initial position after extension

Long-term guarantee

- Plastic protector preserving possible breaks of the pipe at the level of the connections



Fixed connection on the supply side

For severe applications, we recommend the use of PUS FF polyurethane spiral tubing with fixed connection on each side.




Special Polyurethane» coupling **Supplied in spare parts:**


- Rotating coupling
- Fixed coupling

POLYURETHANE RECOILS WITH SCRATCH-RESISTANT FITTINGS


Spiral Hose w/ fixed and rotating fittings

	NPT male thread	ID (in)	Max length (ft)	Part number
	1/4" MNPT	1/4"	6.5'	PUS 252
	1/4" MNPT	1/4"	13'	PUS 254
	1/4" MNPT	5/16"	13'	PUS 264
	1/4" MNPT	5/16"	20'	PUS 266
	1/4" MNPT	5/16"	26'	PUS 268
	1/4" MNPT	5/16"	32'	PUS 2610
	3/8" MNPT	3/8"	26'	PUS 288
	3/8" MNPT	3/8"	50'	PUS 2815
Blue				


Spiral Hose w/ fixed and rotating fittings

	NPT male thread	ID (in)	Max length (ft)	Part number
	1/4" MNPT	5/16"	13'	PUS 264R
	1/4" MNPT	5/16"	20'	PUS 266R
Red				


Spiral Hose w/ fixed and rotating fittings

	NPT male thread	ID (in)	Max length (ft)	Part number
	1/4" MNPT	5/16"	13'	PUS 264J
	1/4" MNPT	5/16"	20'	PUS 266J
Yellow				

Spiral Hose w/ fixed and rotating fittings

	NPT male thread	ID (in)	Max length (ft)	Part number
	1/4" MNPT	5/16"	13'	PUS 264V
	1/4" MNPT	5/16"	20'	PUS 266V
Green				

Spiral Hose w/ fixed and rotating fittings

	NPT male thread	ID (in)	Max length (ft)	Part number
	1/4" MNPT	5/16"	13'	PUS 264NR
	1/4" MNPT	5/16"	20'	PUS 266NR
Black				



Prevost Corporation - PO Box 17708 - Greenville, SC 29606
Phone: (800) 845-7220 - Fax: (864) 284-6428
E mail: sales.corp@prevostusa.com - Web: www.prevostusa.com

Download the Perfect Shop at:
www.prevostusa.com

SHOP DOC US 17

Published by Prevost - 05.2017
This document may not be deemed contractually binding.
To provide better service for customers, Prevost reserves
the right to alter product characteristics without notice.

