

NEW

3/8" FLEXAIR hybrid polymer hose with pressed metal sleeves, non-scratch sheath and prevoS1 quick safety couplings



Technical characteristics

Operating pressure: 29 to 174 psi

Temperature: +5°F to +140°F

Construction: PVC

Equipped with: Coupler and adapter

ID (in)	Coupler	Plug	Length (ft)	Parts Numbers
3/8"	ISI 06	IRP 06	25'	RST RISB3825
3/8"	ISI 06	IRP 06	35'	RST RISB3835
3/8"	ISI 06	IRP 06	50'	RST RISB3850
3/8"	ISI 06	IRP 06	100'	RST RISB38100
3/8"	USI 06	URP 06	25'	RST RUSB3825
3/8"	USI 06	URP 06	35'	RST RUSB3835
3/8"	USI 06	URP 06	50'	RST RUSB3850
3/8"	USI 06	URP 06	100'	RST RUSB38100
3/8"	ESI 07	ERP 07	25'	RST RESB3825
3/8"	ESI 07	ERP 07	35'	RST RESB3835
3/8"	ESI 07	ERP 07	50'	RST RESB3850
3/8"	ESI 07	ERP 07	100'	RST RESB38100
3/8"	ASI 06	ARP 06	25'	RST RASB3825
3/8"	ASI 06	ARP 06	35'	RST RASB3835
3/8"	ASI 06	ARP 06	50'	RST RASB3850
3/8"	ASI 06	ARP 06	100'	RST RASB38100