


## PS 781 – Four-Hole Open Angle Connector



"A" Angle	"B" In.
7½°	3¾"
15°	
22½°	
30°	3⅛"
37½°	
45°	
52½°	
60°	3⅝"
67½°	
75°	
82½°	

Weight/100 pcs: 78 lbs.

### MATERIAL:

All Power-Strut fittings are formed in punch press dies from mild, pickled and oiled, bar or strip steel. Plain or electro-galvanized fittings meet the requirements for ASTM A575 and A-576, or ASTM A-36.

### STANDARD FINISH:

All Power-Strut fittings are available in painted green or electro-galvanized finish.

### STANDARD DIMENSIONS:

Standard dimensions on all fittings are as follows except where otherwise indicated:

Fitting Thickness: ¼"  
 Fitting Width: 1 5/8"  
 Hole Diameter: 9/16"  
 Hole Spacing: 1 7/8" on centers and 1 3/16" from ends.

### ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

Project: \_\_\_\_\_  
 Architect / Engineer: \_\_\_\_\_  
 Date: \_\_\_\_\_ Phone: \_\_\_\_\_  
 Contractor: \_\_\_\_\_  
 Address: \_\_\_\_\_

Approval Stamp:

Notes 1: \_\_\_\_\_  
 \_\_\_\_\_  
 Notes 2: \_\_\_\_\_  
 \_\_\_\_\_