

ZTEK®

LIGHTWEIGHT POLYCARBONATE ONE PIECE SPECTACLE



PART	LENS	PART	LENS
S2510S***	Clear	S2540S***	Orange
S2510ST****	Clear (Anti-Fog)	S2560S***	Infinity Blue
S2510SRT**	Clear with retail tag	S2560ST****	Infinity Blue (Anti-Fog)
S2514S***	1.5 IR Filter	S2565S**	Purple Haze
S2515S***	Coffee	S2570S**	Silver Mirror
S2520S***	Gray	S2575S***	Blue Mirror
S2520ST***	Gray (Anti-Fog)	S2580S***	Indoor/Outdoor Mirror
S2520SRT**	Gray with retail tag	S2590S**	Gold Mirror
S2530S***	Amber	S25ARCS**	IR Filter

- Integrated nose piece.
- Soft, non-slip rubber temple tips provide non-binding fit.
- Economical wrap-around single lens provides full panoramic view.
- Lenses are coated for superior scratch resistance, provides 99.9% protection from harmful UV rays.

GENERAL SPECIFICATION

Bridge: 13mm

Lens Base: 10 Curve

Lens Size Diagonal: 64mm

Lens Size Vertical: 44mm

Lens Thickness: 2.5mm

Overall Length (Lens-Tip): 154mm

Overall Width (Hinge-Hinge): 137.5mm

PD: 68mm

Weight: 21gm

PACKAGING



















Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

ZTEK®**LIGHTWEIGHT POLYCARBONATE ONE PIECE SPECTACLE**

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Attractive & stylish unitary lens
Frame	Polycarbonate	Matted finish integral to lens
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	V bridge - integral to lens
Temple	Polycarbonate	Matte finish - straight back design
Temple Tips	PVC	Soft to prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S2510S	 Clear	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2510ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2510SRT	 Clear with retail tag	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2514S	 1.5 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2515S	 Coffee	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2520S	 Gray	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2520ST	 Gray (Anti-Fog)	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2520SRT	 Gray with retail tag	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2530S	 Amber	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2540S	 Orange	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2560S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2560ST	 Infinity Blue (Anti-Fog)	P Z87 + U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2565S	 Purple Haze	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2570S	 Silver Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2575S	 Blue Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2580S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2590S	 Gold Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S25ARCS	 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices