

1/2" DRIVE SCREWDRIVER BIT SOCKETS

- › Made of heat-treated alloy steel.
- › Ball detent.

	Size	Product #	Tip Width (in)	Overall Length (in)	Weight (lbs)
Slotted	7/16"	⊖ J5407A	1/16	3-5/32	0.2
	1/2"	⊖ J5408A	5/64	3-5/32	0.22
	5/8"	⊖ J5409A	3/32	3-5/32	0.27
Phillips	#2	⊕ J5402	2-5/32	2-5/32	0.19
	#3	⊕ J5403	2-5/32	2-5/32	0.18
	#4	⊕ J5404	2-5/32	2-5/32	0.19



1/2" DRIVE HEX BIT SOCKETS

- › Bit holders have a hex opening to hold the bit allowing the bit holder to take the full load of torque.
- › Made of heat-treated alloy steel.
- › Polished chrome finish.

	INCH	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)
STANDARD	1/4	J54411/4	1-3/4	3-1/4	0.19
	5/16	J54415/16	1-3/4	3-1/4	0.22
	3/8	J54413/8	1-3/4	3-1/4	0.25
	7/16	J54417/16	1-3/4	3-1/4	0.28
	1/2	J54411/2	1-7/8	3-5/8	0.46
	9/16	J54419/16	1-7/8	3-5/8	0.50
	5/8	J54415/8	2	4	0.85
	3/4	J54413/4	2	4	0.92
EXTRA LONG	1/4	J54411/4XL	3-1/8	4-5/8	0.20
	5/16	J54415/16XL	4-1/8	5-5/8	0.29
	3/8	J54413/8XL	4-1/8	5-5/8	0.42
	1/2	J54411/2XL	5-3/8	7-1/8	0.60
	9/16	J54419/16XL	5-3/8	7-1/8	0.77
	5/8	J54415/8XL	5-3/16	7-3/16	0.86



	MM	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)
STANDARD	6	J5441-6M	1-3/4	3-1/4	0.20
	8	J5441-8M	1-3/4	3-1/4	0.22
	10	J5441-10M	1-3/4	3-1/4	0.26
	12	J5441-12M	1-3/4	3-1/4	0.29
	13	J5441-13M	1-7/8	3-41/64	0.46
	14	J5441-14M	1-7/8	3-41/64	0.50
	15	J5441-15M	1-7/8	3-41/64	0.50
	17	J5441-17M	2	4	0.87
	18	J5441-18M	2	4	0.90
	19	J5441-19M	2	4	0.94
	EXTRA LONG	12	J5441-12MXL	5-5/8	7-1/8
14		J5441-14MXL	5-3/8	7-1/8	0.75
17		J5441-17MXL	5-1/8	7-1/8	1.20

