



No.	Size	Width	Spread	Per Unit	Shipping Wt. Lbs.	Duty
T7404	4'	21-1/2"	36-1/8"	4.5	21.5	375 lbs. Load Capacity - Type IAA
T7406	6'	25"	50-1/8"	7.3	30.0	375 lbs. Load Capacity - Type IAA
T7408	8'	28-1/2"	64-1/8"	10.5	40.5	375 lbs. Load Capacity - Type IAA
T7410	10'	32"	78-1/4"	14.2	51.5	375 lbs. Load Capacity - Type IAA
T7412	12'	35-1/2"	92-1/4"	18.3	63.5	375 lbs. Load Capacity - Type IAA
T7414	14'	39"	106-1/4"	22.8	86.0	300 lbs. Load Capacity - Type IA
T7416	16'	42-1/8"	120-1/4"	27.7	103.5	300 lbs. Load Capacity - Type IA
T7418	18'	46"	136-1/8"	33.1	126.0	300 lbs. Load Capacity - Type IA
T7420	20'	49-1/2"	150-1/8"	38.8	149.0	300 lbs. Load Capacity - Type IA

++ Designed for one or two person jobs. Note: When used as a double stepladder, the maximum load per side, including person and materials, shall not exceed the duty rating of ladder.

## Dimensions

2				
Top:	8-1/4" x 14-1/2"	Steps:	3" wide	
Rails:	3-1/8" wide	Flange:	1-3/16" wide	

## **Associated Accessories**

21 - Grating Shoes

http://wernerladder.com/catalog/details.php PDF created with pdfFactory Pro trial version www.pdffactory.com



Why Werner | About Us | FAQs | ProZone | Legal Notices | Site Map | Contact Us Visit Werner's Image Database ©2004 Werner Co. All rights reserved.