



Zebra® Advanced Desktop Printers



GK420t™ (direct thermal/ thermal transfer)
GK420d™ (direct thermal)
GT800™ (direct thermal/ thermal transfer)



Advanced, Affordable and Flexible

Zebra's advanced line of desktop printers features professional-quality, reliable printing at a competitive price. Dependable performance and advanced features — along with fast print speeds, network manageability and easy-load designs — enable users to improve operational efficiencies, boost profitability and reduce downtime.

The advanced line is flexible, making it a top choice for a variety of mid-volume and distributed-printing applications. Reliably producing quality text, barcodes or graphics, the advanced line offers three connectivity interfaces and easy upgrades with ZPL® and EPL™ programming languages.

The GK420t and GT800 offer direct thermal and thermal transfer printing power in sleek and compact designs. The GT800 features a 300-meter ribbon for fewer ribbon changes along with a standard moveable sensor. Additional GT800 options include 300 dpi and a full-width cutter or peel dispenser. The GK420d offers only direct thermal printing.

Ideal for space-constrained environments, these printers have a small footprint and clamshell design. Simplify setup and operation with an easy ribbon-loading system and auto calibration. Affordable quality and reliable performance make these printers an excellent choice for companies worldwide.

Ideal for These Applications

- **Healthcare**
 - Patient identification
 - Pharmacy and product labeling
- **Retail**
 - Price marking
 - Coupon and receipt printing
 - Inventory and product labeling
- **Transportation & Logistics**
 - Shipping labels
- **Hospitality & Leisure**
 - Boarding passes
 - Bag tags
- **Security**
 - Visitor ID
 - Evidence tracking
 - Parking passes

SPECIFICATIONS AT A GLANCE*

Printer Name

GK420t
GK420d
GT800 (not available in North America)

Standard Features

- Print methods: Thermal transfer or direct thermal
- Programming language: EPL™ and ZPL® are standard construction: Dual-wall frame
- Tool-less printhead and platen replacement
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Auto-calibration of media
- Triple connectivity: USB, Parallel, Serial
- 300 meter ribbon capacity (GT800 Model only)
- 32bit RISC processor (GT800 Model only)
- Certified Microsoft® Windows® drivers
- ENERGY STAR® qualified

Printer Specifications

Resolution

- 203dpi/8dots per mm
- Optional 300dpi/12dots per mm (GT800 Model only)

Memory

- GT800 Model: 8MB Flash, 8MB SDRAM
- G-Series GK Models: 4MB Flash, 8MB SDRAM (standard)

Print Width

4.09"/104mm

Maximum Print Length

39"/991mm

Maximum Print Speed

- 5"/127mm per second (203dpi)
- 4"/102mm per second (300dpi, GT800 Model only)

Media Sensors

- GT800 Model: Multi-position transmissive and full-width reflective sensor
- G-Series GK Models: Fixed reflective and transmissive sensors

Media Characteristics

- Maximum Media Roll Size: 5"/127mm O.D. on a 1"/25.4mm, 1.5"/38mm I.D. core
- Media Thickness: 0.003~0.007"/0.08~0.18mm

GT800 Model:

- Media Width: 0.75~4.49"/19~114mm
- Media Length: 0.25~39"/6.5~991mm
- Media Types: Roll-fed or fan-fed, die cut or continuous direct thermal labels with or without black line, tag stock, continuous receipt paper, wristbands, and liner-free direct thermal media

G-Series GK Models:

- Maximum Label and Liner Length: Maximum non-continuous: 39"/991mm
- Maximum non-continuous: 39"/991mm
- Maximum Label and Liner Width: 0.75~4.25"/19~108mm
- Media Types: Roll-fed or fan-fed, die-cut or continuous direct thermal labels with or without black line, tag stock, continuous receipt paper, wristbands

Ribbon Characteristics

GT800 Model

- Outside Diameter: 2.6"/66mm (300m); 1.34"/34mm (74m)
- Standard Length: 984'/300m; 244'/74m
- Ratio: – 1:4 media to roll to ribbon (300m) – 1:1 media to roll to ribbon (74m)
- Width: 1.33"~4.3"/33.8~110mm
- Core I.D.: – 300m ribbon 1"/25.4mm – 74m ribbon 0.5"/12.7mm

G-Series GK Models

- Outside diameter: 1.36"/35mm
- Standard length: 244'/74m
- Ratio: 1:1 media to roll to ribbon
- Width: 1.33~4.3"/33.8~109.2mm
- Core inner diameter: 0.5"/12.7mm

Operating Characteristics

Environmental

- Operating Temperature: 40~105°F/4.4~41°C
- Storage Temperature: -40~140°F/-40~60°C
- Operating Humidity: 10% ~ 90% non-condensing
- Storage Humidity: 5% ~ 95% non-condensing

Electrical

- Auto-detectable (PFC Compliant) 100-240VAV, 50-60Hz
- ENERGY STAR qualified printers

Agency Approvals

GT800 Model:

- TUV-R NRTL, TUV-R CB, NOM, KCC, CE, FCC Class-B

G-Series GK Models:

- Emissions: FCC Part 15, Subpart B (Class B), ICES 003, VCCI, C-Tick, CQC, EAC, KCC, BSMI, ICES-003
- Emissions and Susceptibility: EN55022 (Class B), EN55024, EN61000-3-2, EN61000-3-3
- Safety: CB Scheme IEC 60950-1, TUV NRTL, C-Tick, CCC, NOM, EAC, KCC, BSMI, BIS

Physical Characteristics

GT800 Model:

Width: 7.75"/197mm
Height: 7.25"/184mm
Depth: 10.75"/273mm
Weight: 5.8 lbs/2.63kg

G-Series GK Models:

	(Direct Thermal)	(Thermal Transfer)
Width:	6.75"/171mm	7.6"/193mm
Height:	6"/152mm	7.5"/191mm
Depth:	8.25"/210mm	10"/254mm
Weight:	3 lbs/1.4kg	4.6 lbs/2.1kg

Fonts/ Graphics/ Symbologies

Fonts and Character Sets

- 16 resident expandable ZPL fonts
- One resident scalable ZPL font
- 5 resident expandable EPL2 fonts
- Supports user-defined fonts and graphics — including custom logos (GT800 Model)
- Native open type font support (G-Series GK Models)
- Unicode™ compliant for multi-language, on-demand thermal printing (G-Series GK Models)

Options and Accessories

- Dispenser: Label peel and present with label present sensor
- Full-width cutter (GT800 Model)
- ZebraNet 10/100 Print Server: Internal Ethernet for network communication and printing
- ZKDU™ and KDU Plus™ keyboard display units for stand-alone printing solutions
- Font Packs: Asian and other international font kits (G-Series GK Models)
- 300dpi/12dots per mm (GT800 Model)

Barcode Symbologies

- Bar Code Ratios: 2:1 (non-rotated) and 3:1
- Linear Bar Codes: Codabar, Code 11 (ZPL), Code 128, Code 39, Code 93, Code 93, EAN-13, EAN-8, EAN-14 (ZPL), German Post Code (EPL), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, Japanese Postnet (EPL), ISBT-128 (ZPL), Logmars (ZPL), MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, and GS1 Databar (formerly RSS)
- 2-Dimensional: Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, QR Code, PDF417, MicroPDF417, Aztec (for EPL and ZPL except where noted)

Communication and Interface Capabilities

- Centronics® Parallel (36pin) connector ports
- RS-232 Serial interface
- USB V1.1 interface, bi-directional
- Optional Ethernet: 10/100 internal (replaces Serial and Parallel ports in G-Series GK Models; replaces Parallel port in GT800 Model)

ZebraLink™ Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- ZBI-Developer™

GT800 Model:

- Zebra Setup Utilities

G-Series GK Models:

- ZebraDesigner Windows Driver
- POS Driver

Networking Options

Ethernet: 10/100 internal (optional)

Firmware

- ZPL II®
- EPL2™
- Web View
- Alert

GT800 Model:

- ZBI 2.0™ (optional)

G-Series GK Models:

- EPL Line Mode (direct thermal only)
- ZBI™



ZEBRA

www.zebra.com

ASIA-PACIFIC HEADQUARTERS

Zebra Technologies Asia Pacific Pte Ltd

71 Robinson Road, #05-01/02/03, Singapore 068895 T: 65 6858 0722 F: 65 6885 0838

Asia-Pacific Sales Representations: Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, New Zealand, Philippines, South Korea, Singapore, Thailand, Taiwan, Vietnam

Other Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom

Latin America: Brazil, Florida (LA Headquarters in USA), Mexico

Middle East & Africa: Dubai, South Africa

(4/15)AP

*Specifications subject to change without notice. ©2015 ZIH Corp. All rights reserved. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZPL, ZPL II and ZebraNet are registered trademarks of ZIH Corp. All rights reserved. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Centronics is a registered trademark of Centronics Data Computer Corporation. ENERGY STAR and the ENERGY STAR mark are registered marks owned by the U.S. government. All other trademarks are the property of their respective owners.