

## Semipneumatic Wheels

▪ Black tread on silver steel hub



Tire Sidewall No.	Wheel Dia.	Wheel Width	Hub Width	Fits Axle	Cap.	Tread	Hub Type	Item No.
<b>Lawn Mower and Equipment Tires</b>								
6x1.5	6"	1 1/2"	1 3/4"	1/2"	55 lb.	Ribbed	Symmetrical	1NXA6
	6"	1 1/2"	1 3/4"	1/2"	50 lb.	Diamond	Offset	1NXA2
7x1.75	6"	1 1/2"	1 3/4"	1/2"	55 lb.	Diamond	Offset	1NXA1
	7"	1 1/2"	1 3/4"	1/2"	55 lb.	Diamond	Offset	1NXA3
8x1.75	8"	1 3/4"	1 3/4"	1/2"	60 lb.	Ribbed	Symmetrical	1NXA7
	8"	1 3/4"	2 1/8"	1/2"	150 lb.	Ribbed	Symmetrical	1NXA8
	8"	1 3/4"	1 3/4"	1/2"	55 lb.	Diamond	Offset	1NXA4
10x1.75	8"	1 3/4"	1 3/4"	1/2"	60 lb.	Diamond	Offset	1NXA5
	10"	1 3/4"	1 1/2"	1/2"	80 lb.	Ribbed	Symmetrical	1NXA9
10x2.75	10"	2 3/4"	3 1/4"	5/8"	300 lb.	Ribbed	Symmetrical	1NWZ1
	10"	2 3/4"	2 3/4"	5/8"	200 lb.	Ribbed	Symmetrical	1NXC1
12x1.75	10"	2 3/4"	2 3/4"	5/8"	200 lb.	Ribbed	Symmetrical	1NXC2
	12"	1 3/4"	1 1/2"	1/2"	90 lb.	Ribbed	Symmetrical	1NXB1
12x3	12"	3"	3 1/4"	5/8"	140 lb.	Ribbed	Symmetrical	1NXC3
	12"	3"	3 1/4"	3/4"	185 lb.	Ribbed	Symmetrical	1NXC4
14x1.75	14"	1 3/4"	2 1/8"	1/2"	100 lb.	Ribbed	Symmetrical	1NXB2
	14"	1 3/4"	2 1/8"	5/8"	175 lb.	Ribbed	Symmetrical	1NXB3
<b>Wheelbarrow and Cart Tires</b>								
16x4	16"	4"	4"	1"	450 lb.	Ribbed	Symmetrical	1NWZ8
	16"	4"	6"	3/4", 5/8"	450 lb.	Ribbed	Symmetrical	1NWZ9



## Solid Rubber Wheels



Tire Sidewall No.	Wheel Dia.	Wheel Width	Hub Length	Fits Axle	Load Rating	Tread	Tread Color	Hub Type	Hub Material	Item No.
<b>Cart Casters</b>										
6x2	6"	2"	2 1/16"	1/2"	250 lb.	Centipede	Black	Centered	Steel	53CM75
8x2	8 3/16"	2 3/32"	2 1/16"	1/2"	300 lb.	Centipede	Black	Centered	Steel	53CM76
4.10/3.50-4	10"	3 5/8"	2 1/4"	5/8"	390 lb.	Ribbed	Black	Offset	Steel	53CM78
10x2.75	10 3/32"	2 1/16"	2 1/4"	5/8"	500 lb.	Ribbed	Black	Offset	Steel	53CM72
4.10/3.50-4	10 3/16"	3 1/64"	2 1/4"	5/8"	390 lb.	Centipede	Black	Offset	Steel	53CM77
<b>Hand Trucks and Cart Casters</b>										
6x2	6"	2"	2 1/2"	1/2"	200 lb.	Ribbed	Black	Symmetrical	Steel	1NWY3
	6"	2"	2 1/4"	5/8"	200 lb.	Ribbed	Black	Symmetrical	Steel	1NXB4
	6"	2"	2 1/4"	5/8"	200 lb.	Ribbed	Black	Offset	Steel	1NXB5
	6"	2"	2 1/4"	5/8"	300 lb.	Ribbed	Black	Symmetrical	Steel	1NWY7
	6"	2"	2 1/4"	3/4"	250 lb.	Ribbed	Black	Symmetrical	Steel	1NXB6
	6"	2"	2 1/4"	3/4"	250 lb.	Ribbed	Black	Offset	Steel	1NXB7
8x2.5	8"	2 1/2"	3"	1/2"	350 lb.	Ribbed	Black	Symmetrical	Steel	1NWY4
	8"	2 1/2"	2 3/4"	5/8"	250 lb.	Ribbed	Black	Symmetrical	Steel	1NXB8
	8"	2 1/2"	2 3/4"	5/8"	350 lb.	Ribbed	Black	Symmetrical	Steel	1NWY8
	8"	2 1/2"	2 3/4"	3/4"	250 lb.	Ribbed	Black	Symmetrical	Steel	1NXB9
	8"	2 1/2"	2 3/4"	3/4"	350 lb.	Ribbed	Black	Symmetrical	Steel	1NWY9
	8"	2 1/2"	2 1/2"	5/8"	400 lb.	Ribbed	Black	Symmetrical	Steel	1NWZ4
8x2	8"	2"	2 1/4"	5/8"	400 lb.	Ribbed	Black	Offset	Steel	1NWZ5
	8"	2"	2 1/4"	5/8"	500 lb.	Ribbed	Black	Offset	Plastic	16V338
	8"	2"	2 1/4"	1/2"	280 lb.	Centipede	Black	Symmetrical	Steel	16V340
10x2.5	9 5/64"	2 25/64"	2 1/4"	3/4"	550 lb.	Ribbed	Black	Offset	Plastic	40N435
	9 5/64"	2 25/64"	3 1/4"	5/8"	550 lb.	Ribbed	Black	Centered	Plastic	40N436
	9 5/64"	2 25/64"	3 1/4"	3/4"	550 lb.	Ribbed	Black	Centered	Plastic	40N437
4.10/3.50-4	10"	3 1/2"	2 1/4"	5/8"	440 lb.	Centipede	Black	Offset	Steel	16V341
12x3	11 5/64"	2 5/64"	3 1/4"	5/8"	600 lb.	Ribbed	Black	Centered	Plastic	40N438
	11 5/64"	2 5/64"	3 1/4"	3/4"	600 lb.	Ribbed	Black	Centered	Plastic	40N439
<b>Lawn Mower and Equipment Tires</b>										
10x2.75	10"	2 3/4"	2 1/4"	5/8"	450 lb.	Ribbed	Black	Offset	Plastic	1NWZ6
	10"	2 3/4"	3 1/4"	5/8"	450 lb.	Ribbed	Black	Symmetrical	Steel	1NWZ7
	10"	2 3/4"	3 1/2"	1/2"	350 lb.	Ribbed	Black	Symmetrical	Steel	1NWY5
	10"	2 3/4"	3"	3/4"	300 lb.	Ribbed	Black	Symmetrical	Steel	1NWZ2
12x3	12"	3"	3 1/2"	1/2"	540 lb.	Ribbed	Black	Symmetrical	Steel	1NWY6
	12"	3"	3 1/4"	3/4"	300 lb.	Ribbed	Black	Symmetrical	Steel	1NWZ3



## Fixed-Height Floor Locks



Use w/Caster Size (in.)	Mounting Height	Retracted Height (in.)	Plate Size	Bolt Hole Spacing (in.)	Mounting Bolt Dia. (in.)	Mounting Plate Thickness (in.)	Item No.
<b>Economical</b>							
4	5 5/8"	4 7/8"	4" x 4 1/2"	2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	16V371
5	6 1/2"	5 3/4"	4" x 4 1/2"	—	3/8"	1/4"	16V372
6	7 1/2"	6 3/4"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	16V373
8	9 1/2"	8 3/4"	4" x 4 1/2"	—	3/8"	1/4"	16V374
<b>Heavy Duty</b>							
4	5 5/8"	4 7/8"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VP58
5	6 1/2"	5 3/4"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VP59
6	7 1/4"	6 1/2"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VP60
6	7 1/2"	6 3/4"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VR15
6	8"	7"	5" x 7 1/4"	Slotted for 3 5/8 x 5 1/4 or 4 1/8 x 6 1/8	1/2"	1/4"	5VR26
8	9 1/2"	8 3/4"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VP61
8	10 1/8"	9 3/8"	4" x 4 1/2"	Slotted for 2 5/8 x 3 5/8 or 3 x 3	3/8"	1/4"	5VR16
8	10 1/2"	9 1/2"	5" x 7 1/4"	Slotted for 3 5/8 x 5 1/4 or 4 1/8 x 6 1/8	1/2"	1/4"	5VR27



## Adjustable, Side-Mount, and Low-Profile Floor Locks



Description	Use w/Caster Size (in.)	Mounting Height	Retracted Height	Overall Size	Bolt Hole Spacing (in.)	Mounting Bolt Dia. (in.)	Mounting Plate Thickness (in.)	STEEL Item No.	STAINLESS STEEL Item No.
Adjustable	4, 5 and 6	6 1/4" to 8"	5 1/2" to 7 1/4"	4 1/2" x 6 1/2"	Slotted for 3 5/8 x 5 1/4,	3/8"	3/8"	1VJN4	2EMZ8
Adjustable	6 and 8	8 1/4" to 11 1/2"	6 1/4" to 9 1/2"	4 1/2" x 6 1/2"	3 x 3 and 2 1/8 x 4 3/4	3/8"	3/8"	1VJN5	2EMZ9
Low-Profile	—	4 9/16"	3 3/4"	3 3/4" x 5 1/2"	4 - 1/2 x 4 - 3/8	3/8"	3/8"	2GWZ8	—
Heavy-Duty Short Foot Pedal	6	8"	6 3/8"	6" x 4 1/2"	—	1/2"	3/4"	16D135	—
Heavy-Duty Long Foot Pedal	6	8"	6 3/8"	6" x 4 1/2"	5 X 2 1/2"	1/2"	3/4"	16D136	—

