

Hose fittings – Reusable


SAE 100R5 style

For use with hose:
1503, 2580, 2651, FC234,
FC300, FC321, FC350,
FC355, FC802

100R5 style

Male pipe


412-
44-412-



Dash size	Hose size	Thread	A		D		EØ	
			mm	in	mm	in	mm	in
412-								
†2-4S*	-04	1/8-27	42,7	1.68	23,4	.92	4,3	0.17
†4-4S*	-04	1/4-18	47,2	1.86	28,2	1.11	4,3	0.17
2-5S*	-05	1/8-27	45,2	1.78	25,4	1.00	5,8	0.23
†4-5S*	-05	1/4-18	49,8	1.96	30,0	1.18	5,8	0.23
†4-6S*	-06	1/4-18	54,1	2.13	31,2	1.23	7,6	0.30
†6-6S*	-06	3/8-18	54,1	2.13	31,2	1.23	6,1	0.24
†6-8S*	-08	3/8-18	63,0	2.48	33,8	1.33	9,9	0.39
†8-8S*	-08	1/2-14	69,3	2.73	40,1	1.58	9,1	0.36
†8-10S*	-10	1/2-14	73,2	2.88	40,4	1.59	12,2	0.48
12-10S*	-10	3/4-14	74,7	2.94	41,9	1.65	12,2	0.48
†12-12S*	-12	3/4-14	82,3	3.24	42,4	1.67	15,5	0.61
†12-16S	-16	3/4-14	71,1	2.80	38,9	1.53	20,8	0.82
†16-16S	-16	1-11 1/2	75,9	2.99	43,7	1.72	20,8	0.82
†16-20S	-20	-11 1/2	81,3	3.20	46,7	1.72	24,1	0.95
†20-20S	-20	1 1/4-11 1/2	82,0	3.23	47,5	1.87	26,7	1.05
†20-24S	-24	1 1/4-11 1/2	90,9	3.58	53,8	2.12	32,5	1.28
†24-24S	-24	1 1/2-11 1/2	88,4	3.48	51,6	2.03	32,5	1.28
†32-32S	-32	2-11 1/2	102,9	4.05	55,9	2.20	44,5	1.75
44-412-								
40-40	-40	2 1/2-8	127,8	5.03	79,5	3.13	53,8	2.12
48-48	-48	3-8	129,3	5.09	81,0	3.19	68,3	2.69

Male pipe

4412-



Dash size	Hose size	Thread	A		D		EØ	
			mm	in	mm	in	mm	in
4412-								
2-4S	-04	1/8-27	42,7	1.68	23,6	.93	3,3	0.13
4-4S	-04	1/4-18	47,5	1.87	28,4	1.12	3,3	0.13
4-5S	-05	1/4-18	49,8	1.96	30,0	1.18	4,3	0.17
4-6S†	-06	1/4-18	54,1	2.13	31,2	1.23	6,1	0.24
6-6S	-06	3/8-18	54,1	2.13	31,2	1.23	5,8	0.23
4-8S	-08	1/4-18	63,0	2.48	33,8	1.33	7,6	0.30
6-8S	-08	3/8-18	63,0	2.48	33,8	1.33	9,1	0.36
8-8S	-08	1/2-14	69,3	2.73	40,1	1.58	9,1	0.36
8-10S	-10	1/2-14	73,2	2.88	40,4	1.59	11,7	0.46
12-10S	-10	3/4-14	74,7	2.94	41,9	1.65	11,7	0.46
8-12S	-12	1/2-14	82,3	3.24	42,7	1.68	12,4	0.49
12-12S	-12	3/4-14	82,3	3.24	42,4	1.67	14,0	0.55

*Requires tools for assembly

† Also supplied in brass. To order, substitute "B" for "S" in part number

††† Available in stainless steel. To order, drop the "S" suffix and add "259-" prefix

Note: For correct socket part number, see page I-3.