www.huyett.com



# 1/4"-28 **SAE-LT**


EXCEEDS 12 HR SALT SPRAY. 8,000 PSI MAX PRESSURE. **SAE J534** 

A common sight on automobile chassis, 90° angle fittings are often used when overhead access is impractical. As with all angled fittings, care should be taken to ensure proper orientation of the greasing nipple to the access point.

#### HISII

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

90° Angle 1/4"-28 Taper Thread Standard Shank




## **1911-B**1 **1 1911-B**1 **1 1911-B**1

- JDT806 + available in STAINLESS
- + AVAILABLE IN BRASS
- + AVAILABLE IN MONEL®

#### HISIIN


90° Angle 1/4"-28 Taper Thread Standard Shank



NO BALL CHECK


#### HITSO

90° Angle 1/4"-28 Taper Thread Long Shank



#### H700259

90° Angle 1/4"-28 Taper Thread Short Shank



L 100259


ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
HI9II 💥	1/4"-28	90	.75″	.20"	.10"	.66"	.25"	.47"	3/8"
HISIIN	1/4"-28	90	.75"	.20"	.10"	.68"	.25"	.49"	3/8"
HIT90	1/4"-28	90	.80"	.30"	.22"	.69"	.25"	.50"	3/8"
H700259	1/4"-28	90	.75″	.16"	.10"	.66"	.25"	.47"	3/8"

### DESIGN FEATURE



THREAD SEALANT IS AUTOMATICALLY ADDED ON MOST DESIGNS, YIELDING A LEAK-FREE PERFORMANCE









John Deere® is a registered trademark of Deere and Company, Moline, Illinois.