


Submittal: SDDPB0616Z



STRONG-POINT[®] PHILLIPS BUGLE HEAD, ZINC PLATED

Size	Part#	Pt.	Case Qty.	Description
6-20 x 1	D610Z	2	10M	Phillips Bugle Head, Zinc Plated
6-20 x 1-1/8	D611Z	2	10M	Phillips Bugle Head, Zinc Plated
6-20 x 1-1/4	D614Z	2	8M	Phillips Bugle Head, Zinc Plated
6-20 x 1-5/8	D615Z	2	5M	Phillips Bugle Head, Zinc Plated
6-20 x 1-7/8	D617Z	2	4M	Phillips Bugle Head, Zinc Plated

Application: Attaches gypsum, insulation and wood to metal.
Drill Capacity (in.): .035 - .090

- Specifications:
- Meets ASTM¹ C 1513 for cold-formed steel framing connections
 - Meets ASTM A 510 for carbon steel manufacturing
 - Meets ASTM C 954 for attaching track to steel studs
 - Manufactured to SAE² J78 for dimensional specifications
 - Meets F.I.P.³-1000.7 for torsional strength and drill speed
 - Meets ASTM F1941 for corrosion resistance

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. Do not over torque as it can cause the head to snap or stripping of the recess. The bugle head fastener is properly seated when the head sits flush or slightly countersunk with the sheathing surface. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)									
Fastener		Steel Gauge							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
6-20	2	126	218	366	496	825	1004		

Shear Values (Avg. Lbs.)									
Fastener		Steel Gauge (Lapped)							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
6-20	2	444	721	875	912				

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)

²(Society of Automotive Engineers)

³(Fastener Inspection Products)

D610Z_D617Z_Rev. A (8/28/17)