



# MT500-4, 5 TON TWO SPEED ELECTRIC TROLLEY 3-PHASE 460V

144190

JET® MT Series Electric Trolley is designed and built for safety, durability, and efficient operation in the toughest industrial applications. Designed with two speeds you can move materials quickly and safely. Allowing your material to then slow down to be placed exactly where you need it without the excessive bump firing. All of this with safe travel speeds up to 79 feet per minute and as low as 20 feet per minute to give you the ability to be more efficient with every load. The MT series is available from 1/2 Ton to 5 Ton capacities. Let's Get to Work.



## FEATURES

- Heavy-Duty motor puts out up to 0.8HP making it the strongest in it's class
- TAA Approved
- Two speeds reduces bump firing to while still allowing high speed movement of materials
- Indoor and Outdoor use with IP-55 rating for trolley and IP-65 rating for the pendant
- Expanded flange capacity kits are available



## JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

# STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE



# MT500-4, 5 TON TWO SPEED ELECTRIC TROLLEY 3-PHASE 460V

144190

## SPECIFICATIONS

Capacity (Lbs.)	1100
Load Capacity (Tons)	5
Maximum Beam Flange Width (In.)	7
Wheel Diameter (In.)	1-3/4
Minimum Beam Curve Radius (In.)	78.7
Minimum Beam Flange Width (In.)	5
Weight (Lbs.)	196
Motor (HP)	0.2 / 0.8
Motor Phase	3
Motor Voltage (V.)	460



# STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE