

540A SERIES CARRIAGE C-CLAMPS

INDUSTRY'S CLASSIC DESIGN



OSCILLATING HEAD



SLIDING CROSS
PIN HANDLE




DUCTILE IRON FRAMES




140 SERIES CARRIAGE C-CLAMPS

LIGHT INDUSTRIAL



DUCTILE IRON FRAMES



EXTRA DEEP REACH
DESIGN



BLACK OXIDE COATING



FEATURES

DUCTILE IRON FRAMES:

- Rugged frames designed for maximum clamping pressure

CLASSIC DESIGN:

- Most popular C-Clamp for over 50 years

BLACK OXIDE COATING:

- Spindles and pads are treated to resist corrosion

OSCILLATING HEAD:

- High quality steel pad is built to last and provide firm gripping action on angular surfaces

IDEAL FOR

- Light Industrial
- Home Craftsman
- Woodworking
- Repair

Stock No.	Model	Nominal Opening Capacity (in.)	Throat Depth (in.)	Clamping Force (lbs.)	Spindle Size (in.)	Net Weight (lbs.)
540 SERIES CARRIAGE						
22001	540A-2-1/2	0 – 2-1/2	1-3/4	1,110	1/2	1
22002	540A-3	0 – 3	1-7/8	1,800	1/2	2
22003	540A-4	0 – 4	2-1/16	2,150	5/8	2
22004	540A-5	0 – 5	2-1/2	2,250	5/8	2
22005	540A-6	0 – 6	2-3/4	2,450	5/8	3
22006	540A-8	0 – 8	3-1/4	2,750	3/4	5
22007	540A-10	0 – 10	3-5/8	2,850	7/8	7
22008	540A-12	0 – 12	3-5/8	2,850	7/8	9
22009	540A-14	0 – 14	3-3/4	2,850	7/8	10

FEATURES

DEEP REACH PATTERN:

- Provided maximum depth for applications requiring increased throat capacity

DUCTILE IRON FRAMES:

- Rugged frames designed for maximum clamping pressure

BLACK OXIDE COATING:

- Spindle and pads are treated to resist corrosion

IDEAL FOR

- Light Industrial
- Home Craftsman
- Woodworking
- Repair

Stock No.	Model	Nominal Opening Capacity (in.)	Throat Depth (in.)	Clamping Force (lbs.)	Spindle Size (in.)	Net Weight (lbs.)
140 SERIES STANDARD CARRIAGE						
41411	141C	0 – 1	1-1/16	645	1/4	1
41416	141-1/2C	0 – 1-1/2	1-1/2	820	5/16	1
41421	142C	0 – 2	1-1/8	800	5/16	1
41423	1422C	0 – 2-1/2	1-7/16	850	3/8	1
41426	142-1/2C	0 – 2-1/2	2-1/2	1,005	3/8	1
41405	143C	0 – 3	2	1,430	3/8	1
41406	144C	0 – 4	2-3/4	1,535	1/2	1
41407	145C	0 – 5	3	1,225	5/8	2
41408	146C	0 – 6	3-1/4	1,400	5/8	3
41409	148C	0 – 8	4	1,700	3/4	4
DEEP REACH CARRIAGE						
42510	251	0 – 1	3	350	1/4	1
42520	252	0 – 2	3-1/2	450	5/16	1
42525	252-1/2	0 – 2-1/2	4	600	3/8	1
42530	253	0 – 3	4-1/2	700	7/16	2
XTRA DEEP REACH CARRIAGE						
42450	245	2-1/2	4-3/4	1,600	7/16	2
42460	246	2-1/2	6-1/4	1,600	7/16	2