


Vinyl Insulated Ring Terminals

NEW
BULK PACKS



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
10010	RED	22-16	#4	.126	.217	.197	.736	.441	.157	.067	.031	100	1,000
10012	RED	22-16	#6	.146	.260	.248	.811	.441	.157	.067	.031	100	1,000
10012B	RED	22-16	#6	.148	.260	.248	.811	.441	.157	.067	.031	1,000	20,000
10014	RED	22-16	#8	.169	.315	.276	.866	.441	.157	.067	.031	100	1,000
10014B	RED	22-16	#8	.169	.315	.276	.866	.441	.157	.067	.031	1,000	20,000
10016	RED	22-16	#10	.209	.315	.276	.866	.441	.157	.067	.031	100	1,000
10016B	RED	22-16	#10	.209	.315	.276	.866	.441	.157	.067	.031	1,000	20,000
10018	RED	22-16	1/4	.252	.457	.433	1.102	.441	.157	.067	.031	100	1,000
10020	RED	22-16	5/16	.331	.457	.433	1.102	.441	.157	.067	.031	100	1,000
10022	RED	22-16	3/8	.413	.535	.547	1.248	.441	.157	.067	.031	100	1,000
10023	RED	22-16	1/2	.512	.772	.630	1.441	.441	.157	.067	.031	100	1,000
10024	RED	22-16	9/16	.591	1.063	.827	1.791	.441	.157	.067	.031	100	1,000
10026	RED	22-16	5/8	.669	1.063	.827	1.791	.441	.157	.067	.031	100	1,000
10028	RED	22-16	3/4	.827	1.063	.827	1.791	.441	.157	.067	.031	100	1,000
10030	BLUE	16-14	#4	.126	.260	.189	.760	.453	.177	.091	.031	100	1,000
10032	BLUE	16-14	#6	.146	.260	.248	.823	.453	.177	.091	.031	100	1,000
10032B	BLUE	16-14	#6	.146	.260	.248	.823	.453	.177	.091	.031	1,000	20,000
10034	BLUE	16-14	#8	.169	.335	.307	.917	.453	.177	.091	.031	100	1,000
10034B	BLUE	16-14	#8	.169	.335	.307	.917	.453	.177	.091	.031	1,000	20,000
10036	BLUE	16-14	#10	.209	.335	.307	.917	.453	.177	.091	.031	100	1,000
10036B	BLUE	16-14	#10	.209	.335	.307	.917	.453	.177	.091	.031	1,000	20,000
10038	BLUE	16-14	1/4	.252	.472	.433	1.114	.453	.177	.091	.031	100	1,000
10038B	BLUE	16-14	1/4	.252	.472	.433	1.114	.453	.177	.091	.031	1,000	20,000
10040	BLUE	16-14	5/16	.331	.472	.433	1.114	.453	.177	.091	.031	100	1,000
10042	BLUE	16-14	3/8	.413	.535	.547	1.260	.453	.177	.091	.031	100	1,000
10044	BLUE	16-14	1/2	.512	.756	.630	1.453	.453	.177	.091	.031	100	1,000
10046	BLUE	16-14	9/16	.591	1.063	.827	1.803	.453	.177	.091	.031	100	1,000
10048	BLUE	16-14	5/8	.669	1.063	.827	1.803	.453	.177	.091	.031	100	1,000
10050	BLUE	16-14	3/4	.827	1.063	.827	1.803	.453	.177	.091	.031	100	1,000
10060	YELLOW	12-10	#6	.146	.283	.240	.937	.555	.248	.134	.039	100	1,000
10062	YELLOW	12-10	#8	.169	.283	.240	.937	.555	.248	.134	.039	100	1,000
10064	YELLOW	12-10	#10	.209	.374	.327	1.024	.555	.248	.134	.039	100	1,000
10064B	YELLOW	12-10	#10	.209	.374	.327	1.024	.555	.248	.134	.039	500	10,000
10066	YELLOW	12-10	1/4	.252	.472	.413	1.205	.555	.248	.134	.039	100	1,000
10066B	YELLOW	12-10	1/4	.252	.472	.413	1.205	.555	.248	.134	.039	500	5,000
10068	YELLOW	12-10	5/16	.331	.591	.524	1.382	.555	.248	.134	.039	100	1,000
10070	YELLOW	12-10	3/8	.413	.591	.524	1.382	.555	.248	.134	.039	100	1,000
10070B	YELLOW	12-10	3/8	.413	.591	.524	1.382	.555	.248	.134	.039	500	5,000
10072	YELLOW	12-10	1/2	.512	.756	.630	1.563	.555	.248	.134	.039	100	1,000
10074	YELLOW	12-10	9/16	.591	1.260	.992	2.177	.555	.248	.134	.039	100	1,000
10076	YELLOW	12-10	5/8	.669	1.260	.992	2.177	.555	.248	.134	.039	100	1,000
10078	YELLOW	12-10	3/4	.827	1.260	.992	2.177	.555	.248	.134	.039	100	1,000