

Nylon Insulated Ring Terminals

NEW
BULK PACKS



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50


MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
11312	RED	22-16	#4	.126	.216	.197	.728	.433	.157	.067	.030	100	1,000
11314	RED	22-16	#6	.146	.260	.248	.803	.433	.157	.067	.030	100	1,000
11314B	RED	22-16	#6	.146	.260	.248	.803	.433	.157	.067	.030	1,000	20,000
11316	RED	22-16	#8	.169	.315	.276	.858	.433	.157	.067	.030	100	1,000
11316B	RED	22-16	#8	.169	.315	.276	.858	.433	.157	.067	.030	1,000	20,000
11318	RED	22-16	#10	.209	.315	.276	.858	.433	.157	.067	.030	100	1,000
11320	RED	22-16	1/4	.252	.457	.433	1.094	.433	.157	.067	.030	100	1,000
11322	RED	22-16	5/16	.331	.457	.433	1.094	.433	.157	.067	.030	100	1,000
11324	RED	22-16	3/8	.413	.535	.547	1.240	.433	.157	.067	.030	100	1,000
11326	RED	22-16	1/2	.512	.756	.630	1.433	.433	.157	.067	.030	100	1,000
11328	RED	22-16	9/16	.591	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
11330	RED	22-16	5/8	.669	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
11332	RED	22-16	3/4	.827	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
11334	BLUE	16-14	#4	.126	.260	.189	.740	.433	.177	.091	.031	100	1,000
11336	BLUE	16-14	#6	.146	.260	.248	.803	.433	.177	.091	.031	100	1,000
11338	BLUE	16-14	#8	.169	.335	.307	.898	.433	.177	.091	.031	100	1,000
11338B	BLUE	16-14	#8	.169	.335	.307	.898	.433	.177	.091	.031	1,000	20,000
11340	BLUE	16-14	#10	.209	.335	.307	.898	.433	.177	.091	.031	100	1,000
11340B	BLUE	16-14	#10	.209	.335	.307	.898	.433	.177	.091	.031	1,000	20,000
11342	BLUE	16-14	1/4	.252	.472	.433	1.094	.433	.177	.091	.031	100	1,000
11342B	BLUE	16-14	1/4	.252	.472	.433	1.094	.433	.177	.091	.031	1,000	10,000
11344	BLUE	16-14	5/16	.331	.472	.433	1.094	.433	.177	.091	.031	100	1,000
11346	BLUE	16-14	3/8	.413	.535	.547	1.240	.433	.177	.091	.031	100	1,000
11348	BLUE	16-14	1/2	.512	.756	.630	1.433	.433	.177	.091	.031	100	1,000
11350	BLUE	16-14	9/16	.591	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
11352	BLUE	16-14	5/8	.669	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
11354	BLUE	16-14	3/4	.827	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
11356	YELLOW	12-10	#6	.146	.283	.240	.894	.512	.252	.134	.039	100	1,000
11358	YELLOW	12-10	#8	.169	.283	.240	.894	.512	.252	.134	.039	100	1,000
11358B	YELLOW	12-10	#8	.169	.283	.240	.894	.512	.252	.134	.039	500	10,000
11360	YELLOW	12-10	#10	.209	.374	.329	1.024	.512	.252	.134	.039	100	1,000
11360B	YELLOW	12-10	#10	.209	.374	.329	1.024	.512	.252	.134	.039	500	10,000
11362	YELLOW	12-10	1/4	.252	.472	.413	1.161	.512	.252	.134	.039	100	1,000
11362B	YELLOW	12-10	1/4	.252	.472	.413	1.161	.512	.252	.134	.039	500	10,000
11364	YELLOW	12-10	5/16	.331	.591	.524	1.339	.512	.252	.134	.039	100	1,000
11366	YELLOW	12-10	3/8	.413	.591	.524	1.339	.512	.252	.134	.039	100	1,000
11368	YELLOW	12-10	1/2	.512	.756	.630	1.520	.512	.252	.134	.039	100	1,000
11370	YELLOW	12-10	9/16	.591	1.260	.992	2.134	.512	.252	.134	.039	100	1,000
11372	YELLOW	12-10	5/8	.669	1.260	.992	2.134	.512	.252	.134	.039	100	1,000
11374	YELLOW	12-10	3/4	.827	1.260	.992	2.134	.512	.252	.134	.039	100	1,000

WIRE MANAGEMENT

Ring Terminals

D15