

# Nylon Insulated Ring Terminals



## MAXIMUM ELECTRIC CURRENT:

AWG	8	6	4	2
AMP	70	95	125	170


**MAXIMUM ELECTRIC RATING:** 221°F (105°C) 600 Volts

**INSULATION MATERIAL:** Nylon

**TERMINAL MATERIAL:**

Electro-Tin Plated Copper - Brazed Seam

**FEATURES:** Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY
11376	RED	8	#6	.146	.315	.366	1.142	.630	.315	.177	.047	100
11378	RED	8	#8	.169	.472	.366	1.232	.630	.315	.177	.047	100
11380	RED	8	#10	.209	.472	.366	1.232	.630	.315	.177	.047	100
11382	RED	8	1/4	.252	.472	.366	1.232	.630	.315	.177	.047	100
11384	RED	8	5/16	.331	.591	.543	1.469	.630	.315	.177	.047	100
11386	RED	8	3/8	.413	.591	.543	1.469	.630	.315	.177	.047	100
11388	RED	8	1/2	.512	.787	.591	1.614	.630	.315	.177	.047	100
11390	BLUE	6	#8	.169	.472	.524	1.606	.846	.433	.228	.059	100
11392	BLUE	6	#10	.209	.472	.524	1.606	.846	.433	.228	.059	100
11394	BLUE	6	1/4	.252	.472	.524	1.606	.846	.433	.228	.059	100
11396	BLUE	6	5/16	.331	.630	.559	1.713	.846	.433	.228	.059	100
11398	BLUE	6	3/8	.413	.630	.559	1.713	.846	.433	.228	.059	100
11400	BLUE	6	7/16	.453	.866	.780	2.047	.846	.433	.228	.059	100
11402	BLUE	6	1/2	.512	.866	.780	2.047	.846	.433	.228	.059	100
11404	YELLOW	4	#8	.169	.480	.594	1.780	.945	.512	.303	.067	100
11406	YELLOW	4	#10	.209	.480	.594	1.780	.945	.512	.303	.067	100
11408	YELLOW	4	1/4	.252	.480	.614	1.772	.945	.512	.303	.067	100
11410	YELLOW	4	5/16	.331	.650	.531	1.791	.945	.512	.303	.067	100
11412	YELLOW	4	3/8	.413	.650	.531	1.791	.945	.512	.303	.067	100
11414	YELLOW	4	7/16	.453	.866	.776	2.146	.945	.512	.303	.067	100
11416	YELLOW	4	1/2	.512	.866	.776	2.146	.945	.512	.303	.067	100
11418	RED	2	#10	.209	.602	.685	2.047	1.063	.571	.370	.071	100
11420	RED	2	1/4	.252	.602	.685	2.047	1.063	.571	.370	.071	100
11422	RED	2	5/16	.331	.602	.685	2.047	1.063	.571	.370	.071	100
11424	RED	2	3/8	.413	.602	.685	2.047	1.063	.571	.370	.071	100
11426	RED	2	7/16	.453	.866	.697	2.193	1.063	.571	.370	.071	100
11428	RED	2	1/2	.512	.866	.697	2.193	1.063	.571	.370	.071	100

WIRE MANAGEMENT Ring Terminals