


Non-Insulated Flange Spade Terminals



MAXIMUM ELECTRIC CURRENT:

| | | | | | | | |
|-----|----|----|----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP | 9 | 12 | 17 | 18 | 30 | 35 | 50 |

MAXIMUM ELECTRIC RATING: 302°F (150°C) 600V


TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Brazed Seam, Serrated Barrel

DIMENSIONS = INCHES

| CAT. NO. | WIRE SIZE AWG | STUD SIZE | D2 | W | F | L | E | D | DI | A | T | BAG QTY | MASTER BAG QTY |
|----------|---------------|-----------|------|------|------|------|------|------|------|------|------|---------|----------------|
| 11761 | 22-16 | #2 | .087 | .252 | .205 | .551 | .189 | .134 | .067 | .059 | .030 | 100 | 1,000 |
| 11742 | 22-16 | #4 | .126 | .252 | .201 | .551 | .189 | .134 | .067 | .059 | .030 | 100 | 1,000 |
| 11744 | 22-16 | #6 | .146 | .252 | .201 | .551 | .189 | .134 | .067 | .059 | .030 | 100 | 1,000 |
| 11746 | 22-16 | #8 | .169 | .335 | .283 | .768 | .189 | .134 | .067 | .059 | .030 | 100 | 1,000 |
| 11748 | 22-16 | #10 | .209 | .295 | .201 | .551 | .189 | .134 | .091 | .059 | .030 | 100 | 1,000 |
| 11750 | 16-14 | #6 | .146 | .295 | .205 | .571 | .189 | .161 | .091 | .059 | .031 | 100 | 1,000 |
| 11752 | 16-14 | #8 | .169 | .315 | .266 | .728 | .189 | .161 | .091 | .059 | .031 | 100 | 1,000 |
| 11754 | 16-14 | #10 | .209 | .335 | .283 | .709 | .189 | .161 | .134 | .059 | .031 | 100 | 1,000 |
| 11756 | 12-10 | #6 | .146 | .299 | .244 | .728 | .236 | .220 | .134 | .059 | .039 | 100 | 1,000 |
| 11758 | 12-10 | #8 | .169 | .335 | .295 | .787 | .236 | .220 | .134 | .059 | .039 | 100 | 1,000 |
| 11760 | 12-10 | #10 | .209 | .299 | .244 | .728 | .236 | .220 | .134 | .059 | .039 | 100 | 1,000 |

Vinyl Insulated Flange Spade Terminals



MAXIMUM ELECTRIC CURRENT:

| | | | | | | | |
|-----|----|----|----|----|----|----|----|
| AWG | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP | 9 | 12 | 17 | 18 | 30 | 35 | 50 |

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600V

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

| CAT. NO. | COLOR | WIRE SIZE AWG | STUD SIZE | D2 | W | F | L | E | D | DI | A | T | BAG QTY | MASTER BAG QTY |
|----------|--------|---------------|-----------|------|------|------|-------|------|------|------|------|------|---------|----------------|
| 11762 | RED | 22-16 | #4 | .126 | .252 | .201 | .795 | .441 | .157 | .067 | .059 | .030 | 100 | 1,000 |
| 11764 | RED | 22-16 | #6 | .146 | .252 | .201 | .795 | .441 | .157 | .067 | .059 | .030 | 100 | 1,000 |
| 11766 | RED | 22-16 | #8 | .169 | .335 | .283 | 1.012 | .441 | .157 | .067 | .059 | .030 | 100 | 1,000 |
| 11768 | RED | 22-16 | #10 | .209 | .295 | .201 | .795 | .441 | .157 | .067 | .059 | .030 | 100 | 1,000 |
| 11770 | BLUE | 16-14 | #6 | .146 | .295 | .205 | .827 | .453 | .177 | .091 | .059 | .031 | 100 | 1,000 |
| 11772 | BLUE | 16-14 | #8 | .169 | .315 | .266 | .728 | .453 | .177 | .091 | .059 | .031 | 100 | 1,000 |
| 11774 | BLUE | 16-14 | #10 | .209 | .335 | .283 | .965 | .453 | .177 | .091 | .059 | .031 | 100 | 1,000 |
| 11776 | YELLOW | 12-10 | #6 | .146 | .299 | .244 | 1.047 | .555 | .248 | .134 | .059 | .039 | 100 | 1,000 |
| 11778 | YELLOW | 12-10 | #8 | .169 | .335 | .295 | 1.106 | .555 | .248 | .134 | .059 | .039 | 100 | 1,000 |
| 11780 | YELLOW | 12-10 | #10 | .209 | .299 | .244 | 1.047 | .555 | .248 | .134 | .059 | .039 | 100 | 1,000 |