

Copper Mechanical Lugs



FIG 1



FIG 2



FIG 3



FIG 4

- Solid One-Piece Copper Connector Made From Extruded or Stamped Electrolytic Copper for Superior Mechanical Strength and Excellent Electrical Performance

- Steel Slotted or Allen-Head Screw
- Suitable For Use With Copper Wire Only
- Rated 600V

DIMENSIONS = INCHES

CAT. NO.	FIG	WIRE RANGE	BOLT SIZE	DIMENSIONS			PAD THICKNESS	SCREW TYPE	BOX QTY
				LENGTH	WIDTH	HEIGHT			
EXTRUDED COPPER - STRAIGHT TANG									
90560	1	6-14	1/4	1.020	5/16	0.375	3/32	1/4" HEX	100
90562	1	4-14	1/4	1.075	0.44	0.45	3/32	1/4" HEX	100
90564	1	2-14	5/16	1.125	0.48	0.458	1/8	1/4" HEX	50
90566	1	1/0-14	7/16	1.277	0.66	0.548	1/8	1/4" HEX	50
90568	1	4/0-2	5/8	1.950	0.95	0.812	7/32	1/4" HEX	10
90593	2	350 MCM-6	9/16	2.00	1.92	1.12	3/16	5/16" HEX	15
COPPER - STRAIGHT & ROUND TANG									
90506	3	6-14	1/4	1.02	0.40	0.375	1/16	SLOTTED	100
90507	3	4-14	5/16	1.075	0.444	0.45	3/32	SLOTTED	100
90550	4	8-14	3/16	1-3/16	0.375	0.375	5/64	SLOTTED	100
90552	4	4-14	1/4	1-1/8	0.50	0.09	3/32	SLOTTED	100
90554	4	1/0-8	5/16	1-1/2	0.75	0.75	3/32	1/4" HEX	50
90556	4	250 MCM-6	3/8	1-15/16	0.93	1-.063	1/8	1/4" HEX	25

Copper Mechanical OffSet Lugs



FIG 1

- Manufactured from High Strength Pure Electrolytic Copper to Insure Both Maximum Strength and Conductivity
- Arched Pressure Bar and V-bottom Collar Positions the Wire for Positive Contact and Maximum Reliability
- Steel Plated Screws/Bolts Prevent Rusting
- Easy to Install with Screwdriver, Wrench or Pliers
- Copper Finish
- Rated 600 Volts

DIMENSIONS = INCHES

CAT. NO.	FIG	AMP RATING	WIRE RANGE	LENGTH	WIDTH	HEIGHT	HOLE SIZE	BOX QTY
SINGLE CONDUCTOR OFF-SET								
90514	1	35A	6-14	1.19	0.38	0.50	0.19	100
90515	1	70A	4-14	1.31	0.50	0.56	0.27	100
90516	1	90A	2-8	1.55	0.50	0.65	0.36	50
90518	1	125A	1/0-2	1.97	0.63	0.88	0.27	50
90520	1	175A	3/0-4	2.19	0.75	1.03	0.41	25
90522	1	225A	4/0-2	2.38	1.00	1.17	0.34	25
90524	1	300A	350 MCM-1/0	3.16	1.00	1.39	0.41	18
90526	1	400A	500 MCM-1/0	4.25	1.50	1.57	0.41	3