



Provoq® ANSI CSA



Soft nosepiece
Rubber temples

| Part No. | Lens and Temples |
|-----------------|---------------------|
| S7210S ●● | Clear |
| S7210ST ●● | AF Clear |
| S7220S ●● | Gray |
| S7220ST ●● | AF Gray |
| S7230S ●● | Amber |
| S7240S ●● | Orange |
| S7255S ●● | Multi-Color Mirror |
| S7260S ●● | Infinity Blue |
| S7270S ●● | Silver Mirror |
| S7275S ●● | Blue Mirror |
| S7280S ●● | I/O Mirror |
| S7280ST ●● | AF I/O Mirror |
| Part No. | Pink Temples |
| SP7210ST ●● | AF Clear |



There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (◐) standards. For specific lens options visit our website or contact your sales representative.

Provoq®

General Specifications

Weight: 24.9 gm
 PD: 64 mm
 Bridge: 16.66 mm
 Lens base: 9 curve
 Lens size diagonal: 79.83 mm
 Lens size vertical: 41.12 mm
 Lens thickness: 2.4 mm
 Overall length (lens - tip): 158 mm
 Overall width (hinge - hinge): 136 mm
 Closest point between temple tips: 79.35 mm
 Closest point between lens: 8.18 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: plated steel
 Temple Tip: thermoplastic rubber (TPR)
 Nosepiece: thermoplastic rubber (TPR)

| Part No. | Lens Markings | Frame Markings |
|----------|-----------------|------------------------------------|
| S7210S | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7210ST | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7220S | P Z87 + U6 L3 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7220ST | P Z87 + U6 L3 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7230S | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7240S | P Z87 + S | P Z87 + |
| S7255S | P Z87 + S | P Z87 + |
| S7260S | P Z87 + S | P Z87 + |
| S7270S | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S7275S | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S5880S | P Z87 + U6 L1.7 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S5880ST | P Z87 + U6 L1.7 | P Z87 + |
| SP7210ST | P Z87 + U6 | P Z87 + |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L3: 18% Max. Visible Light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

