

INTREPID II®

Eye Protection Without Distraction



Black Temples

Part	Lens
SB8810S	Clear
SB8820S	Gray
SB8830S	Amber
SB8835S	Sun Block Bronze
SB8880S	Indoor/Outdoor Mirror






- Suitable for both working environments and sports activities.
- Thin, soft flange of the extra wide nosepiece distributes weight of the glass evenly across the bridge, eliminating pressure on the nose.
- Flexible rubber temples generate a soft cushion for pressure-free fit behind the ear, and secure the eyewear from shifting out of place.
- Maximum eye protection, and ultra-light design ideal for all-day versatility.
- Scratch-resistant, polycarbonate lens provides 99.9% of UV protection.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

GENERAL SPECIFICATION

Bridge: 14.1mm
Closest Point Between Lens: N/A
Closest Point Between Temple Tips: 83mm
Lens Base: 6.5 Curve
Lens Size Diagonal: 145.2mm
Lens Size Vertical: 50.6mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 172mm
Overall Width (Hinge-Hinge): 136.4mm
PD: 68mm
Weight: 30gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6.5 base wrap around lens
Parts	Polycarbonate	Secured with lens with screws
Nose Piece	Polycarbonate	Soft nose pad slips on hard nose piece, universal fit
	TPE	
Temples	Polycarbonate	Co-injected soft temple tips for comfort
	TPE	
Hinge	Polycarbonate	3 barrel type
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8810S	 Clear	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8820S	 Gray	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8830S	 Amber	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8835S	 Sun Block Bronze	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8880S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA standard for protection devices