



Chemical Division

TECHNICAL DATA SHEET

STICK-KUTTM

Description:

Relton's Stick-Kut is a blended wax stick designed for use in applications where liquid coolants are not feasible or desirable. It comes packaged in a convenient push-up cartridge that is easy to apply and eliminates spilling and evaporation. Stick-Kut can extend tool life, reduce loading, stop binding, and prevent burring in a variety of applications.

Typical Uses

- Manual application on rotating or stationary cutting tools, grinding wheels or belts
- Use on aluminum, brass, plastic, ferrous and non-ferrous materials.
- Lubricates band saws to leave a clean, smooth cut
- Eliminates grinding wheel heat build-up and extends wheel life
- Reduces loading of sanding belts
- Extends tool life in tapping, drilling, milling, reaming, cutting, forming, etc.

Typical Inspections:

Appearance/Form: Light beige, waxy solid; waxy odor

VOC: 0.00 Flash Point: 400°F Melting Point, (°F): 140-145 Specific Gravity: . 89

Features:

- 1. Contains EP agents for anti-weld properties
- 2. Retains its lubrication properties longer than liquid products
- 3. Non-gumming
- 4. Reduces heat and improves surface finishes
- 5. Does not contain ingredients identified as hazardous
- 6. Will not stain aluminum