

# PRO300S Decking System



**Applications:** Decking on decks and docks, subfloor to wood or steel, wall plates, stair treads, sheathing, fiber-cement siding to steel

- Expanded depth settings for high-density flooring materials
- Reversible and replaceable non-skid teeth
- Uniform toenailing and countersink on slick surfaces
- Sure-grip guide tube increases stability for a broad range of screws
- The patented curved collation strips (U.S. Patent 7,051,875) hold the screws up and away from the work surface, making moving and positioning the tool easier. They are also pointed on the inserted end to simplify loading.

*Limited lifetime warranty on attachment and extension, 1-year limited warranty on screw-driver motors (see specific manufacturer's warranty for more information)*



**The PRO300S System includes:**

- PRO300S Decking Attachment (also sold separately)
- Extension for stand-up driving
- Choice of Makita® or DeWalt® screwdriver motors
- Screw quiver for keeping screws at your fingertips
- Rugged tool case to protect your equipment on the jobsite
- Decking nose clip for accurate and consistent fastening

*The decking nose clip positions the screw on the deck board and centers it on the joist for an easy, uniform installation from a standing position.*

# PRO300S System

C-F-2017 © 2017 SIMPSON STRONG-TIE COMPANY INC.

Drive These Collated Screws	
Deck-Drive™ DSV Wood Screw	p. 256
Deck-Drive™ DWP Wood SS Screw	p. 257
Deck-Drive™ DHPD Hardwood Screw	p. 257
Strong Drive® WSNTL Wood Screw	p. 267
Trim-Head Screw: Type 17 Point	p. 259
Trim-Head Screw: Sharp Point	p. 258
Bugle-Head Wood Screw	p. 259
CBSDQ Sheathing-to-CFS Screw	p. 281
Strong Drive® WSV Subfloor Screw	p. 267
Deck-Drive™ DCU Composite Screw	p. 265

System Options	Model No.
DeWalt® 2,500 rpm screwdriver motor	PRO300SD25K
Makita® 2,500 rpm screwdriver motor	PRO300SM25K
Makita® 3,500 rpm screwdriver motor	PRO300SM35K
Parts	Model No.
Attachment only	QDPRO300SG2
Replacement attachment mandrel	PMANDREL75

For more information on screwdriver motors and RPM recommendations per application, see pp. 244–245.