

Nylon Self-Locking Ty-Rap® Cable Ties

Temperature Rating: -40°F to 185°F. Flammability Rating: UL 94 V-2.

- ▶ Low Profile Head — Won't Slip, Won't Snag
- ▶ Non-Magnetic Stainless Steel Lock Maintains the Right Tension
- ▶ Smooth Molded Body — Less Stress Sensitive than Notched Ties
- ▶ Adjustable Design So Always the Right Size and Bundle Tightness
- ▶ NEC Approved for Use in Plenums (Actual Air-Carrying Metal Duct in the Ceiling Space)
- ▶ UL and CSA Approved



Standard Nylon Ty-Rap® Cable Ties

Cable ties made from natural nylon 6/6 are excellent performers in most applications.

Body Width (In.)	Length (In.)	Max. Wire Bundle Dia. (In.)	Tensile Strength (Lbs.)	Stock No.	Mfr.'s Type	Pkg. Qty.	EACH		Stock No.	Mfr.'s Type	Pkg. Qty.	EACH	
							1-4	5-9				1-4	5-9
0.091	3.62	0.625	18	70092869	TY523M	100	8.77	7.90	70092874	TY23M	1000	31.81	28.65
0.091	7.00	1.500	18	70092879	TY52315M	100	13.61	12.26	70092883	TYB2315M	1000	67.42	60.73
0.091	8.00	2.000	18	70092887	TY5232M	100	13.88	12.50	70092892	TY232M	1000	47.54	42.82
0.091	14.00	4.000	18	70092896	TY524M	100	13.88	12.50	70092900	TY234M	1000	91.11	82.07
0.140	5.50	1.125	40	70092904	TY524M	100	12.19	10.98	70092909	TY24M	1000	37.69	33.95
0.140	8.19	2.000	40	70092922	TY5242M	100	18.07	16.27	70092926	TY242M	1000	55.32	49.83
0.140	11.08	3.000	40	70092931	TY525M	100	22.82	20.56	70092936	TY25M	1000	112.89	101.69
0.140	14.50	4.000	40	70092948	TY5244M	100	33.73	30.38	70092953	TY244M	1000	190.17	171.30
0.184	7.31	1.750	50	70092958	TY525M	100	14.64	13.19	70092959	TY25M	1000	69.50	62.60
0.184	11.60	3.000	50	70092962	TY5253M	100	31.74	28.59	70092964	TY253M	1000	132.43	119.29
0.184	14.20	4.000	50	70092966	TY528M	100	35.70	32.16	70092967	TY28M	1000	158.71	142.96
0.270	8.00	2.000	120	70092970	TY5272M	50	20.56	18.52	70092970	TY272M	500	196.39	176.90
0.270	13.38	3.500	120	70092972	TY527M	50	15.40	13.88	70092973	TY27M	500	162.59	146.46
0.270	18.00	5.000	120	70093086	TY5275M	50	37.41	33.70	70093087	TY275M	500	293.12	264.03
0.270	18.00	7.000	120	70091834	TY5277M	50	44.71	40.27	70091812	TY277M	500	109.79	105.94
0.301	30.00	9.000	120	70092976	TY529M	50	56.96	51.30	70092977	TY29M	500	396.68	357.31
0.320	35.00	10.000	175	70091840	TY53510M	25	76.63	69.03	—	—	—	—	—

Black Weather Resistant Nylon Ty-Rap® Cable Ties

Recommended for outdoor use — Black ties have good UV resistance and this prolongs the useful life of the tie.

Body Width (In.)	Length (In.)	Max. Wire Bundle Dia. (In.)	Tensile Strength (Lbs.)	Stock No.	Mfr.'s Type	Pkg. Qty.	EACH		Stock No.	Mfr.'s Type	Pkg. Qty.	EACH	
							1-4	5-9				1-4	5-9
0.091	3.62	0.625	18	70092870	TY523MX	100	12.52	11.27	70092875	TY23MX	1000	49.62	44.69
0.091	7.00	1.500	18	70091829	TY52315MX	100	19.83	17.86	—	—	—	—	—
0.091	8.00	2.000	18	70092888	TY5232MX	100	19.83	17.86	70092893	TY232MX	1000	70.88	63.85
0.091	14.00	4.000	18	70092890	TY5234MX	100	19.83	17.86	70091809	TY234MX	1000	123.44	111.19
0.140	5.50	1.125	30	70092914	TY524MX	100	16.15	14.54	70092918	TY24MX	1000	51.17	46.09
0.140	8.19	2.000	30	70092923	TY5242MX	100	24.01	21.63	70092927	TY242MX	1000	68.46	61.67
0.140	11.10	3.000	30	70092939	TY526MX	100	29.23	26.33	70092943	TY26MX	1000	158.71	142.96
0.140	14.50	4.000	30	70091832	TY5244MX	100	39.49	35.57	70091810	TY244MX	1000	252.41	227.36
0.184	7.31	1.750	50	70092960	TY525MX	100	17.86	16.09	70092961	TY25MX	1000	70.54	63.54
0.184	11.60	3.000	50	70092963	TY5253MX	100	37.69	33.95	70092965	TY253MX	1000	189.82	170.99
0.184	14.20	4.000	50	70092968	TY528MX	100	38.98	35.12	70092969	TY28MX	1000	243.59	219.42
0.270	8.75	2.000	120	70091833	TY5272MX	100	19.84	17.87	70092971	TY272MX	500	160.17	144.28
0.270	13.40	3.500	120	70092974	TY527MX	50	25.79	23.23	70092975	TY27MX	500	188.44	169.74
0.270	18.00	5.000	120	70093088	TY5275MX	50	39.45	35.54	70093089	TY275MX	500	353.28	318.22
0.270	24.30	7.000	120	70091835	TY5277MX	50	42.50	38.29	—	—	—	—	—
0.301	30.00	9.000	120	70091837	TY529MX	50	67.85	61.11	—	—	—	—	—
0.320	35.00	10.000	175	70091842	TY53510MX	25	82.08	73.94	—	—	—	—	—

Cable Straps with Bolt/Screw Holes

Temperature Rating: -40°F to 185°F. Flammability Rating: UL 94 V-2.

Natural Nylon Cable Straps

Cable ties made from natural nylon 6/6 are excellent performers in most applications.

Body Width (In.)	Length (In.)	Max. Wire Bundle Dia. (In.)	Mounting Hole	Tensile Strength (Lbs.)	Stock No.	Mfr.'s Type	Pkg. Qty.	EACH		Stock No.	Mfr.'s Type	Pkg. Qty.	EACH	
								1-4	5-9				1-4	5-9
0.091	4.00	0.625	#4	18	70092978	TY533M	100	24.77	22.32	70092979	TY33M	1000	226.65	204.16
0.140	6.00	1.125	#8	40	70092980	TY534M	100	24.96	22.49	70092981	TY34M	1000	209.53	188.74
0.140	7.80	1.750	#10	50	70092982	TY535M	100	24.98	22.50	70092983	TY35M	1000	175.47	158.06
0.184	14.60	4.000	#10	50	70091843	TY5354M	100	72.01	64.86	70091824	TY354M	1000	560.14	504.55
0.301	13.90	3.500	1/4"	120	70092984	TY537M	50	12.49	11.25	70092985	TY37M	500	277.82	250.25

Black Weather Resistant Nylon Cable Straps

Recommended for outdoor use — Black ties have good UV resistance and this prolongs the useful life of the tie.

Body Width (In.)	Length (In.)	Max. Wire Bundle Dia. (In.)	Mounting Hole	Tensile Strength (Lbs.)	Stock No.	Mfr.'s Type	Pkg. Qty.	EACH		Stock No.	Mfr.'s Type	Pkg. Qty.	EACH	
								1-4	5-9				1-4	5-9
0.091	4.00	0.625	#4	18	70091838	TY533MX	100	29.96	26.99	70091822	TY33MX	1000	280.76	252.90
0.140	6.00	1.125	#8	40	70091839	TY534MX	100	30.98	27.91	70091823	TY34MX	1000	307.90	277.35
0.184	7.80	1.750	#10	50	70091845	TY535MX	100	27.18	24.48	70091827	TY35MX	1000	175.47	158.06
0.184	14.60	4.000	#10	50	70091844	TY5354MX	100	83.57	75.28	70091825	TY354MX	1000	745.12	671.18
0.301	13.90	3.500	1/4"	120	70091848	TY537MX	50	49.42	44.51	70091828	TY37MX	500	325.88	293.54

Identification Cable Ties

These cable ties, made from natural nylon 6/6, can be permanently marked with the marking pens listed on this page and are excellent performers in most applications.

Stock No.	Mfr.'s Type	Max. Wire Bundle Dia. (In.)	Marking Pad Size	Minimum Unlocking Strength (Lbs.)	Cable Type	Length (In.)	Width (In.)	PKG./100	
								1-4	5-9
70092986	TY546M	1.750	5.000 × 0.875	50	Standard	7.25	0.184	45.62	41.10
70091850	TY546MT*	1.750	1.210 × 1.000	50	Standard	7.25	0.184	80.51	72.52
70092987	TY548M	4.000	5.000 × 2.125	50	Standard	14.20	0.184	62.38	56.19
70091852	TY553M	0.625	0.813 × 0.359	18	Miniature	4.00	0.091	24.81	22.35
70092988	TY5512M	2.000	1.000 × 0.313	18	Miniature	8.30	0.094	35.70	32.16

*Package of 50.

Ty-Gun™ Cable Tie Tool — Ergonomic Design



- ▶ 360° Rotating Nose for Use in Any Position
- ▶ Light-Weight (8.5 Oz.) with Adjustable Handle Span to Fit Large and Small Hands
- ▶ Anti-Recoil Mechanism, Reduces Vibration Shock

Stock No.	Mfr.'s Type	Tie Width (In.)	Wt. (Lbs.)	EACH
70092282	ERG50	0.094-0.184	18-50	218.66
70092283	ERG120	0.184-0.301	50-120	402.05

Hand Tools

Model WT193A



Pistol-type easy tension adjustment. Cuts tails off flush.

Stock No.	Mfr.'s Type	Description	EACH
70039940	WT193A	0.094"-0.184" width ties	200.11

Models WT1-TB and WT2-TB

Compact hand tool made of high-impact plastic. Pre-set tension. Cuts off flush. Lightweight and economical.



Stock No.	Type	Description	EACH
70039941	Type WT1-TB	0.094"-0.184" width ties	29.61
70039942	Type WT2-TB	0.184"-0.301" width ties	40.42



TY546MT