

VARDEX

Advanced Threading Solutions

MAIN CATALOG

Thread Turning

Thread Milling

INCH

VARGUS is a world leading developer, manufacturer and supplier of high-quality, precision threading, grooving, turning and hand deburring tools.

Established in 1960, VARGUS is the cutting tools division of the NEUMO Ehrenberg Group, a multinational organization headquartered in Germany.

With 13 international subsidiaries, and a network of distributors, warehouses and certified ISO 9001 manufacturing facilities, VARGUS Ltd. serves customers in more than 100 countries around the globe. A customer-focused organization, VARGUS Ltd. is committed to providing products and solutions of the highest quality and excellent value, and is renowned for its technical expertise and uncompromising service.

COMPANY PRODUCTS:

VARDEX
Advanced Threading Solutions is the company's prominent product line for Thread Turning, Thread Milling, and Gear Milling Solutions.

Thread Turning: The VARDEX TT tools offer an extensive collection of pitches and standards in different grades, IC ranges and types of insert styles, as well as customized methods for the oil and gas industry.

Thread Milling: The VARDEX TM line provides a wide range of applications and solutions in multi-tooth, single-tooth for deep holes, and solid carbide tools.

Gear Milling: The VARDEX Gear Milling line is a revolutionary concept for gear, rack and spline applications, offered in indexable inserts and solid carbide tools.

VARGUS GENius™: VARGUS' industry-leading Thread Turning and Thread Milling solutions are seamlessly complimented by the VARGUS GENius™ software – The most powerful tool selector, cutting data and CNC program generating software.

GROOVEX
Innovative Grooving & Turning Solutions, the newest product line by VARGUS, provides innovative solutions for grooving, boring and turning, in a wide range of applications.

SHAVIV
Leading Deburring Solutions, manufactures world leading hand-deburring solutions for metals and plastics.





FLINE

Fixed Clamping System



VRX

Multipurpose Premium Grade



MEGALINE

For Extra Large Pitches



V-CAP Toolholders

Polygon Shaped Shanks



Oil&Gas

Professional Threading Solutions



Mini-3 IC 5.0

Tools for Small Applications



VG-Cut

Machining Between Shoulders



Mini-V

Miniature Vertical Tools



TMSD Vertical

Multi-Flute Vertical Tools



Contents

THREAD TURNING

| | |
|----------------------------|----|
| Thread Turning System..... | 12 |
|----------------------------|----|



Thread Turning Inserts..... 17

| | |
|--------------------------------------|-----|
| Vardex Ordering Code System..... | 18 |
| Partial Profile 60° | 21 |
| Partial Profile 55° | 28 |
| ISO Metric..... | 34 |
| American UN..... | 49 |
| American UNR..... | 62 |
| Whitworth | 63 |
| BSPT | 73 |
| NPT | 76 |
| ANPT..... | 82 |
| NPTF | 83 |
| NPS..... | 87 |
| Round (DIN 405) | 88 |
| Round (DIN 20400)..... | 89 |
| Trapez..... | 93 |
| American ACME..... | 101 |
| American ACME (2G) | 108 |
| Stub ACME | 110 |
| UNJ..... | 115 |
| MJ..... | 120 |
| American Buttress..... | 122 |
| British Buttress..... | 126 |
| Metric Buttress (Sägengewinde) | 127 |
| API..... | 132 |
| API Buttress Casing..... | 134 |
| API Round Casing & Tubing..... | 138 |
| VAM..... | 144 |
| New VAM..... | 146 |
| EL-Extreme Line..... | 148 |
| Hughes H-90..... | 149 |
| Pg..... | 150 |



Thread Turning Toolholders 153

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 154 |
|----------------------------------|-----|

External Toolholders

| | |
|--------------------------------|-----|
| Standard | 156 |
| Standard F-Line | 157 |
| V-CAP..... | 157 |
| Standard with Clamp..... | 158 |
| Oil & Gas..... | 159 |
| U Style | 160 |
| U Style with Clamp..... | 160 |
| Slim Throat..... | 161 |
| VG-Cut..... | 162 |
| V Style..... | 163 |
| Z+ Style | 163 |
| M+ Style..... | 164 |
| F-Line M+ Style..... | 164 |
| T+ Style..... | 165 |
| 14D Standard..... | 165 |
| Off-Set Qualified (FQ)..... | 166 |
| Drop Head-Qualified (CQ) | 166 |
| Miniature Square Shank..... | 167 |
| Miniature Round Shank..... | 167 |

Internal Toolholders

| | |
|--------------------------------|-----|
| Standard | 168 |
| Standard F-Line | 169 |
| V6 Style | 169 |
| V-CAP..... | 170 |
| Standard for Coarse Pitch..... | 171 |
| U Style for Coarse Pitch | 171 |
| Standard with Clamp..... | 172 |
| U Style | 173 |

| | |
|----------------------------------|-----|
| U style with Clamp | 174 |
| V Style | 174 |
| Z+ Style | 175 |
| M+ Style | 175 |
| F-Line M+ Style..... | 176 |
| T+ Style..... | 176 |
| 14D Standard..... | 177 |
| 14D Standard with Clamp..... | 177 |
| Oil & Gas..... | 178 |
| Standard with Carbide Shank..... | 179 |
| Mini-V | 180 |
| Mini-3 Standard..... | 184 |
| Mini-3 U Style | 185 |
| Mini-3 Adjustable..... | 186 |
| Mini-L..... | 186 |
| Mini-L Adjustable | 187 |
| Micro - Double Ended..... | 187 |
| Microscope - Single Ended..... | 188 |



TT Technical Data..... 193

| | |
|--|-----|
| Thread Terminology | 194 |
| Machining a Multi-Start Thread..... | 195 |
| Insert Profile Styles | 195 |
| Thread Turning Methods for Symmetrical Inserts | 196 |
| Thread Infeed Methods..... | 196 |
| Thread Turning Methods for Asymmetrical Inserts | 197 |
| Calculating the Helix Angle | 198 |
| Anvils..... | 199 |
| Oil & Gas Anvils..... | 200 |
| Anvil Kits | 200 |
| Spare Parts..... | 201 |
| Grades and Their Applications..... | 202 |
| Recommended Grades and Cutting Speeds..... | 204 |
| Cutting Conditions Parameters..... | 208 |
| Number of Passes | 209 |
| Depths of Cut and Number of Passes for Mini-V..... | 209 |
| Number of Passes and Depth of Cut for Multi+ | 210 |
| Step by Step Thread Turning..... | 212 |

| | |
|---------------------------------|-----|
| Material Comparison Table | 216 |
| Troubleshooting | 220 |

THREAD MILLING

| | |
|-------------------------------------|-----|
| Thread Milling Systems | 224 |
| Thread Milling Methods..... | 226 |
| The Thread Milling Advantages | 227 |



MiTM..... 229

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 230 |
|----------------------------------|-----|

MiTM Inserts

| | |
|------------------|-----|
| ISO Metric..... | 232 |
| American UN..... | 233 |
| Whitworth | 235 |
| NPT | 236 |
| NPTF | 236 |
| BSPT..... | 237 |
| Plug Insert..... | 237 |

MiTM Toolholders

| | |
|--|-----|
| Standard Toolholders (MiTM 19)..... | 238 |
| Conical Toolholders (MiTM 19) | 239 |
| Standard Toolholders (MiTM 24)..... | 240 |
| Conical Toolholders (MiTM 24) | 241 |
| Standard Toolholders (MiTM 25)..... | 242 |
| Conical Toolholders (MiTM 25) | 243 |
| Shell Mill (MiTM 25)..... | 244 |
| Standard Toolholders (MiTM 40)..... | 245 |
| Shell Mill (MiTM 40)..... | 246 |
| Standard Toolholders (MiTM 41)..... | 247 |
| Shell Mill (MiTM 41)..... | 248 |
| Recommended Grades, Cutting Speeds and Feed | 249 |



STANDARD Thread Milling..... 251

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 252 |
|----------------------------------|-----|

Standard Inserts

| | |
|----------------------|-----|
| ISO Metric..... | 254 |
| American UN..... | 259 |
| UNJ..... | 266 |
| Whitworth | 267 |
| NPT..... | 271 |
| NPTF (Dry Seal)..... | 272 |
| NPS..... | 273 |
| BSPT..... | 274 |
| Pg..... | 275 |
| ACME | 276 |
| Trapez..... | 277 |

Standard Toolholders

| | |
|--|-----|
| TM Standard..... | 278 |
| TML Long Tools..... | 280 |
| 124/... - For Coarse Pitch Threads..... | 282 |
| TMN - For Conical Threads..... | 284 |
| TM2 - Twin Flutes | 286 |
| TMO - Twin Flute Offset | 287 |
| TM Shell Mill | 288 |
| TMS - Single Point (Standard Inserts)..... | 290 |
| TMV - Single Point (Vertical Insert)..... | 290 |
| Recommended Grades, Cutting Speeds and Feed | 291 |



TMSD.....293

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 294 |
|----------------------------------|-----|

TMSD Vertical Inserts

| | |
|--------------------------|-----|
| Partial Profile 60°..... | 296 |
| Partial Profile 55°..... | 297 |
| Trapez..... | 298 |
| Stub ACME | 298 |

TMSD Vertical Toolholders

| | |
|--|-----|
| Vertical Toolholders Weldon Shank | 299 |
| Vertical Toolholders Carbide Cylindrical Shank..... | 300 |

TMSD Inserts

| | |
|--------------------------------|-----|
| Partial Profile 60°..... | 301 |
| Partial Profile 55°..... | 302 |
| ISO Metric..... | 303 |
| American UN..... | 304 |
| NPT..... | 305 |
| Trapez..... | 306 |
| American ACME..... | 307 |
| Stub ACME | 307 |
| American Buttress..... | 308 |
| API Round Casing & Tubing..... | 309 |

TMSD Toolholders

| | |
|---|-----|
| Standard Toolholders Weldon Shank (U Style)..... | 310 |
| Standard Toolholders Carbide Cylindrical Shank (U Style)..... | 312 |
| Standard Toolholders Steel Cylindrical Shank (U Style)..... | 314 |
| Shell Mill (U Style) | 316 |
| Standard Toolholders Weldon Shank (L Style - Mini L)..... | 318 |
| Standard Toolholders Carbide Cylindrical Shank (L Style - Mini L)..... | 320 |
| Standard Toolholders Weldon Shank (L Style - 3/8" L)..... | 322 |
| Standard Toolholders Carbide Cylindrical Shank (L Style - 3/8" L)..... | 323 |
| Shell Mill (L Style - 3/8" L)..... | 324 |
| Shell Mill (5/8" V Style)..... | 325 |
| Standard Toolholders Steel Cylindrical Shank (A Style)..... | 326 |
| Recommended Grades, Cutting Speeds and Feed | 327 |



TM Solid.....329

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 330 |
| Helicool | 332 |
| Helicool-R (HCR)..... | 339 |
| Helicool-C (HCC)..... | 340 |
| HTC (Thriller) | 341 |
| He-Lex..... | 342 |
| Deep Threading | 346 |

| | |
|--|-----|
| MilliPro | 348 |
| MilliPro Dental..... | 352 |
| MilliPro EL..... | 353 |
| MilliPro HD..... | 354 |
| Straight | 356 |
| Recommended Grades, Cutting Speeds and Feed | 364 |



TM Technical Data.....367

| | |
|--|-----|
| About Thread Milling..... | 368 |
| Preparing for the Thread Milling Operation..... | 370 |
| List of "G" Codes (ISO) for CNC Program..... | 371 |
| Minimum Bore Diameters for TM Standard line | 372 |
| Spare Parts..... | 374 |
| Troubleshooting | 376 |

MINI PRO



MiniPro Inserts.....379

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 380 |
|----------------------------------|-----|

PowerBore Inserts

| | |
|--------------------|-----|
| CD0W Inserts | 381 |
| TD0W Inserts..... | 381 |
| WC0W Inserts | 382 |

Micro Boring Inserts

| | |
|---------------------------------|-----|
| Micro Boring - Boring | 383 |
| Micro Boring - Copy..... | 384 |
| Micro Boring - Chamfer..... | 384 |
| Micro Boring - Long Nose..... | 385 |
| Micro Boring - Back Boring..... | 386 |
| Micro Boring - Boredrill..... | 386 |

Micro Grooving Inserts

| | |
|---|-----|
| DIN 472 Retaining Ring Grooves for Bores | 387 |
| CIRCLIP Inch Standard..... | 389 |

| | |
|---------------------------------|-----|
| DIN 7993 Snap Ring Grooves..... | 391 |
| Snap Ring Grooves..... | 392 |
| DIN 3770 - Grooves | 393 |
| CIRCLIP - Face Grooves | 393 |



MiniPro Toolholders.....395

| | |
|----------------------------------|-----|
| Vardex Ordering Code System..... | 396 |
| PowerBore Toolholders..... | 397 |
| Micro Toolholders | 401 |



MiniPro Technical Data.....403

| | |
|--|-----|
| Recommended Grades, Cutting Speeds and Feed | 404 |
| Spare Parts..... | 405 |

VARGUS GENius™ – The most powerful tool selector, cutting data and CNC program generating software for the metal cutting tools industry.

Thread Turning: The Vargus GENius™ guides the user to the right tool and the best cutting conditions for the application.

Thread Milling: In a few simple steps, the Vargus GENius™ provides the user with the best tool and optimal machining data, as well as the G-Code for all popular CNC machines.

The VARGUS GENius™ is free and available in 16 languages in iOS and Android Apps, Online, Desktop, and SETUP versions.

VARGUS GENius™ | Tool Selector and CNC Program Generator

Anywhere! Anytime!

The most popular and advanced thread turning and thread milling software on the market today.



Available in 4 versions at www.vargus.com



- Online interactive software
- Always on, always updated!



- Stand-alone software application
- MS Windows OS-based program
- Automatic updates



- USB memory devices
- MS Windows operating system-based program
- To install, open ZIP and click Setup



- Available for iOS and Android devices
- New responsive design!
- Use on any device, anywhere in the world!

Whether you require a non-standard size, a complex shape or a special design, the Vargus Custom Made Solutions team has the experience and know-how for essentially any tooling solution.


Working closely with the customer, VARGUS engineers provide the best solution for your operation, as well as guide and advise in the implementation of the customized machining process.

The Custom Made Solutions team has all of the know-how to design the right cutting tool, using the latest techniques and top-of-the-line technology.

Contact your VARGUS Sales Representative for more details.



Quality | Innovation | Service



GEAR MILLING

Advanced Technologies for Gear, Spline and Rack Manufacturing



Revolutionary and cost-effective solutions for Gear, Spline & Rack applications, tailor-made to order or available as standard for Spline.


The complete Gear Milling Product Catalog is available at www.vargususa.com



Gear Milling Tool Range



End Mill



Shell Mill



Disc Mill



Solid Carbide



THREAD TURNING

| | |
|------------------------|-----|
| ■ Inserts | 17 |
| ■ Toolholders | 153 |
| ■ Technical Data | 193 |

Thread Turning System - EXTERNAL


Standard




V6



SCB




Standard




Standard with Clamp



V-Cap



Off-Set Qualified



Drop Head-Qualified



Miniature Square Shank




Miniature Round Shank

FLINE




IC 1/2\"/>




F Style

U Style




U Style




U Style with Clamp

V Style



1/4\"/>



Slim Throat

VG-Cut




Monoblock

Thread Turning System - EXTERNAL







V Style



MEGALINE



Multiplus





Oil&Gas




Thread Turning System - INTERNAL

Standard



Standard




Standard with Clamp



V-Cap



6°



Oil & Gas



Carbide Shank



SCB



Miniature Square Shank




Miniature Round Shank

FLINE




F Style

U Style



U Style




U Style with Clamp

V Style




5/8"V



V Style

MEGALINE



5/8"MG



MG Style

Multiplus




M+ Style





FLINE



MF+ Style



Z+ Style




T+ Style

Thread Turning System - INTERNAL

Mini-V



Steel Shank



Carbide Shank



Sleeve Clamping Shank

MINIPRO



Mini-3
 IC 4.0, IC 5.0, IC 6.0



Steel Shank /
 Carbide Implanted Shank



Mini-3 Adjustable



Carbide Shank



Mini-5L



Steel Shank /
 Carbide Implanted Shank



Mini-5L Adjustable

MINIPRO




Micro Double-Ended



Micro Sleeve

microscope



Micro Single-Ended



2 Flats Round Shank



4 Flats Round Shank




Square Shank



Drop Head

Oil&Gas




14D




14D



14D with Clamping



CNGA




Chaser



T+ Style



On Edge



Thread Turning Inserts


Vardex Ordering Code System

■ Threading Inserts

| | | | | | | | | | | | |
|----------|----------|----------|----------|-----------|-----------|----------|----------|----------|-----------|------------|-----------|
| 3 | | E | R | 12 | UN | | | | | VTX | |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |

1 - Insert Size

5LK - IC5.0L mm
 4.0K - IC4.0 mm
 5.0K - IC5.0 mm
 6.0K - IC6.0 mm
 2 - IC1/4"
 3 - IC 3/8"
 4 - IC 1/2"
 5 - IC5/8"
 14D - 14D
 1616 - Chaser size 16x16mm



2 - Insert Style

U  V  MG 
 U Style Vertical Mega Line

L  J  F 
 Mini-L SCB F-Line

3 - Type of Insert

E - External
 I - Internal
 EI - External + Internal

4 - RH/LH Insert

R - Right Hand Insert
 L - Left Hand Insert
 None - Right + Left Insert

5 - Pitch

| Full Profile - Pitch Range | |
|-------------------------------|------------|
| mm | TPI |
| 0.35-25.0 | 72-1 |
| Partial Profile - Pitch Range | |
| mm | TPI |
| A 0.5 - 1.5 | 48 - 16 |
| B 1.75 - 2.0 | 14 - 11 |
| AG 0.5 - 3.0 | 48 - 8 |
| G 1.75 - 3.0 | 14 - 8 |
| N 3.5 - 5.0 | 7 - 5 |
| U 5.5 - 8.0 | 4.5 - 3.25 |
| Q 5.5 - 6.0 | 4.5 - 4 |
| U 6.5 - 9.0 | 4 - 2.75 |
| V 6.0 - 10.0 | 4 - 2.5 |
| S 0.5 - 2.0 | 48 - 13 |

6 - Standard

| | |
|-------------------------------------|-----------------------------------|
| 60 - Partial Profile 60° | STACME - Stub ACME |
| 55 - Partial Profile 55° | UNJ - UNJ |
| ISO - ISO Metric | MJ - ISO 5855 |
| UN - American UN | ABUT - American Buttress |
| UNR - American UNR | BBUT - British Buttress |
| W - Whitworth for BSW, BSP | SAGE - Metric Buttress DIN 513 |
| BSPT - British Standard Pipe Thread | API - API |
| NPT - NPT | BUT - API Buttress Casing |
| ANPT - ANPT | APIRD - API Round Casing & Tubing |
| NPTF - NPTF | VAM - VAM |
| NPS - NPS | NVAM - New Vam |
| RD - Round DIN 405 | EL - Extreme Line Casing |
| RD20400 - Round DIN 20400 | H90 - H90 |
| TR - Trapez DIN 103 | PG - Pg DIN 40430 |
| ACME - ACME | |

7 - No. of Cutting Corners

6C - V6 Cutting Corners

8 - API Form

| |
|-----|
| 382 |
| 383 |
| 403 |
| 502 |
| 503 |
| 652 |

9 - No. of Teeth

(for Multitooth Style)
 2, 3, 5, 6, 8

10 - Multitooth Style

M+  T+ 
 Z+  S+ 

Multi^{plus}

11 - Coarse Pitch Inserts

158/...

12 - Carbide Grade

VKX, VTX, VCB, VM7, VK2, VK2P,
 VHx, VBx, VRx, VTXP, VKXP, VRXP

■ Micro Threading Inserts - Double Ended

| 3 | S | I | R | 0.5 | ISO | VMX | |
|---|---------------------------|---|---------------------------|-----|---|-----|--------------------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
| 1 - Insert Dia. | 2 - Insert Style | | 3 - Type of Insert | | 4 - RH/LH Insert | | 5 - Pitch |
| 3.0 - 3.0 mm 4.0 - 4.0 mm 6.0 - 6.0 mm 8.0 - 8.0 mm 10.0 - 10.0 mm | S - Micro Insert | | I - Internal | | R - Right Hand Insert L - Left Hand Insert | | Full Profile - Pitch Range |
| | | | | | | | mm TPI |
| | | | | | | | 0.30-1.5 40-16 |
| | | | | | | | Partial Profile - Pitch Range |
| | | | | | | | mm TPI |
| | | | | | | | A 0.5 - 1.5 A 48 - 16 |
| | | | | | | | F 0.5 - 3.0 F 48 - 24 |
| 6 - Standard | 7 - Carbide Grades | | | | | | |
| 60 - Partial Profile 60° 55 - Partial Profile 55° ISO - ISO Metric MJ - ISO 5855 NPT - NPT NPTF - NPTF UN - American UN W - Whitworth for BSW, BSP | VMX | | | | | | |

microscope

■ Micro Threading Inserts - Single Ended

| M | 5 | 42 | TH | 0.5 | ISO | L16 | R | VBX |
|--------------------------------|--------------------------------------|-----------|--------------------------------|---|-----|-----|---|-----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 1 - Product Line | 2 - Insert Size [mm] | | 3 - Min. Bore Dia. [mm] | | | | | |
| M, MS - Microscope | 4, 5, 6, 7 | | 3,2, 4,2,... | | | | | |
| 4 - Type of Application | 5 - Pitch (for Threading) | | | 6 - Threading Standard | | | | |
| TH - Threading | Full Profile - Pitch Range | | | 60 - Partial Profile 60° 55 - Partial Profile 55° ISO - ISO Metric UN - American UN W - Whitworth for BSW, BSP NPT - NPT | | | | |
| | mm TPI | | | | | | | |
| | 0.5-1.5 32-16 | | | | | | | |
| | Partial Profile - Pitch Range | | | | | | | |
| | mm TPI | | | | | | | |
| | A | 0.5 - 1.5 | A | 48 - 16 | | | | |
| | F | 0.5 - 1.0 | F | 48 - 24 | | | | |
| 7 - Overhang [mm] | 8 - LH or RH | | | 9 - Carbide Grades | | | | |
| L16 | R - RH Helix L - LH Helix | | | VBX | | | | |

■ CNGA and On Edge Inserts for Oil & Gas

| | | | | | | | | | | |
|----------|----------|----------|----------|----------|----------|----------|----------|----------|--------------|------------|
| C | N | G | A | 6 | 4 | I | R | 5 | BUT75 | VKX |
| T | N | E | C | 4 | 3 | E | R | 4 | APIRD | VKX |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |

| | | | | | | | | | | | | | | | |
|--|--|--|-----------------------|---|---|--|------------------|--|-------------|-----------|-----------|-------------|----------|-----------|--|
| 1 - Insert Shape | 2 - Clearance Angle on Major Cutting Edge | 3 - Tolerances | 4 - Clamp Type | | | | | | | | | | | | |
| | | <table border="1"> <tr> <td>IC</td> <td>S</td> <td>m</td> </tr> <tr> <td>Theoretical diameter of inscribed circle</td> <td>Insert thickness</td> <td></td> </tr> <tr> <td>E ±0.025 mm</td> <td>±0.025 mm</td> <td>±0.025 mm</td> </tr> <tr> <td>G ±0.025 mm</td> <td>±0.13 mm</td> <td>±0.025 mm</td> </tr> </table> | IC | S | m | Theoretical diameter of inscribed circle | Insert thickness | | E ±0.025 mm | ±0.025 mm | ±0.025 mm | G ±0.025 mm | ±0.13 mm | ±0.025 mm | |
| IC | S | m | | | | | | | | | | | | | |
| Theoretical diameter of inscribed circle | Insert thickness | | | | | | | | | | | | | | |
| E ±0.025 mm | ±0.025 mm | ±0.025 mm | | | | | | | | | | | | | |
| G ±0.025 mm | ±0.13 mm | ±0.025 mm | | | | | | | | | | | | | |

| | | | | |
|--|---|--|---|------------------|
| 5 - Theoretical diameter of inscribed circle | 6 - Thickness | 7 - Type of Insert | 8 - RH/LH Insert | 9 - Pitch |
| 4 - 1/2" (12.7 mm) 5 - 5/8" (15.875 mm) 6 - 6/8" (19.05 mm) | 3 - 3/16" (4.76 mm) 4 - 4/16" (6.35 mm) 5 - 5/16" (7.94 mm) 6 - 6/16" (9.525 mm) | E - External I - Internal EI - External + Internal | R - Right Hand Insert L - Left Hand Insert | 10-5 TPI |
| 10 - Standard | | 11 - No. of Teeth | 12 - Carbide Grades | |
| ACME - ACME STACME - Stub ACME API - API BUT - API Buttress Casing APIRD - API Round Casing & Tubing | | (For Multitooth Style) T3-T5 | VKX, VKXP, VTX, VTXP | |

■ VG-Cut Inserts

| | | | | | | | | |
|-----------|----------|------------|-----------|-----------|-----------|----------|-----------|------------|
| VG | D | 3.0 | UN | 12 | RH | - | RS | VPG |
| 1 | 2 | 3 | 4 | 5 | 6 | | 7 | 8 |


| | | | | | | | | | | | |
|---|--------------------------------------|------------------------------|---|---------|----|-----|-------------|--------|----------------------|---|-----|
| 1 - Line Name | 2 - Number of Cutting Corners | 3 - Inserts Width | 4 - Standard | | | | | | | | |
| VG - Deep Grooving, Threading & Parting Off | D - Double | 3.0 mm | 60 - Partial Profile 60° 55 - Partial Profile 55° ISO - ISO Metric UN - American UN W - Whitworth for BSW, BSP NPT - NPT | | | | | | | | |
| 5 - Pitch | 6 - RH/LH Inserts | 7 - Top Rake Geometry | 8 - Carbide Grade | | | | | | | | |
| Full Profile - Pitch Range <table border="1"> <tr><td>mm</td><td>TPI</td></tr> <tr><td>0.5-2.0</td><td>32-11.5</td></tr> </table> Partial Profile - Pitch Range <table border="1"> <tr><td>mm</td><td>TPI</td></tr> <tr><td>A 0.5 - 1.5</td><td>48 -16</td></tr> </table> | mm | TPI | 0.5-2.0 | 32-11.5 | mm | TPI | A 0.5 - 1.5 | 48 -16 | RH Helix LH Helix | RS - Close to right shoulder LS - Close to left shoulder | VPG |
| mm | TPI | | | | | | | | | | |
| 0.5-2.0 | 32-11.5 | | | | | | | | | | |
| mm | TPI | | | | | | | | | | |
| A 0.5 - 1.5 | 48 -16 | | | | | | | | | | |

■ Mini-V Inserts

| | | | | | | |
|----------|-----------|-----------|------------|------------|----------|------------|
| V | 08 | TH | 1.5 | ISO | R | VBX |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------|--------------------------|--------------------------------|--|-------------------------------|-----|---------|-------|--|----|-----|---|----------|-------|---|---------|-------|---|----------|-------|---|----------|-------|---|----------|------|----|---------|------|---|
| 1 - Product Line | 2 - Insert Style | 3 - Type of Application | 4 - Pitch (for Threading) | 5 - Threading Standard | | | | | | | | | | | | | | | | | | | | | | | | | |
| V - Mini-V | 08, 11, 14, 16 | TH - Threading | Full Profile - Pitch Range <table border="1"> <tr><td>mm</td><td>TPI</td></tr> <tr><td>0.5-2.0</td><td>32-12</td></tr> </table> Partial Profile - Pitch Range <table border="1"> <tr><td></td><td>mm</td><td>TPI</td></tr> <tr><td>A</td><td>0.5-1.50</td><td>48-16</td></tr> <tr><td>H</td><td>0.5-.75</td><td>48-32</td></tr> <tr><td>I</td><td>1.0-1.25</td><td>24-20</td></tr> <tr><td>J</td><td>1.5-1.75</td><td>16-14</td></tr> <tr><td>G</td><td>1.75-3.0</td><td>14-8</td></tr> <tr><td>AG</td><td>0.5-3.0</td><td>48-8</td></tr> </table> | mm | TPI | 0.5-2.0 | 32-12 | | mm | TPI | A | 0.5-1.50 | 48-16 | H | 0.5-.75 | 48-32 | I | 1.0-1.25 | 24-20 | J | 1.5-1.75 | 16-14 | G | 1.75-3.0 | 14-8 | AG | 0.5-3.0 | 48-8 | 60 - Partial Profile 60° 55 - Partial Profile 55° ISO - ISO Metric UN - American UN W - Whitworth for BSW, BSP BSPT - British Standard Pipe Thread NPT - NPT National Pipe Thread NPTF - NPTF National Seal Pipe Thread TR - Trapez Din 103 |
| mm | TPI | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.5-2.0 | 32-12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | mm | TPI | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 0.5-1.50 | 48-16 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| H | 0.5-.75 | 48-32 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I | 1.0-1.25 | 24-20 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| J | 1.5-1.75 | 16-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | 1.75-3.0 | 14-8 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AG | 0.5-3.0 | 48-8 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 - RH | 7 - Carbide Grade | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R - RH Helix | VBX | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Partial Profile 60°



Standard



SCB



V6





F-Line

| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | | |
|-------------|-------|----------|---------------|--------------|-----------------|----|------|-------|-----|------------|-----|-------------|
| | IC | L inch | mm | TPI | RH | LH | r | X | Y | | RH | LH |
| 1/4" | .43 | 0.5-1.5 | 48-16 | 2ERA60... | 2ELA60... | | .002 | .03 | .04 | - | - | NL..-2 (LH) |
| | | 0.5-1.5 | 48-16 | 3ERA60... | 3ELA60... | | .002 | .03 | .04 | | | |
| 3/8" | .63 | 1.75-3.0 | 14-8 | 3ERG60... | 3ELG60... | | .011 | .05 | .07 | YE3 | YI3 | AL..-3 (LH) |
| | | 0.5-3.0 | 48-8 | 3ERAG60... | 3ELAG60... | | .003 | .05 | .07 | | | |
| 3/8" SCB | .63 | 0.5-1.5 | 48-16 | 3JERA60... | | | .002 | .02 | .03 | | | |
| | | 1.75-3.0 | 14-8 | 3JERG60... | | | .011 | .04 | .06 | YE3 | - | AL..-3 |
| | | 0.5-3.0 | 48-8 | 3JERAG60... | | | .003 | .04 | .06 | | | |
| 3/8" V6 | .63 | 0.5-2.0 | 48-13 | 3ERS60-6C... | | | .002 | .07 | .12 | YE3-6C | - | AL..-3 |
| 1/2" | .87 | 3.5-5.0 | 7-5 | 4ERN60... | 4ELN60... | | .021 | .07 | .10 | YE4 | YI4 | AL..-4 (LH) |
| 1/2"F | .91 | 3.5-5.0 | 7-5 | 4FERN60... | | | .021 | .07 | .10 | YE4F | - | AL..-4F |
| 5/8" | 1.06 | 5.5-6.0 | 4.5-4 | 5ERQ60... | 5ELQ60... | | .025 | .08 | .12 | YE5 | YI5 | AL..-5 (LH) |

Partial Profile 60° (con't)

External



U Style



| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | | |
|-------------|-------|---------|---------------|------------|-----------------|------|-----|-------|------|------|---------------|
| | IC | L inch | mm | TPI | RH+LH | r | X | Y | RH | LH | Toolholder |
| 1/2"U | .87 | 5.5-8.0 | 4.5-3.25 | 4UEIU60... | | .012 | .02 | .43 | YE4U | YI4U | AL...-4U (LH) |
| 5/8"U | 1.06 | 6.5-9.0 | 4-2.75 | 5UEIU60... | | .015 | .04 | .54 | YE5U | YI5U | AL...-5U (LH) |

Slim Throat



| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | | | Toolholder |
|-------------|-------|----------|---------------|-------------|-----------------|------|-----|-----|-----|---------------|
| | IC | L inch | mm | TPI | RH | LH | r | X | Y | |
| 1/4"V | .43 | 0.5-1.5 | 48-16 | 2VERA60... | 2VELA60... | .002 | .03 | .09 | .13 | NL...-2V (LH) |
| | | 0.5-1.5 | 48-16 | 3VERA60... | 3VELA60... | .002 | .04 | .11 | .14 | |
| 3/8"V | .63 | 1.75-3.0 | 14-8 | 3VERG60... | 3VELG60... | .011 | .04 | .07 | .14 | NL...-3V (LH) |
| | | 0.5-3.0 | 48-8 | 3VERAG60... | 3VELAG60... | .003 | .04 | .07 | .14 | |
| 1/2"V | .87 | 3.5-5.0 | 7-5 | 4VERN60... | 4VELN60... | .021 | .04 | .09 | .19 | NL...-4V (LH) |




V Style



| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | | | Toolholder |
|-------------|-------|----------|---------------|------------|-----------------|-----|-----|-----|-----|------------------|
| | IC | L inch | mm | TPI | RH | LH | r | X | Y | |
| 5/8"V | 1.06 | 6.0-10.0 | 4-2.5 | 5VERV60... | 5VELV60... | .03 | .02 | .20 | .39 | NL...-5V-10 (LH) |

Partial Profile 60°

External




VG-Cut

VG-Cut



| Pocket Size | Ordering Code | Pitch | | Dimensions inch | | | No. of Passes | Helix Deg | Min. Thread Diameter | Toolholder | |
|-------------|----------------|-------|---------|-----------------|------|-----|---------------|-----------|----------------------|---------------------|-----------|
| | | RH | W ref | mm | TPI | R | | | | | Y |
| 3 | VGD3.0A60RH... | .12 | 0.5-1.5 | 48-16 | .002 | .07 | .86 | 5 - 8 | 1.5° | Partial Profile A60 | VEG...T12 |

Partial Profile 60° (con't)



Standard



SCB





F-Line

| | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--|-------------|--------|----------|-------|---------------|-----------|-----------------|-----|-----|--------|-----|-------------------------|
| | IC | L inch | mm | TPI | RH | LH | r | X | Y | RH | LH | |
| | 1/4" | .43 | 0.5-1.5 | 48-16 | 2IRA60... | 2ILA60... | .002 | .03 | .04 | - | - | NVR...-2 (LH) |
| | 1/4" SCB | .43 | 0.5-1.5 | 48-16 | 2JIRA60... | | .002 | .02 | .03 | - | - | NVR...-2 |
| | 3/8" | .63 | 0.5-1.5 | 48-16 | 3IRA60... | 3ILA60... | .002 | .03 | .04 | Y13 | YE3 | AVR...-3 (LH) |
| | | | 1.75-3.0 | 14-8 | 3IRG60... | 3ILG60... | .006 | .05 | .07 | | | |
| | 3/8" SCB | .63 | 0.5-1.5 | 48-16 | 3JIRA60... | | .002 | .02 | .03 | Y13 | - | AVR...-3 |
| | | | 1.75-3.0 | 14-8 | 3JIRG60... | | .006 | .04 | .06 | | | |
| | | | 0.5-3.0 | 48-8 | 3JIRAG60... | | .002 | .04 | .06 | | | |
| | 3/8" V6 | .63 | 0.5-2.0 | 48-14 | 3IRS60-6C... | | .001 | .06 | .10 | Y13-6C | - | AVR...-3 NVRC...-3V6 |
| | 1/2" | .87 | 3.5-5.0 | 7-5 | 4IRN60... | 4ILN60... | .012 | .07 | .10 | Y14 | YE4 | AVR...-4 (LH) |
| | 1/2"F | .91 | 3.5-5.0 | 7-5 | 4FIRN60... | | .012 | .07 | .10 | Y14F | - | AVRC...-4F |
| | 5/8" | 1.06 | 5.5-6.0 | 4.5-4 | 5IRQ60... | 5ILQ60... | .012 | .07 | .11 | Y15 | YE5 | AVR...-5 (LH) |

Partial Profile 60° (con't)

Internal



U Style



| Insert Size | | Pitch | | Ordering Code | Dimensions inch | | | Anvil | | |
|-------------|--------|---------|----------|---------------|-----------------|-----|-----|-------|------|----------------|
| IC | L inch | mm | TPI | RH+LH | r | X | Y | RH | LH | Toolholder |
| 1/2"U | .87 | 5.5-8.0 | 4.5-3.25 | 4UEIU60... | .012 | .02 | .43 | YI4U | YE4U | AVR...-4U (LH) |
| 5/8"U | 1.06 | 6.5-9.0 | 4-2.75 | 5UEIU60... | .015 | .04 | .54 | YI5U | YE5U | AVR...-5U (LH) |


V Style



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | | |
|-------------|--------|----------|-------|---------------|------------|-----------------|-----|-----|-----|----------------|
| IC | L inch | mm | TPI | RH | LH | r | X | Y | T | Toolholder |
| 5/8"V | 1.06 | 6.0-10.0 | 4-2.5 | 5VIRV60... | 5VILV60... | .014 | .04 | .17 | .31 | NVR...-5V (LH) |

Partial Profile 60° (con't)

Mini-V




Mini-V



| Insert Style | Pitch | | Ordering Code | Dimensions inch | | | | | | Helix Deg. | Toolholder |
|--------------|-------|----------|---------------|-----------------|-----|-----|------|------|-----|------------|------------|
| | TPI | mm | | d | T | F | Y | r | | | |
| V08 | 48-32 | 0.5-0.75 | V08THH60R... | .236 | .15 | .17 | .02 | .001 | 1.5 | .V08-... | |
| | 24-20 | 1.0-1.25 | V08THI60R... | | | .18 | .03 | .004 | 2.5 | | |
| | 16-14 | 1.5-1.75 | V08THJ60R... | | | .19 | .04 | .006 | 3 | | |
| V11 | 48-32 | 0.5-0.75 | V11THH60R... | .315 | .17 | .23 | .02 | .012 | 1.5 | .V11-... | |
| | 24-20 | 1.0-1.25 | V11THI60R... | | | .24 | .03 | .004 | 1.5 | | |
| | 16-14 | 1.5-1.75 | V11THJ60R... | | | .22 | .04 | .006 | 3 | | |
| V14 | 48-16 | 0.5-1.5 | V14THA60R... | .354 | .22 | .35 | .04 | .002 | 1.5 | .V14-... | |
| | 14-8 | 1.75-3.0 | V14THG60R... | | | .07 | .006 | | | | |
| | 48-8 | 0.5-3.0 | V14THAG60R... | | | .07 | .002 | | | | |
| V16 | 48-16 | 0.5-1.5 | V16THA60R... | .433 | .22 | .40 | .04 | .002 | 1.5 | .V16-... | |
| | 14-8 | 1.75-3.0 | V16THG60R... | | | .07 | .006 | | | | |
| | 48-8 | 0.5-3.0 | V16THAG60R... | | | .07 | .002 | | | | |

Partial Profile 60° (con't)



Mini-3 Standard



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|----------|-------|---------------|--------------|-----------------|-----|-----|----------------|-------------------|
| IC mm | L inch | mm | TPI | RH | LH | r | Y | F | inch | |
| 4.0 | .24 | 0.5-1.25 | 48-20 | 4.0KIRA60... | 4.0KILA60... | .002 | .02 | .15 | .25 | .NVR...-4.0K (LH) |
| 5.0 | .31 | 0.5-1.5 | 48-16 | 5.0KIRA60... | 5.0KILA60... | .002 | .03 | .19 | .31 | .NVR...-5.0K (LH) |
| 6.0 | .39 | 0.5-1.5 | 48-16 | 6.0KIRA60... | 6.0KILA60... | .002 | .04 | .21 | .39 | .NVR...-6.0K (LH) |

Left handed tool supplied by request (Example: 6.0ILA60...).

Mini-3 U Style




| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|----------|-------|---------------|--|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | mm | TPI | RH+LH | | r | Y | F | inch | |
| 5.0U | .31 | 1.75-2.0 | 14-11 | 5.0KUIB60... | | .006 | .16 | .23 | .35 | .NVR...-5.0KU (LH) |

Mini-L



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|---------|-------|-------------|---------------|------|-----------------|-----|------|------------------|------------|
| IC mm | mm | TPI | RH | LH | r | Y | F | inch | | |
| 5.0L | 0.5-1.5 | 48-16 | 5LKIRA60... | 5LKILA60... | .002 | .04 | .18 | .31 | .NVR...-5LK (LH) | |

Partial Profile 60° (con't)

MINIPRO


Micro - Double Ended

| Insert Dia. | | Pitch | | Ordering Code | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|---------|-------|--|---------------|-----------------|-----|------|-----|-----|----------------|------------|
| d mm | mm | TPI | | RH | r | L1 | L | F | Y | inch | |
| 3.0 | 0.5-1.0 | 48-24 | | 3.0SIRF60... | .002 | .63 | 1.97 | .06 | .04 | .13 | SMC..-3.0 |
| 4.0 | 0.5-1.0 | 48-24 | | 4.0SIRF60... | .002 | .63 | 1.97 | .08 | .04 | .17 | SMC..-4.0 |
| 6.0 | 0.5-1.5 | 48-16 | | 6.0SIRA60... | .002 | .63 | 1.97 | .10 | .04 | .24 | SMC..-6.0 |

Left handed tool supplied by request (Example: 6.0SILA60...).


Micro - Single Ended

microscope

| Insert Dia. | | Pitch | | Ordering Code | Dimensions inch | | | | | | | Min. Bore Dia. | Toolholder |
|-------------|---------|-------|--|---------------------|-----------------|------|-----|-----|-----|---------|-------|----------------|------------|
| d mm | mm | TPI | | RH/LH | Helix ° | r | L1 | F | Y | L2 ref* | L ref | D inch | |
| 4.0 | 0.5-1.0 | 48-24 | | MS429THF60L16R/L... | 3.5 | .001 | .63 | .04 | .04 | .72 | 1.39 | .13 | MH...-4.0 |
| | 0.5-1.0 | 48-24 | | MS439THF60L16R/L... | | .001 | | .07 | | | | .17 | |
| 6.0 | 0.5-1.5 | 48-16 | | M659THA60L16R/L... | | .002 | | .11 | | .73 | 1.66 | .24 | MH...-6.0 |

* L2 Ref: Repeatability within +/- .0008

Partial Profile 55°




Standard



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|----------|-------|---------------|------------|-----------------|-----|-----|--------|-----|-------------|
| IC | L inch | mm | TPI | RH | LH | r | X | Y | RH | LH | |
| 1/4" | .43 | 0.5-1.5 | 48-16 | 2ERA55... | 2ELA55... | .002 | .03 | .04 | - | - | NL..-2 (LH) |
| | | 0.5-1.5 | 48-16 | 3ERA55... | 3ELA55... | .002 | .03 | .04 | | | |
| 3/8" | .63 | 1.75-3.0 | 14-8 | 3ERG55... | 3ELG55... | .008 | .05 | .07 | YE3 | YI3 | AL..-3 (LH) |
| | | 0.5-3.0 | 48-8 | 3ERAG55... | 3ELAG55... | .003 | .05 | .07 | | | |
| 3/8" | .63 | 0.5-1.5 | 48-16 | 3JERA55... | | .002 | .02 | .03 | | | |
| | | 1.75-3.0 | 14-8 | 3JERG55... | | .008 | .04 | .06 | YE3 | - | AL..-3 |
| | | 0.5-3.0 | 48-8 | 3JERAG55... | | .003 | .04 | .06 | | | |
| 3/8" | .63 | 0.5-1.75 | 48-14 | 3ERS55-6C... | | .002 | .07 | .11 | YE3-6C | - | AL..-3 |
| 1/2" | .87 | 3.5-5.0 | 7-5 | 4ERN55... | 4ELN55... | .017 | .07 | .10 | YE4 | YI4 | AL..-4 (LH) |
| 1/2" | .91 | 3.5-5.0 | 7-5 | 4FERN55... | | .017 | .07 | .10 | YE4F | - | AL..-4F |
| 5/8" | 1.06 | 5.5-6.0 | 4.5-4 | 5ERQ55... | 5ELQ55... | .024 | .08 | .11 | YE5 | YI5 | AL..-5 (LH) |

Partial Profile 55° (con't)



U Style



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | |
|-------------|--------|---------|----------|---------------|--|-----------------|-----|-----|-------|------|--------------|
| IC | L inch | mm | TPI | RH+LH | | r | X | Y | RH | LH | Toolholder |
| 1/2"U | .87 | 5.5-8.0 | 4.5-3.25 | 4UEIU55... | | .024 | .04 | .43 | YE4U | YI4U | AL..-4U (LH) |
| 5/8"U | 1.06 | 6.5-9.0 | 4-2.75 | 5UEIU55... | | .031 | .05 | .54 | YE5U | YI5U | AL..-5U (LH) |

Slim Throat




| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | | |
|-------------|--------|----------|-------|---------------|-------------|-----------------|-----|-----|-----|--------------|
| IC | L inch | mm | TPI | RH | LH | r | X | Y | T | Toolholder |
| 1/4"V | .43 | 0.5-1.5 | 48-16 | 2VERA55... | 2VELA55... | .002 | .03 | .11 | .13 | NL..-2V (LH) |
| | | 0.5-1.5 | 48-16 | 3VERA55... | 3VELA55... | .002 | .04 | .11 | .14 | |
| 3/8"V | .63 | 1.75-3.0 | 14-8 | 3VERG55... | 3VELG55... | .008 | .04 | .07 | .14 | NL..-3V (LH) |
| | | 0.5-3.0 | 48-8 | 3VERAG55... | 3VELAG55... | .003 | .04 | .07 | .14 | |
| 1/2"V | .87 | 3.5-5.0 | 7-5 | 4VERN55... | 4VELN55... | .017 | .04 | .09 | .19 | NL..-4V (LH) |

V Style



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | | |
|-------------|--------|---------|--------|---------------|------------|-----------------|-----|-----|-----|----------------|
| IC | L inch | mm | TPI | RH | LH | r | X | Y | T | Toolholder |
| 5/8"V | 1.06 | 6.0-9.0 | 4-2.75 | 5VERV55... | 5VELV55... | .028 | .04 | .17 | .31 | NL..-5V-8 (LH) |

Partial Profile 55°




VG-Cut



| Pocket Size | Ordering Code | Dimensions inch | | | | | No. of Passes | Helix | Min. Thread Diameter | Toolholder |
|-------------|----------------|-----------------|-----------|------|-----|-------|---------------|---------------------|----------------------|------------|
| | RH | W ref | Pitch TPI | R | Y | L ref | Deg | | Monoblock | |
| 3 | VGD3.0A55RH... | .12 | 48-16 | .002 | .07 | 0.86 | 1.5° | Partial Profile A55 | VGE...T12 | |

Partial Profile 55° (con't)




Standard



| Insert Size | Pitch | | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|-------------|-------|----------|-------|---------------|------------|-----------------|------|-----|-------|--------|------------|------------------------|
| | IC | L inch | mm | TPI | RH | LH | r | X | Y | RH | | LH |
| 1/4" | .43 | 0.5-1.5 | 48-16 | 2IRA55... | 2ILA55... | | .002 | .03 | .04 | - | - | NVR...-2 (LH) |
| 1/4" SCB | .43 | 0.5-1.5 | 48-16 | 2JIRA55... | | | .002 | .02 | .03 | - | - | NVR...-2 |
| 3/8" | .63 | 0.5-1.5 | 48-16 | 3IRA55... | 3ILA55... | | .002 | .03 | .04 | Y13 | YE3 | AVR...-3 (LH) |
| | | 1.75-3.0 | 14-8 | 3IRG55... | 3ILG55... | | .008 | .05 | .07 | | | |
| | | 0.5-3.0 | 48-8 | 3IRAG55... | 3ILAG55... | | .003 | .05 | .07 | | | |
| 3/8" SCB | .63 | 0.5-1.5 | 48-16 | 3JIRA55... | | | .002 | .02 | .03 | Y13 | - | AVR...-3 |
| | | 1.75-3.0 | 14-8 | 3JIRG55... | | | .008 | .04 | .06 | | | |
| | | 0.5-3.0 | 48-8 | 3JIRAG55... | | | .003 | .04 | .06 | | | |
| 3/8" V6 | .63 | 0.5-1.5 | 48-16 | 3IRS55-6C... | | | .002 | .06 | .10 | Y13-6C | - | AVR...-3 NVR...-3V6 |
| 1/2" | .87 | 3.5-5.0 | 7-5 | 4IRN55... | 4ILN55... | | .017 | .07 | .10 | Y14 | YE4 | AVR...-4 (LH) |
| 1/2" F | .91 | 3.5-5.0 | 7-5 | 4FIRN55... | | | .017 | .07 | .10 | Y14F | - | AVRC...-4F |
| 5/8" | 1.06 | 5.5-6.0 | 4.5-4 | 5IRQ55... | 5ILQ55... | | .024 | .08 | .11 | Y15 | YE5 | AVR...-5 (LH) |

Partial Profile 55° (con't)



U Style



| Insert Size | | Pitch | | Ordering Code | Dimensions inch | | | Anvil | | |
|-------------|--------|---------|----------|---------------|-----------------|-----|-----|-------|------|----------------|
| IC | L inch | mm | TPI | RH+LH | r | X | Y | RH | LH | Toolholder |
| 1/2"U | .87 | 5.5-8.0 | 4.5-3.25 | 4UEIU55... | .024 | .04 | .43 | Y14U | YE4U | AVR...-4U (LH) |
| 5/8"U | 1.06 | 6.5-9.0 | 4-2.75 | 5UEIU55... | .031 | .05 | .54 | Y15U | YE5U | AVR...-5U (LH) |

V Style



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | | |
|-------------|--------|---------|--------|---------------|------------|-----------------|-----|-----|-----|----------------|
| IC | L inch | mm | TPI | RH | LH | r | X | Y | T | Toolholder |
| 5/8"V | 1.06 | 6.0-9.0 | 4-2.75 | 5VIRV55... | 5VILV55... | .028 | .04 | .17 | .31 | NVR...-5V (LH) |

Partial Profile 55° (con't)

Mini-V




Mini-V



| Insert Style | Pitch | | Ordering Code | Dimensions inch | | | | | Helix | Toolholder |
|--------------|-------|----------|---------------|-----------------|-----|-----|-----|------|-------|------------|
| | TPI | mm | RH | d | T | F | Y | r | Deg. | |
| V14 | 48-16 | 0.5-1.5 | V14THA55R... | .354 | .22 | .35 | .04 | .002 | 1.5 | .V14-... |
| | 14-8 | 1.75-3.0 | V14THG55R... | | | | .07 | .008 | | |
| | 48-8 | 0.5-3.0 | V14THAG55R... | | | | .07 | .003 | | |
| V16 | 48-16 | 0.5-1.5 | V16THA55R... | .433 | .22 | .40 | .04 | .003 | 1.5 | .V16-... |
| | 14-8 | 1.75-3.0 | V16THG55R... | | | | .07 | .010 | | |
| | 48-8 | 0.5-3.0 | V16THAG55R... | | | | .07 | .003 | | |

Partial Profile 55° (con't)

MINIPRO



Mini-3 Standard



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|----------|-------|---------------|--------------|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | mm | TPI | RH | LH | r | Y | F | inch | |
| 4.0 | .24 | 0.5-1.25 | 48-20 | 4.0KIRA55... | 4.0KILA55... | .002 | .02 | .15 | .25 | .NVR...-4.0K (LH) |
| 5.0 | .31 | 0.5-1.5 | 48-16 | 5.0KIRA55... | 5.0KILA55... | .002 | .03 | .19 | .31 | .NVRC...-5.0K (LH) |
| 6.0 | .39 | 0.5-1.50 | 48-16 | 6.0KIRA55... | 6.0KILA55... | .002 | .04 | .21 | .39 | .NVR...-6.0K (LH) |

Mini-3 U Style



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|----------|-------|---------------|--|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | mm | TPI | RH+LH | | r | Y | F | inch | |
| 5.0U | .31 | 1.75-2.0 | 14-11 | 5.0KUIB55... | | .008 | .16 | .22 | .35 | .NVR...-5.0KU (LH) |


Mini-L



| Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|---------|-------|-------------|---------------|------|-----------------|-----|------|------------------|------------|
| IC mm | mm | TPI | RH | LH | r | Y | F | inch | | |
| 5.0L | 0.5-1.5 | 48-16 | 5LKIRA55... | 5LKILA55... | .002 | .04 | .18 | .31 | .NVR...-5LK (LH) | |

Partial Profile 55° (con't)

MINIPRO



Micro - Double Ended

| Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | | Min. Bore Dia. | |
|-------------|---------|---------------|--------------|-----------------|-----|------|-----|-----|------|----------------|--|
| d mm | mm | TPI | RH | r | L1 | L | F | Y | inch | Toolholder | |
| 3.0 | 0.5-1.0 | 48-24 | 3.0SIRF55... | .002 | .63 | 1.97 | .06 | .04 | .13 | SMC..-3.0 | |
| 4.0 | 0.5-1.0 | 48-24 | 4.0SIRF55... | .002 | .63 | 1.97 | .08 | .04 | .17 | SMC..-4.0 | |
| 6.0 | 0.5-1.5 | 48-16 | 6.0SIRA55... | .002 | .63 | 1.97 | .10 | .04 | .24 | SMC..-6.0 | |

Left handed tool supplied by request (Example: 6.0SILA55...).

Micro - Single Ended


microscope

| Insert Dia. | Pitch | | Ordering Code | Dimensions inch | | | | | | | | Min. Bore Dia. | |
|-------------|---------|-------|---------------------|-----------------|------|-----|-----|-----|---------|-------|--------|----------------|--|
| d mm | mm | TPI | RH/LH | Helix° | r | L1 | F | Y | L2 ref* | L ref | D inch | Toolholder | |
| 4.0 | 0.5-1.0 | 48-24 | MS429THF55L16R/L... | 3.5 | .002 | .63 | .04 | .03 | .72 | 1.39 | .13 | MH...-4.0 | |
| | 0.5-1.0 | 48-24 | MS439THF55L16R/L... | | | | .07 | | | .17 | | | |
| 6.0 | 0.5-1.5 | 48-16 | M659THA55L16R/L... | | .002 | | .11 | .04 | .73 | 1.66 | .24 | MH...-6.0 | |


* L2 Ref: Repeatability within +/- .0008

ISO Metric

External



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Standard


Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------------|--------------|---------------|---------------|-----------------|-----|-----|-------|-----|-------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 0.25 | 2ER0.25ISO... | 2EL0.25ISO... | .006 | .02 | .01 | - | - | NL..-2 (LH) |
| | | 0.3 | 2ER0.3ISO... | 2EL0.3ISO... | .007 | .03 | .01 | | | |
| | | 0.35 | 2ER0.35ISO... | 2EL0.35ISO... | .008 | .03 | .02 | | | |
| | | 0.4 | 2ER0.4ISO... | 2EL0.4ISO... | .010 | .03 | .02 | | | |
| | | 0.45 | 2ER0.45ISO... | 2EL0.45ISO... | .011 | .03 | .02 | | | |
| | | 0.5 | 2ER0.5ISO... | 2EL0.5ISO... | .012 | .02 | .02 | | | |
| | | 0.6 | 2ER0.6ISO... | 2EL0.6ISO... | .015 | .02 | .02 | | | |
| | | 0.7 | 2ER0.7ISO... | 2EL0.7ISO... | .017 | .02 | .02 | | | |
| | | 0.75 | 2ER0.75ISO... | 2EL0.75ISO... | .018 | .02 | .02 | | | |
| | | 0.8 | 2ER0.8ISO... | 2EL0.8ISO... | .019 | .02 | .02 | | | |
| | | 1.0 | 2ER1.0ISO... | 2EL1.0ISO... | .024 | .03 | .03 | | | |
| | | 1.25 | 2ER1.25ISO... | 2EL1.25ISO... | .030 | .03 | .04 | | | |
| | | 1.5 | 2ER1.5ISO... | 2EL1.5ISO... | .036 | .03 | .04 | | | |
| | | 1.75 | 2ER1.75ISO... | 2EL1.75ISO... | .042 | .03 | .04 | | | |
| 3/8" | .63 | 0.25 | 3ER0.25ISO... | 3EL0.25ISO... | .006 | .02 | .01 | YE3 | YI3 | AL..-3 (LH) |
| | | 0.3 | 3ER0.3ISO... | 3EL0.3ISO... | .007 | .03 | .01 | | | |
| | | 0.35 | 3ER0.35ISO... | 3EL0.35ISO... | .008 | .03 | .02 | | | |
| | | 0.4 | 3ER0.4ISO... | 3EL0.4ISO... | .010 | .03 | .02 | | | |
| | | 0.45 | 3ER0.45ISO... | 3EL0.45ISO... | .011 | .03 | .02 | | | |
| | | 0.5 | 3ER0.5ISO... | 3EL0.5ISO... | .012 | .02 | .02 | | | |
| | | 0.6 | 3ER0.6ISO... | 3EL0.6ISO... | .015 | .02 | .02 | | | |
| | | 0.7 | 3ER0.7ISO... | 3EL0.7ISO... | .017 | .02 | .02 | | | |
| | | 0.75 | 3ER0.75ISO... | 3EL0.75ISO... | .018 | .02 | .02 | | | |
| | | 0.8 | 3ER0.8ISO... | 3EL0.8ISO... | .019 | .02 | .02 | | | |
| | | 1.0 | 3ER1.0ISO... | 3EL1.0ISO... | .024 | .03 | .03 | | | |
| | | 1.25 | 3ER1.25ISO... | 3EL1.25ISO... | .030 | .03 | .04 | | | |
| | | 1.5 | 3ER1.5ISO... | 3EL1.5ISO... | .036 | .03 | .04 | | | |
| | | 1.75 | 3ER1.75ISO... | 3EL1.75ISO... | .042 | .04 | .05 | | | |
| 2.0 | 3ER2.0ISO... | 3EL2.0ISO... | .048 | .04 | .05 | | | | | |
| 2.5 | 3ER2.5ISO... | 3EL2.5ISO... | .060 | .04 | .06 | | | | | |
| 3.0 | 3ER3.0ISO... | 3EL3.0ISO... | .072 | .05 | .06 | | | | | |
| 3.5 | 3ER3.5ISO... | 3EL3.5ISO... | .085 | .06 | .07 | | | | | |




ISO Metric (con't)


External




Defined by: R262 (DIN 13)
Tolerance class: 6g/6H




SCB
Sintered
Chipbreaker



V6



Standard



F-Line


Standard




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|------------------|--------------|-----------------|-----|-----|--------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 3/8" SCB | .63 | 0.5 | 3JER0.5ISO... | | .012 | .05 | .02 | YE3 | - | AL...-3 |
| | | 0.75 | 3JER0.75ISO... | | .018 | .05 | .02 | | | |
| | | 0.8 | 3JER0.8ISO... | | .019 | .05 | .02 | | | |
| | | 1.0 | 3JER1.0ISO... | | .024 | .03 | .03 | | | |
| | | 1.25 | 3JER1.25ISO... | | .030 | .03 | .03 | | | |
| | | 1.5 | 3JER1.5ISO... | | .036 | .03 | .03 | | | |
| | | 1.75 | 3JER1.75ISO... | | .042 | .05 | .06 | | | |
| | | 2.0 | 3JER2.0ISO... | | .048 | .05 | .06 | | | |
| | | 2.5 | 3JER2.5ISO... | | .060 | .05 | .06 | | | |
| | | 3.0 | 3JER3.0ISO... | | .072 | .05 | .06 | | | |
| 3/8" V6 | .63 | 0.5 | 3ER0.5ISO-6C... | | .012 | .09 | .07 | YE3-6C | - | AL...-3 |
| | | 0.75 | 3ER0.75ISO-6C... | | .018 | .08 | .07 | | | |
| | | 0.8 | 3ER0.8ISO-6C... | | .019 | .08 | .07 | | | |
| | | 1.0 | 3ER1.0ISO-6C... | | .024 | .07 | .08 | | | |
| | | 1.25 | 3ER1.25ISO-6C... | | .030 | .07 | .08 | | | |
| | | 1.5 | 3ER1.5ISO-6C... | | .036 | .07 | .09 | | | |
| | | 1.75 | 3ER1.75ISO-6C... | | .042 | .07 | .10 | | | |
| | | 2.0 | 3ER2.0ISO-6C... | | .048 | .07 | .11 | | | |
| 1/2" | .87 | 3.5 | 4ER3.5ISO... | 4EL3.5ISO... | .085 | .06 | .09 | YE4 | Y14 | AL...-4 (LH) |
| | | 4.0 | 4ER4.0ISO... | 4EL4.0ISO... | .096 | .06 | .09 | | | |
| | | 4.5 | 4ER4.5ISO... | 4EL4.5ISO... | .109 | .07 | .09 | | | |
| | | 5.0 | 4ER5.0ISO... | 4EL5.0ISO... | .121 | .07 | .10 | | | |
| | | 5.5 | 4ER5.5ISO... | 4EL5.5ISO... | .133 | .07 | .11 | | | |
| | | 6.0 | 4ER6.0ISO... | 4EL6.0ISO... | .145 | .07 | .11 | | | |
| 1/2"F | .91 | 3.5 | 4FER3.5ISO... | | .085 | .06 | .09 | YE4F | - | AL...-4F |
| | | 4.0 | 4FER4.0ISO... | | .096 | .06 | .09 | | | |
| | | 4.5 | 4FER4.5ISO... | | .109 | .07 | .09 | | | |
| | | 5.0 | 4FER5.0ISO... | | .121 | .07 | .10 | | | |
| | | 5.5 | 4FER5.5ISO... | | .133 | .07 | .11 | | | |
| | | 6.0 | 4FER6.0ISO... | | .145 | .07 | .11 | | | |
| 5/8" | 1.06 | 5.5 | 5ER5.5ISO... | 5EL5.5ISO... | .133 | .07 | .11 | YE5 | Y15 | AL...-5 (LH) |
| | | 6.0 | 5ER6.0ISO... | 5EL6.0ISO... | .145 | .08 | .11 | | | |

ISO Metric (con't)


External



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



U Style



V Style / Slim Throat

U Style



| IC | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------|-------------|-----|--------------|---------------|-------|-----------------|------|------|--------------|--|------------|
| | L inch | mm | | RH+LH | h min | X | Y | RH | LH | | |
| 1/2"U | .87 | 5.0 | 4UE5.0ISO... | .121 | .09 | .43 | YE4U | YI4U | AL...4U (LH) | | |
| | | 5.5 | 4UE5.5ISO... | .132 | .09 | .43 | | | | | |
| | | 6.0 | 4UE6.0ISO... | .145 | .10 | .43 | | | | | |
| 5/8"U | 1.06 | 8.0 | 5UE8.0ISO... | .193 | .09 | .54 | YE5U | YI5U | AL...5U (LH) | | |

Slim Throat



| IC | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Toolholder |
|-------|---------------|---------------|----------------|----------------|------|-----------------|-----|-----|--------------|
| | L inch | mm | | RH | LH | h min | X | Y | |
| 1/4"V | .43 | 0.75 | 2VER0.75ISO... | 2VEL0.75ISO... | .018 | .03 | .10 | .13 | NL...2V (LH) |
| | | 1.0 | 2VER1.0ISO... | 2VEL1.0ISO... | .024 | .03 | .10 | .13 | |
| | | 1.5 | 2VER1.5ISO... | 2VEL1.5ISO... | .036 | .03 | .09 | .13 | |
| | | 1.75 | 2VER1.75ISO... | 2VEL1.75ISO... | .042 | .03 | .08 | .13 | |
| | | 2.0 | 2VER2.0ISO... | 2VEL2.0ISO... | .048 | .03 | .07 | .13 | |
| 3/8"V | .63 | 0.35 | 3VER0.35ISO... | 3VEL0.35ISO... | .008 | .04 | .13 | .14 | NL...3V (LH) |
| | | 0.4 | 3VER0.4ISO... | 3VEL0.4ISO... | .010 | .04 | .13 | .14 | |
| | | 0.5 | 3VER0.5ISO... | 3VEL0.5ISO... | .012 | .04 | .12 | .14 | |
| | | 0.75 | 3VER0.75ISO... | 3VEL0.75ISO... | .018 | .04 | .12 | .14 | |
| | | 0.8 | 3VER0.8ISO... | 3VEL0.8ISO... | .019 | .04 | .12 | .14 | |
| | | 1.0 | 3VER1.0ISO... | 3VEL1.0ISO... | .024 | .04 | .11 | .14 | |
| | | 1.25 | 3VER1.25ISO... | 3VEL1.25ISO... | .030 | .04 | .11 | .14 | |
| | | 1.5 | 3VER1.5ISO... | 3VEL1.5ISO... | .036 | .04 | .10 | .14 | |
| | | 1.75 | 3VER1.75ISO... | 3VEL1.75ISO... | .042 | .04 | .10 | .14 | |
| | | 2.0 | 3VER2.0ISO... | 3VEL2.0ISO... | .048 | .04 | .09 | .14 | |
| | | 2.5 | 3VER2.5ISO... | 3VEL2.5ISO... | .060 | .04 | .08 | .14 | |
| 3.0 | 3VER3.0ISO... | 3VEL3.0ISO... | .072 | .04 | .08 | .14 | | | |



V Style



| IC | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Toolholder |
|-------|-------------|------|----------------|----------------|------|-----------------|-----|-----|----------------|
| | L inch | mm | | RH | LH | h min | X | Y | |
| 5/8"V | 1.06 | 5.5 | 5VER5.5ISO... | 5VEL5.5ISO... | .133 | .04 | .13 | .24 | NL...5V-6 (LH) |
| | | 6.0 | 5VER6.0ISO... | 5VEL6.0ISO... | .145 | .04 | .13 | .24 | |
| | | 8.0 | 5VER8.0ISO... | 5VEL8.0ISO... | .193 | .04 | .17 | .31 | |
| | | 10.0 | 5VER10.0ISO... | 5VEL10.0ISO... | .241 | .04 | .20 | .39 | |


ISO Metric (con't)

External



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H

RS/LS Varied range of threading standards for machining between shoulders and close to spindle.



VG-Cut




| Pocket Size | Ordering Code | Dimensions inch | | | | | No. of Passes | Helix | Min. Thread Diameter | Toolholder |
|-------------|------------------------------|-----------------|-------|----------|-------|-----|---------------|-------|----------------------|------------|
| | | RH | W ref | Pitch mm | h min | Y | | | | |
| 3 | VG D3.0 ISO 0.50 RH-RS/LS... | | | 0.50 | .012 | .02 | 5 - 7 | | M 3x0.5 | VGE...T12 |
| | VG D3.0 ISO 0.75 RH-RS/LS... | | | 0.75 | .018 | .03 | 5 - 8 | | M 5x0.75 | |
| | VG D3.0 ISO 1.00 RH-RS/LS... | | | 1.00 | .024 | .03 | 5 - 9 | | M 6x1 | |
| | VG D3.0 ISO 1.25 RH-RS/LS... | .12 | | 1.25 | .030 | .03 | 6 - 10 | 2.5° | M 8x1.25 | |
| | VG D3.0 ISO 1.50 RH-RS/LS... | | | 1.50 | .036 | .04 | 7 - 12 | | M10x1.5 Coarse | |
| | VG D3.0 ISO 1.75 RH-RS/LS... | | | 1.75 | .042 | .05 | 8 - 14 | | M12x1.75 Coarse | |
| | VG D3.0 ISO 2.00 RH-RS/LS... | | | 2.00 | .048 | .05 | 9 - 14 | | M16x2.0 Coarse | |

LH Helix threads available upon request.



ISO Metric (con't)

MEGALINE

External



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H




Mega Line

External




| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|-----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 12.0 | 5MGER12.0ISO... | 42495 | .290 | .16 | .44 | 105 | 49 |
| | | 16.0 | 5MGER16.0ISO... | 42496 | .387 | .18 | | 140 | 66 |
| | | 18.0 | 5MGER18.0ISO... | 42497 | .435 | .19 | | 158 | 74 |
| | | 20.0 | 5MGER20.0ISO... | 42498 | .483 | .21 | | 175 | 82 |
| | | 25.0 | 5MGER25.0ISO... | 42499 | .604 | .18 | | 219 | 102 |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.



External Toolholders for ISO Metric

MEGA/LINE




| External | | | | | | | Spare Parts | | |
|-----------------|----------------|---------|-----------------|------|-----|------------------------------|---|---|-----|
| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.) |  |  | |
| | RH | | H=B=H1 | F | L1 | L2 | Insert Screw | Torx Key | |
| 5MGER12.0ISO... | NL100-5MG12ISO | 66450 | 1.00 | .65 | 6.1 | .866 | M43x12 | S5MG | K6T |
| | NL125-5MG12ISO | 66451 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG12ISO | 66452 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER16.0ISO... | NL100-5MG16ISO | 66453 | 1.00 | .65 | 6.1 | .866 | M57x16 | | |
| | NL125-5MG16ISO | 66454 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG16ISO | 66455 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER18.0ISO... | NL100-5MG18ISO | 66456 | 1.00 | .65 | 6.1 | .866 | M65x18 | | |
| | NL125-5MG18ISO | 66457 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG18ISO | 66458 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER20.0ISO... | NL100-5MG20ISO | 66459 | 1.00 | .65 | 6.1 | .866 | M72x20 | | |
| | NL125-5MG20ISO | 66460 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG20ISO | 66461 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER25.0ISO... | NL100-5MG25ISO | 66462 | 1.00 | .65 | 6.1 | .866 | M90x25 | | |
| | NL125-5MG25ISO | 66463 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG25ISO | 66464 | 1.50 | 1.24 | 8.1 | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

ISO Metric (con't)


External




Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



M+ Style



F-Line M+



T+ Style

M+ Style



FLINE

| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|--------|------------|
| IC | L inch | mm | | RH | h min | X | Y | RH | |
| 3/8" | .63 | 1.0 | 3 | 3ER1.0ISO3M+... | .024 | .07 | .10 | YE3M | AL...-3 |
| | | 1.5 | 2 | 3ER1.5ISO2M+... | .036 | .06 | .09 | | |
| | | 2.0 | 2 | 3ER2.0ISO2M+... | .048 | .08 | .12 | | |
| 1/2" | .87 | 1.5 | 3 | 4ER1.5ISO3M+... | .036 | .10 | .15 | YE4M | AL...-4 |
| | | 2.0 | 2 | 4ER2.0ISO2M+... | .048 | .08 | .12 | | |
| | | 2.0 | 3 | 4ER2.0ISO3M+... | .048 | .13 | .20 | | |
| | | 2.5 | 2 | 4ER2.5ISO2M+... | .060 | .10 | .15 | | |
| 1/2"F | .91 | 2.0 | 2 | 4FER2.0ISO2M+... | .048 | .08 | .12 | YE4M2F | AL...-4MF |
| | | 2.0 | 3 | 4FER2.0ISO3M+... | .048 | .13 | .20 | YE4M3F | |
| 5/8" | 1.06 | 3.0 | 2 | 5ER3.0ISO2M+... | .072 | .12 | .19 | YE5M | AL...-5M |


T+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|-----------------|-----------------|-----|-----|-------|------------|
| IC | L inch | mm | | RH | h min | X | Y | RH | |
| 1/2"T | .87 | 1.5 | 8 | 4ER1.5ISO8T+... | .036 | .01 | .49 | Y4T | AL...-4T |
| | | 2.0 | 8 | 4ER2.0ISO8T+... | .048 | .01 | .69 | | |

ISO Metric (con't)


Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Standard



SCB
Sintered
Chipbreaker

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|---------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 0.35 | 2IR0.35ISO... | 2IL0.35ISO... | .008 | .03 | .01 | - | - | NVR..-2 (LH) |
| | | 0.4 | 2IR0.4ISO... | 2IL0.4ISO... | .009 | .03 | .02 | | | |
| | | 0.45 | 2IR0.45ISO... | 2IL0.45ISO... | .010 | .03 | .02 | | | |
| | | 0.5 | 2IR0.5ISO... | 2IL0.5ISO... | .011 | .02 | .02 | | | |
| | | 0.6 | 2IR0.6ISO... | 2IL0.6ISO... | .014 | .02 | .02 | | | |
| | | 0.7 | 2IR0.7ISO... | 2IL0.7ISO... | .016 | .02 | .02 | | | |
| | | 0.75 | 2IR0.75ISO... | 2IL0.75ISO... | .017 | .02 | .02 | | | |
| | | 0.8 | 2IR0.8ISO... | 2IL0.8ISO... | .018 | .02 | .02 | | | |
| | | 1.0 | 2IR1.0ISO... | 2IL1.0ISO... | .023 | .02 | .03 | | | |
| | | 1.25 | 2IR1.25ISO... | 2IL1.25ISO... | .028 | .03 | .04 | | | |
| | | 1.5 | 2IR1.5ISO... | 2IL1.5ISO... | .034 | .03 | .04 | | | |
| | | 1.75 | 2IR1.75ISO... | 2IL1.75ISO... | .040 | .04 | .04 | | | |
| | | 2.0 | 2IR2.0ISO... | 2IL2.0ISO... | .045 | .04 | .04 | | | |
| 1/4" SCB | .43 | 0.5 | 2JIR0.5ISO... | | .011 | .05 | .02 | - | - | NVR..-2 |
| | | 0.75 | 2JIR0.75ISO... | | .017 | .05 | .02 | | | |
| | | 0.8 | 2JIR0.8ISO... | | .018 | .05 | .02 | | | |
| | | 1.0 | 2JIR1.0ISO... | | .023 | .03 | .03 | | | |
| | | 1.25 | 2JIR1.25ISO... | | .028 | .03 | .03 | | | |
| 3/8" | .63 | 0.35 | 3IR0.35ISO... | 3IL0.35ISO... | .008 | .03 | .01 | Y13 | YE3 | AVR..-3 (LH) |
| | | 0.4 | 3IR0.4ISO... | 3IL0.4ISO... | .009 | .03 | .02 | | | |
| | | 0.45 | 3IR0.45ISO... | 3IL0.45ISO... | .010 | .03 | .02 | | | |
| | | 0.5 | 3IR0.5ISO... | 3IL0.5ISO... | .011 | .02 | .02 | | | |
| | | 0.6 | 3IR0.6ISO... | 3IL0.6ISO... | .014 | .02 | .02 | | | |
| | | 0.7 | 3IR0.7ISO... | 3IL0.7ISO... | .016 | .02 | .02 | | | |
| | | 0.75 | 3IR0.75ISO... | 3IL0.75ISO... | .017 | .02 | .02 | | | |
| | | 0.8 | 3IR0.8ISO... | 3IL0.8ISO... | .018 | .02 | .02 | | | |
| | | 1.0 | 3IR1.0ISO... | 3IL1.0ISO... | .023 | .02 | .03 | | | |
| | | 1.25 | 3IR1.25ISO... | 3IL1.25ISO... | .028 | .03 | .04 | | | |
| | | 1.5 | 3IR1.5ISO... | 3IL1.5ISO... | .034 | .03 | .04 | | | |
| | | 1.75 | 3IR1.75ISO... | 3IL1.75ISO... | .040 | .04 | .05 | | | |
| | | 2.0 | 3IR2.0ISO... | 3IL2.0ISO... | .045 | .04 | .05 | | | |
| | | 2.5 | 3IR2.5ISO... | 3IL2.5ISO... | .057 | .04 | .06 | | | |
| | | 3.0 | 3IR3.0ISO... | 3IL3.0ISO... | .068 | .04 | .06 | | | |
| | | 3.5 | 3IR3.5ISO... | 3IL3.5ISO... | .080 | .05 | .06 | | | |

ISO Metric (con't)

Internal

Defined by: R262 (DIN 13)
Tolerance class: 6g/6H

SCB
Sintered
Chipbreaker

V6


Standard

F-Line

Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|-------------|--------|-------|---------------|------------------|-----------------|------|-----|-------|--------|------------|-------------------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | | |
| | 3/8" | .63 | 1.0 | 3JIR1.0ISO... | | .023 | .03 | .03 | Y13 | - | AVR...-3 |
| | | | 1.25 | 3JIR1.25ISO... | | .028 | .03 | .03 | | | |
| | | | 1.5 | 3JIR1.5ISO... | | .034 | .03 | .03 | | | |
| | | | 1.75 | 3JIR1.75ISO... | | .040 | .04 | .06 | | | |
| | | | 2.0 | 3JIR2.0ISO... | | .045 | .04 | .06 | | | |
| | | | 2.5 | 3JIR2.5ISO... | | .057 | .04 | .06 | | | |
| | | | 3.0 | 3JIR3.0ISO... | | .068 | .04 | .06 | | | |
| | 3/8" | .63 | 0.5 | 3IR0.5ISO-6C... | | .011 | .08 | .07 | Y13-6C | - | AVR...-3 NVRC...-3V6 |
| | | | 0.75 | 3IR0.75ISO-6C... | | .017 | .08 | .07 | | | |
| | | | 0.8 | 3IR0.8ISO-6C... | | .018 | .07 | .07 | | | |
| | | | 1.0 | 3IR1.0ISO-6C... | | .023 | .08 | .08 | | | |
| | | | 1.25 | 3IR1.25ISO-6C... | | .028 | .07 | .09 | | | |
| | | | 1.5 | 3IR1.5ISO-6C... | | .034 | .06 | .09 | | | |
| | | | 1.75 | 3IR1.75ISO-6C... | | .040 | .06 | .09 | | | |
| | 1/2" | .87 | 3.5 | 4IR3.5ISO... | 4IL3.5ISO... | .080 | .06 | .09 | Y14 | YE4 | AVR...-4 (LH) |
| | | | 4.0 | 4IR4.0ISO... | 4IL4.0ISO... | .091 | .06 | .09 | | | |
| | | | 4.5 | 4IR4.5ISO... | 4IL4.5ISO... | .102 | .06 | .09 | | | |
| | | | 5.0 | 4IR5.0ISO... | 4IL5.0ISO... | .114 | .06 | .09 | | | |
| | | | 5.5 | 4IR5.5ISO... | 4IL5.5ISO... | .125 | .06 | .09 | | | |
| | | | 6.0 | 4IR6.0ISO... | 4IL6.0ISO... | .136 | .07 | .10 | | | |
| | 1/2" | .91 | 3.5 | 4FIR3.5ISO... | | .080 | .06 | .09 | Y14F | | AVRC...-4F |
| | | | 4 | 4FIR4.0ISO... | | .091 | .06 | .09 | | | |
| | | | 4.5 | 4FIR4.5ISO... | | .102 | .06 | .09 | | | |
| | | | 5 | 4FIR5.0ISO... | | .114 | .06 | .09 | | | |
| | | | 5.5 | 4FIR5.5ISO... | | .125 | .06 | .09 | | | |
| | | | 6 | 4FIR6.0ISO... | | .136 | .07 | .10 | | | |
| | 5/8" | 1.06 | 4.5 | 5IR4.5ISO... | 5IL4.5ISO... | .102 | .06 | .09 | Y15 | YE5 | AVR...-5 (LH) |
| | | | 5.0 | 5IR5.0ISO... | 5IL5.0ISO... | .114 | .06 | .09 | | | |
| | | | 5.5 | 5IR5.5ISO... | 5IL5.5ISO... | .125 | .06 | .09 | | | |
| | | | 6.0 | 5IR6.0ISO... | 5IL6.0ISO... | .136 | .07 | .10 | | | |

ISO Metric (con't)



U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|-------|-----------------|-----|-----|-------|------|----------------|
| IC | L inch | mm | RH+LH | h min | X | Y | RH | LH | | |
| 1/2"U | .87 | 5.5 | 4UI5.5ISO... | | .125 | .09 | .43 | Y14U | YE4U | AVR...-4U (LH) |
| | | 6.0 | 4UI6.0ISO... | | .136 | .08 | .43 | | | |
| 5/8"U | 1.06 | 8.0 | 5UI8.0ISO... | | .182 | .09 | .54 | Y15U | YE5U | AVR...-5U (LH) |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|-----|----------------|------------|
| IC | L inch | mm | RH | LH | h min | X | Y | T | | |
| 5/8"V | 1.06 | 6.0 | 5VIR6.0ISO... | 5VIL6.0ISO... | .136 | .04 | .13 | .24 | NVR...-5V (LH) | |
| | | 8.0 | 5VIR8.0ISO... | 5VIL8.0ISO... | .182 | .04 | .17 | .31 | | |
| | | 10.0 | 5VIR10.0ISO... | 5VIL10.0ISO... | .227 | .04 | .20 | .39 | | |


M+ Style



FLINE

| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|------------------|-------|-----------------|-----|-----|--------|-------------|
| IC | L inch | mm | | RH | h min | X | Y | RH | | |
| 3/8" | .63 | 1.0 | 3 | 3IR1.0ISO3M+... | | .023 | .07 | .10 | Y13M | AVR...-3 |
| | | 1.5 | 2 | 3IR1.5ISO2M+... | | .034 | .06 | .09 | | |
| | | 2.0 | 2 | 3IR2.0ISO2M+... | | .045 | .08 | .12 | | |
| 1/2" | .87 | 1.5 | 3 | 4IR1.5ISO3M+... | | .034 | .10 | .15 | Y14M | AVR...-4 |
| | | 2.0 | 2 | 4IR2.0ISO2M+... | | .045 | .08 | .12 | | |
| 1/2"F | .91 | 2.0 | 2 | 4FIR2.0ISO2M+... | | .045 | .08 | .12 | Y14M2F | AVRC...-4MF |
| 5/8" | 1.06 | 3.0 | 2 | 5IR3.0ISO2M+... | | .068 | .12 | .19 | Y15M | AVR...-5M |

T+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|-----------------|-------|-----------------|-----|-----|-------|------------|
| IC | L inch | mm | | RH | h min | X | Y | RH | | |
| 1/2" | .87 | 1.5 | 8 | 4IR1.5ISO8T+... | | .034 | .01 | .49 | Y4T | AVR...-4T |
| | | 2.0 | 8 | 4IR2.0ISO8T+... | | .045 | .01 | .69 | | |


ISO Metric (con't)

MEGALINE


Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Mega Line




Internal




| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|-----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 12.0 | 5MGIR12.0ISO... | 42490 | .273 | .10 | .41 | 99 | 46 |
| | | 16.0 | 5MGIR16.0ISO... | 42491 | .367 | .12 | | 132 | 62 |
| | | 18.0 | 5MGIR18.0ISO... | 42492 | .413 | .12 | | 149 | 69 |
| | | 20.0 | 5MGIR20.0ISO... | 42493 | .458 | .13 | | 165 | 77 |
| | | 25.0 | 5MGIR25.0ISO... | 42494 | .574 | .14 | | 206 | 96 |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.



Internal Toolholders for ISO Metric

MEGA/LINE



Internal

Spare Parts


| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Spare Parts | |
|-----------------|------------------|---------|-----------------|-------|----------|-----|------|------|----------------|-----------------------------------|---------------------|--------------------|--------------|
| | | | A | L | L1 (max) | D | D1 | F | | inch | Short Chip Material | Long Chip Material | Insert Screw |
| 5MGIR12.0ISO... | NVRC150-5MG12ISO | 66465 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.36 | (M73-90)x12 | (M85-90)x12 | S5MG | K6T |
| | NVRC200-5MG12ISO | 66466 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.75 | (M83-90)x12 | (M83-90)x12 | | |
| 5MGIR16.0ISO... | NVRC150-5MG16ISO | 66467 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.34 | (M77-190)x16 | (M89-190)x16 | | |
| | NVRC200-5MG16ISO | 66468 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.74 | (M87-190)x16 | (M101-190)x16 | | |
| 5MGIR18.0ISO... | NVRC250-5MG16ISO | 66469 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.29 | (M97-190)x16 | (M113-190)x16 | | |
| | NVRC150-5MG18ISO | 66470 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.58 | (M85-230)x18 | (M91-230)x18 | | |
| | NVRC200-5MG18ISO | 66471 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.74 | (M89-230)x18 | (M103-230)x18 | | |
| 5MGIR20.0ISO... | NVRC250-5MG18ISO | 66472 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.29 | (M99-230)x18 | (M115-230)x18 | | |
| | NVRC150-5MG20ISO | 66473 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.77 | (M92-290)x20 | (M93-290)x20 | | |
| | NVRC200-5MG20ISO | 66474 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.77 | (M92-290)x20 | (M105-290)x20 | | |
| 5MGIR25.0ISO... | NVRC250-5MG20ISO | 66475 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.24 | (M101-290)x20 | (M117-290)x20 | | |
| | NVRC150-5MG25ISO | 66476 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 3.23 | (M109-405)x25 | (M109-405)x25 | | |
| | NVRC200-5MG25ISO | 66477 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 3.23 | (M109-405)x25 | (M110-405)x25 | | |
| | NVRC250-5MG25ISO | 66478 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.27 | (M110-405)x25 | (M127-405)x25 | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.


ISO Metric (con't)

Mini-V

Internal




Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Mini-V



| Min. Thread | Insert Style | Pitch | Ordering Code | Dimensions inch | | | | | | Helix | Toolholder |
|-------------|--------------|-------|------------------|-----------------|-----|-----|-----|------|-----|----------|------------|
| | | | | mm | RH | d | T | F | Y | | |
| M8x0.5 | V08 | 0.5 | V08TH0.50ISOR... | .24 | .15 | .15 | .01 | .29 | 1 | .V08-... | |
| M8.5x0.75 | | 0.75 | V08TH0.75ISOR... | | | .16 | .02 | .43 | 1.5 | | |
| M9x1.0 | | 1.0 | V08TH1.0ISOR... | | | .17 | .02 | .58 | 2 | | |
| M10x1.25 | | 1.25 | V08TH1.25ISOR... | | | .17 | .03 | .72 | 2.5 | | |
| M10x1.5 | | 1.5 | V08TH1.5ISOR... | | | .18 | .04 | .87 | 3 | | |
| M12x1.75 | | 1.75 | V08TH1.75ISOR... | | | .19 | .04 | 1.01 | 3 | | |
| M14x2.0 | V11 | 2.0 | V11TH2.0ISOR... | .31 | .17 | .25 | .04 | 1.15 | 2.5 | .V11-... | |



Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|------------------|------------------|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | mm | RH | LH | h min | Y | F | inch | |
| 4.0 | .24 | 0.25 | 4.0KIR0.25ISO... | 4.0KIL0.25ISO... | .006 | .01 | .13 | .23 | .NVR...-4.0K (LH) |
| | | 0.5 | 4.0KIR0.5ISO... | 4.0KIL0.5ISO... | .011 | .02 | .13 | .24 | |
| | | 0.75 | 4.0KIR0.75ISO... | 4.0KIL0.75ISO... | .017 | .02 | .14 | .24 | |
| | | 1.0 | 4.0KIR1.0ISO... | 4.0KIL1.0ISO... | .023 | .03 | .14 | .25 | |
| | | 1.25 | 4.0KIR1.25ISO... | 4.0KIL1.25ISO... | .028 | .02 | .15 | .25 | |
| 5.0 | .31 | 0.5 | 5.0KIR0.5ISO... | 5.0KIL0.5ISO... | .011 | .02 | | | .NVRC...-5.0K (LH) |
| | | 0.75 | 5.0KIR0.75ISO... | 5.0KIL0.75ISO... | .017 | .02 | | | |
| | | 1.0 | 5.0KIR1.0ISO... | 5.0KIL1.0ISO... | .023 | .02 | | | |
| | | 1.25 | 5.0KIR1.25ISO... | 5.0KIL1.25ISO... | .028 | .03 | .19 | .31 | |
| | | 1.5 | 5.0KIR1.5ISO... | 5.0KIL1.5ISO... | .034 | .03 | | | |
| 6.0 | .39 | 0.5 | 6.0KIR0.5ISO... | 6.0KIL0.5ISO... | .011 | .02 | .17 | .37 | .NVR...-6.0K (LH) |
| | | 0.75 | 6.0KIR0.75ISO... | 6.0KIL0.75ISO... | .017 | .02 | .18 | .37 | |
| | | 1.0 | 6.0KIR1.0ISO... | 6.0KIL1.0ISO... | .023 | .03 | .19 | .38 | |
| | | 1.25 | 6.0KIR1.25ISO... | 6.0KIL1.25ISO... | .028 | .04 | .19 | .39 | |
| | | 1.5 | 6.0KIR1.5ISO... | 6.0KIL1.5ISO... | .034 | .04 | .20 | .39 | |
| | | 1.75 | 6.0KIR1.75ISO... | 6.0KIL1.75ISO... | .040 | .04 | .20 | .39 | |
| | | 2.0 | 6.0KIR2.0ISO... | 6.0KIL2.0ISO... | .045 | .04 | .21 | .39 | |

Mini-3 U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|-----------------|--|-----------------|-----|-----|----------------|---------------------|
| IC mm | L inch | mm | RH+LH | | h min | Y | F | inch | |
| 5.0U | .31 | 2.0 | 5.0KUI2.0ISO... | | .048 | .16 | .22 | .35 | .NVRC...-5.0KU (LH) |


Mini-L



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|------|-----------------|-----------------|----|-----------------|-----|-----|----------------|------------------|
| IC mm | mm | mm | RH | LH | h min | Y | F | inch | |
| 5.0L | 0.35 | 5LKIR0.35ISO... | 5LKIL0.35ISO... | | .008 | .01 | .15 | .29 | .NVR...-5LK (LH) |
| | 0.5 | 5LKIR0.5ISO... | 5LKIL0.5ISO... | | .011 | .02 | .15 | .29 | |
| | 0.75 | 5LKIR0.75ISO... | 5LKIL0.75ISO... | | .017 | .02 | .15 | .30 | |
| | 1.0 | 5LKIR1.0ISO... | 5LKIL1.0ISO... | | .023 | .03 | .16 | .30 | |
| | 1.25 | 5LKIR1.25ISO... | 5LKIL1.25ISO... | | .028 | .04 | .17 | .31 | |
| | 1.5 | 5LKIR1.5ISO... | 5LKIL1.5ISO... | | .034 | .04 | .17 | .31 | |
| | 1.75 | 5LKIR1.75ISO... | 5LKIL1.75ISO... | | .040 | .04 | .18 | .31 | |
| | 2.0 | 5LKIR2.0ISO... | 5LKIL2.0ISO... | | .045 | .04 | .18 | .31 | |

ISO Metric (con't)

MINIPRO



Micro - Double Ended

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------|------------------|------------------|------|-----------------|-----|------|------|-------|----------------|------------|
| | d mm | | mm | RH | L1 | L | F | Y | h min | inch | |
| M4 x 0.3 | 3.0 | 0.3 | 3.0SIR0.3ISO... | .63 | 1.97 | .05 | .01 | .007 | .13 | SMC...-3.0 | |
| M4 x 0.4 | | 0.4 | 3.0SIR0.4ISO... | .63 | 1.97 | .05 | .01 | .009 | .13 | | |
| M4 x 0.5 | | 0.5 | 3.0SIR0.5ISO... | .63 | 1.97 | .05 | .02 | .011 | .13 | | |
| M4 x 0.6 | | 0.6 | 3.0SIR0.6ISO... | .63 | 1.97 | .05 | .02 | .014 | .13 | | |
| M4.5 x 0.7 | | 0.7 | 3.0SIR0.7ISO... | .63 | 1.97 | .06 | .02 | .016 | .13 | | |
| M4.5 x 0.75 | 0.75 | 3.0SIR0.75ISO... | .63 | 1.97 | .06 | .02 | .017 | .13 | | | |
| M5 x 0.8 | 4.0 | 0.8 | 3.0SIR0.8ISO... | .63 | 1.97 | .06 | .02 | .018 | .13 | SMC...-4.0 | |
| M5 x 0.4 | | 0.4 | 4.0SIR0.4ISO... | .63 | 1.97 | .06 | .01 | .009 | .16 | | |
| M5 x 0.5 | | 0.5 | 4.0SIR0.5ISO... | .63 | 1.97 | .06 | .02 | .011 | .16 | | |
| M5 x 0.6 | | 0.6 | 4.0SIR0.6ISO... | .63 | 1.97 | .07 | .02 | .014 | .16 | | |
| M5 x 0.7 | | 0.7 | 4.0SIR0.7ISO... | .63 | 1.97 | .07 | .02 | .016 | .16 | | |
| M5.5 x 0.75 | 0.75 | 4.0SIR0.75ISO... | .63 | 1.97 | .07 | .02 | .017 | .17 | | | |
| M5.5 x 0.8 | 0.8 | 4.0SIR0.8ISO... | .63 | 1.97 | .07 | .02 | .018 | .17 | | | |
| M6 x 1 | 6.0 | 1.0 | 4.0SIR1.0ISO... | .63 | 1.97 | .08 | .04 | .023 | .17 | SMC...-6.0 | |
| M6 x 0.5 | | 0.5 | 6.0SIR0.5ISO... | .63 | 1.97 | .07 | .02 | .011 | .21 | | |
| M6.5 x 0.75 | | 0.75 | 6.0SIR0.75ISO... | .63 | 1.97 | .08 | .02 | .017 | .22 | | |
| M7 x 1 | | 1.0 | 6.0SIR1.0ISO... | .63 | 1.97 | .09 | .03 | .023 | .22 | | |
| M8 x 1.25 | | 1.25 | 6.0SIR1.25ISO... | .63 | 1.97 | .09 | .04 | .028 | .23 | | |
| M10.5 x 1.5 | 1.5 | 6.0SIR1.5ISO... | .63 | 1.97 | .10 | .04 | .034 | .24 | | | |

Left handed tool supplied by request (Example: 3.0SIL0.3ISO...).

Micro - Single Ended


microscope

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | | | Min. Bore Dia. | Toolholder |
|-----------|-------------|-------|-------------------------|-------|-----------------|-----|-----|------|-------|---------|-------|----------------|------------|
| | d mm | | mm | RH/LH | Helix ° | L1 | F | Y | h min | L2 ref* | L ref | D inch | |
| M4x0.5 | 4.0 | 0.5 | MS429TH0.50ISOL16R/L... | 3.5 | .63 | .04 | .02 | .011 | .72 | 1.39 | .13 | MH...-4.0 | |
| M5x0.5 | | 0.5 | MS439TH0.50ISOL16R/L... | | | .07 | .02 | .011 | | | .17 | | |
| M4x0.7 | | 0.7 | MS429TH0.70ISOL16R/L... | | | .04 | .02 | .016 | | | .13 | | |
| M5x0.8 | | 0.8 | MS429TH0.80ISOL16R/L... | | | .04 | .02 | .018 | | | .16 | | |
| M6x1.0 | | 1.0 | MS439TH1.00ISOL16R/L... | | | .07 | .03 | .023 | | | .19 | | |
| M5.5x0.5 | 5.0 | 0.5 | MS42TH0.50ISOL16R/L... | 3 | .63 | .07 | .02 | .011 | .72 | 1.62 | .19 | MH...-5.0 | |
| M5.5x0.75 | | 0.75 | M542TH0.75ISOL16R/L... | | | .07 | .02 | .017 | | | .18 | | |
| M7x1.0 | | 1.0 | M549TH1.00ISOL16R/L... | | | .09 | .03 | .023 | | | .23 | | |
| M6x0.5 | | 0.5 | M649TH0.50ISOL16R/L... | | | .07 | .02 | .011 | | | .21 | | |
| M6.5x0.75 | | 0.75 | M649TH0.75ISOL16R/L... | | | .07 | .02 | .017 | | | .22 | | |
| M7.5x1.0 | 6.0 | 1.0 | M659TH1.00ISOL16R/L... | 3 | .63 | .11 | .03 | .023 | .73 | 1.66 | .25 | MH...-6.0 | |
| M8x1.25 | | 1.25 | M659TH1.25ISOL16R/L... | | | .11 | .04 | .028 | | | .25 | | |
| M10x1.5 | | 1.5 | M659TH1.50ISOL16R/L... | | | .11 | .04 | .034 | | | .25 | | |


* L2 Ref: Repeatability within +/-0.0008

American UN - UNC, UNF, UNEF, UNS

External



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Standard

Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|------------|------------|---------------|--------------|-----------------|-----|-----|-------|-----|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 72 | 2ER72UN... | 2EL72UN... | .009 | .03 | .02 | - | - | NL..-2 (LH) |
| | | 64 | 2ER64UN... | 2EL64UN... | .009 | .03 | .02 | | | |
| | | 56 | 2ER56UN... | 2EL56UN... | .011 | .03 | .02 | | | |
| | | 48 | 2ER48UN... | 2EL48UN... | .013 | .02 | .02 | | | |
| | | 44 | 2ER44UN... | 2EL44UN... | .014 | .02 | .02 | | | |
| | | 40 | 2ER40UN... | 2EL40UN... | .015 | .02 | .02 | | | |
| | | 36 | 2ER36UN... | 2EL36UN... | .017 | .02 | .02 | | | |
| | | 32 | 2ER32UN... | 2EL32UN... | .019 | .02 | .02 | | | |
| | | 28 | 2ER28UN... | 2EL28UN... | .022 | .02 | .03 | | | |
| | | 27 | 2ER27UN... | 2EL27UN... | .023 | .03 | .03 | | | |
| | | 24 | 2ER24UN... | 2EL24UN... | .026 | .03 | .03 | | | |
| | | 20 | 2ER20UN... | 2EL20UN... | .031 | .03 | .04 | | | |
| | | 18 | 2ER18UN... | 2EL18UN... | .034 | .03 | .04 | | | |
| | | 16 | 2ER16UN... | 2EL16UN... | .038 | .04 | .04 | | | |
| 14 | 2ER14UN... | 2EL14UN... | .044 | .04 | .04 | | | | | |
| 3/8" | .63 | 80 | 3ER80UN... | 3EL80UN... | .007 | .03 | .01 | YE3 | YI3 | AL..-3 (LH) |
| | | 72 | 3ER72UN... | 3EL72UN... | .009 | .03 | .02 | | | |
| | | 64 | 3ER64UN... | 3EL64UN... | .009 | .03 | .02 | | | |
| | | 56 | 3ER56UN... | 3EL56UN... | .011 | .03 | .02 | | | |
| | | 48 | 3ER48UN... | 3EL48UN... | .013 | .02 | .02 | | | |
| | | 44 | 3ER44UN... | 3EL44UN... | .014 | .02 | .02 | | | |
| | | 40 | 3ER40UN... | 3EL40UN... | .015 | .02 | .02 | | | |
| | | 36 | 3ER36UN... | 3EL36UN... | .017 | .02 | .02 | | | |
| | | 32 | 3ER32UN... | 3EL32UN... | .019 | .02 | .02 | | | |
| | | 28 | 3ER28UN... | 3EL28UN... | .022 | .02 | .03 | | | |
| | | 27 | 3ER27UN... | 3EL27UN... | .023 | .03 | .03 | | | |
| | | 26 | 3ER26UN... | 3EL26UN... | .023 | .03 | .03 | | | |
| | | 24 | 3ER24UN... | 3EL24UN... | .026 | .03 | .03 | | | |
| | | 20 | 3ER20UN... | 3EL20UN... | .031 | .03 | .04 | | | |
| | | 18 | 3ER18UN... | 3EL18UN... | .034 | .03 | .04 | | | |
| | | 16 | 3ER16UN... | 3EL16UN... | .038 | .04 | .04 | | | |
| | | 14 | 3ER14UN... | 3EL14UN... | .044 | .04 | .05 | | | |
| | | 13 | 3ER13UN... | 3EL13UN... | .047 | .04 | .05 | | | |
| | | 12 | 3ER12UN... | 3EL12UN... | .051 | .04 | .06 | | | |
| | | 11.5 | 3ER11.5UN... | 3EL11.5UN... | .053 | .04 | .06 | | | |
| 11 | 3ER11UN... | 3EL11UN... | .056 | .04 | .06 | | | | | |
| 10 | 3ER10UN... | 3EL10UN... | .061 | .04 | .06 | | | | | |
| 9 | 3ER9UN... | 3EL9UN... | .068 | .05 | .07 | | | | | |
| 8 | 3ER8UN... | 3EL8UN... | .077 | .05 | .06 | | | | | |



American UN - UNC, UNF, UNEF, UNS (con't)

External

Defined by: ANSI B1.1:74
Tolerance class: 2A/2B

SCB
Sintered
Chipbreaker

V6

Standard

F-Line

U Style

Standard


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|---|--------|-------|---------------|---------------|-----------------|------|-----|-------|--------|------------|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  SCB | 3/8" | .63 | 36 | 3JER36UN... | | .017 | .05 | .02 | YE3 | - | AL..-3 |
| | | | 32 | 3JER32UN... | | .019 | .05 | .02 | | | |
| | | | 28 | 3JER28UN... | | .022 | .03 | .03 | | | |
| | | | 24 | 3JER24UN... | | .026 | .03 | .03 | | | |
| | | | 20 | 3JER20UN... | | .031 | .03 | .03 | | | |
| | | | 18 | 3JER18UN... | | .034 | .03 | .03 | | | |
| | | | 16 | 3JER16UN... | | .038 | .03 | .03 | | | |
| | | | 14 | 3JER14UN... | | .044 | .05 | .06 | | | |
| | | | 13 | 3JER13UN... | | .047 | .05 | .06 | | | |
| | | | 12 | 3JER12UN... | | .051 | .05 | .06 | | | |
| | | | 10 | 3JER10UN... | | .061 | .05 | .06 | | | |
|  V6 | 3/8" | .63 | 32 | 3ER32UN-6C... | | .019 | .08 | .07 | YE3-6C | - | AL..-3 |
| | | | 28 | 3ER28UN-6C... | | .022 | .08 | .08 | | | |
| | | | 24 | 3ER24UN-6C... | | .026 | .07 | .08 | | | |
| | | | 20 | 3ER20UN-6C... | | .031 | .07 | .08 | | | |
| | | | 18 | 3ER18UN-6C... | | .034 | .07 | .09 | | | |
| | | | 16 | 3ER16UN-6C... | | .038 | .07 | .09 | | | |
| | | | 14 | 3ER14UN-6C... | | .044 | .07 | .11 | | | |
|  | 1/2" | .87 | 7 | 4ER7UN... | 4EL7UN... | .087 | .06 | .09 | YE4 | YI4 | AL..-4 (LH) |
| | | | 6 | 4ER6UN... | 4EL6UN... | .102 | .06 | .09 | | | |
| | | | 5 | 4ER5UN... | 4EL5UN... | .123 | .07 | .10 | | | |
|  F-LINE | 1/2"F | .91 | 7 | 4FER7UN... | | .087 | .06 | .09 | YE4F | | AL..-4F |
| | | | 6 | 4FER6UN... | | .102 | .06 | .09 | | | |
| | 5/8" | 1.06 | 4.5 | 5ER4.5UN... | 5EL4.5UN... | .136 | .07 | .11 | YE5 | YI5 | AL..-5 (LH) |
| | | | 4 | 5ER4UN... | 5EL4UN... | .153 | .08 | .12 | | | |

U Style


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|---|--------|-------|---------------|-------------|-----------------|-----|-----|-------|------|--------------|
| IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
|  | 1/2"U | .87 | 4.5 | 4UE4.5UN... | .136 | .08 | .43 | YE4U | YI4U | AL..-4U (LH) |
| | | | 4 | 4UE4UN... | .153 | .08 | .43 | | | |
| | 5/8"U | 1.06 | 3 | 5UE3UN... | .204 | .10 | .54 | YE5U | YI5U | AL..-5U (LH) |

American UN - UNC, UNF, UNEF, UNS (con't)

External



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Slim Throat



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|-------------|-------------|---------------|-------------|-----------------|-----|-----|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 1/4"V | .43 | 20 | 2VER20UN... | 2VEL20UN... | .031 | .03 | .09 | .13 | NL..-2V (LH) |
| | | 18 | 2VER18UN... | 2VEL18UN... | .034 | .03 | .09 | .13 | |
| | | 16 | 2VER16UN... | 2VEL16UN... | .038 | .03 | .09 | .13 | |
| | | 14 | 2VER14UN... | 2VEL14UN... | .044 | .03 | .08 | .13 | |
| | | 12 | 2VER12UN... | 2VEL12UN... | .051 | .03 | .07 | .13 | |
| 3/8"V | .63 | 32 | 3VER32UN... | 3VEL32UN... | .019 | .04 | .12 | .14 | NL..-3V (LH) |
| | | 28 | 3VER28UN... | 3VEL28UN... | .022 | .04 | .12 | .14 | |
| | | 24 | 3VER24UN... | 3VEL24UN... | .026 | .04 | .11 | .14 | |
| | | 20 | 3VER20UN... | 3VEL20UN... | .031 | .04 | .11 | .14 | |
| | | 18 | 3VER18UN... | 3VEL18UN... | .034 | .04 | .10 | .14 | |
| | | 16 | 3VER16UN... | 3VEL16UN... | .038 | .04 | .10 | .14 | |
| | | 14 | 3VER14UN... | 3VEL14UN... | .044 | .04 | .09 | .14 | |
| | | 12 | 3VER12UN... | 3VEL12UN... | .051 | .04 | .09 | .14 | |
| 10 | 3VER10UN... | 3VEL10UN... | .061 | .04 | .08 | .14 | | | |
| 8 | 3VER8UN... | 3VEL8UN... | .077 | .04 | .08 | .14 | | | |
| 1/2"V | .87 | 7 | 4VER7UN... | 4VEL7UN... | .087 | .04 | .10 | .19 | NL..-4V (LH) |



V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|---------------|------------|-----------------|-----|-----|-----|----------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 4 | 5VER4UN... | 5VEL4UN... | .153 | .04 | .13 | .24 | NL..-5V-6 (LH) |
| | | 3 | 5VER3UN... | 5VEL3UN... | .204 | .04 | .17 | .31 | NL..-5V-8 (LH) |


American UN - UNC, UNF, UNEF, UNS (con't)

External



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B

RS/LS Varied range of threading standards for machining between shoulders and close to spindle.



VG-Cut




| Pocket Size | Ordering Code | Dimensions inch | | | | | No. of Passes | Helix | | Min. Thread Diameter | Toolholder |
|-------------|-----------------------|-----------------|-------|-----------|-------|-----|---------------|-------|-----|----------------------|----------------------------|
| | | RH | W ref | Pitch TPI | h min | Y | | L ref | Deg | | |
| 3 | VGD3.0UN32RH-RS/LS... | | | 32 | .019 | .03 | 5 - 8 | | | 5/32"-32 UNC | Monoblock VGE...T12 |
| | VGD3.0UN28RH-RS/LS... | | | 28 | .022 | .03 | 5 - 9 | | | 3/16"-28 UNC | |
| | VGD3.0UN24RH-RS/LS... | | | 24 | .026 | .03 | 5 - 9 | | | 7/32"-24 UNC | |
| | VGD3.0UN20RH-RS/LS... | | .12 | 20 | .031 | .03 | 6 - 10 | 2.5° | | 1/4"-20 UNC | |
| | VGD3.0UN18RH-RS/LS... | | | 18 | .034 | .04 | 7 - 12 | | | 5/16"-18 UNC | |
| | VGD3.0UN16RH-RS/LS... | | | 16 | .038 | .04 | 7 - 12 | | | 3/8"-16 UNC | |
| | VGD3.0UN14RH-RS/LS... | | | 14 | .044 | .04 | 8 - 14 | | | 7/16"-14 UNC | |
| | VGD3.0UN12RH-RS/LS... | | | 12 | .051 | .05 | 8 - 14 | | | 9/16"-14 UNC | |


LH Helix threads available upon request.

American UN - UNC, UNF, UNEF, UNS (con't)

External



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



M+ Style

F-Line M+

M+ Style




FLINE


| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|----------------|-----------------|-----|-----|--------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | |
| 3/8" | .63 | 20 | 3 | 3ER20UN3M+... | .031 | .09 | .13 | YE3M | AL...-3 |
| | | 18 | 2 | 3ER18UN2M+... | .034 | .06 | .09 | | |
| | | 18 | 3 | 3ER18UN3M+... | .034 | .09 | .14 | | |
| | | 16 | 2 | 3ER16UN2M+... | .038 | .07 | .10 | | |
| | | 14 | 2 | 3ER14UN2M+... | .044 | .07 | .11 | | |
| 1/2" | .87 | 16 | 3 | 4ER16UN3M+... | .038 | .10 | .16 | YE4M | AL...-4 |
| | | 14 | 2 | 4ER14UN2M+... | .044 | .07 | .11 | | |
| | | 12 | 2 | 4ER12UN2M+... | .051 | .09 | .13 | | |
| | | 12 | 3 | 4ER12UN3M+... | .051 | .13 | .21 | | |
| | | 11 | 2 | 4ER11UN2M+... | .056 | .09 | .14 | | |
| 1/2"F | .91 | 16 | 3 | 4FER16UN3M+... | .038 | .10 | .16 | YE4M3F | AL...-4MF |
| | | 12 | 3 | 4FER12UN3M+... | .051 | .13 | .21 | | |
| | | 12 | 2 | 4FER12UN2M+... | .051 | .09 | .13 | YE4M2F | |
| | | 10 | 2 | 4FER10UN2M+... | .061 | .10 | .15 | | |
| 5/8" | 1.06 | 8 | 2 | 5ER8UN2M+... | .077 | .12 | .19 | YE5M | AL...-5M |

American UN - UNC, UNF, UNEF, UNS (con't)


Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Standard




SCB
Sintered
Chipbreaker

Standard


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|---|-------------|------------|---------------|-------------|-----------------|------|-----|-------|-----|------------|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  | 1/4" | .43 | 72 | 2IR72UN... | 2IL72UN... | .008 | .03 | .01 | - | - | NVR..-2 (LH) |
| | | | 64 | 2IR64UN... | 2IL64UN... | .009 | .03 | .02 | | | |
| | | | 56 | 2IR56UN... | 2IL56UN... | .010 | .03 | .02 | | | |
| | | | 48 | 2IR48UN... | 2IL48UN... | .012 | .02 | .02 | | | |
| | | | 44 | 2IR44UN... | 2IL44UN... | .013 | .02 | .02 | | | |
| | | | 40 | 2IR40UN... | 2IL40UN... | .015 | .02 | .02 | | | |
| | | | 36 | 2IR36UN... | 2IL36UN... | .016 | .02 | .02 | | | |
| | | | 32 | 2IR32UN... | 2IL32UN... | .018 | .02 | .02 | | | |
| | | | 28 | 2IR28UN... | 2IL28UN... | .020 | .02 | .03 | | | |
| | | | 27 | 2IR27UN... | 2IL27UN... | .021 | .03 | .03 | | | |
| | | | 24 | 2IR24UN... | 2IL24UN... | .024 | .03 | .03 | | | |
| | | | 20 | 2IR20UN... | 2IL20UN... | .029 | .03 | .04 | | | |
| | | | 18 | 2IR18UN... | 2IL18UN... | .032 | .03 | .04 | | | |
| | | | 16 | 2IR16UN... | 2IL16UN... | .036 | .04 | .04 | | | |
| 14 | 2IR14UN... | 2IL14UN... | .041 | .04 | .04 | | | | | | |
|  | 1/4" SCB | .43 | 36 | 2JIR36UN... | | .016 | .04 | .02 | - | - | NVR..-2 |
| | | | 32 | 2JIR32UN... | | .018 | .05 | .02 | | | |
| | | | 28 | 2JIR28UN... | | .020 | .02 | .03 | | | |
| | | | 24 | 2JIR24UN... | | .024 | .03 | .03 | | | |
| | | | 20 | 2JIR20UN... | | .029 | .02 | .03 | | | |
| | | | 18 | 2JIR18UN... | | .032 | .02 | .03 | | | |
|  | 3/8" | .63 | 72 | 3IR72UN... | 3IL72UN... | .008 | .03 | .01 | Y13 | YE3 | AVR..-3 (LH) |
| | | | 64 | 3IR64UN... | 3IL64UN... | .009 | .03 | .02 | | | |
| | | | 56 | 3IR56UN... | 3IL56UN... | .010 | .03 | .02 | | | |
| | | | 48 | 3IR48UN... | 3IL48UN... | .012 | .02 | .02 | | | |
| | | | 44 | 3IR44UN... | 3IL44UN... | .013 | .02 | .02 | | | |
| | | | 40 | 3IR40UN... | 3IL40UN... | .015 | .02 | .02 | | | |
| | | | 36 | 3IR36UN... | 3IL36UN... | .016 | .02 | .02 | | | |
| | | | 32 | 3IR32UN... | 3IL32UN... | .020 | .02 | .02 | | | |
| | | | 28 | 3IR28UN... | 3IL28UN... | .020 | .02 | .03 | | | |
| | | | 27 | 3IR27UN... | 3IL27UN... | .021 | .03 | .03 | | | |
| | | | 26 | 3IR26UN... | 3IL26UN... | .022 | .03 | .03 | | | |

American UN - UNC, UNF, UNEF, UNS (con't)


Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Standard



SCB
Sintered
Chipbreaker

Standard




SCB


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|------------|-----------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 24 | 3IR24UN... | 3IL24UN... | .024 | .03 | .03 | Y13 | YE3 | AVR..-3 (LH) |
| | | 20 | 3IR20UN... | 3IL20UN... | .029 | .03 | .04 | | | |
| | | 18 | 3IR18UN... | 3IL18UN... | .032 | .03 | .04 | | | |
| | | 16 | 3IR16UN... | 3IL16UN... | .036 | .04 | .04 | | | |
| | | 14 | 3IR14UN... | 3IL14UN... | .041 | .04 | .05 | | | |
| | | 13 | 3IR13UN... | 3IL13UN... | .044 | .04 | .05 | | | |
| | | 12 | 3IR12UN... | 3IL12UN... | .048 | .04 | .06 | | | |
| | | 11.5 | 3IR11.5UN... | 3IL11.5UN... | .050 | .04 | .06 | | | |
| | | 11 | 3IR11UN... | 3IL11UN... | .052 | .04 | .06 | | | |
| | | 10 | 3IR10UN... | 3IL10UN... | .058 | .04 | .06 | | | |
| 9 | 3IR9UN... | 3IL9UN... | .064 | .05 | .07 | | | | | |
| 8 | 3IR8UN... | 3IL8UN... | .072 | .04 | .06 | | | | | |
| 3/8" SCB | .63 | 28 | 3JIR28UN... | | .020 | .02 | .03 | Y13 | - | AVR..-3 |
| | | 24 | 3JIR24UN... | | .024 | .03 | .03 | | | |
| | | 20 | 3JIR20UN... | | .029 | .02 | .03 | | | |
| | | 18 | 3JIR18UN... | | .032 | .02 | .03 | | | |
| | | 16 | 3JIR16UN... | | .036 | .03 | .03 | | | |
| | | 14 | 3JIR14UN... | | .041 | .04 | .06 | | | |
| | | 13 | 3JIR13UN... | | .044 | .04 | .06 | | | |
| | | 12 | 3JIR12UN... | | .048 | .04 | .06 | | | |
| | | 10 | 3JIR10UN... | | .058 | .04 | .06 | | | |
| | | 9 | 3JIR9UN... | | .064 | .04 | .06 | | | |
| 8 | 3JIR8UN... | | .072 | .04 | .06 | | | | | |

American UN - UNC, UNF, UNEF, UNS (con't)


Internal




Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



V6



Standard



F-Line


Standard




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------------|--------|-------|---------------|-------------|-----------------|-----|-----|------------------|-----|------------------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" V6 | .63 | 32 | 3IR32UN-6C... | | .020 | .08 | .07 | Y13-6C | - | AVR..-3 NVRC..-3V6 |
| | | 28 | 3IR28UN-6C... | | .020 | .07 | .07 | | | |
| | | 24 | 3IR24UN-6C... | | .024 | .07 | .07 | | | |
| | | 20 | 3IR20UN-6C... | | .029 | .07 | .08 | | | |
| | | 18 | 3IR18UN-6C... | | .032 | .07 | .08 | | | |
| | | 16 | 3IR16UN-6C... | | .036 | .06 | .09 | | | |
| | | 14 | 3IR14UN-6C... | | .041 | .07 | .10 | | | |
| | | 13 | 3IR13UN-6C... | | .044 | .07 | .11 | | | |
| 1/2" | .87 | 7 | 4IR7UN... | 4IL7UN... | .082 | .06 | .09 | Y14 | YE4 | AVR..-4 (LH) |
| | | 6 | 4IR6UN... | 4IL6UN... | .096 | .06 | .09 | | | |
| | | 5 | 4IR5UN... | 4IL5UN... | .115 | .06 | .09 | | | |
| 1/2" ^F | .91 | 7 | 4FIR7UN... | | .082 | .06 | .09 | Y14 ^F | | AVRC...-4 ^F |
| | | 6 | 4FIR6UN... | | .096 | .06 | .09 | | | |
| 5/8" | 1.06 | 4.5 | 5IR4.5UN... | 5IL4.5UN... | .128 | .07 | .09 | Y15 | YE5 | AVR..-5 (LH) |
| | | 4 | 5IR4UN... | 5IL4UN... | .144 | .07 | .11 | | | |

American UNC (con't)

Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Coarse Pitch

U Style Coarse Pitch

Coarse Pitch RH



| Thread | Insert Size | | Ordering Code | Dimensions inch | | | Toolholder RH | Min Bore Dia. inch |
|--------------|-------------|--------|----------------------|-----------------|-------|-----|--------------------|--------------------|
| | IC | L inch | | RH | h min | X | | |
| 1/2" x 13UN | 6.0 | .39 | 6.0KIR13UN158/001... | .044 | .03 | .04 | BNVRC0375S-6.0K | .42 |
| 9/16" x 12UN | 1/4" | .43 | 2IR12UN158/002... | .048 | .04 | .04 | NVRC040-2-157/001 | .47 |
| 5/8" x 11UN | 1/4"U | | 2UIR11UN158/003... | .052 | .05 | .22 | NVRC044-2U-157/002 | .53 |
| 3/4" x 10UN | 3/8" | .63 | 3IR10UN... | .058 | .04 | .06 | NVRC050-3-157/016 | .64 |
| 7/8" x 9UN | | | 3IR9UN... | .064 | .05 | .07 | NVRC050-3-157/016 | .76 |
| 1" x 8UN | | | 3IR8UN... | .072 | .04 | .06 | NVRC0625-3 | .87 |
| 1 1/8" x 7UN | 1/2" | .87 | 4IR7UN... | .082 | .06 | .09 | NVRC075-4 | .97 |
| 1 1/4" x 7UN | | | 4IR7UN... | .082 | .06 | .09 | NVRC075-4 | 1.09 |
| 1 3/8" x 6UN | | | 4IR6UN... | .096 | .06 | .09 | NVRC075-4 | 1.19 |

Coarse Pitch LH



| Thread | Insert Size | | Ordering Code | Dimensions inch | | | Toolholder LH | Min Bore Dia. inch |
|--------------|-------------|--------|----------------------|-----------------|-------|-----|----------------------|--------------------|
| | IC | L inch | | LH | h min | X | | |
| 1/2" x 13UN | 6.0 | .39 | 6.0KIL13UN158/016... | .044 | .03 | .04 | BNVRC0375S-6.0KLH | .42 |
| 9/16" x 12UN | 1/4" | .43 | 2IL12UN158/017... | .048 | .04 | .04 | NVRC040-2LH-157/025 | .47 |
| 5/8" x 11UN | 1/4"U | | 2UIR11UN158/003... | .052 | .05 | .22 | NVRC044-2ULH-157/026 | .53 |
| 3/4" x 10UN | 3/8" | .63 | 3IL10UN... | .058 | .04 | .06 | NVRC050-3LH-157/035 | .64 |
| 7/8" x 9UN | | | 3IL9UN... | .064 | .05 | .07 | NVRC050-3LH-157/035 | .76 |
| 1" x 8UN | | | 3IL8UN... | .072 | .04 | .06 | NVRC0625-3LH | .87 |
| 1 1/8" x 7UN | 1/2" | .87 | 4IL7UN... | .082 | .06 | .09 | NVRC075-4LH | .97 |
| 1 1/4" x 7UN | | | 4IL7UN... | .082 | .06 | .09 | NVRC075-4LH | 1.09 |
| 1 3/8" x 6UN | | | 4IL6UN... | .096 | .06 | .09 | NVRC075-4LH | 1.19 |

U Type RH inserts can be used for both LH and RH applications.

American UN - UNC, UNF, UNEF, UNS (con't)

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2A/2B

U Style V Style M+ Style F-Line M+

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|-------|-----------------|-----|------|-------|---------------|------------|
| IC | L inch | TPI | RH+LH | h min | X | Y | RH | LH | | |
| 1/2"U | .87 | 4.5 | 4UI4.5UN... | .128 | .09 | .43 | YI4U | YE4U | AVR..-4U (LH) | |
| | | 4 | 4UI4UN... | .144 | .09 | .43 | | | | |
| 5/8"U | 1.06 | 3 | 5UI3UN... | .193 | .11 | .54 | YI5U | YE5U | AVR..-5U (LH) | |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | | Toolholder |
|-------------|--------|-------|---------------|------------|-----------------|-----|-----|-----|---------------|------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | | |
| 5/8"V | 1.06 | 4 | 5VIR4UN... | 5VIL4UN... | .144 | .04 | .13 | .24 | NVR..-5V (LH) | |
| | | 3 | 5VIR3UN... | 5VIL3UN... | .193 | .04 | .17 | .31 | | |

M+ Style




F-LINE

| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|----------------|----|-----------------|-----|-----|--------|-------------|
| IC | L inch | TPI | | RH | LH | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 12 | 2 | 3IR12UN2M+... | | .048 | .09 | .13 | YI3M | AVR..-3 |
| | | 14 | 2 | 3IR14UN2M+... | | .041 | .07 | .11 | | |
| | | 16 | 2 | 3IR16UN2M+... | | .036 | .07 | .10 | | |
| 1/2" | .87 | 16 | 3 | 4IR16UN3M+... | | .036 | .10 | .16 | YI4M | AVR..-4 |
| | | 14 | 2 | 4IR14UN2M+... | | .041 | .07 | .11 | | |
| | | 12 | 2 | 4IR12UN2M+... | | .048 | .09 | .13 | | |
| 1/2"F | .91 | 12 | 2 | 4FIR12UN2M+... | | .048 | .09 | .13 | YI4M2F | AVRC...-4MF |
| 5/8" | 1.06 | 8 | 2 | 5IR8UN2M+... | | .072 | .12 | .19 | YI5M | AVR..-5M |


American UN - UNC, UNF, UNEF, UNS (con't)

Mini-V

Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Mini-V



| Min. Thread | Insert Style | Pitch | Ordering Code | Dimensions inch | | | | | | Helix | Toolholder |
|-------------|--------------|-------|---------------|-----------------|-----|-----|-----|------|-----|----------|------------|
| | | | | TPI | RH | d | T | F | Y | | |
| 3/8"-32UNEF | V08 | 32 | V08TH32UNR... | .24 | .15 | .17 | .02 | .018 | 1.5 | .V08-... | |
| 3/8"-28UN | | 28 | V08TH28UNR... | | | .17 | .02 | .020 | 2 | | |
| 3/8"-24UNF | | 24 | V08TH24UNR... | | | .17 | .03 | .024 | 2 | | |
| 3/8"-20UN | | 20 | V08TH20UNR... | | | .18 | .03 | .029 | 2.5 | | |
| 3/8"-18UNS | | 18 | V08TH18UNR... | | | .18 | .03 | .032 | 2.5 | | |
| 3/8"-16UNC | | 16 | V08TH16UNR... | | | .17 | .04 | .036 | 2.5 | | |
| 7/16"-14UNC | V11 | 14 | V08TH14UNR... | .31 | .17 | .19 | .04 | .041 | 3 | .V11-... | |
| 9/16"-12UNC | | 12 | V11TH12UNR... | | | .25 | .05 | .048 | 2.5 | | |

American UN - UNC, UNF, UNEF, UNS (con't)

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2A/2B

Mini-3 Standard

| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-----|-------------|--------|---------------|---------------|---------------|-----------------|-------|-----|-------------------|-------------------|
| | IC mm | L inch | | TPI | RH | LH | h min | Y | F | |
| | 4.0 | .24 | 32 | 4.0KIR32UN... | 4.0KIL32UN... | .018 | .02 | .14 | .24 | .NVR...-4.0K (LH) |
| | | | 28 | 4.0KIR28UN... | 4.0KIL28UN... | .020 | .02 | .14 | .24 | |
| | | | 24 | 4.0KIR24UN... | 4.0KIL24UN... | .024 | .02 | .14 | .25 | |
| | | | 20 | 4.0KIR20UN... | 4.0KIL20UN... | .029 | .02 | .15 | .25 | |
| | | | 18 | 4.0KIR18UN... | 4.0KIL18UN... | .032 | .03 | .15 | .25 | |
| | 5.0 | .31 | 32 | 5.0KIR32UN... | 5.0KIL32UN... | .018 | .02 | | | .NVR...-5.0K (LH) |
| | | | 28 | 5.0KIR28UN... | 5.0KIL28UN... | .020 | .02 | | | |
| | | | 24 | 5.0KIR24UN... | 5.0KIL24UN... | .024 | .02 | | | |
| | | | 20 | 5.0KIR20UN... | 5.0KIL20UN... | .029 | .03 | .19 | .31 | |
| | | | 18 | 5.0KIR18UN... | 5.0KIL18UN... | .032 | .03 | | | |
| 6.0 | .39 | 40 | 6.0KIR40UN... | 6.0KIL40UN... | .015 | .02 | .18 | .37 | .NVR...-6.0K (LH) | |
| | | 32 | 6.0KIR32UN... | 6.0KIL32UN... | .018 | .02 | .18 | .37 | | |
| | | 28 | 6.0KIR28UN... | 6.0KIL28UN... | .020 | .03 | .19 | .38 | | |
| | | 24 | 6.0KIR24UN... | 6.0KIL24UN... | .024 | .03 | .19 | .38 | | |
| | | 20 | 6.0KIR20UN... | 6.0KIL20UN... | .029 | .04 | .19 | .39 | | |
| | | 18 | 6.0KIR18UN... | 6.0KIL18UN... | .032 | .04 | .20 | .39 | | |
| | | 16 | 6.0KIR16UN... | 6.0KIL16UN... | .036 | .04 | .20 | .39 | | |

Mini-3 U Style


| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|--|-------------|--------|-------|---------------|-------|-----------------|-----|-----|--------------------|------------|
| | IC mm | L inch | | TPI | RH+LH | h min | Y | F | inch | |
| | 5.0U | .31 | 13 | 5.0KUI13UN... | .047 | | .22 | | .NVR...-5.0KU (LH) | |
| | | | 12 | 5.0KUI12UN... | .051 | .16 | .22 | .35 | | |
| | | | 11 | 5.0KUI11UN... | .056 | .22 | | | | |

Mini-L

| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|--|-------------|-----|--------------|---------------|------|-----------------|-----|-----|------------------|------------|
| | IC mm | TPI | | RH | LH | h min | Y | F | inch | |
| | 5.0L | 40 | 5LKIR40UN... | 5LKIL40UN... | .015 | .02 | .15 | .30 | .NVR...-5LK (LH) | |
| | | 32 | 5LKIR32UN... | 5LKIL32UN... | .018 | .02 | .15 | .30 | | |
| | | 28 | 5LKIR28UN... | 5LKIL28UN... | .020 | .03 | .16 | .30 | | |
| | | 24 | 5LKIR24UN... | 5LKIL24UN... | .024 | .03 | .16 | .30 | | |
| | | 20 | 5LKIR20UN... | 5LKIL20UN... | .029 | .04 | .17 | .30 | | |
| | | 18 | 5LKIR18UN... | 5LKIL18UN... | .032 | .04 | .17 | .31 | | |
| | | 16 | 5LKIR16UN... | 5LKIL16UN... | .036 | .04 | .17 | .31 | | |
| | | 14 | 5LKIR14UN... | 5LKIL14UN... | .041 | .04 | .18 | .31 | | |

American UN - UNC, UNF, UNEF, UNS (con't)

MINIPRO



Micro - Double Ended

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------|-------|---------------|-----|-----------------|-----|-----|-------|------|----------------|------------|
| | d mm | mm | RH | L1 | L | F | Y | h min | Inch | | |
| 10-40UNS | 3.0 | 40 | 3.0SIR40UN... | .63 | 1.97 | .05 | .02 | .015 | .13 | SMC..-3.0 | |
| 8-36UNF | | 36 | 3.0SIR36UN... | .63 | 1.97 | .06 | .02 | .016 | .13 | | |
| 8-32UNF | | 32 | 3.0SIR32UN... | .63 | 1.97 | .06 | .02 | .018 | .13 | | |
| 10-40UNS | 4.0 | 40 | 4.0SIR40UN... | .63 | 1.97 | .06 | .02 | .015 | .16 | SMC..-4.0 | |
| 10-36UNS | | 36 | 4.0SIR36UN... | .63 | 1.97 | .07 | .02 | .016 | .16 | | |
| 12-32UNEF | | 32 | 4.0SIR32UN... | .63 | 1.97 | .07 | .02 | .018 | .16 | | |
| 12-28UNF | 4.0 | 28 | 4.0SIR28UN... | .63 | 1.97 | .07 | .03 | .020 | .17 | SMC..-4.0 | |
| 1/4"-27UNS | | 27 | 4.0SIR27UN... | .63 | 1.97 | .07 | .03 | .021 | .17 | | |
| 12-24UNC | | 24 | 4.0SIR24UN... | .63 | 1.97 | .08 | .03 | .024 | .17 | | |
| 1/4"-20UNC | 6.0 | 20 | 4.0SIR20UN... | .63 | 1.97 | .08 | .03 | .029 | .17 | SMC..-6.0 | |
| 1/4"-32UNEF | | 32 | 6.0SIR32UN... | .63 | 1.97 | .08 | .02 | .018 | .22 | | |
| 5/16"-28UN | | 28 | 6.0SIR28UN... | .63 | 1.97 | .08 | .03 | .020 | .22 | | |
| 5/16"-27UNS | 6.0 | 27 | 6.0SIR27UN... | .63 | 1.97 | .08 | .03 | .021 | .22 | SMC..-6.0 | |
| 5/16"-24UNF | | 24 | 6.0SIR24UN... | .63 | 1.97 | .09 | .03 | .024 | .22 | | |
| 5/16"-20UN | | 20 | 6.0SIR20UN... | .63 | 1.97 | .09 | .04 | .029 | .23 | | |
| 5/16"-18UNC | 6.0 | 18 | 6.0SIR18UN... | .63 | 1.97 | .09 | .04 | .032 | .23 | SMC..-6.0 | |
| 3/8"-16UNC | | 16 | 6.0SIR16UN... | .63 | 1.97 | .10 | .04 | .036 | .24 | | |

Left handed tool supplied by request (Example: 6.0SIL16UN...).

Micro - Single Ended


microscope

| Thread | Insert Dia. | Pitch | Ordering Code | | Helix ° | L1 | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------|-------|----------------------|---------|---------|-----|-----------------|------|-----|-------|---------|----------------|------------|
| | d mm | TPI | RH/LH | Helix ° | | | L1 | F | Y | h min | L2 ref* | L ref | |
| No.8-32UNC | 4.0 | 32 | MS429TH32UNL16R/L... | 3.5 | .63 | .04 | .02 | .018 | .72 | 1.39 | .13 | MH...-4.0 | |
| No.10-28UNS | | 28 | MS429TH28UNL16R/L... | | | .04 | .03 | .020 | | | | | .14 |
| 1/4"-27UNS | 5.0 | 27 | M549TH27UNL16R/L... | 3.5 | .63 | .09 | .03 | .021 | .72 | 1.62 | .21 | MH...-5.0 | |
| 1/4"-24UNS | | 24 | M542TH24UNL16R/L... | | | .07 | .03 | .024 | | | | | .18 |
| 1/4"-20UNC | 6.0 | 20 | M542TH20UNL16R/L... | 3.5 | .63 | .07 | .04 | .029 | .73 | 1.66 | .25 | MH...-6.0 | |
| 5/16"-18UNC | | 18 | M659TH18UNL16R/L... | | | .11 | .04 | .032 | | | | | .30 |
| 3/8"-16UNC | | 16 | M659TH16UNL16R/L... | | | .11 | .04 | .036 | | | | | .30 |


* L2 Ref: Repeatability within +/- .0008

American UNR

External



Defined by: ASME B1.1-2003
Tolerance class: 2A/2B



Standard External



Standard - External



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 8 | 3ER8UNR... | 3EL8UNR... | .077 | .05 | .06 | YE3 | YI3 | AL...-3 (LH) |

Whitworth - BSW, BSP, BSF, BSB

External



Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A

Standard


Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|-----------|-----------|---------------|-----------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 72 | 2ER72W... | 2EL72W... | .009 | .03 | .02 | - | - | NL ...-2 (LH) |
| | | 60 | 2ER60W... | 2EL60W... | .011 | .03 | .02 | | | |
| | | 56 | 2ER56W... | 2EL56W... | .011 | .03 | .02 | | | |
| | | 48 | 2ER48W... | 2EL48W... | .013 | .02 | .02 | | | |
| | | 40 | 2ER40W... | 2EL40W... | .016 | .02 | .02 | | | |
| | | 36 | 2ER36W... | 2EL36W... | .018 | .02 | .02 | | | |
| | | 32 | 2ER32W... | 2EL32W... | .020 | .02 | .02 | | | |
| | | 28 | 2ER28W... | 2EL28W... | .023 | .02 | .03 | | | |
| | | 26 | 2ER26W... | 2EL26W... | .025 | .03 | .03 | | | |
| | | 24 | 2ER24W... | 2EL24W... | .027 | .03 | .03 | | | |
| | | 22 | 2ER22W... | 2EL22W... | .029 | .03 | .04 | | | |
| | | 20 | 2ER20W... | 2EL20W... | .032 | .03 | .04 | | | |
| | | 19 | 2ER19W... | 2EL19W... | .034 | .03 | .04 | | | |
| | | 18 | 2ER18W... | 2EL18W... | .035 | .03 | .04 | | | |
| 16 | 2ER16W... | 2EL16W... | .040 | .04 | .04 | | | | | |
| 14 | 2ER14W... | 2EL14W... | .046 | .04 | .05 | | | | | |
| 3/8" | .63 | 72 | 3ER72W... | 3EL72W... | .009 | .03 | .02 | YE3 | YI3 | AL...-3 (LH) |
| | | 60 | 3ER60W... | 3EL60W... | .011 | .03 | .02 | | | |
| | | 56 | 3ER56W... | 3EL56W... | .011 | .03 | .02 | | | |
| | | 48 | 3ER48W... | 3EL48W... | .013 | .02 | .02 | | | |
| | | 40 | 3ER40W... | 3EL40W... | .016 | .02 | .02 | | | |
| | | 36 | 3ER36W... | 3EL36W... | .018 | .02 | .02 | | | |
| | | 32 | 3ER32W... | 3EL32W... | .020 | .02 | .02 | | | |
| | | 30 | 3ER30W... | 3EL30W... | .022 | .02 | .03 | | | |
| | | 28 | 3ER28W... | 3EL28W... | .023 | .02 | .03 | | | |
| | | 26 | 3ER26W... | 3EL26W... | .025 | .03 | .03 | | | |
| | | 24 | 3ER24W... | 3EL24W... | .027 | .03 | .03 | | | |
| | | 22 | 3ER22W... | 3EL22W... | .029 | .03 | .04 | | | |
| | | 20 | 3ER20W... | 3EL20W... | .032 | .03 | .04 | | | |
| | | 19 | 3ER19W... | 3EL19W... | .034 | .03 | .04 | | | |
| | | 18 | 3ER18W... | 3EL18W... | .035 | .03 | .04 | | | |
| | | 16 | 3ER16W... | 3EL16W... | .040 | .04 | .04 | | | |
| | | 14 | 3ER14W... | 3EL14W... | .046 | .04 | .05 | | | |
| | | 12 | 3ER12W... | 3EL12W... | .054 | .04 | .06 | | | |
| 11 | 3ER11W... | 3EL11W... | .058 | .04 | .06 | | | | | |
| 10 | 3ER10W... | 3EL10W... | .064 | .04 | .06 | | | | | |
| 9 | 3ER9W... | 3EL9W... | .071 | .05 | .07 | | | | | |
| 8 | 3ER8W... | 3EL8W... | .080 | .05 | .06 | | | | | |




Whitworth - BSW, BSP, BSF, BSB (con't)


External




Defined by: B.S.84:1956,
DIN 259, ISO228/1:1982
Tolerance class: Medium class A




SCB
Sintered
Chipbreaker




V6



Standard



F-Line



U Style

Standard


| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|---|-------------|------|-------|--------------|---------------|------|-----------------|-----|--------|-------|-------------|------------|
| | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | | |
|  SCB | 3/8" SCB | .63 | 36 | 3JER36W... | | .018 | .05 | .02 | YE3 | - | AL..-3 | |
| | | | 32 | 3JER32W... | | .020 | .05 | .02 | | | | |
| | | | 28 | 3JER28W... | | .023 | .03 | .03 | | | | |
| | | | 24 | 3JER24W... | | .027 | .03 | .03 | | | | |
| | | | 20 | 3JER20W... | | .032 | .03 | .03 | | | | |
| | | | 19 | 3JER19W... | | .034 | .03 | .03 | | | | |
| | | | 18 | 3JER18W... | | .035 | .03 | .03 | | | | |
| | | | 16 | 3JER16W... | | .040 | .03 | .03 | | | | |
| | | | 14 | 3JER14W... | | .046 | .05 | .06 | | | | |
| | | | 12 | 3JER12W... | | .054 | .05 | .06 | | | | |
| | | | 11 | 3JER11W... | | .058 | .05 | .06 | | | | |
| | | | 10 | 3JER10W... | | .064 | .05 | .06 | | | | |
|  V6 | 3/8" V6 | .63 | 19 | 3ER19W-6C... | | .034 | .07 | .09 | YE3-6C | - | AL..-3 | |
| | | | 16 | 3ER16W-6C... | | .040 | .06 | .09 | | | | |
| | | | 14 | 3ER14W-6C... | | .046 | .07 | .11 | | | | |
| | | | 12 | 3ER12W-6C... | | .054 | .07 | .12 | | | | |
|  Standard | 1/2" | .87 | 7 | 4ER7W... | 4EL7W... | .095 | .06 | .09 | YE4 | Y14 | AL..-4 (LH) | |
| | | | 6 | 4ER6W... | 4EL6W... | .107 | .06 | .09 | | | | |
| | | | 5 | 4ER5W... | 4EL5W... | .128 | .07 | .09 | | | | |
| | | | 7 | 4FER7W... | | .095 | .06 | .10 | | | | |
|  F-Line | 1/2" F | .91 | 6 | 4FER6W... | | .107 | .06 | .09 | YE4F | | AL..-4F | |
| | | | 5 | 4FER5W... | | .128 | .07 | .09 | | | | |
| | | | 4.5 | 5ER4.5W... | 5EL4.5W... | .142 | .07 | .10 | | | | |
| | 5/8" | 1.06 | 4 | 5ER4W... | 5EL4W... | .160 | .08 | .11 | YE5 | Y15 | AL..-5 (LH) | |

U Style


| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--|-------------|------|-------|--------------|---------------|------|-----------------|-----|------|-------|--------------|------------|
| | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | | | |
|  U Style | 1/2" U | .87 | 4.5 | 4UEI4.5W... | | .142 | .09 | .43 | YE4U | Y14U | AL..-4U (LH) | |
| | | | 4 | 4UEI4W... | | .160 | .07 | .43 | | | | |
| | | | 3.5 | 4UEI3.5W... | | .183 | .08 | .43 | | | | |
| | | | 3.25 | 4UEI3.25W... | | .197 | .08 | .43 | | | | |
| | 5/8" U | 1.06 | 3.5 | 5UEI3.5W... | | .183 | .08 | .54 | YE5U | Y15U | AL..-5U (LH) | |
| | | | 3.25 | 5UEI3.25W... | | .197 | .08 | .54 | | | | |
| | | | 3 | 5UEI3W... | | .213 | .09 | .54 | | | | |
| | | | 2.75 | 5UEI2.75W... | | .233 | .09 | .54 | | | | |

Whitworth - BSW, BSP, BSF, BSB (con't)


External




Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A



V Style / Slim Throat



M+ Style



F-Line M+

Slim Throat



| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Toolholder |
|-------|-------------|--------|------------|---------------|------|-----------------|-----|-----|---------------|
| | IC | L inch | | RH | LH | h min | X | Y | |
| 1/4"V | .43 | 19 | 2VER19W... | 2VEL19W... | .034 | .03 | .09 | .13 | NL...-2V (LH) |
| | | 14 | 2VER14W... | 2VEL14W... | .046 | .03 | .08 | .13 | |
| | | 11 | 2VER11W... | 2VEL11W... | .058 | .03 | .07 | .13 | |
| 3/8"V | .63 | 19 | 3VER19W... | 3VEL19W... | .034 | .04 | .11 | .14 | NL...-3V (LH) |
| | | 18 | 3VER18W... | 3VEL18W... | .035 | .04 | .10 | .14 | |
| | | 16 | 3VER16W... | 3VEL16W... | .040 | .04 | .10 | .14 | |
| | | 14 | 3VER14W... | 3VEL14W... | .046 | .04 | .09 | .14 | |
| | | 12 | 3VER12W... | 3VEL12W... | .054 | .04 | .09 | .14 | |
| | | 11 | 3VER11W... | 3VEL11W... | .058 | .04 | .08 | .14 | |

V Style



| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Toolholder |
|-------|-------------|--------|-------------|---------------|------|-----------------|-----|-----|------------------|
| | IC | L inch | | RH | LH | h min | X | Y | |
| 5/8"V | 1.06 | 4 | 5VER4W... | 5VEL4W... | .160 | .039 | .13 | .24 | NL...-5V-6 (LH) |
| | | 3 | 5VER3W... | 5VEL3W... | .213 | .039 | .17 | .31 | NL...-5V-8 (LH) |
| | | 2.5 | 5VER2.5W... | 5VEL2.5W... | .256 | .039 | .21 | .39 | NL...-5V-10 (LH) |

M+ Style





FLINE

| | Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | Toolholder |
|-------|-------------|--------|-------|---------------|---------------|------|-----------------|-----|--------|-----------|------------|
| | IC | L inch | | | RH | LH | h min | X | Y | RH | |
| 3/8" | .63 | 28 | 2 | 3ER28W2M+... | | .023 | .05 | .06 | YE3M | AL...-3 | |
| | | 19 | 2 | 3ER19W2M+... | | .034 | .06 | .09 | | | |
| | | 19 | 3 | 3ER19W3M+... | | .034 | .09 | .13 | | | |
| | | 14 | 2 | 3ER14W2M+... | | .046 | .08 | .12 | | | |
| 1/2" | .87 | 14 | 3 | 4ER14W3M+... | | .046 | .11 | .18 | YE4M | AL...-4 | |
| | | 11 | 2 | 4ER11W2M+... | | .058 | .09 | .14 | | | |
| 1/2"F | .91 | 11 | 2 | 4FER11W2M+... | | .058 | .09 | .14 | YE4M2F | AL...-4MF | |


Whitworth - BSW, BSP, BSF, BSB (con't)

External



Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A

RS/LS Varied range of threading standards for machining between shoulders and close to spindle.



VG-Cut




| Pocket Size | Ordering Code | Dimensions inch | | | | | No. of Passes | Helix | Min. Thread Diameter | Toolholder |
|-------------|----------------------|-----------------|-------|-----------|-------|-----|---------------|-----------|----------------------|------------------------|
| | | RH | W ref | Pitch TPI | h min | Y | | | | |
| 3 | VGD3.0W19RH-RS/LS... | | .12 | 19 | .034 | .04 | .86 | 7-12 | 1/2"-19BSW | Monoblock VGE...T12 |
| | VGD3.0W14RH-RS/LS... | | .12 | 14 | .046 | .05 | .86 | 8-14 2.5° | 1/2"-14BSW | |
| | VGD3.0W11RH/LH... | | .12 | 11 | .060 | .07 | .86 | 8-14 | 5/8-11BSW | |


LH Helix threads available upon request.

Whitworth - BSW, BSP, BSF, BSB (con't)

Internal



Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A



Standard


SCB
Sintered
Chipbreaker

Standard


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|--|-------------|-----------|---------------|------------|-----------------|------|-----|-------|-----|------------|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  | 1/4" | .43 | 72 | 2IR72W... | 2IL72W... | .009 | .03 | .02 | - | - | NVR..-2 (LH) |
| | | | 60 | 2IR60W... | 2IL60W... | .011 | .03 | .02 | | | |
| | | | 56 | 2IR56W... | 2IL56W... | .011 | .03 | .02 | | | |
| | | | 48 | 2IR48W... | 2IL48W... | .013 | .02 | .02 | | | |
| | | | 40 | 2IR40W... | 2IL40W... | .016 | .02 | .02 | | | |
| | | | 36 | 2IR36W... | 2IL36W... | .018 | .02 | .02 | | | |
| | | | 32 | 2IR32W... | 2IL32W... | .020 | .02 | .02 | | | |
| | | | 28 | 2IR28W... | 2IL28W... | .023 | .02 | .03 | | | |
| | | | 26 | 2IR26W... | 2IL26W... | .025 | .03 | .03 | | | |
| | | | 24 | 2IR24W... | 2IL24W... | .027 | .03 | .03 | | | |
| | | | 22 | 2IR22W... | 2IL22W... | .029 | .03 | .04 | | | |
| | | | 20 | 2IR20W... | 2IL20W... | .032 | .03 | .04 | | | |
| | | | 19 | 2IR19W... | 2IL19W... | .034 | .03 | .04 | | | |
| | | | 18 | 2IR18W... | 2IL18W... | .035 | .03 | .04 | | | |
| 16 | 2IR16W... | 2IL16W... | .040 | .04 | .04 | | | | | | |
| 14 | 2IR14W... | 2IL14W... | .046 | .04 | .04 | | | | | | |
| 12 | 2IR12W... | 2IL12W... | .052 | .04 | .05 | | | | | | |
|  SCB | 1/4" SCB | .43 | 36 | 2JIR36W... | | .018 | .05 | .02 | - | - | NVR..-2 |
| | | | 32 | 2JIR32W... | | .020 | .05 | .02 | | | |
| | | | 28 | 2JIR28W... | | .023 | .03 | .03 | | | |
| | | | 24 | 2JIR24W... | | .027 | .03 | .03 | | | |
| | | | 20 | 2JIR20W... | | .032 | .03 | .03 | | | |
| | | | 19 | 2JIR19W... | | .034 | .02 | .03 | | | |
| | | | 18 | 2JIR18W... | | .035 | .03 | .03 | | | |
| 16 | 2JIR16W... | | .040 | .03 | .03 | | | | | | |
| 14 | 2JIR14W... | | .046 | .03 | .04 | | | | | | |
|  | 3/8" | .63 | 72 | 3IR72W... | 3IL72W... | .009 | .03 | .02 | YI3 | YE3 | AVR..-3 (LH) |
| | | | 60 | 3IR60W... | 3IL60W... | .011 | .03 | .02 | | | |
| | | | 56 | 3IR56W... | 3IL56W... | .011 | .03 | .02 | | | |
| | | | 48 | 3IR48W... | 3IL48W... | .013 | .02 | .02 | | | |
| | | | 40 | 3IR40W... | 3IL40W... | .016 | .02 | .02 | | | |
| | | | 36 | 3IR36W... | 3IL36W... | .018 | .02 | .02 | | | |
| | | | 32 | 3IR32W... | 3IL32W... | .020 | .02 | .02 | | | |
| | | | 30 | 3IR30W... | 3IL30W... | .022 | .02 | .03 | | | |

Whitworth - BSW, BSP, BSF, BSB (con't)

Internal



Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A




Standard


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|--|-------------|----------|---------------|--------------|-----------------|------|-----|-------|--------|------------|-------------------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  | 3/8" | .63 | 28 | 3IR28W... | 3IL28W... | .023 | .02 | .03 | YI3 | YE3 | AVR...-3 (LH) |
| | | | 26 | 3IR26W... | 3IL26W... | .025 | .03 | .03 | | | |
| | | | 24 | 3IR24W... | 3IL24W... | .027 | .03 | .03 | | | |
| | | | 22 | 3IR22W... | 3IL22W... | .029 | .03 | .04 | | | |
| | | | 20 | 3IR20W... | 3IL20W... | .032 | .03 | .04 | | | |
| | | | 19 | 3IR19W... | 3IL19W... | .034 | .03 | .04 | | | |
| | | | 18 | 3IR18W... | 3IL18W... | .035 | .03 | .04 | | | |
| | | | 16 | 3IR16W... | 3IL16W... | .040 | .04 | .04 | | | |
| | | | 14 | 3IR14W... | 3IL14W... | .046 | .04 | .05 | | | |
| | | | 12 | 3IR12W... | 3IL12W... | .054 | .04 | .06 | | | |
| | | | 11 | 3IR11W... | 3IL11W... | .058 | .04 | .06 | | | |
| | | | 10 | 3IR10W... | 3IL10W... | .064 | .04 | .06 | | | |
| 9 | 3IR9W... | 3IL9W... | .071 | .05 | .07 | | | | | | |
| 8 | 3IR8W... | 3IL8W... | .080 | .05 | .06 | | | | | | |
|  SCB | 3/8" SCB | .63 | 28 | 3JIR28W... | | .023 | .03 | .03 | YI3 | - | AVR...-3 |
| | | | 24 | 3JIR24W... | | .027 | .03 | .03 | | | |
| | | | 20 | 3JIR20W... | | .032 | .03 | .03 | | | |
| | | | 19 | 3JIR19W... | | .034 | .02 | .02 | | | |
| | | | 18 | 3JIR18W... | | .035 | .03 | .03 | | | |
| | | | 16 | 3JIR16W... | | .040 | .03 | .03 | | | |
| | | | 14 | 3JIR14W... | | .046 | .05 | .06 | | | |
| | | | 12 | 3JIR12W... | | .054 | .05 | .06 | | | |
|  V6 | 3/8" V6 | .63 | 19 | 3IR19W-6C... | | .034 | .07 | .09 | YI3-6C | - | AVR...-3 NVRC...-3V6 |
| | | | 16 | 3IR16W-6C... | | .040 | .06 | .10 | | | |
| | | | 14 | 3IR14W-6C... | | .046 | .07 | .11 | | | |
| | | | 12 | 3IR12W-6C... | | .054 | .07 | .10 | | | |
|  | 1/2" | .87 | 7 | 4IR7W... | 4IL7W... | .095 | .06 | .09 | YI4 | YE4 | AVR...-4 (LH) |
| | | | 6 | 4IR6W... | 4IL6W... | .107 | .06 | .09 | | | |
| | | | 5 | 4IR5W... | 4IL5W... | .128 | .07 | .09 | | | |
|  | 1/2" F | .91 | 7 | 4FIR7W... | | .095 | .06 | .09 | YI4F | | AVRC...-4F |
| | | | 6 | 4FIR6W... | | .107 | .06 | .09 | | | |
| | | | 5 | 4FIR5W... | | .128 | .07 | .09 | | | |
|  | 5/8" | 1.06 | 4.5 | 5IR4.5W... | 5IL4.5W... | .142 | .07 | .10 | YI5 | YE5 | AVR...-5 (LH) |
| | | | 4 | 5IR4W... | 5IL4W... | .160 | .08 | .11 | | | |

FLINE


Whitworth - BSW, BSP, BSF, BSB (con't)

Internal







U Style



V Style



M+ Style



F-Line M+

Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|-------|-----------------|-----|------|-------|----------------|------------|
| IC | L inch | TPI | RH+LH | h min | X | Y | RH | LH | | |
| 1/2"U | .87 | 4.5 | 4UEI4.5W... | .142 | .09 | .43 | YI4U | YE4U | AVR...-4U (LH) | |
| | | 4 | 4UEI4W... | .160 | .07 | .43 | | | | |
| | | 3.5 | 4UEI3.5W... | .183 | .08 | .43 | | | | |
| | | 3.25 | 4UEI3.25W... | .197 | .08 | .43 | | | | |
| 5/8"U | 1.06 | 3.5 | 5UEI3.5W... | .183 | .08 | .54 | YI5U | YE5U | AVR...-5U (LH) | |
| | | 3.25 | 5UEI3.25W... | .197 | .08 | .54 | | | | |
| | | 3 | 5UEI3W... | .213 | .09 | .54 | | | | |
| | | 2.75 | 5UEI2.75W... | .233 | .09 | .54 | | | | |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | | Toolholder |
|-------------|--------|-------|---------------|-------------|-----------------|-----|-----|-----|----------------|------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | | |
| 5/8"V | 1.06 | 4 | 5VIR4W... | 5VIL4W... | .160 | .04 | .13 | .24 | NVR...-5V (LH) | |
| | | 3 | 5VIR3W... | 5VIL3W... | .213 | .04 | .17 | .31 | | |
| | | 2.5 | 5VIR2.5W... | 5VIL2.5W... | .256 | .04 | .20 | .39 | | |

M+ Style



FLINE


| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|---------------|-------|-----------------|-----|--------|--------------|--|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder | |
| 3/8" | .63 | 14 | 2 | 3IR14W2M+... | .046 | .08 | .12 | YI3M | AVR...-3 | |
| 1/2" | .87 | 11 | 2 | 4IR11W2M+... | .058 | .09 | .14 | YI4M | AVR...-4 | |
| 1/2"F | .91 | 11 | 2 | 4FIR11W2M+... | .058 | .09 | .14 | YI4M2F | AVRC... -4MF | |

Multiplus


Whitworth - BSW, BSP, BSF, BSB (con't)

Mini-V

Internal



Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium Class A



Mini-V



| Min. Thread | Insert Style | Pitch | Ordering Code | Dimensions inch | | | | | | Helix | Toolholder |
|-------------|--------------|-------|---------------|-----------------|-----|-----|-----|------|---|----------|------------|
| | | | | TPI | RH | d | T | F | Y | | |
| 1/2"x19W | V11 | 19 | V11TH19WR... | .31 | .17 | .24 | .03 | .034 | 2 | .V11-... | |

Internal

Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A

Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|----------------|-------------------|
| IC mm | L inch | TPI | RH | LH | h min | Y | F | inch | |
| 4.0 | .24 | 26 | 4.0KIR26W... | 4.0KIL26W... | .025 | .02 | .14 | .25 | .NVR...-4.0K (LH) |
| | | 22 | 4.0KIR22W... | 4.0KIL22W... | .029 | .02 | .15 | .25 | |
| | | 20 | 4.0KIR20W... | 4.0KIL20W... | .032 | .03 | .15 | .25 | |
| | | 19 | 4.0KIR19W... | 4.0KIL19W... | .034 | .03 | .15 | .25 | |
| | | 18 | 4.0KIR18W... | 4.0KIL18W... | .035 | .03 | .15 | .25 | |
| 5.0 | .31 | 28 | 5.0KIR28W... | 5.0KIL28W... | .023 | .02 | | | .NVR...-5.0K (LH) |
| | | 24 | 5.0KIR24W... | 5.0KIL24W... | .027 | .02 | | | |
| | | 20 | 5.0KIR20W... | 5.0KIL20W... | .032 | .03 | .19 | .31 | |
| | | 19 | 5.0KIR19W... | 5.0KIL19W... | .034 | .03 | | | |
| | | 18 | 5.0KIR18W... | 5.0KIL18W... | .035 | .03 | | | |
| 6.0 | .39 | 28 | 6.0KIR28W... | 6.0KIL28W... | .023 | .03 | .19 | .38 | .NVR...-6.0K (LH) |
| | | 19 | 6.0KIR19W... | 6.0KIL19W... | .034 | .04 | .20 | .39 | |
| | | 14 | 6.0KIR14W... | 6.0KIL14W... | .046 | .04 | .21 | .39 | |

Mini-3 U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|---------------|-------|-----------------|-----|------|--------------------|------------|
| IC mm | L inch | TPI | RH+LH | h min | Y | F | inch | | |
| 5.0U | .31 | 14 | 5.0KUI14W... | .046 | | .22 | | .NVR...-5.0KU (LH) | |
| | | 12 | 5.0KUI12W... | .054 | .16 | .22 | .35 | | |
| | | 11 | 5.0KUI11W... | .058 | | .22 | | | |

Mini-L



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-----|-------------|---------------|-------|-----------------|-----|------|------------------|------------|
| IC mm | TPI | RH | LH | h min | Y | F | inch | | |
| 5.0 L | 28 | 5LKIR28W... | 5LKIL28W... | .023 | .03 | .16 | .30 | .NVR...-5LK (LH) | |
| | 19 | 5LKIR19W... | 5LKIL19W... | .034 | .04 | .17 | .31 | | |
| | 14 | 5LKIR14W... | 5LKIL14W... | .046 | .04 | .18 | .31 | | |

Whitworth - BSW, BSP, BSF, BSB (con't)

MINIPRO

Internal

Defined by: B.S.84:1956,
DIN 259, ISO228/1:1982
Tolerance class: Medium class A

RH-Single Ended

RH-Double Ended

Micro - Double Ended

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------|-------|---------------|-----|-----------------|-----|-----|-------|------|----------------|------------|
| | d mm | TPI | RH | L1 | L | F | Y | h min | inch | | |
| 1/16"-28BSP | 4.0 | 28 | 4.0SIR28W... | .63 | 1.97 | .07 | .03 | .023 | .17 | SMC...-4.0 | |
| 1/4"-26BSF | | 26 | 4.0SIR26W... | .63 | 1.97 | .08 | .03 | .025 | .17 | | |
| 1/4"-24BSW | | 24 | 4.0SIR24W... | .63 | 1.97 | .08 | .03 | .027 | .17 | | |
| 1/16"-28BSP | 6.0 | 28 | 6.0SIR28W... | .63 | 1.97 | .10 | .03 | .023 | .24 | SMC...-6.0 | |
| 5/16"-28BSW | | 26 | 6.0SIR26W... | .63 | 1.97 | .10 | .03 | .025 | .24 | | |
| 5/16"-24BSW | | 24 | 6.0SIR24W... | .63 | 1.97 | .10 | .03 | .027 | .24 | | |
| 5/16"-22BSW | | 22 | 6.0SIR22W... | .63 | 1.97 | .10 | .04 | .029 | .24 | | |
| 3/8"-20BSF | | 20 | 6.0SIR20W... | .63 | 1.97 | .10 | .04 | .032 | .24 | | |
| 1/4"-19BSP | | 19 | 6.0SIR19W... | .63 | 1.97 | .10 | .04 | .034 | .24 | | |

Left handed tool supplied by request (Example: 6.0SIL19W...).

Micro - Single Ended

microscope

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------|-------|--------------------|--------|-----------------|-----|-----|-------|---------|-------|--------|----------------|------------|
| | d mm | TPI | RH/LH | Helix° | L1 | F | Y | h min | L2 ref* | L ref | D Inch | | |
| 1/16"-28BSP | 6.0 | 28 | M659TH28WL16R/L... | 3.5 | .63 | .11 | .03 | .02 | .73 | 1.66 | .26 | MH...-6.0 | |
| 1/4"-19BSP | | 19 | M659TH19WL16R/L... | | | | .04 | .03 | | | .45 | | |

* L2 Ref: Repeatability within +/-0.008

BSPT

External

Defined by: B.S. 21:1985
Tolerance class: Standard BSPT

Standard

SCB
Sintered
Chipbreaker

V6

Slim Throat

Standard


| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--|-------------|--------|-------|-----------------|--------------|-----------------|-----|-----|--------|-----|--------------|
| | IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| | 1/4" | .43 | 28 | 2ER28BSPT... | 2EL28BSPT... | .023 | .02 | .02 | - | - | NL...-2 (LH) |
| | | | 19 | 2ER19BSPT... | 2EL19BSPT... | .034 | .03 | .04 | - | - | |
| | | | 14 | 2ER14BSPT... | 2EL14BSPT... | .046 | .04 | .04 | - | - | |
| | 3/8" | .63 | 28 | 3ER28BSPT... | 3EL28BSPT... | .023 | .02 | .02 | YE3 | YI3 | AL...-3 (LH) |
| | | | 19 | 3ER19BSPT... | 3EL19BSPT... | .034 | .03 | .04 | | | |
| | | | 14 | 3ER14BSPT... | 3EL14BSPT... | .046 | .04 | .05 | | | |
| | | | 11 | 3ER11BSPT... | 3EL11BSPT... | .058 | .04 | .06 | | | |
| | 3/8" SCB | .63 | 28 | 3JER28BSPT... | | .023 | .03 | .03 | YE3 | - | AL...-3 |
| | | | 19 | 3JER19BSPT... | | .034 | .03 | .03 | | | |
| | | | 14 | 3JER14BSPT... | | .046 | .05 | .06 | | | |
| | 3/8" V6 | .63 | 19 | 3ER19BSPT-6C... | | .034 | .07 | .09 | YE3-6C | - | AL...-3 |
| | | | 14 | 3ER14BSPT-6C... | | .046 | .07 | .11 | | | |

Slim Throat


| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|--|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-----|---------------|
| | IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| | 3/8"V | .63 | 28 | 3VER28BSPT... | 3VEL28BSPT... | .023 | .04 | .12 | .14 | NL...-3V (LH) |
| | | | 19 | 3VER19BSPT... | 3VEL19BSPT... | .034 | .04 | .11 | .14 | |
| | | | 14 | 3VER14BSPT... | 3VEL14BSPT... | .046 | .04 | .09 | .14 | |
| | | | 11 | 3VER11BSPT... | 3VEL11BSPT... | .058 | .04 | .08 | .14 | |

BSPT (con't)


Internal




Defined by: B.S. 21:1985
Tolerance class: Standard BSPT



Standard



SCB
Sintered
Chipbreaker



V6

Standard




| IC | L inch | TPI | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-----|-----------------|--------------|-----------------|-----|-----|--------|-----|-----------------------|
| | | | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 28 | 2IR28BSPT... | 2IL28BSPT... | .023 | .02 | .02 | - | - | NVR..-2 (LH) |
| | | 19 | 2IR19BSPT... | 2IL19BSPT... | .034 | .03 | .04 | - | - | |
| | | 14 | 2IR14BSPT... | 2IL14BSPT... | .046 | .04 | .04 | - | - | |
| 1/4" SCB | .43 | 28 | 2JIR28BSPT... | | .023 | .03 | .03 | - | - | NVR..-2 |
| | | 19 | 2JIR19BSPT... | | .034 | .03 | .03 | - | - | |
| 3/8" | .63 | 28 | 3IR28BSPT... | 3IL28BSPT... | .023 | .02 | .02 | YI3 | YE3 | AVR..-3 (LH) |
| | | 19 | 3IR19BSPT... | 3IL19BSPT... | .034 | .03 | .04 | | | |
| | | 14 | 3IR14BSPT... | 3IL14BSPT... | .046 | .04 | .05 | | | |
| | | 11 | 3IR11BSPT... | 3IL11BSPT... | .058 | .04 | .06 | | | |
| 3/8" SCB | .63 | 28 | 3JIR28BSPT... | | .023 | .03 | .03 | YI3 | - | AVR..-3 |
| | | 19 | 3JIR19BSPT... | | .034 | .03 | .03 | | | |
| | | 14 | 3JIR14BSPT... | | .046 | .05 | .06 | | | |
| 3/8" V6 | .63 | 19 | 3IR19BSPT-6C... | | .034 | .07 | .09 | YI3-6C | - | AVR..-3 NVR...-3V6 |
| | | 14 | 3IR14BSPT-6C... | | .046 | .07 | .11 | | | |


BSPT

Mini-V

Internal



Defined by: B.S.21:1985
Tolerance class: Standard BSPT



Mini-V



| Min. Thread | Insert Style | Pitch | Ordering Code | | Dimensions inch | | | | | Helix | Toolholder |
|-------------|--------------|-------|-----------------|----|-----------------|-----|-----|-----|-------|-------|------------|
| | | | TPI | RH | d | T | F | Y | h min | | |
| 1/4"-19BSPT | V11 | 19 | V11TH19BSPTR... | | .31 | .17 | .24 | .04 | .034 | 2.5 | .V11... |

BSPT (con't)



Internal

Defined by: B.S. 21:1985
Tolerance class: Standard BSPT

Mini-3 Standard



| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|--------|-----------------|-----------------|-----------------|-------|-----|----------------|-------------------|
| | IC mm | L inch | TPI | RH | LH | h min | Y | F | |
| 4.0 | .24 | 28 | 4.0KIR28BSPT... | 4.0KIL28BSPT... | .023 | .02 | .14 | .25 | .NVR...-4.0K (LH) |
| | | 28 | 5.0KIR28BSPT... | 5.0KIL28BSPT... | .023 | .02 | .19 | .31 | .NVR...-5.0K (LH) |
| 5.0 | .31 | 19 | 5.0KIR19BSPT... | 5.0KIL19BSPT... | .034 | .03 | .19 | .31 | .NVR...-5.0K (LH) |
| | | 28 | 6.0KIR28BSPT... | 6.0KIL28BSPT... | .023 | .02 | .19 | .38 | |
| | | 19 | 6.0KIR19BSPT... | 6.0KIL19BSPT... | .034 | .04 | .20 | .39 | .NVR...-6.0K (LH) |
| 6.0 | .39 | 14 | 6.0KIR14BSPT... | 6.0KIL14BSPT... | .046 | .05 | .21 | .39 | |


Mini-L




| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|-----|----------------|----------------|-----------------|-----|-----|----------------|------------------|
| | IC mm | TPI | RH | LH | h min | Y | F | inch | |
| 5.0L | | 28 | 5LKIR28BSPT... | 5LKIL28BSPT... | .023 | .02 | .16 | .30 | |
| | | 19 | 5LKIR19BSPT... | 5LKIL19BSPT... | .034 | .04 | .17 | .31 | .NVR...-5LK (LH) |
| | | 14 | 5LKIR14BSPT... | 5LKIL14BSPT... | .046 | .05 | .18 | .31 | |

NPT


External




Defined by: USAS B2.1:1968
Tolerance class: Standard NPT




Standard



SCB
Sintered
Chipbreaker



V6



Slim Throat

Standard



SCB



V6

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|---------------|-----------------|-----|-----|--------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 27 | 2ER27NPT... | 2EL27NPT... | .026 | .03 | .03 | - | - | NL...-2 (LH) |
| | | 18 | 2ER18NPT... | 2EL18NPT... | .040 | .03 | .04 | | | |
| | | 14 | 2ER14NPT... | 2EL14NPT... | .052 | .03 | .04 | | | |
| 3/8" | .63 | 27 | 3ER27NPT... | 3EL27NPT... | .026 | .03 | .03 | YE3 | Y13 | AL...-3 (LH) |
| | | 18 | 3ER18NPT... | 3EL18NPT... | .040 | .03 | .04 | | | |
| | | 14 | 3ER14NPT... | 3EL14NPT... | .052 | .04 | .05 | | | |
| | | 11.5 | 3ER11.5NPT... | 3EL11.5NPT... | .065 | .04 | .06 | | | |
| 3/8" SCB | .63 | 27 | 3JER27NPT... | | .026 | .02 | .03 | YE3 | - | AL...-3 |
| | | 18 | 3JER18NPT... | | .040 | .02 | .03 | | | |
| | | 14 | 3JER14NPT... | | .052 | .04 | .06 | | | |
| | | 11.5 | 3JER11.5NPT... | | .065 | .04 | .06 | | | |
| 3/8" V6 | .63 | 14 | 3ER14NPT-6C... | | .052 | .07 | .12 | YE3-6C | - | AL...-3 |

Slim Throat



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|----------------|-----------------|-----------------|-----|-----|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 1/4"V | .43 | 27 | 2VER27NPT... | 2VEL27NPT... | .026 | .03 | .08 | .13 | NL...-2V (LH) |
| | | 18 | 2VER18NPT... | 2VEL18NPT... | .040 | .03 | .07 | .13 | |
| | | 14 | 2VER14NPT... | 2VEL14NPT... | .052 | .03 | .07 | .13 | |
| | | 11.5 | 2VER11.5NPT... | 2VEL11.5NPT... | .065 | .03 | .08 | .13 | |
| 3/8"V | .63 | 27 | 3VER27NPT... | 3VEL27NPT... | .026 | .04 | .11 | .14 | NL...-3V (LH) |
| | | 18 | 3VER18NPT... | 3VEL18NPT... | .040 | .04 | .10 | .14 | |
| | | 11.5 | 3VER11.5NPT... | 3VEL11.5 NPT... | .065 | .04 | .08 | .14 | |

NPT (con't)

External

Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

RS/LS

Varied range of threading standards for machining between shoulders and close to spindle.

VG-Cut



| Pocket Size | Ordering Code | Dimensions inch | | | No. of Passes | Helix | Min. Thread Diameter | Toolholder |
|-------------|--------------------------|-----------------|-----------|-------|---------------|-------------|----------------------|----------------------|
| | RH | W ref | Pitch TPI | h min | Y | L ref | Deg | Monoblock |
| 3 | VGD3.0NPT18RH-RS/LS... | | 18 | .040 | .05 | 7 - 12 | | 1/4"-18NPT |
| 3 | VGD3.0NPT14RH-RS/LS... | .12 | 14 | .052 | .06 | 0.86 8 - 14 | 1.5° | 1/2"-14NPT VGE...T12 |
| 3 | VGD3.0NPT11.5RH-RS/LS... | | 12 | .065 | .06 | 9 - 15 | | 1"-11.5NPT |

LH Helix threads available upon request.

NPT (con't)

External

Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

M+ Style

F-Line M+

Z+ Style

M+ Style



FLINE

| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------------------|-----------------|-----|-----|--------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 14 | 2 | 3ER14NPT2M+... | .052 | .08 | .12 | YE3M | AL..-3 |
| 1/2" | .87 | 11.5 | 2 | 4ER11.5NPT2M+... | .065 | .09 | .13 | YE4M | AL..-4 |
| 1/2" | .91 | 11.5 | 2 | 4FER11.5NPT2M+... | .065 | .09 | .13 | YE4M2F | AL..-4MF |
| 5/8" | 1.06 | 11.5 | 3 | 5ER11.5NPT3M+... | .065 | .14 | .22 | YE5M | AL..-5M |
| | | 8 | 2 | 5ER8NPT2M+... | .095 | .12 | .19 | | |


Z+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 11.5 | 2 | 4ER11.5NPT2Z+... | .065 | .11 | .39 | YE4Z | AL..-4Z |
| | | 8 | 2 | 4ER8NPT2Z+... | .095 | .13 | .38 | | |

NPT (con't)

Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Standard

SCB
Sintered
Chipbreaker

V6

Standard



SCB




V6


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|---------------|-----------------|-----|-----|--------|-----|------------------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 27 | 2IR27NPT... | 2IL27NPT... | .026 | .03 | .03 | - | - | NVR..-2 (LH) |
| | | 18 | 2IR18NPT... | 2IL18NPT... | .040 | .03 | .04 | | | |
| | | 14 | 2IR14NPT... | 2IL14NPT... | .052 | .03 | .04 | | | |
| 1/4" SCB | .43 | 27 | 2JIR27NPT... | | .026 | .02 | .03 | - | - | NVR..-2 |
| | | 18 | 2JIR18NPT... | | .040 | .02 | .03 | | | |
| 3/8" | .63 | 27 | 3IR27NPT... | 3IL27NPT... | .026 | .03 | .03 | Y13 | YE3 | AVR..-3 (LH) |
| | | 18 | 3IR18NPT... | 3IL18NPT... | .040 | .03 | .04 | | | |
| | | 14 | 3IR14NPT... | 3IL14NPT... | .052 | .04 | .05 | | | |
| | | 11.5 | 3IR11.5NPT... | 3IL11.5NPT... | .065 | .04 | .06 | | | |
| 3/8" SCB | .63 | 27 | 3JIR27NPT... | | .026 | .02 | .03 | Y13 | - | AVR..-3 |
| | | 18 | 3JIR18NPT... | | .040 | .02 | .03 | | | |
| | | 14 | 3JIR14NPT... | | .052 | .04 | .06 | | | |
| | | 11.5 | 3JIR11.5NPT... | | .065 | .04 | .06 | | | |
| 3/8" V6 | .63 | 14 | 3IR14NPT-6C... | | .052 | .07 | .11 | Y13-6C | - | AVR..-3 NVRC...-3V6 |

NPT (con't)


Internal




Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



M+ Style



F-Line M+



Z+ Style

M+ Style



F LINE

| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------------------|-----------------|-----|-----|--------|-------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 14 | 2 | 3IR14NPT2M+... | .052 | .08 | .12 | YI3M | AVR...-3 |
| 1/2" | .87 | 11.5 | 2 | 4IR11.5NPT2M+... | .065 | .09 | .13 | YI4M | AVR...-4 |
| 1/2"F | .91 | 11.5 | 2 | 4FIR11.5NPT2M+... | .065 | .09 | .13 | YI4M2F | AVRC...-4MF |
| 5/8" | 1.06 | 11.5 | 3 | 5IR11.5NPT3M+... | .065 | .14 | .22 | YI5M | AVR...-5M |
| | | 8 | 2 | 5IR8NPT2M+... | .095 | .12 | .19 | | |

Z+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 11.5 | 2 | 4IR11.5NPT2Z+... | .065 | .11 | .39 | YI4Z | AVR...-4Z |
| | | 8 | 2 | 4IR8NPT2Z+... | .095 | .13 | .38 | | |


NPT (con't)

Mini-V

Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Mini-V




| Min. Thread | Insert Style | Pitch | Ordering Code | | Dimensions inch | | | | | Helix | Toolholder |
|-------------|--------------|-------|----------------|----|-----------------|-----|-----|-----|-------|-------|------------|
| | | | TPI | RH | d | T | F | Y | h min | | |
| 1/8"-27NPT | V08 | 27 | V08TH27NPTR... | | .24 | .15 | .17 | .02 | .025 | 2 | .V08-... |
| 1/4"-18NPT | | 18 | V08TH18NPTR... | | | | .19 | .04 | .039 | 2 | |





NPT

MINIPRO

Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Mini-3 Standard



| Insert Size | Pitch | Ordering Code | | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|---------------|----------------|----------------|-----------------|------|-------|----------------|-------------------|
| | | IC mm | L inch | TPI | RH | LH | h min | | |
| 4.0 | .24 | 27 | 4.0KIR27NPT... | 4.0KIL27NPT... | .026 | .02 | .15 | .25 | .NVR...-4.0K (LH) |
| | | | 5.0KIR27NPT... | 5.0KIL27NPT... | .026 | .02 | .19 | | |
| 5.0 | .31 | 18 | 5.0KIR18NPT... | 5.0KIL18NPT... | .040 | .03 | .21 | .31 | .NVR...-5.0K (LH) |
| | | | 6.0KIR27NPT... | 6.0KIL27NPT... | .026 | .03 | .21 | | |
| 6.0 | .39 | 18 | 6.0KIR18NPT... | 6.0KIL18NPT... | .040 | .04 | .21 | .39 | .NVR...-6.0K (LH) |
| | | | 14 | 6.0KIR14NPT... | 6.0KIL14NPT... | .052 | .04 | | |


Mini-L



| Insert Size | Pitch | Ordering Code | | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|---------------|---------------|---------------|-----------------|-------|------|------------------|------------|
| | | IC mm | TPI | RH | LH | h min | Y | | |
| 5.0L | 27 | 5LKIR27NPT... | 5LKIL27NPT... | .026 | .03 | .18 | .315 | .NVR...-5LK (LH) | |
| | | 18 | 5LKIR18NPT... | 5LKIL18NPT... | .040 | .04 | | | .18 |
| | | 14 | 5LKIR14NPT... | 5LKIL14NPT... | .052 | .04 | | | .18 |

NPT (con't)

MINIPRO



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

RH-Single Ended

RH-Double Ended

Micro - Double Ended

| Thread | Insert Dia. d mm | Pitch TPI | Ordering Code RH | Dimensions inch | | | | | Min. Bore Dia. mm | Toolholder |
|-------------|---------------------|--------------|---------------------|-----------------|------|-----|-----|-------|----------------------|------------|
| 1/16"-27NPT | 6.0 | 27 | 6.0SIR27NPT... | L1 | L | F | Y | h min | .23 | SMC...-6.0 |
| 1/4"-18NPT | | 18 | 6.0SIR18NPT... | .63 | 1.97 | .10 | .04 | .026 | | |

Left handed tool supplied by request (Example: 6.0SIL18NPT...).

Micro - Single Ended


microscope

| Thread | Insert Dia. d mm | Pitch TPI | Ordering Code RH/LH | Helix° | L1 | Dimensions inch | | | L2 ref* | L ref | Min. Bore Dia. D mm | Toolholder | | | |
|-------------|---------------------|--------------|------------------------|--------|-----|-----------------|---|-------|---------|-------|------------------------|------------|-----|-----|------|
| 1/16"-27NPT | 6.0 | 27 | M659TH27NPTL16R/L... | 3.5 | .63 | F | Y | h min | .73 | 1.66 | .24 | MH...-6.0 | | | |
| 1/4"-18NPT | | 18 | M659TH18NPTL16R/L... | | | | | | | | | | .11 | .04 | .040 |
| 1/2"-14NPT | | 14 | M659TH14NPTL16R/L... | | | | | | | | | | .11 | .04 | .052 |


* L2 Ref: Repeatability within +/- .0008

ANPT


External / Internal



Defined by: MIL-P-7105B
Tolerance class: Standard ANPT



External Standard



Internal Standard

Standard - External



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 18 | 3ER18ANPT... | 3EL18ANPT... | .043 | .03 | .04 | YE3 | YI3 | AL...-3 (LH) |
| | | 14 | 3ER14ANPT... | 3EL14ANPT... | .055 | .03 | .04 | | | |

Standard - Internal



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 18 | 2IR18ANPT... | 2IL18ANPT... | .043 | .03 | .04 | - | - | NVR...-2 (LH) |
| 3/8" | .63 | 14 | 3IR14ANPT... | 3IL14ANPT... | .055 | .03 | .04 | YI3 | YE3 | AVR...-3 (LH) |

NPTF

External

Defined by: ANSI B1.20.3-1976
Tolerance class: Standard NPTF

Standard

SCB
Sintered
Chipbreaker

M+ Style

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-----------------|----------------|-----------------|-----|-----|-------|-----|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 27 | 2ER27NPTF... | 2EL27NPTF... | .025 | .03 | .03 | - | - | NL..-2 (LH) |
| | | 18 | 2ER18NPTF... | 2EL18NPTF... | .039 | .03 | .04 | | | |
| | | 14 | 2ER14NPTF... | 2EL14NPTF... | .053 | .03 | .04 | | | |
| 3/8" | .63 | 27 | 3ER27NPTF... | 3EL27NPTF... | .025 | .03 | .03 | YE3 | YI3 | AL..-3 (LH) |
| | | 18 | 3ER18NPTF... | 3EL18NPTF... | .039 | .03 | .04 | | | |
| | | 14 | 3ER14NPTF... | 3EL14NPTF... | .053 | .04 | .05 | | | |
| | | 11.5 | 3ER11.5NPTF... | 3EL11.5NPTF... | .064 | .04 | .06 | | | |
| 3/8" SCB | .63 | 27 | 3JER27NPTF... | | .025 | .03 | .03 | YE3 | - | AL..-3 |
| | | 18 | 3JER18NPTF... | | .039 | .02 | .03 | | | |
| | | 14 | 3JER14NPTF... | | .053 | .04 | .06 | | | |
| | | 11.5 | 3JER11.5NPTF... | | .064 | .04 | .06 | | | |
| | | 8 | 3JER8NPTF... | | .094 | .04 | .06 | | | |

M+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-------|-----------------|-----------------|------|-----|-------|------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | | |
| 3/8" | .63 | 14 | 2 | 3ER14NPTF2M+... | | .053 | .08 | .12 | YE3M | AL...-3 |




NPTF (con't)


Internal




Defined by: ANSI B1.20.3-1976
Tolerance class: Standard NPTF



Standard



SCB
Sintered
Chipbreaker



M+ Style

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-----------------|----------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 27 | 2IR27NPTF... | 2IL27NPTF... | .025 | .03 | .03 | - | - | NVR..-2 (LH) |
| | | 18 | 2IR18NPTF... | 2IL18NPTF... | .039 | .03 | .04 | | | |
| | | 14 | 2IR14NPTF... | 2IL14NPTF... | .053 | .03 | .04 | | | |
| 1/4" SCB | .43 | 27 | 2JIR27NPTF... | | .025 | .03 | .03 | - | - | NVR..-2 |
| | | 18 | 2JIR18NPTF... | | .039 | .02 | .03 | | | |
| 3/8" | .63 | 27 | 3IR27NPTF... | 3IL27NPTF... | .025 | .03 | .03 | YI3 | YE3 | AVR..-3 (LH) |
| | | 18 | 3IR18NPTF... | 3IL18NPTF... | .039 | .03 | .04 | | | |
| | | 14 | 3IR14NPTF... | 3IL14NPTF... | .053 | .04 | .05 | | | |
| | | 11.5 | 3IR11.5NPTF... | 3IL11.5NPTF... | .064 | .04 | .06 | | | |
| 3/8" SCB | .63 | 27 | 3JIR27NPTF... | | .025 | .03 | .03 | YI3 | - | AVR..-3 |
| | | 18 | 3JIR18NPTF... | | .039 | .02 | .03 | | | |
| | | 14 | 3JIR14NPTF... | | .053 | .04 | .06 | | | |
| | | 11.5 | 3JIR11.5NPTF... | | .064 | .04 | .06 | | | |
| | | 8 | 3JIR8NPTF... | | .094 | .04 | .06 | | | |



SCB

M+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-------|-----------------|-----------------|-----|-----|-------|---------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | | |
| 3/8" | .63 | 14 | 2 | 3IR14NPTF2M+... | .053 | .08 | .12 | YI3M | AVR..-3 | |


NPTF (con't)

Mini-V

Internal



Defined by: ANSI 1.20.3-1976
Tolerance class: Standard NPTF








Mini-V



| Min. Thread | Insert Style | Pitch | Ordering Code | Dimensions inch | | | | | Helix | Toolholder |
|-------------|--------------|-------|-----------------|-----------------|-----|-----|-----|-------|-------|------------|
| | | | | d | T | F | Y | h min | | |
| 1/4"-18NPTF | V08 | 18 | V08TH18NPTFR... | .24 | .15 | .18 | .04 | .04 | 2.0 | .V08-... |

NPTF (con't)

Internal



Defined by: ANSI B1.20.3-1976
Tolerance class: Standard NPTF

Mini-3 Standard



| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|--------|-----------------|-----------------|-----------------|-------|-----|----------------|--------------------|
| | IC mm | L inch | TPI | RH | LH | h min | Y | F | |
| 4.0 | .24 | 27 | 4.0KIR27NPTF... | 4.0KIL27NPTF... | .025 | .02 | .14 | .25 | .NVR...-4.0K (LH) |
| | | 18 | 5.0KIR18NPTF... | 5.0KIL18NPTF... | .039 | .03 | .19 | .31 | .NVRC...-5.0K (LH) |
| 6.0 | .39 | 27 | 6.0KIR27NPTF... | 6.0KIL27NPTF... | .025 | .03 | .21 | .39 | .NVR...-6.0K (LH) |
| | | 18 | 6.0KIR18NPTF... | 6.0KIL18NPTF... | .039 | .04 | .21 | | |
| | | 14 | 6.0KIR14NPTF... | 6.0KIL14NPTF... | .053 | .04 | .21 | | |


Mini-L




| Insert Size | Pitch | | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-------|-----|----------------|----------------|-----------------|-----|-----|----------------|------------------|
| | IC mm | TPI | RH | LH | h min | Y | F | inch | |
| 5.0L | | 27 | 5LKIR27NPTF... | 5LKIL27NPTF... | .025 | .03 | .18 | .31 | .NVR...-5LK (LH) |
| | | 18 | 5LKIR18NPTF... | 5LKIL18NPTF... | .039 | .04 | .18 | | |
| | | 14 | 5LKIR14NPTF... | 5LKIL14NPTF... | .053 | .04 | .18 | | |

NPTF

Internal



Defined by: ANSI B1.20.3-1976
Tolerance class: Standard NPTF



RH-Double Ended


Micro - Double Ended

| Thread | Insert Dia. | Pitch | Ordering Code | | Dimensions inch | | | | | Min. Bore Dia. | Toolholder |
|--------------|-------------|-------|-----------------|----|-----------------|------|-----|-----|-------|----------------|------------|
| | d mm | TPI | RH | LH | L1 | L | F | Y | h min | inch | |
| 1/16"-27NPTF | 6.0 | 27 | 6.0SIR27NPTF... | | .63 | 1.97 | .10 | .03 | .025 | .24 | SMC...-6.0 |
| 1/4"-18NPTF | | 18 | 6.0SIR18NPTF... | | .63 | 1.97 | .10 | .04 | .039 | | |


Left handed tool supplied by request (Example: 6.0SIL18NPTF...).

NPS


External / Internal



Defined by: USA NBS H28 (1957)
Tolerance class: Standard NPS



External Standard



Internal Standard

Standard - External



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 24 | 3ER24NPS... | 3EL24NPS... | .031 | .03 | .03 | YE3 | YI3 | AL...-3 (LH) |
| | | 16 | 3ER16NPS... | 3EL16NPS... | .048 | .03 | .04 | | | |
| | | 14 | 3ER14NPS... | 3EL14NPS... | .052 | .04 | .05 | | | |
| | | 12 | 3ER12NPS... | 3EL12NPS... | .064 | .04 | .06 | | | |
| | | 11.5 | 3ER11.5NPS... | 3EL11.5NPS... | .067 | .04 | .06 | | | |
| 1/2" | .87 | 9 | 3ER9NPS... | 3EL9NPS... | .087 | .05 | .06 | YE4 | YI4 | AL...-4 (LH) |
| | | 8 | 4ER8NPS... | 4EL8NPS... | .097 | .05 | .07 | | | |
| | | 7 | 4ER7NPS... | 4EL7NPS... | .111 | .06 | .09 | | | |
| 5/8" | 1.06 | 6 | 4ER6NPS... | 4EL6NPS... | .130 | .06 | .09 | YE5 | YI5 | AL...-5 (LH) |
| | | 5 | 5ER5NPS... | 5EL5NPS... | .157 | .07 | .11 | | | |


Standard - Internal




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 24 | 3IR24NPS... | 3IL24NPS... | .031 | .03 | .03 | YI3 | YE3 | AVR...-3 (LH) |
| | | 14 | 3IR14NPS... | 3IL14NPS... | .052 | .04 | .05 | | | |
| | | 12 | 3IR12NPS... | 3IL12NPS... | .064 | .04 | .06 | | | |
| | | 11.5 | 3IR11.5NPS... | 3IL11.5NPS... | .067 | .04 | .06 | | | |
| 1/2" | .87 | 9 | 3IR9NPS... | 3IL9NPS... | .087 | .05 | .06 | YI4 | YE4 | AVR...-4 (LH) |
| | | 8 | 4IR8NPS... | 4IL8NPS... | .097 | .05 | .07 | | | |
| | | 7 | 4IR7NPS... | 4IL7NPS... | .111 | .06 | .09 | | | |
| 5/8" | 1.06 | 6 | 4IR6NPS... | 4IL6NPS... | .130 | .06 | .09 | YI5 | YE5 | AVR...-5 (LH) |
| | | 5 | 5IR5NPS... | 5IL5NPS... | .157 | .07 | .11 | | | |

Round (DIN 405)


External



Defined by: DIN 405
Tolerance class: 7h/7H



Standard



F-Line


Standard




FLINE

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|------------|-----------------|-----|-----|-------|-----|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 10 | 3ER10RD... | 3EL10RD... | .050 | .04 | .05 | YE3 | YI3 | AL..-3 (LH) |
| | | 8 | 3ER8RD... | 3EL8RD... | .063 | .06 | .05 | | | |
| | | 6 | 3ER6RD... | 3EL6RD... | .083 | .06 | .07 | | | |
| 1/2" | .87 | 6 | 4ER6RD... | 4EL6RD... | .083 | .06 | .07 | YE4 | YI4 | AL..-4 (LH) |
| | | 4 | 4ER4RD... | 4EL4RD... | .125 | .09 | .09 | | | |
| 1/2"F | .91 | 6 | 4FER6RD... | | .083 | .06 | .07 | YE4F | | AL...-4F |
| | | 4 | 4FER4RD... | | .125 | .09 | .09 | | | |
| 5/8" | 1.06 | 4 | 5ER4RD... | 5EL4RD... | .125 | .09 | .09 | YE5 | YI5 | AL..-5 (LH) |


Internal



Defined by: DIN 405
Tolerance class: 7h/7H



Standard



F-Line

Standard




FLINE


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 10 | 3IR10RD... | 3IL10RD... | .050 | .04 | .05 | YI3 | YE3 | AVR..-3 (LH) |
| | | 8 | 3IR8RD... | 3IL8RD... | .063 | .06 | .06 | | | |
| | | 6 | 3IR6RD... | 3IL6RD... | .083 | .06 | .06 | | | |
| 1/2" | .87 | 6 | 4IR6RD... | 4IL6RD... | .083 | .06 | .07 | YI4 | YE4 | AVR..-4 (LH) |
| | | 4 | 4IR4RD... | 4IL4RD... | .125 | .09 | .09 | | | |
| 1/2"F | .91 | 6 | 4FIR6RD... | | .083 | .06 | .07 | YI4F | | AVRC...-4F |
| | | 4 | 4FIR4RD... | | .125 | .09 | .09 | | | |
| 5/8" | 1.06 | 4 | 5IR4RD... | 5IL4RD... | .125 | .09 | .09 | YI5 | YE5 | AVR..-5 (LH) |

Round (DIN 20400)


External




Defined by: DIN 20400
Tolerance class: Standard



Standard



F-Line



U Style

Standard



F-LINE

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-------------------|------------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/2" | .87 | 3.0 | 4ER3.0RD20400... | 4EL3.0RD20400... | .065 | .05 | .07 | YE4 | YI4 | AL...-4 (LH) |
| | | 4.0 | 4ER4.0RD20400... | 4EL4.0RD20400... | .087 | .06 | .09 | | | |
| | | 5.0 | 4ER5.0RD20400... | 4EL5.0RD20400... | .108 | .06 | .07 | | | |
| | | 6.0 | 4ER6.0RD20400... | 4EL6.0RD20400... | .130 | .07 | .08 | | | |
| 1/2"F | .91 | 3.0 | 4FER3.0RD20400... | | .065 | .05 | .07 | YE4F | | AL...-4F |
| | | 4.0 | 4FER4.0RD20400... | | .087 | .06 | .09 | | | |
| | | 5.0 | 4FER5.0RD20400... | | .108 | .06 | .07 | | | |
| | | 6.0 | 4FER6.0RD20400... | | .130 | .07 | .08 | | | |

U Style




| Insert Size | | Pitch | Ordering Code | Dimensions inch | | | Anvil | | Toolholder | |
|-------------|--------|-------|-------------------|-----------------|------|-----|-------|------|------------|---------------|
| IC | L inch | mm | RH+LH | h min | X | Y | RH | LH | | |
| 5/8"U | 1.06 | 8.0 | 5UEI8.0RD20400... | | .173 | .11 | .53 | YE5U | YI5U | AL...-5U (LH) |



Round (DIN 20400) (con't)

MEGALINE

External



Defined by: DIN 20400
Tolerance class: Standard




Mega Line

External





| Insert Size | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | | | |
|-------------|-------|---------------|---------------------|-----------------|--------|-----|------------------|-----|-------|----|
| | | | | IC | L inch | mm | RH | VKX | h min | X |
| 5/8" MG | 1.06 | 10.0 | 5MGER10.0RD20400... | 42517 | .217 | .16 | | | 78 | 36 |
| | | 12.0 | 5MGER12.0RD20400... | 42518 | .260 | .21 | .44 | | 93 | 43 |
| | | 16.0 | 5MGER16.0RD20400... | 42519 | .346 | .19 | | | 124 | 58 |



External Toolholders for Round (DIN 20400)

MEGALINE




External

| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.-Max.) | Spare Parts | | |
|---------------------|---------------|---------|-----------------|--------|-----|-----------------------------------|----------------|------|--------------|
| | | | RH | H=B=H1 | F | | L1 | L2 | Insert Screw |
| 5MGER10.0RD20400... | NL100-5MG10RD | 66251 | 1.00 | .65 | 6.1 | .87 | (RD132-170)x10 | S5MG | K6T |
| | NL125-5MG10RD | 66253 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG10RD | 66256 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER12.0RD20400... | NL100-5MG12RD | 66257 | 1.00 | .65 | 6.1 | .87 | (RD180-224)x12 | S5MG | K6T |
| | NL125-5MG12RD | 66258 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG12RD | 66259 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER16.0RD20400... | NL100-5MG16RD | 66262 | 1.00 | .65 | 6.1 | .87 | (RD236-300)x16 | S5MG | K6T |
| | NL125-5MG16RD | 66263 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG16RD | 66266 | 1.50 | 1.24 | 8.1 | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Round (DIN 20400) (con't)


Internal




Defined by: DIN 20400
Tolerance class: Standard



Standard



F-Line



U Style

Standard



F.LINE

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-------------------|------------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/2" | .87 | 3.0 | 4IR3.0RD20400... | 4IL3.0RD20400... | .065 | .05 | .07 | YI4 | YE4 | AVR..-4 (LH) |
| | | 4.0 | 4IR4.0RD20400... | 4IL4.0RD20400... | .087 | .06 | .09 | | | |
| | | 5.0 | 4IR5.0RD20400... | 4IL5.0RD20400... | .108 | .06 | .07 | | | |
| | | 6.0 | 4IR6.0RD20400... | 4IL6.0RD20400... | .130 | .07 | .08 | | | |
| 1/2"F | .91 | 3.0 | 4FIR3.0RD20400... | | .065 | .05 | .07 | YI4F | | AVRC...-4F |
| | | 4.0 | 4FIR4.0RD20400... | | .087 | .06 | .09 | | | |
| | | 5.0 | 4FIR5.0RD20400... | | .108 | .06 | .07 | | | |
| | | 6.0 | 4FIR6.0RD20400... | | .130 | .07 | .08 | | | |

U Style




| Insert Size | | Pitch | Ordering Code | Dimensions inch | | | Anvil | | Toolholder | |
|-------------|--------|-------|-------------------|-----------------|------|-----|-------|------|------------|---------------|
| IC | L inch | mm | RH+LH | h min | X | Y | RH | LH | | |
| 5/8"U | 1.06 | 8.0 | 5UEI8.0RD20400... | | .173 | .11 | .53 | YI5U | YE5U | AVR..-5U (LH) |


Round (DIN 20400) (con't)

MEGALINE


Internal



Defined by: DIN 20400
Tolerance class: Standard




Mega Line





Internal



| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|---------------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch-Min. Depth of Cut (On radius) | 0.006inch-Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 10.0 | 5MGIR10.0RD20400... | 42514 | .217 | .16 | | 78 | 36 |
| | | 12.0 | 5MGIR12.0RD20400... | 42515 | .260 | .21 | .41 | 93 | 43 |
| | | 16.0 | 5MGIR16.0RD20400... | 42516 | .346 | .19 | | 124 | 58 |



Internal Toolholders for Round (DIN 20400) MEGALINE




Internal

| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | Min. Bore Dia. inch | Thread Diameter Range (Min.-Max.) | | Spare Parts | |
|---------------------|-----------------|---------|-----------------|-------|----------|-----|------|------|---------------------|-----------------------------------|--------------------|--------------|----------|
| | | | A | L | L1 (max) | D | D1 | F | | Short Chip Material | Long Chip Material | Insert Screw | Torx Key |
| 5MGIR10.0RD20400... | NVRC150-5MG10RD | 66276 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 4.8 | (RD132-170)x10 | (RD132-170)x10 | S5MG | K6T |
| | NVRC200-5MG10RD | 66278 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | | | | | |
| | NVRC250-5MG10RD | 66288 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | | | | | |
| 5MGIR12.0RD20400... | NVRC150-5MG12RD | 66289 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 6.61 | (RD180-224)x12 | (RD180-224)x12 | | |
| | NVRC200-5MG12RD | 66293 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | | | | | |
| | NVRC250-5MG12RD | 66318 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | | | | | |
| 5MGIR16.0RD20400... | NVRC150-5MG16RD | 66321 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 8.66 | (RD236-300)x16 | (RD236-300)x16 | | |
| | NVRC200-5MG16RD | 66339 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | | | | | |
| | NVRC250-5MG16RD | 66340 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Trapez

External



Defined by: DIN 103
Tolerance class: 7e/7H



Standard
F-Line
U Style
V Style

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|-------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 1.5 | 2ER1.5TR... | 2EL1.5TR... | .035 | .03 | .04 | - | - | NL...-2 (LH) |
| | | 1.5 | 3ER1.5TR... | 3EL1.5TR... | .035 | .04 | .04 | | | |
| 3/8" | .63 | 2.0 | 3ER2.0TR... | 3EL2.0TR... | .049 | .04 | .05 | YE3 | YI3 | AL...-3 (LH) |
| | | 2.5 | 3ER2.5TR... | 3EL2.5TR... | .061 | .05 | .06 | | | |
| | | 3.0 | 3ER3.0TR... | 3EL3.0TR... | .069 | .05 | .06 | | | |
| 1/2" | .87 | 4.0 | 4ER4.0TR... | 4EL4.0TR... | .089 | .07 | .07 | YE4 | YI4 | AL...-4 (LH) |
| | | 5.0 | 4ER5.0TR... | 4EL5.0TR... | .108 | .08 | .10 | | | |
| 1/2"F | .91 | 4.0 | 4FER4.0TR... | | .089 | .07 | .07 | YE4F | | AL...-4F |
| | | 5.0 | 4FER5.0TR... | | .108 | .08 | .10 | | | |
| | | 6.0 | 4FER6.0TR... | | .138 | .09 | .11 | | | |
| 5/8" | 1.06 | 6.0 | 5ER6.0TR... | 5EL6.0TR... | .138 | .09 | .11 | YE5 | YI5 | AL...-5 (LH) |

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--|-----------------|-----|-----|-------|------|---------------|
| IC | L inch | mm | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 6.0 | 4UE6.0TR... | | .138 | .08 | .43 | YE4U | YI4U | AL...-4U (LH) |
| | | 7.0 | 4UE7.0TR... | | .157 | .09 | .43 | | | |
| | | 8.0 | 4UE8.0TR... | | .177 | .10 | .43 | | | |
| 5/8"U | 1.06 | 8.0 | 5UE8.0TR... | | .177 | .10 | .54 | YE5U | YI5U | AL...-5U (LH) |
| | | 9.0 | 5UE9.0TR... | | .197 | .12 | .54 | | | |

V Style




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-----|-----------------|
| IC | L inch | mm | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 6.0 | 5VER6.0TR... | 5VEL6.0TR... | .138 | .04 | .13 | .24 | NL...-5V-6 (LH) |
| | | 7.0 | 5VER7.0TR... | 5VEL7.0TR... | .157 | .04 | .13 | .24 | |
| | | 8.0 | 5VER8.0TR... | 5VEL8.0TR... | .177 | .04 | .13 | .24 | NL...-5V-8 (LH) |
| | | 9.0 | 5VER9.0TR... | 5VEL9.0TR... | .197 | .04 | .17 | .31 | |
| | | 10.0 | 5VER10.0TR... | 5VEL10.0TR... | .217 | .04 | .17 | .31 | |
| | | 12.0 | 5VER12.0TR... | 5VEL12.0TR... | .256 | .04 | .20 | .39 | |



Trapez (con't)

MEGALINE

External



Defined by: DIN 103
Tolerance class: 7e/7H



Mega Line




External



| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch-Min. Depth of Cut (On radius) | 0.006inch-Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 12.0 | 5MGER12.0TR... | 42540 | .256 | .21 | .44 | 94 | 44 |
| | | 14.0 | 5MGER14.0TR... | 42541 | .315 | .17 | | 115 | 54 |
| | | 16.0 | 5MGER16.0TR... | 42530 | .354 | .21 | | 129 | 60 |
| | | 18.0 | 5MGER18.0TR... | 42531 | .394 | .21 | | 143 | 67 |
| | | 20.0 | 5MGER20.0TR... | 42532 | .433 | .29 | | 158 | 74 |
| | | 24.0 | 5MGER24.0TR... | 42533 | .512 | .29 | | 186 | 87 |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

External Toolholders for Trapez



External


Spare Parts

| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.-Max.) |  |  |
|----------------|---------------|---------|-----------------|--------|-----|-----------------------------------|---|---|
| | | | RH | H=B=H1 | F | | | |
| 5MGER12.0TR... | NL100-5MG12TR | 66491 | 1.00 | .65 | 6.1 | .87 (TR44-300)x12 | S5MG | K6T |
| | NL125-5MG12TR | 66492 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG12TR | 66493 | 1.50 | 1.24 | 8.1 | | | |
| 5MGER14.0TR... | NL100-5MG14TR | 66494 | 1.00 | .65 | 6.1 | .87 (TR55-145)x14 | | |
| | NL125-5MG14TR | 66495 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG14TR | 66496 | 1.50 | 1.24 | 8.1 | | | |
| 5MGER16.0TR... | NL100-5MG16TR | 66497 | 1.00 | .65 | 6.1 | .87 (TR65-175)x16 | | |
| | NL125-5MG16TR | 66498 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG16TR | 66499 | 1.50 | 1.24 | 8.1 | | | |
| 5MGER18.0TR... | NL100-5MG18TR | 66500 | 1.00 | .65 | 6.1 | .87 (TR85-200)x18 | | |
| | NL125-5MG18TR | 66501 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG18TR | 66502 | 1.50 | 1.24 | 8.1 | | | |
| 5MGER20.0TR... | NL100-5MG20TR | 66503 | 1.00 | .65 | 6.1 | .87 (TR100-230)x20 | | |
| | NL125-5MG20TR | 66504 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG20TR | 66505 | 1.50 | 1.24 | 8.1 | | | |
| 5MGER24.0TR... | NL100-5MG24TR | 66506 | 1.00 | .65 | 6.1 | .87 (TR135-300)x24 | | |
| | NL125-5MG24TR | 66507 | 1.25 | .93 | 6.9 | | | |
| | NL150-5MG24TR | 66508 | 1.50 | 1.24 | 8.1 | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Trapez (con't)


Internal




Defined by: DIN 103
Tolerance class: 7e/7H



Standard



F-Line



U Style

Standard




FLINE


| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------|-------------|-------------|--------------|---------------|------|-----------------|-----|------|-------|--------------|------------|
| | IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 1.5 | 2IR1.5TR... | 2IL1.5TR... | .035 | .03 | .04 | - | - | NVR 8-2 (LH) | |
| | | 1.5 | 3IR1.5TR... | 3IL1.5TR... | .035 | .04 | .04 | Y13 | YE3 | AVR..-3 (LH) | |
| | | 2.0 | 3IR2.0TR... | 3IL2.0TR... | .049 | .04 | .05 | | | | |
| 2.5 | 3IR2.5TR... | 3IL2.5TR... | .060 | .05 | .06 | | | | | | |
| 3/8" | .63 | 3.0 | 3IR3.0TR... | 3IL3.0TR... | .069 | .05 | .06 | Y14 | YE4 | AVR..-4 (LH) | |
| | | 4.0 | 4IR4.0TR... | 4IL4.0TR... | .089 | .07 | .07 | | | | |
| | | 5.0 | 4IR5.0TR... | 4IL5.0TR... | .108 | .08 | .10 | | | | |
| 1/2" | .87 | 6.0 | 4IR6.0TR... | 4IL6.0TR... | .138 | .09 | .11 | Y14F | | AVRC...-4F | |
| | | 4.0 | 4FIR4.0TR... | | .089 | .07 | .07 | | | | |
| | | 5.0 | 4FIR5.0TR... | | .108 | .08 | .10 | | | | |
| 1/2"F | .91 | 6.0 | 4FIR6.0TR... | | .138 | .09 | .11 | | | | |
| | | 6.0 | 5IR6.0TR... | 5IL6.0TR... | .138 | .09 | .11 | | | | Y15 |

Trapez (con't)


Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Coarse Pitch



U Style Coarse Pitch

Coarse Pitch RH

| | Thread | Insert Size | | Ordering Code | Dimensions inch | | | Toolholder RH | Min Bore Dia. |
|---|---------------------|-------------|---------------------|---------------------|-----------------|-----|--------------------|--------------------|---------------|
| | | IC | L inch | RH | h min | X | Y | Inch | Inch |
|  | TR18x4 | 3/8"U | .63 | 3UIR4.0TR158/013... | .089 | .08 | .31 | NVRC044-3U-157/020 | .55 |
| | TR20x4 | 3/8" | .63 | 3IR4.0TR158/012... | .089 | .06 | .07 | NVRC050-3-157/006 | .63 |
| | TR22x5 | 3/8"U | .63 | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC055-3U-157/018 | .67 |
| | TR24x5 | | | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC059-3U-157/019 | .75 |
| | TR26x5 | | | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC059-3U-157/019 | .83 |
| | TR28x5 | 1/2" | .87 | 4IR5.0TR... | .108 | .09 | .11 | NVRC075-4-157/008 | .91 |
| | TR30x6 | 1/2"U | .87 | 4UIR6.0TR158/007... | .138 | .08 | .43 | NVRC075-4U-157/011 | .94 |
| | TR36x6 | 5/8" | 1.06 | 5IR6.0TR... | .138 | .09 | .11 | NVRC100-5-157/012 | 1.18 |
| | TR38x7 | 1/2"U | .87 | 4UIR7.0TR158/008... | .157 | .09 | .43 | NVRC100-4U-157/013 | 1.22 |
| | TR40x7 | | | 4UIR7.0TR158/008... | .157 | .09 | .43 | NVRC100-4U-157/013 | 1.30 |
| TR42x7 | 4UIR7.0TR158/008... | | | .157 | .09 | .43 | NVRC125-4U-157/014 | 1.38 | |
| TR44x7 | 4UIR7.0TR158/008... | | | .157 | .09 | .43 | NVRC125-4U-157/014 | 1.46 | |
| TR46x8 | 5/8"U | 1.06 | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5U-157/015 | 1.50 | |
| TR48x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5U-157/015 | 1.57 | |
| TR50x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5U-157/015 | 1.65 | |
| TR52x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5U-157/015 | 1.73 | |


Coarse Pitch LH

| | Thread | Insert Size | | Ordering Code | Dimensions inch | | | Toolholder LH | Min Bore Dia. |
|---|---------------------|-------------|---------------------|---------------------|-----------------|-----|----------------------|----------------------|---------------|
| | | IC | L inch | LH | h min | X | Y | Inch | Inch |
|  | TR18x4 | 3/8"U | .63 | 3UIR4.0TR158/013... | .089 | .08 | .31 | NVRC044-3ULH-157/038 | .55 |
| | TR20x4 | 3/8" | .63 | 3IL4.0TR158/015... | .089 | .06 | .07 | NVRC050-3LH-157/030 | .63 |
| | TR22x5 | 3/8"U | .63 | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC055-3ULH-157/036 | .67 |
| | TR24x5 | | | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC059-3ULH-157/037 | .75 |
| | TR26x5 | | | 3UIR5.0TR158/011... | .108 | .06 | .31 | NVRC059-3ULH-157/037 | .83 |
| | TR28x5 | 1/2" | .87 | 4IL5.0TR... | .108 | .09 | .11 | NVRC075-4LH-157/017 | .91 |
| | TR30x6 | 1/2"U | .87 | 4UIR6.0TR158/007... | .138 | .08 | .43 | NVRC075-4ULH-157/024 | .94 |
| | TR36x6 | 5/8" | 1.06 | 5IL6.0TR... | .138 | .09 | .11 | NVRC100-5LH-157/031 | 1.18 |
| | TR38x7 | 1/2"U | .87 | 4UIR7.0TR158/008... | .157 | .09 | .43 | NVRC100-4ULH-157/032 | 1.22 |
| | TR40x7 | | | 4UIR7.0TR158/008... | .157 | .09 | .43 | NVRC100-4ULH-157/032 | 1.30 |
| TR42x7 | 4UIR7.0TR158/008... | | | .157 | .09 | .43 | NVRC125-4ULH-157/033 | 1.38 | |
| TR44x7 | 4UIR7.0TR158/008... | | | .157 | .09 | .43 | NVRC125-4ULH-157/033 | 1.46 | |
| TR46x8 | 5/8"U | 1.06 | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5ULH-157/034 | 1.50 | |
| TR48x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5ULH-157/034 | 1.57 | |
| TR50x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5ULH-157/034 | 1.65 | |
| TR52x8 | | | 5UIR8.0TR158/010... | .177 | .10 | .53 | NVRC125-5ULH-157/034 | 1.73 | |


U Type RH inserts can be used for both LH and RH applications.

Trapez (con't)


Internal



Defined by: DIN 103
Tolerance class: 7e/7H



U Style



V Style

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--|-----------------|-----|-----|-------|------|---------------|
| IC | L inch | mm | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 6.0 | 4UI6.0TR... | | .138 | .08 | .43 | YI4U | YE4U | AVR..-4U (LH) |
| | | 7.0 | 4UI7.0TR... | | .157 | .09 | .43 | | | |
| | | 8.0 | 4UI8.0TR... | | .177 | .10 | .43 | | | |
| 5/8"U | 1.06 | 8.0 | 5UI8.0TR... | | .177 | .10 | .54 | YI5U | YE5U | AVR..-5U (LH) |
| | | 9.0 | 5UI9.0TR... | | .197 | .12 | .54 | | | |

V Style




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-----|---------------|
| IC | L inch | mm | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 6.0 | 5VIR6.0TR... | 5VIL6.0TR... | .138 | .04 | .13 | .24 | NVR..-5V (LH) |
| | | 7.0 | 5VIR7.0TR... | 5VIL7.0TR... | .157 | .04 | .13 | .24 | |
| | | 8.0 | 5VIR8.0TR... | 5VIL8.0TR... | .177 | .04 | .13 | .24 | |
| | | 9.0 | 5VIR9.0TR... | 5VIL9.0TR... | .197 | .04 | .17 | .31 | |
| | | 10.0 | 5VIR10.0TR... | 5VIL10.0TR... | .217 | .04 | .17 | .31 | |
| | | 12.0 | 5VIR12.0TR... | 5VIL12.0TR... | .256 | .04 | .20 | .39 | |


Trapez

MEGA LINE


Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Mega Line




Internal




| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch-Min. Depth of Cut (On radius) | 0.006inch-Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 12.0 | 5MGIR12.0TR... | 42534 | .25 | .21 | .41 | 96 | 45 |
| | | 14.0 | 5MGIR14.0TR... | 42535 | .31 | .17 | | 118 | 55 |
| | | 16.0 | 5MGIR16.0TR... | 42536 | .35 | .21 | | 131 | 61 |
| | | 18.0 | 5MGIR18.0TR... | 42537 | .39 | .21 | | 145 | 68 |
| | | 20.0 | 5MGIR20.0TR... | 42538 | .43 | .29 | | 160 | 75 |
| | | 24.0 | 5MGIR24.0TR... | 42539 | .51 | .29 | | 188 | 88 |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.



Internal Toolholders for Trapez

MEGA/LINE



Internal

Spare Parts


| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Spare Parts | | |
|----------------|-----------------|---------|-----------------|-------|----------|-----|------|------|------|----------------|-----------------------------------|--------------------|--------------|----------|--|
| | | | A | L | L1 (max) | D | D1 | F | inch | | Short Chip Material | Long Chip Material | Insert Screw | Torx Key | |
| | | | RH | | | | | | | | | | | | |
| 5MGIR12.OTR... | NVRC150-5MG12TR | 66509 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.87 | (TR85-300)x12 | (TR85-300)x12 | S5MG | K6T | | |
| | NVRC200-5MG12TR | 66510 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.87 | (TR85-300)x12 | (TR95-300)x12 | | | | |
| | NVRC250-5MG12TR | 66511 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.27 | (TR95-300)x12 | (TR105-300)x12 | | | | |
| 5MGIR14.OTR... | NVRC150-5MG14TR | 66512 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 3.98 | (TR115-145)x14 | (TR115-145)x14 | | | | |
| | NVRC200-5MG14TR | 66513 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 3.98 | (TR115-145)x14 | (TR115-145)x14 | | | | |
| | NVRC250-5MG14TR | 66514 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.98 | (TR115-145)x14 | (TR115-145)x14 | | | | |
| 5MGIR16.OTR... | NVRC150-5MG16TR | 66515 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.52 | (TR80-175)x16 | (TR150-175)x16 | | | | |
| | NVRC200-5MG16TR | 66516 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 5.28 | (TR150-175)x16 | (TR150-175)x16 | | | | |
| | NVRC250-5MG16TR | 66517 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 5.28 | (TR150-175)x16 | (TR150-175)x16 | | | | |
| 5MGIR18.OTR... | NVRC150-5MG18TR | 66518 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.64 | (TR85-200)x18 | (TR90-200)x18 | | | | |
| | NVRC200-5MG18TR | 66519 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.83 | (TR90-200)x18 | (TR180-200)x18 | | | | |
| | NVRC250-5MG18TR | 66520 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 6.38 | (TR180-200)x18 | (TR180-200)x18 | | | | |
| 5MGIR20.OTR... | NVRC150-5MG20TR | 66521 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 3.15 | (TR100-230)x20 | (TR100-230)x20 | | | | |
| | NVRC200-5MG20TR | 66522 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 3.15 | (TR100-230)x20 | (TR100-230)x20 | | | | |
| | NVRC250-5MG20TR | 66523 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.35 | (TR105-230)x20 | (TR210-230)x20 | | | | |
| 5MGIR24.OTR... | NVRC150-5MG24TR | 66524 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 4.37 | (TR135-300)x24 | (TR135-300)x24 | | | | |
| | NVRC200-5MG24TR | 66525 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 4.37 | (TR135-300)x24 | (TR135-300)x24 | | | | |
| | NVRC250-5MG24TR | 66526 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 4.37 | (TR135-300)x24 | (TR135-300)x24 | | | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.


Trapez (con't)

Mini-V

Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Mini-V




| Min. Thread | Insert Style | Pitch | Ordering Code | | Dimensions inch | | | | | Helix | Toolholder |
|-------------|--------------|-------|----------------|-----|-----------------|-----|-----|-------|------|----------|------------|
| | | | RH | d | T | F | Y | h min | Deg. | | |
| TR10x2.0 | V08 | 2.0 | V08TH2.0TRR... | .24 | .15 | .19 | .04 | .05 | 3.5 | .V08-... | |
| TR11x3.0 | | 3.0 | V08TH3.0TRR... | .19 | .05 | .07 | 5 | | | | |
| TR16x4.0 | V11 | 4.0 | V11TH4.0TRR... | .31 | .17 | .26 | .06 | .09 | 4.5 | .V11-... | |






Trapez

MINIPRO

Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-------|-----|----------------|-------------------|
| IC mm | L inch | | mm | RH | LH | h min | Y | F | |
| 5.0 | .31 | 1.5 | 5.0KIR1.5TR... | 5.0KIL1.5TR... | .033 | .03 | .19 | .31 | .NVR...-5.0K (LH) |
| 6.0 | .39 | 1.5 | 6.0KIR1.5TR... | 6.0KIL1.5TR... | .033 | .03 | .21 | .39 | .NVR...-6.0K (LH) |
| | | 2.0 | 6.0KIR2.0TR... | 6.0KIL2.0TR... | .049 | .05 | .21 | .39 | |

Mini-3 U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|---------------|-------|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | | mm | RH+LH | h min | Y | F | inch | |
| 5.0U | .31 | 2.0 | 5.0KUI2TR... | | .049 | .16 | .22 | .35 | .NVR...-5.0KU (LH) |

Mini-L



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-----|---------------|---------------|------|-----------------|-----|-----|------------------|------------|
| IC mm | mm | | RH | LH | h min | Y | F | inch | |
| 5.0L | 1.5 | 5LKIR1.5TR... | 5LKIL1.5TR... | .033 | .03 | .18 | .31 | .NVR...-5LK (LH) | |
| | 2.0 | 5LKIR2.0TR... | 5LKIL2.0TR... | .049 | .05 | .19 | .35 | | |

American ACME

External

Defined by: ANSI B1.5:1988
Tolerance class: 3G

Standard

| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--------|-------------|--------|--------------|---------------|--------------|-----------------|-----|------|-------|-------------|-------------|
| | IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| | 1/4" | 0.43 | 16 | 2ER16ACME... | 2EL16ACME... | .036 | .04 | .04 | - | - | NL..-2 (LH) |
| | | | 14 | 3ER14ACME... | 3EL14ACME... | .041 | .04 | .05 | | | |
| | 3/8" | .63 | 12 | 3ER12ACME... | 3EL12ACME... | .047 | .04 | .05 | YE3 | YI3 | AL..-3 (LH) |
| | | | 10 | 3ER10ACME... | 3EL10ACME... | .060 | .05 | .06 | | | |
| | | | 8 | 3ER8ACME... | 3EL8ACME... | .072 | .06 | .06 | | | |
| | | | 7 | 3ER7ACME... | 3EL7ACME... | .082 | .07 | .09 | | | |
| 1/2" | .87 | 7 | 4ER7ACME... | 4EL7ACME... | .082 | .07 | .09 | YE4 | YI4 | AL..-4 (LH) | |
| | | 6 | 4ER6ACME... | 4EL6ACME... | .093 | .07 | .08 | | | | |
| | | 5 | 4ER5ACME... | 4EL5ACME... | .110 | .08 | .09 | | | | |
| 1/2" F | .91 | 6 | 4FER6ACME... | | .093 | .07 | .08 | YE4F | | AL...-4F | |
| | | 5 | 4FER5ACME... | | .110 | .08 | .09 | | | | |
| 5/8" | 1.06 | 4 | 5ER4ACME... | 5EL4ACME... | .135 | .09 | .11 | YE5 | YI5 | AL..-5 (LH) | |

F.LINE

U Style

| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--------|-------------|--------|-------------|---------------|------|-----------------|-----|------|-------|--------------|--------------|
| | IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
| | 1/2" U | .87 | 4 | 4UE4ACME... | | .135 | .09 | .43 | YE4U | YI4U | AL..-4U (LH) |
| | | | 3 | 4UE3ACME... | | .177 | .12 | .43 | | | |
| 5/8" U | 1.06 | 3 | 5UE3ACME... | | .177 | .12 | .54 | YE5U | YI5U | AL..-5U (LH) | |

V Style

| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|--|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|-----|----------------|
| | IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| | 5/8" V | 1.06 | 4 | 5VER4ACME... | 5VEL4ACME... | .135 | .04 | .13 | .24 | NL..-5V-6 (LH) |
| | | | 3.5 | 5VER3.5ACME... | 5VEL3.5ACME... | .152 | .04 | .13 | .24 | |
| | | | 3 | 5VER3ACME... | 5VEL3ACME... | .177 | .04 | .13 | .24 | |
| | | | 2 | 5VER2ACME... | 5VEL2ACME... | .260 | .04 | .20 | .39 | |

On Edge


| | Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | |
|------|-------------|--------|-------------------|-------------------|------|-----------------|-----|-----|-----|-----|
| | IC | L inch | TPI | RH | | h min | T | Ø C | X | Y |
| | 1/2" | .87 | 12 | TNEC43E112ACME... | | .047 | .19 | .20 | .02 | .09 |
| | | | 10 | TNEC43E110ACME... | | .060 | | | | |
| | | | 8 | TNEC43E108ACME... | | .072 | | | | |
| | | | 6 | TNEC43E106ACME... | | .093 | | | | |
| | | | 4 | TNEC43E104ACME... | | .135 | | | | |
| 5/8" | 1.06 | 4 | TNEC54E104ACME... | | .135 | .25 | .26 | | .13 | |
| | | 3 | TNEC54E103ACME... | | .177 | | | | | |
| 3/4" | 1.26 | 2 | TNEC56E102ACME... | | .260 | .38 | .31 | | .19 | |

On Edge inserts are suited to existing toolholders on the market.



American ACME (con't)

MEGALINE

External




Defined by: ANSI B1.5:1988
Tolerance class: 3G



Mega Line



External

| Insert Size | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | | | |
|-------------|-------|---------------|-------------------|-----------------|--------|-----|------------------|-----|-------|----|
| | | | | IC | L inch | TPI | RH | VKX | h min | X |
| 5/8" MG | 1.06 | 2 | 5MGER2ACME... | 42511 | .260 | .19 | .45 | | 95 | 44 |
| | | 1 1/2 | 5MGER1-1/2ACME... | 42508 | .343 | .23 | | | 125 | 58 |
| | | 1 1/3 | 5MGER1-1/3ACME... | 42509 | .385 | .27 | | | 140 | 65 |
| | | 1 | 5MGER1ACME... | 42510 | .510 | .33 | | | 186 | 87 |



External Toolholders for American ACME

MEGALINE




External

| Insert | Ordering Code | EDP No. | Dimensions | | | | Thread Diameter Range (Min.-Max.) | Spare Parts | |
|-------------------|--------------------|---------|------------|------|-----|-----|-----------------------------------|--------------|----------|
| | | | H=B=H1 | F | L1 | L2 | | Insert Screw | Torx Key |
| 5MGER2ACME... | NL100-5MG2ACME | 66409 | 1.00 | .65 | 6.1 | .87 | (3"-5")-2ACME | S5MG | K6T |
| | NL125-5MG2ACME | 66410 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG2ACME | 66412 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER1-1/2ACME... | NL100-5MG1-1/2ACME | 66413 | 1.00 | .65 | 6.1 | .87 | (3"-5")-1 1/2ACME | S5MG | K6T |
| | NL125-5MG1-1/2ACME | 66414 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG1-1/2ACME | 66415 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER1-1/3ACME... | NL100-5MG1-1/3ACME | 66416 | 1.00 | .65 | 6.1 | .87 | (3"-5")-1 1/3ACME | S5MG | K6T |
| | NL125-5MG1-1/3ACME | 66417 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG1-1/3ACME | 66418 | 1.50 | 1.24 | 8.1 | | | | |
| 5MGER1ACME... | NL100-5MG1ACME | 66420 | 1.00 | .65 | 6.1 | .87 | (3.5"-5")-1ACME | S5MG | K6T |
| | NL125-5MG1ACME | 66422 | 1.25 | .93 | 6.9 | | | | |
| | NL150-5MG1ACME | 66423 | 1.50 | 1.24 | 8.1 | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

American ACME (con't)

Internal



Defined by: ANSI B1.5:1988
Tolerance class: 3G



Standard

F-Line

Standard




FLINE


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 16 | 2IR16ACME... | 2IL16ACME... | .036 | .04 | .04 | - | - | NVR..-2 (LH) |
| | | 16 | 3IR16ACME... | 3IL16ACME... | .036 | .04 | .04 | | | |
| 3/8" | .63 | 14 | 3IR14ACME... | 3IL14ACME... | .041 | .04 | .05 | | | AVR..-3 (LH) |
| | | 12 | 3IR12ACME... | 3IL12ACME... | .047 | .05 | .05 | Y13 | YE3 | |
| | | 10 | 3IR10ACME... | 3IL10ACME... | .060 | .05 | .05 | | | |
| | | 8 | 3IR8ACME... | 3IL8ACME... | .072 | .06 | .06 | | | |
| 1/2" | .87 | 6 | 4IR6ACME... | 4IL6ACME... | .093 | .07 | .08 | Y14 | YE4 | AVR..-4 (LH) |
| | | 5 | 4IR5ACME... | 4IL5ACME... | .110 | .08 | .09 | | | |
| 1/2"F | .91 | 6 | 4FIR6ACME... | | .093 | .07 | .08 | Y14F | | AVRC...-4F |
| | | 5 | 4FIR5ACME... | | .110 | .08 | .09 | | | |
| 5/8" | 1.06 | 4 | 5IR4ACME... | 5IL4ACME... | .135 | .09 | .10 | Y15 | YE5 | AVR..-5 (LH) |

American ACME (con't)


Internal



Defined by: ANSI B1.5:1988
Tolerance class: 3G



Standard




U Style

Coarse Pitch RH



| Thread | Insert Size | | Ordering Code | Dimensions inch | | | Anvil | Min Bore Dia. | |
|----------|-------------|--------|-------------------------|-----------------|-----|-----|--------|-----------------------|------|
| TPI | IC | L inch | RH | h min | X | Y | RH | Toolholder RH | Inch |
| 1/2"x10 | 6.0U | .39 | 6.0KUIR10ACME158/005... | .060 | .04 | .20 | - | NVRC032-6.0KU-157/003 | .40 |
| 5/8"x8 | 1/4"U | .43 | 2UIR8ACME158/006... | .072 | .04 | .22 | - | NVRC039-2U-157/004 | .50 |
| 3/4"x6 | 3/8" | .63 | 3IR6ACME... | .093 | .07 | .07 | - | NVRC044-3-157/005 | .58 |
| 7/8"x6 | | | 3IR6ACME... | .093 | .07 | .07 | - | NVRC050-3-157/006 | .73 |
| 1"x5 | 1/2" | .87 | 4IR5ACME158/018... | .110 | .08 | .09 | - | NVRC067-4-157/039 | .83 |
| 1 1/8"x5 | | | 4IR5ACME... | .110 | .08 | .09 | - | NVRC075-4-157/008 | .94 |
| 1 1/4"x5 | | | 4IR5ACME... | .110 | .08 | .09 | - | NVRC075-4-157/009 | 1.07 |
| 1 1/2"x4 | 5/8" | 1.06 | 5IR4ACME... | .135 | .09 | .10 | - | NVRC110-5-157/010 | 1.27 |
| 1 3/4"x4 | | | 5IR4ACME... | .135 | .09 | .10 | YI5-1P | AVRC125-5 | 1.53 |

Coarse Pitch LH



| Thread | Insert Size | | Ordering Code | Dimensions inch | | | Anvil | Min Bore Dia. | |
|----------|-------------|--------|-------------------------|-----------------|-----|-----|--------|-------------------------|------|
| TPI | IC | L inch | LH | h min | X | Y | LH | Toolholder LH | Inch |
| 1/2"x10 | 6.0U | .39 | 6.0KUIR10ACME158/005... | .060 | .04 | .20 | - | NVRC032-6.0KULH-157/027 | .40 |
| 5/8"x8 | 1/4"U | .43 | 2UIR8ACME158/006... | .072 | .04 | .22 | - | NVRC039-2ULH-157/028 | .50 |
| 3/4"x6 | 3/8" | .63 | 3IL6ACME... | .093 | .07 | .07 | - | NVRC044-3LH-157/029 | .58 |
| 7/8"x6 | | | 3IL6ACME... | .093 | .07 | .07 | - | NVRC050-3LH-157/030 | .73 |
| 1"x5 | 1/2" | .87 | 4IL5ACME158/019... | .110 | .08 | .09 | - | NVRC067-4LH-157/040 | .83 |
| 1 1/8"x5 | | | 4IL5ACME... | .110 | .08 | .09 | - | NVRC075-4LH-157/017 | .94 |
| 1 1/4"x5 | | | 4IL5ACME... | .110 | .08 | .09 | - | NVRC075-4LH-157/021 | 1.07 |
| 1 1/2"x4 | 5/8" | 1.06 | 5IL4ACME... | .135 | .09 | .10 | - | NVRC110-5LH-157/023 | 1.27 |
| 1 3/4"x4 | | | 5IL4ACME... | .135 | .09 | .10 | YE5-1P | AVRC125-5LH | 1.53 |

U Type RH inserts can be used for both LH and RH applications.


U Style




| Insert Size | Pitch | Ordering Code | Dimensions inch | | | Anvil | | | |
|-------------|--------|---------------|-----------------|-------|-----|-------|------|------|---------------|
| IC | L inch | TPI | RH+LH | h min | X | Y | RH | LH | Toolholder |
| 1/2"U | .87 | 4 | 4UI4ACME... | .135 | .09 | .43 | YI4U | YE4U | AVR..-4U (LH) |
| | | 3 | 4UI3ACME... | .177 | .11 | .43 | | | |
| 5/8"U | 1.06 | 3 | SUI3ACME... | .177 | .11 | .54 | YI5U | YE5U | AVR..-5U(LH) |


American ACME (con't)

Internal




Defined by: ANSI B1.5:1988
Tolerance class: 3G





V Style



On Edge

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|-----|----------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 4 | 5VIR4ACME... | 5VIL4ACME... | .135 | .04 | .13 | .24 | NVR...-5V (LH) |
| | | 3.5 | 5VIR3.5ACME... | 5VIL3.5ACME... | .152 | .04 | .13 | .24 | |
| | | 3 | 5VIR3ACME... | 5VIL3ACME... | .177 | .04 | .13 | .24 | |
| | | 2 | 5VIR2ACME... | 5VIL2ACME... | .260 | .04 | .20 | .39 | |

On Edge




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | |
|-------------|--------|-------|-------------------|----|-----------------|-----|-----|-----|-----|
| IC | L inch | TPI | RH | LH | h min | T | Ø C | X | Y |
| 1/2" | .87 | 12 | TNEC43EI12ACME... | | .047 | .19 | .20 | .02 | .09 |
| | | 10 | TNEC43EI10ACME... | | .060 | | | | |
| | | 8 | TNEC43EI8ACME... | | .072 | | | | |
| | | 6 | TNEC43EI6ACME... | | .093 | | | | |
| | | 4 | TNEC43EI4ACME... | | .135 | | | | |
| 5/8" | 1.06 | 4 | TNEC54EI4ACME... | | .135 | .25 | .26 | .13 | |
| | | 3 | TNEC54EI3ACME... | | .177 | | | | |
| 3/4" | 1.26 | 2 | TNEC56EI2ACME... | | .260 | .38 | .31 | .19 | |

On Edge inserts are suited to existing toolholders on the market.


American ACME (con't)

MEGALINE


Internal



Defined by: ANSI B1.5:1988
Tolerance class: 3G




Mega Line



Internal





| Insert Size | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | | |
|-------------|-------|---------------|-------------------|-----------------|--------|-----|------------------|-----|-------|
| | | | | IC | L inch | TPI | RH | VKX | h min |
| 5/8" MG | 1.06 | 2 | 5MGIR2ACME... | 42507 | .257 | .19 | .41 | 94 | 44 |
| | | 1 1/2 | 5MGIR1-1/2ACME... | 42504 | .337 | .23 | | 124 | 58 |
| | | 1 1/3 | 5MGIR1-1/3ACME... | 42505 | .376 | .27 | | 139 | 65 |
| | | 1 | 5MGIR1ACME... | 42506 | .495 | .33 | | 184 | 86 |



Internal Toolholders for American ACME

MEGALINE




Internal

| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Spare Parts | |
|-------------------|----------------------|---------|-----------------|-------|---|----------|------|------|------|---------------------|-----------------------------------|---------------------|--------------------|--------------|
| | | | RH | A | L | L1 (max) | D | D1 | F | | inch | Short Chip Material | Long Chip Material | Insert Screw |
| 5MGIR2ACME... | NVRC150-5MG2ACME | 66424 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.50 | (3"-5")-2ACME | (3.5"-5")-2ACME | S5MG | K6T | |
| | NVRC200-5MG2ACME | 66425 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 3.00 | (3.5"-5")-2ACME | (4"-5")-2ACME | | | |
| | NVRC250-5MG2ACME | 66426 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.50 | (4"-5")-2ACME | (4.5"-5")-2ACME | | | |
| 5MGIR1-1/2ACME... | NVRC150-5MG1-1/2ACME | 66434 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.33 | (3"-5")-1 1/2ACME | (3.5"-5")-1 1/2ACME | | | |
| | NVRC200-5MG1-1/2ACME | 66442 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.83 | (3.5"-5")-1 1/2ACME | (4"-5")-1 1/2ACME | | | |
| | NVRC250-5MG1-1/2ACME | 66443 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.33 | (4"-5")-1 1/2ACME | (4.5"-5")-1 1/2ACME | | | |
| 5MGIR1-1/3ACME... | NVRC150-5MG1-1/3ACME | 66444 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.25 | (3"-5")-1 1/3ACME | (3.5"-5")-1 1/3ACME | | | |
| | NVRC200-5MG1-1/3ACME | 66445 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 2.75 | (3.5"-5")-1 1/3ACME | (4.0"-5")-1 1/3ACME | | | |
| | NVRC250-5MG1-1/3ACME | 66446 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.25 | (4.0"-5")-1 1/3ACME | (4.5"-5")-1 1/3ACME | | | |
| 5MGIR1ACME... | NVRC150-5MG1ACME | 66447 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.50 | (3.5"-5")-1ACME | (4"-5")-1ACME | | | |
| | NVRC200-5MG1ACME | 66448 | 1.81 | 10.15 | 5 | 2.0 | 1.99 | 1.83 | 3.00 | (4"-5")-1ACME | (4.5"-5")-1ACME | | | |
| | NVRC250-5MG1ACME | 66449 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.00 | (4"-5")-1ACME | (4.5"-5")-1ACME | | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

American ACME (con't)

MINIPRO



Defined by: ANSI B1.5:1988
Tolerance class: 3G

Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|-----------------|-----------------|-----------------|-----|-----|----------------|-------------------|
| IC mm | L inch | TPI | RH | LH | h min | Y | F | inch | |
| 5.0 | .31 | 16 | 5.0KIR16ACME... | 5.0KIL16ACME... | .036 | .03 | .19 | .31 | .NVR...-5.0K (LH) |
| 6.0 | .39 | 12 | 6.0KIR12ACME... | 6.0KIL12ACME... | .047 | .04 | .20 | .39 | .NVR...-6.0K (LH) |

Mini-3 U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|-----------------|--|-----------------|-----|-----|----------------|--------------------|
| IC mm | L inch | TPI | RH+LH | | h min | Y | F | inch | |
| 5.0U | .31 | 14 | 5.0KUI14ACME... | | .041 | .16 | .23 | .35 | .NVR...-5.0KU (LH) |
| | | 12 | 5.0KUI12ACME... | | .047 | | | | |
| | | 10 | 5.0KUI10ACME... | | .060 | | | | |


Mini-L




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-----|----------------|----------------|-------|-----------------|-----|------|------------------|------------|
| IC mm | TPI | RH | LH | h min | Y | F | inch | | |
| 5.0L | 12 | 5LKIR12ACME... | 5LKIL12ACME... | .047 | .04 | .17 | .31 | .NVR...-5LK (LH) | |

American ACME (2G)


External



Defined by: ANSI B1.5:1988
Tolerance class: 2G



Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-----------------|-----------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 10 | 3ER10ACME-2G... | 3EL10ACME-2G... | 1.52 | .05 | .06 | YE3 | YI3 | AL...-3 (LH) |
| | | 8 | 3ER8ACME-2G... | 3EL8ACME-2G... | 1.84 | .06 | .06 | | | |
| 1/2" | .87 | 5 | 4ER5ACME-2G... | 4EL5ACME-2G... | 2.79 | .08 | .09 | YE4 | YI4 | AL...-4 (LH) |
| 1/2"F | .91 | 5 | 4FER5ACME-2G... | | 2.79 | .08 | .09 | YE4F | | AL...-4F |

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|------------------|--|-----------------|-----|-----|-------|------|---------------|
| IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 4 | 4UE4ACME-2G... | | .135 | .09 | .43 | YE4U | YI4U | AL...-4U (LH) |
| | | 3.5 | 4UE3.5ACME-2G... | | .152 | .10 | .43 | | | |
| | | 3 | 4UE3ACME-2G... | | .177 | .12 | .43 | | | |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|-------------------|-------------------|-----------------|-----|-----|-----|-----------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 4 | 5VER4ACME-2G... | 5VEL4ACME-2G... | .135 | .04 | .13 | .24 | NL...-5V-6 (LH) |
| | | 3.5 | 5VER3.5ACME-2G... | 5VEL3.5ACME-2G... | .152 | .04 | .13 | .24 | |
| | | 3 | 5VER3ACME-2G... | 5VEL3ACME-2G... | .177 | .04 | .13 | .24 | |

American ACME (2G) (con't)

Internal

Defined by: ANSI B1.5:1988
Tolerance class: 2G

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|-----------------|-----------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 10 | 3IR10ACME-2G... | 3IL10ACME-2G... | .060 | .05 | .05 | YI3 | YE3 | AVR..-3 (LH) |
| | | 8 | 3IR8ACME-2G... | 3IL8ACME-2G... | .072 | .06 | .06 | | | |
| 1/2" | .87 | 5 | 4IR5ACME-2G... | 4IL5ACME-2G... | .110 | .08 | .09 | YI4 | YE4 | AVR..-4 (LH) |
| 1/2"F | .91 | 5 | 4FIR5ACME-2G... | | .110 | .08 | .09 | YI4F | | AVRC...-4F |



FLINE

U Style




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|------------------|--|-----------------|-----|-----|-------|------|---------------|
| IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 4 | 4UI4ACME-2G... | | .135 | .09 | .43 | YI4U | YE4U | AVR..-4U (LH) |
| | | 3.5 | 4UI3.5ACME-2G... | | .152 | .10 | .43 | | | |
| | | 3 | 4UI3ACME-2G... | | .177 | .11 | .43 | | | |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|-------------------|-------------------|-----------------|-----|-----|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | T | |
| 5/8"V | 1.06 | 4 | 5VIR4ACME-2G... | 5VIL4ACME-2G... | .135 | .04 | .13 | .24 | NVR..-5V (LH) |
| | | 3.5 | 5VIR3.5ACME-2G... | 5VIL3.5ACME-2G... | .152 | .04 | .13 | .24 | |
| | | 3 | 5VIR3ACME-2G... | 5VIL3ACME-2G... | .177 | .04 | .13 | .24 | |

Stub ACME



Standard

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | | |
|--|---------------|------|----------------|----------------|----------------|----------------|-----------------|-----|-----|--------------|-----|------------|------|----------|
| | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | | | | |
|  | .43 | 16 | 2ER16STACME... | 2EL16STACME... | .024 | .04 | .04 | - | - | AL...-3 (LH) | | | | |
| | | | 3ER16STACME... | 3EL16STACME... | .024 | .04 | .04 | | | | | | | |
| | | 3/8" | .63 | 14 | 3ER14STACME... | 3EL14STACME... | .026 | .04 | .04 | | YE3 | YI3 | | |
| | | | | 12 | 3ER12STACME... | 3EL12STACME... | .030 | .05 | .05 | | | | | |
| | | | | 10 | 3ER10STACME... | 3EL10STACME... | .040 | .05 | .05 | | | | | |
| | | | | 8 | 3ER8STACME... | 3EL8STACME... | .048 | .05 | .05 | | | | | |
|  | .87 | 6 | 4ER6STACME... | 4EL6STACME... | .060 | .07 | .07 | YE4 | YI4 | AL...-4 (LH) | | | | |
| | | 5 | 4ER5STACME... | 4EL5STACME... | .070 | .08 | .09 | | | | | | | |
| | | 4 | 4ER4STACME... | 4EL4STACME... | .085 | .09 | .09 | | | | | | | |
| | | 1/2" | .91 | 6 | 4FER6STACME... | | .060 | | | | .07 | .07 | YE4F | AL...-4F |
| | | | | 5 | 4FER5STACME... | | .070 | | | | .08 | .09 | | |
| | | 5/8" | 1.06 | 4 | 5ER4STACME... | 5EL4STACME... | .085 | | | | .09 | .09 | YE5 | YI5 |
| 3 | 5ER3STACME... | | | 5EL3STACME... | .110 | .11 | .11 | | | | | | | |

U Style

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|---|-------------|-----|---------------|-------|---------------|-----|-----------------|------|---------------|-------|--|------------|
| | L inch | TPI | RH+LH | h min | X | Y | RH | LH | | | | |
|  | .87 | 4 | 4UE4STACME... | .085 | .10 | .43 | YE4U | YI4U | AL...-4U (LH) | | | |
| | | 3 | 4UE3STACME... | .110 | .13 | .43 | | | | | | |

V Style

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Toolholder |
|---|-------------|-----|----------------|----------------|---------------|-----|-----------------|-----|-----------------|-----------------|
| | L inch | TPI | RH | LH | h min | X | Y | T | | |
|  | 1.06 | 4 | 5VER4STACME... | 5VEL4STACME... | .085 | .04 | .13 | .24 | NL...-5V-6 (LH) | |
| | | 3 | 5VER3STACME... | 5VEL3STACME... | .110 | .04 | .13 | .24 | | |
| | | 2 | 5VER2STACME... | 5VEL2STACME... | .160 | .04 | .17 | .31 | | NL...-5V-8 (LH) |

On Edge

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | |
|---|-------------|-----|---------------------|-------|---------------|-----|-----------------|-----|--|--|
| | L inch | TPI | RH | h min | T | ØC | X | Y | | |
|  | .63 | 12 | TNEC32EI12STACME... | .030 | .13 | .15 | .04 | .06 | | |
| | | 10 | TNEC32EI10STACME... | .040 | | | | | | |
| | | 8 | TNEC32EI8STACME... | .048 | | | | | | |
| 1/2" | .87 | 12 | TNEC43EI12STACME... | .030 | .19 | .20 | .02 | .09 | | |
| | | 10 | TNEC43EI10STACME... | .040 | | | | | | |
| | | 8 | TNEC43EI8STACME... | .048 | | | | | | |
| | | 6 | TNEC43EI6STACME... | .060 | | | | | | |
| 5/8" | 1.06 | 4 | TNEC54EI4STACME... | .085 | .25 | .26 | .13 | | | |

On Edge inserts are suited to existing toolholders on the market.

Stub ACME (con't)

MEGA/LINE

External


Defined by: ANSI B1.8:1988
Tolerance class: 2G

Mega Line

External



| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|-----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | TPI | RH | VKX | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 1 | 5MGER1STACME... | 42513 | .310 | .37 | .45 | 113 | 53 |



External Toolholders for Stub ACME

MEGA/LINE


External

Spare Parts

| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.-Max.) | | |
|-----------------|------------------|---------|-----------------|------|-----|-----------------------------------|--------------|----------|
| | RH | | H=B=H1 | F | L1 | L2 | Insert Screw | Torx Key |
| 5MGER1STACME... | NL100-5MG1STACME | 66403 | 1.00 | .650 | 6.1 | | S5MG | K6T |
| | NL125-5MG1STACME | 66404 | 1.25 | .930 | 6.9 | .87 | | |
| | NL150-5MG1STACME | 66405 | 1.50 | 1.24 | 8.1 | | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Stub ACME (con't)



Standard

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--------|-------------|-----|----------------|----------------|---------------|-----|-----------------|------|-----|--------------|--|------------|
| | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | | |
| 1/4" | .43 | 16 | 2IR16STACME... | 2IL16STACME... | .024 | .04 | .04 | - | - | NVR..-2 (LH) | | |
| | | 16 | 3IR16STACME... | 3IL16STACME... | .024 | .04 | .04 | | | | | |
| | | 14 | 3IR14STACME... | 3IL14STACME... | .026 | .04 | .04 | | | | | |
| 3/8" | .63 | 12 | 3IR12STACME... | 3IL12STACME... | .030 | .04 | .05 | YI3 | YE3 | AVR..-3 (LH) | | |
| | | 10 | 3IR10STACME... | 3IL10STACME... | .040 | .05 | .05 | | | | | |
| | | 8 | 3IR8STACME... | 3IL8STACME... | .048 | .06 | .06 | | | | | |
| | | 6 | 3IR6STACME... | 3IL6STACME... | .060 | .07 | .07 | | | | | |
| | | 6 | 4IR6STACME... | 4IL6STACME... | .060 | .07 | .07 | | | | | |
| 1/2" | .87 | 5 | 4IR5STACME... | 4IL5STACME... | .070 | .08 | .09 | YI4 | YE4 | AVR..-4 (LH) | | |
| | | 4 | 4IR4STACME... | 4IL4STACME... | .085 | .09 | .09 | | | | | |
| | | 6 | 4FIR6STACME... | | .060 | .07 | .07 | | | | | |
| 1/2" F | .91 | 5 | 4FIR5STACME... | | .070 | .08 | .09 | YI4F | | AVRC...-4F | | |
| | | 4 | 4FIR4STACME... | | .085 | .09 | .09 | | | | | |
| 5/8" | 1.06 | 4 | 5IR4STACME... | 5IL4STACME... | .085 | .09 | .09 | YI5 | YE5 | AVR..-5 (LH) | | |
| | | 3 | 5IR3STACME... | 5IL3STACME... | .110 | .11 | .11 | | | | | |

U Style

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|--------|-------------|-----|---------------|--|---------------|-----|-----------------|------|------|---------------|--|------------|
| | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | | | |
| 1/2" U | .87 | 4 | 4UI4STACME... | | .085 | .10 | .43 | YI4U | YE4U | AVR..-4U (LH) | | |
| | | 3 | 4UI3STACME... | | .110 | .13 | .43 | | | | | |

V Style

| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | Toolholder |
|--------|-------------|-----|----------------|----------------|---------------|-----|-----------------|-----|---------------|------------|
| | L inch | TPI | RH | LH | h min | X | Y | T | | |
| 5/8" V | 1.06 | 4 | 5VIR4STACME... | 5VIL4STACME... | .085 | .04 | .13 | .24 | NVR..-5V (LH) | |
| | | 3 | 5VIR3STACME... | 5VIL3STACME... | .110 | .04 | .13 | .24 | | |
| | | 2 | 5VIR2STACME... | 5VIL2STACME... | .160 | .04 | .17 | .31 | | |

On Edge


| IC | Insert Size | | Pitch | | Ordering Code | | Dimensions inch | | | |
|------|-------------|-----|---------------------|--|---------------|-----|-----------------|-----|-----|--|
| | L inch | TPI | RH | | h min | T | Ø C | X | Y | |
| 3/8" | .63 | 12 | TNEC32EI12STACME... | | .030 | .13 | .15 | .04 | .06 | |
| | | 10 | TNEC32EI10STACME... | | .040 | | | | | |
| | | 8 | TNEC32EI8STACME... | | .048 | | | | | |
| 1/2" | .87 | 12 | TNEC43EI12STACME... | | .030 | .19 | .20 | .02 | .09 | |
| | | 10 | TNEC43EI10STACME... | | .040 | | | | | |
| | | 8 | TNEC43EI8STACME... | | .048 | | | | | |
| | | 6 | TNEC43EI6STACME... | | .060 | | | | | |
| | | 4 | TNEC43EI4STACME... | | .085 | | | | | |
| 5/8" | 1.06 | 4 | TNEC54EI4STACME... | | .085 | .25 | .26 | | .13 | |

On Edge inserts are suited to existing toolholders on the market.


Stub ACME (con't)

MEGA/LINE


Internal



Defined by: ANSI B1.8:1988
Tolerance class: 2G



Mega Line






Internal



| IC | L inch | Pitch TPI | Ordering Code RH | EDP No. VKX | Dimensions inch | | | Number of Passes | |
|---------|--------|--------------|---------------------|----------------|-----------------|-----|-----|---|---|
| | | | | | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 1 | 5MGIR1STACME... | 42512 | .308 | .37 | .41 | 113 | 53 |

Internal Toolholders for Stub ACME


MEGA/LINE

Internal

| Insert | Ordering Code | EDP No. | Dimensions | | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Spare Parts | |
|-----------------|--------------------|---------|------------|-------|----------|-----|------|------|------|-------------------|-----------------------------------|--------------------|--------------|----------|
| | | | A | L | L1 (max) | D | D1 | F | inch | | Short Chip Material | Long Chip Material | Insert Screw | Torx Key |
| 5MGIR1STACME... | NVRC150-5MG1STACME | 66406 | 1.42 | 9.15 | 4 | 1.5 | 1.49 | 1.63 | 2.9 | (3.5"-5")-1STACME | (3.5"-5")-1STACME | S5MG | K6T | |
| | NVRC200-5MG1STACME | 66407 | 1.81 | 10.15 | 5 | 2 | 1.99 | 1.83 | 2.9 | (3.5"-5")-1STACME | (4.0"-5")-1STACME | | | |
| | NVRC250-5MG1STACME | 66408 | 2.28 | 11.10 | 6 | 2.5 | 2.49 | 2.03 | 3.4 | (4.0"-5")-1STACME | (4.5"-5")-1STACME | | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Stub ACME (con't)



Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|-------------------|-------------------|-----------------|-----|-----|----------------|-------------------|
| IC mm | L inch | TPI | RH | LH | h min | Y | F | inch | |
| 5.0 | .31 | 16 | 5.0KIR16STACME... | 5.0KIL16STACME... | .024 | .03 | .19 | .31 | .NVR...-5.0K (LH) |
| 6.0 | .39 | 12 | 6.0KIR12STACME... | 6.0KIL12STACME... | .030 | .05 | .20 | .39 | .NVR...-6.0K (LH) |

Mini-3 U Style



| Insert Size | | Pitch | Ordering Code | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|-------------------|-----------------|-----|-----|----------------|------------|
| IC mm | L inch | TPI | RH+LH | h min | Y | F | inch | |
| 5.0U | .31 | 14 | 5.0KUI14STACME... | .026 | | .23 | .35 | |
| | | 12 | 5.0KUI12STACME... | .030 | .16 | .22 | | |
| | | 10 | 5.0KUI10STACME... | .040 | | .22 | | |


Mini-L




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-----|-------|------------------|------------------|-----------------|-----|-----|----------------|------------------|
| IC mm | TPI | | RH | LH | h min | Y | F | inch | |
| 5.0L | 12 | | 5LKIR12STACME... | 5LKIL12STACME... | .030 | .05 | .17 | .31 | .NVR...-5LK (LH) |

UNJ - UNJC, UNJF, UNJEF, UNJS

External



Defined by: MIL-S-8879C
Tolerance class: 3A/3B



Standard


Standard




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|-------------|------------|---------------|-------------|-----------------|-------------|------|-------|----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 48 | 2ER48UNJ... | 2EL48UNJ... | .012 | .02 | .02 | - | - | NL...-2 (LH) |
| | | 44 | 2ER44UNJ... | 2EL44UNJ... | .013 | .02 | .02 | | | |
| | | 40 | 2ER40UNJ... | 2EL40UNJ... | .015 | .02 | .02 | | | |
| | | 36 | 2ER36UNJ... | 2EL36UNJ... | .016 | .02 | .02 | | | |
| | | 32 | 2ER32UNJ... | 2EL32UNJ... | .018 | .02 | .03 | | | |
| | | 28 | 2ER28UNJ... | 2EL28UNJ... | .020 | .03 | .03 | | | |
| | | 24 | 2ER24UNJ... | 2EL24UNJ... | .024 | .03 | .03 | | | |
| | | 20 | 2ER20UNJ... | 2EL20UNJ... | .029 | .03 | .04 | | | |
| | | 18 | 2ER18UNJ... | 2EL18UNJ... | .032 | .03 | .04 | | | |
| | | 16 | 2ER16UNJ... | 2EL16UNJ... | .036 | .04 | .04 | | | |
| | | 14 | 2ER14UNJ... | 2EL14UNJ... | .041 | .04 | .05 | | | |
| | | 3/8" | .63 | 48 | 3ER48UNJ... | 3EL48UNJ... | .012 | | | |
| 44 | 3ER44UNJ... | | | 3EL44UNJ... | .013 | .02 | .02 | | | |
| 40 | 3ER40UNJ... | | | 3EL40UNJ... | .015 | .02 | .02 | | | |
| 36 | 3ER36UNJ... | | | 3EL36UNJ... | .016 | .02 | .02 | | | |
| 32 | 3ER32UNJ... | | | 3EL32UNJ... | .018 | .02 | .03 | | | |
| 28 | 3ER28UNJ... | | | 3EL28UNJ... | .020 | .03 | .03 | | | |
| 24 | 3ER24UNJ... | | | 3EL24UNJ... | .024 | .03 | .03 | | | |
| 20 | 3ER20UNJ... | | | 3EL20UNJ... | .029 | .03 | .04 | | | |
| 18 | 3ER18UNJ... | | | 3EL18UNJ... | .032 | .03 | .04 | | | |
| 16 | 3ER16UNJ... | | | 3EL16UNJ... | .036 | .04 | .04 | | | |
| 14 | 3ER14UNJ... | | | 3EL14UNJ... | .041 | .04 | .05 | | | |
| 13 | 3ER13UNJ... | | | 3EL13UNJ... | .044 | .04 | .05 | | | |
| 12 | 3ER12UNJ... | | | 3EL12UNJ... | .048 | .04 | .05 | | | |
| 11 | 3ER11UNJ... | | | 3EL11UNJ... | .052 | .05 | .06 | | | |
| 10 | 3ER10UNJ... | | | 3EL10UNJ... | .058 | .05 | .06 | | | |
| 9 | 3ER9UNJ... | | | 3EL9UNJ... | .064 | .05 | .07 | | | |
| 8 | 3ER8UNJ... | 3EL8UNJ... | .072 | .05 | .06 | | | | | |

UNJ - UNJC, UNJF, UNJEF, UNJS (con't)


External




Defined by: MIL-S-8879C
Tolerance class: 3A/3B



SCB
Sintered
Chipbreaker



Standard



U Style

Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|---|-------------|-------|---------------|--------------|-----------------|------|-----|-------|-----|------------|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  | 3/8" SCB | .63 | 36 | 3JER36UNJ... | | .016 | .05 | .02 | YE3 | - | AL..-3 |
| | | | 32 | 3JER32UNJ... | | .018 | .05 | .02 | | | |
| | | | 28 | 3JER28UNJ... | | .020 | .03 | .03 | | | |
| | | | 24 | 3JER24UNJ... | | .024 | .03 | .03 | | | |
| | | | 20 | 3JER20UNJ... | | .029 | .03 | .03 | | | |
| | | | 18 | 3JER18UNJ... | | .032 | .03 | .03 | | | |
| | | | 16 | 3JER16UNJ... | | .036 | .03 | .03 | | | |
| | | | 14 | 3JER14UNJ... | | .041 | .05 | .06 | | | |
| | | | 12 | 3JER12UNJ... | | .048 | .05 | .06 | | | |
| | | | 10 | 3JER10UNJ... | | .058 | .05 | .06 | | | |
|  | 1/2" | .87 | 7 | 4ER7UNJ... | 4EL7UNJ... | .082 | .07 | .09 | YE4 | YI4 | AL..-4 (LH) |
| | | | 6 | 4ER6UNJ... | 4EL6UNJ... | .096 | .07 | .09 | | | |
| | | | 5 | 4ER5UNJ... | 4EL5UNJ... | .115 | .07 | .10 | | | |
| | 5/8" | 1.06 | 4.5 | 5ER4.5UNJ... | 5EL4.5UNJ... | .128 | .08 | .11 | YE5 | YI5 | AL..-5 (LH) |
| | | | 4 | 5ER4UNJ... | 5EL4UNJ... | .144 | .09 | .12 | | | |


U Style




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--|-----------------|-----|-----|-------|------|--------------|
| IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 4.5 | 4UE4.5UNJ... | | .128 | .08 | .43 | YE4U | YI4U | AL..-4U (LH) |
| | | 4 | 4UE4UNJ... | | .144 | .09 | .43 | | | |

UNJ - UNJC, UNJF, UNJEF, UNJS (con't)


Internal



Defined by: MIL-S-8879C
Tolerance class: 3A/3B



Standard



SCB
Sintered
Chipbreaker

Standard




SCB


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|-------------|-----------------|-----|-----|-------|----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 48 | 2IR48UNJ... | 2IL48UNJ... | .011 | .02 | .02 | - | - | NVR..-2 (LH) |
| | | 44 | 2IR44UNJ... | 2IL44UNJ... | .012 | .02 | .02 | | | |
| | | 40 | 2IR40UNJ... | 2IL40UNJ... | .013 | .02 | .02 | | | |
| | | 36 | 2IR36UNJ... | 2IL36UNJ... | .015 | .02 | .02 | | | |
| | | 32 | 2IR32UNJ... | 2IL32UNJ... | .017 | .02 | .03 | | | |
| | | 28 | 2IR28UNJ... | 2IL28UNJ... | .019 | .03 | .03 | | | |
| | | 24 | 2IR24UNJ... | 2IL24UNJ... | .022 | .03 | .03 | | | |
| | | 20 | 2IR20UNJ... | 2IL20UNJ... | .026 | .03 | .04 | | | |
| | | 18 | 2IR18UNJ... | 2IL18UNJ... | .029 | .03 | .04 | | | |
| | | 16 | 2IR16UNJ... | 2IL16UNJ... | .033 | .04 | .04 | | | |
| 1/4" SCB | .43 | 36 | 2JIR36UNJ... | | .015 | .04 | .02 | - | - | NVR..-2 |
| | | 32 | 2JIR32UNJ... | | .017 | .05 | .02 | | | |
| | | 28 | 2JIR28UNJ... | | .019 | .02 | .03 | | | |
| | | 24 | 2JIR24UNJ... | | .022 | .02 | .03 | | | |
| | | 20 | 2JIR20UNJ... | | .026 | .02 | .03 | | | |
| | | 18 | 2JIR18UNJ... | | .029 | .02 | .03 | | | |
| | | 16 | 2JIR16UNJ... | | .033 | .02 | .03 | | | |
| | | 14 | 2JIR14UNJ... | | .037 | .02 | .03 | | | |

UNJ - UNJC, UNJF, UNJEF, UNJS (con't)


Internal



Defined by: MIL-S-8879C
Tolerance class: 3A/3B



Standard



SCB
Sintered
Chipbreaker

Standard

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder | |
|---|-------------|-------------|---------------|--------------|-----------------|------|-----|-------|-----|--------------|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | | |
|  | 3/8" | .63 | 48 | 3IR48UNJ... | 3IL48UNJ... | .011 | .02 | .02 | Y13 | YE3 | AVR..-3 (LH) |
| | | | 44 | 3IR44UNJ... | 3IL44UNJ... | .012 | .02 | .02 | | | |
| | | | 40 | 3IR40UNJ... | 3IL40UNJ... | .013 | .02 | .02 | | | |
| | | | 36 | 3IR36UNJ... | 3IL36UNJ... | .015 | .02 | .02 | | | |
| | | | 32 | 3IR32UNJ... | 3IL32UNJ... | .017 | .02 | .03 | | | |
| | | | 28 | 3IR28UNJ... | 3IL28UNJ... | .019 | .03 | .03 | | | |
| | | | 24 | 3IR24UNJ... | 3IL24UNJ... | .022 | .03 | .03 | | | |
| | | | 20 | 3IR20UNJ... | 3IL20UNJ... | .026 | .03 | .04 | | | |
| | | | 18 | 3IR18UNJ... | 3IL18UNJ... | .029 | .03 | .04 | | | |
| | | | 16 | 3IR16UNJ... | 3IL16UNJ... | .033 | .04 | .04 | | | |
| | | | 14 | 3IR14UNJ... | 3IL14UNJ... | .037 | .04 | .05 | | | |
| | | | 13 | 3IR13UNJ... | 3IL13UNJ... | .040 | .04 | .05 | | | |
| | | | 12 | 3IR12UNJ... | 3IL12UNJ... | .044 | .04 | .05 | | | |
| | | | 11 | 3IR11UNJ... | 3IL11UNJ... | .048 | .05 | .06 | | | |
| 10 | 3IR10UNJ... | 3IL10UNJ... | .052 | .05 | .06 | | | | | | |
| 9 | 3IR9UNJ... | 3IL9UNJ... | .058 | .05 | .07 | | | | | | |
| 8 | 3IR8UNJ... | 3IL8UNJ... | .065 | .05 | .06 | | | | | | |
|  | 3/8" SCB | .63 | 28 | 3JIR28UNJ... | | .019 | .02 | .03 | Y13 | - | AVR..-3 |
| | | | 24 | 3JIR24UNJ... | | .022 | .02 | .03 | | | |
| | | | 20 | 3JIR20UNJ... | | .026 | .02 | .03 | | | |
| | | | 18 | 3JIR18UNJ... | | .029 | .02 | .03 | | | |
| | | | 16 | 3JIR16UNJ... | | .033 | .02 | .03 | | | |
| | | | 14 | 3JIR14UNJ... | | .037 | .04 | .06 | | | |
| | | | 12 | 3JIR12UNJ... | | .044 | .04 | .06 | | | |
| | | | 10 | 3JIR10UNJ... | | .052 | .04 | .06 | | | |
| 8 | 3JIR8UNJ... | | .065 | .04 | .06 | | | | | | |
|  | 1/2" | .87 | 7 | 4IR7UNJ... | 4IL7UNJ... | .075 | .07 | .09 | Y14 | YE4 | AVR..-4 (LH) |
| | | | 6 | 4IR6UNJ... | 4IL6UNJ... | .087 | .07 | .09 | | | |
| | | | 5 | 4IR5UNJ... | 4IL5UNJ... | .105 | .07 | .10 | | | |
| 5/8" | 1.06 | 4.5 | 5IR4.5UNJ... | 5IL4.5UNJ... | .116 | .08 | .11 | Y15 | YE5 | AVR..-5 (LH) | |
| | | 4 | 5IR4UNJ... | 5IL4UNJ... | .131 | .09 | .09 | | | | |

UNJ - UNJC, UNJF, UNJEF, UNJS (con't)

Internal

Defined by: MIL-S-8879C
Tolerance class: 3A/3B

U Style

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--|-----------------|-----|-----|-------|------|----------------|
| IC | L inch | TPI | RH+LH | | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 4.5 | 4UI4.5UNJ... | | .116 | .08 | .43 | Y14U | YE4U | AVR...-4U (LH) |
| | | 4 | 4UI4UNJ... | | .131 | .09 | .43 | | | |

UNJ - UNJC, UNJF, UNJEF, UNJS

MINIPRO

Internal

Defined by: MIL-S-8879C
Tolerance class: 3A/3B

Mini-3 Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|----------------|-------------------|------------|
| IC mm | L inch | TPI | RH | LH | h min | Y | F | inch | | |
| 6.0 | .39 | 20 | 6.0KIR20UNJ... | 6.0KIL20UNJ... | .026 | .04 | .19 | .39 | .NVR...-6.0K (LH) | |


Mini-L




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | | Toolholder |
|-------------|-----|---------------|---------------|-------|-----------------|-----|------|------------------|--|------------|
| IC mm | TPI | RH | LH | h min | Y | F | inch | | | |
| 5.0L | 32 | 5LKIR32UNJ... | 5LKIL32UNJ... | .017 | .02 | .15 | .30 | .NVR...-5LK (LH) | | |
| | 28 | 5LKIR28UNJ... | 5LKIL28UNJ... | .019 | .02 | .16 | .30 | | | |
| | 24 | 5LKIR24UNJ... | 5LKIL24UNJ... | .022 | .03 | .17 | .30 | | | |
| | 20 | 5LKIR20UNJ... | 5LKIL20UNJ... | .026 | .04 | .17 | .30 | | | |
| | 18 | 5LKIR18UNJ... | 5LKIL18UNJ... | .029 | .04 | .17 | .31 | | | |
| | 16 | 5LKIR16UNJ... | 5LKIL16UNJ... | .033 | .04 | .17 | .31 | | | |
| | 14 | 5LKIR14UNJ... | 5LKIL14UNJ... | .037 | .04 | .18 | .31 | | | |

MJ


External



Defined by: ISO 5855
Tolerance class: 4h/6h-4H/5H



Standard



Slim Throat

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 1.0 | 2ER1.0MJ... | 2EL1.0MJ... | .023 | .03 | .03 | - | - | NL...-2 (LH) |
| | | 1.25 | 2ER1.25MJ... | 2EL1.25MJ... | .028 | .03 | .04 | | | |
| | | 1.5 | 2ER1.5MJ... | 2EL1.5MJ... | .034 | .03 | .04 | | | |
| 3/8" | .63 | 0.7 | 3ER0.7MJ... | 3EL0.7MJ... | .016 | .02 | .02 | YE3 | YI3 | AL...-3 (LH) |
| | | 0.8 | 3ER0.8MJ... | 3EL0.8MJ... | .018 | .03 | .03 | | | |
| | | 1.0 | 3ER1.0MJ... | 3EL1.0MJ... | .023 | .03 | .03 | | | |
| | | 1.25 | 3ER1.25MJ... | 3EL1.25MJ... | .028 | .03 | .04 | | | |
| | | 1.5 | 3ER1.5MJ... | 3EL1.5MJ... | .034 | .03 | .04 | | | |
| | | 2.0 | 3ER2.0MJ... | 3EL2.0MJ... | .045 | .04 | .05 | | | |
| | | 2.5 | 3ER2.5MJ... | 3EL2.5MJ... | .059 | .04 | .06 | | | |
| | | 3.0 | 3ER3.0MJ... | 3EL3.0MJ... | .068 | .05 | .06 | | | |


Slim Throat




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | | Toolholder |
|-------------|--------|-------|---------------|---------------|-----------------|-----|-----|-----|---------------|
| IC | L inch | mm | RH | LH | h min | X | Y | T | |
| 1/4"V | .43 | 0.7 | 2VER0.7MJ... | 2VEL0.7MJ... | .016 | .03 | .10 | .13 | NL...-2V (LH) |
| | | 0.8 | 2VER0.8MJ... | 2VEL0.8MJ... | .017 | .03 | .10 | .13 | |
| | | 0.9 | 2VER0.9MJ... | 2VEL0.9MJ... | .021 | .03 | .10 | .13 | |
| | | 1.0 | 2VER1.0MJ... | 2VEL1.0MJ... | .023 | .03 | .10 | .13 | |
| | | 1.25 | 2VER1.25MJ... | 2VEL1.25MJ... | .028 | .03 | .09 | .13 | |
| | | 1.5 | 2VER1.5MJ... | 2VEL1.5MJ... | .034 | .03 | .09 | .13 | |

MJ (con't)


Internal



Defined by: ISO 5855
Tolerance class: 4h/6h-4H/5H



Standard



Mini-L

Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|-------------|-------------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC mm | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 1.0 | 2IR1.0MJ... | 2IL1.0MJ... | .019 | .02 | .03 | - | - | NVR..-2 (LH) |
| | | 1.25 | 2IR1.25MJ... | 2IL1.25MJ... | .024 | .03 | .04 | | | |
| | | 1.5 | 2IR1.5MJ... | 2IL1.5MJ... | .029 | .03 | .04 | | | |
| | | 2.0 | 2IR2.0MJ... | 2IL2.0MJ... | .038 | .03 | .04 | | | |
| 3/8" | .63 | 0.75 | 3IR0.75MJ... | 3IL0.75MJ... | .015 | .02 | .02 | Y13 | YE3 | AVR.-3 (LH) |
| | | 0.8 | 3IR0.8MJ... | 3IL0.8MJ... | .017 | .03 | .03 | | | |
| | | 1.0 | 3IR1.0MJ... | 3IL1.0MJ... | .019 | .02 | .03 | | | |
| | | 1.25 | 3IR1.25MJ... | 3IL1.25MJ... | .024 | .03 | .04 | | | |
| | | 1.5 | 3IR1.5MJ... | 3IL1.5MJ... | .029 | .03 | .04 | | | |
| | | 2.0 | 3IR2.0MJ... | 3IL2.0MJ... | .038 | .03 | .05 | | | |
| | | 2.5 | 3IR2.5MJ... | 3IL2.5MJ... | .048 | .04 | .06 | | | |
| 3.0 | 3IR3.0MJ... | 3IL3.0MJ... | .057 | .05 | .06 | | | | | |

Mini - L




MINIPRO


| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--|-------|----------------|----------------|-----------------|-----|-----|----------------|------------------|
| IC mm | | mm | RH | LH | h min | Y | F | inch | |
| 5.0L | | 1.0 | 5LKIR1.0MJ... | 5LKIL1.0MJ... | .019 | .03 | .16 | .30 | .NVR...-5LK (LH) |
| | | 1.25 | 5LKIR1.25MJ... | 5LKIL1.25MJ... | .024 | .04 | .17 | .30 | |
| | | 1.5 | 5LKIR1.50MJ... | 5LKIL1.50MJ... | .029 | .04 | .17 | .30 | |

American Buttress


External



Defined by: ANSI B1.9.1973
Tolerance class: Class 2



Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|-------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 20 | 2ER20ABUT... | 2EL20ABUT... | .033 | .04 | .06 | - | - | NL..-2 (LH) |
| | | 16 | 2ER16ABUT... | 2EL16ABUT... | .041 | .05 | .07 | - | - | NL..-2 (LH) |
| 3/8" | .63 | 20 | 3ER20ABUT... | 3EL20ABUT... | .033 | .04 | .06 | YE3 | YI3 | AL..-3 (LH) |
| | | 16 | 3ER16ABUT... | 3EL16ABUT... | .041 | .05 | .07 | | | |
| | | 12 | 3ER12ABUT... | 3EL12ABUT... | .055 | .06 | .08 | | | |
| 1/2" | .87 | 10 | 3ER10ABUT... | 3EL10ABUT... | .066 | .06 | .09 | YE4 | YI4 | AL..-4 (LH) |
| | | 8 | 4ER8ABUT... | 4EL8ABUT... | .083 | .08 | .13 | | | |
| 1/2"F | .91 | 8 | 4FER8ABUT... | 4EL6ABUT... | .083 | .08 | .13 | YE4F | | AL...-4F |
| | | 6 | 4FER6ABUT... | | .110 | .09 | .14 | | | |

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-----------|-----------|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 4 | 4UER4ABUT... | 4UEL4ABUT... | .166 | .09 | .39 | YE4U-BUT4 | YI4U-BUT4 | AL..-4U (LH) |
| 5/8"U | 1.06 | 3 | 5UER3ABUT... | 5UEL3ABUT... | .221 | .12 | .48 | YE5U-BUT3 | YI5U-BUT3 | AL..-5U (LH) |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | T | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|-----|---------------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | | |
| 5/8"V | 1.06 | 4 | 5VER4ABUT... | 5VEL4ABUT... | .166 | .02 | .07 | .24 | NL..-5V-6 (LH) |
| | | 3 | 5VER3ABUT... | 5VEL3ABUT... | .221 | .02 | .09 | .31 | NL..-5V-8 (LH) |
| | | 2.5 | 5VER2.5ABUT... | 5VEL2.5ABUT... | .265 | .02 | .11 | .39 | NL..-5V-10ABUT (LH) |

American Buttress (con't)

MEGA/LINE

External


Defined by: ANSI B1.9.1973
Tolerance class: Class 2

Mega Line



External



| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|-----------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | TPI | RH | VKX | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 2 | 5MGER2ABUT... | 42503 | .332 | .06 | .61 | 120 | 56 |
| | | 1.5 | 5MGER1.5ABUT... | 42502 | .442 | .07 | | 160 | 75 |



External Toolholders for American Buttress **MEGA**/LINE




External

| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.-Max.) | Spare Parts | | |
|-----------------|------------------|---------|-----------------|-----|-----|-----------------------------------|-------------------|--------------|----------|
| | | | H=B=H1 | F | L1 | | L2 | Insert Screw | Torx Key |
| 5MGER2ABUT... | NL100-5MG2ABUT | 66479 | 1.00 | .37 | 5.9 | 1.22 | (7"-24")-2ABUT | S5MG | K6T |
| | NL125-5MG2ABUT | 66480 | 1.25 | .65 | 6.7 | | | | |
| | NL150-5MG2ABUT | 66481 | 1.50 | .96 | 7.9 | | | | |
| 5MGER1.5ABUT... | NL100-5MG1.5ABUT | 66482 | 1.00 | .37 | 5.9 | 1.22 | (11"-24")-1.5ABUT | | |
| | NL125-5MG1.5ABUT | 66483 | 1.25 | .65 | 6.7 | | | | |
| | NL150-5MG1.5ABUT | 66484 | 1.50 | .96 | 7.9 | | | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

American Buttress (con't)



Standard



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 20 | 2IR20ABUT... | 2IL20ABUT... | .033 | .04 | .06 | - | - | NVR...-2 (LH) |
| | | 16 | 2IR16ABUT... | 2IL16ABUT... | .041 | .05 | .07 | - | - | |
| 3/8" | .63 | 20 | 3IR20ABUT... | 3IL20ABUT... | .033 | .04 | .06 | YI3 | YE3 | AVR...-3 (LH) |
| | | 16 | 3IR16ABUT... | 3IL16ABUT... | .041 | .05 | .07 | | | |
| | | 12 | 3IR12ABUT... | 3IL12ABUT... | .055 | .06 | .08 | | | |
| 1/2" | .87 | 10 | 3IR10ABUT... | 3IL10ABUT... | .066 | .06 | .09 | YI4 | YE4 | AVR...-4 (LH) |
| | | 8 | 4IR8ABUT... | 4IL8ABUT... | .083 | .08 | .13 | | | |
| 1/2" F | .91 | 6 | 4IR6ABUT... | 4IL6ABUT... | .110 | .09 | .14 | YI4F | | AVRC...-4F |
| | | 8 | 4FIR8ABUT... | | .083 | .08 | .13 | | | |
| | | 6 | 4FIR6ABUT... | | .110 | .09 | .14 | | | |

U Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|---------|---------|----------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 1/2" U | .87 | 4 | 4UIR4ABUT... | 4UIL4ABUT... | .166 | .09 | .39 | YI4U-4B | YE4U-4B | AVR...-4U (LH) |
| 5/8" U | 1.06 | 3 | 5UIR3ABUT... | 5UIL3ABUT... | .221 | .12 | .48 | YI5U-3B | YE5U-3B | AVR...-5U (LH) |

V Style



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Toolholder | |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|------------|----------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | | T |
| 5/8" V | 1.06 | 4 | 5VIR4ABUT... | 5VIL4ABUT... | .166 | .02 | .07 | .24 | NVR...-5V (LH) |
| | | 3 | 5VIR3ABUT... | 5VIL3ABUT... | .221 | .02 | .09 | .31 | |
| | | 2.5 | 5VIR2.5ABUT... | 5VIL2.5ABUT... | .265 | .02 | .11 | .39 | |

American Buttress (con't)


MEGA/LINE

Internal

Defined by: ANSI B1.9.1973
Tolerance class: Class 2

Mega Line

Internal



| IC | L inch | TPI | RH | VKX | h min | X | Y | Number of Passes | |
|---------|--------|-----|--------------|-------|-------|-----|-----|---|---|
| | | | | | | | | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 2 | 5MGIR2ABUT | 42501 | .352 | .06 | .63 | 128 | 60 |
| | | 1.5 | 5MGIR1.5ABUT | 42500 | .469 | .07 | | 170 | 79 |


Internal Toolholders for American Buttress

| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Spare Parts | |
|-----------------|--------------------|---------|-----------------|-------|----------|-----|------|------|----------------|-----------------------------------|---------------------|--------------------|--------------|
| | | | A | L | L1 (max) | D | D1 | F | | inch | Short Chip Material | Long Chip Material | Insert Screw |
| 5MGIR2ABUT... | NVRC150-5MG2ABUT | 66485 | 1.42 | 9.05 | 4 | 1.5 | 1.49 | 1.38 | 6.4 | (7"-16")-2ABUT | (7"-16")-2ABUT | S5MG | K6T |
| | NVRC200-5MG2ABUT | 66486 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.56 | | | | | |
| | NVRC250-5MG2ABUT | 66487 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 1.81 | | | | | |
| 5MGIR1.5ABUT... | NVRC150-5MG1.5ABUT | 66488 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.38 | 10.2 | (11"-22")-1.5ABUT | (11"-22")-1.5ABUT | S5MG | K6T |
| | NVRC200-5MG1.5ABUT | 66489 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.56 | | | | | |
| | NVRC250-5MG1.5ABUT | 66490 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 1.81 | | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

British Buttress

External



Defined by: B.S. 1657: 1950
Tolerance class: Medium Class



Standard




Standard




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 16 | 3ER16BBUT... | 3EL16BBUT... | .031 | .04 | .06 | YE3 | YI3 | AL...-3 (LH) |
| | | 12 | 3ER12BBUT... | 3EL12BBUT... | .042 | .06 | .08 | | | |
| | | 10 | 3ER10BBUT... | 3EL10BBUT... | .050 | .06 | .09 | | | |
| | | 8 | 3ER8BBUT... | 3EL8BBUT... | .063 | .06 | .10 | | | |
| 1/2" | .87 | 8 | 4ER8BBUT... | 4EL8BBUT... | .063 | .06 | .10 | YE4 | YI4 | AL...-4 (LH) |

British Buttress

Internal



Defined by: B.S. 1657: 1950
Tolerance class: Medium Class



Standard




Standard






| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|---------------|--------------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 16 | 3IR16BBUT... | 3IL16BBUT... | .031 | .04 | .06 | YI3 | YE3 | AVR...-3 (LH) |
| | | 12 | 3IR12BBUT... | 3IL12BBUT... | .042 | .06 | .08 | | | |
| | | 10 | 3IR10BBUT... | 3IL10BBUT... | .050 | .06 | .09 | | | |
| | | 8 | 3IR8BBUT... | 3IL8BBUT... | .063 | .06 | .10 | | | |
| 1/2" | .87 | 8 | 4IR8BBUT... | 4IL8BBUT... | .063 | .06 | .10 | YI4 | YE4 | AVR...-4 (LH) |

Metric Buttress (Sägengewinde)

External



Defined by: DIN 513
Tolerance class: Medium Class

Standard - External



| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|---------------|-----------------|-----|-----|-------------|-------------|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 2.0 | 3ER2.0SAGE... | 3EL2.0SAGE... | .069 | .06 | .08 | YE3 | YI3 | AL...-3 (LH) |
| | | 2.0 | 4ER2.0SAGE... | 4EL2.0SAGE... | .069 | .06 | .08 | | | |
| 1/2" | .87 | 3.0 | 4ER3.0SAGE... | 4EL3.0SAGE... | .102 | .07 | .10 | YE4 | YI4 | AL...-4 (LH) |
| | | 4.0 | 4ER4.0SAGE... | 4EL4.0SAGE... | .140 | .07 | .12 | | | |
| 1/2"F | .91 | 3.0 | 4FER3.0SAGE... | | .102 | .07 | .10 | YE4F | | AL...-4F |
| | | 4.0 | 4FER4.0SAGE... | | .140 | .07 | .12 | | | |
| 5/8" | 1.06 | 4.0 | 5ER4.0SAGE... | 5EL4.0SAGE... | .140 | .07 | .13 | YE5 082/038 | YI5 082/039 | AL...-5 (LH) |

U Style - External




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|------------|------------|---------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/2"U | .87 | 5.0 | 4UER5.0SAGE... | 4UEL5.0SAGE... | .174 | .05 | .41 | YE4U-SAGE5 | YI4U-SAGE5 | AL...-4U (LH) |
| | | 6.0 | 4UER6.0SAGE... | 4UEL6.0SAGE... | .208 | .05 | .40 | YE4U-SAGE6 | YI4U-SAGE6 | |


Metric Buttress (Sägengewinde) (con't)

MEGALINE

External



Defined by: DIN 513
Tolerance class: Medium Class




Mega Line

External




| Insert Size | | Pitch | Ordering Code | EDP No. | Dimensions inch | | | Number of Passes | |
|-------------|--------|-------|------------------|---------|-----------------|-----|-----|---|---|
| IC | L inch | mm | RH | VKX | h min | X | Y | 0.003inch-Min. Depth of Cut (On radius) | 0.006inch-Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 10.0 | 5MGER10.OSAGE... | 42522 | .342 | .06 | .52 | 124 | 58 |
| | | 12.0 | 5MGER12.OSAGE... | 42523 | .410 | .07 | | 149 | 69 |
| | | 14.0 | 5MGER14.OSAGE... | 42524 | .478 | .08 | | 174 | 81 |
| | | 16.0 | 5MGER16.OSAGE... | 42525 | .547 | .13 | | 198 | 93 |
| | | 20.0 | 5MGER20.OSAGE... | 42526 | .983 | .10 | | 248 | 116 |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.



External Toolholders for Metric Buttress (Sägewinde) **MEGA/LINE**




External

| Insert | Ordering Code | EDP No. | Dimensions inch | | | Thread Diameter Range (Min.-Max.) | Spare Parts | | |
|------------------|-----------------|---------|-----------------|------|-----|-----------------------------------|---------------|--|--|
| | | | H=B=H1 | F | L1 | | L2 |  Insert Screw |  Torx Key |
| 5MGER10.0SAGE... | NL100-5MG10SAGE | 66341 | 1.00 | .46 | 5.9 | 1.2 | (S65-80)x10 | S5MG | K6T |
| | NL125-5MG10SAGE | 66342 | 1.25 | .74 | 6.7 | | | | |
| | NL150-5MG10SAGE | 66343 | 1.50 | 1.06 | 7.9 | | | | |
| 5MGER12.0SAGE... | NL100-5MG12SAGE | 66344 | 1.00 | .46 | 5.9 | 1.2 | (S85-146)x12 | | |
| | NL125-5MG12SAGE | 66364 | 1.25 | .74 | 6.7 | | | | |
| | NL150-5MG12SAGE | 66365 | 1.50 | 1.06 | 7.9 | | | | |
| 5MGER14.0SAGE... | NL100-5MG14SAGE | 66366 | 1.00 | .46 | 5.9 | 1.2 | (S115-145)x14 | | |
| | NL125-5MG14SAGE | 66367 | 1.25 | .74 | 6.7 | | | | |
| | NL150-5MG14SAGE | 66368 | 1.50 | 1.06 | 7.9 | | | | |
| 5MGER16.0SAGE... | NL100-5MG16SAGE | 66382 | 1.00 | .46 | 5.9 | 1.2 | (S150-175)x16 | | |
| | NL125-5MG16SAGE | 66383 | 1.25 | .74 | 6.7 | | | | |
| | NL150-5MG16SAGE | 66384 | 1.50 | 1.06 | 7.9 | | | | |
| 5MGER20.0SAGE... | NL100-5MG20SAGE | 66385 | 1.00 | .46 | 5.9 | 1.2 | (S210-230)x20 | | |
| | NL125-5MG20SAGE | 66387 | 1.25 | .74 | 6.7 | | | | |
| | NL150-5MG20SAGE | 66388 | 1.50 | 1.06 | 7.9 | | | | |


Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.

Metric Buttress (Sägewinde) (con't)


Internal



Defined by: DIN 513
Tolerance class: Medium Class



Standard - Internal



FLINE

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|---------------|-----------------|-----|-----|-------------|-------------|--------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 3/8" | .63 | 2.0 | 3IR2.0SAGE... | 3IL2.0SAGE... | .059 | .06 | .09 | YI3 | YE3 | AVR..-3 (LH) |
| 1/2" | .87 | 3.0 | 4IR3.0SAGE... | 4IL3.0SAGE... | .089 | .07 | .11 | YI4 | YE4 | AVR..-4 (LH) |
| | | 4.0 | 4IR4.0SAGE... | 4IL4.0SAGE... | .122 | .08 | .13 | | | |
| 1/2" F | .91 | 3.0 | 4FIR3.0SAGE... | | .089 | .07 | .11 | YI4F | | AVRC...-4F |
| | | 4.0 | 4FIR4.0SAGE... | | .122 | .08 | .13 | | | |
| 5/8" | 1.06 | 4.0 | 5IR4.0SAGE... | 5IL4.0SAGE... | .122 | .08 | .13 | YI5 082/039 | YE5 082/038 | AVR..-5 (LH) |

U Style - Internal




| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|----------------|----------------|-----------------|-----|-----|---------|---------|---------------|
| IC | L inch | mm | RH | LH | h min | X | Y | RH | LH | |
| 1/2" U | .87 | 5.0 | 4UIR5.0SAGE... | 4UIL5.0SAGE... | .148 | .07 | .41 | YI4U-5S | YE4U-5S | AVR..-4U (LH) |
| | | 6.0 | 4UIR6.0SAGE... | 4UIL6.0SAGE... | .179 | .07 | .40 | YI4U-6S | YE4U-6S | |


Metric Buttress (Sägewinde) (con't)

MEGA/LINE

Internal



Defined by: DIN 513
Tolerance class: Medium Class




Mega Line





Internal



| IC | L inch | Pitch mm | Ordering Code RH | EDP No. VKX | Dimensions inch | | | Number of Passes | |
|---------|--------|----------|------------------|-------------|-----------------|-----|-----|---|---|
| | | | | | h min | X | Y | 0.003inch–Min. Depth of Cut (On radius) | 0.006inch–Max. Depth of Cut (On radius) |
| 5/8" MG | 1.06 | 10.0 | 5MGIR10.0SAGE... | 42527 | .284 | .11 | .54 | 103 | 48 |
| | | 12.0 | 5MGIR12.0SAGE... | 42528 | .341 | .13 | .54 | 124 | 58 |
| | | 14.0 | 5MGIR14.0SAGE... | 42529 | .398 | .15 | .54 | 145 | 67 |
| | | 16.0 | 5MGIR16.0SAGE... | 42520 | .456 | .17 | .54 | 165 | 77 |
| | | 20.0 | 5MGIR20.0SAGE... | 42521 | .571 | .20 | .54 | 207 | 97 |



Internal Toolholders for Metric Buttress (Sägewinde) MEGA/LINE



Internal


Spare Parts

| Insert | Ordering Code | EDP No. | Dimensions inch | | | | | | | Min. Bore Dia. | Thread Diameter Range (Min.-Max.) | | Insert Screw | Torx Key |
|------------------|-------------------|---------|-----------------|-------|---|----------|------|------|------|----------------|-----------------------------------|---------------------|--------------|----------|
| | | | RH | A | L | L1 (max) | D | D1 | F | | inch | Short Chip Material | | |
| 5MGIR10.0SAGE... | NVRC150-5MG10SAGE | 66389 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.22 | 1.97 | | (S65-80)x10 | (S75-80)x10 | S5MG | K6T |
| | NVRC150-5MG12SAGE | 66390 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.63 | 2.64 | | (S85-400)x12 | (S90-400)x12 | | |
| 5MGIR12.0SAGE... | NVRC200-5MG12SAGE | 66391 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.83 | 2.84 | | (S90-400)x12 | (S105-400)x12 | | |
| | NVRC250-5MG12SAGE | 66392 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 2.03 | 3.27 | | (S105-400)x12 | (S250-400)x12 | | |
| 5MGIR14.0SAGE... | NVRC150-5MG14SAGE | 66393 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.63 | 3.70 | | (S115-145)x14 | (S115-145)x14 | | |
| | NVRC200-5MG14SAGE | 66395 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.83 | 3.70 | | (S115-145)x14 | (S115-145)x14 | | |
| | NVRC250-5MG14SAGE | 66396 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 2.03 | 3.70 | | (S115-145)x14 | (S120-145)x14 | | |
| 5MGIR16.0SAGE... | NVRC150-5MG16SAGE | 66397 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.63 | 4.96 | | (S150-175)x16 | (S150-175)x16 | | |
| | NVRC200-5MG16SAGE | 66398 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.83 | 4.96 | | (S150-175)x16 | (S150-175)x16 | | |
| | NVRC250-5MG16SAGE | 66399 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 2.03 | 4.96 | | (S150-175)x16 | (S150-175)x16 | | |
| 5MGIR20.0SAGE... | NVRC150-5MG20SAGE | 66400 | 1.42 | 9.07 | 4 | 1.5 | 1.49 | 1.63 | 2.95 | | (S105-230)x20 | (S105-230)x20 | | |
| | NVRC200-5MG20SAGE | 66401 | 1.81 | 10.05 | 5 | 2.0 | 1.99 | 1.83 | 2.95 | | (S105-230)x20 | (S210-230)x20 | | |
| | NVRC250-5MG20SAGE | 66402 | 2.28 | 11.04 | 6 | 2.5 | 2.49 | 2.03 | 3.19 | | (S210-230)x20 | (S210-230)x20 | | |

Recommended thread infeed method for Mega Line: Flank or Modified Flank 1°.


API

External




$$\alpha = \arctg (IPF/24)$$


Defined by: API SPEC. 7:1990
Tolerance class: Standard API



Standard



F-Line



On Edge

Standard



F LINE

| Insert Size | | Pitch | Thread | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|---------|-------|---------------|----------------------|----------------|----------------------------------|-----------------|-----|-----|---------------------------|-----------------------------------|
| IC | L inch | TPI | IPF | RH | | | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 4 | V-0.038R | 2 | 4ER4API382... | NC23-NC50 | .122 | .08 | .11 | YEI 4-API-1P or YE4 | AL...-4 5BUT/API or AL...-4 |
| | | 4 | V-0.038R | 3 | 4ER4API383... | NC56-NC77 | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 4ER4API502... | 6 5/8" REG, 5 1/2" FH, 6 5/8" FH | .148 | .08 | .11 | | |
| | | 4 | V-0.050 | 3 | 4ER4API503... | 5 1/2", 7 5/8", 8 5/8" REG | .147 | .08 | .11 | | |
| | | 5 | V-0.040 | 3 | 4ER5API403... | 2 3/8"-4 1/2" REG | .118 | .07 | .10 | | |
| 1/2" F | .91 | 4 | V-0.038R | 2 | 4FER4API382... | NC23-NC50 | .122 | .08 | .11 | YE4F | AL...-4F |
| | | 4 | V-0.038R | 3 | 4FER4API383... | NC56-NC77 | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 4FER4API502... | 6 5/8" REG, 5 1/2" FH, 6 5/8" FH | .148 | .08 | .11 | | |
| | | 4 | V-0.050 | 3 | 4FER4API503... | 5 1/2", 7 5/8", 8 5/8" REG | .147 | .08 | .11 | | |
| | | 5 | V-0.040 | 3 | 4FER5API403... | 2 3/8"-4 1/2" REG | .118 | .07 | .10 | | |
| 5/8" | 1.06 | 4 | V-0.038R | 2 | 5ER4API382... | NC23-NC50 | .122 | .08 | .11 | YE5OIL | AL...-5 OIL |
| | | 4 | V-0.038R | 3 | 5ER4API383... | NC56-NC77 | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 5ER4API502... | 6 5/8" REG, 5 1/2" FH, 6 5/8" FH | .148 | .08 | .12 | | |
| | | 4 | V-0.050 | 3 | 5ER4API503... | 5 1/2", 7 5/8", 8 5/8" REG | .147 | .08 | .12 | | |
| | | 5 | V-0.040 | 3 | 5ER5API403... | 2 3/8"-4 1/2" REG | .118 | .07 | .11 | | |
| 4 | V-0.065 | 2 | 5ER4API652... | 2 3/8" IF - 5 1/2 IF | .111 | .09 | .11 | | | | |

On Edge



| Insert Size | | Pitch | Thread | Taper | Ordering Code | Size | Dimensions inch | | | | Position | |
|-------------|--------|-------|---------|-------|--------------------|--------------------------------|-----------------|-------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | | R | h min | T | Ø C | X | Y |
| 5/8" | 1.06 | 5 | V-0.040 | 3 | TNEC54ER5API403... | 2 3/8"-4 1/2" REG | .020 | .118 | .25 | .26 | .92 | .15 |
| | | 4 | V-0.050 | 2 | TNEC55ER4API502... | 6 5/8" REG, 5 1/2 FH, 6 5/8 FH | .025 | .148 | .31 | | | .20 |
| | | 4 | V-0.050 | 3 | TNEC55ER4API503... | 5 1/2", 7 5/8", 8 5/8" REG | .025 | .148 | .31 | | | .20 |
| | | 4 | V-0.038 | 2 | TNEC55ER4API382... | NC23-NC50, 2 3/8 - 6 5/8 IF | .038 | .122 | .31 | | | .20 |
| | | 4 | V-0.038 | 3 | TNEC55ER4API383... | NC56-NC77 | .038 | .122 | .31 | | | .20 |

On Edge inserts are compatible with most commonly used toolholders in the market.

API (con't)

Internal

$\alpha = \arctg(IPF/24)$

Defined by: API SPEC. 7:1990
Tolerance class: Standard API

Standard

F-Line

On Edge

Standard



| Insert Size | | Pitch | Thread | Taper | Ordering Code | | Size | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|----------|-------|----------------|---------------------------------|------|-----------------|-----|-----|---------------------------|---|
| IC | L inch | TPI | IPF | RH | | | | h min | X | Y | RH | |
| 1/2" | .87 | 4 | V-0.038R | 2 | 4IR4API382... | NC23-NC50 | | .122 | .08 | .11 | YEI 4-API-1P or YI4 | AVRC...-4 5BUT/API or AVR...-4 |
| | | 4 | V-0.038R | 3 | 4IR4API383... | NC56-NC77 | | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 4IR4API502... | 6 5/8" REG, 5 1/2"FH, 6 5/8" FH | | .148 | .08 | .12 | | |
| | | 4 | V-0.050 | 3 | 4IR4API503... | 5 1/2", 7 5/8", 8 5/8" REG | | .147 | .08 | .11 | | |
| | | 5 | V-0.040 | 3 | 4IR5API403... | 2 3/8"-4 1/2" REG | | .118 | .07 | .10 | | |
| 1/2" F | .91 | 4 | V-0.038R | 2 | 4FIR4API382... | NC23-NC50 | | .122 | .08 | .11 | YI4F | AVRC...-4F |
| | | 4 | V-0.038R | 3 | 4FIR4API383... | NC56-NC77 | | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 4FIR4API502... | 6 5/8" REG, 5 1/2"FH, 6 5/8"FH | | .148 | .08 | .12 | | |
| | | 4 | V-0.050 | 3 | 4FIR4API503... | 5 1/2", 7 5/8", 8 5/8" REG | | .147 | .08 | .11 | | |
| | | 5 | V-0.040 | 3 | 4FIR5API403... | 2 3/8"-4 1/2" REG | | .118 | .07 | .10 | | |
| 5/8" | 1.06 | 4 | V-0.038R | 2 | 5IR4API382... | NC23-NC50 | | .122 | .08 | .11 | YI5OIL | AVR...-5 OIL |
| | | 4 | V-0.038R | 3 | 5IR4API383... | NC56-NC77 | | .121 | .08 | .11 | | |
| | | 4 | V-0.050 | 2 | 5IR4API502... | 6 5/8" REG, 5 1/2"FH, 6 5/8" FH | | .148 | .08 | .12 | | |
| | | 4 | V-0.050 | 3 | 5IR4API503... | 5 1/2", 7 5/8", 8 5/8" REG | | .147 | .08 | .12 | | |
| | | 5 | V-0.040 | 3 | 5IR5API403... | 2 3/8"-4 1/2" REG | | .118 | .07 | .11 | | |
| | | 4 | V-0.065 | 2 | 5IR4API652... | 2 3/8"IF- 5 1/2"IF | | .111 | .09 | .11 | | |

On Edge




| Insert Size | | Pitch | Thread | Taper | Ordering Code | | Size | Dimensions inch | | | | Position | |
|-------------|--------|-------|---------|-------|--------------------|--------------------------------|------|-----------------|-------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | | | R | h min | T | ØC | X | Y |
| 5/8" | 1.06 | 5 | V-0.040 | 3 | TNEC54IR5API403... | 2 3/8"-4 1/2" REG | | .020 | .118 | .25 | .26 | .92 | .15 |
| | | 4 | V-0.050 | 2 | TNEC55IR4API502... | 6 5/8" REG, 5 1/2 FH, 6 5/8 FH | | .025 | .148 | .31 | | | .20 |
| | | 4 | V-0.050 | 3 | TNEC55IR4API503... | 5 1/2", 7 5/8", 8 5/8" REG | | .025 | .148 | .31 | | | .20 |
| | | 4 | V-0.038 | 2 | TNEC55IR4API382... | NC23-NC50, 2 3/8 - 6 5/8 IF | | .038 | .122 | .31 | | | .20 |
| | | 4 | V-0.038 | 3 | TNEC55IR4API383... | NC56-NC77 | | .038 | .122 | .31 | | | .20 |


On Edge inserts are compatible with most commonly used toolholders in the market.

API Buttress Casing

External



Defined by: STD.5B.1979
Tolerance class: Standard API



Standard



| Insert Size | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | | |
|-------------|-------|-------|---------------|---------------|-----------------|--------|-----|-------|------------------|-----------------------------|
| | | | | | IC | L inch | TPI | IPF | RH | Toolholder |
| 1/2" | .87 | 5 | .75 | 4ER5BUT75... | 4 1/2"-13 3/8" | .061 | .12 | .07 | YEI 4-BUT or YE4 | AL...-4 5BUT/API or AL...-4 |
| | | | | 4ER5BUT1... | 16"-20" | .061 | .12 | .07 | | |
| 1/2"F | .91 | 5 | .75 | 4FER5BUT75... | 4 1/2"-13 3/8" | .061 | .12 | .07 | YE4F | AL...-4F |
| | | | | 4FER5BUT1... | 16"-20" | .061 | .12 | .07 | | |



FLINE

M+ Style



| Insert Size | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Anvil | | |
|-------------|-------|-------|-------|---------------|-----------------|-----------------|--------|-----|-------|------|------------|
| | | | | | | IC | L inch | TPI | IPF | RH | Toolholder |
| 5/8" | 1.06 | 5 | .75 | 2 | 5ER5BUT752M+... | 4 1/2"-13 3/8" | .061 | .19 | .27 | YE5M | AL...-5M |

T+ Style




| Insert Size | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Anvil | | | |
|-------------|-------|-------|-------|---------------|------|-----------------|----------------|------|-------|-----|------------|----------|
| | | | | | | IC | L inch | TPI | IPF | RH | Toolholder | |
| 1/2"T | .87 | 5 | .75 | 1 | 3 | 4ER5BUT753T+... | 4 1/2"-13 3/8" | .061 | .10 | .63 | Y4T | AL...-4T |
| | | | | | | 4ER5BUT13T+... | 16"-20" | | | | | |

14D



| Insert Size | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | Anvil | | |
|-------------|-------|-------|-------|-------------------|-----------------|-----------------|-----|------------------|----|------------|
| | | | | | | IC | TPI | IPF | RH | Toolholder |
| 14D | 5 | .75 | 2 | 14DER5BUT752T+... | 4 1/2"-9 5/8" | .061 | .39 | Y14DER-5 BUT | | AL...-14D |
| | | | | | 10 3/4"-13 3/8" | | | Y14DER-5BUT-0.4N | | |
| | | | | | 16"-20" | | | Y14DER-5BUT-0.4N | | |

API Buttress Casing (con't)




On Edge



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|--------|-------|-------|-------------------|----------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | h min | T | Ø C | X | Y |
| 5/8" | 1.06 | 5 | .75 | TNEC54ER5BUT75... | 4 1/2"-13 3/8" | .061 | .25 | .26 | .92 | .16 |
| | | 5 | 1 | TNEC54ER5BUT1... | 16"-20" | | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.

CNGA




Multiplus

| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-----|-------|-------|---------------------|----------------|-------|-----------------|-----|-----|----------|--|
| IC | TPI | IPF | | RH | | h min | T | Ø C | X | Y | |
| 3/4" | 5 | .75 | 3 | CNGA64ER5BUT75T3... | 4 1/2"-13 3/8" | .061 | .25 | .31 | .74 | .22 | |
| | 5 | 1 | 3 | CNGA64ER5BUT1T3... | 16"-20" | | | | | | |

CNGA inserts are compatible with most commonly used toolholders in the market.

Chaser




Multiplus


| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-----|-------|-------|--------------------|----------------|-------|-----------------|-----|-----|----------|--|
| L | TPI | IPF | | RH | | h min | T | X | Y | | |
| .63 | 5 | .75 | 3 | 1616ER5BUT753S+... | 4 1/2"-13 3/8" | .061 | .19 | .62 | .13 | | |
| | 5 | 1 | 3 | 1616ER5BUT13S+... | 16"-20" | | | | | | |

Chaser inserts are compatible with most commonly used toolholders in the market.

API Buttress Casing (con't)



Standard



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|---------------|----------------|-----------------|-----|-----|------------------|--------------------------------|
| IC | L inch | TPI | IPF | RH | h min | X | Y | RH | Toolholder | |
| 1/2" | .87 | 5 | .75 | 4IR5BUT75... | 4 1/2"-13 3/8" | .061 | .11 | .07 | YEI 4-BUT or Y14 | AVRC...-4 5BUT/API or AVR...-4 |
| | | 5 | 1 | 4IR5BUT1... | 16"-20" | .061 | .11 | .07 | | |
| 1/2"F | .91 | 5 | .75 | 4FIR5BUT75... | 4 1/2"-13 3/8" | .061 | .11 | .07 | Y14F | AVRC...-4F |
| | | 5 | 1 | 4FIR5BUT1... | 16"-20" | .061 | .11 | .07 | | |

FLINE

M+ Style




| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------|-----------------|----------------|-----------------|-----|------------|-------|-----------|
| IC | L inch | TPI | IPF | RH | h min | X | Y | RH | Toolholder | | |
| 5/8" | 1.06 | 5 | .75 | 2 | 5IR5BUT752M+... | 4 1/2"-13 3/8" | .061 | .19 | .26 | Y15M | AVR...-5M |

T+ Style



| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------|-----------------|----------------|-----------------|-----|------------|-------|-----------|
| IC | L inch | TPI | IPF | RH | h min | X | Y | RH | Toolholder | | |
| 1/2"T | .87 | 5 | .75 | 3 | 4IR5BUT753T+... | 4 1/2"-13 3/8" | .061 | .10 | .63 | Y4T | AVR...-4T |
| | | | 1 | | 4IR5BUT13T+... | 16"-20" | | | | | |

14D



| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|-----|-------|-------|-------------------|-----------------|------|-----------------|------------------|-------------|-------|--|
| IC | TPI | IPF | RH | h min | Y | RH | Toolholder | | | | |
| 14D | 5 | .75 | 2 | 14DIR5BUT752T+... | 4 1/2"-9 5/8" | .061 | .39 | Y14DIR-5 BUT | AVRC...-14D | | |
| | | 1 | | 14DIR5BUT12T+... | 10 3/4"-13 3/8" | | | Y14DIR-5BUT-0.4N | | | |
| | 5 | 1 | 2 | 14DIR5BUT12T+... | 16"-20" | .061 | .39 | Y14DIR-5BUT-0.4N | AVRC...-14D | | |

API Buttress Casing (con't)

Internal

Defined by: STD.5B:1979
Tolerance class: Standard API

On Edge

CNGA

Chaser

On Edge



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|--------|-------|-------|-------------------|----------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | h min | T | Ø C | X | Y |
| 5/8" | 1.06 | 5 | .75 | TNEC54IR5BUT75... | 4 1/2"-13 3/8" | .061 | .25 | .26 | .92 | .17 |
| | | 5 | 1 | TNEC54IR5BUT1... | 16"-20" | | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.


CNGA



| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-----|-------|-------|---------------------|----------------|-------|-----------------|-----|-----|----------|--|
| IC | TPI | IPF | | RH | | h min | T | Ø C | X | Y | |
| 3/4" | 5 | .75 | 3 | CNGA64IR5BUT75T3... | 4 1/2"-13 3/8" | .061 | .25 | .31 | .74 | .22 | |
| | 5 | .75 | 2 | CNGA64IR5BUT75T2... | 4 1/2"-13 3/8" | | | | | .41 | |
| | 5 | 1 | 3 | CNGA64IR5BUT1T3... | 16"-20" | | | | | .22 | |

CNGA inserts are compatible with most commonly used toolholders in the market.

Chaser




| Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-----|-------|-------|--------------------|----------------|-------|-----------------|-----|-----|----------|--|
| L | TPI | IPF | | RH | | h min | T | X | Y | | |
| .63 | 5 | .75 | 3 | 1616IR5BUT75S3+... | 4 1/2"-13 3/8" | .061 | .19 | .62 | .13 | | |
| | 5 | 1 | 3 | 1616IR5BUT13S+... | 16"-20" | | | | | | |


Chaser inserts are compatible with most commonly used toolholders in the market.

API Round Casing & Tubing


External




Defined by: API STD. 5B:1979
Tolerance class: Standard API RD




Standard




SCB Sintered Chipbreaker



M+ Style



F-Line M+



Z+ Style


Standard



SCB

| Insert Size | | Pitch | | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|--|----------------|-----------------|-----|-----|-------------------------|--------------------------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 10 | | 3ER10APIRD... | .056 | .05 | .06 | YEI3-APIRD or YE3 | AL...-3 APIRD or AL...-3 |
| | | 8 | | 3ER8APIRD... | .071 | .05 | .06 | | |
| 3/8" SCB | .63 | 10 | | 3JER10APIRD... | .056 | .05 | .06 | | |
| | | 8 | | 3JER8APIRD... | .071 | .05 | .06 | | |

M+ Style



F.LINE

| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------------------|-----------------|-----|-----|--------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 10 | 2 | 4ER10APIRD2M+... | .056 | .09 | .15 | YE4M | AL...-4 |
| 1/2"F | .91 | 10 | 2 | 4FER10APIRD2M+... | .056 | .09 | .15 | YE4M2F | AL...-4MF |
| 5/8" | 1.06 | 10 | 3 | 5ER10APIRD3M+... | .056 | .15 | .25 | YE5M | AL...-5M |
| | | 8 | 2 | 5ER8APIRD2M+... | .071 | .11 | .18 | | |


Z+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 10 | 2 | 4ER10APIRD2Z+... | .056 | .12 | .39 | YE4Z | AL...-4Z |
| | | 8 | 2 | 4ER8APIRD2Z+... | .071 | .15 | .38 | | |

API Round Casing & Tubing (con't)


External



Defined by: API STD. 5B:1979
Tolerance class: Standard API RD



T+ Style



14D -
2 Cutting Edges

T+ Style



| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | | RH | h min | X | Y | RH | Toolholder |
| 1/2" T | .87 | 10 | 6 | 4ER10APIRD6T+... | .056 | .01 | .64 | | |
| | | 8 | 3 | 4ER8APIRD3T+... | .071 | .01 | .56 | Y4T | AL...-4T |
| | | 8 | 5 | 4ER8APIRD5T+... | .071 | .01 | .66 | | |


14D




| Insert Size | | Pitch | Teeth | Ordering Code | Size | Dimensions inch | | Anvil | |
|-------------|-----|-------|-------|--------------------|---------------|-----------------|-----|--------------------|------------|
| IC | TPI | | | RH | | h min | Y | RH | Toolholder |
| 14D | | 10 | 4 | 14DER10APIRD4T+... | 2 3/8" and up | .056 | .34 | Y14DER-10 APIRD | |
| | | 10 | 3 | 14DER10APIRD3T+... | 2 3/8" and up | | .35 | Y14DER-10 APIRD-3+ | AL...-14D |
| | | 8 | 3 | 14DER8APIRD3T+... | 2 3/8" and up | .071 | .32 | Y14DER-8 APIRD | |

API Round Casing & Tubing (con't)


External




Defined by: API STD. 5B:1979
Tolerance class: Standard API RD



On Edge



CNGA



Chaser


On Edge



| Insert Size | | Pitch | Ordering Code | Dimensions inch | | | Position | |
|-------------|--------|-------|--------------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | RH | h min | T | ØC | X | Y |
| 1/2" | .87 | 10 | TNEC43ER10APIRD... | .056 | .19 | .20 | .73 | .13 |
| | | 8 | TNEC43ER8APIRD... | .071 | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.


CNGA



| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Position | |
|-------------|-----|-------|----------------------|---------------|-----------------|-----|-----|----------|--|
| IC | TPI | | RH | h min | T | ØC | X | Y | |
| 3/4" | 10 | 5 | CNGA64ER10APIRDT5... | .056 | .25 | .31 | .74 | .18 | |
| | 8 | 4 | CNGA64ER8APIRDT4... | .071 | | | | | |

CNGA inserts are compatible with most commonly used toolholders in the market.

Chaser



| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Position | |
|-------------|-----|-------|---------------------|---------------|-----------------|-----|-----|----------|--|
| L | TPI | | RH | h min | T | X | Y | | |
| .63 | 10 | 4 | 1616ER10APIRD4S+... | .056 | .19 | .61 | .17 | | |
| | 8 | 3 | 1616ER8APIRD3S+... | .071 | | | | .63 | |

Chaser inserts are compatible with most commonly used toolholders in the market.

API Round Casing & Tubing (con't)

Internal

Defined by: API STD. 5B:1979
Tolerance class: Standard
API RD

Standard


SCB
Sintered
Chipbreaker

M+ Style

F-Line M+

Z+ Style

Standard



SCB

| Insert Size | | Pitch | Ordering Code | | Dimensions inch | | | Anvil | |
|-------------|--------|-------|---------------|--|-----------------|-----|-----|-------------------------|-----------------------------------|
| IC | L inch | TPI | RH | | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 10 | 3IR10APIRD... | | .056 | .05 | .06 | YEI3-APIRD or YI3 | AVRC... 3APIRD or AVRC...-3 |
| | | 8 | 3IR8APIRD... | | .071 | .05 | .06 | | |
| 3/8" SCB | .63 | 10 | 3JR10APIRD... | | .056 | .05 | .06 | | |
| | | 8 | 3JR8APIRD... | | .071 | .05 | .06 | | |

M+ Style



F-LINE

| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|-------------------|--|-----------------|-----|-----|--------|-------------|
| IC | L inch | TPI | | RH | | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 10 | 2 | 4IR10APIRD2M+... | | .056 | .09 | .15 | YI4M | AVR...-4 |
| | | 8 | 2 | 4IR8APIRD2M+... | | .071 | .11 | .18 | | |
| 1/2" F | .91 | 10 | 2 | 4FIR10APIRD2M+... | | .056 | .09 | .15 | YI4M2F | AVRC...-4MF |
| | | 8 | 2 | 4FIR8APIRD2M+... | | .071 | .11 | .18 | | |
| 5/8" | 1.06 | 10 | 3 | 5IR10APIRD3M+... | | .056 | .15 | .25 | YI5M | AVR...-5M |
| | | 8 | 2 | 5IR8APIRD2M+... | | .071 | .11 | .18 | | |


Z+ Style




| Insert Size | | Pitch | Teeth | Ordering Code | | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|------------------|--|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | | RH | | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 10 | 2 | 4IR10APIRD2Z+... | | .056 | .12 | .39 | YI4Z | AVR...-4Z |
| | | 8 | 2 | 4IR8APIRD2Z+... | | .071 | .15 | .38 | | |

API Round Casing & Tubing (con't)


Internal



Defined by: STD. 5B:1979
Tolerance class: Standard API RD



Z+ Style




14D -
2 Cutting Edges

T+ Style



| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------|-------|-------|------------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | RH | h min | X | Y | RH | | |
| 1/2" T | .87 | 10 | 6 | 4IR10APIRD6T+... | .056 | .01 | .66 | Y4T | AVR...-4T |
| | | 8 | 3 | 4IR8APIRD3T+... | .071 | .01 | .56 | | |
| | | 8 | 5 | 4IR8APIRD5T+... | .071 | .01 | .66 | | |


14D




| Insert Size | | Pitch | Teeth | Ordering Code | Size | Dimensions inch | | Anvil | Toolholder |
|-------------|-----|-------|--------------------|---------------|-------|-----------------|--------------------|-------------|----------------|
| IC | TPI | | | | h min | Y | | | |
| 14D | 10 | 4 | 14DIR10APIRD4T+... | 2 3/8" and up | .056 | .34 | Y14DIR-10 APIRD | AVRC...-14D | |
| | 10 | 3 | 14DIR10APIRD3T+... | 2 3/8" and up | | .35 | Y14DIR-10 APIRD-3+ | | |
| | 8 | 3 | 14DIR8APIRD3T+... | 2 3/8" and up | | .071 | .32 | | Y14DIR-8 APIRD |

API Round Casing & Tubing (con't)

Internal



Defined by: STD. 5B:1979
Tolerance class: Standard API RD



On Edge
CNGA
Chaser


On Edge



| Insert Size | | Pitch | Ordering Code | Dimensions inch | | | Position | |
|-------------|--------|-------|--------------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | RH | h min | T | Ø C | X | Y |
| 1/2" | .87 | 10 | TNEC43IR10APIRD... | .056 | .19 | .20 | .73 | .13 |
| | | 8 | TNEC43IR8APIRD... | .071 | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.


CNGA



| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | | Position | |
|-------------|-----|-------|----------------------|---------------|-----------------|-----|-----|----------|--|
| IC | TPI | | RH | h min | T | Ø C | X | Y | |
| 3/4" | 10 | 5 | CNGA64IR10APIRDT5... | .056 | .25 | .31 | .74 | .18 | |
| | 8 | 4 | CNGA64IR8APIRDT4... | .071 | | | | | |

CNGA inserts are compatible with most commonly used toolholders in the market.

Chaser




| Insert Size | | Pitch | Teeth | Ordering Code | Dimensions inch | | Position | |
|-------------|-----|-------|---------------------|---------------|-----------------|-----|----------|-----|
| L | TPI | | RH | h min | T | X | Y | |
| .63 | 10 | 4 | 1616IR10APIRD4S+... | .056 | .19 | .61 | .22 | |
| | 8 | 3 | 1616IR8APIRD3S+... | .071 | | | | .63 |


Chaser inserts are compatible with most commonly used toolholders in the market.

VAM


External




$\alpha = \arctg (IPF/24)$



Standard




F-Line



On Edge

Defined by: VAM
Tolerance class: Standard VAM

Standard



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------------|---------------|----------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | IPF | RH | | h min | X | Y | RH | Toolholder |
| 3/8" | .63 | 8 | .75 | 3ER8VAM... | 2 3/8", 2 7/8" | .038 | .07 | .07 | YE3 | AL...-3 |
| | | 6 | | 4ER6VAM... | 3 1/2" | .038 | .09 | .09 | YE4 | AL...-4 |
| 1/2" | .87 | 5 | | 4ER5VAM... | 5"-9 5/8" | .061 | .09 | .11 | YE4F | AL...-4F |
| | | 6 | | 4FER6VAM... | 3 1/2" | .038 | .09 | .09 | | |
| 1/2"F | .91 | 5 | 4FER5VAM... | 5"-9 5/8" | .061 | .09 | .11 | | | |

FLINE

On Edge



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|--------|-------|-------|-----------------|----------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | h min | T | ØC | X | Y |
| 1/2" | .87 | 8 | .75 | TNEC43ER8VAM... | 2 3/8", 2 7/8" | .038 | .19 | .20 | .73 | .13 |
| | | 6 | | TNEC43ER6VAM... | 3 1/2" | .038 | .19 | | | .11 |
| 5/8" | 1.06 | 5 | | TNEC54ER5VAM... | 5"-9 5/8" | .061 | .25 | .26 | .92 | .16 |

On Edge inserts are compatible with most commonly used toolholders in the market.

VAM (con't)

Internal

$\alpha = \arctg (IPF/24)$

Defined by: VAM
Tolerance class: Standard VAM


Standard

F-Line

On Edge

CNGA

Standard



F-LINE

| Insert Size | Pitch | | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | Toolholder |
|-------------|-------|--------|-------|---------------|----------------|-----------------|-----|-----|-------|------------|
| | IC | L inch | | | | TPI | IPF | RH | | |
| 3/8" | .63 | 8 | | 3IR8VAM... | 2 3/8", 2 7/8" | .040 | .07 | .07 | Y13 | AVR...-3 |
| | | | | 4IR6VAM... | | | | | | |
| 1/2" | .87 | 6 | .75 | 4IR5VAM... | 5"-9 5/8" | .061 | .09 | .10 | Y14F | AVRC...-4F |
| | | 5 | | 4FIR6VAM... | | | | | | |
| 1/2"F | .91 | 6 | | 4FIR5VAM... | 5"-9 5/8" | .061 | .09 | .10 | | |
| | | 5 | | | | | | | | |

On Edge



| Insert Size | Pitch | | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-------|--------|-------|-----------------|----------------|-----------------|-----|-----|----------|-----|
| | IC | L inch | | | | TPI | IPF | RH | h min | T |
| 1/2" | .87 | 8 | .75 | TNEC43IR8VAM... | 2 3/8", 2 7/8" | .040 | .19 | .20 | .73 | .13 |
| | | 6 | | TNEC43IR6VAM... | | | | | | |
| 5/8" | 1.06 | 5 | | TNEC54IR5VAM... | 5"- 9 5/8" | .061 | .25 | .26 | .92 | .17 |

On Edge inserts are compatible with most commonly used toolholders in the market.

CNGA

Multiplus




| Insert Size | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|-------|-------|-------|---------------------|------------|-----------------|-----|-----|----------|-------|
| | | | | | | IC | TPI | IPF | RH | h min |
| 3/4" | 5 | .75 | 2 | CNGA64IR5VAM75T2... | 5"- 9 5/8" | .061 | .25 | .31 | .74 | .37 |


CNGA inserts are compatible with most commonly used toolholders in the market.

New VAM


External



Defined by: VAM
Tolerance class: Standard VAM




Standard



F-Line

Standard



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | Toolholder |
|-------------|--------------|-----------|-------|---------------|----------------|-----------------|------|----------|-------|------------|
| IC | L inch | TPI | IPF | RH | | h min | X | Y | RH | |
| 3/8" | .63 | 8 | .75 | 3ER8NVAM... | 2 3/8", 2 7/8" | .038 | .07 | .07 | YE3 | AL...-3 |
| | | 6 | | 4ER6NVAM... | 3 1/2" | .038 | .09 | .09 | YE4 | AL...-4 |
| 5 | 4ER5NVAM... | 5"-9 5/8" | | .061 | .09 | .09 | | | | |
| 6 | 4FER6NVAM... | 3 1/2" | | .038 | .09 | .08 | YE4F | AL...-4F | | |
| 1/2" | .87 | 5 | | 4FER5NVAM... | 5"-9 5/8" | .061 | .10 | .09 | | |
| | | 6 | | | | | | | | |
| 1/2"F | .91 | 5 | | | | | | | | |
| | | 6 | | | | | | | | |

New VAM (con't)

Internal

Defined by: VAM
Tolerance class: Standard VAM

Standard

F-Line

On Edge

CNGA

Standard

| | Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|---|-------------|--------|-------------|--------------|---------------|----------------|-----------------|-----|-----|----------|------------|
| | IC | L inch | TPI | IPF | RH | | h min | X | Y | RH | Toolholder |
| | 3/8" | .63 | 8 | .75 | 3IR8NVAM... | 2 3/8", 2 7/8" | .048 | .07 | .07 | Y13 | AVR...-3 |
| | 1/2" | .87 | 6 | | 4IR6NVAM... | 3 1/2" | .048 | .10 | .10 | | |
| 5 | | | 4IR5NVAM... | | 5"-9 5/8" | .070 | .09 | .10 | Y14 | AVR...-4 | |
| | 1/2"F | .91 | 6 | | 4FIR6NVAM... | 3 1/2" | .048 | .08 | .07 | Y14F | AVRC...-4F |
| | | | 5 | 4FIR5NVAM... | 5"-9 5/8" | .070 | .08 | .08 | | | |

On Edge

| | Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | | |
|--|-------------|--------|-------|-------|------------------|-----------------|-----------------|-----|-----|-----|-----|
| | IC | L inch | TPI | IPF | RH | | h min | T | Ø C | X | Y |
| | 1/2" | .87 | 8 | .75 | TNEC43IR8NVAM... | 2 3/8" - 2 7/8" | .048 | .19 | .20 | .73 | .13 |
| | | | 6 | | TNEC43IR6NVAM... | 3 1/2" - 4 1/2" | .048 | .19 | .20 | | |
| | 5/8" | 1.06 | 5 | | TNEC54IR5NVAM... | 5"-16" | .070 | .25 | .26 | .92 | .17 |

On Edge inserts are compatible with most commonly used toolholders in the market.


CNGA

| | Insert Size | | Pitch | Taper | Teeth | Ordering Code | Size | Dimensions inch | | | Position | |
|--|-------------|-----|-------|-------|----------------------|-----------------|------|-----------------|-----|-----|----------|---|
| | IC | TPI | IPF | | | RH | | h min | T | Ø C | X | Y |
| | 3/4" | 6 | .75 | 2 | CNGA64IR6NVAM75T2... | 3 1/2" - 4 1/2" | .048 | .25 | .31 | .74 | .37 | |
| | | 5 | | | CNGA64IR5NVAM75T2... | 5"-16" | .070 | .25 | | | | |


CNGA inserts are compatible with most commonly used toolholders in the market.



EL-Extreme Line



Standard - External



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|---------------|----------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | IPF | RH | | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 6 | 1.5 | 4ER6EL15... | 5"-7 5/8" | .048 | .07 | .07 | YE4 | AL..-4 |
| | | 5 | 1.25 | 4ER5EL125... | 8 5/8"-10 3/4" | .067 | .09 | .09 | | |

On Edge - External



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|--------|-------|-------|-------------------|----------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | h min | T | Ø C | X | Y |
| 5/8" | 1.06 | 6 | 1.5 | TNEC54ER6EL15... | 5"-7 5/8" | .048 | .25 | .26 | .92 | .19 |
| | | 5 | 1.25 | TNEC54ER5EL125... | 8 5/8"-10 3/4" | .067 | .25 | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.

Standard - Internal



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | |
|-------------|--------|-------|-------|---------------|----------------|-----------------|-----|-----|-------|------------|
| IC | L inch | TPI | IPF | RH | | h min | X | Y | RH | Toolholder |
| 1/2" | .87 | 6 | 1.5 | 4IR6EL15... | 5"-7 5/8" | .055 | .07 | .07 | Y14 | AVR..-4 |
| | | 5 | 1.25 | 4IR5EL125... | 8 5/8"-10 3/4" | .075 | .09 | .09 | | |


On Edge - Internal



| Insert Size | | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | |
|-------------|--------|-------|-------|-------------------|----------------|-----------------|-----|-----|----------|-----|
| IC | L inch | TPI | IPF | RH | | h min | T | Ø C | X | Y |
| 5/8" | 1.06 | 6 | 1.5 | TNEC54IR6EL15... | 5"-7 5/8" | .055 | .25 | .26 | .92 | .19 |
| | | 5 | 1.25 | TNEC54IR5EL125... | 8 5/8"-10 3/4" | .075 | .25 | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.

Hughes H-90



U Style - External



| Insert Size | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | | |
|-------------|-------|-------|---------------|----------------|-----------------|--------|-----|-------|----------|-------------|
| | | | | | IC | L inch | TPI | IPF | RH | Toolholder |
| 1/2" U | .87 | 3.5 | 2 | 4UER3.5H902... | 3 1/2"-6 5/8" | .098 | .17 | .43 | YE4U-H90 | AL...-4U |
| | | | | 4UER3.5H903... | 7"-8 5/8" | .098 | .17 | .43 | YE5U-H90 | AL...-5UH90 |
| 5/8" U | 1.06 | 3 | 1.25* | 5UER3H90SL... | 2 3/8"-3 1/2" | .088 | .22 | .54 | | |

On Edge - External



| Insert Size | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | | | |
|-------------|-------|-------|---------------|--------------------|-----------------|--------|-----|----------|-----|-------|-----|
| | | | | | IC | L inch | TPI | IPF | RH | h min | T |
| 5/8" | 1.06 | 3.5 | 2 | TNEC55ER3.5H902... | 3 1/2"-6 5/8" | .098 | .31 | .26 | .92 | .17 | |
| | | 3.5 | 3 | TNEC55ER3.5H903... | 7"-8 5/8" | .098 | .31 | | | | .17 |
| | | 3 | 1.25* | TNEC56ER3H90SL... | 2 3/8"-3 1/2" | .088 | .38 | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.

U Style - Internal



| Insert Size | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Anvil | | |
|-------------|-------|-------|---------------|----------------|-----------------|--------|-----|-------|----------|--------------|
| | | | | | IC | L inch | TPI | IPF | RH | Toolholder |
| 1/2" U | .87 | 3.5 | 2 | 4UIR3.5H902... | 3 1/2"-6 5/8" | .098 | .17 | .43 | YI4U-H90 | AVR...-4U |
| | | | | 4UIR3.5H903... | 7"-8 5/8" | .098 | .17 | .43 | YI5U-H90 | AVR...-5UH90 |
| 5/8" U | 1.06 | 3 | 1.25* | 5UIR3H90SL... | 2 3/8"-3 1/2" | .088 | .22 | .54 | | |

On Edge - Internal




| Insert Size | Pitch | Taper | Ordering Code | Size | Dimensions inch | | | Position | | | |
|-------------|-------|-------|---------------|--------------------|-----------------|--------|-----|----------|-----|-------|-----|
| | | | | | IC | L inch | TPI | IPF | RH | h min | T |
| 5/8" | 1.06 | 3.5 | 2 | TNEC55IR3.5H902... | 3 1/2"-6 5/8" | .098 | .31 | .26 | .92 | .17 | |
| | | 3.5 | 3 | TNEC55IR3.5H903... | 7"-8 5/8" | .098 | .31 | | | | .17 |
| | | 3 | 1.25* | TNEC56IR3H90SL... | 2 3/8"-3 1/2" | .088 | .38 | | | | |

On Edge inserts are compatible with most commonly used toolholders in the market.


* H-90 Slimline.

Pg


External / Internal



Defined by: DIN 40430
Tolerance class: Standard



Standard External



Standard Internal

Standard - External








| Insert Size | | Pitch | Thread | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|------------------|---------------|------------|-----------------|-----|-----|-------|-----|--------------|
| IC | L inch | TPI | | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 20 | Pg7 | 2ER20PG... | 2EL20PG... | .024 | .03 | .04 | - | - | NL...-2 (LH) |
| | | 18 | Pg9/11/13.5/16 | 2ER18PG... | 2EL18PG... | .026 | .03 | .04 | - | - | |
| | | 16 | Pg21/29/36/42/48 | 2ER16PG... | 2EL16PG... | .030 | .04 | .04 | - | - | |
| 3/8" | .63 | 20 | Pg7 | 3ER20PG... | 3EL20PG... | .024 | .03 | .04 | YE3 | YI3 | AL...-3 (LH) |
| | | 18 | Pg9/11/13.5/16 | 3ER18PG... | 3EL18PG... | .026 | .03 | .04 | YE3 | YI3 | |
| | | 16 | Pg21/29/36/42/48 | 3ER16PG... | 3EL16PG... | .030 | .04 | .04 | YE3 | YI3 | |

Standard - Internal



| Insert Size | | Pitch | Thread | Ordering Code | | Dimensions inch | | | Anvil | | Toolholder |
|-------------|--------|-------|------------------|---------------|------------|-----------------|-----|-----|-------|-----|---------------|
| IC | L inch | TPI | | RH | LH | h min | X | Y | RH | LH | |
| 1/4" | .43 | 20 | Pg7 | 2IR20PG... | 2IL20PG... | .025 | .03 | .04 | - | - | NVR...-2 (LH) |
| | | 18 | Pg9/11/13.5/16 | 2IR18PG... | 2IL18PG... | .026 | .03 | .04 | - | - | |
| | | 16 | Pg21/29/36/42/48 | 2IR16PG... | 2IL16PG... | .030 | .04 | .04 | - | - | |
| 3/8" | .63 | 20 | Pg7 | 3IR20PG... | 3IL20PG... | .025 | .03 | .04 | YI3 | YE3 | AVR...-3 (LH) |
| | | 18 | Pg11/13.5/16 | 3IR18PG... | 3IL18PG... | .026 | .03 | .04 | YI3 | YE3 | |
| | | 16 | Pg21/29/36/42/48 | 3IR16PG... | 3IL16PG... | .030 | .03 | .04 | YI3 | YE3 | |

Internal



Defined by: DIN 40430
Tolerance class: Standard

Mini-3 Standard



| Insert Size | | Pitch | Thread | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|--------|-------|----------------|---------------|---------------|-----------------|-----|-----|----------------|---------------------|
| IC mm | L inch | TPI | | RH | LH | h min | Y | F | inch | |
| 5.0 | .31 | 20 | Pg7 | 5.0KIR20PG... | 5.0KIL20PG... | .024 | .03 | .19 | .31 | (C)NVR...-5.0K (LH) |
| | | 20 | Pg7 | 6.0KIR20PG... | 6.0KIL20PG... | .024 | .03 | .21 | | |
| 6.0 | .39 | 18 | Pg9/11/13.5/16 | 6.0KIR18PG... | 6.0KIL18PG... | .026 | .04 | .21 | .39 | .NVR...-6.0K (LH) |

Mini-L



| Insert Size | | Pitch | Thread | Ordering Code | | Dimensions inch | | | Min. Bore Dia. | Toolholder |
|-------------|-----|----------------|--------|---------------|--------------|-----------------|-----|-----|----------------|------------------|
| IC mm | TPI | | | RH | LH | h min | Y | F | inch | |
| 5.0L | 20 | Pg7 | | 5LKIR20PG... | 5LKIL20PG... | .024 | .03 | .18 | .31 | .NVR...-5LK (LH) |
| | 18 | Pg9/11/13.5/16 | | 5LKIR18PG... | 5LKIL18PG... | .026 | .04 | .18 | | |



Thread Turning Toolholders

Vardex Ordering Code System

External Toolholders

| | | | | | | | | | |
|--|---|-----------------|---|---------------|---------------|--|---------------|---------------|---------------|
| A 1 | L 2 | 125 3 | - 4 | 4 4 | U 5 | C 6 | 7 7 | 8 8 | 9 9 |
| 1 - Anvil A - Anvil Required N - No Anvil Required O - Miniature Holder | 2 - Holder Style L - External V - Miniature Square Shank VR - Miniature Round Shank | | 3 - Shank Square [Inch] 031, 3/8, 050, 0625, 075, 100, 125, 150, 200 | | | 4 - Insert Size 2 - IC1/4" 3 - IC3/8" 4 - IC1/2" 5 - IC5/8" | | | |
| 5 - Insert Style U - U style V - Vertical F - F Line M - Multi+ M MF - Multi+ F Line Z - Multi+ Z T - Multi+ T 14D - Multi+ 14D MG - Mega Line | 6 - Clamping C - With Clamping | | 7 - Insert Width [mm] (for IC5/8"V) 6, 8, 10 | | | | | | |
| 8 - Tool Type CQ - Drop Head FQ - Off-Set Oil - For API Inserts | 9 - RH/LH Holder None - Right Hand LH - Left Hand | | | | | | | | |

Internal Toolholders

| | | | | | | | | | | | | |
|--|---------------|--|---------------|---|---------------|--|---------------|---|--|-----------------|--|-----------------|
| C 1 | A 2 | VR 3 | C 4 | 075 5 | 6 6 | - 7 | 3 7 | 8 8 | 9 9 | 10 10 | 11 11 | 12 12 |
| 1 - Shank Type B - Anti Vibration System C - Carbide Shank S - Mini Holders | | 2 - Anvil A - Anvil Required N - No Anvil Required O - Miniature Holder | | 3 - Tool Type VR - Internal Round Shank | | 4 - Cooling C - With Coolant Channel | | | 5 - Shank Front Dia. (Inch) 0375, 050, 0625, 075, 100, 125, 150, 200, 250 6.2 mm (Mini Adjust) 8.0 mm (Mini Adjust) | | 6 - Holder Length (Mini Holders) U - Ultra Short S - Short M - Medium L - Long T - Adjustable | |
| 7 - Insert Size 5LK - IC5.0L mm 4.0K - IC4.0 mm 5.0K - IC5.0 mm 6.0K - IC6.0 mm 2 - IC1/4" 3 - IC3/8" 4 - IC1/2" 5 - IC5/8" | | 8 - Insert Style U - U style V - Vertical F - F Line M - Multi+ M MF - Multi+ F Line Z - Multi+ Z T - Multi+ T 14D - Multi+ 14D MG - Mega Line | | 9 - Clamping C - With Clamp | | 10 - Oil Field OIL - For API Inserts | | 11 - RH/LH Holder None - Right Hand LH - Left Hand | | | | |
| 12 - Serial No. 157/... (Coarse Pitch Holder) V6 (V6 Holder) | | | | | | | | | | | | |

Micro, Microscope & Adjustable Toolholders (Sleeves)

| | | | | | | | | | | | |
|---|---------------|---|------------------|---|---------------|--|----------------|--|--|---|--|
| M 1 | H 2 | C 3 | 0750 4 | - 5 | 4 5 | - 6 | 4F 6 | | | | |
| 1 - Holder Shape S - Sleeve (Double Ended) M - Microscope (Single Ended) | | 2 - Holder Type V - Adjustable Holders for Mini M - Micro (Double Ended) H - Microscope Holder HS - Microscope with Square Shank HD - Microscope with Drop Head | | 3 - Cooling C - Coolant Channel | | 4 - Shank Size [Inch] 0500, 0625, 0750, 1000 | | 5 - Holder Bore Size [mm] Micro Size 3, 4, 5, 6, 7, 8, 10 Adjustable Holders (for Mini) 6.2, 8 | | 6 - No. of Flats 4F - 4 Flats None - 2 Flats | |

V-CAP Toolholders

| | | | | | | | | | |
|-------------|-----------|----------|----------|----------|----------|-----------|------------|----------|----------|
| VCAP | 40 | - | S | E | R | 27 | 050 | - | 3 |
| 1 | 2 | | 3 | 4 | 5 | 6 | 7 | | 8 |

| | | | | |
|-----------------------------|--------------------------------|-------------------------|--------------------------------|---------------------------------|
| 1 - Holder Style | 2 - D (Polygon Size mm) | 3 - Insert Style | 4 - External / Internal | 5 - RH / LH |
| VCAP - Vargus Polygon Shank | 32, 40, 50, 63 | S - Threading | E - External I - Internal | R - Right Hand L - Left Hand |

| | | |
|---------------------------|--------------------------|------------------------|
| 6 - Cutting Radius | 7 - Tool Overhang | 8 - Insert Size |
| .47-2.17 | 1.57-4.13 | 3 - IC3/8" |

VG-Cut Toolholders for Threading

| | | | | | | |
|-----------|----------|----------|-------------|----------|----------|------------|
| VG | E | R | 2525 | - | 3 | T12 |
| 1 | 2 | 3 | 4 | | 5 | 6 |

| | | | |
|----------------------------------|---------------------------------|---------------------------------|-----------------------|
| 1 - Line Name | 2 - Application Approach | 3 - RH / LH | 4 - Shank Size |
| VG - Deep Grooving & Parting Off | E - External | R - Right Hand L - Left Hand | Width-Height |

| | |
|------------------------|--------------------------------|
| 5 - Pocket Size | 6 - Depth of Cut |
| 3 | T12 - Limit Depth of Cut 12 mm |

Mini-V Holders

| | | | | | | |
|----------|----------|-----------|----------|-----------|-----------|----------|
| C | V | 08 | - | 12 | 21 | - |
| 1 | 2 | 3 | | 4 | 5 | 6 |




| | | | | | |
|---|-------------------------|-------------------------|---|-----------------------------|---------------|
| 1 - Holder Type | 2 - Product Line | 3 - Insert Style | 4 - Shank Diameter | 5 - Tool Overhang | 6 - RH |
| C - Carbide Shank None - Steel Shank | V - Mini-V | 08, 11, 14, 16 | 06 - .236" 08 - .315" 12 - .472" 16 - .630" 0500 - 500" 0625 - .625" | .827" - 3.150" 12 - 80mm | None - RH |

Mini-V Sleeves

| | | | | |
|-----------|----------|-------------|----------|----------|
| MH | C | 0625 | - | 6 |
| 1 | 2 | 3 | | 4 |

| | | | |
|------------------------|----------------------|--|-----------------------------|
| 1 - Holder Type | 2 - Cooling | 3 - Shank Dia. | 4 - Sleeve Bore Dia. |
| MH - Microscope Holder | C - Cooling Channels | 12 - .472" 16 - .630" 0500 - .5" 0625 - 5/8" 0750 - 3/4" | .236" - .315" |

External Toolholders




Standard

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
|-------------|---------------|---------|-----------------|------|------|------|--------------|-------------|----------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | | | | | |
| 1/4" | NL031-2 | 66214 | .31 | .43 | 5.37 | .69 | SN2T | - | K2T | - | - |
| | NL050-3 | 66220 | .50 | .63 | 3.27 | .87 | SA3T | - | K3T | - | - |
| 3/8" | AL3/8-3 | 66091 | .37 | .63 | 2.45 | .76 | SA3T | SY3T | K3T | YE3 | YI3 |
| | AL050-3 | 66000 | .50 | .63 | 3.27 | .87 | | | | | |
| | AL0625-3 | 66005 | .63 | .63 | 5.00 | 1.02 | | | | | |
| | AL075-3 | 66007 | .75 | .75 | 5.00 | 1.02 | | | | | |
| | AL100-3 | 66016 | 1.00 | 1.00 | 6.00 | 1.20 | | | | | |
| | AL125-3 | 66036 | 1.25 | 1.25 | 7.00 | 1.18 | | | | | |
| 1/2" | AL100-4 | 66024 | 1.00 | 1.00 | 6.00 | 1.42 | SA4T | SY4T | K4T | YE4 | YI4 |
| | AL125-4 | 66042 | 1.25 | 1.25 | 7.00 | 1.42 | | | | | |
| | AL150-4 | 66066 | 1.50 | 1.50 | 8.00 | 1.42 | | | | | |
| 5/8" | AL100-5 | 66034 | 1.00 | 1.25 | 6.00 | 1.57 | SA5T | SY5T | K5T | YE5 | YI5 |
| | AL125-5 | 66051 | 1.25 | 1.25 | 7.00 | 1.57 | | | | | |
| | AL150-5 | 66073 | 1.50 | 1.50 | 8.00 | 1.57 | | | | | |
| | AL200-5 | 66085 | 2.00 | 2.00 | 1.00 | 1.57 | | | | | |


The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AL075-3**LH**).



Standard F-Line

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | |  |  |  |  |
|-------------|---------------|---------|-----------------|------|------|------|---|--|---|---|
| IC | RH | | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Torx Key | Anvil RH |
| 1/2" F | AL100-4F | 66660 | 1.00 | 1.00 | 6.00 | 1.30 | SA4T | SY4T | K6T | YE4F |
| | AL125-4F | 66661 | 1.25 | 1.25 | 7.00 | 1.30 | | | | |
| | AL150-4F | 66662 | 1.50 | 1.50 | 8.00 | 1.30 | | | | |



V-CAP




Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | |  |  |  |  |  |  |
|-------------|-------------------|---------|-----------------|------|------|---|---|---|---|---|---|
| IC | RH | | D mm | F | L2 | Insert Screw | Anvil Screw | Torx Key | Coolant Jet | Anvil RH | Anvil LH |
| 3/8" | VCAP32-SER22040-3 | 66717 | 32 | .87 | 1.57 | SA3T | SY3T | K3T | OD6 | YE3 | YI3 |
| | VCAP40-SER27050-3 | 66165 | 40 | 1.06 | 1.97 | | | | | | |
| | VCAP50-SER35060-3 | 66166 | 50 | 1.38 | 2.36 | | | | | | |
| | VCAP63-SER45065-3 | 66167 | 63 | 1.77 | 2.56 | | | | | | |

The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example VCAP32-SEL22040-3).

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.

External Toolholders



Standard with Clamp



(Dual System, Screw or Clamp)

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | Spare Parts | | | | | |
|-------------|---------------|---------|-----------------|------|-------|------|--------------|-------------|-------|----------|----------|----------|
| | | | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Clamp | Torx Key | Anvil RH | Anvil LH |
| 3/8" | AL075-3C | 66008 | .75 | .75 | 5.00 | 1.20 | SA3T | SY3T | C3 | K3CT | YE3 | YI3 |
| | AL100-3C | 66017 | 1.00 | 1.00 | 6.00 | 1.20 | | | | | | |
| | AL125-3C | 66031 | 1.25 | 1.25 | 7.00 | 1.20 | | | | | | |
| 1/2" | AL100-4C | 66330 | 1.00 | 1.00 | 6.00 | 1.42 | SA4T | SY4T | C4 | K4T | YE4 | YI4 |
| | AL125-4C | 66222 | 1.25 | 1.25 | 7.00 | 1.42 | | | | | | |
| | AL150-4C | 66223 | 1.50 | 1.50 | 8.00 | 1.42 | | | | | | |
| 5/8" | AL100-5C | 66327 | 1.00 | 1.25 | 6.00 | 1.57 | SA5T | SY5T | C5 | K5T | YE5 | YI5 |
| | AL125-5C | 66224 | 1.25 | 1.25 | 7.00 | 1.57 | | | | | | |
| | AL150-5C | 66225 | 1.50 | 1.50 | 8.00 | 1.57 | | | | | | |
| | AL200-5C | 66230 | 2.00 | 2.00 | 10.00 | 1.57 | | | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AL075-3CLH).

External Toolholders




Oil & Gas



Spare Parts

| Insert Size | Ordering Code | EDP No. | Thread Form | Connection No. or Size | Dimensions Inch | | | Helix Angle Deg. | | | | | |
|-------------|-----------------|---------|-----------------------|------------------------|-----------------|------|------|------------------|--------------|-------------|----------|--------------------------|----------|
| IC | RH | | | | H=H1=B=F L1 L2 | | | | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 3/8" | AL125-3 APIRD | 66527 | APIRD 8 | 2.375"-20" | 1.25 | 7.00 | 1.30 | 1 | SA3T | SY3T | K3T | YEI3 APIRD | |
| | AL150-3 APIRD | 66528 | APIRD10 | 1.05"-3.5" | 1.50 | 8.00 | 1.60 | 1 | | | | | |
| 1/2" | AL125-45BUT/API | 66532 | 5BUT, V0.038R, V0.050 | 4 1/2"-20" | 1.25 | 7.00 | 1.30 | 0 | SA4T | SY4T | K4T | YEI4-API-1P YEI4-5BUT | |
| | AL150-45BUT/API | 66533 | V0.040, V0.055 | NC10-NC77 all sizes | 1.50 | 8.00 | 1.60 | 0 | | | | | |
| 5/8" | AL125-5OIL | 66058 | V0.038R, V0.050 | NC23-NC77 all sizes | 1.25 | 7.00 | 1.60 | 1.5 | SA5T | SY5T | K5T | YE5OIL | YI5OIL |
| | AL150-5OIL | 66075 | V0.038R, V0.050 | NC23-NC77 all sizes | 1.50 | 8.00 | 1.60 | 1.5 | | | | | |

The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AL150-5OIL LH)




External Toolholders





U Style

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | |
|-------------|---------------|---------|-----------------|------|-------|------|--------------|-------------|----------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 1/2"U | AL125-4U | 66048 | 1.25 | 1.25 | 7.00 | 1.52 | SA4T | SY4T | K4T | YE4U | YI4U |
| | AL150-4U | 66247 | 1.50 | 1.50 | 8.00 | 1.52 | | | | | |
| 5/8"U | AL125-5U | 66059 | 1.25 | 1.25 | 7.00 | 1.57 | | | | | |
| | AL150-5U | 66076 | 1.50 | 1.50 | 8.00 | 1.57 | SA5T | SY5T | K5T | YE5U | YI5U |
| | AL200-5U | 66249 | 2.00 | 2.00 | 10.00 | 1.57 | | | | | |



External Toolholders




U Style with Clamp

(Dual System, Screw or Clamp)


Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | | |
|-------------|---------------|---------|-----------------|------|-------|------|--------------|-------------|-------|----------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Clamp | Torx Key | Anvil RH | Anvil LH |
| 1/2"U | AL125-4UC | 66250 | 1.25 | 1.25 | 7.00 | 1.52 | SA4T | SY4T | C4 | K4T | YE4U | YI4U |
| | AL150-4UC | 66251 | 1.50 | 1.50 | 8.00 | 1.52 | | | | | | |
| 5/8"U | AL125-5UC | 66252 | 1.25 | 1.25 | 7.00 | 1.57 | | | | | | |
| | AL150-5UC | 66253 | 1.50 | 1.50 | 8.00 | 1.57 | SA5T | SY5T | C5 | K5T | YE5U | YI5U |
| | AL200-5UC | 66256 | 2.00 | 2.00 | 10.00 | 1.57 | | | | | | |

All U Style Toolholders have a 1.5° helix angle. For other helix angles see page 199.
The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AL100-4ULH).



External Toolholders





Slim Throat

| Insert Size | | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | Spare Parts | |
|-------------|-----------|---------------|---------|-----------------|-----|------|-----|-----|------|------|-----|--------------|----------|
| IC | RH | | H=B=F | H1 | A | B1 | C | C1 | L1 | L2 | r | Insert Screw | Torx Key |
| 1/4"V | NL0315-2V | 66257 | .31 | .39 | .28 | .19 | .50 | .45 | 2.50 | .60 | .04 | SN2T | K2T |
| | NL0375-2V | 67226 | .37 | .37 | .27 | .25 | .50 | .45 | 2.75 | .60 | .04 | | |
| | NL050-2V | 67232 | .50 | .50 | .27 | .37 | .57 | .45 | 3.15 | .60 | .12 | | |
| | NL0625-2V | 67229 | .62 | .62 | .27 | .50 | .57 | .45 | 4.00 | .60 | .12 | | |
| 3/8"V | NL0625-3V | 67201 | .62 | .62 | .27 | .47 | .57 | .45 | 4.00 | 1.00 | .12 | SN3TV | K3T |
| | NL075-3V | 67203 | .75 | .75 | .27 | .60 | .65 | .45 | 5.00 | 1.20 | .12 | | |
| | NL100-3V | 67205 | 1.00 | 1.00 | .27 | .85 | .65 | .45 | 6.00 | 1.20 | .20 | | |
| | NL125-3V | 66258 | 1.25 | 1.25 | .27 | 1.20 | .65 | .45 | 7.00 | 1.20 | .20 | | |
| 1/2"V | NL150-3V | 66259 | 1.50 | 1.50 | .28 | 1.25 | .65 | .45 | 8.00 | 1.20 | .20 | SN4T | K4T |
| | NL100-4V | 66221 | 1.00 | 1.00 | .47 | .81 | .65 | .45 | 6.00 | 1.20 | .20 | | |
| | NL125-4V | 66263 | 1.25 | 1.25 | .47 | 1.07 | .65 | .45 | 7.00 | 1.20 | .20 | | |
| | NL150-4V | 66266 | 1.50 | 1.50 | .47 | 1.31 | .65 | .45 | 8.00 | 1.20 | .20 | | |

All Slim Throat toolholders have a 1.5° helix angle see page 199.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example NL0325-2VLH).

External Toolholders






Monoblock

Spare Parts

| Ordering Code | | Dimensions Inch | | | | | | | |   | |
|-----------------|------|-----------------|-----------|-------|------|------|------|-----|-------|---|----------|
| RH/LH | PW | t max | HxB | H1 | F | L1 | L2 | a | H2 | Cylindrical Holder Screw | Torx Key |
| VGER/L0625-3T12 | | | .625X.625 | .625 | .578 | | | | 0.162 | | |
| VGER/L075-3T12 | .118 | .472 | .750X.750 | .750 | .703 | 5.00 | 1.38 | .09 | - | SM4,0X18-T20 | K6T |
| VGER/L100-3T12 | | | 1.00X1.00 | 1.000 | .953 | | | | - | | |

External Toolholders




Reinforced Monoblock

Spare Parts

| Ordering Code | | Dimensions Inch | | | | | | | |   | |
|-------------------|------|-----------------|-----------|-------|------|------|------|-----|--------------------------|---|--|
| RH/LH | PW | D max | HxB | H1 | F | L1 | L2 | a | Cylindrical Holder Screw | Torx Key | |
| VGER/L0625-3T12PH | | 1.02 | .625X.625 | .625 | .578 | | .87 | | | | |
| VGER/L075-3T21PH | .118 | 1.65 | .750X.750 | .750 | .703 | 5.00 | 1.18 | .09 | SCM4X14 | KT-15 | |
| VGER/L100-3T21PH | | 1.65 | 1.00X1.00 | 1.000 | .953 | | 1.18 | | | | |

All VG-Cut tooling have 1.5° helix angle.

External Toolholders



V Style


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | |
|-------------|------------------|---------|-----------------|------|------|------|------|--------------|----------|
| IC | RH | | H=H1=B | B1 | F | L1 | L2 | Insert Screw | Torx key |
| 5/8"V | NL125-5V-6 | 67213 | 1.25 | 1.00 | 1.25 | 7.00 | 1.57 | SN6T | K6T |
| | NL125-5V-8 | 67214 | 1.25 | 1.00 | 1.33 | 7.00 | 1.57 | | |
| | NL125-5V-10 | 67212 | 1.25 | 1.00 | 1.40 | 7.00 | 1.57 | | |
| | NL125-5V-10ABUT* | 66382 | 1.25 | 1.00 | 1.40 | 7.00 | 1.57 | | |
| | NL150-5V-6 | 66383 | 1.50 | 1.24 | 1.50 | 8.00 | 1.57 | | |
| | NL150-5V-8 | 66384 | 1.50 | 1.24 | 1.63 | 8.00 | 1.57 | | |
| | NL150-5V-10 | 67215 | 1.50 | 1.24 | 1.65 | 8.00 | 1.57 | | |
| | NL150-5V-10ABUT* | 66385 | 1.50 | 1.24 | 1.65 | 8.00 | 1.57 | | |

All V Style toolholders have a 1° helix angle.

The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example NL125-5V-6 LH).

* To be used only with inserts 5VER2.5ABUT...

External Toolholders





Z+ Style

| Insert Size | Ordering Code | Dimensions Inch | | | | | Spare Parts | | | | |
|-------------|---------------|-----------------|------|------|-------|--------------|-------------|----------|----------|----------|------|
| IC | RH | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH | |
| 1/2"Z | AL125-4Z | 66386 | 1.25 | 1.25 | 7.00 | 1.52 | SA4T | SY4T | K4T | YE4Z | YI4Z |
| | AL150-4Z | 66387 | 1.50 | 1.50 | 8.00 | 1.52 | | | | | |
| 5/8"Z | AL125-5Z | 66388 | 1.25 | 1.25 | 7.00 | 1.57 | SA5T | SY5T | K5T | YE5Z | YI5Z |
| | AL150-5Z | 66389 | 1.50 | 1.50 | 8.00 | 1.57 | | | | | |
| | AL200-5Z | 66390 | 2.00 | 2.00 | 10.00 | 1.57 | | | | | |

All Z Style toolholders have a 1.5° helix angle.



External Toolholders




M+ Style


Spare Parts



| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
|-------------|---------------|---------|-----------------|------|-------|------|--------------|-------------|----------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | | | | | |
| 5/8" M | AL125-5M | 66391 | 1.25 | 1.25 | 7.00 | 1.57 | SA5T | SY5T | K5T | YE5M | YI5M |
| | AL150-5M | 66392 | 1.50 | 1.50 | 8.00 | 1.57 | | | | | |
| | AL200-5M | 66393 | 2.00 | 2.00 | 10.00 | 1.57 | | | | | |



External Toolholders



F-Line M+ Style


Spare Parts



| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | Insert Screw | Anvil Screw | Torx Key | Anvil RH |
|-------------|---------------|---------|-----------------|------|------|------|--------------|-------------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | | | | |
| 1/2" F | AL100-4MF | 66714 | 1.00 | 1.00 | 6.10 | 1.30 | SA4T | SY4T | K6T | YE4M2F |
| | AL125-4MF | 66663 | 1.25 | 1.25 | 7.00 | 1.30 | | | | |
| | AL150-4MF | 66664 | 1.50 | 1.50 | 8.00 | 1.30 | | | | |



The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.



T+ Style


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | |
|-------------|---------------|---------|-----------------|------|------|------|
| IC | RH | H=H1=B | F | L1 | L2 | |
| 1/2" T | AL100-4T | 66334 | 1.00 | 1.08 | 6.00 | 1.20 |
| | AL125-4T | 66394 | 1.25 | 1.33 | 7.00 | 1.20 |
| | AL150-4T | 66395 | 1.50 | 1.58 | 8.00 | 1.20 |

Spare Parts



| Insert Screw | Anvil Screw | Insert Torx Key | Anvil Torx Key | Anvil RH/LH |
|--------------|-------------|-----------------|----------------|-------------|
| SA4T | SY4K2 | K4T | K2 | Y4T |

All T Style toolholders have a 0° helix angle.



14D Standard

| Insert Size | Ordering Code | Dimensions Inch | | | |
|-------------|---------------|-----------------|------|------|------|
| IC | RH | H=H1=B | F | L1 | L2 |
| 14D | AL100-14D | 1.00 | 1.75 | 5.80 | 1.00 |
| | AL125-14D | 1.25 | 1.50 | 7.00 | 1.00 |
| | AL150-14D | 1.50 | 1.50 | 8.00 | 1.25 |




Spare Parts



| Insert Screw | Anvil Screw & Washer | Torx Key | Anvil Key |
|--------------|----------------------|----------|-----------|
| SA5T | M4x6(14D) | KT15 | K5T |

14D holders are supplied without anvils. For specific applications, please use the anvils indicated in the table on page 199.

External Toolholders






Off-Set Qualified (FQ)

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | |
|-------------|---------------|---------|-----------------|------|------|------|--------------|-------------|----------|----------|----------|
| IC | RH | | H=H1=B | F | L1 | L2 | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 3/8" | AL075-3FQ | 66011 | .75 | 1.00 | 6.00 | 1.00 | SA3T | SY3T | K3T | YE3 | YI3 |
| | AL100-3FQ | 66020 | 1.00 | 1.25 | 6.00 | 1.00 | | | | | |
| | AL125-3FQ | 66039 | 1.25 | 1.50 | 6.00 | 1.20 | | | | | |
| 1/2" | AL100-4FQ | 66027 | 1.00 | 1.25 | 6.00 | 1.20 | SA4T | SY4T | K4T | YE4 | YI4 |
| | AL125-4FQ | 66045 | 1.25 | 1.50 | 6.00 | 1.20 | | | | | |
| 5/8" | AL125-5FQ | 66053 | 1.25 | 1.50 | 6.00 | 1.20 | SA5T | SY5T | K5T | YE5 | YI5 |

External Toolholders




Drop Head-Qualified (CQ)



Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | | | |
|-------------|---------------|---------|-----------------|------|------|------|------|------|--------------|-------------|----------|----------|----------|
| IC | RH | | H=B | F | L1 | L2 | L3 | H1 | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 3/8" | AL075-3CQ | 66009 | .75 | 1.00 | 5.00 | .88 | 1.50 | .69 | SA3T | SY3T | K3T | YE3 | YI3 |
| | AL100-3CQ | 66018 | 1.00 | 1.25 | 6.00 | .88 | 1.50 | .87 | | | | | |
| | AL125-3CQ | 66037 | 1.25 | 1.50 | 7.00 | .88 | 1.50 | .87 | | | | | |
| 1/2" | AL100-4CQ | 66025 | 1.00 | 1.25 | 6.00 | 1.13 | 1.50 | .87 | SA4T | SY4T | K4T | YE4 | YI4 |
| | AL125-4CQ | 66043 | 1.25 | 1.50 | 7.00 | 1.13 | 1.50 | .87 | | | | | |
| 5/8" | AL125-5CQ | 66052 | 1.25 | 1.50 | 7.00 | 1.25 | 1.69 | 1.00 | SA5T | SY5T | K5T | YE5 | YI5 |

The above toolholders have a 1.5° helix angle. For other helix angles see page 199.
The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AL075-3FQLH).




External + Internal Toolholders




Miniature Square Shank*

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Min. Bore Dia. | Spare Parts | |
|-------------|---------------|---------|-----------------|------|----------|-----|------|----------------|---|---|
| | | | A | L | L1 (max) | F | Inch | |  |  |
| 1/4" | RH | | | | | | | | Insert Screw | Torx Key |
| | OV8-2 | 66282 | .31 | 3.94 | 1.00 | .47 | 1.15 | SN2T | K2T | |
| | OV10-2 | 66280 | .39 | 3.94 | 1.00 | .55 | 1.42 | | | |



External + Internal Toolholders




Miniature Round Shank*

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | Min. Bore Dia. | Spare Parts | |
|-------------|---------------|---------|-----------------|------|----------|-----|-----|-----|------|----------------|---|---|
| | | | A | L | L1 (max) | D | D1 | F | Inch | |  |  |
| 1/4" | RH | | | | | | | | | | | |
| | OVR12-2 | 66272 | .45 | 3.94 | .98 | .47 | .39 | .29 | .51 | SN2T | K2T | |
| | OVR15-2 | 66274 | .56 | 3.94 | 1.26 | .59 | .51 | .35 | .63 | | | |
| | OVR16D-2 | 66217 | .60 | 3.94 | 1.26 | .63 | .51 | .35 | .63 | | | |


* Miniature square and round toolholders are designed for use on automatic lathes for the optical and other precision industries. They can be used for both external and internal threading, as follows:

| | | | | |
|---------------|----|----|----|----|
| Thread | ER | EL | IR | IL |
| Insert | ER | EL | IR | IL |
| Holder | LH | RH | RH | LH |

Miniature toolholders have a 0.5° helix angle.
The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example OV8-2LH).



Internal Toolholders




Standard

Spare Parts

| Insert Size | Ordering Code | Dimensions Inch | | | | | | | | Min. Bore Dia. | Spare Parts | | | | |
|-------------|---------------|-----------------|------|-------|----------|------|------|------|------|----------------|--------------|-------------|----------|----------|----------|
| IC | RH | EDP No. | A | L | L1 (max) | D | D1 | F | Inch | | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 1/4" | NVRC0375D-2 | 66234 | .67 | 7.00 | 1.00 | .75 | .37 | .28 | .50 | | SN2T | - | K2T | - | - |
| | NVRC050-2 | 66236 | .67 | 7.00 | 1.25 | .75 | .50 | .37 | .65 | | | | | | |
| 3/8" | NVRC050-3 | 66238 | .67 | 7.00 | 1.25 | .75 | .62 | .40 | .67 | | SN3T | - | K3T | - | - |
| | NVRC0625-3 | 66240 | .67 | 7.00 | 1.50 | .75 | .62 | .46 | .80 | | | | | | |
| | NVRC0625D-3 | 66242 | .58 | 6.00 | 2.48 | .625 | .62 | .46 | .80 | | | | | | |
| | AVRC075-3 | 66098 | .67 | 7.00 | 3.00 | .75 | .75 | .51 | .90 | | | | | | |
| | AVRC100-3 | 66100 | 1.12 | 10.00 | 2.50 | 1.25 | 1.00 | .65 | 1.20 | | | | | | |
| 3/8" | AVRC100D-3 | 66104 | .89 | 8.00 | 4.00 | 1.00 | 1.00 | .65 | 1.20 | | SA3T | SY3T | K3T | YI3 | YE3 |
| | AVRC125-3 | 66108 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .77 | 1.45 | | | | | | |
| | AVRC150-3 | 66114 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | .90 | 1.65 | | | | | | |
| | AVRC200-3 | 66294 | 1.80 | 14.00 | 8.00 | 2.00 | 1.99 | 1.10 | 2.22 | | | | | | |
| 1/2" | NVRC075-4 | 66244 | .67 | 7.00 | 3.00 | .75 | .75 | .59 | 1.00 | | SN4T | - | K4T | - | - |
| | AVRC100-4 | 66102 | 1.12 | 10.00 | 2.50 | 1.25 | 1.00 | .71 | 1.25 | | | | | | |
| | AVRC100D-4 | 66106 | .89 | 8.00 | 4.00 | 1.00 | 1.00 | .71 | 1.25 | | SA4T | SY4T | K4T | YI4 | YE4 |
| | AVRC125-4 | 66110 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .85 | 1.50 | | | | | | |
| | AVRC150-4 | 66116 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | .98 | 1.75 | | | | | | |
| 5/8" | AVRC200-4 | 66715 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.22 | 2.17 | | | | | | |
| | AVRC125-5 | 66112 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .88 | 1.55 | | SN5T | SY5T | K5T | YI5 | YE5 |
| | AVRC150-5 | 66118 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.00 | 1.80 | | | | | | |
| | AVRC200-5 | 66120 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.25 | 2.30 | | SA5T | SY5T | K5T | YI5 | YE5 |
| 5/8" | AVRC250-5 | 66123 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.50 | 2.80 | | | | | | |

- The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
- Toolholders with prefix "N" cannot be used with an anvil.
- Holders with coolant channel are available as standard (Example NVRC0375D-2).
- The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example NVR0375D-2**LH**).




Standard F-Line

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | Spare Parts | | | |
|-------------|---------------|---------|-----------------|----------|------|------|------|------|----------------|-------------|----------|----------|------|
| IC | RH | A | L | L1 (max) | D | D1 | F | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH | |
| 1/2" F | AVRC100-4F | 66665 | 1.12 | 10.0 | 2.50 | 1.25 | 1.00 | .64 | 1.25 | SA4T | SY4T | K6T | Y14F |
| | AVRC100D-4F | 66672 | .89 | 8.0 | 4.00 | 1.00 | 1.00 | .64 | 1.25 | | | | |
| | AVRC125-4F | 66666 | 1.12 | 10.0 | 5.00 | 1.25 | 1.25 | .76 | 1.50 | | | | |
| | AVRC150-4F | 66667 | 1.34 | 12.0 | 6.00 | 1.50 | 1.50 | .90 | 1.75 | | | | |
| | AVRC200-4F | 66716 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.22 | 2.17 | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.




V6 Style

Spare Parts




| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | Spare Parts | |
|-------------|---------------|---------|-----------------|----------|------|------|-----|------|----------------|-------------|-----|
| IC | RH | A | L | L1 (max) | D | D1 | F | Inch | Insert Screw | Torx Key | |
| 3/8" V6 | NVRC050-3V6 | 66231 | .67 | 7.00 | 1.25 | .75 | .50 | .40 | .67 | SN3TM | K3T |
| | NVRC0625-3V6 | 66232 | .67 | 7.00 | 1.50 | .75 | .62 | .46 | .80 | | |
| | NVRC0625D-3V6 | 66233 | .58 | 6.00 | 2.48 | .625 | .62 | .46 | .80 | | |

* V6 inserts cannot be used on standard internal toolholders without anvil. For this purpose you must use one of these special V6 toolholders. The above toolholders have a 1.5° helix angle.



Internal Toolholders




V-CAP

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Min. Bore Dia. | Spare Parts | | | | |
|-------------------|-------------------|---------|-----------------|------|------|------|----------|----------------|--------------|-------------|----------|----------|----------|
| IC | RH | | D1 | D mm | F | L2 | L1 (max) | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 3/8" | VCAP40-SIR12060-3 | 66169 | .61 | 40 | .47 | 2.36 | 1.46 | .79 | SN3T | - | K3T | - | - |
| | VCAP40-SIR14060-3 | 66170 | .73 | | .55 | 2.36 | 1.50 | .98 | | | | | |
| | VCAP40-SIR17070-3 | 66171 | .96 | | .67 | 2.76 | 1.89 | 1.26 | SA3T | SY3T | K3T | Y13 | YE3 |
| | VCAP40-SIR22090-3 | 66172 | 1.26 | .87 | 3.54 | 2.72 | 1.57 | | | | | | |
| | VCAP40-SIR27080-3 | 66175 | 1.56 | 1.06 | 3.15 | 2.36 | 1.97 | | | | | | |
| | VCAP50-SIR12060-3 | 66176 | .61 | 50 | .47 | 2.36 | 1.38 | .79 | SN3T | - | K3T | - | - |
| | VCAP50-SIR14060-3 | 66177 | .73 | | .55 | 2.36 | 1.42 | .98 | | | | | |
| | VCAP50-SIR17070-3 | 66178 | .96 | | .67 | 2.76 | 1.85 | 1.26 | SA3T | SY3T | K3T | Y13 | YE3 |
| | VCAP50-SIR22090-3 | 66718 | 1.26 | | .87 | 3.54 | 2.68 | 1.57 | | | | | |
| | VCAP50-SIR27105-3 | 66180 | 1.57 | | 1.06 | 4.13 | 3.31 | 1.97 | | | | | |
| | VCAP63-SIR14070-3 | 66181 | .73 | | 63 | .55 | 2.76 | 1.65 | .98 | | | | |
| | VCAP63-SIR17075-3 | 66182 | .96 | .67 | | 2.95 | 1.89 | 1.26 | SA3T | SY3T | K3T | Y13 | YE3 |
| VCAP63-SIR22090-3 | 66184 | 1.26 | .87 | 3.54 | | 2.52 | 1.57 | | | | | | |
| VCAP63-SIR27105-3 | 66168 | 1.57 | 1.06 | 4.13 | | 3.15 | 1.97 | | | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example VCAP40-SIR12060-3).

Internal Toolholders






Standard for Coarse Pitch

| Insert Size | | | | | | | | | | | Ordering Code | | Dimensions Inch | | | | F to Insert | Holder Helix | Spare Parts | |
|-------------|-------------------|---------|---------------------|---------|------|-------|----------|------|------|------|---------------|--------------|-----------------|--|--|--|-------------|--------------|-------------|--|
| IC | RH | EDP No. | LH | EDP No. | A | L | L1 (max) | D | D1 | Inch | Deg. | Insert Screw | Torx Key | | | | | | | |
| 1/4" | NVRC040-2-157/001 | 66297 | NVRC040-2LH-157/025 | 66717 | .67 | 7.00 | .98 | .75 | .40 | .26 | 3.0 | SN2T | K2T | | | | | | | |
| | NVRC044-3-157/005 | 66301 | NVRC044-3LH-157/029 | 66718 | .67 | 7.00 | 1.00 | .75 | .44 | .33 | 4.5 | SN3TM | K3T | | | | | | | |
| 3/8" | NVRC050-3-157/006 | 66302 | NVRC050-3LH-157/030 | 66685 | .67 | 7.00 | 1.26 | .75 | .51 | .36 | 4.0 | SN3T | K3T | | | | | | | |
| | NVRC050-3-157/016 | 66322 | NVRC050-3LH-157/035 | 66686 | .67 | 7.00 | 1.26 | .75 | .54 | .35 | 2.5 | | | | | | | | | |
| 1/2" | NVRC067-4-157/007 | 66303 | NVRC067-4LH-157/022 | 66719 | .67 | 7.00 | 1.57 | .75 | .66 | .45 | 4.0 | SN4TM | K4T | | | | | | | |
| | NVRC067-4-157/039 | 66721 | NVRC067-4LH-157/040 | 66720 | .67 | 7.00 | 1.60 | .75 | .65 | .53 | 4.0 | | | | | | | | | |
| | NVRC075-4-157/008 | 66304 | NVRC075-4LH-157/017 | 66687 | .67 | 7.00 | 1.97 | .75 | .77 | .49 | 3.5 | SN4T | K4T | | | | | | | |
| | NVRC075-4-157/009 | 66305 | NVRC075-4LH-157/021 | 66308 | .67 | 7.00 | 1.97 | .75 | .77 | .49 | 3.0 | | | | | | | | | |
| 5/8" | NVRC100-5-157/012 | 66362 | NVRC100-5LH-157/031 | 66688 | 1.12 | 10.00 | 2.36 | 1.25 | .98 | .66 | 3.3 | SN5TM | K5T | | | | | | | |
| | NVRC110-5-157/010 | 66306 | NVRC110-5LH-157/023 | 66323 | 1.12 | 10.00 | 1.97 | 1.25 | 1.10 | .70 | 3.5 | | | | | | | | | |

U Style for Coarse Pitch

| Insert Size | | | | | | | | | | | Ordering Code | | Dimensions Inch | | | | F to Insert | Holder Helix | Spare Parts | |
|-------------|-----------------------|---------|-------------------------|---------|------|-------|----------|------|------|------|---------------|--------------|-----------------|--|--|--|-------------|--------------|-------------|--|
| IC | RH | EDP No. | LH | EDP No. | A | L | L1 (max) | D | D1 | Inch | Deg. | Insert Screw | Torx Key | | | | | | | |
| 6.0U | NVRC032-6.0KU-157/003 | 66299 | NVRC032-6.0KULH-157/027 | 66722 | .67 | 7.00 | .94 | .75 | .31 | .23 | 4.0 | SN6MTN | KIP6 | | | | | | | |
| 1/4"U | NVRC039-2U-157/004 | 66300 | NVRC039-2ULH-157/028 | 66723 | .67 | 7.00 | 1.26 | .75 | .39 | .29 | 4.0 | SM2T8 | K2T | | | | | | | |
| | NVRC044-2U-157/002 | 66298 | NVRC044-2ULH-157/026 | 66724 | .67 | 7.00 | 1.26 | .75 | .44 | .29 | 3.0 | | | | | | | | | |
| 3/8"U | NVRC044-3U-157/020 | 66420 | NVRC044-3ULH-157/038 | 66725 | .67 | 7.00 | 1.26 | .75 | .43 | .32 | 4.5 | | | | | | | | | |
| | NVRC055-3U-157/018 | 66396 | NVRC055-3ULH-157/036 | 66726 | .67 | 7.00 | 1.50 | .75 | .53 | .39 | 4.5 | SN3TM | K3T | | | | | | | |
| | NVRC059-3U-157/019 | 66363 | NVRC059-3ULH-157/037 | 66433 | .67 | 7.00 | 1.50 | .75 | .61 | .43 | 4.0 | | | | | | | | | |
| 1/2"U | NVRC075-4U-157/011 | 66329 | NVRC075-4ULH-157/024 | 66430 | .67 | 7.00 | 1.57 | .75 | .76 | .54 | 4.0 | SN4T | K4T | | | | | | | |
| | NVRC100-4U-157/013 | 66360 | NVRC100-4ULH-157/032 | 66689 | 1.12 | 10.00 | 2.36 | 1.25 | .98 | .69 | 3.5 | | | | | | | | | |
| | NVRC125-4U-157/014 | 66136 | NVRC125-4ULH-157/033 | 66690 | 1.12 | 10.00 | 2.36 | 1.25 | 1.17 | .74 | 3.3 | SA4T | K4T | | | | | | | |
| 5/8"U | NVRC125-5U-157/015 | 66361 | NVRC125-5ULH-157/034 | 66691 | 1.12 | 10.00 | 2.36 | 1.25 | 1.24 | .83 | 3.2 | SN5T | K5T | | | | | | | |

Internal Toolholders




Standard with Clamp

(Dual System, Screw or Clamp)

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | Min. Bore Dia. | Spare Parts | | | | | |
|-------------|---------------|---------|-----------------|-------|-------|------|----------|------|------|----------------|-------------|------|--------------|-------------|-------|----------|
| | | | IC | RH | A | L | L1 (max) | D | D1 | | F | Inch | Insert Screw | Anvil Screw | Clamp | Torx Key |
| 3/8" | AVR075-3C | 66130 | .67 | 7.00 | 3.00 | .75 | .75 | .51 | .94 | | | | | | | |
| | AVR100-3C | 66397 | 1.12 | 10.00 | 2.50 | 1.25 | 1.00 | .65 | 1.20 | | | | | | | |
| | AVR100D-3C | 66132 | .90 | 8.00 | 4.00 | 1.00 | 1.00 | .65 | 1.20 | SA3T | SY3T | C3 | K3CT | YI3 | YE3 | |
| | AVR125-3C | 66398 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .77 | 1.45 | | | | | | | |
| 1/2" | AVR150-3C | 66399 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | .90 | 1.65 | | | | | | | |
| | AVR100-4C | 66400 | 1.12 | 10.00 | 2.50 | 1.25 | 1.00 | .71 | 1.25 | | | | | | | |
| | AVR100D-4C | 66401 | .90 | 8.00 | 4.00 | 1.00 | 1.00 | .71 | 1.25 | SA4T | SY4T | C4 | K4T | YI4 | YE4 | |
| | AVR125-4C | 66402 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .85 | 1.50 | | | | | | | |
| 5/8" | AVR150-4C | 66403 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | .98 | 1.75 | | | | | | | |
| | AVR125-5C | 66404 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .88 | 1.55 | SN5T | SY5T | C5 | K5T | YI5 | YE5 | |
| | AVR150-5C | 66405 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.00 | 1.80 | | | | | | | |
| | AVR200-5C | 66406 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.25 | 2.30 | SA5T | SY5T | C5 | K5T | YI5 | YE5 | |
| | AVR250-5C | 66407 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.50 | 2.80 | | | | | | | |

- The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
- Holders with coolant channel available as standard (Example AVR075-3C).
- The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AVR075-3CLH).




U Style


Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | Spare Parts | | | | |
|-------------|---------------|---------|-----------------|-------|-------|------|----------|------|----------------|-------------|------|------|--------------|-------------|
| | | | IC | RH | A | L | L1 (max) | D | | D1 | F | Inch | Insert Screw | Anvil Screw |
| 1/2"U | AVR125-4U | 66421 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | 1.01 | 1.65 | SA4T | SY4T | K4T | YI4U | YE4U |
| | AVR150-4U | 66156 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.12 | 1.90 | SA4T | SY4T | K4T | YI4U | YE4U |
| 5/8"U | NVR125-5U | 66264 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .98 | 1.65 | SN5T | - | K5T | - | - |
| | AVR150-5U | 66162 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.13 | 1.90 | SA5T | SY5T | K5T | YI5U | YE5U |
| | AVR200-5U | 66179 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.37 | 2.40 | SA5T | SY5T | K5T | YI5U | YE5U |
| | AVR250-5U | 66187 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.31 | 2.90 | SA5T | SY5T | K5T | YI5U | YE5U |

- The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
- Holders with coolant channel available as standard (Example AVRC125-4U).
- The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AVR125-4ULH).



Internal Toolholders




U style with Clamp

(Dual System, Screw or Clamp)


Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | Spare Parts | | | | | |
|-------------|---------------|---------|-----------------|-------|-------|------|----------|------|----------------|-------------|------|------|--------------|-------------|-------|
| | | | IC | RH | A | L | L1 (max) | D | | D1 | F | Inch | Insert Screw | Anvil Screw | Clamp |
| 1/2"U | AVR125-4UC | 66408 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | 1.01 | 1.65 | SA4T | SY4T | C4 | K4T | YI4U | YE4U |
| | AVR150-4UC | 66409 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.12 | 1.90 | | | | | | |
| 5/8"U | AVR150-5UC | 66410 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.13 | 1.90 | SA5T | SY5T | C5 | K5T | YI5U | YE5U |
| | AVR200-5UC | 66411 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.37 | 2.40 | | | | | | |
| | AVR250-5UC | 66412 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.61 | 2.90 | | | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.



Internal Toolholders



V Style

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | W | Spare Parts | |
|-------------|---------------|---------|-----------------|-------|-------|------|----------|------|------|-------------|--------------|
| | | | IC | RH | A | L | L1 (max) | D | | F | Insert Screw |
| 5/8"V | NVR125-5V | 67219 | 1.20 | 10.00 | 5.00 | 1.25 | .82 | .256 | SN6T | K6T | |
| | NVR150-5V | 67220 | 1.34 | 12.00 | 6.00 | 1.50 | 1.08 | | | | |
| | NVR200-5V | 67222 | 1.80 | 14.00 | 8.00 | 2.00 | 1.33 | | | | |
| | NVR250-5V | 67223 | 2.26 | 16.00 | 10.00 | 2.50 | 1.58 | | | | |


The above toolholders have a 1.0° helix angle.

Minimum Bore Diameter

| | Pitch mm | 6.0 ISO | 8.0 ISO | 10.0 ISO |
|-----------|-----------|---------|---------|----------|
| Holder | Pitch TPI | 4 UN | 3 UN | 2.5 W |
| NVR125-5V | | 1.62 | 1.62 | 1.62 |
| NVR150-5V | | 1.98 | 2.17 | 2.44 |
| NVR200-5V | | 2.37 | 2.37 | 2.44 |
| NVR250-5V | | 2.76 | 2.68 | 2.68 |

The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example AVR125-4UCLH). Holders with coolant channel available as standard (Example AVRC125-4UC).


Internal Toolholders



Z+ Style

| Z+ Style | | | | | | | | | Spare Parts  | | | | | |
|-------------|---------------|---------|-----------------|-------|----------|------|------|------|---|--|---|---|---|---|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. |  |  |  |  |  |
| IC | RH | | A | L | L1 (max) | D | D1 | F | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 1/2"Z | AVR125-4Z | 66413 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | 1.01 | 1.65 | SA4T | SY4T | K4T | Y14Z | YE4Z |
| | AVR150-4Z | 66414 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.12 | 1.90 | | | | | |
| 5/8"Z | NVR125-5Z | 66415 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .98 | 1.65 | SN5T | - | K5T | - | - |
| | AVR150-5Z | 66416 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.13 | 1.90 | | | | | |
| | AVR200-5Z | 66417 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.37 | 2.40 | SA5T | SY5T | K5T | Y15Z | YE5Z |
| | AVR250-5Z | 66418 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.61 | 2.90 | | | | | |

Internal Toolholders





M+ Style

| M+ Style | | | | | | | | | Spare Parts  | | | | | |
|-------------|---------------|---------|-----------------|-------|----------|------|------|------|---|--|---|---|---|---|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. |  |  |  |  |  |
| IC | RH | | A | L | L1 (max) | D | D1 | F | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 5/8"M | AVR125-5M | 66127 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .88 | 1.55 | SN5T | SY5T | K5T | Y15M | YE5M |
| | AVR150-5M | 66161 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | 1.00 | 1.80 | | | | | |
| | AVR200-5M | 66419 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.25 | 2.30 | SA5T | SY5T | K5T | Y15M | YE5M |
| | AVR250-5M | 66422 | 2.26 | 16.00 | 10.00 | 2.50 | 2.50 | 1.50 | 2.80 | | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.
Holders with coolant channel available as standard (Example AVR125-4Z).

Internal Toolholders



F-Line M+ Style




Spare Parts



| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | | | | |
|-------------|---------------|---------|-----------------|-------|----------|------|------|------|----------------|--------------|-------------|----------|----------|
| IC | RH | | A | L | L1 (max) | D | D1 | F | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH |
| 1/2" F | AVRC100-4MF | 66665 | 1.12 | 10.00 | 2.50 | 1.25 | 1.00 | .64 | 1.25 | SA4T | SY4T | K6T | Y14M2F |
| | AVRC100D-4MF | 66672 | .89 | 8.00 | 4.00 | 1.00 | 1.00 | .64 | 1.25 | | | | |
| | AVRC125-4MF | 66666 | 1.12 | 10.00 | 5.00 | 1.25 | 1.25 | .76 | 1.50 | | | | |
| | AVRC150-4MF | 66667 | 1.34 | 12.00 | 6.00 | 1.50 | 1.50 | .90 | 1.75 | | | | |
| | AVRC200-4MF | 66713 | 1.80 | 14.00 | 8.00 | 2.00 | 2.00 | 1.22 | 2.17 | | | | |

The above toolholders have a 1.5° helix angle. For other helix angles, see page 199.

Internal Toolholders




T+ Style

Spare Parts




| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Min. Bore Dia. | | | | | |
|-------------|---------------|---------|-----------------|-------|----------|------|------|------|----------------|-------------|----------|----------------|-------------|--|
| IC | RH | | A | L | L1 (max) | D | F | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil Torx Key | Anvil RH/LH | |
| 1/2" T | AVR150-4T | 66423 | 1.34 | 12.00 | 6.00 | 1.50 | .88 | 2.40 | SA4T | SY4K2 | K4T | K2 | Y4T | |
| | AVR200-4T | 66424 | 1.80 | 14.00 | 8.00 | 2.00 | 1.13 | 2.75 | | | | | | |
| | AVR250-4T | 66425 | 2.26 | 16.00 | 10.00 | 2.50 | 1.38 | 3.25 | | | | | | |

All toolholders have a 0° helix angle.
 Holders with coolant channel available as standard (Example: AVR150-4T).




Internal Toolholders




14D Standard

| Insert Size | | Ordering Code | | | | | Dimensions Inch | | Min. Bore Dia. | Spare Parts | | | |
|-------------|-------------|---------------|-------|----------|------|------|-----------------|--|----------------|----------------------|----------|-----------|--|
| IC | RH | A | L | L1 (max) | D | F | Inch | | Insert Screw | Anvil Screw & Washer | Torx Key | Anvil Key | |
| 14D | AVRC150-14D | 1.34 | 12.00 | 6.00 | 1.50 | 1.03 | 2.15 | | SA5T | M4x6(14D) | K5T | KT15 | |
| | AVRC200-14D | 1.80 | 12.00 | 8.00 | 2.00 | 1.00 | 2.15 | | | | | | |



Internal Toolholders






14D Standard with Clamp

| Insert Size | | Ordering Code | | | | | Dimensions Inch | | Min. Bore Dia. | Spare Parts | | | | |
|-------------|--------------|---------------|-------|----------|------|------|-----------------|--|----------------|----------------------|-------|----------|-----------|--|
| IC | RH | A | L | L1 (max) | D | F | Inch | | Insert Screw | Anvil Screw & Washer | Clamp | Torx Key | Anvil Key | |
| 14D | AVRC150-14DC | 1.34 | 12.00 | 6.00 | 1.50 | 1.03 | 2.15 | | SA5T | M4x6(14D) | C5 | K5T | KT15 | |
| | AVRC200-14DC | 1.80 | 12.00 | 8.00 | 2.00 | 1.00 | 2.15 | | | | | | | |

14D holders are supplied without anvils. For specific applications, please use the anvils indicated in the table on page 200.

Internal Toolholders



Thread Turning Toolholders


Oil & Gas

Spare Parts

| Insert Size | Ordering Code | EDP No. | Thread Form | Connection No. or Size | Dimensions Inch | | | | Helix Angle Deg. |  | | | | | | | |
|-------------|--------------------|---------|---|-----------------------------------|-----------------|-------|------|------|------------------|---|-------------|----------|--------------------------|--|--|--|--|
| | | | | | A | L | D | F | | Insert Screw | Anvil Screw | Torx Key | Anvil RH | | | | |
| | RH | | | | | | | | | | | | | | | | |
| 3/8" | AVRC100-3 APIRD | 66529 | APIRD 8 APIRD 10 | 2.375"-20" 1.315"-3.5" | 1.12 | 10.00 | 1.00 | .65 | 1 | | | | | | | | |
| | AVRC125-3 APIRD | 66530 | APIRD 8 APIRD 10 | 2.375"-20" 1.66"-3.5" | 1.12 | 10.00 | 1.25 | .77 | 1 | SA3T | SY3T | K3T | YEI3-APIRD | | | | |
| | AVRC150-3 APIRD | 66531 | APIRD 8 APIRD 10 | 2.375"-20" 1.9"-3.5" | 1.34 | 12.00 | 1.50 | .90 | 0 | | | | | | | | |
| 1/2" | AVRC150-4 5BUT/API | 66534 | 5BUT, V0.038R, V0.050, V0.040, V0.055 | 4 1/2"-20" NC10-NC77 all sizes | 1.34 | 12.00 | 1.50 | .98 | 0 | SA4T | SY4T | K4T | YEI4-API-1P YEI4-5BUT | | | | |
| | AVR200-5OIL | 66426 | V0.038R | NC23-NC38 | 1.80 | 12.00 | 2.00 | .90 | 1.5 | | | | | | | | |
| 5/8" | AVRC200-5OIL | 66122 | V0.038R | NC23-NC38 | | | | | | SA5T | SY5T | K5T | YI5OIL | | | | |
| | AVR300-5OIL | 66188 | V0.050R | NC40-NC77 | 2.68 | 16.00 | 3.00 | 1.50 | 1.5 | | | | | | | | |
| | AVRC300-5OIL | 66125 | V0.050R | NC40-NC77 | | | | | | | | | | | | | |

Toolholders ordered with an internal coolant channel have an internal BSP 1/2" thread for connection to the flexible coolant pipe.

Internal Toolholders




Standard with Carbide Shank

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Min. Bore Dia. |  | | | | |
|-------------|---------------|---------|-----------------|-----|-----|-------|----------|----------------|--|-------------|----------|----------|----------|
| IC | RH | | D | A | F | L | L1 (Max) | Inch | Insert Screw | Anvil Screw | Torx Key | Anvil RH | Anvil LH |
| 1/4" | CNVRC0375-2 | 66196 | .37 | .35 | .28 | 6.00 | 2.22 | .50 | SN2T | - | K2T | - | - |
| | CNVRC050-2 | 66197 | .50 | .48 | .35 | 7.00 | 3.00 | .60 | | | | | |
| 3/8" | CNVRC050-3 | 66199 | .50 | .48 | .40 | 7.00 | 3.00 | .67 | SN3T | - | K3T | - | - |
| | CNVRC0625-3 | 66200 | .62 | .60 | .45 | 8.00 | 3.72 | .80 | | | | | |
| | CAVRC075-3 | 66194 | .75 | .73 | .51 | 10.00 | 4.50 | .90 | SA3T | SY3T | K3T | Y13 | YE3 |
| 1/2" | CNVRC075-4 | 66202 | .75 | .73 | .59 | 10.00 | 4.50 | 1.00 | SN4T | - | K4T | - | - |




Toolholders with prefix "CN" cannot be used with an anvil. The above toolholders have coolant channel as standard.



The above toolholders have 1.5° helix angle. For other helix angles see page 199.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example CNVRC0375-2LH).

Internal Toolholders


Mini-V



Carbide Shank with Alloy Steel Head



Spare Parts

| Insert Style | Ordering Code | | Dimensions Inch | | | | | Spare Parts | | |
|--------------|---------------|---------------|-----------------|-------|-------|------|------|-------------|------------|----------|
| | Sleeve | RH | A | L | L1 | D | D1 | Screw | Size | Torx Key |
| V08 | - | CV08-05000827 | .433 | 3.150 | .827 | .500 | .236 | SNV08 | M2.6x.45x8 | K2T |
| | - | CV08-05001180 | | 3.540 | 1.181 | | | | | |
| V11 | - | CV11-05001142 | .433 | 3.150 | 1.142 | .500 | .315 | SNV11 | M3.5x.6x10 | K3T |
| | - | CV11-05001654 | | 3.540 | 1.654 | | | | | |
| V16 | - | CV16-05001575 | .591 | 5.120 | 1.575 | .625 | .433 | SNV16 | M5x.8x12 | K4T |
| | - | CV16-06251575 | | 5.120 | 1.575 | | | | | |



Internal Toolholders

Mini-V




Thread Turning Toolholders

Reinforced Carbide Shank


Spare Parts

| Insert Style | | Ordering Code | | Dimensions Inch | | | | | Spare Parts | | |
|--------------|----|---------------|------|-----------------|-------|------|-------|-------|-------------|------|--|
| Sleeve | RH | A | L | L1 | D | S1 | Screw | Size | Key | | |
| V14 | - | CV14-05001339 | .433 | 3.940 | 1.339 | .500 | .379 | SNV14 | M4x0.7x12 | KT15 | |



Internal Toolholders


Mini-V



Alloy Steel Shank (Metric)


Spare Parts

| Insert Style | | Ordering Code | Dimensions mm | | | | | Spare Parts | | |
|--------------|----|---------------|---------------|-----|----|--------|----|-------------|-------------|----------|
| Sleeve | RH | | A | L | L1 | D (mm) | D1 | Screw | Size | Torx Key |
| V08 | - | V08-1612 | 15.6 | 80 | 12 | 16 | 6 | SNV08 | M2.6x0.45x8 | K2T |
| V11 | - | V11-1612 | 15.6 | 80 | 12 | | 8 | SNV11 | M3.5x0.6x10 | K3T |
| V16 | - | V16-1622 | 15.0 | 100 | 22 | | 11 | SNV16 | M5.0x0.8x12 | K4T |



Internal Toolholders


Mini-V



Alloy Steel Shank (Metric)



Spare Parts

| Insert Style | | Ordering Code | Dimensions mm | | | | | | Spare Parts | | |
|--------------|----|---------------|---------------|-----|----|--------|-----|----|-------------|-----------|----------|
| Sleeve | RH | | A | L | L1 | D (mm) | S1 | S2 | Screw | Size | Torx Key |
| V14 | - | V14-1620 | 15.0 | 100 | 20 | 16 | 9.5 | 11 | SNV14 | M4x0.7x12 | KT15 |



Internal Toolholders


Mini-V



Holder for Sleeve Clamping


Spare Parts

| Insert Style | Ordering Code | Dimensions Inch | | | | | Ordering Code | Spare Parts | | |
|--------------|---------------|-----------------|-------|----------|--------|------|---------------|-------------|-------------|----------|
| | RH | A | L | L1 (max) | D (mm) | D1 | Sleeve | Screw | Size | Torx Key |
| V08 | CV08-0621 | - | 1.772 | .827 | 6 | .236 | MHC...-6 | SNV08 | M2.6x0.45x8 | K2T |
| V11 | CV11-0829 | - | 2.539 | 1.142 | 8 | .315 | MHC...-8 | SNV11 | M3.5x0.6x10 | K3T |



Internal Toolholders


Mini-V



Sleeves


Spare Parts

| Ordering Code | | Dimensions Inch | | | | Spare Parts | |
|---------------|------------|-----------------|-------|-------|-------|-------------|----------|
| d (mm) | Sleeve | D=B | H1 | H | L | Screw | Torx Key |
| 6 | MHC 0500-6 | 0.500 | 0.644 | 0.394 | 2.756 | SL7DT15 | KT15 |
| | MHC 0625-6 | 0.625 | 0.732 | 0.551 | 2.953 | | |
| | MHC 0750-6 | 0.750 | 0.866 | 0.709 | 3.543 | | |
| 8 | MHC 0625-8 | 0.625 | 0.732 | 0.583 | 1.667 | | |
| | MHC 0750-8 | 0.750 | 0.769 | 0.697 | 1.667 | | |



Internal Toolholders Standard


MINIPRO




Mini-3 Standard

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Anti-Vibration System |  |  |
|-------------|----------------|---------|-----------------|------|------|-----|-----|-----------------------|---|---|
| IC mm | RH | | A | L | L1 | D | D1 | | Insert Screw | Torx Key |
| 4.0 | SNVR0205-4.0K | 42267 | .46 | 4.00 | .47 | .50 | .20 | No | SN4MT | K6MT |
| | CNVRC0205-4.0K | 66347 | .20 | 4.00 | 1.02 | .25 | .20 | Carbide Shank | | |



Internal Toolholders Standard




Mini-3 Standard

Spare Parts


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Anti-Vibration System |  |  |
|-------------|---------------|---------|-----------------|------|------|-----|-----|-----------------------|---|---|
| IC mm | RH | | A | L | L1 | D | D1 | | Insert Screw | Torx Key |
| 5.0 | NVRC260-5.0K | 66258 | .59 | 5.00 | .70 | .62 | .26 | No | SN5MT | K6MT |
| | CNVRC260-5.0K | 66262 | .28 | 5.00 | 1.22 | .31 | .26 | Carbide Shank | | |

The above toolholders have 2.5° helix angle.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example: CNVRC205-4.0K**LH**).



Internal Toolholders U Style


MINIPRO




Thread Turning Toolholders

Mini-3 U Style

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Anti-Vibration System | Spare Parts | |
|-------------|----------------|---------|-----------------|------|------|-----|---------------|-----------------------|---|---|
| | | | A | L | L1 | D | D1 | |  |  |
| 5.0U | NVRC290-5.0KU | 66247 | .59 | 5.00 | .83 | .62 | .29 | No | SN5MT | K6MT |
| | CNVRC290-5.0KU | 66249 | .28 | 5.00 | 1.38 | .31 | Carbide Shank | | | |




Internal Toolholders



Mini-3 Standard


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Anti-Vibration System | Spare Parts | |
|-------------|-----------------|---------|-----------------|------|------|------|-----|-----------------------|---|---|
| | | | A | L | L1 | D | D1 | |  |  |
| 6.0 | SNVRC0375U-6.0K | 66692 | .36 | 3.23 | .63 | .375 | .31 | No | SN6MTN | KIP6 |
| | BNVRC0375S-6.0K | 66693 | .36 | 3.50 | .87 | | | Carbide Implanted | | |
| | BNVRC0375M-6.0K | 66694 | .36 | 3.86 | 1.22 | | | Carbide Implanted | | |
| | BNVRC0375L-6.0K | 66695 | .36 | 4.33 | 1.69 | | | Carbide Implanted | | |
| 6.0 | SNVRC050U-6.0K | 66696 | .49 | 3.23 | .63 | .50 | .31 | No | SN6MTN | KIP6 |
| | BNVRC050S-6.0K | 66697 | .49 | 3.50 | .87 | | | Carbide Implanted | | |
| | BNVRC050M-6.0K | 66698 | .49 | 3.86 | 1.22 | | | Carbide Implanted | | |
| | BNVRC050L-6.0K | 66699 | .49 | 4.33 | 1.69 | | | Carbide Implanted | | |

The above toolholders have 2.5° helix angle.
 The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example: NVRC290-5.0KULH).



Internal Toolholders


MINIPRO




Mini-3 Adjustable

Spare Parts

| Insert Size | | EDP No. | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | |
|-------------|-------------|---------|----------------|---------|-----------------|---|----------|------|------|--------------|---------------------------|-----------------|----------------------|
| IC mm | Sleeve | | Holder RH | | A | L | L1 | D | D1 | Insert Screw | Torx Key for Insert Screw | Holder Screw x3 | Key for Holder Screw |
| 6.0 | SVC0625-8.0 | 66700 | BNVRC8.0T-6.0K | 66701 | .584 | 4 | .315-2.2 | .625 | .315 | SN6MTN | KIP6 | S4.0 | K2.0 |



Internal Toolholders




Mini-L

Spare Parts



| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Anti-Vibration System | Spare Parts | |
|-------------|----------------|---------|-----------------|------|------|------|-----|-----------------------|--------------|----------|
| IC mm | RH | | A | L | L1 | D | D1 | | Insert Screw | Torx Key |
| 5.0L | SNVRC0375U-5LK | 66702 | .36 | 3.19 | .63 | .375 | .24 | No | SN5LSTR | K7MT |
| | BNVRC0375S-5LK | 66703 | .36 | 3.43 | .87 | | | Carbide Implanted | | |
| | BNVRC0375M-5LK | 66704 | .36 | 3.82 | 1.22 | | | Carbide Implanted | | |
| | BNVRC0375L-5LK | 66705 | .36 | 4.29 | 1.69 | | | Carbide Implanted | | |
| 5.0L | SNVRC050U-5LK | 66706 | .49 | 3.19 | .63 | .50 | .24 | No | SN5LSTR | K7MT |
| | BNVRC050S-5LK | 66707 | .49 | 3.43 | .87 | | | Carbide Implanted | | |
| | BNVRC050M-5LK | 66708 | .49 | 3.82 | 1.22 | | | Carbide Implanted | | |
| | BNVRC050L-5LK | 66709 | .49 | 4.29 | 1.69 | | | Carbide Implanted | | |

The above toolholders have 2.5° helix angle.
The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example: SNVRC375U-5LK**LH**).



Internal Toolholders

MINIPRO




Mini-L-Adjustable



Spare Parts

| Insert Size | EDP No. | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | | |
|-------------|-------------|---------------|---------------|-----------------|-----|------|-----------|------|--------------|---------------------------|------------------|----------------------|------|
| IC mm | Sleeve | Holder RH | | A | L | L1 | D | D1 | Insert Screw | Torx Key for Insert Screw | Holder Screw x 3 | Key for Holder Screw | |
| 5.0L | SVC0625-6.2 | 66710 | BNVRC6.2T-5LK | 66711 | .58 | 4.00 | .315-1.73 | .625 | .24 | SN5LSTR | K7MT | S4.0 | K2.0 |

The above toolholders are for RH inserts. For LH inserts, add LH to the toolholder's ordering code (Example: BNVRC6.2T-5LK**LH**).




Internal Toolholders



Micro - Double Ended

Spare Parts

| Micro Insert Dia. | Shank Dia. | Ordering Code | EDP No. | Dimensions Inch | | | Location Screw (Every toolholder package contains the full range of location screws needed) | | Clamping Screw x 3 | | |
|-------------------|------------|---------------|---------|-----------------|-------------|------|--|------|--------------------|------------|------|
| d mm | D | | | L | L1 | L0 | Screw | M | Key | Screw | Key |
| 3 | .50 | SMC050-3.0 | 41075 | 3.15 | .35- Short | 3.50 | 4GISM8X28 | 1.10 | K4.0 | M4X0.7X4.0 | K2.0 |
| | .625 | SMC0625-3.0 | 40210 | | .63- Medium | 3.78 | 4GISM8X21 | .83 | | | |
| | .75 | SMC075-3.0 | 41080 | 3.74 | .35- Short | 4.09 | 4GISM8X49 | 1.93 | | | |
| 4 | .50 | SMC050-4.0 | 41092 | 3.15 | .63- Medium | 3.78 | 4GISM8X21 | .83 | | | |
| | | | | | .83- Long | 3.98 | 4GISM8X16 | .63 | | | |
| | | | | | .35- Short | 4.09 | 4GISM8X49 | 1.93 | | | |
| | .625 | SMC0625-4.0 | 40212 | 3.74 | .63- Medium | 4.37 | 4GISM8X42 | 1.65 | | | |
| | | | | | .83- Long | 4.57 | 4GISM8X37 | 1.46 | | | |
| | | | | | .35- Short | 3.50 | 4GISM8X28 | 1.10 | | | |
| 6 | .50 | SMC050-6.0 | 41517 | 3.15 | .63- Medium | 3.78 | 4GISM8X21 | .83 | | | |
| | | | | | .83- Long | 3.98 | 4GISM8X16 | .63 | | | |
| | | | | | .35- Short | 4.09 | 4GISM8X49 | 1.93 | | | |
| | .625 | SMC0625-6.0 | 40214 | 3.74 | .63- Medium | 4.37 | 4GISM8X42 | 1.65 | | | |
| | | | | | .83- Long | 4.57 | 4GISM8X37 | 1.46 | | | |
| | | | | | .35- Short | 3.50 | 4GISM8X28 | 1.10 | | | |




Round Shanks 2 Flats (Inch)

| Micro Insert Dia. | Ordering Code | Dimensions Inch | | | | | Spare Parts | |
|-------------------|---------------|-----------------|------|------|------|------|------------------------------|----------------------|
| d mm | | D | B | H1 | H | L | | |
| 4.0 | MHC0500-4 | .500 | .500 | .644 | .394 | 2.76 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| | MHC0625-4 | .625 | .638 | .732 | .551 | 2.95 | | |
| | MHC0750-4 | .750 | .827 | .827 | .709 | 3.54 | | |
| 5.0 | MHC0500-5 | .500 | .500 | .644 | .394 | 2.76 | | |
| | MHC0625-5 | .625 | .638 | .732 | .551 | 2.95 | | |
| | MHC0750-5 | .750 | .827 | .827 | .709 | 3.54 | | |
| 6.0 | MHC0500-6 | .500 | .500 | .644 | .394 | 2.76 | | |
| | MHC0625-6 | .625 | .638 | .732 | .551 | 2.95 | | |
| | MHC0750-6 | .750 | .827 | .827 | .709 | 3.54 | | |
| 7.0 | MHC0625-7 | .625 | .638 | .732 | .551 | 2.95 | | |
| | MHC0750-7 | .750 | .827 | .827 | .709 | 3.54 | | |

Round Shanks 2 Flats (Metric)

| Micro Insert Dia. | Ordering Code | Dimensions mm | | | | Spare Parts | |
|-------------------|---------------|---------------|------|------|----|------------------------------|----------------------|
| d mm | | D=B | H1 | H | L | | |
| 4.0 | MHC10-4 | 10 | 14 | 8.8 | 65 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| | MHC12-4 | 12 | 16 | 10.8 | 70 | | |
| | MHC16-4 | 16 | 17.6 | 14.8 | 75 | | |
| | MHC20-4 | 20 | 22 | 18.8 | 84 | | |
| 5.0 | MHC10-5 | 10 | 14 | 8.8 | 65 | | |
| | MHC12-5 | 12 | 16 | 10.8 | 70 | | |
| | MHC16-5 | 16 | 18.6 | 14.8 | 75 | | |
| 6.0 | MHC20-5 | 20 | 22 | 18.8 | 84 | | |
| | MHC12-6 | 12 | 16 | 10.8 | 70 | | |
| | MHC16-6 | 16 | 18.6 | 14.8 | 75 | | |
| 7.0 | MHC20-6 | 20 | 22 | 18.8 | 84 | | |
| | MHC16-7 | 16 | 18.6 | 14.8 | 75 | | |
| | MHC20-7 | 20 | 22 | 18.8 | 84 | | |

*Torx+ Screw and key are now available for improved clamping



Micro - Single Ended


Round Shank - 4 Flats (Inch)

| Micro Insert Dia. | Ordering Code | Dimensions Inch | | | | Spare Parts | |
|-------------------|---------------|-----------------|-------|-----|------|------------------------------|----------------------|
| d (mm) | | D | B | H | L | Clamping Screw | Torx Key |
| 4.0 | MHC0875-4-4F | .875 | .925 | .82 | 3.29 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| | MHC1000-4-4F | 1.000 | 1.063 | .90 | 4.33 | | |
| 5.0 | MHC0875-5-4F | .875 | .925 | .82 | 3.29 | | |
| | MHC1000-5-4F | 1.000 | 1.063 | .90 | 4.33 | | |
| 6.0 | MHC1000-6-4F | 1.000 | 1.063 | .90 | 4.33 | | |

Round Shank - 4 Flats (Metric)

| Micro Insert Dia. | Ordering Code | Dimensions mm | | | | Spare Parts | |
|-------------------|---------------|---------------|------|------|------|------------------------------|----------------------|
| d mm | | D | B | H | L | Clamping Screw | Torx Key |
| 4.0 | MHC20-4-4F | 20.0 | 22.0 | 18.8 | 83.5 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| | MHC22-4-4F | 22.0 | 24.0 | 20.0 | | | |
| | MHC23-4-4F | 23.0 | 25.0 | 21.0 | 110 | | |
| | MHC25-4-4F | 25.0 | 27.0 | 23.0 | | | |
| | MHC28-4-4F | 28.0 | 30.0 | 26.0 | | | |
| 5.0 | MHC20-5-4F | 20.0 | 22.0 | 18.8 | 83.5 | | |
| | MHC22-5-4F | 22.0 | 24.0 | 20.0 | 110 | | |
| | MHC23-5-4F | 23.0 | 25.0 | 21.0 | | | |
| | MHC25-5-4F | 25.0 | 27.0 | 23.0 | | | |
| | MHC28-5-4F | 28.0 | 30.0 | 26.0 | | | |
| 6.0 | MHC20-6-4F | 20.0 | 22.0 | 18.8 | | 83.5 | |
| | MHC22-6-4F | 22.0 | 24.0 | 20.0 | | | |
| | MHC23-6-4F | 23.0 | 25.0 | 21.0 | 110 | | |
| | MHC25-6-4F | 25.0 | 27.0 | 23.0 | | | |
| | MHC28-6-4F | 28.0 | 30.0 | 26.0 | | | |
| 7.0 | MHC22-7-4F | 22.0 | 24.0 | 20.0 | 110 | | |
| | MHC23-7-4F | 23.0 | 25.0 | 21.0 | | | |
| | MHC25-7-4F | 25.0 | 27.0 | 23.0 | | | |
| | MHC28-7-4F | 28.0 | 30.0 | 26.0 | | | |

*Torx+ Screw and key are now available for improved clamping



Microscope Holder with Square Shank (Inch)

Spare Parts


| Micro Insert Dia. | Ordering Code | Dimensions Inch | | | |  |  |
|-------------------|---------------|-----------------|-------|------|-------|---|---|
| d (mm) | | H=H2=B | H1 | L | L1 | Clamping Screw | Torx Key |
| 4.0 | MHS0500-4 | .500 | .827 | 4.00 | .984 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| | MHS0625-4 | .625 | .984 | 5.00 | .984 | | |
| 5.0 | MHS0500-5 | .500 | .846 | 4.00 | 1.063 | | |
| | MHS0625-5 | .625 | 1.004 | 5.00 | 1.377 | | |
| 6.0 | MHS0500-6 | .500 | .866 | 4.00 | 1.063 | | |
| | MHS0625-6 | .625 | 1.024 | 5.00 | 1.377 | | |
| 7.0 | MHS0625-7 | .625 | 1.043 | 5.00 | 1.377 | | |

Microscope Holder with Square Shank (Metric)

Spare Parts

| Micro Insert Dia. | Ordering Code | Dimensions mm | | | |  |  |
|-------------------|---------------|---------------|------|-------|------|---|---|
| d mm | | H=H2=B | H1 | L | L1 | Clamping Screw | Torx Key |
| 4.0 | MHS1010-4 | 10.0 | 19.0 | 100.0 | 25.0 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| 5.0 | MHS1010-5 | 10.0 | 19.5 | 100.0 | 25.0 | | |
| 4.0 | MHS1212-4 | 12.0 | 21.0 | 100.0 | 25.0 | | |
| 5.0 | MHS1212-5 | 12.0 | 21.5 | 100.0 | 27.0 | | |
| 6.0 | MHS1212-6 | 12.0 | 22.0 | 100.0 | 27.0 | | |

*Torx+ Screw and key are now available for improved clamping



Microscope Holder with Drop Head (Inch)

Spare Parts


| Micro Insert Dia. | Ordering Code | Dimensions Inch | | | | | | | | | | | | | | | |
|-------------------|----------------|-----------------|-------|------|-------|-------|------|-------|-------|------------------------------|----------------------|-------|------|-------|-------|------------------------------|----------------------|
| d mm | | a=b=h | L3 | H | L | L1 | F | D max | L2 | Clamping Screw | Torx Key | | | | | | |
| 4.0 | MHD0375-4L0700 | .375 | 1.437 | .630 | 3.898 | 1.142 | .748 | 1.024 | .709 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* | | | | | | |
| 5.0 | MHD0375-5L0800 | | 1.890 | | | | | | .906 | | | | | | | | |
| 6.0 | MHD0375-6L0800 | | 2.087 | | | | | | .906 | | | | | | | | |
| 4.0 | MHD0500-4L0700 | .500 | 1.437 | .748 | | | | | 3.898 | | | 1.142 | .748 | 1.024 | .709 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| 5.0 | MHD0500-5L0800 | | 1.890 | | | | | | | | | | | | .906 | | |
| 6.0 | MHD0500-6L1000 | | 2.087 | | | | | | | | | | | | 1.102 | | |

Microscope Holder with Drop Head (Metric)

Spare Parts

| Micro Insert Dia. | Ordering Code | Dimensions mm | | | | | | | | | | | | | | | |
|-------------------|----------------|---------------|------|------|------|------|------|-------|------|------------------------------|----------------------|------|------|------|------|------------------------------|----------------------|
| d mm | | a=b=h | L3 | H | L | L1 | F | D max | L2 | Clamping Screw | Torx Key | | | | | | |
| 4.0 | MHD1010-4L0500 | 10.0 | 31.5 | 16.0 | 99.0 | 29.0 | 19.0 | 26.0 | 13.0 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* | | | | | | |
| 5.0 | MHD1010-5L0800 | | 48.0 | | | | | | 23.0 | | | | | | | | |
| 6.0 | MHD1010-6L1000 | | 53.0 | | | | | | 28.0 | | | | | | | | |
| 4.0 | MHD1212-4L0700 | 12.0 | 36.5 | 18.0 | | | | | 99.0 | | | 29.0 | 19.0 | 26.0 | 18.0 | SL7DT15 or SL7DBT15IP* | KT15 or F15IP* |
| 5.0 | MHD1212-5L0800 | | 48.0 | | | | | | | | | | | | 23.0 | | |
| 6.0 | MHD1212-6L1000 | | 53.0 | | | | | | | | | | | | 28.0 | | |

*Torx+ Screw and key are now available for improved clamping



Thread Turning Technical Data

Thread Terminology

External Thread

A thread on the external surface of a cylinder screw or cone.

Depth of Thread

The distance between crest and root measured normal to the axis.


Pitch

The distance between two corresponding points on adjacent thread forms is measured parallel to the axis. This distance can be defined in either millimeters or by TPI (threads per inch).

Nominal Diameter

The diameter from which the diameter limits are derived by the application of deviation allowances and tolerances.

External Thread



Major Diameter

The largest diameter of a screw thread.

Pitch Diameter

On a straight thread, the diameter of an imaginary cylinder, the surface of which cuts the thread forms where the width of the thread and groove are equal.

Minor Diameter

The smallest diameter of a screw thread.

Helix Angle

For a straight thread, where the lead of the thread and the pitch diameter circle circumference form a right angled triangle, the helix angle is the angle opposite the lead.

Straight Thread

A thread formed on a cylinder.


Taper Thread

A thread formed on a cone.

Internal Thread


A thread on the internal surface of a cylinder or cone.

Left-hand thread




A thread which, when viewed axially, winds in a counterclockwise and receding direction. All left-hand threads are designated LH.

Right-hand thread



A thread which, when viewed axially, winds in a clockwise and receding direction. Threads are always right-hand unless otherwise specified.

The Helix Angle β



Lead


The distance a threaded part moves axially, with respect to a fixed mating part, in one complete revolution.

The lead is equal to the pitch multiplied by the number of thread starts.


Machining a Multi-Start Thread

A thread in which the lead is an integral multiple, greater than one, of the pitch.
 A multi-start thread permits a more rapid advance without a coarser (larger) thread form.


First Start Machined



Second Start Machined




Third Start Machined
(Final, 3 Starts Thread)



Lead = 3 x Pitch


Insert Profile Styles

Partial Profile




The V partial profile insert cuts without topping the outer diameter of the thread. The same insert can be used for a range of different thread pitches which have a common thread angle.

Full Profile




The full profile insert will form a complete thread profile including the crest. For every thread pitch and standard, a separate insert is required.

Full Profile for Fine Pitches



The full profile for Fine Pitches will form a complete thread. The topping of the outer diameter is generated by the second tooth.

Semi Full




The Semi full profile insert will form a complete thread including crest radius but without topping the outer diameter. Mainly used for trapezoidal profiles.


Thread Turning Methods for Symmetrical Inserts

| Thread | Inserts & Toolholder | Rotation | Feed Direction | Helix Method | Drawing No. |
|---------------------|----------------------|------------------|----------------|--------------|-------------|
| Right Hand External | EX RH | Counterclockwise | Towards chuck | Regular | 1 |
| | EX LH | Clockwise | From chuck | Reversed | 2 |
| Right Hand Internal | IN RH | Counterclockwise | Towards chuck | Regular | 3 |
| | IN LH | Clockwise | From chuck | Reversed | 4 |
| Left Hand External | EX LH | Clockwise | Towards chuck | Regular | 5 |
| | EX RH | Counterclockwise | From chuck | Reversed | 6 |
| Left Hand Internal | IN LH | Clockwise | Towards chuck | Regular | 7 |
| | IN RH | Counterclockwise | From chuck | Reversed | 8 |


External RH Thread




External LH Thread



Internal RH Thread




Internal LH Thread



Thread Infeed Methods

Radial Infeed




Radial infeed is the simplest and quickest method.

The feed is perpendicular to the turning axis, and both flanks of the insert perform the cutting operation.

Radial infeed is recommended in 3 cases:

- When the pitch is smaller than 16 TPI
- For material with short chips
- For work with hardened material


Flank Infeed (modified)



Flank infeed is recommended in the following cases:

- When the thread pitch is greater than 16 TPI, using the radial method, the effective cutting edge length is too large, resulting in chatter.
- For TRAPEZ and ACME. The radial method result in three cutting edges, making chip flow very difficult.

Alternate Flank Infeed




Use of the alternate flank method is recommended especially in large pitches and for materials with long chips.

This method divides the load equally on both flanks, resulting in equal wear along the cutting edges. Alternate flank infeed requires more complicated programming, and is not available on all lathes.


Thread Turning Methods for Asymmetrical Inserts (ABUT, BBUT, SAGE)

| Thread | Inserts & Toolholder | Rotation | Feed Direction | Helix Method | Drawing No. |
|---------------------|----------------------|------------------|----------------|--------------|-------------|
| Right Hand External | EX RH | Counterclockwise | Towards chuck | Regular | 1 |
| | EX LH | Clockwise | From chuck | Reversed | 2 |
| Right Hand Internal | IN RH | Counterclockwise | Towards chuck | Regular | 3 |
| | IN LH | Clockwise | From chuck | Reversed | 4 |
| Left Hand External | EX LH | Clockwise | Towards chuck | Regular | 5 |
| | EX RH | Counterclockwise | From chuck | Reversed | 6 |
| Left Hand Internal | IN LH | Clockwise | Towards chuck | Regular | 7 |
| | IN RH | Counterclockwise | From chuck | Reversed | 8 |


External RH Thread




External LH Thread



Internal RH Thread




Internal LH Thread




Calculating the Helix Angle and Choosing The Right Anvil

Flank Clearance Angle α (For External Inserts)



Vardex toolholders are designed to tilt the insert when seated in the toolholder (10° for external, 15° for internal tooling).


This results in the differing flank clearance angles, based on the geometry of the insert. To ensure that the side of the insert cutting edge will not rub on the workpiece, it is most important that the insert helix angle be correct - especially in profiles with small enclosed flank angles. This correction is provided by Vardex anvils.



$$\alpha = \arctan(\tan(\phi/2) \times \tan\delta)$$

Where: α - Flank clearance angle
 δ - Tilt angle
 ϕ - Enclosed flank angle

Calculating the Helix Angle β




The helix angle is calculated by the following formula:

$$\beta = \arctan \frac{P \times N}{\pi \times D}$$

β - Helix angle [°]
 P - Pitch [mm]
 N - No. of starts
 D - Pitch diameter [mm]
 Lead = P x N

The helix angle can also be found from the diagram below.

Helix Angle Diagram



*For Multi-start threads, use the lead value instead of the pitch

Anvils

| Resultant Helix Angle | | 4.5° | 3.5° | 2.5° | 1.5° | 0.5° | 0° | -0.5° | -1.5° | |
|-----------------------|--------|-----------------|-----------|-----------|---------------|-----------|-----------|-------------|-------------|-----------|
| Insert Size | | Holder | | | Ordering Code | | | | | |
| IC | L Inch | | | | | | | | | |
| 3/8" | .63 | ER / IL | YE3-3P | YE3-2P | YE3-1P | YE3 | YE3-1N | YE3-1.5N | YE3-2N | YE3-3N |
| | | EL / IR | YI3-3P | YI3-2P | YI3-1P | YI3 | YI3-1N | YI3-1.5N | YI3-2N | YI3-3N |
| 3/8" V6 | .63 | ER | YE3-6C-3P | YE3-6C-2P | YE3-6C-1P | YE3-6C | YE3-6C-1N | YE3-6C-1.5N | YE3-6C-2N | YE3-6C-3N |
| | | IR | YI3-6C-3P | YI3-6C-2P | YI3-6C-1P | YI3-6C | YI3-6C-1N | YI3-6C-1.5N | YI3-6C-2N | YI3-6C-3N |
| 1/2" | .87 | ER / IL | YE4-3P | YE4-2P | YE4-1P | YE4 | YE4-1N | YE4-1.5N | YE4-2N | YE4-3N |
| | | EL / IR | YI4-3P | YI4-2P | YI4-1P | YI4 | YI4-1N | YI4-1.5N | YI4-2N | YI4-3N |
| 1/2"F | .91 | ER | YE4F-3P | YE4F-2P | YE4F-1P | YE4F | YE4F-1N | YE4F-1.5N | | |
| | | IR | YI4F-3P | YI4F-2P | YI4F-1P | YI4F | YI4F-1N | YI4F-1.5N | | |
| 1/2"U | .87 | ER / IL | YE4U-3P | YE4U-2P | YE4U-1P | YE4U | YE4U-1N | YE4U-1.5N | YE4U-2N | YE4U-3N |
| | | EL / IR | YI4U-3P | YI4U-2P | YI4U-1P | YI4U | YI4U-1N | YI4U-1.5N | YI4U-2N | YI4U-3N |
| 5/8" | 1.06 | ER / IL | YE5-3P | YE5-2P | YE5-1P | YE5 | YE5-1N | YE5-1.5N | YE5-2N | YE5-3N |
| | | EL / IR | YI5-3P | YI5-2P | YI5-1P | YI5 | YI5-1N | YI5-1.5N | YI5-2N | YI5-3N |
| 5/8"U | 1.06 | ER / IL | YE5U-3P | YE5U-2P | YE5U-1P | YE5U | YE5U-1N | YE5U-1.5N | YE5U-2N | YE5U-3N |
| | | EL / IR | YI5U-3P | YI5U-2P | YI5U-1P | YI5U | YI5U-1N | YI5U-1.5N | YI5U-2N | YI5U-3N |
| 3/8"M+ | .63 | ER / IL | | | YE3M-1P | YE3M | YE3M-1N | YE3M-1.5N | YE3M-2N | |
| | | EL / IR | | | YI3M-1P | YI3M | YI3M-1N | YI3M-1.5N | | |
| 1/2"M+ | .87 | ER / IL | | | YE4M-1P | YE4M | YE4M-1N | YE4M-1.5N | YE4M-2N | |
| | | EL / IR | | | YI4M-1P | YI4M | YI4M-1N | YI4M-1.5N | | |
| 1/2"F 2M+ | .91 | ER | | | YE4M2F-1P | YE4M2F | YE4M2F-1N | YE4M2F-1.5N | | |
| 1/2"F 3M+ | | | | | YE4M3F-1P | YE4M3F | YE4M3F-1N | YE4M3F-1.5N | | |
| 1/2"F 2M+ | | | IR | | | YI4M2F-1P | YI4M2F | YI4M2F-1N | YI4M2F-1.5N | |
| 5/8"M+ | 1.06 | ER / IL | | | | YE5M | YE5M-1N | YE5M-1.5N | | |
| | | EL / IR | | | | YI5M | YI5M-1N | YI5M-1.5N | | |
| 1/2"Z+ | .87 | ER / IL | | | YE4Z-1P | YE4Z | YE4Z-1N | | | |
| | | EL / IR | | | YI4Z-1P | YI4Z | YI4Z-1N | | | |
| 5/8"Z+ | 1.06 | ER / IL | | | | YE5Z | | | | |
| | | EL / IR | | | | YI5Z | | | | |
| 1/2"T+ | .87 | ER / IL EL / IR | | | | | | Y4T | | |

Thread Turning
Technical Data

| Standard Anvil | | V6 Anvil | | U Style Anvil | | M+ Style Anvil | | Z+ Style Anvil | | T+ Style Anvil | |
|----------------|-------|---------------------------------|----|---------------|-------|----------------|-------|----------------|-------|------------------------|-------|
| | | | | | | | | | | | |
| ER/IL | EL/IR | ER | IR | ER/IL | EL/IR | ER/IL | EL/IR | ER/IL | EL/IR | ER/IL | EL/IR |
| | | V6 is indicated on the backside | | | | | | | | Same anvil turned over | |

| F.LINE Anvil | | F.LINE M+ Style Anvil | |
|--------------|----|-----------------------|----|
| | | | |
| ER | IR | ER | IR |

Oil&Gas - Anvils

| Resultant Helix Angle | 3° | 2° | 1° | 0° | 0.5° |
|-----------------------|-------------|-------------|-------------|----|---------------|
| Insert Size | | | | | |
| 3/8" APIRD | | | YEI3-APIRD | | |
| 1/2" API | YEI4-API-3P | YEI4-API-2P | YEI4-API-1P | | |
| 1/2" BUT | | | | | YEI4-BUT-0.5N |

Oil&Gas - 14D Anvils

| Standard | Application | Anvils with Protected Second Cutting Edge | | | |
|---------------------------|-------------------------------|---|---|---------------------------------------|--|
| | | Ordering Code External Application | | Ordering Code Internal Application | |
| API Round Casing & Tubing | 10 TPI from Ø 2 3/8" and up | Y14DER-10APIRD (4 teeth) |  | Y14DIR-10APIRD (4 teeth) |  |
| | 10 TPI from Ø 2 3/8" and up | Y14DER10APIRD-3+ (3 teeth) |  | Y14DIR10APIRD-3+ (3 teeth) |  |
| | 8 TPI from Ø 2 3/8" and up | Y14DER-8APIRD |  | Y14DIR-8APIRD |  |
| API Buttress Casing | 5 TPI for Ø 4 1/2" - Ø 9 5/8" | Y14DER-5 BUT |  | Y14DIR-5 BUT |  |
| | 5 TPI for Ø 10 3/4" and up | Y14DER-5BUT-0.4N |  | Y14DIR-5BUT-0.4N |  |


Anvil Kits

| Anvil Size | | Ordering Code | Included Anvils: |
|------------|------|---------------|---------------------------|
| IC | L mm | | |
| 3/8" | .63 | ABY3 | YE3-2P, 1P, 1N, 2N, 3N |
| | | | YI3-2P, 1P, 1N, 2N, 3N |
| 3/8" V6 | .63 | ABY3-6C | YE3-6C-2P, 1P, 1N, 2N, 3N |
| | | | YI3-6C-2P, 1P, 1N, 2N, 3N |
| 1/2" | .87 | ABY4 | YE4-2P, 1P, 1N, 2N, 3N |
| | | | YI4-2P, 1P, 1N, 2N, 3N |
| 1/2"U | .87 | ABY4U | YE4U-2P, 1P, 1N, 2N, 3N |
| | | | YI4U-2P, 1P, 1N, 2N, 3N |
| 5/8" | 1.06 | ABYE5 | YE5-2P, 1P, 1N, 2N, 3N |
| | | ABYI5 | YI5-2P, 1P, 1N, 2N, 3N |
| 5/8"U | 1.06 | ABYE5U | YE5U-2P, 1P, 1N, 2N, 3N |
| | | ABYI5U | YI5U-2P, 1P, 1N, 2N, 3N |

To ensure that you always have on hand an assortment of anvils for any job, we recommend that anvil kits be readily available.

Important!

Use a V6 anvil when using a V6 insert.




For External RH
use YE3-6C anvil.

For Internal RH
use YI3-6C anvil.



Spare Parts

External and Internal Toolholders (not including Micro and Microscope)




| Toolholder | Insert Size | | Insert Screw / Clamp Screw | | Anvil Screw & Washer | | Anvil | | | |
|------------------------|--------------|-------------|----------------------------|------------------|----------------------|----------|-----------|-------------|-------------|--|
| | IC | Designation | Thread | Designation | Thread | Key | Torx size | EX RH/IN LH | IN RH/EX LH | |
| Standard | 1/4" | SN2T | M2.6x0.45x6.5 | - | - | K2T | T8 | - | - | |
| | 3/8", 3/8"V6 | SA3T | 5-40UNCx11.3 | SY3T | UNC5x7.3 | K3T | T10 | YE3/YE3-6C | YI3/YI3-6C | |
| | 3/8" | SN3T | 5-40UNCx8.8 | - | - | K3T | T10 | - | - | |
| | 1/2" | SA4T | 8-32UNCx14.0 | SY4T | UNC8x9.3 | K4T | T20 | YE4 | YI4 | |
| | 1/2" | SN4T | 8-32UNCx11.0 | - | - | K4T | T20 | - | - | |
| | 1/2F" | SA4T | 8-32UNCx14.0 | SY4T | UNC8x9.3 | K6T | T20 | YE4F | YI4F | |
| | 5/8" | SA5T | M5x0.8x22.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5 | YI5 | |
| | 5/8" | SN5T | M5x0.8x13.9 | - | - | K5T | T25 | - | - | |
| Standard Coarse | 3/8" | SN3TM | 5-40UNCx7.3 | - | - | K3T | T10 | - | - | |
| | 1/2" | SN4TM | 8-32UNCx9.8 | - | - | K4T | T20 | - | - | |
| | 5/8" | SN5TM | M5x0.8x13.9 | - | - | K5T | T25 | - | - | |
| Standard with Clamp | 3/8" | SA3T/C3 | UNC5x12.0/M5x0.8x22.0 | SY3T | UNC5x7.3 | K3CT | T15/T10 | YE3 | YI3 | |
| | 1/2" | SA4T/C4 | UNC8x15.2/M6x1.0x29.5 | SY4T | UNC8x9.3 | K4T | T20 | YE4 | YI4 | |
| | 5/8" | SA5T/C5 | M5x0.8x22.0/M8x1.25x28.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5 | YI5 | |
| U Style | 1/2"U | SA4T | UNC8x15.2 | SY4T | UNC8x9.3 | K4T | T20 | YE4U | YI4U | |
| | 5/8"U | SA5T | M5x0.8x22.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5U | YI5U | |
| U Style with Clamp | 1/2" | SA4T/C4 | UNC8x15.2/M6x1.0x29.5 | SY4T | UNC8x9.3 | K4T | T20 | YE4U | YI4U | |
| | 5/8" | SA5T/C5 | M5x0.8x22.0/M8x1.25x28.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5U | YI5U | |
| V Style | 1/4"V | SN2T | M2.6x0.45x6.5 | - | - | K2T | T8 | - | - | |
| | 3/8"V | SN3TV | 5-40UNCx6.7 | - | - | K3T | T10 | - | - | |
| | 1/2"V | SN4T | 8-32UNCx11.0 | - | - | K4T | T20 | - | - | |
| | 5/8"V | SN6T | M6x1.0x29.0 | - | - | K6T | T20 | - | - | |
| Mega Line | 5/8"MG | S5MG | M5x0.8x16.0 | - | - | K6T | T20 | - | - | |
| Z+ Style | 1/2"Z | SA4T | UNC8x15.2 | SY4T | UNC8x9.3 | K4T | T20 | YE4Z | YI4Z | |
| | 5/8"Z | SA5T | M5x0.8x22.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5Z | YI5Z | |
| M+ Style | 3/8"M | SA3T | UNC5x12.0 | SY3T | UNC5x7.3 | K3T | T10 | YE3M | YI3M | |
| | 1/2"M | SA4T | UNC8x15.2 | SY4T | UNC8x9.3 | K4T | T20 | YE4M | YI4M | |
| | 5/8"M | SA5T | M5x0.8x22.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5M | YI5M | |
| T+ Style | 1/2"T | SA4T | UNC8x15.2 | SY4K2 | UNC8x7.3 | K4T/K2 | T20/T8 | Y4T | Y4T | |
| API | 5/8" | SA5T/C5 | M5x0.8x22.0/M8x1.25x28.0 | SY5T | M5x0.8x9.5 | K5T | T25 | YE5OIL | YI5OIL | |
| API 14D | 14D | SA5T | M5x0.8x22.0 | M4x0.7x6.0 (14D) | - | K5T/KT15 | T25/T15 | Y14DER-... | Y14DIR-... | |
| Mini-V | V08 | SNV08 | M2.6x0.45x8 | - | - | K2T | T8 | - | - | |
| | V11 | SNV11 | M3.5x0.6x10 | - | - | K3T | T10 | - | - | |
| | V14 | SNV14 | M4x0.7x12 | - | - | KT15 | T15 | - | - | |
| | V16 | SNV16 | M5x0.8x12 | - | - | K4T | T20 | - | - | |
| Mini-L | 5.0L | SN5LSTR | M2.2x0.45x4.5 | - | - | K7MT | T7 | - | - | |
| Mini-3 | 4.0mm | SN4MT | M2x0.4x4.0 | - | - | K6MT | T6 | - | - | |
| | 5.0mm | SN5MT | M2x0.4x5.3 | - | - | K6MT | T6 | - | - | |
| | 6.0mm | SN6MTN | M2.0x0.4x4.7 | - | - | KIP6 | T+6 | - | - | |
| Mini Adjustable Holder | - | S4.0 | M4x0.7x4.0 | - | - | K2.0 | - | - | - | |


For Micro and Microscope Toolholders see pages 187-191


Grades and Their Applications

| General Use | | |
|---|--|--|
| VRX | VTX | VKX |
|  <p>Premium multipurpose submicron grade for stronger wear resistance and improved productivity. AlTiN alloyed PVD coated.</p> |  <p>General purpose grade with tough submicron substrate. Provides good fracture toughness in non-rigid cutting conditions. TiAlN coated.</p> |  <p>General purpose grade, excellent in steel and stainless steel, recommended for rigid cutting conditions. Ground or sintered chipbreaker styles. TiN coated.</p> |

| General Use | Stainless Steel | Non Ferrous, High Temperature Alloys and Titanium | |
|--|---|---|---|
| VCB | VM7 | VK2 | VK2P |
|  <p>Sintered chipbreaker with ground profile for machining materials with long chips. TiAlN coated.</p> |  <p>Specialty grade for threading stainless steel. Multi-layer PVD coated.</p> |  <p>Uncoated grade for non-ferrous, aluminum, high temperature and titanium alloys.</p> |  <p>Highly-polished version of the VK2 uncoated grade for high quality surface finish in aluminum.</p> |

| VG-Cut | Oil&Gas | General Use for Oil & Gas Materials | |
|---|---|--|--|
| VPG | VRXP | VTXP | VKXP |
|  <p>Sub-micron substrate for a wide range of applications. Excellent anti-fracture resistance. Highly recommended for medium to high cutting speeds. TiAlN coated.</p> |  <p>Premium submicron grade with reinforced cutting edge for the oil & gas industry. Ideal for steel and stainless steel in unstable cutting conditions. AlTiN alloyed PVD coated.</p> |  <p>Excellent all-purpose grade, tailor-made to the oil & gas industry with reinforced cutting edge. Recommended for non-rigid cutting conditions. TiAlN coated.</p> |  <p>General purpose grade, excellent in steel and stainless steel, and highly recommended for rigid cutting conditions. Special design with reinforced cutting edge for the oil & gas industry. TiN coated.</p> |

| Micro Line | MINIPRO | For all Mini Inserts |
|--|---------|---|
| VMX | | VTX |
|  <p>General purpose carbide grade for Micro double-ended inserts. TiN coated.</p> | |  <p>Sub-micron grade for general machining in low and medium cutting speeds. Highly recommended for stainless steel. TiAlN coated.</p> |

| microscope | Mini 5L & Mini IC 6.0 | Mini IC4.0, IC5.0 & Mini-V |
|---|--|---|
| VBX | VKX | VBX |
|  <p>General purpose carbide grade for microScope threading inserts. TiCN coated.</p> |  <p>General purpose carbide grade for the Mini 5L and Mini 6.0 inserts. TiN coated.</p> |  <p>Sub-micron grade for general machining in low and medium cutting speeds for Mini 4.0K, 5.0K and Mini-V lines. Highly recommended for steel. TiCN coated.</p> |

Thread Turning Grades According to Product Lines

General

| Insert Style | VRX | VTX | VKX | VCB | VM7 | VK2 | VK2P | VPG |
|----------------------------|-----|-----|-----|-----|-----|-----|------|-----|
| TT inserts (General) | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | |
| SCB (Sintered Chipbreaker) | | | ✓ | ✓ | | | | |
| V6 | | | ✓ | | | | | |
| Mega Line | | | ✓ | | | | | |
| F Line | ✓ | ✓ | | | | | | |
| VG Cut | | | | | | | | ✓ |

Oil & Gas



| Insert Style | VRX | VTX | VKX | VRXP | VTXP | VKXP |
|--------------|-----|-----|-----|------|------|------|
| T+ | | ✓ | ✓ | | ✓ | ✓ |
| 14D | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| CNGA | | ✓ | | | ✓ | |
| On Edge | | ✓ | | | ✓ | |
| Chaser | | ✓ | | | ✓ | ✓ |

MiniPro



| Insert Style | VKX | VTX | VBX | VMX |
|---------------------------|-----|-----|-----|-----|
| Mini 4.0K, 5.0K | | ✓ | ✓ | |
| Mini 5LK, 6.0K RH | ✓ | ✓ | | |
| Mini 5LK, 6.0K LH | ✓ | | | ✓ |
| Mini-V | | ✓ | ✓ | |
| Micro (Double Ended) | | | | ✓ |
| Microscope (Single Ended) | | | ✓ | |


Recommended Grades and Cutting Speeds Vc [ft/min] Not Including MiniPro Line

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | | | | |
|-------------------------------------|------------|--|------------------------------------|-------------|----------|----------|----------------|----------|---------|
| | | | | Coated | | | | Uncoated | |
| | | | | VKX(P) | VCB | VM7 | VTX(P), VRX(P) | VK2(P) | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 377-623 | 377-623 | | 377-623 | |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 328-574 | 328-541 | | 328-574 | |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 295-541 | 295-509 | | 295-541 | |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 328-591 | 328-591 | | 328-591 | |
| | 5 | | Hardened | 275 | 246-459 | 246-459 | | 246-459 | |
| | 6 | | Hardened | 350 | 230-443 | 230-443 | | 230-443 | |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 262-394 | 262-394 | | 262-394 | |
| | 8 | | Hardened | 325 | 164-328 | 164-328 | | 164-328 | |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 230-427 | 230-427 | | 230-427 | |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 197-394 | 197-394 | | 197-394 | |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 230-427 | 230-427 | 230-492 | 230-427 | |
| | 12 | | Hardened | 330 | 197-377 | 164-312 | 197-410 | 197-377 | |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 295-459 | 262-394 | 295-525 | 295-459 | |
| | 14 | | Super Austenitic | 200 | 131-361 | 98-328 | 131-394 | 131-361 | |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 295-394 | 295-394 | 295-492 | 295-394 | |
| | 16 | | Hardened | 330 | 213-361 | 213-361 | 213-394 | 213-361 | |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 279-361 | 279-361 | 279-394 | 279-361 | |
| | 18 | | Hardened | 330 | 197-328 | 197-328 | 197-361 | 197-328 | |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 197-230 | 230-394 | | 197-230 | |
| | 29 | | Pearlitic (long chips) | 230 | 197-476 | 230-394 | | 197-476 | |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 230-427 | 230-427 | | 230-427 | |
| | 31 | | High Tensile Strength | 260 | 197-377 | 197-328 | | 197-377 | |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 410-525 | 410-525 | | 410-525 | |
| 33 | Pearlitic | | 260 | 295-394 | 295-394 | | 295-394 | | |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-1198 | 328-820 | | 328-1198 | 328-820 |
| | 35 | | Aged | 100 | 262-722 | 262-591 | | 262-722 | 262-525 |
| | 36 | Aluminium Alloys Cast | Cast | 75 | 656-1312 | 656-1312 | | 656-1312 | 262-394 |
| | 37 | | Cast & Aged | 90 | 656-919 | 656-919 | | 656-919 | 230-328 |
| | 38 | Aluminium Alloys Cast Si 13-22% | 130 | 197-591 | 197-492 | | 197-591 | 164-394 | |
| | 39 | Copper and Copper Alloys | Brass | 90 | 262-738 | 262-689 | | 262-738 | 230-558 |
| | 40 | | Bronze And Non Leaded Copper | 100 | 262-837 | 262-689 | | 262-837 | 230-558 |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 148-197 | 148-197 | | 148-197 | 98-164 |
| | 20 | | Aged (iron based) | 280 | 98-164 | 98-164 | | 98-164 | 82-131 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 66-98 | 66-98 | | 66-98 | 66-98 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 49-82 | 49-82 | | 49-82 | 49-82 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 459-558 | 459-558 | | 459-558 | 197-328 |
| | 24 | | αβ Alloys | 1050Rm | 164-230 | 164-230 | | 164-230 | 131-197 |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRC | 148-197 | 148-197 | | 148-197 | |
| | 26 | | | 51-55HRC | 131-164 | 131-164 | | 131-164 | |

Calculation of N [RPM]

$$N = \frac{12 \times V_c}{\pi \times D}$$

$$V_c = \frac{N \times \pi \times D}{12}$$



N - Revolution Per Minute [RPM]
V_c - Cutting Speed [ft/min]
D - Workpiece Diameter [Inch]

Recommended Grades and Cutting Speeds Vc [ft/min] **MINIPRO** Mini, Micro and Microscope

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] Coated | | | |
|-------------------------------------|------------|--|------------------------------------|--------------------|------------------|--------------------|---------|
| | | | | VMX (Micro) | VBX (Microscope) | VKX/VBX VTX (Mini) | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 164-394 | 459-656 | 131-262 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 131-328 | 394-591 | 131-262 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 98-262 | 361-591 | 131-262 |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 164-230 | 328-509 | 131-262 |
| | 5 | | Hardened | 275 | 131-197 | 295-476 | 131-262 |
| | 6 | | Hardened | 350 | 98-164 | 262-443 | 131-262 |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 98-164 | 213-377 | 131-197 |
| | 8 | | Hardened | 325 | 82-131 | 164-328 | 131-197 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 98-164 | 98-164 | 131-197 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 82-131 | 82-131 | 131-197 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 197-328 | 262-394 | 131-197 |
| | 12 | | Hardened | 330 | 131-197 | 180-312 | 131-197 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 164-295 | 197-328 | 131-197 |
| | 14 | | Super Austenitic | 200 | 131-197 | 164-295 | 131-197 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 131-197 | 197-262 | 131-197 |
| | 16 | | Hardened | 330 | 98-164 | 148-213 | 131-197 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 131-197 | 164-230 | 131-197 |
| | 18 | | Hardened | 330 | 98-164 | 131-197 | 131-197 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 164-230 | 197-262 | 131-262 |
| | 29 | | Pearlitic (long chips) | 230 | 164-230 | 197-262 | 131-262 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 164-230 | 197-262 | 131-262 |
| | 31 | | High Tensile Strength | 260 | 131-197 | 131-230 | 131-262 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 164-230 | 197-262 | 131-262 |
| | 33 | | Pearlitic | 260 | 197-262 | 230-295 | 131-262 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-984 | 262-787 | 131-394 |
| | 35 | | Aged | 100 | 328-492 | 328-558 | 131-394 |
| | 36 | Aluminium Alloys | Cast | 75 | 328-492 | 328-492 | 131-394 |
| | 37 | | Cast & Aged | 90 | 197-328 | 197-328 | 131-394 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 328-492 | 328-492 | 131-394 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 197-328 | 262-656 | 131-394 |
| | 40 | | Bronze And Non Lead Copper | 100 | 197-328 | 262-656 | 131-394 |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 82-148 | 82-148 | 98-148 |
| | 20 | | Aged (iron based) | 280 | 66-98 | 66-98 | 66-98 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 49-66 | 49-66 | 49-66 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 33-49 | 33-49 | 49-66 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 197-328 | 197-328 | 230-328 |
| | 24 | | α+β Alloys | 1050Rm | 131-164 | 131-164 | 131-164 |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 66-131 | 66-131 | 66-131 |
| | 26 | | | 51-55HRc | 66-131 | 66-131 | 66-131 |

Recommended Grades and Cutting Speeds Vc [ft/min] **VG-Cut**

Thread Turning
Technical Data

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | |
|--------------------------------|-------------------------------------|--|------------------------------------|-----------------------|----------|
| | | | | VPG | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 394-853 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 295-722 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 295-722 |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 295-722 |
| | 5 | | Hardened | 275 | 197-525 |
| | 6 | | Hardened | 350 | 164-328 |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 295-722 |
| | 8 | | Hardened | 325 | 164-328 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 295-722 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 197-525 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 197-525 |
| | 12 | | Hardened | 330 | 164-459 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 197-525 |
| | 14 | | Super Austenitic | 200 | 197-525 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 197-525 |
| | 16 | | Hardened | 330 | 164-459 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 197-525 |
| | 18 | | Hardened | 330 | 164-459 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 525-787 |
| | 29 | | Pearlitic (long chips) | 230 | 459-722 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 525-787 |
| | 31 | | High Tensile Strength | 260 | 328-656 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 328-656 |
| | 33 | | Pearlitic | 260 | 328-656 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 656-1476 |
| | 35 | | Aged | 100 | 656-1148 |
| | 36 | Aluminium Alloys | Cast | 75 | 656-1476 |
| | 37 | | Cast & Aged | 90 | 656-1476 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 656-1148 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 656-1476 |
| | 40 | | Bronze And Non Leaded Copper | 100 | 656-1476 |
| | S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 |
| 20 | | Aged (iron based) | | 280 | 66-164 |
| 21 | | Annealed (nickel or cobalt based) | | 250 | 66-164 |
| 22 | | Aged (nickel or cobalt based) | | 350 | 66-164 |
| 23 | | Titanium Alloys | Pure 99.5 Ti | 400Rm | 98-164 |
| 24 | | | α+β Alloys | 1050Rm | 98-230 |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 66-131 |
| | 26 | | | 51-55HRc | 49-98 |

Recommended Grades, Cutting Speeds Vc [ft/min]

Mini-V

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | |
|-------------------------------------|------------|---|------------------------------------|-------------|---------|
| | | | | VBX / VTX* | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 131-262 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 131-262 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 131-262 |
| | 4 | Low Alloy Steel (alloying elements≤5%) | Non Hardened | 180 | 131-262 |
| | 5 | | Hardened | 275 | 131-262 |
| | 6 | | Hardened | 350 | 131-262 |
| | 7 | High Alloy Steel (alloying elements>5%) | Annealed | 200 | 131-197 |
| | 8 | | Hardened | 325 | 131-197 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 131-197 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 131-197 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 131-197 |
| | 12 | | Hardened | 330 | 131-197 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 131-197 |
| | 14 | | Super Austenitic | 200 | 131-197 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 131-197 |
| | 16 | | Hardened | 330 | 131-197 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 131-197 |
| | 18 | | Hardened | 330 | 131-197 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 131-262 |
| | 29 | | Pearlitic (long chips) | 230 | 131-262 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 131-262 |
| | 31 | | High Tensile Strength | 260 | 131-262 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 131-262 |
| | 33 | | Pearlitic | 260 | 131-262 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 131-394 |
| | 35 | | Aged | 100 | 131-394 |
| | 36 | Aluminium Alloys | Cast | 75 | 131-394 |
| | 37 | | Cast & Aged | 90 | 131-394 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 131-394 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 131-394 |
| | 40 | | Bronze And Non Leaded Copper | 100 | 131-394 |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 66-98 |
| | 20 | | Aged (iron based) | 280 | 66-98 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 49-66 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 33-49 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 131-197 |
| | 24 | | α+β Alloys | 1050Rm | 66-98 |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 49-65 |
| | 26 | | | 51-55HRc | 49-65 |

* Available for sizes V08 and V11. Sizes V14 and V16 are available upon request.

Thread Turning
Technical Data

Cutting Conditions Parameters

| | | |
|--------------------|---|--|
| Workpiece | Material Type | |
| | Material Dimension: Diameter and Length | |
| | Chipflow Character | |
| | Material Hardness | |
| Thread Application | External or Internal | |
| | Profile Shape | |
| | Surface Finish | |
| Machine | Machine Stability | |
| | Max. RPM | |
| | Clamping System Stability | |
| Coolant | Coolant Type | |
| Holders | Holder Cross Section Area | |
| | Holder Overhang | |
| | Through Coolant Option | |
| | Shank Type: Carbide, Alloy, Carbide Implant | |
| Insert | Grade | |
| | Profile Shape: Pitch and Depth | |
| | Nose Radius | |
| | Chipbreaker Style | |

Number of Passes

| Pitch | mm | 0.50 | 0.75 | 1.00 | 1.25 | 1.50 | 1.75 | 2.00 | 2.50 | 3.00 | 3.50 | 4.00 | 4.50 | 5.00 | 5.50 | 6.00 | 8.00 |
|--|-----|------|------|------|------|------|-------|-------|------|------|-------|-------|-------|-------|-------|-------|-------|
| | TPI | 48 | 32 | 24 | 20 | 16 | 14 | 12 | 10 | 8 | 7 | 6 | 5.5 | 5 | 4.5 | 4 | 3 |
| No. of passes | | 4-6 | 4-7 | 4-8 | 5-9 | 6-10 | 7-12 | 7-12 | 8-14 | 9-16 | 10-18 | 11-18 | 11-19 | 12-20 | 12-20 | 12-20 | 15-24 |
| No. of passes (SCB) | | 3-4 | 3-4 | 3-5 | 4-6 | 5-6 | 6-8 | 6-8 | 8-10 | 9-12 | 10-14 | | | | | | |
| No. of passes (Micro / Microscope & Mini) | | 6-9 | 6-11 | 6-12 | 8-14 | 9-15 | 11-18 | 11-18 | | | | | | | | | |

Depths of Cut and Number of Passes for Mini-V

1. Intensive coolant is strongly recommended.
2. Infeed method - modified flank infeed 1°.
3. Number of passes can be decreased when high pressure cooling is used.

Option of modified volume chip

Mini-V

| | Pitch mm | 0.5 | 0.75 | 1 | 1.25 | 1.5 | 1.75 | 2 | 2.5 | 3 | 3.5 | 4 | | | | |
|--------------|-----------|--------------------------|------|----|------|-----|------|----|-----|----|-----|----|----|---|---|--|
| | Pitch TPI | 48 | 32 | 27 | 24 | 20 | 19 | 18 | 16 | 14 | 12 | 10 | 8 | 7 | 6 | |
| Insert Style | Standard | Passes (modified volume) | | | | | | | | | | | | | | |
| V08 | ISO | | | | | | | | | | | | | | | |
| | UN | 13 | 19 | | 25 | 16 | | | 19 | 22 | | | | | | |
| | W | | | | | | | | | | | | | | | |
| | NPT | | | 28 | | | | 43 | | | | | | | | |
| | NPTF | | | | | | | | | | | | | | | |
| V11 | ISO | | | | | | | | | | | | | | | |
| | UN | 13 | 19 | | 25 | 16 | | | 19 | 22 | 24 | | | | | |
| | W | | | | | | | | | | | | | | | |
| | BSPT | | | | | | 19 | | | | | | | | | |
| V14 | ISO | | | | | | | | | | | | | | | |
| | UN | 7 | 10 | | 13 | 16 | | | 19 | 22 | 24 | 32 | 38 | | | |
| | W | | | | | | | | | | | | | | | |
| V16 | ISO | | | | | | | | | | | | | | | |
| | UN | 7 | 10 | | 13 | 16 | | | 19 | 22 | 24 | 32 | 38 | | | |
| | W | | | | | | | | | | | | | | | |

Option of constant depth chip

Mini-V

| | Pitch mm | 0.5 | 0.75 | 1 | 1.25 | 1.5 | 1.75 | 2 | 2.5 | 3 | 3.5 | 4 | | | | |
|--------------|-----------|---------------|-------|-------|-------|-------|-------|-------|-------|--------|--------|-------|-------|---|---|--------|
| | Pitch TPI | 48 | 32 | 27 | 24 | 20 | 19 | 18 | 16 | 14 | 12 | 10 | 8 | 7 | 6 | |
| Insert Style | Standard | Passes (same) | | | | | | | | | | | | | | |
| V08 | ISO | | | | | | | | | | | | | | | |
| | UN | 11-24 | 17-35 | | 23-48 | 18-28 | | | 21-34 | 25-40 | | | | | | |
| | W | | | | | | | | | | | | | | | |
| | NPT | | | 25-53 | | | | 40-83 | | | | | | | | |
| | NPTF | | | | | | | | | | | | | | | |
| V11 | TR | | | | | | | | | 50-104 | 70-145 | | | | | |
| | ISO | | | | | | | | | | | | | | | |
| | UN | 11-24 | 17-35 | | 23-48 | 14-28 | | | 17-34 | 20-40 | 23-46 | | | | | |
| | W | | | | | | | | | | | | | | | |
| | BSPT | | | | | | 21-34 | | | | | | | | | |
| V14 | TR | | | | | | | | | | | | | | | 90-187 |
| | ISO | | | | | | | | | | | | | | | |
| | UN | 11-24 | 17-35 | | 23-48 | 14-28 | | | 9-15 | 11-18 | 11-18 | 12-21 | 18-24 | | | |
| V16 | W | | | | | | | | | | | | | | | |
| | ISO | | | | | | | | | | | | | | | |
| | UN | 11-24 | 17-35 | | 23-48 | 14-28 | | | 9-15 | 11-18 | 11-18 | 12-21 | 18-24 | | | |
| V16 | W | | | | | | | | | | | | | | | |

Number of Passes and Depth of Cut per Pass for Multi+ Inserts



Thread Turning
Technical Data

| Standard | Insert Type | Insert Size | | Pitch | Teeth | Ordering Code | Passes | Depth of cut per pass | | | |
|--------------|--------------|-------------|---------------|--------|-----------------|-----------------|-----------------|-----------------------|------|------|------|
| | | IC | L Inch | | | | | RH | | | |
| | | | | | | | | 1 | 2 | 3 | 4 |
| ISO External | M+ | 3/8" | .63 | 1.0 mm | 3 | 3ER1.0ISO3M+... | 2 | .013 | .012 | | |
| | | | | 1.5 mm | 2 | 3ER1.5ISO2M+... | 3 | .013 | .012 | .011 | |
| | | | | 2.0 mm | 2 | 3ER2.0ISO2M+... | 3 | .018 | .016 | .015 | |
| | | 1/2" | .87 | 1.5 mm | 3 | 4ER1.5ISO3M+... | 2 | .019 | .018 | | |
| | | | | 2.0 mm | 2 | 4ER2.0ISO2M+... | 3 | .018 | .016 | .015 | |
| | | | | 2.0 mm | 3 | 4ER2.0ISO3M+... | 2 | .025 | .023 | | |
| | 5/8" | 1.06 | 3.0 mm | 2 | 5ER3.0ISO2M+... | 4 | .018 | .017 | .015 | .014 | |
| | T+ | 1/2" T | .87 | 1.5 mm | 8 | 4ER1.5ISO8T+... | 1 | .037 | | | |
| | | | | 2.0 mm | 8 | 4ER2.0ISO8T+... | 1 | .048 | | | |
| | ISO Internal | M+ | 3/8" | .63 | 1.0 mm | 3 | 3IR1.0ISO3M+... | 2 | .012 | .011 | |
| 1.5 mm | | | | | 2 | 3IR1.5ISO2M+... | 3 | .012 | .011 | .011 | |
| 2.0 mm | | | | | 2 | 3IR2.0ISO2M+... | 3 | .017 | .015 | .014 | |
| 1/2" | | | .87 | 1.5 mm | 3 | 4IR1.5ISO3M+... | 2 | .018 | .016 | | |
| | | | | 2.0 mm | 2 | 4IR2.0ISO2M+... | 3 | .017 | .015 | .014 | |
| | | | | 2.0 mm | 3 | 4IR2.0ISO3M+... | 2 | .023 | .022 | | |
| 5/8" | | 1.06 | 3.0 mm | 2 | 5IR3.0ISO2M+... | 4 | .019 | .018 | .017 | .015 | |
| T+ | | 1/2" | .87 | 1.5 mm | 8 | 4IR1.5ISO8T+... | 1 | .034 | | | |
| | | | | 2.0 mm | 8 | 4IR2.0ISO8T+... | 1 | .045 | | | |
| UN External | | M+ | 3/8" | .63 | 20 TPI | 3 | 3ER20UN3M+... | 2 | .016 | .015 | |
| | 18 TPI | | | | 2 | 3ER18UN2M+... | 3 | .013 | .011 | .011 | |
| | 18 TPI | | | | 3 | 3ER18UN3M+... | 2 | .018 | .017 | | |
| | 16 TPI | | | | 2 | 3ER16UN2M+... | 3 | .014 | .013 | .012 | |
| | 14 TPI | | | | 2 | 3ER14UN2M+... | 3 | .017 | .015 | .015 | |
| | 12 TPI | | | | 2 | 3ER12UN2M+... | 3 | .019 | .017 | .016 | |
| | 1/2" | | .87 | 16 TPI | 3 | 4ER16UN3M+... | 2 | .020 | .019 | | |
| | | | | 14 TPI | 2 | 4ER14UN2M+... | 3 | .017 | .015 | .015 | |
| | | | | 12 TPI | 2 | 4ER12UN2M+... | 3 | .019 | .017 | .016 | |
| | | | | 12 TPI | 3 | 4ER12UN3M+... | 2 | .026 | .025 | | |
| | 11 TPI | 2 | 4ER11UN2M+... | 4 | .017 | .015 | .014 | .013 | | | |
| | 10 TPI | 2 | 4ER10UN2M+... | 4 | .018 | .017 | .016 | .014 | | | |
| | 5/8" | 1.06 | 8 TPI | 2 | 5ER8UN2M+... | 4 | .022 | .020 | .019 | .016 | |
| | UN Internal | M+ | 3/8" | .63 | 12 TPI | 2 | 3IR12UN2M+... | 3 | .018 | .015 | .015 |
| 14 TPI | | | | | 2 | 3IR14UN2M+... | 3 | .016 | .014 | .013 | |
| 16 TPI | | | | | 2 | 3IR16UN2M+... | 3 | .013 | .012 | .011 | |
| 1/2" | | | .87 | 16 TPI | 3 | 4IR16UN3M+... | 2 | .019 | .017 | | |
| | | | | 14 TPI | 2 | 4IR14UN2M+... | 3 | .016 | .014 | .013 | |
| | | | | 12 TPI | 2 | 4IR12UN2M+... | 3 | .018 | .015 | .015 | |
| 12 TPI | | 3 | 4IR12UN3M+... | 2 | .025 | .023 | | | | | |
| 5/8" | | 1.06 | 8 TPI | 2 | 5IR8UN2M+... | 4 | .020 | .019 | .017 | .015 | |
| BSW External | | M+ | 3/8" | .63 | 28 TPI | 2 | 3ER28W2M+... | 3 | .009 | .008 | .008 |
| | | | | | 19 TPI | 2 | 3ER19W2M+... | 3 | .013 | .011 | .011 |
| | 19 TPI | | | | 3 | 3ER19W3M+... | 2 | .018 | .016 | | |
| | 14 TPI | | | | 2 | 3ER14W2M+... | 3 | .017 | .015 | .014 | |
| | 1/2" | | .87 | 14 TPI | 3 | 4ER14W3M+... | 2 | .024 | .022 | | |
| | | | | 11 TPI | 2 | 4ER11W2M+... | 4 | .017 | .015 | .014 | .012 |

Number of Passes and Depth of Cut per Pass for Multi+ Inserts

| Standard | Insert Type | Insert Size | | Pitch | Teeth | Ordering Code | Passes | Depth of cut per pass | | | | |
|---------------|-------------|-------------|--------|-------|-------|---------------|------------------|-----------------------|------|------|------|------|
| | | IC | L Inch | | | | | RH | | | | |
| BSW Internal | M+ | 3/8" | .63 | 14 | TPI | 2 | 3R14W2M+... | 3 | .017 | .015 | .014 | |
| | | 1/2" | .87 | 11 | TPI | 2 | 4R11W2M+... | 4 | .017 | .015 | .014 | .012 |
| NPT External | M+ | 3/8" | .63 | 14 | TPI | 2 | 3ER14NPT2M+... | 3 | .020 | .018 | .017 | |
| | | 1/2" | .87 | 11.5 | TPI | 2 | 4ER11.5NPT2M+... | 4 | .018 | .017 | .017 | .016 |
| | | 5/8" | 1.06 | 11.5 | TPI | 3 | 5ER11.5NPT3M+... | 4 | .019 | .017 | .017 | .015 |
| | Z+ | 1/2" | .87 | 8 | TPI | 2 | 4ER11.5NPT2Z+... | 4 | .018 | .017 | .017 | .016 |
| | | 5/8" | 1.06 | 8 | TPI | 2 | 5ER8NPT2M+... | 4 | .028 | .025 | .024 | .021 |
| NPT Internal | M+ | 3/8" | .63 | 14 | TPI | 2 | 3R14NPT2M+... | 3 | .020 | .018 | .017 | |
| | | 1/2" | .87 | 11.5 | TPI | 2 | 4R11.5NPT2M+... | 4 | .018 | .017 | .017 | .016 |
| | | 5/8" | 1.06 | 11.5 | TPI | 2 | 5R11.5NPT3M+... | 4 | .019 | .017 | .017 | .015 |
| | Z+ | 1/2" | .87 | 8 | TPI | 2 | 4R11.5NPT2Z+... | 4 | .018 | .017 | .017 | .016 |
| | | 5/8" | 1.06 | 8 | TPI | 2 | 5R8NPT2M+... | 4 | .028 | .025 | .024 | .021 |
| NPTF External | M+ | 3/8" | .63 | 14 | TPI | 2 | 3ER14NPTF2M+... | 3 | .020 | .017 | .017 | |
| NPTF Internal | M+ | 3/8" | .63 | 14 | TPI | 2 | 3R14NPTF2M+... | 3 | .020 | .017 | .017 | |

 Thread Turning
Technical Data

API RD, API BUT, OTTM, OTTG

The following table provides the optimal cutting pass division options, depending on the material, machine stability and clamping conditions:

| Application | No. of Passes/ Pass No. | 1 | 2 | 3 | 4 | 5 | 6 |
|--------------------------------|-------------------------|------|------|------|------|------|------|
| APIRD 8 Ex, In | 3 passes | .035 | .032 | .004 | | | |
| | 4 passes | .024 | .023 | .020 | .004 | | |
| | 5 passes | .019 | .019 | .017 | .013 | .004 | |
| | 6 passes | .015 | .016 | .015 | .011 | .009 | .004 |
| APIRD 10 Ex, In | 3 passes | .026 | .025 | .004 | | | |
| | 4 passes | .017 | .018 | .016 | .004 | | |
| | 5 passes | .013 | .015 | .013 | .010 | .004 | |
| | 6 passes | .011 | .013 | .011 | .009 | .007 | .004 |
| BUT 5 Ex, In | 3 passes | .030 | .028 | .004 | | | |
| | 4 passes | .020 | .020 | .018 | .004 | | |
| | 5 passes | .016 | .016 | .015 | .011 | .004 | |
| | 6 passes | .013 | .014 | .013 | .010 | .008 | .004 |
| OTTM 5 Ex, In OTTG 5 Ex, In | 3 passes | .030 | .029 | .004 | | | |
| | 4 passes | .020 | .020 | .019 | .004 | | |
| | 5 passes | .016 | .016 | .015 | .012 | .004 | |
| | 6 passes | .013 | .014 | .013 | .010 | .009 | .004 |



M+ Style



Z+ Style




T+ Style



14D Style



CNGA Style




Chaser Style

Cutting Speed Recommendations for Materials Specified by API STB


| Material | J55-K55 | N80-L80-C95-TN70 | TN95-P110-TN110 |
|------------------------|---------|------------------|-----------------|
| Cutting Speed (ft/min) | 558-656 | 492-591 | 427-525 |

Step by Step Thread Turning - Example 1




Application:
 Thread: External Right Hand
 1 1/2 x 10UN
 Material: 4140 (25 HRC)

1 Choose the Thread Turning Method



Feed direction towards the chuck was chosen.
 Therefore, an external right hand insert and an external right hand holder will be used.


2 Choose the Insert Size



Chosen insert: 3ER10UN


| Insert Size | | Pitch | Ordering Code | Anvil | Toolholder |
|-------------|--------|-------|---------------|-------|------------|
| IC | L Inch | TPI | RH | RH | |
| 3/8" | .63 | 10 | 3ER10UN... | YE3 | AL..-3(LH) |

3 Choose the Toolholder



Chosen toolholder: AL100-3

| Insert Size | | Ordering Code | Dimensions Inch | | |
|-------------|---------|---------------|-----------------|------|------|
| IC | RH | H=H1=B | F | L1 | L2 |
| 3/8" | AL100-3 | 1.00 | 1.00 | 6.05 | 1.20 |



From the table, using a pitch of 2.5 mm (10 TPI) and a workpiece diameter of 40 mm (1.57"), we find the helix angle to be 1.5°.

5 Choose the Correct Anvil

Anvil chosen: YE3

| Insert Size | | Ordering Code | | Holder | Ordering Code | 3.5 | 2.5 | 1.5 | 0.5 |
|-------------|--------|---------------|--------|--------|---------------|--------|-----|------------|-----|
| IC | L Inch | | | | | | | | |
| 3/8" | .63 | ER/IL | YE3-2P | YE3-1P | YE3 | YE3-1N | | | |

6 Choose the Carbide Grade and Cutting Speed

Carbide Grade chosen: VTX

Cutting Speed: 420 ft/min

| Material: | | Hardness Brinell HB | VTX | VCB |
|-----------|---|---------------------|-----|---------|
| P | Low alloy steel (alloying elements ≤ 5%) | Non hardened | 180 | 328-590 |
| | | Hardened | 275 | 246-459 |
| | | Hardened | 350 | 230-433 |

7 Determine the Number of Passes

Number of passes: 14


ISO External

| Pitch | mm | 1.50 | 1.75 | 2.00 | 2.50 | 3.00 | 3.50 | 4.00 |
|---------------|-----|------|------|------|-------------|------|-------|-------|
| | TPI | 16 | 14 | 12 | 10 | 8 | 7 | 6 |
| No. of Passes | | 6-10 | 7-12 | 7-12 | 8-14 | 9-16 | 10-18 | 11-18 |

Summary


| | |
|----------------------------|------------------------------------|
| Thread Type | 1½x10UN External Right Hand |
| 1 Feed Direction: | Towards the chuck |
| 2 Insert and Grade: | 3ER10UN VTX |
| 3 Toolholder: | AL 100 - 3 |
| 4 Helix Angle: | 1.5° |
| 5 Anvil: | YE3 |
| 6 Cutting Speed: | 420 ft/min |
| 7 Number of Passes: | 10 |

Step by Step Thread Turning - Example 2




Application:
 Thread: Internal Right Hand
 ACME
 Pitch: 6 TPI
 Bore dia: 5"
 Material: Stainless Steel Austemetic

1 Choose the Thread Turning Method



To facilitate the removal of chips from the machined area, we chose a feed direction away from the chuck. Therefore, an internal left hand insert and an internal left hand toolholder are to be used.


2 Choose the Insert Size



Chosen insert: 4IL6ACME

| Insert Size | Pitch | Ordering Code | Anvil | Toolholder |
|-------------|--------|---------------|-------------|-----------------|
| IC | L Inch | TPI | RH | LH |
| 1/2" | .87 | 6 | 4IL6ACME... | YE4 AVR..-4(LH) |


3 Choose the Toolholder



Chosen toolholder: AVR 40-4LH

| Insert Size | Ordering Code | Dimensions Inch | | | | | | Min Bore |
|-------------|---------------|-----------------|-------|------|------|------|-----|----------|
| IC | RH | A | L | L1 | D | D1 | F | Inch |
| 1/2" | AVR150-4 | 1.34 | 12.00 | 2.50 | 1.50 | 1.50 | .98 | 1.75 |

4 Determine the Helix Angle



In this case, a right hand thread is being turned with a left hand toolholder. The reverse helix method is used. From the lower part of the table, using a pitch of 6 TPI and a bore diameter of 5", we obtain a helix angle of **-0.65°**.

5 Choose the Correct Anvil

Anvil chosen: YE4-2N

| Insert Size | | Ordering Code | | | | | |
|-------------|--------|---------------|-----|--------|----------|---------------|--------|
| IC | L Inch | | | | | | |
| 1/2" | .87 | ER/IL | YE4 | YE4-1N | YE4-1.5N | YE4-2N | YE4-3N |

6 Choose the Carbide Grade and Cutting Speed

Carbide grade chosen: VTX
 Cutting speed: 140 ft/min

| | Material: | Hardness Brinell HB | VTX | VCB |
|----------|----------------------------|---------------------|-----|---------|
| M | Stainless Steel Austenitic | Austenitic | 180 | 295-459 |
| | | Super Austenitic | 200 | 131-136 |
| | | | | 266-394 |
| | | | | 98-328 |

7 Determine the Number of Passes

Number of passes: 18

ACME External & Internal

| Pitch | mm | 3.00 | 3.50 | 4.00 | 4.50 | 5.00 | 5.50 | 6.00 |
|---------------|-----|------|-------|--------------|-------|-------|-------|-------|
| | TPI | 8 | 7 | 6 | 5.5 | 5 | 4.5 | 4 |
| No. of Passes | | 9-16 | 10-18 | 11-18 | 11-19 | 12-20 | 12-20 | 12-20 |

Summary

| | |
|----------------------------|--------------------------------------|
| Thread Type | 5"x6 ACME Internal Right Hand |
| 1 Feed Direction: | Away from the chuck |
| 2 Insert and Grade: | 4IL6ACME VTX |
| 3 Toolholder: | AVR 150-4LH |
| 4 Helix Angle: | -0.65° |
| 5 Anvil: | YE4-2N |
| 6 Cutting Speed: | 420 ft/min |
| 7 Number of Passes: | 18 |

Material Comparison Table

| Material Group | Vargus No. | USA AISI/SAE | Germany W.-Nr. | Germany DIN | Great Britain BS | France AFNOR | Italy UNI |
|----------------|------------|---------------------|----------------|-----------------|---------------------|-------------------------|-------------------|
| P Steel | 1 | 1015 | 1.0037 | St37-2 | Fe360B | E24-2 | Fe360 B FU |
| | 1 | 1020 | 1.0044 | St44-2 | Fe430B FN | E28-2 | Fe430B FN |
| | 2 | ASTM A570Gr.50 | 1.0050 | St50-2 | Fe490-2 FN | A50-2 | Fe490 |
| | 2 | - | 1.0070 | St70-2 | Fe690-2 FN | A70-2 | Fe690 |
| | 1 | 1015 | 1.0401 | C15 | 080M15 | CC12 | C15C16 |
| | 1 | 1020 | 1.0402 | C22 | 050A20 | CC20 | C20C21 |
| | 2 | 1035 | 1.0501 | C35 | 060A35 | CC35 | C35 |
| | 2 | 1045 | 1.0503 | C45 | 080M46 | CC45 | C45 |
| | 2 | 1055 | 1.0535 | C55 | 070M55 | - | C55 |
| | 2 | 1060 | 1.0601 | C60 | 080A62 | CC55 | C60 |
| | 1 | 1213 | 1.0715 | 95Mn28 | 230M07 | S250 | CF9SMn28 |
| | 1 | 12L13 | 1.0718 | 95MnPb28 | - | S250Pb | CF9SMnPb28 |
| | 1 | - | 1.0722 | 10SPb20 | - | 10PbF2 | CF10SPb20 |
| | 2 | 1140 | 1.0726 | 35S20 | 212M36 | 35MF4 | - |
| | 2 | 1215 | 1.0736 | 95Mn36 | 240M07 | S300 | CF9SMn36 |
| | 2 | 12L14 | 1.0737 | 95MnPb36 | - | S300Pb | CF9SMnPb36 |
| | 2 | 9255 | 1.0904 | 55Si7 | 250A53 | 55S7 | 55Si8 |
| | 2 | 9262 | 1.0961 | 60SiCr7 | - | 60SC7 | 60SiCr8 |
| | 1 | 1015 | 1.1141 | Ck15 | 080M15 | XC1 2 | C16 |
| | 2 | 1039 | 1.1157 | 40Mn4 | 150M36 | 35M5 | - |
| | 2 | 1025 | 1.1158 | Ck25 | - | - | - |
| | 2 | 1335 | 1.1167 | 36Mn5 | - | 40M5 | - |
| | 2 | 1330 | 1.1170 | 28Mn6 | 150M28 | 20M5 | C28Mn |
| | 2 | 1035 | 1.1183 | Cf35 | 060A35 | XC38TS | C36 |
| | 2 | 1045 | 1.1191 | Ck45 | 080M46 | XC42 | C45 |
| | 2 | 1055 | 1.1203 | Ck55 | 070M55 | XC55 | C50 |
| | 3 | 1050 | 1.1213 | Cf53 | 060A52 | XC48TS | C53 |
| | 3 | 1060 | 1.1221 | Ck60 | 080A62 | XC60 | C60 |
| | 8 | 1095 | 1.1274 | Ck101 | 060A96 | - | - |
| | 9 | - | 1.3401 | X120Mn12 | Z120M12 | Z120M12 | XG120Mn12 |
| | 8 | 52100 | 1.3505 | 100Cr6 | 534A99 | 100C6 | 100Cr6 |
| | 8 | ASTM A20Gr.A | 1.5415 | 15Mo3 | 1501-240 | 15D3 | 16Mo3KW |
| | 8 | 4520 | 1.5423 | 16Mo5 | 1503-245-420 | - | 16Mo5 |
| | 4 | ASTMA350LF5 | 1.5622 | 14Ni6 | - | 16N6 | 14Ni6 |
| | 8 | ASTM A353 | 1.5662 | X8Ni9 | 1501-509; 510 | - | X10Ni9 |
| | 8 | 2515 | 1.5680 | 12Ni19 | - | Z18N5 | - |
| | 5 | 3135 | 1.5710 | 36NiCr6 | 640A35 | 35NC6 | - |
| | 5 | 3415 | 1.5732 | 14NiCr10 | - | 14NC11 | 16NiCr11 |
| | 5 | 3415; 3310 | 1.5752 | 14NiCr14 | 655M13; 655M12 | 12NC15 | - |
| | 5 | 9840 | 1.6511 | 36CrNiMo4 | 816M40 | 40NCD3 | 38NiCrMo4(KB) |
| | 5 | 8620 | 1.6523 | 21NiCrMo2 | 805M20 | 20NCD2 | 20NiCrMo2 |
| | 5 | 8740 | 1.6546 | 40NiCrMo22 | 311-Type7 | - | 40NiCrMo2(KB) |
| | 5 | 4340 | 1.6582 | 34CrNiMo6 | 817M40 | 35NCD6 | 35NiCrMo6(KB) |
| | 5 | - | 1.6587 | 17CrNiMo6 | 820A16 | 18NCD6 | - |
| | 5 | - | 1.6657 | 14NiCrMo134 | 832M13 | - | 15NiCrMo13 |
| | 2 | 5015 | 1.7015 | 15Cr3 | 523M15 | 12C3 | - |
| | 5 | 5132 | 1.7033 | 34Cr4 | 530A32 | 32C4 | 34Cr4(KB) |
| | 5 | 5140 | 1.7035 | 41Cr4 | 530M40 | 42C4 | 41Cr4 |
| | 5 | 5140 | 1.7045 | 42Cr4 | - | - | - |
| | 5 | 5115 | 1.7131 | 16MnCr5 | (527M20) | 16MC5 | 16MnCr5 |
| | 5 | 5155 | 1.7176 | 55Cr3 | 527A60 | 55C3 | - |
| | 5 | 4130 | 1.7218 | 25CrMo4 | 1717CDS110 | 25CD4 | 25CrMo4(KB) |
| | 5 | 4137; 4135 | 1.7220 | 34CrMo4 | 708A37 | 35CD4 | 35CrMo4 |
| | 5 | 4140; 4142 | 1.7223 | 41CrMo4 | 708M40 | 42CD4TS | 41CrMo4 |
| | 5 | 4140 | 1.7225 | 42CrMo4 | 708M40 | 42CD4 | 42CrMo4 |
| | 5 | - | 1.7262 | 15CrMo5 | - | 12CD4 | - |
| | 5 | ASTM A182; F11; F12 | 1.7335 | 13CrMo4 4 | 1501-620Gr.27 | 15CD3.5; 15CD4.5 | 14CrMo4 5 |
| | 5 | - | 1.7361 | 32CrMo12 | 722M24 | 30CD12 | 32CrMo12 |
| | 5 | ASTM A182; F22 | 1.7380 | 10CrMo9 10 | 1501-622; Gr.31; 45 | 12CD9; 10 | 12CrMo9, 10 |
| | 5 | - | 1.7715 | 14MoV6 3 | 1503-660-440 | - | - |
| | 5 | 6150 | 1.8159 | 50CrV4 | 735A50 | 50CV4 | 50CrV4 |
| | 8 | - | 1.8509 | 41CrAlMo7 | 905M39 | 40CAD6, 12 | 41CrAlMo7 |
| | 8 | - | 1.8523 | 39CrMoV13 9 | 897M39 | - | 36CrMoV12 |
| | 5 | W.110 | 1.1545 | C105W1 | - | Y1105 | C98KU; C100KU |
| | 5 | W.112 | 1.1663 | C125W | - | Y2120 | C120KU |
| | 8 | L3 | 1.2067 | 100Cr6 | BL3 | Y100C6 | - |
| | 10 | D3 | 1.2080 | X210Cr12 | BD3 | Z200Cr12 | X210Cr13KU |
| | 10 | - | - | - | - | - | X250Cr12KU |
| | 10 | - | 1.2311 | 40CrMnMo7 | - | - | 35CrMo8KU |
| | 10 | - | 1.2312 | 40CrMnMoS8-6 | - | - | - |
| | 10 | H11 | 1.2343 | X38CrMoV5-1 | BH11 | Z38CDV5 | X37CrMoV51 1KU |
| | 10 | H13 | 1.2344 | X40CrMoV5-1 | BH13 | Z40CDV5 | X35CrMoV05KU |
| | 10 | - | - | - | - | - | X40CrMoV511KU |
| | 10 | A2 | 1.2363 | X100CrMoV5-1 | BA2 | Z1 00CDV5 | X100CrMoV51KU |
| | 10 | - | 1.2367 | X38CrMoV5-3 | - | Z38CDV5-3 | - |
| | 10 | D2 | 1.2379 | X155CrVMo 12-1 | BD2 | Z160CDV12 | X155CrVMo12 1 KU |
| | 10 | - | 1.2419 | 105WCr6 | - | 105WC13 | 10WCr6; 107WCr5KU |
| | 10 | - | 1.2436 | X210CrW12 | - | - | X215CrW121KU |
| | 10 | S1 | 1.2542 | 45WCrV17 | BS1 | - | 45WCrV8KU |
| | 10 | H21 | 1.2581 | X30WCrV9 3 | BH21 | Z30WCV9 | X30WCrV9 3KU |
| | 10 | - | 1.2601 | X165CrMoV12 | - | - | X165CrMoV12KU |
| | 10 | L6 | 1.2713 | 55NiCrMoV6 | - | 55NCDV7 | - |
| | 10 | - | 1.2738 | 40CrMnNiMo8-6-4 | - | - | - |
| | 10 | W210 | 1.2833 | 100V1 | BW2 | Y1105V; 100V2 | - |
| | 10 | - | 1.3243 | S 6-5-2-5 | - | Z85WDKCV-06-05-05-04-02 | HS 6-5-2-5 |
| | 10 | T4 | 1.3255 | S 18-1-2-5 | BT4 | Z80WKCV-18-05-04-01 | X78WCo1805KU |
| | 10 | M2 | 1.3343 | S 6-5-2 | BM2 | Z85WDCV-06-05-04-02 | X82WMo0605KU |
| | 10 | M7 | 1.3348 | S 2-9-2 | - | Z100WCWV-09-04-02-02 | HS 2-9-2 |
| | 10 | T1 | 1.3355 | S 18-0-1 | BT1 | Z80WCV-18-04-01 | X75W18KU |

Thread Turning
Technical Data

| Sweden SS | Japan JIS | Russia GOST | Spain UNE | Vargus No. |
|--------------|-----------------|-----------------------|--|---------------|
| 1311 | STKM 12A;C | – | Fe360B | 1 |
| 1412 | SM400A;B;C | St4ps;sp | Fe430B FN | 1 |
| 1550 | SS490 | St5ps;sp | A490-2 | 2 |
| – | – | – | A690-2 | 2 |
| 1350 | – | – | F.111 | 1 |
| 1450 | – | 20 | 1 C 22 ; F.112 | 1 |
| 1550 | – | 30 | F. 113 | 2 |
| 1650 | – | 45 | F.114 | 2 |
| 1655 | – | 55 | F.115 | 2 |
| – | – | 60(G) | – | 2 |
| 1912 | SUM22 | – | F.2111-11SMn28 | 1 |
| 1914 | SUM22L | – | F.2112-11SMnPb28 | 1 |
| – | – | – | F.2122-10SPb20 | 1 |
| 1957 | – | – | F.210.G | 2 |
| – | – | – | F.2113-12SMn35 | 2 |
| 1926 | – | – | F.2114-12SMnPb35 | 2 |
| 2085 | – | 55S2 | F.1440-56Si7 | 2 |
| – | – | – | F.1442-60SiCr8 | 2 |
| 1370 | S15C | 15 | F.1110-C15k ; F.1511-C16k | 1 |
| – | – | 40G | – | 2 |
| – | S25C | 25 | F.1120-C25k | 2 |
| 2120 | SMn438(H) | 35G2 ; 35GL | F.1203-36Mn6 ; F.8212-36Mn5 | 2 |
| – | SCM1 | 30G | 28Mn6 | 2 |
| 1572 | S35C | 35 | – | 2 |
| 1672 | S45C | 45 | F.1140-C45k ; F.1142-C48k | 2 |
| – | S55C | 55 | F.1150-C55k | 2 |
| 1674 | S50C | 50 | – | 3 |
| 1678 | S58C | 60 ;60G ;60GA | – | 3 |
| 1870 | SUP4 | – | – | 8 |
| – | SCMnH/1 | 110G13L | F.8251-AM-X120Mn12 | 9 |
| 2258 | SUJ2 | SchCh15 | F.1310-100Cr6 | 8 |
| 2912 | – | – | F.2601-16Mo3 | 8 |
| – | – | – | F.2602-16Mo5 | 8 |
| – | – | – | F.2641-15Ni6 | 4 |
| – | – | – | F.2645-X8Ni09 | 8 |
| – | – | – | – | 8 |
| – | SNC236 | – | – | 5 |
| – | SNC415(H) | – | F.1540-15NiCr11 | 5 |
| – | SNC81 5(H) | – | – | 5 |
| – | – | 40ChN2MA ; 40ChGNM | F.1280-35NiCrMo4 | 5 |
| 2506 | SNCM220(H) | 20ChGNM | F.1552-20NiCrMo2 ; F.1534-20NiMo31 | 5 |
| – | SNCM240 | 38ChGNM | F.1204-40NiCrMo2 ; F.1205-40NiCrMo2DF | 5 |
| 2541 | – | 38Ch2N2MA | F.1272-40NiCrMo7 ;34CrNiMo6 | 5 |
| – | – | – | F.1560-14NiCrMo13 | 5 |
| – | – | – | F.1560-14NiCrMo13 ;F.1569-14NiCrMo131 | 5 |
| – | SCr415(H) | 15Ch | – | 2 |
| – | SCr430(H) | 35Ch | F.8221-35Cr4 | 5 |
| – | SCr440(H) | 40Ch | F.1211-41Cr4DF ; F.1202-42Cr4 | 5 |
| 2245 | SCr440 | 40Ch | F.1202-42Cr4 | 5 |
| 2511 | – | 18ChG | F.1516-16MnCr5 ; F.1517-16MnCr5 | 5 |
| – | SUP9(A) | 50ChGA | F.1431-55Cr3 | 5 |
| 2225 | SCM420 | 20ChM ; 30ChM | F.8372-AM26CrMo4;F.8330-AM25CrMo4;F.1256-30CrMo4-1 | 5 |
| 2234 | SCM432 ; SCCRM3 | AS38ChGM;35ChM;35ChML | F.8331-AM34CrMo4;F.823134CrMo4;F.1250-35CrMo4;F.1254-35CrMo4DF | 5 |
| 2244 | SCM440 | 40ChFA | F.8332-AM42CrMo4;F.8232-42CrMo4;F.1252-40CrMo4 | 5 |
| 2244 | SCM440(H) | – | F.8332-AM42CrMo4;F.8232-42CrMo4;F.1252-40CrMo4 | 5 |
| 2216 | SCM415(H) | – | F.1551-12CrMo4 | 5 |
| – | – | 12ChM ; 15ChM | F.2631-14CrMo45 | 5 |
| 2240 | – | – | F.124.A | 5 |
| 2218 | – | 12Ch8 | TU.H | 5 |
| – | – | – | F.2621-13MoCrV6 | 5 |
| 2230 | SUP10 | 50ChGFA ; 50ChFA | F.1430-51CrV4 | 5 |
| 2940 | – | 38ChMJuA | F.1740-41CrAlMo7 | 8 |
| – | – | – | – | 8 |
| 1880 | – | U10A-1;2 | F.516 | 5 |
| – | SK2 | U13 | F.5123 ; C120 | 5 |
| – | – | Ch | F.5230 ; 100Cr6 | 8 |
| – | SKD1 | Ch12 | F.5212 ; X210 Cr12 | 10 |
| – | – | – | – | 10 |
| – | – | – | – | 10 |
| – | – | – | – | 10 |
| – | SKD6 | 4ChMFS | F.5317 ; X37 CrMoV5 | 10 |
| 2242 | SKD61 | 4ChMF1S | F.5318 ; X40CrMoC5 | 10 |
| – | – | – | – | 10 |
| 2260 | SKD12 | – | F.5227 ; X100CrMoV5 | 10 |
| – | – | – | – | 10 |
| 2310 | SKD11 | – | F.520A | 10 |
| 2140 | SKS31;SKS2,SKS3 | ChWG | F.5233 ; 105WCr5 | 10 |
| 2312 | SKD2 | – | F.5213 ; X210CrW12 | 10 |
| 2710 | – | 5ChW2SF | F.5241 ; 45WCrSi8 | 10 |
| – | SKD5 | 3Ch2W8F | F.5323 ; X30WCrV9 | 10 |
| 2310 | – | – | F.5211 ; X160CrMoV12 | 10 |
| – | SKT4 | 5ChNM | F.520S | 10 |
| – | – | – | – | 10 |
| – | SKS43 | – | – | 10 |
| 2723 | SKH55 | 2723 | R6M5K5 | 10 |
| – | SKH3 | – | F.5530 ; 18-1-1-5 | 10 |
| 2722 | SKH9 | (R6AM5) ; R6M5 | F.5603 ; 6-5-2 | 10 |
| 2782 | – | – | F.5607 ; 18-0-1 | 10 |
| – | SKH2 | R18 | F.5520 ; 18-0-1 | 10 |

P







Material Comparison Table (con't)

| Material Group | Vargus No. | USA AISI/SAE | Germany W.-Nr. | Germany DIN | Great Britain BS | France AFNOR | Italy UNI | |
|-------------------------------------|-----------------------|--------------|------------------|-------------------|------------------|----------------------|-----------------|---|
| M Stainless Steel | 12 | 403 | 1.4000 | X6Cr13 | 403S17 | Z6C13 | X6Cr13 | |
| | 12 | - | 1.4001 | X7Cr14 | - | - | - | |
| | 12 | 410 | 1.4006 | X10Cr13 | 410S21 | Z10C14 | X12Cr13 | |
| | 12 | 430 | 1.4016 | X6Cr17 | 430S15 | Z8C17 | X8Cr17 | |
| | 12 | - | 1.4027 | G-X20Cr14 | 420C29 | Z20C13M | - | |
| | 12 | - | 1.4034 | X46Cr13 | 420S45 | Z40CM;Z38C13M | X40Cr14 | |
| | 12 | 431 | 1.4057 | X20CrNi172 | 431S29 | Z15CNi6.02 | X16CrNi16 | |
| | 12 | 430 | 1.4104 | X12CrMoS17 | - | Z10CF17 | X10CrS17 | |
| | 12 | 434 | 1.4113 | X6CrMo171 | 434S17 | Z8CD17.01 | X8CrMo17 | |
| | 12 | - | 1.4313 | X5CrNi134 | 425C11 | Z4CND13.4M | - | |
| | 12 | - | 1.4408 | G-X6CrNiMo18 10 | 316C16 | - | - | |
| | 12 | HW3 | 1.4718 | X45CrSi93 | 401S45 | Z45CS 9 | X45CrSi8 | |
| | 12 | 405 | 1.4724 | X10CrAl13 | 403S17 | Z10C13 | X101CrAl12 | |
| | 11 | - | 1.4742 | X10CrAl18 | 430S15 | Z12CAS18 | X8Cr17 | |
| | 12 | HNV6 | 1.4747 | X80CrNiSi20 | 443S65 | Z80CSN20.02 | X80CrSiNi20 | |
| | 11 | 446 | 1.4762 | X10CrAl24 | - | Z10CAS24 | X16Cr26 | |
| | 13 | 304 | 1.4301 | X5CrNi18 10 | 304S15 | Z6CN18.09 | X5CrNi1810 | |
| | 13 | 303 | 1.4305 | X10CrNiSi18 9 | 303S21 | Z10CNF 18.09 | X10CrNiSi 18.09 | |
| | 13 | 304L | 1.4306 | X2CrNi19 11 | 304S12;304C12 | Z2CN18.10;Z3CN 19.10 | X2CrNi18.11 | |
| | 13 | CF8 | 1.4308 | G-X6CrNi18 9 | 304C15 | Z6CN18.10M | - | |
| | 13 | 301 | 1.4310 | X12CrNi177 | 301S21 | Z12CN 17.07 | X1 2CrNi1 707 | |
| | 13 | 304LN | 1.4311 | X2CrNiN18 10 | 304S62 | Z2CN18.10 | - | |
| | 13 | 316 | 1.4401 | X5CrNiMo17122 | 316S16 | Z6CND17.11 | X5CrNiMo17 12 | |
| | 13 | 316LN | 1.4429 | X2CrNiMoN17133 | - | Z2CND17.13 | - | |
| | 13 | 316L | 1.4435 | X2CrNiMo18143 | 316S12 | Z2CND17.13 | X2CrNiMo17 13 | |
| | 13 | 317L | 1.4438 | X2CrNiMo17133 | 317S12 | Z2CND19.15 | X2CrNiMo18 16 | |
| | 13 | 329 | 1.4460 | X8CrNiMo275 | - | - | - | |
| | 12 | 321 | 1.4541 | X6CrNiTi18 10 | 2337 | Z6CNT18.10 | X6CrNiTi18 11 | |
| | 12 | 347 | 1.4550 | X6CrNiNb18 10 | 347S17 | Z6CNNb18.10 | X6CrNiNb18 11 | |
| | 12 | 316Ti | 1.4571 | X6CrNiMoTi17122 | 320S17 | Z6NDT1 7.12 | X6CrNiMoTi17 12 | |
| | 12 | - | 1.4581 | G-X5CrNiMoNb18 10 | 318C17 | Z4CNDNb18 12M | XG8CrNiMo18 11 | |
| | 12 | 318 | 1.4583 | X10CrNiMoNb18 12 | - | Z6CNDNb17 13B | X6CrNiMoNb17 13 | |
| | 13 | 309 | 1.4828 | X15CrNiSi20 12 | 309S24 | Z15CNS20.12 | - | |
| | 13 | 310S | 1.4845 | X12CrNi25 21 | 310S24 | Z12CN25 20 | X6CrNi25 20 | |
| | 13 | 330 | 1.4864 | X12NiCr36 16 | - | Z12NCS35.16 | - | |
| | 13 | - | 1.4865 | G-X40NiCrSi38 18 | 330C11 | - | XG50NiCr39 19 | |
| | 13 | EV8 | 1.4871 | X53CrMnNiN2 19 | 349S54;321S12 | Z52CMN21.09 | X53CrMnNiN219 | |
| | 13 | 321 | 1.4878 | X12CrNiTi18 9 | 321S320 | Z6CNT18.12B | X6CrNiTi1811 | |
| | K Cast Iron | 30 | No 20 B | 0.6010 | GG10 | - | Ft 10 D | - |
| | | 30 | No 25 B | 0.6015 | GG15 | Grade 150 | Ft 15 D | - |
| | | 30 | No 30 B | 0.6020 | GG20 | Grade 220 | Ft 20 D | - |
| | | 29 | No 35 B; No 40 B | 0.6025 | GG25 | Grade 260 | Ft 25 D | - |
| | | 29 | No 45 B | 0.6030 | GG30 | Grade 300 | R 30 D | - |
| | | 29 | No 50 B | 0.6035 | GG35 | Grade 350 | Ft 35 D | - |
| | | 29 | No 55 B | 0.6040 | GG40 | Grade 400 | Ft 40 D | - |
| 29 | | ASTM | - | DIN4694 | 3468: 1974 | - | - | |
| 29 | | A436-72 | - | GGL- | - | A32-301 | - | |
| 29 | | Type 2 | - | NiCr20 2 | L-NiCr 20 2 | L-NC 20 2 | - | |
| 30 | | 60-40-18 | 0.7040 | GGG 40 | SNG 420/12 | FCS 400-12 | GS 370-17 | |
| 30 | | - | 0.7043 | GGG 40.3 | SNG 370/17 | FGS 370-17 | - | |
| 30 | | - | 0.7033 | GGG 35.3 | - | - | - | |
| 31 | | 80-55-06 | 0.7050 | GGG 50 | SNG 500/7 | FGS 500-7 | GS 500 | |
| 31 | | - | 0.7060 | GGG 60 | SNG 600/3 | FGS 600-3 | - | |
| 31 | | 100-70-03 | 0.7070 | GGG70 | SNG 700/2 | FGS 700-2 | GS 700-2 | |
| 31 | | - | - | DIN 1694 | - | L-NM 13 7 | - | |
| 31 | | Type 2 | - | GGG NiMn 13 7 | L-NiMn 13 7 | L-NC 20 2 | - | |
| 31 | | - | - | GGG NiCr 20 2 | L-NC 20 2 | - | - | |
| 28 | | 32510 | 0.8135 | GTS-35 | B 340/12 | MN 35-10 | - | |
| 29 | | 40010 | 0.8145 | GTS-45 | P 440/7 | - | - | |
| 29 | | 50005 | 0.8155 | GTS-55 | P 510/4 | MP50-5 | - | |
| 29 | 70003 | 0.8165 | GTS-65 | P 570/3 | MP 60-3 | - | | |
| 29 | 80002 | 0.8170 | GTS-70 | P690/2 | MP 70-2 | - | | |
| N Non-Ferrous Metals | 36 | - | - | G-AISI12 | LM20 | - | - | |
| | 36 | - | - | GD-AISI12 | - | - | - | |
| | 36 | - | - | GD-AISI8Cu3 | LM24 | - | - | |
| | 36 | - | - | G-AISI10Mg | LM9 | - | - | |
| | 36 | - | - | G-AISI12 | LM6 | - | - | |
| S Heat Resistant Material | 19 | 330 | 1.4864 | X12NiCrSi | - | Z12NCS35.16 | - | |
| | 19 | - | 1.4865 | G-X40NiCrSi | 330C11 | - | XG50NiCr | |
| | 19 | 5390 A | 2.4603 | - | - | NC22FeD | - | |
| | 19 | - | 2.4630 | NiCr20Ti | HR5, 203-4 | NC20T | - | |
| | 19 | 5666 | 2.4856 | NiCr22Mo9N | - | NC22FeDNB | - | |
| | 19 | 5537 C | LW2.496 | CoCr20W15 | - | KC20WN | - | |
| | 19 | 4676 | 2.4375 | NiCu30Al | 3072-76 | - | - | |
| | 19 | - | 2.4631 | NiCr20TiAk | HR40,601 | NC20TA | - | |
| | 19 | AMS 5399 | 2.4973 | NiCr19Co11 | - | NC19KDT | - | |
| | 21 | 5391 | LW2.467 | S-NiCr13Al6 | 3146-3 | NC12AD | - | |
| | 21 | 5660 | LW2.466 | NiCr19Fe19 | HR8 | NC19FeNb | - | |
| | 21 | 5383 | LW2.466 | NiCr19Fe19 | - | NC20K14 | - | |
| | 21 | - | - | CoCr22W14 | - | KC22WN | - | |
| | 21 | - | LW2.467 | NiCo15Cr10 | - | - | - | |
| | 23 | - | - | TiAl14Mo4Sn4Si0.5 | - | - | - | |
| | 23 | - | - | TiAl5Sn2.5 | TA14/17 | T-A5E | - | |
| | 23 | - | - | TiAl6V4 | TA10-13/TA2 | T-A6V | - | |
| 23 | - | - | TiAl6V4ELI | TA11 | - | - | | |

Thread Turning
Technical Data

| Sweden SS | Japan JIS | Russia GOST | Spain UNE | Vargus No. | | |
|--------------|-------------------|---|--|---------------|----------|----------|
| 2301 | SUS403 | 08Ch13 | F.3110-X6Cr13 ; F.8401-AM-X12Cr13 | 12 | M | |
| - | - | 08Ch13 | F.3110-X6Cr13 ; F.8401-AM-X12Cr13 | 12 | | |
| 2302 | SUS410 | 12Ch13 ; 15Ch13L | F.3401-X10Cr13 | 12 | | |
| 2320 | SUS430 | 12Ch17 | F.3113-X6Cr17 | 12 | | |
| - | SCS2 | 20Ch13L | - | 12 | | |
| 2304 | SUS420J2 | 40Ch13 | F.3405-X45Cr13 | 12 | | |
| 2321 | SUS431 | 20Ch17N2 | F.3427-X19CrNi172 | 12 | | |
| 2383 | SUS430F | - | F.3117-X10CrSi17 ; F.3413-X14CrMoSi7 | 12 | | |
| 2325 | SUS434 | - | F.3116-X6CrMo171 | 12 | | |
| - | SCS5 | - | - | 12 | | |
| - | SCS14 | 07Ch18N10G2S2M2L | F.8414-AM-X7CrNiMo2010 | 12 | | |
| - | SUH1 | 40Ch9S2 | F.3220-X45CrSi09-03 | 12 | | |
| - | SUS405 | 10Ch13SJu | F.3152-X10CrAl13 | 12 | | |
| - | SUH21 | 15Ch18SJu | F.3153-X10CrAl18 | 11 | | |
| - | SUH4 | - | F.3222-X80CrSiNi20-02 | 12 | | |
| 2322 | SUH446 | - | F.3154-X10CrAl24 | 11 | | |
| 2332 | SUS304 | 08Ch18N10 | F.3551-X5CrNi1811; F.3541-X5CrNi1810 ; F.3504-X6CrNi1910 | 13 | | |
| 2346 | SUS303 | - | F.3508-X10CrNiSi18-09 | 13 | | |
| 2352 | SCS19; SUS304L | 03Ch18N11 | F.3503-X2CrNi1810 | 13 | | |
| 2333 | SCS13 | 07Ch18N9L | - | 13 | | |
| 2331 | SUS301 | - | F.3517-X12CrNi177 | 13 | | |
| 2371 | SUS304LN | - | F.3541-X2CrNi1810 | 13 | | |
| 2347 | SUS316 | - | F.3534-X5CrNiMo17122 | 13 | | |
| 2375 | SUS316LN | - | F.3543-X2CrNiMoN17133 | 13 | | |
| 2353 | SCS16 | 03Ch17N14M3 | F.3533-X2CrNiMo17132 | 13 | | |
| 2367 | SUS317L | - | F.3539-X2CrNiMo18164 | 13 | | |
| 2324 | SUS329L; | - | F.3309-X8CrNiMo27-05; F.3552-X8CrNiMo266 | 13 | | |
| 58B | SUS321 | 06Ch18N10T; 08Ch18N10T; 09Ch18N10T; 12Ch18N10T | F.3523-X6CrNiTi1810 | 12 | | |
| 2338 | SUS347 | 08Ch18N12B | F.3524-X6CrNiNb1810 | 12 | | |
| 2350 | - | 10Ch17N13M2T | F.3535-X6CrNiMoTi17122 | 12 | | |
| - | SCS22 | - | - | 12 | | |
| - | - | - | - | 12 | | |
| - | SUH309 | 20Ch20N14S2 | F.3312-X15CrNiSi20-12 | 13 | | |
| 2361 | SUH310 | 20Ch23N18 | - | 13 | | |
| - | SUH330 | - | F.3313-X12CrNiSi36-16 | 13 | | |
| - | SCH15 | - | - | 13 | | |
| - | SUH35;SUH36;SU321 | 55Ch20G9AN4 | F.3217-X53CrMnNiN21-09 | 13 | | |
| - | - | - | - | 13 | | |
| 01 10 | - | C410 | FG10 | 30 | | K |
| 01 15 | - | C415 | FG15 | 30 | | |
| 01 20 | - | C420 | FG20 | 30 | | |
| 01 25 | - | C425 | FG25 | 29 | | |
| 01 30 | - | C430 | FG30 | 29 | | |
| 01 35 | - | C435 | FG35 | 29 | | |
| 01 40 | - | C440 | - | 29 | | |
| MB | - | - | - | 29 | | |
| ISO-215 | - | - | - | 29 | | |
| 523 | - | - | - | 29 | | |
| 07 17-02 | - | VC42-12 | - | 30 | | |
| 07 17-12 | - | VC42-12 | - | 30 | | |
| 07 17-15 | - | - | - | 30 | | |
| 07 27-02 | - | VC50-2 | - | 31 | | |
| 07 32-03 | - | VC60-2 | - | 31 | | |
| 07 37-01 | - | VC70-2 | - | 31 | | |
| 07 72 | - | - | - | 31 | | |
| 07 76 | - | - | - | 31 | | |
| - | - | - | - | 31 | | |
| 08 15 | - | - | - | 28 | | |
| 08 52 | - | - | - | 29 | | |
| 08 54 | - | - | - | 29 | | |
| 08 58 | - | - | - | 29 | | |
| 08 62 | - | - | - | 29 | | |
| 4260 | - | - | - | 36 | N | |
| 4247 | - | - | - | 36 | | |
| 4250 | - | - | - | 36 | | |
| 4253 | - | - | - | 36 | | |
| 4261 | - | - | - | 36 | | |
| - | SUH 330 | - | F.3313-X12CrNiSi36-16 | 19 | | S |
| - | SCH 15 | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 19 | | |
| - | - | - | - | 21 | | |
| - | - | - | - | 21 | | |
| - | - | - | - | 21 | | |
| - | - | - | - | 21 | | |
| - | - | - | - | 23 | | |
| - | - | - | - | 23 | | |
| - | - | - | - | 23 | | |
| - | - | - | - | 23 | | |

Troubleshooting

| Problem | Possible Cause | Solution |
|---|--|--|
|  <p>Increased flank wear</p> | Cutting speed too high -----> Depth of cut too low/ too many passes -----> Unsuitable carbide grade -----> Insufficient cooling -----> | Reduce cutting speed / use coated insert Increase the depth of cut per pass Use a coated carbide grade Increase coolant flow rate |
|  <p>Uneven cutting edge wear</p> | Incorrect helix angle -----> Wrong infeed method -----> | Choose the correct anvil Use the alternating flank infeed method |
|  <p>Extreme plastic deformation</p> | Depth of cut too large -----> Insufficient cooling -----> Cutting speed too high -----> Unsuitable carbide grade -----> Nose radius too small -----> | Decrease depth of cut/ increase number of passes Increase coolant flow rate Reduce cutting speed Use a tougher carbide Use an insert with a larger radius, if possible |
|  <p>Cutting edge breakage</p> | Depth of cut too large -----> Extreme plastic deformation -----> Insufficient cooling -----> Unsuitable carbide grade -----> Instability -----> | Decrease depth of cut/ increase number of passes Use a tougher carbide Increase flow rate and/ or correct flow direction Use a tougher carbide Check stability of the system |
|  <p>Built-up edge</p> | Incorrect cutting speed -----> Unsuitable carbide grade -----> | Change the cutting speed Use a coated carbide |
|  <p>Thread profile is too shallow</p> | The tool is not at the workpiece axis height ---> Insert is not machining the thread crest -----> Worn insert -----> | Change tool height Measure the workpiece diameter Change the cutting edge sooner |
|  <p>Poor surface quality</p> | Cutting speed too low -----> Wrong anvil -----> Flank infeed method is not appropriate -----> | Increase cutting speed Choose correct anvil Use the alternate flank or radial infeed method |

VRX

Multipurpose Premium Grade

Multipurpose Thread Turning Grade for Stronger
Wear Resistance and Improved Productivity


Redefining the **Threading** Benchmark




AlTiN Alloyed PVD Coating

High Oxidation Temperature

Submicron Substrate



See page 202 for more information.



THREAD MILLING

| | |
|------------------------|-----|
| ■ MiTM | 229 |
| ■ TM Standard | 251 |
| ■ TMSD | 293 |
| ■ TM Solid | 329 |
| ■ Technical Data | 367 |

Thread Milling Systems

MiTM Multi-Flute Indexable Thread Mill Inserts

MiTM19 (A) For Small Bores



Standard



Conical

MiTM24 (M) For Medium Bores



Standard



Conical

MiTM25 (S) For Standard Applications



Standard



Conical



Shell Mill



Shell Mill Conical

MiTM40 (L) For Long Threads



Standard



Shell Mill



Shell Mill Conical

MiTM41 (B) For Large Pitches



Standard



Shell Mill

Standard

Standard / TMF



Mini TMMC



Standard TMC



Coarse 124/...



TMLC



TM2C



TMOc



TM Shell Mill

Coarse Pitch



Coarse 124/...
(Standard TMC Style)



Coarse 124/...
(Mini TMMC Style)

Conical



TMNC

TMSC - Single Point



TMSC

TMVC - Single Point Vertical



TMVC

Thread Milling Systems

TMSD Thread Milling for Deep Holes

U Style For Large Pitches



L Style (Mini L) For Small Bores and Short L2



Vertical Style (7V, 9V, 11V)



L Style (3/8" L) For Large Trapezoid Profiles and ABUT




A Style For Shorter L2



TM Solid Solid Carbide Thread Milling Tools

Helical Flutes with Coolant



Helical Flutes



Miniature Tools



Straight Flutes




Long Tools




Thread Milling Methods

(for RH Tools only)


External




Right Hand Thread - Conventional Milling



Left Hand Thread - Conventional Milling




Right Hand Thread - Climb Milling




Left Hand Thread - Climb Milling


Internal




Right Hand Thread - Conventional Milling



Left Hand Thread - Conventional Milling




Right Hand Thread - Climb Milling



Left Hand Thread - Climb Milling

The Thread Milling Advantages

- Enables machining of large work pieces which cannot be easily mounted on a lathe
- Easily machine non-rotatable and asymmetrical parts
- Complete operation in one clamping
- Threading of large diameters requires less power than threading using taps
- No upper limits to bore diameter
- Chips are short
- Blind holes without a thread relief groove can be machined
- Thread relief grooves are unnecessary
- One holder can be used for both internal and external threads
- One tool can be used for both right hand and left hand thread
- Inventory can be reduced to a minimum as small range of tooling covers a wide range of thread diameters
- Interchangeable inserts
- Suitable for machining of hard materials
- Threads have a high surface finish
- Allows for correction of tool diameter and length
- Interrupted cuts are easily machined
- One tool for a wide range of materials
- A better thread quality in soft materials where taps normally tear the material
- Short machining time due to high cutting speed and rapid feed rates
- Small cutting forces allow machining of parts with thin walls





MiTM

Super Fast Thread Milling System

Inserts | Toolholders

Vardex Ordering Code System

MiTM Inserts

| | | | | | | | |
|--|---|---|----------------|--|--|-------------------------|--|
| R 1 | 25 2 | I 3 | 12 4 | UN 5 | TM 6 | VBX 7 | |
| 1 - Product Line R - MiTM line | 2 - Insert Style 19, 24, 25, 40, 41 | 3 - Type of Insert I - Internal E - External EI-External+Internal NC- Plug | | 4 - Pitch 0.5-6.0 mm 32-4 TPI | 5 - Standard ISO- ISO Metric UN-American UN W- BSW, BSP NPT-NPT NPTF-NPTF BSPT-BSPT | 6 - System TM | 7 - Carbide Grade VBX VTX |

MiTM Holders (Standard and Conical)

| | | | | | | | | |
|--|---|--|---------------------------------------|-------------------------------------|----------|-----------------|---------------|---------------|
| R 1 | TM 2 | C 3 | 100 4 | 067 5 | - | 110 6 | S 7 | 2 8 |
| 1 - Product Line R - MiTM line BR - MiTM with Anti-vibration System | 2 - Holder Type TM - Standard Holder TMN - Conical Holder | 3 - Cooling C- Coolant Channel | 4 - Shank Dia. .75, 1, 1.25 | 5 - Cutting Dia. .54-1.42 | | | | |
| 6 - Tool Overhang 1.02-3.15 | 7 - Insert Style A - 19 M - 24 S - 25 L - 40 B - 41 | 8 - No. of Flutes 1 - 5 | | | | | | |

MiTM Shell Mill

| | | | | | | | | | |
|--|--|--|--------------------------------------|--|----------|-----------------|----------|-----------------|---------------|
| R 1 | TM 2 | C 3 | - | D150 4 | - | 050 5 | - | 25S 6 | 5 7 |
| 1 - Product Line R - MiTM line | 2 - Holder Type TM - Standard Holder TMN - Conical Holder | 3 - Cooling C- Coolant Channel | 4 - Cutting Dia. 1.54-2.48 | 5 - Drive Hole Dia. .50, .75, 1.00 | | | | | |
| 6 - Insert Style 25S 40L 41B | 7 - No. of Flutes 5 - 8 | | | | | | | | |

MiTM

The VARDEX Multi-flute Indexable Thread Milling (MiTM) system for fast machining, reduces cycle times when machining threads with long inserts. Nickel coating for all MiTM toolholders provides better anti-rust protection.

MiTM 19 (A) For Small Bores



Standard
No. of Flutes (Z) 1
Cutting Dia. (D2) .39-.46
Tool Overhang (L1) .79-.99



Conical
No. of Flutes (Z) 1
Cutting Dia. (D2) .42
Tool Overhang (L1) .71

MiTM 24 (M) For Medium Bores



Standard
No. of Flutes (Z) 1-2
Cutting Dia. (D2) .53-.63
Tool Overhang (L1) 1.02-1.42



Conical
No. of Flutes (Z) 1
Cutting Dia. (D2) .55
Tool Overhang (L1) 1.02

MiTM 25 (S) For Standard Applications



Standard
No. of Flutes (Z) 2-5
Cutting Dia. (D2) .67-1.18
Tool Overhang (L1) 1.10-3.15



Conical
No. of Flutes (Z) 2-4
Cutting Dia. (D2) .68-1.12
Tool Overhang (L1) 1.10-1.70

MiTM 40 (L) For Long Threads



Standard
No. of Flutes (Z) 3-4
Cutting Dia. (D2) .87-1.18
Tool Overhang (L1) 1.69-3.15

MiTM 41 (B) For Large Pitches



Standard
No. of Flutes (Z) 1-5
Cutting Dia. (D2) .84-1.42
Tool Overhang (L1) 1.69-2.56



Shell Mill
No. of Flutes (Z) 5-9
Cutting Dia. (D2) 1.54-2.32
Tool Overhang (L1) max. 7.87



Shell Mill Conical
No. of Flutes (Z) 5
Cutting Dia. (D2) 1.53
Tool Overhang (L1) max. 7.87



Shell Mill
No. of Flutes (Z) 7-9
Cutting Dia. (D2) 1.93-2.32
Tool Overhang (L1) max. 7.87



Shell Mill Conical
No. of Flutes (Z) 7
Cutting Dia. (D2) 1.93
Tool Overhang (L1) max. 7.87




Shell Mill
No. of Flutes (Z) 5-6
Cutting Dia. (D2) 2.09-2.48
Tool Overhang (L1) max. 7.87




ISO Metric

External / Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Standard MiTM

| Insert Style | Pitch | Ordering Code | EDP No. | Ordering Code | EDP No. | Cutting Edge | Teeth | Toolholder | | |
|--------------|-------|-------------------|---------|------------------|-------------------|--------------|-------|------------|------|----|
| L | mm | External | | Internal | VTX | VBX | Le | Zt | | |
| 19 | 0.5 | | | R19I0.50ISOTM... | 81001 | 81000 | 1 | .79 | 40 | |
| | 0.75 | | | R19I0.75ISOTM... | 81003 | 81002 | 1 | .79 | 27 | |
| | 1.0 | | | R19I1.00ISOTM... | 81005 | 81004 | 1 | .79 | 20 | |
| | 1.25 | | | R19I1.25ISOTM... | 81007 | 81006 | 1 | .79 | 16 | |
| | 1.5 | | | R19I1.50ISOTM... | 81009 | 81008 | 1 | .77 | 13 | |
| | 1.75 | | | R19I1.75ISOTM... | 81011 | 81010 | 1 | .76 | 11 | |
| 24 | 2.0 | | | R19I2.00ISOTM... | 81013 | 81012 | 1 | .79 | 10 | |
| | 0.5 | | | R24I0.50ISOTM... | 80753 | 80754 | 1 | .96 | 49 | |
| | 0.75 | | | R24I0.75ISOTM... | 80755 | 80751 | 1 | .97 | 33 | |
| | 1.0 | | | R24I1.00ISOTM... | 80756 | 80757 | 1 | .94 | 24 | |
| | 1.25 | | | R24I1.25ISOTM... | 80758 | 80759 | 1 | .98 | 20 | |
| | 1.5 | | | R24I1.50ISOTM... | 80760 | 80761 | 1 | .94 | 16 | |
| 25 | 1.75 | | | R24I1.75ISOTM... | 80762 | 80763 | 1 | .96 | 14 | |
| | 2.0 | | | R24I2.00ISOTM... | 80764 | 80765 | 1 | .94 | 12 | |
| | 2.5 | | | R24I2.50ISOTM... | 80766 | 80767 | 1 | .98 | 10 | |
| | 1.0 | R25E1.00ISOTM... | 80584 | 80585 | R25I1.00ISOTM... | 80482 | 80483 | 2 | .94 | 24 |
| | 1.25 | R25E1.25ISOTM... | 81046 | 81047 | R25I1.25ISOTM... | 81048 | 81049 | 2 | .93 | 19 |
| | 1.5 | R25E1.50ISOTM... | 80586 | 80587 | R25I1.50ISOTM... | 80484 | 80485 | 2 | .94 | 16 |
| 40 | 2.0 | R25E2.00ISOTM... | 80588 | 80589 | R25I2.00ISOTM... | 80486 | 80487 | 2 | .94 | 12 |
| | 2.5 | R25E2.50ISOTM... | 80590 | 80591 | R25I2.50ISOTM... | 80488 | 80489 | 2 | .98 | 10 |
| | 3.0 | *R25E3.00ISOTM... | 80592 | 80593 | *R25I3.00ISOTM... | 80490 | 80491 | 2 | .94 | 8 |
| 41 | 1.0 | | | R40I1.00ISOTM... | 80702 | 80703 | 2 | 1.54 | 39 | |
| | 1.5 | | | R40I1.50ISOTM... | 80704 | 80705 | 2 | 1.54 | 26 | |
| | 2.0 | | | R40I2.00ISOTM... | 80706 | 80707 | 2 | 1.50 | 19 | |
| | 2.5 | | | R40I2.50ISOTM... | 80708 | 80709 | 2 | 1.48 | 15 | |
| | 3.0 | | | R40I3.00ISOTM... | 80710 | 80711 | 2 | 1.54 | 13 | |
| | 3.0 | R41E3.00ISOTM... | 80768 | 80769 | R41I3.00ISOTM... | 80782 | 80783 | 2 | 1.54 | 13 |
| 41 | 3.5 | R41E3.50ISOTM... | 80770 | 80771 | R41I3.50ISOTM... | 80784 | 80785 | 2 | 1.52 | 11 |
| | 4.0 | R41E4.00ISOTM... | 80772 | 80773 | R41I4.00ISOTM... | 80786 | 80787 | 2 | 1.57 | 10 |
| | 4.5 | R41E4.50ISOTM... | 80774 | 80775 | R41I4.50ISOTM... | 80788 | 80789 | 2 | 1.59 | 9 |
| | 5.0 | R41E5.00ISOTM... | 80776 | 80777 | R41I5.00ISOTM... | 80790 | 80791 | 2 | 1.57 | 8 |
| | 5.5 | R41E5.50ISOTM... | 80778 | 80779 | R41I5.50ISOTM... | 80792 | 80793 | 2 | 1.52 | 7 |
| | 6.0 | R41E6.00ISOTM... | 80780 | 80781 | R41I6.00ISOTM... | 80794 | 80795 | 2 | 1.42 | 6 |


* 3.0 ISO inserts do not fit into toolholder RTMC100067...
For external insert 3.0 ISO use for CNC program (D2 + .02").

MiTM inserts 25, 40 and 41 are offered with 2 cutting edges. In case of chip flow difficulty, inserts with a single cutting edge can be ordered by request. Example: R25I2.00ISOTM(S)...




American UN - UNC, UNF, UNEF, UNS


External / Internal




Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



MiTM 19



MiTM 24



MiTM 25

Standard MiTM



| Insert Style | Pitch | Ordering Code | EDP No. | | Ordering Code | EDP No. | | Cutting Edge | Teeth | Toolholder | |
|--------------|-------|---------------|---------|-------|---------------|---------|-------|--------------|-------|------------|-------------|
| | | | VTX | VBX | | VTX | VBX | | | | |
| L | TPI | External | VTX | VBX | Internal | VTX | VBX | Le | Zt | | |
| 19 | 32 | | | | R19I32UNTM... | 81015 | 81014 | 1 | .78 | 25 | RTMC...A |
| | 28 | | | | R19I28UNTM... | 81017 | 81016 | 1 | .79 | 22 | |
| | 27 | | | | R19I27UNTM... | 81019 | 81018 | 1 | .78 | 21 | |
| | 24 | | | | R19I24UNTM... | 81021 | 81020 | 1 | .79 | 19 | |
| | 20 | | | | R19I20UNTM... | 81023 | 81022 | 1 | .75 | 15 | |
| | 18 | | | | R19I18UNTM... | 81025 | 81024 | 1 | .78 | 14 | |
| | 16 | | | | R19I16UNTM... | 81027 | 81026 | 1 | .75 | 12 | |
| | 14 | | | | R19I14UNTM... | 81029 | 81028 | 1 | .79 | 11 | |
| | 13 | | | | R19I13UNTM... | 81031 | 81030 | 1 | .77 | 10 | |
| 24 | 32 | | | | R24I32UNTM... | 80796 | 80797 | 1 | .97 | 31 | RTMC...M |
| | 28 | | | | R24I28UNTM... | 80798 | 80799 | 1 | .96 | 27 | |
| | 24 | | | | R24I24UNTM... | 80802 | 80803 | 1 | .96 | 23 | |
| | 20 | | | | R24I20UNTM... | 80804 | 80805 | 1 | .95 | 19 | |
| | 18 | | | | R24I18UNTM... | 80806 | 80807 | 1 | .94 | 17 | |
| | 16 | | | | R24I16UNTM... | 80808 | 80809 | 1 | .94 | 15 | |
| | 14 | | | | R24I14UNTM... | 80810 | 80811 | 1 | .93 | 13 | |
| | 12 | | | | R24I12UNTM... | 80812 | 80813 | 1 | .92 | 11 | |
| | 10 | | | | R24I10UNTM... | 80814 | 80815 | 1 | .90 | 9 | |
| 25 | 20 | R25E20UNTM... | 80594 | 80595 | R25I20UNTM... | 80492 | 80493 | 2 | .95 | 19 | (B)RTMC...S |
| | 18 | R25E18UNTM... | 80596 | 80597 | R25I18UNTM... | 80494 | 80495 | 2 | .94 | 17 | |
| | 16 | R25E16UNTM... | 80598 | 80599 | R25I16UNTM... | 80496 | 80497 | 2 | .94 | 15 | |
| | 14 | R25E14UNTM... | 80600 | 80601 | R25I14UNTM... | 80498 | 80499 | 2 | .93 | 13 | |
| | 12 | R25E12UNTM... | 80602 | 80603 | R25I12UNTM... | 80500 | 80501 | 2 | .92 | 11 | |
| | 10 | R25E10UNTM... | 80604 | 80605 | R25I10UNTM... | 80502 | 80503 | 2 | .90 | 9 | |
| | 9 | *R25E9UNTM... | 80606 | 80607 | *R25I9UNTM... | 80504 | 80505 | 2 | .89 | 8 | |
| | 8 | *R25E8UNTM... | 80608 | 80609 | *R25I8UNTM... | 80506 | 80507 | 2 | .87 | 7 | |


* Note: 8 UN & 9 UN inserts do not fit into toolholder RTMC100067...
For external insert 8 UN use for CNC program (D2 + .02").

MiTM inserts 25, 40 and 41 are offered with 2 cutting edges. In case of chip flow difficulty, inserts with a single cutting edge can be ordered by request. Example: R25I20UNTM(S)...





American UN - UNC, UNF, UNEF, UNS (con't)

External / Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



MITM

Standard MiTM



| Insert Style | Pitch | Ordering Code | EDP No. | | Ordering Code | EDP No. | | Cutting Edge | Teeth | Toolholder |
|--------------|-------|----------------|---------|-------|----------------|---------|-------|--------------|-------|------------|
| L | TPI | External | VTX | VBX | Internal | VTX | VBX | Le | Zt | |
| 40 | 20 | | | | R40I20UNTM... | 80712 | 80713 | 2 | 1.55 | 31 |
| | 18 | | | | R40I18UNTM... | 80714 | 80715 | 2 | 1.56 | 28 |
| | 16 | | | | R40I16UNTM... | 80716 | 80717 | 2 | 1.56 | 25 |
| | 14 | | | | R40I14UNTM... | 80718 | 80719 | 2 | 1.57 | 22 |
| | 12 | | | | R40I12UNTM... | 80720 | 80721 | 2 | 1.50 | 18 |
| | 10 | | | | R40I10UNTM... | 80722 | 80723 | 2 | 1.50 | 15 |
| | 9 | | | | R40I9UNTM... | 80724 | 80725 | 2 | 1.56 | 14 |
| 41 | 8 | | | | R40I8UNTM... | 80726 | 80727 | 2 | 1.50 | 12 |
| | 8 | R41E8UNTM... | 80816 | 80817 | R41I8UNTM... | 80828 | 80829 | 2 | 1.50 | 12 |
| | 7 | R41E7UNTM... | 80818 | 80819 | R41I7UNTM... | 80830 | 80831 | 2 | 1.57 | 11 |
| | 6 | R41E6UNTM... | 80820 | 80821 | R41I6UNTM... | 80832 | 80833 | 2 | 1.50 | 9 |
| | 5 | R41E5UNTM... | 80822 | 80823 | R41I5UNTM... | 80834 | 80835 | 2 | 1.40 | 7 |
| | 4.5 | R41E4.5UNTM... | 80824 | 80825 | R41I4.5UNTM... | 80836 | 80837 | 2 | 1.56 | 7 |
| | 4 | R41E4UNTM... | 80826 | 80827 | R41I4UNTM... | 80838 | 80839 | 2 | 1.50 | 6 |

(B)RTMC...L
RTMC...B

MiTM inserts 25, 40 and 41 are offered with 2 cutting edges. In case of chip flow difficulty, inserts with a single cutting edge can be ordered by request. Example: R25I20UNTM(S)...



Whitworth for BSF, BSP (G)

External / Internal

Defined by: B.S.84:1956, DIN 259, DIN ISO228/1:1982
Tolerance class: Medium Class A

Standard MiTM

| Insert Style | Pitch | Ordering Code | | EDP No. | | Ordering Code | | EDP No. | | Cutting Edge | Teeth | Toolholder |
|--------------|-------|-------------------|-------|---------|-------------|---------------|-------|---------|------|--------------|-------------|------------|
| | | External+Internal | VTX | VBX | Internal | VTX | VBX | Le | Zt | | | |
| 19 | 19 | R19EI19WTM... | 81035 | 81034 | | | | 1 | .79 | 15 | RTMC...A | |
| | 16 | R19EI16WTM... | 81037 | 81036 | | | | 1 | .75 | 12 | | |
| | 14 | R19EI14WTM... | 81039 | 81038 | | | | 1 | .79 | 11 | | |
| 24 | 19 | R24EI19WTM... | 80844 | 80845 | | | | 1 | .95 | 18 | RTMC...M | |
| | 14 | R24EI14WTM... | 80846 | 80847 | | | | 1 | .93 | 13 | | |
| | 12 | R24EI12WTM... | 80848 | 80849 | | | | 1 | .92 | 11 | | |
| 25 | 16 | R25EI16WTM... | 80508 | 80509 | | | | 2 | .94 | 15 | (B)RTMC...S | |
| | 14 | R25EI14WTM... | 80510 | 80511 | | | | 2 | .93 | 13 | | |
| | 12 | R25EI12WTM... | 80512 | 80513 | | | | 2 | .92 | 11 | | |
| 40 | 16 | R40EI16WTM... | 80610 | 80611 | | | | 2 | 1.56 | 25 | (B)RTMC...L | |
| | 14 | R40EI14WTM... | 80612 | 80613 | | | | 2 | 1.57 | 22 | | |
| | 12 | R40EI12WTM... | 80614 | 80615 | | | | 2 | 1.50 | 18 | | |
| 41 | 8 | | | | R41I8WTM... | 80850 | 80851 | 2 | 1.50 | 12 | RTMC...B | |
| | 7 | | | | R41I7WTM... | 80852 | 80853 | 2 | 1.57 | 11 | | |
| | 6 | | | | R41I6WTM... | 80854 | 80855 | 2 | 1.50 | 9 | | |

MiTM inserts 25, 40 and 41 are offered with 2 cutting edges. In case of chip flow difficulty, inserts with a single cutting edge can be ordered by request. Example: R25EI16WTM(S)...



NPT

External / Internal

Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

Standard MiTM

| Insert Style | Pitch | Ordering Code | EDP No. | | Cutting Edge | Teeth | Toolholder | |
|--------------|-------|--------------------|---------|-------|--------------|-------|------------|---------------------|
| | | | VTX | VBX | | | | |
| L | TPI | External+Internal | VTX | VBX | Le | Zt | | |
| 19 | 18 | R19EI18NPT-TM... | 81041 | 81040 | 1 | .78 | 14 | RTMNC...A |
| 24 | 18 | R24EI18NPT-TM... | 80873 | 80874 | 1 | .94 | 17 | RTMNC...M |
| 25 | 14 | R25EI14NPT-TM... | 80516 | 80517 | 1 | .93 | 13 | RTMNC...S |
| | 11.5 | R25EI11.5NPT-TM... | 80518 | 80519 | 1 | .96 | 11 | |
| 40 | 8 | R25EI8NPT-TM... | 80580 | 80581 | 1 | .87 | 7 | RTMNC-D150-050-25S5 |
| | 11.5 | R40EI11.5NPT-TM... | 80743 | 80744 | 1 | 1.48 | 17 | RTMNC-D190-075-40L7 |
| 41 | 8 | R40EI8NPT-TM... | 80728 | 80729 | 1 | 1.50 | 12 | |
| | 8 | R41EI8NPT-TM... | 80840 | 80841 | 1 | 1.50 | 12 | RTMC...B |

NPTF

External / Internal


Defined by: ANSI B1.20.3-1976
Tolerance class: Standard NPTF

Standard MiTM


| Insert Style | Pitch | Ordering Code | EDP No. | | Cutting Edge | Teeth | Toolholder | |
|--------------|-------|--------------------|---------|-------|--------------|-------|------------|---------------------|
| | | | VTX | VBX | | | | |
| L | TPI | External+Internal | VTX | VBX | Le | Zt | | |
| 19 | 18 | R19EI18NPTFTM... | 81043 | 81042 | 1 | .78 | 14 | RTMNC...A |
| 24 | 18 | R24EI18NPTFTM... | 80875 | 80876 | 1 | .94 | 17 | RTMNC...M |
| 25 | 14 | R25EI14NPTFTM... | 80520 | 80521 | 1 | .93 | 13 | RTMNC...S |
| | 11.5 | R25EI11.5NPTFTM... | 80522 | 80523 | 1 | .96 | 11 | |
| 40 | 8 | R25EI8NPTFTM... | 80582 | 80583 | 1 | .87 | 7 | RTMNC-D150-050-25S5 |
| | 11.5 | R40EI11.5NPTFTM... | 80745 | 80746 | 1 | 1.48 | 17 | RTMNC-D190-075-40L7 |
| 41 | 8 | R40EI8NPTFTM... | 80730 | 80731 | 1 | 1.50 | 12 | |
| | 8 | R41EI8NPTFTM... | 80842 | 80843 | 1 | 1.50 | 12 | RTMC...B |

BSPT


External / Internal




Defined by: B.S. 21:1985
Tolerance class: Standard BSPT




MiTM 19



MiTM 24



MiTM 25



MiTM 40

Standard MiTM



| Insert Style | Pitch | Ordering Code | EDP No. | | Cutting Edge | Teeth | | Toolholder |
|--------------|-------|-------------------|---------|-------|--------------|-------|----|---------------------|
| L | TPI | External+Internal | VTX | VBX | | Le | Zt | |
| 19 | 19 | R19EI19BSPT-TM... | 81045 | 81044 | 1 | .79 | 15 | RTMNC...A |
| 24 | 19 | R24EI19BSPT-TM... | 80871 | 80872 | 1 | .95 | 18 | RTMNC 075055-102M1 |
| 25 | 14 | R25EI14BSPT-TM... | 80524 | 80525 | 1 | .93 | 13 | RTMNC...S |
| | 11 | R25EI11BSPT-TM... | 80526 | 80527 | 1 | .91 | 10 | |
| 40 | 11 | R40EI11BSPT-TM... | 80732 | 80733 | 1 | 1.55 | 17 | RTMNC-D190-075-40L7 |

Plug Insert




| Insert Style | Ordering Code | EDP No. | Teeth | Toolholder |
|--------------|-------------------|---------|----------|--------------------------|
| L | External+Internal | | Zt | |
| 24 | R24NC | 80858 | | RTMC...M |
| 25 | R25NC | 80532 | No Teeth | (B)RTMC...S RTMNC...S |
| 40 | R40NC | 80626 | | (B)RTMC...L RTMNC...L |
| 41 | R41NC | 80859 | | RTMC...B |

Fill unused toolholder pockets with plug inserts (R..NC).
This assures balance and prevents instability and chips from packing into empty pockets.

MITM

Standard Toolholders (MiTM 19)





Coolant-Thru is recommended, especially when $D2 > 0.7 \times$ nominal thread diameter

RTMC - for Standard Threads


| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | |
|--------------|------------------|---------|-----------------|-----|-----|-----|-----|---------------|--------------------------|--|
| | | | L | L1 | D | D1 | D2 | | Z |  |
| 19 | RTMC050039-079A1 | 80643 | 2.69 | .79 | .50 | .30 | .39 | 1 | Location Screw x2 | Torx+ Screwdriver |
| | RTMC050046-098A1 | 80646 | 2.91 | .99 | .50 | .34 | .46 | 1 | SLD3IP6 (M3x0.5) (80654) | KIP6 <ul style="list-style-type: none"> • Use the included Vardex Torx+ screwdriver only. • Recommended max. torque 1.2 NxM (80656) |

Standard Thread Application by Toolholder


| Toolholder | Min. Thread Dia. | | | | | | |
|------------------|------------------|------------------|---|---------|--|---------|--------|
| | D2 (Inch) | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | BSF | BSP(G) |
| RTMC050039-079A1 | .39 | M12x1.75 | M11x0.5; M11x0.75; M11.5x1; M12x1.25; M12x1.5 | 1/2-13 | 7/16-32UN; 7/16-28UNEF; 7/16-27UNS; 1/2-24UNS; 1/2-20UNF; 1/2-18UNS; 1/2-16UN; 1/2-14UNS | 1/2-16 | 1/4-19 |
| RTMC050046-098A1 | .46 | M14x2.0; M16x2.0 | M12.5x0.5; M13x0.75; M13x1; M13.5x1.25; M14x1.5; M14x1.75 | 5/16-12 | 1/2-32UN; 5/16-28UNS; 5/16-27UNS; 5/16-24UNEF; 5/16-20UN; 5/16-18UNF; 5/16-16UN; 5/16-14UNS; | 5/16-14 | 1/4-14 |



2 Step Clamping System



Conical Toolholders (MiTM 19)






RTMNC - for Conical Threads

| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | |
|--------------|-------------------|---------|-----------------|-----|-----|-----|-----|---------------|--------------------------|--|
| | | | L | L1 | D | D1 | D2 | | Z | Location Screw x2 |
| 19 | RTMNC050039-074A1 | 80653 | 2.63 | .71 | .50 | .32 | .42 | 1 | SLD3IP6 (M3x0.5) (80654) | <ul style="list-style-type: none"> • Use the included Vardex Torx+ screwdriver only. • Recommended max. torque 1.2 NxM (80656) |


Conical Thread Application by Toolholder

| Toolholder | D2 (Inch) | NPT | NPTF | BSPT |
|------------|-----------|-------------------|------|-------------------|
| | | RTMNC050039-074A1 | .42 | 1/4-18* 3/8-18 |


* Using MiTM 19 tools the maximum thread length is .413"



2 Step Clamping System



Standard Toolholders (MiTM 24)







MITM

RTMC - for Standard Threads


| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | |
|--------------|------------------|---------|-----------------|------|-----|-----|-----|---------------|--------------------------|--|
| | | | L | L1 | D | D1 | D2 | | Z |  |
| 24 | RTMC075053-102M1 | 80860 | 3.27 | 1.02 | .75 | .42 | .53 | 1 | SLD4IP8 (M4x0.7) (80533) | Torx+ Screwdriver KIP8 •Use the included Vardex Torx+ screwdriver only. •Recommended max. torque 1.2 NxM (70231) |
| | RTMC075059-118M1 | 80861 | 3.39 | 1.18 | .75 | .47 | .59 | 1 | | |
| | RTMC075063-110M2 | 80752 | 3.31 | 1.10 | .75 | .49 | .63 | 2 | | |
| | RTMC075063-142M1 | 80862 | 3.62 | 1.42 | .75 | .49 | .63 | 1 | | |

Standard Thread Application by Toolholder

| Toolholder | Min. Thread Dia. | | | | | | |
|------------------|------------------|--------------|--|--------|---|-----------------|----------------|
| | D2 (Inch) | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | BSF | BSP(G) |
| RTMC075053-102M1 | .53 | M16x2 | M14.5x0.5; M15x0.75; M15x1; M15x1.25; M16x1.5; M16x1.75 | - | 1/16-12UN; 5/8-14UNS; 5/8-16UN; 5/8-18UNF; 3/8-20UN; 3/8-24UNEF; 3/8-28UN; 3/8-32UN | 1/16-14; 3/4-12 | 3/8-19; 1/2-14 |
| RTMC075059-118M1 | .59 | M18x2.5 | M16x0.5; M17x0.75; M17x1; M17x1.25; M17x1.5; M18x1.75; M18x2 | 3/4-10 | 3/4-12UN; 3/4-14UNS; 1/16-16UN; 1/16-20UN; 1/16-24UNEF; 1/16-28UN; 1/16-32UN | 3/4-12 | 1/2-14 |
| RTMC075063-110M2 | .63 | M20x2.5 | M17x0.5; M17x0.75; M18x1; M18x1.25; M18x1.5; M18x1.75; M19x2 | 3/4-10 | 3/4-12UN; 3/4-14UNS; 3/4-16UN; 3/4-18UNS; 3/4-20UNEF; 1/16-24UNEF; 1/16-28UN; 1/16-32UN | 3/4-12 | 1/2-14 |
| RTMC075063-142M1 | .63 | M20x2.5 | M17x0.5; M17x0.75; M18x1; M18x1.25; M18x1.5; M18x1.75; M19x2 | 3/4-10 | 3/4-12UN; 3/4-14UNS; 3/4-16UN; 3/4-18UNS; 3/4-20UNEF; 1/16-24UNEF; 1/16-28UN; 1/16-32UN | 3/4-12 | 1/2-14 |



Conical Toolholders (MiTM 24)





RTMC - for Conical Threads

| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | | No. of Flutes | Spare Parts | |
|--------------|-------------------|---------|-----------------|------|-----|-----|-----|---|--------------------------|--|---|
| | | | L | L1 | D | D1 | D2 | Z | |  |  |
| 24 | RTMNC075055-102M1 | 80863 | 3.23 | 1.02 | .75 | .45 | .55 | 1 | SLD4IP8 (M4x0.7) (80533) | KIP8 •Use the included Vardex Torx+ screwdriver only. •Recommended max. torque 1.2 Nm (70231) | |


Conical Thread Application by Toolholder

| Toolholder | D2 (Inch) | Thread Dia. | | |
|-------------------|-----------|-------------|--------|--------|
| | | NPT | NPTF | BSPT |
| RTMNC075055-102M1 | .55 | 3/8-18 | 3/8-18 | 3/8-19 |



MITM

Standard Toolholders (MiTM 25)



Coolant-Thru is recommended, especially when $D2 > 0.7 \times$ nominal thread diameter





RTMC - for Standard Threads

Spare Parts


| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | | No. of Flutes | Location Screw x2 | Torx+ Screwdriver |
|--------------|-------------------|---------|-----------------|------|------|-----|-----|---|--------------------------|--|-------------------|
| | | | L | L1 | D | D1 | D2 | Z | | | |
| 25 | RTMC075067-110S2 | 80748 | 3.29 | 1.10 | .75 | .55 | .67 | 2 | SLD4IP8 (M4x0.7) (80533) | KIP8 • Use the included Vardex Torx+ screwdriver only. • Recommended max. torque 1.2 NxM (70231) | |
| | RTMC075067-145S2 | 80747 | 3.65 | 1.45 | | | | | | | |
| | RTMC100067-110S2 | 80471 | 3.50 | 1.10 | | | | | | | |
| | RTMC100067-145S2 | 80472 | 3.86 | 1.45 | | | | | | | |
| | RTMC100075-125S2 | 80633 | 3.65 | 1.25 | 1.00 | .60 | .75 | 2 | | | |
| | RTMC100075-175S2 | 80634 | 4.15 | 1.75 | | | | | | | |
| | RTMC100081-150S3 | 80474 | 3.90 | 1.50 | | | | | | | |
| | RTMC100081-175S3 | 80475 | 4.15 | 1.75 | | | | | | | |
| | RTMC100087-170S3 | 80476 | 4.09 | 1.70 | | | | | | | |
| | RTMC100087-220S3 | 80478 | 4.60 | 2.20 | | | | | | | |
| | RTMC100118-220S5 | 80479 | 4.53 | 2.20 | | | | | | | |
| | BRTMC100118-315S4 | 80481 | 5.51 | 3.15 | | | | | | | |

Standard Thread Application by Toolholder

| Toolholder | Min.Thread Dia. | | | | | | |
|--------------------|-----------------|------------------|---------------------------------------|------------|---|--|--------|
| | D2 (Inch) | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | BSF | BSP(G) |
| RTMC 075067-110S2 | .67 | M20x2.5 | M19x1; M19x1.5; M20x2 | - | 7/8-10UNS; 15/16-12UN; 7/8-14UNF; 3/4-16UNF; 3/4-18UNS; 3/4-20UNEF | 7/8-11; 7/8-12; 7/8-14; 7/8-16 | 1/2-14 |
| RTMC 075067-145S2 | | | | | | | |
| RTMC 100067-110S2 | | | | | | | |
| RTMC 100067-145S2 | .75 | M22x2.5 M24x3 | M21x1; M21x1.5; M22x2 | 7/8-9; 1-8 | 7/8-20UNEF; 7/8-18UNS; 7/8-16UN; 7/8-14UNF; 7/8-12UN; 7/8-10UNS | 7/8-16; 7/8-14; 15/16-12; 15/16-11 | 5/8-14 |
| RTMC 100075-125S2 | | | | | | | |
| RTMC 100075-175S2 | | | | | | | |
| RTMC 100081-150S3 | | | | | | | |
| RTMC 100081-175S3 | .81 | M24x3 | M22x1; M23x1.5; M23x2; M23.5x2.5 | 1-8 | 15/16-9UN; 1-10UNS; 15/16-12UN; 1-14UNS; 15/16-16UN; 7/8-18UNS; 7/8-20UNEF | 1-11; 1-12; 1-14; 1-16 | 5/8-14 |
| RTMC 100087-170S3 | | | | | | | |
| RTMC 100087-220S3 | .87 | M27x3 | M24x1; M24x1.5; M25x2; M25x2.5 | - | 1 1/16-8UN; 1-9UN; 1-10UNS; 1-12UNF; 1-14UNS; 1-16UN; 1-18UN; 15/16-20UNEF | 1-11; 1-12; 1-14; 1-16 | 3/4-14 |
| RTMC 100118-220S5 | | | | | | | |
| BRTMC 100118-315S4 | 1.18 | - | M32x1; M32x1.5; M33x2; M33x2.5; M34x3 | - | 1 3/8-8UN; 1 3/8-9UN; 1 3/8-10UN; 1 3/16-12UN; 1 3/8-14UNS; 1 1/16-16UN; 1 1/16-18UNEF; 1 1/16-20UN | 1 3/8-11; 1 3/8-12; 1 3/8-14; 1 3/8-16 | 1-11 |



Conical Toolholders (MiTM 25)



Coolant-Thru is recommended, especially when $D2 > 0.7 \times$ nominal thread diameter




RTMNC - for Conical Threads

Spare Parts


| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | | No. of Flutes | Spare Parts | |
|--------------|-------------------|---------|-----------------|------|------|------|------|---|--------------------------------|---|---|
| | | | L | L1 | D | D1 | D2 | Z | |  |  |
| 25 | RTMNC075067-110S2 | 80749 | 3.29 | 1.10 | .75 | .55 | .68 | 2 | SLD4IP8 (M4x0.7) (80533) | Torx+ Screwdriver | |
| | RTMNC100067-110S2 | 80473 | 3.50 | 1.10 | 1.00 | .55 | .68 | 2 | | | |
| | RTMNC100087-170S3 | 80477 | 4.09 | 1.70 | 1.00 | .71 | .87 | 3 | | | |
| | RTMNC100110-170S4 | 80480 | 4.06 | 1.70 | 1.00 | 1.10 | 1.12 | 4 | | | |

Conical Thread Application by Toolholder

| Toolholder | Thread Dia. | | | |
|-------------------|-------------|---|--|---|
| | D2 (Inch) | NPT | NPTF | BSPT |
| RTMNC075067-110S2 | .68 | 1/2-14; 3/4-14; 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 1/2 -14; 3/4-14; 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 1/2 -14; 3/4-14 |
| RTMNC100067-110S2 | | | | |
| RTMNC100087-170S3 | .87 | 3/4-14; 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 3/4-14; 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 3/4-14; 1-11; 1 1/4-11; 1 1/2-11; 2-11; 2 1/2-11; 3-11; 4-11; 5-11; 6-11 |
| RTMNC100110-170S4 | 1.12 | 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 1-11.5; 1 1/4-11.5; 1 1/2-11.5; 2-11.5 | 1-11; 1 1/4-11; 1 1/2-11; 2-11; 2 1/2-11; 3-11; 4-11; 5-11; 6-11 |



Shell Mill (MiTM 25)



Coolant-Thru is recommended, especially when $D2 > 0.7 \times$ nominal thread diameter

Conical and Standard Shell Mills

| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | | |
|--------------|---------------------|--------------------|-----------------|-------|-------|------|------|----------------------|--------------------------|---|----------------------|
| | | | D1 | D2 | d(H7) | H | Z | | Location Screw x2 | Torx+ Screwdriver | Holder Screw |
| Standard | 25 | RTMC-D150-050-2555 | 80569 | 1.38 | 1.54 | .50 | 1.26 | 5 | SLD4IP8 (M4x0.7) (80533) | Use the included Vardex Torx+ screwdriver only. Recommended max. torque 1.2 NxM (70231) | 1/4"-28x1.25 (70263) |
| | | RTMC-D190-075-2557 | 80570 | 1.77 | 1.93 | .75 | 1.38 | 7 | | | 3/8"-24x1.25 (70223) |
| | | RTMC-D230-100-2559 | 80571 | 2.17 | 2.32 | 1.00 | 1.58 | 9 | | | 1/2"-20x1.50 (70262) |
| Conical | RTMNC-D150-050-2555 | 80572 | 1.38 | 1.53* | .50 | 1.26 | 5 | 1/4"-28x1.25 (70263) | | | |

* For inserts 8NPT and 8NPTF use for CNC program 1.55".





Standard Thread Applications by Toolholder

| Toolholder | | Min. Thread Dia. | | | | |
|------------|--------------------|------------------|---|--|--|-----------------------------------|
| | D2 (Inch) | ISO (fine) | UN/UNF/UNEF/UNS | BSW | BSP(G) | |
| Standard | RTMC-D150-050-2555 | 1.54 | M42x1; M42x1.25; M42 x1.5; M45x2; M45x3 | 1 ¹ / ₁₆ -12UNF; 1 ³ / ₄ -14UNS; 1 ⁵ / ₈ -16UN 1 ⁵ / ₈ -18UNEF; 1 ⁵ / ₈ -20UN; | 1 ³ / ₄ -16 1 ³ / ₄ -12 | 1 ¹ / ₂ -11 |
| | RTMC-D190-075-2557 | 1.93 | M52x1; M52x1.25; M55x1.5; M55x2; M55x3 | 2 ¹ / ₈ -12UN; 2 ¹ / ₁₆ -16UN; 2 ¹ / ₈ -20UN; 2 ¹ / ₈ -8UN 2 ¹ / ₄ -10UNS; 2 ¹ / ₄ -14UNS; 2 ¹ / ₄ -18UNS | 2 ¹ / ₄ -16 2 ¹ / ₄ -12 | 1 ³ / ₄ -11 |
| | RTMC-D230-100-2559 | 2.32 | M64x1; M64x1.25; M64x1.5; M64x2; M65x3 | 2 ¹ / ₂ -18UN; 2 ¹ / ₂ -20UN; 2 ¹ / ₂ -8UN 2 ¹ / ₂ -12UN; 2 ¹ / ₂ -10UN; 2 ¹ / ₂ -14UN; 2 ¹ / ₂ -16UN | 2 ¹ / ₂ -16 2 ¹ / ₂ -12 | 2 ¹ / ₄ -11 |


Conical Thread Applications by Toolholder

| Toolholder | | Thread Dia. | | | |
|------------|---------------------|-------------|---|--|--------------------------------------|
| | D2 (Inch) | NPT | NPTF | BSPT | |
| Conical | RTMNC-D150-050-2555 | 1.53* | 1 ¹ / ₂ - 11.5; 2-11.5; 2 ¹ / ₂ (and up) -8 | 1 ¹ / ₂ - 11.5; 2-11.5 | 1 ¹ / ₂ -6 x11 |

* For inserts 8NPT and 8NPTF use for CNC program 1.55".



Standard Toolholders (MiTM 40)





RTMC - for Standard Threads


| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | | |
|--------------|-------------------|---------|-----------------|------|------|------|------|---------------|---------------------------------|--------------------------------|---|
| | | | L | L1 | D | D1 | D2 | | Z | Location Screw | Clamping Screw x2 |
| 40 | RTMC100087-169L3 | 80618 | 4.00 | 1.69 | 1.00 | .71 | .87 | 3 | SLD4IP8A (M4x0.7) (80533) | SCD4IP8 (M4x0.7) (80622) | <ul style="list-style-type: none"> • Use the included Vardex Torx+ screwdriver only. • Recommended max. torque 1.2 Nm (70231) |
| | RTMC100087-256L3 | 80619 | 4.87 | 2.56 | 1.00 | .71 | .87 | 3 | | | |
| | RTMC125118-215L4 | 80620 | 4.55 | 2.15 | 1.25 | 1.02 | 1.18 | 4 | | | |
| | BRTMC125118-315L3 | 80621 | 5.35 | 3.15 | 1.25 | 1.02 | 1.18 | 3 | | | |

Standard Thread Application by Toolholder


| Toolholder | Min. Thread Dia. | | | | | | | | |
|-------------------|------------------|--------------|---|-----|--|--|--|---|--------|
| | D2 (Inch) | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | | | BSF | BSP(G) |
| RTMC100087-169L3 | .87 | M27x3 | M24x1; M24x1.5 M25x2; M25x2.5 | - | 1 ¹¹ / ₁₆ -8UN; 1-9UN; 1-10UNS; 1-12UNF; 1-14UNS; 1-16UN; 1-18UN; 1 ¹ / ₁₆ -20UNEF | | | 1-11; 1-12; 1-14; 1-16; | ¾-14 |
| RTMC100087-256L3 | .87 | M27x3 | M24x1; M24x1.5 M25x2; M25x2.5 | - | 1 ¹¹ / ₁₆ -8UN; 1-9UN; 1-10UNS; 1-12UNF; 1-14UNS; 1-16UN; 1-18UN; 1 ¹ / ₁₆ -20UNEF | | | 1-11; 1-12; 1-14; 1-16; | ¾-14 |
| RTMC125118-215L4 | 1.18 | - | M32x1; M32x1.5 M33x2; M33x2.5; M34x3 | - | 1 ³ / ₈ -8UN; 1 ³ / ₈ -9UN; 1 ³ / ₈ -10UN; 1 ¹ / ₁₆ -12UN; 1 ³ / ₈ -14UNS; 1 ¹ / ₁₆ -16UN; 1 ¹ / ₁₆ -18UNEF; 1 ¹ / ₁₆ -20UN | | | 1 ³ / ₈ -11; 1 ³ / ₈ -12; 1 ³ / ₈ -14; 1 ³ / ₈ -16 | 1-11 |
| BRTMC125118-315L3 | 1.18 | - | M32x1; M32x1.5 M33x2; M33x2.5; M34x3 | - | 1 ³ / ₈ -8UN; 1 ³ / ₈ -9UN; 1 ³ / ₈ -10UN; 1 ¹ / ₁₆ -12UN; 1 ³ / ₈ -14UNS; 1 ¹ / ₁₆ -16UN; 1 ¹ / ₁₆ -18UNEF; 1 ¹ / ₁₆ -20UN | | | 1 ³ / ₈ -11; 1 ³ / ₈ -12; 1 ³ / ₈ -14; 1 ³ / ₈ -16 | 1-11 |



2 Step Clamping System



Shell Mill (MiTM 40)



Conical and Standard Shell Mills

Spare Parts




| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | | | | |
|--------------|---------------------|---------|-----------------|------|-------|------|---|---------------------------------|--------------------------------|----------------------|-------------------|--|----------------------|
| | | | D1 | D2 | d(H7) | H | Z | | Location Screw | Clamping Screw x2 | Torx+ Screwdriver | Holder Screw | |
| Standard | RTMC-D190-075-40L7 | 80623 | 1.77 | 1.93 | .75 | 1.97 | 7 | SLD4IP8A (M4x0.7) (80533) | SCD4IP8 (M4x0.7) (80622) | Torx+ Screwdriver | Holder Screw | •Use the included Vardex Torx+ screwdriver only. •Recommended max. torque 1.2 NxM (70231) | 3/8"-24x1.25 (70223) |
| | RTMC-D230-100-40L9 | 80624 | 2.17 | 2.32 | 1.00 | 2.00 | 9 | | | | | | 1/2"-20x1.5 (70224) |
| Conical | RTMNC-D190-075-40L7 | 80625 | 1.77 | 1.93 | .75 | 1.97 | 7 | | | | | | 3/8"-24x1.25 (70223) |

Standard Thread Application by Toolholder


| Toolholder | | Min. Thread Dia. | | | | |
|------------|--------------------|------------------|------------------------------|--|----------------------|-----------|
| | | D2 (Inch) | ISO (fine) | UN/UNF/UNEF/UNS | BSW | BSP(G) |
| Standard | RTMC-D190-075-40L7 | 1.93 | M52x1; M55x1.5; M55x2; M55x3 | 2 1/8 -8UN; 2 1/8 -12UN; 2 1/16-16UN; 2 1/8 - 20UN; 2 1/4 -10UNS; 2 1/4 -14UNS; 2 1/4 -18UNS | 2 1/4 -12; 2 1/4 -16 | 1 3/4 -11 |
| | RTMC-D230-100-40L9 | 2.32 | M64x1; M64x1.5; M64x2; M65x3 | 2 1/2 -8UN; 2 1/2 -10UNS; 2 1/2 -12UN; 2 1/2 -14UNS; 2 1/2 -16UN; 2 1/2 -18UNS; 2 1/2 -20UN | 2 1/2 -12; 2 1/2 -16 | 2 1/4 -11 |

Conical Thread Application by Toolholder


| Toolholder | | Min. Thread Dia. | | | |
|------------|---------------------|------------------|--------------------------|----------------------|--------|
| | | D2 (Inch) | NPT | NPTF | BSPT |
| Conical | RTMNC-D190-075-40L7 | 1.93 | 2-11.5; 2 1/2-8 (and up) | 2-11.5; 2 1/2-8; 3-8 | 2-6x11 |



2 Step Clamping System



Standard Toolholders (MiTM 41)



Coolant-Thru is recommended, especially when $D2 > 0.7 \times$ nominal thread diameter




RTMC - for Standard Threads

| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | Spare Parts | | |
|--------------|------------------|---------|-----------------|------|------|------|------|---------------|---------------------------------|--------------------------------|---|
| | | | L | L1 | D | D1 | D2* | | Z | Location Screw x2 | Clamping Screw |
| 41 | RTMC100083-177B1 | 80654 | 4.13 | 1.77 | 1.00 | .63 | .835 | 1 | SLD4IP8A (M4x0.7) (80533) | SCD4IP8 (M4x0.7) (80622) | Torx+ Screwdriver KIP8 •Use the included Vardex Torx+ screwdriver only. •Recommended max. torque 1.2 NxM (70231) |
| | RTMC100096-169B2 | 80864 | 4.13 | 1.69 | 1.00 | .76 | .97 | 2 | | | |
| | RTMC125118-169B3 | 80865 | 4.13 | 1.69 | 1.25 | .95 | 1.18 | 3 | | | |
| | RTMC125118-256B3 | 80866 | 5.00 | 2.56 | 1.25 | .95 | 1.18 | 3 | | | |
| | RTMC125141-169B5 | 80867 | 4.13 | 1.69 | 1.25 | 1.11 | 1.42 | 5 | | | |
| | RTMC125141-256B4 | 80868 | 4.98 | 2.56 | 1.25 | 1.11 | 1.42 | 4 | | | |


Standard Thread Application by Toolholder

| Toolholder | Min. Thread Dia. | | | | | | | |
|------------------|------------------|---------------------------------------|------------------------------|---|------------------------|------------------------------------|---------|---------|
| | D2* (Inch) | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | BSW/BSF | NPT | NPTF |
| RTMC100083-177B1 | .835 | M27x3; M30x3.5; M33x3.5; M36x4; M39x4 | M30x3; M42x4 | 1-8, 1 1/8-7; 1 1/4-7; 1 3/8-6; 1 1/2-6 | 1 1/16-8UN; 1 1/16-6UN | 1-8BSW; 1 1/8-7BSW | - | - |
| RTMC100096-169B2 | .97 | M30x3.5; M36x4 | M28x3; M45x4 | 1 1/8-7; 1 3/8-6 | 1 1/8-8UN; 1 1/16-6UN | 1 3/8-8BSF; 1 1/4-7BSW | - | - |
| RTMC125118-169B3 | 1.18 | M36x4; M42x4.5 | M34x3; M34x3.5; M45x4 | 1 3/8-6 | 1 3/8-8UN; 1 1/16-6UN | 1 3/8-8BSF; 1 3/4-7BSF; 1 1/2-6BSW | - | - |
| RTMC125118-256B3 | 1.18 | M36x4; M42x4.5 | M34x3; M34x3.5; M45x4 | 1 3/8-6 | 1 3/8-8UN; 1 1/16-6UN | 1 3/8-8BSF; 1 3/4-7BSF; 1 1/2-6BSW | - | - |
| RTMC125141-169B5 | 1.42 | M42x4.5; M48x5; M56x5.5; M64x6 | M40x3; M40x3.5; M42x4; M70x6 | 1 3/4-5; 2-4.5; 2 1/2-4 | 1 3/8-8UN; 1 3/8-6UN | 1 3/8-8BSF; 1 3/4-7BSF; 1 1/8-6BSF | 2 1/2-8 | 2 1/2-8 |
| RTMC125141-256B4 | 1.42 | M42x4.5; M48x5; M56x5.5; M64x6 | M40x3; M40x3.5; M42x4; M70x6 | 1 3/4-5; 2-4.5; 2 1/2-4 | 1 3/8-8UN; 1 3/8-6UN | 1 3/8-8BSF; 1 3/4-7BSF; 1 1/8-6BSF | 2 1/2-8 | 2 1/2-8 |


* For external applications, inserts R41E... use for CNC program (D2 +0.024").



2 Step Clamping System



Shell Mill (MiTM 41)



Coolant-Thru is recommended, especially when D2 > 0.7 x nominal thread diameter


MITM

| Standard Shell Mill | | | | | | | Spare Parts | | | | |
|---------------------|--------------------|-------|-----------------|-------|-------|---------------|-------------|---------------------------|--------------------------|---|---------------------|
| Insert Style | Ordering Code | | Dimensions Inch | | | No. of Flutes | | | | | |
| | | | D1 | D2* | d(H7) | H | Z | Location Screw x2 | Clamping Screw | Torx+ Screwdriver | Holder Screw |
| 41 | RTMC-D209-075-41B5 | 80869 | 1.77 | 2.08* | .75 | 2.00 | 5 | SLD4IP8A (M4x0.7) (80533) | SCD4IP8 (M4x0.7) (80622) | KIP8 •Use the included Vardex Torx+ screwdriver only. •Recommended max. torque 1.2 Nm (70231) | 3/8"-24x1.5 (70264) |
| | RTMC-D248-100-41B6 | 80870 | 2.17 | 2.48* | 1.00 | 2.00 | 6 | | | | 1/2"-20x1.5 (70224) |

Standard Thread Application by Toolholder

| Toolholder | D2* (Inch) | Min. Thread Dia. | | | | | | |
|--------------------|------------|------------------|-----------------|---------|-------------------------|------------------|---------|---------|
| | | ISO (coarse) | ISO (fine) | UNC | UN/UNF/UNEF/UNS | BSF | NPT | NPTF |
| RTMC-D209-075-41B5 | 2.08* | M64x6 | M58x4; M70x6 | 2 1/2-4 | 2 3/8-6UN; 2 3/8-8UN | 2 3/8-8; 2 1/2-6 | 2 1/2-8 | 2 1/2-8 |
| RTMC-D248-100-41B6 | 2.48* | - | M68x4; M70x6 | 3-4 | 2 3/4-6UN; 2 3/4-8UN | 2 3/4-8; 2 3/4-6 | 2 1/2-8 | 2 1/2-8 |

* For external applications, inserts R41E... use for CNC program (D2+.024").



Recommended Grades, Cutting Speeds Vc [ft/min] and Feed f [inch/tooth]

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | Feed f [inch/tooth] | | |
|-------------------------------------|------------------------------|--|------------------------------------|-------------|-----------|---------------------|---------------|-------------|
| | | | | VBX | VTX | (Excluding MiTM 19) | (for MiTM 19) | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 328-689 | 295-591 | .0039-.0138 | .0024-.0079 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 328-591 | 295-558 | .0039-.0157 | .0024-.0098 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 328-558 | 295-525 | .0039-.0138 | .0024-.0079 |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 262-459 | 295-509 | .0039-.0157 | .0024-.0098 |
| | 5 | | Hardened | 275 | 262-492 | 262-525 | .0039-.0138 | .0024-.0079 |
| | 6 | | Hardened | 350 | 230-459 | 230-492 | .0039-.0118 | .0024-.0079 |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 197-427 | 230-377 | .0039-.0138 | .0024-.0079 |
| | 8 | | Hardened | 325 | 230-361 | 197-328 | .0039-.0079 | .0024-.0039 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 328-558 | 328-558 | .0039-.0118 | .0024-.0079 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 230-394 | 230-427 | .0039-.0079 | .0024-.0039 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 328-558 | 394-591 | .0039-.0118 | .0024-.0079 |
| | 12 | | Hardened | 330 | 328-558 | 394-591 | .0039-.0079 | .0024-.0039 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 230-459 | 328-459 | .0039-.0118 | .0024-.0079 |
| | 14 | | Super Austenitic | 200 | 230-459 | 328-459 | .0039-.0079 | .0024-.0039 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 230-459 | 328-459 | .0039-.0118 | .0024-.0079 |
| | 16 | | Hardened | 330 | 230-459 | 328-459 | .0039-.0079 | .0024-.0039 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 230-394 | 328-394 | .0039-.0118 | .0024-.0079 |
| | 18 | | Hardened | 330 | 230-394 | 328-394 | .0039-.0079 | .0024-.0039 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 197-427 | 328-394 | .0020-.0063 | .0012-.0039 |
| | 29 | | Pearlitic (long chips) | 230 | 197-394 | 262-328 | .0016-.0039 | .0008-.0024 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 197-427 | 262-328 | .0039-.0118 | .0024-.0079 |
| | 31 | | High Tensile Strength | 260 | 197-328 | 262-328 | .0039-.0079 | .0024-.0039 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 197-410 | 262-328 | .0039-.0118 | .0024-.0079 |
| | 33 | | Pearlitic | 260 | 164-295 | 197-295 | .0039-.0079 | .0024-.0039 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-820 | - | .0059-.0217 | .0035-.0118 |
| | 35 | | Aged | 100 | 328-591 | - | .0059-.0197 | .0035-.0118 |
| | 36 | Aluminium Alloys | Cast | 75 | 492-1.312 | - | .0059-.0197 | .0035-.0118 |
| | 37 | | Cast & Aged | 90 | 492-919 | - | .0039-.0157 | .0024-.0098 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 262-492 | - | .0059-.0197 | .0035-.0118 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 394-689 | 328-656 | .0059-.0197 | .0035-.0118 |
| 40 | Bronze And Non Leaded Copper | | 100 | 394-689 | 328-656 | .0039-.0157 | .0024-.0098 | |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 66-148 | 66-131 | .0039-.0079 | .0024-.0039 |
| | 20 | | Aged (iron based) | 280 | 66-98 | 66-98 | .0016-.0039 | .0008-.0024 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 49-66 | 49-66 | .0016-.0039 | .0008-.0024 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 33-49 | 33-49 | .0016-.0039 | .0008-.0024 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 230-459 | 230-394 | .0016-.0039 | .0008-.0024 |
| 24 | α+β Alloys | | 1050Rm | 66-164 | 66-164 | .0016-.0039 | .0008-.0024 | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 49-148 | 49-148 | .0024-.0047 | .0016-.0028 |
| | 26 | | | 51-55HRc | 49-131 | 49-131 | .0016-.0031 | .0008-.0020 |

MITM

Grades

| Grade | Application | Sample |
|------------|---|---|
| VBX | TiCN coated carbide grade. Excellent grade for steels and general use. |  |
| VTX | TiAlN coated carbide grade. Ideal for Stainless Steels. |  |



STANDARD


Thread Milling

Inserts | Toolholders

Vardex Ordering Code System

■ Thread Milling Inserts

| | | | | | | | | |
|----------|----------|----------|-----------|-----------|------------|----------|------------|----------------|
| 3 | B | I | 12 | UN | TM2 | F | VBX | 028/... |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |

| | | | | |
|---|--|---|---|---|
| 1 - Insert Size 6.0 - 6.0 mm 2 - 1/4" 3 - 3/8" 3B - 3/8"B 4 - 1/2" 5 - 5/8" 6B - 3/4"B |  | 2 - Cutting Edge Length B - TMB | 3 - Type of Insert E - External I - Internal EI - External + Internal | 4 - Pitch 80 - 4TPI 0.35 - 6.0mm |
| 5 - Standard ISO - ISO Metric UN - American UN UNJ - UNJ W - Whitworth for BSW, BSP NPT - NPT NPTF - NPTF NPS - NPS | BSPT - British Standard Pipe Thread PG - Pg DIN 40430 ACME - ACME TR - Trapez DIN 103 | 6 - System TM2 TM | 7 - Pitch Type F = Fine Pitch | 8 - Coarse Pitch Inserts 028/... |
| | | | | 9 - Carbide Grade VBX VTX VK2 |

TM Standard

■ Thread Milling Toolholders

| | | | | | | | | | | | |
|----------|-----------|----------|----------|------------|----------|----------|----------|----------|-----------|----------|-----------|
| B | TM | N | C | 075 | - | 3 | B | - | LH | - | 10 |
| 1 | 2 | 3 | 4 | 5 | | 6 | 7 | 8 | 9 | | |

| | | | |
|---|---|--|--|
| 1 - Shank Type B - Anti Vibration System | 2 - System TM - Thread Milling | 3 - Holder Type 2 - Twin Flute M - Mini L - Long Tool N - Tapered Holder V - Vertical Holder S - Single Point O - Offset W - Wide Cut. Dia. | 4 - Cooling C - Coolant Channel |
| 5 - Shank Dia. 0375 - 3/8" 050 - 1/2" 0625 - 5/8" 075 - 3/4" 100 - 1" 125 - 1 1/4" | 6 - Insert Size 6.0 - 6.0mm 2 - 1/4" 3 - 3/8" 3B - 3/8"B 4 - 1/2" 5 - 5/8" 6B - 3/4"B | 7 - Cut. Edge Length B - TMB | 9 - RH / LH Holder None - Right Hand LH - Left Hand |
| | | 8 - Serial No. (for TMO Holders) 1 - 16 | 10 - Serial No. (for Coarse Pitch Holders) 124/... |

■ Thread Milling Shell Mill

| | | | | | | | |
|-------------|----------|-------------|----------|------------|----------|----------|----------|
| TMSH | - | D250 | - | 075 | - | 3 | B |
| 1 | | 2 | | 3 | | 4 | 5 |

| | | | |
|---|---|--|--|
| 1 - System Thread Mill Shell Mill | 2 - Cutting Dia. 150 - 1.50" 200 - 1.97" 250 - 2.48" 300 - 3.15" 400 - 3.94" 500 - 4.92" | 3 - Drive Hole Dia. 1/2", 3/4", 1", 1 1/4", 1 1/2" | 4 - Insert Size 2 - 1/4" 3 - 3/8" 3B - 3/8"B 5 - 5/8" 6B - 3/4"B |
| 5 - Cut. Edge Length B - TMB | | | |

Thread Milling Standard System

TMMC
 Miniature Applications



No. of Flutes (Z) 1
 Cutting Dia. (D2) .35
 Tool Overhang (L1) .57-67

TMC
 Standard Applications



No. of Flutes (Z) 1
 Cutting Dia. (D2) .45-1.81
 Tool Overhang (L1) .47-2.56

TMC 124/...
 Coarse Pitch Thread




No. of Flutes (Z) 1
 Cutting Dia. (D2) .35-.87
 Tool Overhang (L1) .59-1.57


TMLC
 For Long Threads



No. of Flutes (Z) 1
 Cutting Dia. (D2) .45-1.81
 Tool Overhang (L1) .67-3.86



TMNC
 For Conical Applications




No. of Flutes (Z) 1
 Cutting Dia. (D2) .61-1.46
 Tool Overhang (L1) .87-2.28

TM2C
 Fast Infeed




No. of Flutes (Z) 2
 Cutting Dia. (D2) .67-2.05
 Tool Overhang (L1) .79-2.56

TMOC
 For Fewer Cycles



No. of Flutes (Z) 1
 Cutting Dia. (D2) .57-1.18
 Tool Overhang (L1) .98-2.05

TMSH
 Fast Machining in Large
 Diameters and Deep Holes



No. of Flutes (Z) 4-9
 Cutting Dia. (D2) 1.5-4.92
 Tool Overhang (L1) Max. 7.87

TMSC
 For Short Threads
 Economical Solutions



No. of Flutes (Z) 1
 Cutting Dia. (D2) .49
 Tool Overhang (L1) .98


TMVC
 For Large Pitches




No. of Flutes (Z) 1
 Cutting Dia. (D2) 1.81
 Tool Overhang (L1) 2.36

ISO Metric

External / Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Standard TM


Standard TM

| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|----------------|------------------|------------------|------|-------|--------------------------|
| IC | L Inch | mm | External | Internal | Inch | | |
| 6.0mm | .41 | 0.5 | | 6.0I0.5ISOTM... | .39 | 20 | TMMC...-6.0 |
| | | 0.75 | | 6.0I0.75ISOTM... | .38 | 13 | |
| | | 1.0 | | 6.0I1.0ISOTM... | .35 | 9 | |
| | | 1.25 | | 6.0I1.25ISOTM... | .34 | 7 | |
| | | 1.5 | | 6.0I1.5ISOTM... | .35 | 6 | |
| 1/4" | .43 | 0.5 | | 2I0.5ISOTM2... | .39 | 20 | TMC...-2 TMSH...-2 |
| | | 0.75 | 2E0.75ISOTM2... | 2I0.75ISOTM2... | .41 | 14 | |
| | | 1.0 | 2E1.0ISOTM2... | 2I1.0ISOTM2... | .39 | 10 | |
| | | 1.25 | 2E1.25ISOTM2... | 2I1.25ISOTM2... | .39 | 8 | |
| | | 1.25 | | 2I1.25ISOTM2... | .34 | 7 | |
| | | 1.5 | 2E1.5ISOTM2... | 2I1.5ISOTM2... | .35 | 6 | |
| 3/8" | .63 | 0.5 | | 3I0.5ISOTM2... | .59 | 30 | TMC...-3 TMSH...-3 |
| | | 0.75 | 3E0.75ISOTM2... | 3I0.75ISOTM2... | .59 | 20 | |
| | | 0.8 | | 3I0.8ISOTM2... | .57 | 18 | |
| | | 1.0 | 3E1.0ISOTM2... | 3I1.0ISOTM2... | .55 | 14 | |
| | | 1.0 | | 3I1.0ISOTM2... | .59 | 15 | |
| | | 1.25 | 3E1.25ISOTM2... | 3I1.25ISOTM2... | .59 | 12 | |
| | | 1.5 | 3E1.5ISOTM2... | 3I1.5ISOTM2... | .59 | 10 | |
| | | 1.75 | 3E1.75ISOTM2... | 3I1.75ISOTM2... | .55 | 8 | |
| 3/8"B | .87 | 1.0 | 3BE1.0ISOTM2... | 3BI1.0ISOTM2... | .87 | 22 | BTMC...-3B TMSH...-3B |
| | | 1.25 | 3BE1.25ISOTM2... | 3BI1.25ISOTM2... | .84 | 17 | |
| | | 1.5 | 3BE1.5ISOTM2... | 3BI1.5ISOTM2... | .83 | 14 | |
| | | 1.75 | 3BE1.75ISOTM2... | 3BI1.75ISOTM2... | .83 | 12 | |
| | | 2.0 | 3BE2.0ISOTM2... | 3BI2.0ISOTM2... | .87 | 11 | |
| 5/8" | 1.06 | 1.0 | | 5I1.0ISOTM2... | 1.02 | 26 | TMC...-5 TMSH...-5 |
| | | 1.25 | 5E1.25ISOTM2... | 5I1.25ISOTM2... | .98 | 20 | |
| | | 1.5 | 5E1.5ISOTM2... | 5I1.5ISOTM2... | 1.00 | 17 | |
| | | 1.75 | 5E1.75ISOTM2... | 5I1.75ISOTM2... | .96 | 14 | |
| | | 2.0 | 5E2.0ISOTM2... | 5I2.0ISOTM2... | .94 | 12 | |
| | | 2.5 | 5E2.5ISOTM2... | 5I2.5ISOTM2... | .98 | 10 | |
| | | 3.0 | 5E3.0ISOTM2... | 5I3.0ISOTM2... | .94 | 8 | |
| | | 3.5 | 5E3.5ISOTM2... | 5I3.5ISOTM2... | .96 | 7 | |
| | | 4.0 | 5E4.0ISOTM2... | 5I4.0ISOTM2... | .94 | 6 | |
| | 4.5 | 5E4.5ISOTM2... | 5I4.5ISOTM2... | .89 | 5 | | |


All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm) which has one cutting edge.

ISO Metric (con't)

External / Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H




Standard TM

Standard TM


| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|-------|-----------------|-----------------|------|-------|------------------------|
| IC | L Inch | mm | External | Internal | Inch | | |
| 3/4"B | 1.52 | 1.5 | 6BE1.5ISOTM2... | 6BI1.5ISOTM2... | 1.42 | 24 | TMC..-6B TMSH...-6B |
| | | 2.0 | 6BE2.0ISOTM2... | 6BI2.0ISOTM2... | 1.42 | 18 | |
| | | 2.5 | 6BE2.5ISOTM2... | 6BI2.5ISOTM2... | 1.38 | 14 | |
| | | 3.0 | 6BE3.0ISOTM2... | 6BI3.0ISOTM2... | 1.42 | 12 | |
| | | 4.0 | 6BE4.0ISOTM2... | 6BI4.0ISOTM2... | 1.26 | 8 | |
| | | 4.5 | 6BE4.5ISOTM2... | 6BI4.5ISOTM2... | 1.24 | 7 | |
| | | 5.0 | 6BE5.0ISOTM2... | 6BI5.0ISOTM2... | 1.18 | 6 | |
| | | 5.5 | 6BE5.5ISOTM2... | 6BI5.5ISOTM2... | 1.30 | 6 | |
| | | 6.0 | 6BE6.0ISOTM2... | 6BI6.0ISOTM2... | 1.18 | 5 | |

ISO Metric (con't)

Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Coarse Pitch TM

Coarse Pitch TM


| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder | Bore Dia. Range |
|------------|-------------|--------|-------------------------|--------------|-----|-------|---------------------|-----------------|
| | IC | L Inch | | | | | | |
| M10 X 0.75 | 6.0 mm | .41 | 6.0I0.75ISOTM028/001... | 1 | .38 | 13 | TMMC050-6.0 | .36 - .39 |
| M10 X 0.75 | | | 6.0I0.75ISOTM028/001... | 1 | .38 | 13 | TMMC075-6.0 | .36 - .39 |
| M12 X 1.25 | | | 6.0I1.25ISOTM028/002... | 1 | .34 | 7 | TMMC050-6.0 | .42 - .45 |
| M12 X 1.25 | | | 6.0I1.25ISOTM028/002... | 1 | .34 | 7 | TMMC075-6.0 | .42 - .45 |
| M12 X 1.75 | 1/4" | .43 | 6.0I1.75ISOTM028/003... | 1 | .34 | 5 | TMMC075-6.0-124/203 | .40 - .75 |
| M14 X 2.0 | | | 2I2.0ISOTM028/004... | 2 | .39 | 5 | TMC050-2 | .46 - .77 |
| M14 X 2.0 | | | 2I2.0ISOTM028/004... | 2 | .39 | 5 | TMC075-2 | .46 - .77 |
| M16 X 2.0 | | | 2I2.0ISOTM028/004... | 2 | .39 | 5 | TMC050-2 | .46 - .77 |
| M16 X 2.0 | 3/8" | .63 | 2I2.0ISOTM028/004... | 2 | .39 | 5 | TMC075-2 | .46 - .77 |
| M20 X 2.5 | | | 3I2.5ISOTM028/005... | 1 | .49 | 5 | TMC075-3-124/201 | .68 - .76 |
| M22 X 2.5 | | | 4I2.5ISOTM028/006... | 1 | .69 | 7 | TMC100-4-124/202 | .76 - 1.24 |
| M24 X 3.0 | | | 4I3.0ISOTM028/007... | 1 | .71 | 6 | TMC100-4-124/202 | .81 - 1.29 |
| M27 X 3.0 | 1/2" | .87 | 4I3.0ISOTM028/007... | 1 | .71 | 6 | TMC100-4-124/202 | .81 - 1.29 |
| M30 X 3.5 | | | 5I3.5ISOTM028/008... | 2 | .96 | 7 | TMC100-5-124/204 | 1.03 - 1.41 |
| M33 X 3.5 | | | 5I3.5ISOTM028/008... | 2 | .96 | 7 | TMC100-5-124/204 | 1.03 - 1.41 |
| M36 X 3.0 | | | 5I3.0ISOTM028/009... | 2 | .94 | 8 | TMC100-5 | 1.29 - 1.54 |
| M36 X 4.0 | 5/8" | 1.06 | 5I4.0ISOTM028/010... | 2 | .94 | 6 | TMC100-5 | 1.24 - 1.52 |
| M39 X 3.0 | | | 5I3.0ISOTM028/009... | 2 | .94 | 8 | TMC100-5 | 1.29 - 1.54 |
| M39 X 4.0 | | | 5I4.0ISOTM028/010... | 2 | .94 | 6 | TMC100-5 | 1.24 - 1.52 |
| M42 X 4.5 | | | 5I4.5ISOTM028/011... | 2 | .89 | 5 | TMC100-5 | 1.46 - 1.89 |
| M45 X 4.5 | | | 5I4.5ISOTM028/011... | 2 | .89 | 5 | TMC100-5 | 1.46 - 1.89 |
| M48 X 5.0 | | | 5I5.0ISOTM028/075... | 2 | .79 | 4 | TMC100-5 | 1.53 - ∞ |
| M52 X 5.0 | | | 5I5.0ISOTM028/075... | 2 | .79 | 4 | TMC100-5 | 1.53 - ∞ |

TM Standard


For Toolholder information, see page 282.

ISO Metric (con't)

External / Internal




Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Standard TM

Standard TM Inserts for TMO Toolholders

| Insert Size | | Pitch | Ordering Code | | Toolholder | ECL |
|-------------|-----------------|-------|-----------------|----------------------|----------------|----------------|
| IC | L Inch | mm | External | Internal | | Inch |
| 1/4" | .43 | 0.5 | | 2I0.5ISOTM2... | TMOC075-2-8 | .75 |
| | | 0.75 | 2E0.75ISOTM2... | 2I0.75ISOTM2... | TMOC075-2-9 | .77 |
| | | 1.0 | 2E1.0ISOTM2... | 2I1.0ISOTM2... | TMOC075-2-8 | .75 |
| | | 1.25 | 2E1.25ISOTM2... | | TMOC075-2-10 | .74 |
| | | 1.25 | | 2I1.25ISOTM2... | TMOC075-2-10 | .64 |
| | | 1.5 | 2E1.5ISOTM2... | | TMOC075-2-8 | .71 |
| | | 1.5 | | 2I1.5ISOTM2... | TMOC075-2-8 | .77 |
| 3/8" | .63 | 0.5 | | 3I0.5ISOTM2... | TMOC075-3-1 | 1.12 |
| | | 0.5 | | 3I0.5ISOTM2... | TMOC075-3-10 | 1.14 |
| | | 0.75 | 3E0.75ISOTM2... | 3I0.75ISOTM2... | TMOC075-3-11 | 1.12 |
| | | 1.0 | 3E1.0ISOTM2... | | TMOC075-3-10 | 1.10 |
| | | 1.0 | | 3I1.0ISOTM2... | TMOC075-3-10 | 1.14 |
| | | 1.25 | 3E1.25ISOTM2... | 3I1.25ISOTM2... | TMOC075-3-7 | 1.13 |
| | | 1.5 | 3E1.5ISOTM2... | 3I1.5ISOTM2... | TMOC075-3-1 | 1.12 |
| | | 1.75 | 3E1.75ISOTM2... | 3I1.75ISOTM2... | TMOC075-3-12 | 1.03 |
| | | 2.0 | 3E2.0ISOTM2... | 3I2.0ISOTM2... | TMOC075-3-10 | 1.10 |
| | | 5/8" | 1.06 | 1.0 | 5E1.0ISOTM2... | 5I1.0ISOTM2... |
| 1.0 | 5E1.0ISOTM2... | | | 5I1.0ISOTM2... | TMOC100-5-16 | 1.85 |
| 1.25 | 5E1.25ISOTM2... | | | 5I1.25ISOTM2... | TMOC100-5-13 | 1.92 |
| 1.5 | 5E1.5ISOTM2... | | | 5I1.5ISOTM2... | TMOC100-5-14 | 1.89 |
| 1.5 | 5E1.5ISOTM2... | | | 5I1.5ISOTM2... | TMOC100-5-16 | 1.83 |
| 1.75 | 5E1.75ISOTM2... | | | 5I1.75ISOTM2... | TMOC100-5-15 | 1.86 |
| 2.0 | 5E2.0ISOTM2... | | | 5I2.0ISOTM2... | TMOC100-5-12 | 1.73 |
| 2.5 | 5E2.5ISOTM2... | | | 5I2.5ISOTM2... | TMOC100-5-12 | 1.77 |
| 2.5 | 5E2.5ISOTM2... | | | 5I2.5ISOTM2... | TMOC100-5-14 | 1.87 |
| 3.0 | 5E3.0ISOTM2... | | | 5I3.0ISOTM2... | TMOC100-5-16 | 1.77 |
| 3.5 | 5E3.5ISOTM2... | | | 5I3.5ISOTM2... | TMOC100-5-16 | 1.79 |
| 4.0 | 5E4.0ISOTM2... | | | 5I4.0ISOTM2... | TMOC100-5-12 | 1.73 |
| 4.5 | 5E4.5ISOTM2... | | | 5I4.5ISOTM2... | TMOC100-5-14 | 1.77 |
| 5.0 | | | | 5I5.0ISOTM028/075... | TMOC100-5-12 | 1.57 |




ECL - The Effective Cutting Length



For Le and number of teeth of the above inserts, see the table for standard inserts on pages 254.
For Toolholder information, see page 287.

ISO Metric (con't)

External / Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Fine Pitch TM

Fine Pitch TM


| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|-------|-------------------|-------------------|------|-------|-----------------------|
| IC | L Inch | mm | External | Internal | Inch | | |
| 6.0mm | .41 | 0.35 | 6.0E0.35ISOTMF... | 6.0I0.35ISOTMF... | .37 | 14 | TMMC...-6.0 |
| | | 0.4 | 6.0E0.4ISOTMF... | 6.0I0.4ISOTMF... | .36 | 12 | |
| | | 0.45 | 6.0E0.45ISOTMF... | 6.0I0.45ISOTMF... | .37 | 11 | |
| | | 0.5 | 6.0E0.5ISOTMF... | | .37 | 10 | |
| | | 0.6 | 6.0E0.6ISOTMF... | | .35 | 8 | |
| | | 0.7 | 6.0E0.7ISOTMF... | | .36 | 7 | |
| | | 0.75 | 6.0E0.75ISOTMF... | | .32 | 6 | |
| | | 0.8 | 6.0E0.8ISOTMF... | | .35 | 6 | |
| 1/4" | .43 | 0.35 | 2E0.35ISOTM2F... | 2I0.35ISOTM2F... | .40 | 15 | TMC...-2 TMSH...-2 |
| | | 0.4 | 2E0.4ISOTM2F... | 2I0.4ISOTM2F... | .39 | 13 | |
| | | 0.45 | 2E0.45ISOTM2F... | 2I0.45ISOTM2F... | .37 | 11 | |
| | | 0.5 | 2E0.5ISOTM2F... | | .37 | 10 | |
| | | 0.6 | 2E0.6ISOTM2F... | | .40 | 9 | |
| | | 0.7 | 2E0.7ISOTM2F... | | .36 | 7 | |
| | | 0.8 | 2E0.8ISOTM2F... | | .35 | 6 | |
| | | 0.9 | 2E0.9ISOTM2F... | | .39 | 6 | |
| 3/8" | .63 | 0.35 | 3E0.35ISOTM2F... | 3I0.35ISOTM2F... | .56 | 21 | TMC...-3 TMSH...-3 |
| | | 0.4 | 3E0.4ISOTM2F... | 3I0.4ISOTM2F... | .58 | 19 | |
| | | 0.45 | 3E0.45ISOTM2F... | 3I0.45ISOTM2F... | .58 | 17 | |
| | | 0.5 | 3E0.5ISOTM2F... | | .53 | 14 | |
| | | 0.6 | 3E0.6ISOTM2F... | | .54 | 12 | |
| | | 0.7 | 3E0.7ISOTM2F... | | .58 | 11 | |
| | | 0.8 | 3E0.8ISOTM2F... | | .54 | 9 | |
| | | 0.9 | 3E0.9ISOTM2F... | | .53 | 8 | |

NOTE: Two orbits are required to complete the thread. Fine Pitch TM Inserts produce partial profile thread.

Sample order: **6.0E0.35ISOTMF VBX**

All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm), which has one cutting edge.

For toolholder information, see page 278.



Fine Pitch Threads


Fine pitch threads are threads with small pitches. It is difficult to produce multitooth inserts for small pitches because of the small radius between the teeth. Vargus developed inserts where every second tooth was dropped to enlarge the radius between the teeth.

Important!


- All the fine pitch inserts are partial profile type (as a result of the enlarged radius).

American UN

External / Internal



Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Standard TM

Standard TM


| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|---------------|---------------|----------------|----------------|---------------|---------------|-----------------------|
| IC | L Inch | TPI | External | Internal | Inch | | |
| 6.0mm | .41 | 32 | | 6.0I32UNTM... | .38 | 12 | TMMC...-6.0 |
| | | 28 | | 6.0I28UNTM... | .36 | 10 | |
| | | 24 | | 6.0I24UNTM... | .38 | 9 | |
| | | 20 | | 6.0I20UNTM... | .35 | 7 | |
| | | 18 | | 6.0I18UNTM... | .33 | 6 | |
| | | 16 | | 6.0I16UNTM... | .31 | 5 | |
| 1/4" | .43 | 48 | | 2I48UNTM2... | .40 | 19 | TMC...-2 TMSH...-2 |
| | | 40 | | 2I40UNTM2... | .40 | 16 | |
| | | 32 | | 2I32UNTM2... | .41 | 13 | |
| | | 28 | 2E28UNTM2... | 2I28UNTM2... | .39 | 11 | |
| | | 27 | 2E27UNTM2... | 2I27UNTM2... | .41 | 11 | |
| | | 24 | 2E24UNTM2... | 2I24UNTM2... | .38 | 9 | |
| | | 20 | 2E20UNTM2... | 2I20UNTM2... | .40 | 8 | |
| | | 18 | 2E18UNTM2... | 2I18UNTM2... | .39 | 7 | |
| | | 16 | 2E16UNTM2... | 2I16UNTM2... | .38 | 6 | |
| 3/8" | .63 | 40 | | 3I40UNTM2... | .58 | 23 | TMC...-3 TMSH...-3 |
| | | 32 | | 3I32UNTM2... | .59 | 19 | |
| | | 28 | 3E28UNTM2... | 3I28UNTM2... | .57 | 16 | |
| | | 27 | 3E27UNTM2... | 3I27UNTM2... | .56 | 15 | |
| | | 26 | 3E26UNTM2... | 3I26UNTM2... | .58 | 15 | |
| | | 24 | 3E24UNTM2... | 3I24UNTM2... | .58 | 14 | |
| | | 20 | 3E20UNTM2... | 3I20UNTM2... | .55 | 11 | |
| | | 18 | 3E18UNTM2... | 3I18UNTM2... | .56 | 10 | |
| | | 16 | 3E16UNTM2... | 3I16UNTM2... | .56 | 9 | |
| | | 14 | 3E14UNTM2... | 3I14UNTM2... | .57 | 8 | |
| | | 13 | 3E13UNTM2... | 3I13UNTM2... | .54 | 6 | |
| | | 12 | 3E12UNTM2... | 3I12UNTM2... | .58 | 7 | |
| | | 11.5 | 3E11.5UNTM2... | 3I11.5UNTM2... | .52 | 6 | |
| | | 3/8"B | .87 | 24 | 3BE24UNTM2... | 3BI24UNTM2... | |
| 20 | 3BE20UNTM2... | | | 3BI20UNTM2... | .85 | 17 | |
| 18 | 3BE18UNTM2... | | | 3BI18UNTM2... | .83 | 15 | |
| 16 | 3BE16UNTM2... | | | 3BI16UNTM2... | .81 | 13 | |
| 14 | 3BE14UNTM2... | | | 3BI14UNTM2... | .86 | 12 | |
| 13 | 3BE13UNTM2... | | | 3BI13UNTM2... | .85 | 11 | |
| 12 | 3BE12UNTM2... | 3BI12UNTM2... | .83 | 10 | | | |

TM Standard


All inserts have 2 cutting edges, except Mini TM (IC 6.0 mm), which has one cutting edge.
For toolholder information, see page 278.

American UN (con't)

External / Internal



Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Standard TM

Standard TM


| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|-------------|----------------|----------------|------|-------|-----------------------|
| IC | L Inch | TPI | External | Internal | Inch | | |
| 5/8" | 1.06 | 24 | 5E24UNTM2... | 5I24UNTM2... | 1.00 | 24 | TMC..-5 TMSH..-5 |
| | | 20 | 5E20UNTM2... | 5I20UNTM2... | 1.00 | 20 | |
| | | 18 | 5E18UNTM2... | 5I18UNTM2... | 1.00 | 18 | |
| | | 16 | 5E16UNTM2... | 5I16UNTM2... | 1.00 | 16 | |
| | | 14 | 5E14UNTM2... | 5I14UNTM2... | 1.00 | 14 | |
| | | 13 | 5E13UNTM2... | 5I13UNTM2... | 1.00 | 13 | |
| | | 12 | 5E12UNTM2... | 5I12UNTM2... | 1.00 | 12 | |
| | | 11.5 | 5E11.5UNTM2... | 5I11.5UNTM2... | 0.96 | 11 | |
| | | 11 | 5E11UNTM2... | 5I11UNTM2... | 1.00 | 11 | |
| | | 10 | 5E10UNTM2... | | 0.90 | 9 | |
| | | 10 | | 5I10UNTM2... | 1.00 | 10 | |
| | | 9 | 5E9UNTM2... | 5I9UNTM2... | 0.89 | 8 | |
| | | 8 | 5E8UNTM2... | 5I8UNTM2... | 0.88 | 7 | |
| | | 7 | 5E7UNTM2... | | 0.86 | 6 | |
| | | 7 | | 5I7UNTM2... | 1.00 | 7 | |
| | | 6 | 5E6UNTM2... | | 0.83 | 5 | |
| 6 | | 5I6UNTM2... | 1.00 | 6 | | | |
| 3/4"B | 1.52 | 6 | 6BE6UNTM2... | 6BI6UNTM2... | 1.33 | 8 | TMC..-6B TMSH..-6B |
| | | 5 | 6BE5UNTM2... | 6BI5UNTM2... | 1.20 | 6 | |
| | | 4.5 | 6BE4.5UNTM2... | 6BI4.5UNTM2... | 1.33 | 6 | |
| | | 4 | 6BE4UNTM2... | 6BI4UNTM2... | 1.25 | 5 | |

TM Standard


All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm), which has one cutting edge. For toolholder information, see page 278.

American UN (con't)

Internal



Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Coarse Pitch TM


Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Bore Dia. Range | |
|-------------|-------------|--------|----------------------|--------------|-----|-------|---------------------|------------|
| | IC | L Inch | | | | | Inch | Inch |
| 7/16"-20UNF | 6.0mm | .41 | 6.0I20UNTM028/012... | 1 | .35 | 7 | TMMC050-6.0 | .38 - .45 |
| 7/16"-20UNF | | | 6.0I20UNTM028/012... | 1 | .35 | 7 | TMMC075-6.0 | .38 - .45 |
| 7/16"-16UN | | | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC050-6.0 | .37 - .56 |
| 7/16"-16UN | | | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC075-6.0 | .37 - .56 |
| 7/16"-14UNC | | | 6.0I14UNTM028/013... | 1 | .36 | 5 | TMMC075-6.0-124/203 | .36 - .39 |
| 1/2"-13UNC | 1/4" | .43 | 2I13UNTM028/015... | 1 | .38 | 5 | TMC075-2-124/205 | .41 - .77 |
| 1/2"-16UN | 6.0mm | .41 | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC050-6.0 | .37 - .56 |
| 1/2"-16UN | | | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC075-6.0 | .37 - .56 |
| 9/16"-12UNC | 1/4" | .43 | 2I12UNTM028/016... | 1 | .33 | 4 | TMC075-2-124/205 | .47 - .61 |
| 9/16"-18UNF | | | 2I18UNTM028/017... | 2 | .39 | 7 | TMC050-2 | .50 - .57 |
| 9/16"-18UNF | | | 2I18UNTM028/017... | 2 | .39 | 7 | TMC075-2 | .50 - .57 |
| 9/16"-16UN | 6.0mm | .41 | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC050-6.0 | .37 - .56 |
| 9/16"-16UN | | | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC075-6.0 | .37 - .56 |
| 5/8"-11UNC | 1/4" | .43 | 2I11UNTM028/018... | 1 | .36 | 4 | TMC075-2-124/206 | .52 - .73 |
| 5/8"-12UN | | | 2I12UNTM028/016... | 1 | .33 | 4 | TMC075-2-124/205 | .47 - .61 |
| 5/8"-16UN | 6.0mm | .41 | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC050-6.0 | .37 - .56 |
| 5/8"-16UN | | | 6.0I16UNTM028/014... | 1 | .31 | 5 | TMMC075-6.0 | .37 - .56 |
| 11/16"-12UN | 1/4" | .43 | 2I12UNTM028/016... | 1 | .33 | 4 | TMC075-2-124/205 | .47 - .61 |
| 3/4"-10UNC | 3/8" | .63 | 3I10UNTM028/019... | 1 | .50 | 5 | TMC0625-3-124/201 | .64 - 1.24 |
| 3/4"-12UN | | | 3I12UNTM028/020... | 2 | .58 | 7 | TMNC0625-3 | .66 - .72 |
| 13/16"-12UN | | | 3I12UNTM028/020... | 2 | .58 | 7 | TMC0625-3 | .72 - .77 |
| 7/8"-9UNC | 1/2" | .87 | 4I9UNTM028/021... | 1 | .67 | 6 | TMC100-4-124/202 | .75 - 1.28 |


TM Standard

American UN (con't)

Internal



Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Coarse Pitch TM

Coarse Pitch TM


| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder | Bore Dia. Range |
|--------------|-------------|--------|-------------------|--------------|------|-------|--------------------|-----------------|
| | IC | L Inch | | | | | | |
| 1"-8UNC | 1/2" | .87 | 4I8UNTM028/022... | 1 | .75 | 6 | TMC100 - 4 124/207 | .86 - 1.11 |
| 1 1/16"-8UN | | | 4I8UNTM028/022... | 1 | .75 | 6 | TMC100-4 124/207 | .86 - 1.11 |
| 1 1/8"-7UNC | | | 4I7UNTM028/023... | 1 | .71 | 5 | TMC100-4 124/202 | .97 - 1.41 |
| 1 1/8"-8UN | | | 4I8UNTM028/022... | 1 | .75 | 6 | TMC100-4 124/207 | .86 - 1.11 |
| 1 3/16"-8UN | | | 4I8UNTM028/022... | 1 | .75 | 6 | TMC100-4 124/207 | .86 - 1.11 |
| 1 1/4"-7UNC | | | 4I7UNTM028/023... | 1 | .71 | 5 | TMC100-4 124/202 | .97 - 1.41 |
| 1 1/4"-8UN | 5/8" | 1.06 | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 124/204 | 1.11 - 1.30 |
| 1 5/16"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 124/204 | 1.11 - 1.30 |
| 1 3/8"-6UNC | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 124/204 | 1.19 - 1.44 |
| 1 3/8"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 124/204 | 1.11 - 1.30 |
| 1 7/16"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 124/204 | 1.19 - 1.44 |
| 1 7/16"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 | 1.30 - 1.54 |
| 1 1/2"-6UNC | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 124/204 | 1.19 - 1.44 |
| 1 1/2"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 | 1.30 - 1.54 |
| 1 9/16"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 124/204 | 1.19 - 1.44 |
| 1 9/16"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 | 1.30 - 1.54 |
| 1 5/8"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |
| 1 5/8"-8UN | | | 5I8UNTM028/024... | 2 | .88 | 7 | TMC100-5 | 1.30 - 1.54 |
| 1 11/16"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |
| 1 3/4"-5UNC | | | 5I5UNTM028/077... | 2 | .80 | 4 | TMC100-5 | 1.53 - ∞ |
| 1 3/4"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |
| 1 13/16"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |
| 1 7/8"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |
| 1 15/16"-6UN | | | 5I6UNTM028/025... | 2 | 1.00 | 6 | TMC100-5 | 1.44 - 1.77 |

TM Standard


For toolholder information, see page 282.

American UN (con't)

External / Internal




Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Standard TM

Standard TM Inserts for TMO Toolholders

| Insert Size | | Pitch | Ordering Code | | | ECL |
|-------------|--------|-------|----------------|----------------|--------------|------|
| IC | L Inch | TPI | External | Internal | Toolholder | Inch |
| 1/4" | .43 | 48 | | 2I48UNTM2... | TMOC075-2-1 | .77 |
| | | 48 | | 2I48UNTM2... | TMOC075-2-2 | .73 |
| | | 48 | | 2I48UNTM2... | TMOC075-2-9 | .75 |
| | | 32 | | 2I32UNTM2... | TMOC075-2-1 | .78 |
| | | 28 | 2E28UNTM2... | 2I28UNTM2... | TMOC075-2-3 | .68 |
| | | 24 | 2E24UNTM2... | 2I24UNTM2... | TMOC075-2-2 | .71 |
| | | 20 | 2E20UNTM2... | 2I20UNTM2... | TMOC075-2-4 | .75 |
| | | 18 | 2E18UNTM2... | 2I18UNTM2... | TMOC075-2-2 | .72 |
| | | 16 | 2E16UNTM2... | 2I16UNTM2... | TMOC075-2-1 | .75 |
| | | 14 | 2E14UNTM2... | 2I14UNTM2... | TMOC075-2-3 | .64 |
| 3/8" | .63 | 32 | | 3I32UNTM2... | TMOC075-3-3 | 1.09 |
| | | 32 | | 3I32UNTM2... | TMOC075-3-11 | 1.13 |
| | | 28 | 3E28UNTM2... | 3I28UNTM2... | TMOC075-3-3 | 1.07 |
| | | 27 | 3E27UNTM2... | 3I27UNTM2... | TMOC075-3-4 | 1.07 |
| | | 24 | 3E24UNTM2... | 3I24UNTM2... | TMOC075-3-6 | 1.08 |
| | | 20 | 3E20UNTM2... | 3I20UNTM2... | TMOC075-3-6 | 1.05 |
| | | 18 | 3E18UNTM2... | 3I18UNTM2... | TMOC075-3-6 | 1.06 |
| | | 16 | 3E16UNTM2... | 3I16UNTM2... | TMOC075-3-6 | 1.06 |
| | | 14 | 3E14UNTM2... | 3I14UNTM2... | TMOC075-3-6 | 1.07 |
| | | 13 | 3E13UNTM2... | 3I13UNTM2... | TMOC075-3-2 | 1.00 |
| | | 12 | 3E12UNTM2... | 3I12UNTM2... | TMOC075-3-6 | 1.08 |
| | | 11.5 | 3E11.5UNTM2... | 3I11.5UNTM2... | TMOC075-3-5 | .96 |




ECL - The Effective Cutting Length


For Le and number of teeth of the above inserts, see the table for standard inserts on pages 254.
For toolholder information, see page 287.

American UN (con't)

External / Internal




Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Standard TM

Standard TM Inserts for TMO Toolholders

| Insert Size | | Pitch | Ordering Code | | | ECL |
|-------------|-------------|-------------------|----------------|----------------|--------------|------|
| IC | L Inch | TPI | External | Internal | Toolholder | Inch |
| 5/8" | 1.06 | 24 | 5E24UNTM2... | 5I24UNTM2... | TMOC100-5-1 | 2.00 |
| | | 24 | 5E24UNTM2... | 5I24UNTM2... | TMOC100-5-2 | 1.83 |
| | | 20 | 5E20UNTM2... | 5I20UNTM2... | TMOC100-5-1 | 2.00 |
| | | 18 | 5E18UNTM2... | 5I18UNTM2... | TMOC100-5-1 | 2.00 |
| | | 18 | 5E18UNTM2... | 5I18UNTM2... | TMOC100-5-2 | 1.83 |
| | | 16 | 5E16UNTM2... | 5I16UNTM2... | TMOC100-5-3 | 1.88 |
| | | 14 | 5E14UNTM2... | 5I14UNTM2... | TMOC100-5-1 | 2.00 |
| | | 14 | 5E14UNTM2... | 5I14UNTM2... | TMOC100-5-4 | 1.86 |
| | | 13 | 5E13UNTM2... | 5I13UNTM2... | TMOC100-5-1 | 2.00 |
| | | 12 | 5E12UNTM2... | 5I12UNTM2... | TMOC100-5-2 | 1.83 |
| | | 12 | 5E12UNTM2... | | TMOC100-5-1 | 2.00 |
| | | 11.5 | 5E11.5UNTM2... | 5I11.5UNTM2... | TMOC100-5-5 | 1.83 |
| | | 11 | 5E11UNTM2... | 5I11UNTM2... | TMOC100-5-6 | 1.91 |
| | | 11 | | 5I11UNTM2... | TMOC100-5-1 | 1.82 |
| | | 10 | 5E10UNTM2... | | TMOC100-5-7 | 1.70 |
| | | 10 | | 5I10UNTM2... | TMOC100-5-7 | 1.80 |
| | | 9 | 5E9UNTM2... | 5I9UNTM2... | TMOC100-5-8 | 1.78 |
| | | 8 | 5E8UNTM2... | 5I8UNTM2... | TMOC100-5-9 | 1.75 |
| | | 7 | 5E7UNTM2... | | TMOC100-5-10 | 1.71 |
| | | 7 | | 5I7UNTM2... | TMOC100-5-10 | 1.86 |
| 6 | 5E6UNTM2... | | TMOC100-5-2 | 1.67 | | |
| 6 | | 5I6UNTM2... | TMOC100-5-2 | 1.83 | | |
| 5 | | 5I5UNTM028/077... | TMOC100-5-7 | 1.60 | | |




ECL - The Effective Cutting Length


For Le and number of teeth of the above inserts, see the table for standard inserts on pages 254.
For toolholder information, see page 287.

American UN (con't)

External / Internal



Defined by: ANSI B1.1.74
Tolerance class: Class 2A/2B



Fine Pitch TM

Fine Pitch TM

| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|-------|----------------|----------------|------|-------|-----------------------|
| IC | L Inch | TPI | External | Internal | Inch | | |
| 6.0mm | .41 | 80 | 6.0E80UNTMF... | 6.0I80UNTMF... | .39 | 16 | TMMC...-6.0 |
| | | 72 | 6.0E72UNTMF... | 6.0I72UNTMF... | .38 | 14 | |
| | | 64 | 6.0E64UNTMF... | 6.0I64UNTMF... | .36 | 12 | |
| | | 56 | 6.0E56UNTMF... | 6.0I56UNTMF... | .38 | 11 | |
| | | 48 | 6.0E48UNTMF... | | .35 | 9 | |
| | | 44 | 6.0E44UNTMF... | | .34 | 8 | |
| | | 40 | 6.0E40UNTMF... | | .33 | 7 | |
| | | 36 | 6.0E36UNTMF... | | .36 | 7 | |
| 1/4" | .43 | 80 | 2E80UNTM2F... | 2I80UNTM2F... | .39 | 16 | TMC...-2 TMSH...-2 |
| | | 72 | 2E72UNTM2F... | 2I72UNTM2F... | .40 | 15 | |
| | | 64 | 2E64UNTM2F... | 2I64UNTM2F... | .39 | 13 | |
| | | 56 | 2E56UNTM2F... | 2I56UNTM2F... | .38 | 11 | |
| | | 48 | 2E48UNTM2F... | | .40 | 10 | |
| | | 44 | 2E44UNTM2F... | | .39 | 9 | |
| | | 40 | 2E40UNTM2F... | | .38 | 8 | |
| | | 36 | 2E36UNTM2F... | | .36 | 7 | |
| 3/8" | .63 | 80 | 3E80UNTM2F... | 3I80UNTM2F... | .56 | 23 | TMC...-3 TMSH...-3 |
| | | 72 | 3E72UNTM2F... | 3I72UNTM2F... | .57 | 21 | |
| | | 64 | 3E64UNTM2F... | 3I64UNTM2F... | .58 | 19 | |
| | | 56 | 3E56UNTM2F... | 3I56UNTM2F... | .55 | 16 | |
| | | 48 | 3E48UNTM2F... | | .56 | 14 | |
| | | 44 | 3E44UNTM2F... | | .57 | 13 | |
| | | 40 | 3E40UNTM2F... | | .58 | 12 | |
| | | 36 | 3E36UNTM2F... | | .58 | 11 | |
| | | 32 | 3E32UNTM2F... | | .53 | 9 | |

NOTE: Two orbits are required to complete the thread. Fine Pitch TM Inserts produce partial profile thread.

Sample order: **6.0E80UNTMF VBX**

All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm), which has one cutting edge.


For toolholder information, see page 278.

Fine Pitch Threads


Fine pitch threads are threads with small pitches. It is difficult to produce multitooth inserts for small pitches because of the small radius between the teeth. Vargus developed inserts where every second tooth was dropped to enlarge the radius between the teeth.

Important!


- All the fine pitch inserts are partial profile type (as a result of the enlarged radius).



External / Internal



Defined by: MIL-S-8879C
Tolerance class: 3A/3B



Standard TM

Standard TM



| Insert Size | | Pitch | Ordering Code | | Le | Teeth | Toolholder |
|-------------|--------|-------|---------------|----------------|------|-------|-----------------------|
| IC | L Inch | TPI | External | Internal | Inch | | |
| 6.0mm | .41 | 24 | | 6.0I24UNJTM... | .38 | 9 | TMMC...-6.0 |
| | | 20 | | 6.0I20UNJTM... | .35 | 7 | |
| | | 18 | | 6.0I18UNJTM... | .33 | 6 | |
| | | 16 | | 6.0I16UNJTM... | .31 | 5 | |
| 1/4" | .43 | 24 | 2E24UNJTM2... | 2I24UNJTM2... | .38 | 9 | TMC...-2 TMSH...-2 |
| | | 20 | 2E20UNJTM2... | 2I20UNJTM2... | .40 | 8 | |
| | | 18 | | 2I18UNJTM2... | .39 | 7 | |
| | | 16 | 2E16UNJTM2... | 2I16UNJTM2... | .38 | 6 | |
| | | 14 | 2E14UNJTM2... | 2I14UNJTM2... | .36 | 5 | |
| 3/8" | .63 | 24 | 3E24UNJTM2... | 3I24UNJTM2... | .58 | 14 | TMC...-3 TMSH...-3 |
| | | 20 | 3E20UNJTM2... | 3I20UNJTM2... | .55 | 11 | |
| | | 18 | 3E18UNJTM2... | 3I18UNJTM2... | .56 | 10 | |
| | | 16 | 3E16UNJTM2... | 3I16UNJTM2... | .56 | 9 | |
| | | 14 | 3E14UNJTM2... | 3I14UNJTM2... | .57 | 8 | |
| | | 13 | 3E13UNJTM2... | | .54 | 7 | |
| 5/8" | 1.06 | 12 | 3E12UNJTM2... | 3I12UNJTM2... | .58 | 7 | TMC...-5 TMSH...-5 |
| | | 16 | 5E16UNJTM2... | 5I16UNJTM2... | 1.00 | 16 | |
| | | 12 | 5E12UNJTM2... | 5I12UNJTM2... | 1.00 | 12 | |
| | | 11 | 5E11UNJTM2... | 5I11UNJTM2... | 1.00 | 11 | |

All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm), which has one cutting edge.
For toolholder information, see page 278.

TM Standard

Whitworth for BSW, BSP

External / Internal



BSW Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
 BSP Defined by: B.S.2779:1956
 Tolerance class: BSW-Medium class A, BSP-Medium class

Standard TM

Standard TM



| Insert Size | | Pitch | Ordering Code | Le | Teeth | Toolholder |
|-------------|--------|-------|---------------------|------|-------|-----------------------|
| IC | L Inch | TPI | External + Internal | Inch | | |
| 6.0mm | .41 | 28 | 6.0EI28WTM... | .36 | 10 | TMMC..-6.0 |
| | | 26 | 6.0EI26WTM... | .35 | 9 | |
| | | 24 | 6.0EI24WTM... | .38 | 9 | |
| | | 20 | 6.0EI20WTM... | .35 | 7 | |
| | | 19 | 6.0EI19WTM... | .37 | 7 | |
| 1/4" | .43 | 28 | 2EI28WTM2... | .39 | 11 | TMC..-2 TMSH..-2 |
| | | 26 | 2EI26WTM2... | .38 | 10 | |
| | | 24 | 2EI24WTM2... | .38 | 9 | |
| | | 20 | 2EI20WTM2... | .40 | 8 | |
| | | 19 | 2EI19WTM2... | .37 | 7 | |
| 3/8" | .63 | 14 | 2EI14WTM2... | .36 | 5 | TMC..-3 TMSH..-3 |
| | | 26 | 3EI26WTM2... | .58 | 15 | |
| | | 24 | 3EI24WTM2... | .58 | 14 | |
| | | 20 | 3EI20WTM2... | .55 | 11 | |
| | | 19 | 3EI19WTM2... | .58 | 11 | |
| | | 18 | 3EI18WTM2... | .56 | 10 | |
| | | 16 | 3EI16WTM2... | .56 | 9 | |
| | | 14 | 3EI14WTM2... | .57 | 8 | |
| 3/8"B | .87 | 12 | 3EI12WTM2... | .58 | 7 | TMC..-3B TMSH..-3B |
| | | 11 | 3EI11WTM2... | .55 | 6 | |
| | | 24 | 3BEI24WTM2... | .83 | 20 | |
| | | 20 | 3BEI20WTM2... | .85 | 17 | |
| | | 19 | 3BEI19WTM2... | .84 | 16 | |
| | | 18 | 3BEI18WTM2... | .83 | 15 | |
| | | 16 | 3BEI16WTM2... | .81 | 13 | |
| 5/8" | 1.06 | 14 | 3BEI14WTM2... | .86 | 12 | TMC..-5 TMSH..-5 |
| | | 12 | 3BEI12WTM2... | .83 | 10 | |
| | | 11 | 3BEI11WTM2... | .82 | 9 | |
| | | 16 | 5EI16WTM2... | 1.00 | 16 | |
| | | 14 | 5EI14WTM2... | 1.00 | 14 | |
| | | 12 | 5EI12WTM2... | .92 | 11 | |
| | | 11 | 5EI11WTM2... | .91 | 10 | |
| | | 10 | 5EI10WTM2... | 1.00 | 10 | |
| 3/4"B | 1.52 | 9 | 5EI9WTM2... | .89 | 8 | TMC..-6B TMSH..-6B |
| | | 8 | 5EI8WTM2... | .88 | 7 | |
| | | 7 | 5EI7WTM2... | .86 | 6 | |
| | | 6 | 5EI6WTM2... | .83 | 5 | |
| | | 11 | 6BEI11WTM2... | 1.36 | 15 | |
| 3/4" | 1.52 | 6 | 6BEI6WTM2... | 1.33 | 8 | TMC..-6B TMSH..-6B |
| | | 5 | 6BEI5WTM2... | 1.20 | 6 | |
| | | 4.5 | 6BEI4.5WTM2... | 1.33 | 6 | |

TM Standard

All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm) which has one cutting edge.
 For toolholder information, see page 278.

Whitworth for BSW only (con't)

Internal



Defined by: B.S.84:1956, DIN259, ISO228/1:1982
Tolerance class: Medium class A

Coarse Pitch TM


Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder | Bore Dia. Range |
|------------|-------------|--------|---------------------|--------------|------|-------|-------------------|-----------------|
| Inch | IC | L Inch | Internal | | Inch | | Inch | |
| 7/16"-18 | 6.0mm | .41 | 6.0118WTM028/035... | 1 | .33 | 6 | TMMC050-6.0 | .37 - .56 |
| 7/16"-18 | | | 6.0118WTM028/035... | 1 | .33 | 6 | TMMC075-6.0 | .37 - .56 |
| 7/16"-26 | | | 6.0126WTM028/036... | 1 | .35 | 9 | TMMC050-6.0 | .39 - .41 |
| 7/16"-26 | | | 6.0126WTM028/036... | 1 | .35 | 9 | TMMC075-6.0 | .39 - .41 |
| 1/2"-16 | 1/4" | .43 | 2116WTM028/051... | 1 | .38 | 6 | TMC075-2 124/205 | .42 - .48 |
| 1/2"-20 | 6.0mm | .41 | 6.0120WTM028/037... | 1 | .35 | 7 | TMMC050-6.0 | .43 - .45 |
| 1/2"-20 | | | 6.0120WTM028/037... | 1 | .35 | 7 | TMMC075-6.0 | .43 - .45 |
| 9/16"-16 | 1/4" | .43 | 2116WTM028/038... | 2 | .38 | 6 | TMC050-2 | .48 - .73 |
| 9/16"-16 | | | 2116WTM028/038... | 2 | .38 | 6 | TMC075-2 | .48 - .73 |
| 5/8"-14 | | | 2114WTM028/039... | 1 | .36 | 5 | TMC075-2 124/206 | .53 - .75 |
| 11/16"-14 | | | 2114WTM028/039... | 1 | .36 | 5 | TMC075-2 124/206 | .53 - .75 |
| 11/16"-16 | | | 2116WTM028/038... | 2 | .38 | 6 | TMC050-2 | .48 - .73 |
| 11/16"-16 | | | 2116WTM028/038... | 2 | .38 | 6 | TMC075-2 | .48 - .73 |
| 3/4"-12 | 3/8" | .63 | 3112WTM028/040... | 1 | .58 | 7 | TMC0625-3 124/201 | .64 - .70 |
| 3/4"-16 | 1/4" | .43 | 2116WTM028/038... | 2 | .38 | 6 | TMC050-2 | .48 - .73 |
| 3/4"-16 | | | 2116WTM028/038... | 2 | .38 | 6 | TMC075-2 | .48 - .73 |
| 13/16"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC0625-3 | .70 - .83 |
| 7/8"-9 | 1/2" | .87 | 419WTM028/042... | 1 | .67 | 6 | TMC100-4 124/202 | .73 - 1.28 |
| 7/8"-11 | | | 4111WTM028/043... | 1 | .73 | 8 | TMC100-4 124/202 | .76 - .87 |
| 15/16"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1"-8 | 1/2" | .87 | 418WTM028/044... | 1 | .63 | 5 | TMC100-4 124/202 | .84 - 1.02 |
| 1"-10 | | | 4110WTM028/045... | 1 | .70 | 7 | TMC100-4 124/202 | .87 - 1.24 |
| 1"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 1/16"-12 | | | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 1/8"-7 | 5/8" | 1.06 | 517WTM028/046... | 1 | .86 | 6 | TMC100-5 124/208 | .94 - 1.07 |
| 1 1/8"-9 | 1/2" | .87 | 419WTM028/042... | 1 | .67 | 6 | TMC100-4 124/202 | .73 - 1.28 |
| 1 1/8"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 3/16"-8 | 5/8" | 1.06 | 518WTM028/047... | 2 | .88 | 7 | TMC100-5 124/204 | 1.02 - 1.28 |
| 1 3/16"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 1/4"-7 | 5/8" | 1.06 | 517WTM028/048... | 2 | .86 | 6 | TMC100-5 124/204 | .85 - 1.41 |
| 1 1/4"-9 | 1/2" | .87 | 419WTM028/042... | 1 | .67 | 6 | TMC100-4 124/202 | .73 - 1.28 |
| 1 1/4"-12 | 3/8" | .63 | 3112WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 5/16"-6 | 5/8" | 1.06 | 516WTM028/049... | 2 | .83 | 5 | TMC100-5 124/204 | 1.10 - 1.28 |
| 1 5/16"-8 | | | 518WTM028/047... | 2 | .88 | 7 | TMC100-5 124/204 | 1.02 - 1.28 |


For toolholder information, see page 282.

Whitworth for BSW only (con't)

Internal



Defined by: B.S.84:1956, DIN259, ISO228/1:1982
Tolerance class: Medium class A



Coarse Pitch TM Inserts



Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder | Bore Dia. Range |
|------------|-------------|--------|-------------------|--------------|-----|-------|------------------|-----------------|
| | IC | L Inch | | | | | | |
| 1 5/16"-12 | 3/8" | .63 | 3I12WTM028/041... | 2 | .58 | 7 | TMC075-3 | .83 - 1.20 |
| 1 3/8"-8 | 5/8" | 1.06 | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5-124/204 | 1.02 - 1.28 |
| 1 3/8"-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5-124/204 | 1.10 - 1.28 |
| 1 3/8"-12 | | | 5I12WTM028/050... | 2 | .92 | 11 | TMC100-5 | 1.27 - 1.36 |
| 1.4-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5-124/204 | 1.10 - 1.28 |
| 1.4-8 | | | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5-124/204 | 1.02 - 1.28 |
| 1.4-12 | | | 5I12WTM028/050... | 2 | .92 | 11 | TMC100-5 | 1.27 - 1.36 |
| 1 7/16"-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5-124/204 | 1.10 - 1.28 |
| 1 7/16"-8 | | | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5 | 1.28 - 1.54 |
| 1 7/16"-12 | | | 5I12WTM028/050... | 2 | .92 | 11 | TMC100-5 | 1.27 - 1.36 |
| 1 1/2"-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5-124/204 | 1.10 - 1.29 |
| 1 1/2"-8 | | | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5 | 1.28 - 1.54 |
| 1.6-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5 | 1.28 - 1.52 |
| 1.6-8 | | | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5 | 1.28 - 1.54 |
| 1 5/8"-8 | | | 5I8WTM028/047... | 2 | .88 | 7 | TMC100-5 | 1.28 - 1.54 |
| 1 5/8"-6 | | | 5I6WTM028/049... | 2 | .83 | 5 | TMC100-5 | 1.28 - 1.52 |
| 1 3/4"-7 | | | 5I7WTM028/048... | 2 | .86 | 6 | TMC100-5 | 1.57 - 1.65 |
| 1 7/8"-6 | | | 5I6 WTM028/049... | 2 | .83 | 5 | TMC125-5 | 1.66 - 1.77 |
| 1.9-6 | | | 5I6 WTM028/049... | 2 | .83 | 5 | TMC125-5 | 1.66 - 1.77 |

For toolholder information, see page 282.

Whitworth for BSW only (con't)

External / Internal




Defined by: B.S.84:1956, DIN259, ISO228/1:1982
Tolerance class: Medium class A

Standard TM

Standard TM Inserts for TMO Toolholders


| Insert Size | | Pitch | Ordering Code | | ECL |
|-------------|--------|-------|---------------------|--------------|------|
| IC | L Inch | TPI | External + Internal | Toolholder | Inch |
| 1/4" | .43 | 28 | 2EI28WTM2... | TMOC075-2-3 | .68 |
| | | 26 | 2EI26WTM2... | TMOC075-2-5 | .73 |
| | | 24 | 2EI24WTM2... | TMOC075-2-2 | .71 |
| | | 20 | 2EI20WTM2... | TMOC075-2-6 | .75 |
| | | 19 | 2EI19WTM2... | TMOC075-2-7 | .68 |
| | | 14 | 2EI14WTM2... | TMOC075-2-3 | .64 |
| 3/8" | .63 | 26 | 3EI26WTM2... | TMOC075-3-2 | 1.08 |
| | | 26 | 3EI26WTM2... | TMOC075-3-6 | 1.04 |
| | | 24 | 3EI24WTM2... | TMOC075-3-7 | 1.12 |
| | | 20 | 3EI20WTM2... | TMOC075-3-6 | 1.05 |
| | | 19 | 3EI19WTM2... | TMOC075-3-8 | 1.11 |
| | | 18 | 3EI18WTM2... | TMOC075-3-6 | 1.06 |
| | | 16 | 3EI16WTM2... | TMOC075-3-6 | 1.06 |
| | | 14 | 3EI14WTM2... | TMOC075-3-6 | 1.07 |
| | | 12 | 3EI12WTM2... | TMOC075-3-6 | 1.08 |
| 5/8" | 1.06 | 11 | 3EI11WTM2... | TMOC075-3-9 | 1.09 |
| | | 16 | 5EI16WTM2... | TMOC100-5-3 | 1.88 |
| | | 14 | 5EI14WTM2... | TMOC100-5-1 | 2.00 |
| | | 14 | 5EI14WTM2... | TMOC100-5-4 | 1.86 |
| | | 12 | 5EI12WTM2... | TMOC100-5-2 | 1.75 |
| | | 11 | 5EI11WTM2... | TMOC100-5-6 | 1.82 |
| | | 10 | 5EI10WTM2... | TMOC100-5-7 | 1.8 |
| | | 9 | 5EI9WTM2... | TMOC100-5-8 | 1.78 |
| | | 8 | 5EI8WTM2... | TMOC100-5-9 | 1.75 |
| | | 7 | 5EI7WTM2... | TMOC100-5-4 | 1.71 |
| | | 6 | 5EI6WTM2... | TMOC100-5-11 | 1.67 |




For Le and number of teeth of the above inserts, see the table for standard inserts on page 254.
For toolholder information see page 278.

NPT

External / Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Standard TM

Standard TM


| Insert Size | | Pitch | Ordering Code | Le | Teeth | Toolholder | |
|-------------|--------|-------|----------------------|------|-------|-------------|---------------|
| IC | L Inch | TPI | External + Internal | Inch | | RH | LH |
| 3/8" | .63 | 18 | 3E18NPT-TM2... * | .56 | 10 | TMNC...-3 | TMNC...-3LH |
| | | 14 | 3E14NPT-TM2... | .57 | 8 | | |
| | | 11.5 | 3E11.5NPT-TM2... | .52 | 6 | | |
| 3/8"B | .87 | 14 | 3BE14NPT-TM2... | .86 | 12 | BTMNC...-3B | BTMNC...-3BLH |
| | | 11.5 | 3BE11.5NPT-TM2... ** | .78 | 9 | | |
| 5/8" | 1.06 | 11.5 | 5E11.5NPT-TM2... | .96 | 11 | TM.C...-5 | TM.C...-5LH |
| | | 8 | 5E18NPT-TM2... | .88 | 7 | | |
| 3/4"B | 1.52 | 11.5 | 6BE11.5NPT-TM2... | 1.39 | 16 | TMC...-6B | TMC...-6BLH |
| | | 8 | 6BE18NPT-TM2... | 1.25 | 10 | | |

* For external thread only.
To thread with insert cutting edge marked "L", use LH toolholders.
For toolholder information, see page 284.


** Single sided insert - RH only.

NPT

Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Coarse Pitch TM


Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder |
|---------|-------------|--------|----------------------|--------------|------|-------|-------------------|
| Inch | IC | L Inch | Internal | | Inch | | |
| 1/4"-18 | 1/4" | .43 | 2I18NPT-TM028/074... | 1 | .39 | 7 | TMC0752-2-124/209 |
| 3/8"-18 | | | 2I18NPT-TM028/074... | 1 | .39 | 7 | TMC0752-2-124/209 |


For toolholder information, see page 284.

NPTF (Dry Seal)

External / Internal



Defined by: ANSI 1.20.3-1976
Tolerance class: Standard NPTF



Standard TM

Standard TM


| Insert Size | | Pitch | Ordering Code | Le | Teeth | Toolholder | |
|-------------|--------|-------|---------------------|------|-------|------------|--------------|
| IC | L Inch | TPI | External + Internal | Inch | | RH | LH |
| 3/8" | .63 | 14 | 3EI14NPTFTM2... | .57 | 8 | TMNC..-3 | TMNC..-3LH |
| | | 11.5 | 3EI11.5NPTFTM2... | .52 | 6 | | |
| 3/8"B | .87 | 14 | 3BEI14NPTFTM2... | .86 | 12 | BTMNC..-3B | BTMNC..-3BLH |
| | | 11.5 | 3BEI11.5NPTFTM2... | .78 | 9 | | |
| 5/8" | 1.06 | 11.5 | 5EI11.5NPTFTM2... | .96 | 11 | TM.C..-5 | TM.C..-5LH |
| | | 8 | 5EI8NPTFTM2... | .88 | 7 | | |
| 3/4"B | 1.52 | 11.5 | 6BEI11.5NPTFTM2... | 1.39 | 16 | TMC..-6B | TMC..-6BLH |
| | | 8 | 6BEI8NPTFTM2... | 1.25 | 10 | | |

To thread with insert cutting edge marked "L", use LH toolholders.
For toolholder information, see page 284.


TM Standard

NPTF (Dry Seal)

Internal



Defined by: ANSI 1.20.3-1976
Tolerance class: Standard NPTF



Coarse Pitch TM


Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder |
|---------|-------------|--------|----------------------|--------------|------|-------|------------------|
| Inch | IC | L Inch | Internal | | Inch | | |
| 1/4"-18 | 1/4" | .43 | 2I18NPTFTM028/078... | 1 | .39 | 7 | TMC075-2-124/209 |
| 3/8"-18 | | | 2I18NPTFTM028/078... | 1 | .39 | 7 | TMC075-2-124/209 |


For toolholder information, see page 284.

NPS

External / Internal



Defined by: USA NBS H28 (1957)
Tolerance class: Standard NPS



Standard TM


Standard TM

| Insert Size | | Pitch | Ordering Code | Le | Teeth | Nominal Thread Size | |
|-------------|--------|-------|---------------------|------|-------|---------------------|-------------|
| IC | L Inch | TPI | External + Internal | Inch | | | Toolholder |
| 3/8" | .63 | 14 | 3EI14NPSTM2... | .57 | 8 | 1/2" | TMNC0625-3 |
| | | 14 | 3EI14NPSTM2... | .57 | 8 | 3/4" | TMNC075-3 |
| | | 11.5 | 3EI11.5NPSTM2... | .52 | 6 | 1", 1 1/4" | TMNC075-3 |
| 3/8"B | .87 | 11.5 | 3BEI11.5NPSTM2...* | .78 | 9 | 1", 1 1/4" | BTMNC075-3B |
| 5/8" | 1.06 | 11.5 | 5EI11.5NPSTM2... | .96 | 11 | 1 1/2", 2" | TMC100-5 |
| | | 8 | 5EI8NPSTM2... | .88 | 7 | 2 1/2" & larger | TMC125-5 |


* One cutting edge.
All inserts have 2 cutting edges.
For toolholder information, see page 278.

BSPT

External / Internal



Defined by: B.S. 21:1985
Tolerance class: Standard BSPT



Standard TM


Standard TM

| Insert Size | | Pitch | Ordering Code | Le | Teeth | Toolholder | |
|-------------|--------|-------|---------------------|------|-------|------------|------------|
| IC | L Inch | TPI | External + Internal | Inch | | RH | LH |
| 1/4" | .43 | 19 | 2EI19BSPT-TM2... | .37 | 7 | TMC..-2 | TMC..-2LH |
| 3/8" | .63 | 14 | 3EI14BSPT-TM2... | .57 | 8 | TMNC..-3 | TMNC..-3LH |
| | | 11 | 3EI11BSPT-TM2... | .55 | 6 | | |
| 5/8" | 1.06 | 11 | 5EI11BSPT-TM2... | .91 | 10 | TMC..-5 | TMC..-5LH |



To thread with insert cutting edge marked "L", use a LH toolholder.
For toolholder information, see page 284.

Pg

External / Internal



Defined by: DIN 40430
Tolerance class: Standard



Standard TM


Standard TM

| Insert Size | | Pitch | Ordering Code | Le | Teeth | Nominal Thread Size | Toolholder |
|-------------|--------|-------|---------------------|------|-------|------------------------------|-------------------|
| IC | L Inch | TPI | External + Internal | Inch | | | |
| 6.0mm | .41 | 20 | 6.0EI20PGTM... | .35 | 7 | Pg7 | TMMC..-6.0 |
| | | 20 | 2EI20PGTM2... | .40 | 8 | Pg7 | |
| 1/4" | .43 | 18 | 2EI18PGTM2... | .39 | 7 | Pg9, Pg11, Pg13.5, Pg16 | TMC..-2 |
| | | 16 | 2EI16PGTM2... | .38 | 6 | Pg21, Pg29, Pg36, Pg42, Pg48 | TMSH..-2 |
| 3/8" | .63 | 20 | 3EI20PGTM2... | .55 | 11 | Pg7 | TMC..-3 |
| | | 18 | 3EI18PGTM2... | .56 | 10 | Pg9, Pg11, Pg13.5, Pg16 | TMSH..-3 |
| 5/8" | 1.06 | 16 | 3EI16PGTM2... | .56 | 9 | Pg21, Pg29, Pg36, Pg42, Pg48 | |
| | | 16 | 5EI16PGTM2... | 1.00 | 16 | Pg21, Pg29, Pg36, Pg42, Pg48 | TMC..-5, TMSH..-5 |



All inserts have 2 cutting edges, except MiniTM (IC 6.0 mm) which has one edge.
For toolholder information, see page 278.

ACME

Internal



Defined by: ANSI B1/5:1988
Tolerance class: 3G



Coarse Pitch TM


Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Bore Dia. Range | |
|-----------|-------------|--------|------------------------|--------------|----------------------|-------|------------------|-------------|
| Inch | IC | L Inch | Internal | | Inch | | Toolholder | Inch |
| 1/2"-16 | 6.0mm | .41 | 6.0116ACMETM028/052... | 1 | .31 | 5 | TMMC050-6.0 | .44 |
| 1/2"-16 | | | 6.0116ACMETM028/052... | 1 | .31 | 5 | TMMC075-6.0 | .44 |
| 5/8"-16 | 1/4" | .43 | 2116ACMETM028/053... | 2 | .38 | 6 | TMC050-2 | .56 |
| 5/8"-16 | | | 2116ACMETM028/053... | 2 | .38 | 6 | TMC075-2 | .56 |
| 5/8"-14 | | | 2114ACMETM028/054... | 1 | .36 | 5 | TMC075-2-124/205 | .55 |
| 3/4"-16 | | | 2116ACMETM028/055... | 2 | .38 | 6 | TMC050-2 | .69 |
| 3/4"-16 | | | 2116ACMETM028/055... | 2 | .38 | 6 | TMC075-2 | .69 |
| 3/4"-14 | | | 2114ACMETM028/083... | 1 | .36 | 5 | TMC075-2-124/206 | .68 |
| 3/4"-14 | | | 2112ACMETM028/056... | 1 | .33 | 4 | TMC075-2-124/206 | .67 |
| 7/8"-14 | | | 3/8" | .63 | 3114ACMETM028/057... | 2 | .57 | 8 |
| 7/8"-12 | 1/4" | .43 | 2112ACMETM028/058... | 1 | .33 | 4 | TMC075-2-124/206 | .79 |
| 1"-14 | 3/8" | .63 | 3114ACMETM028/059... | 2 | .57 | 8 | TMC0625-3 | .93 |
| 1"-12 | | | 3112ACMETM028/060... | 2 | .58 | 7 | TMNC0625-3 | .91 |
| 1"-10 | 1/2" | .87 | 4110ACMETM028/061... | 1 | .70 | 7 | TMC100-4-124/202 | .90 |
| 1"-8 | | | 418ACMETM028/062... | 1 | .75 | 6 | TMC100-4-124/202 | .87 |
| 1 1/8"-12 | 3/8" | .63 | 3112ACMETM028/060... | 2 | .58 | 7 | TMC0625-3 | 1.04 |
| 1 1/8"-10 | 1/2" | .87 | 4110ACMETM028/084... | 1 | .70 | 7 | TMC100-4-124/207 | 1.02 |
| 1 1/8"-8 | | | 418ACMETM028/063... | 1 | .75 | 6 | TMC100-4-124/202 | 1.00 - 1.12 |
| 1 1/4"-12 | 3/8" | .63 | 3112ACMETM028/060... | 2 | .58 | 7 | TMC075-3 | 1.17 |
| 1 1/4"-10 | 5/8" | 1.06 | 5110ACMETM028/064... | 2 | .90 | 9 | TMC100-5-124/204 | 1.15 |
| 1 1/4"-8 | 1/2" | .87 | 418ACMETM028/063... | 1 | .75 | 6 | TMC100-4-124/202 | 1.00 - 1.12 |
| 1 3/8"-10 | 5/8" | 1.06 | 5110ACMETM028/065... | 2 | .90 | 9 | TMC100-5-124/204 | 1.27 |
| 1 3/8"-8 | | | 518ACMETM028/066... | 2 | .88 | 7 | TMC100-5-124/204 | 1.25 |
| 1 3/8"-6 | | | 516ACMETM028/067... | 1 | .83 | 5 | TMC100-5-124/208 | 1.20 |
| 1 1/2"-10 | | | 5110ACMETM028/068... | 2 | .90 | 9 | TMC100-5 | 1.40 |
| 1 1/2"-8 | | | 518ACMETM028/069... | 2 | .88 | 7 | TMC100-5-124/204 | 1.37 |
| 1 1/2"-6 | | | 516ACMETM028/070... | 2 | .83 | 5 | TMC100-5-124/204 | 1.33 |
| 1 3/4"-10 | | | 5110ACMETM028/064... | 2 | .90 | 9 | TMC125-5 | 1.65 |
| 1 3/4"-8 | | | 518ACMETM028/069... | 2 | .88 | 7 | TMC100-5 | 1.62 |
| 1 3/4"-6 | | | 516ACMETM028/070... | 2 | .83 | 5 | TMC100-5 | 1.58 |
| 1 3/4"-5 | | | 515ACMETM028/071... | 2 | .80 | 4 | TMC100-5-124/204 | 1.55 |
| 2"-8 | | | 518ACMETM028/069... | 2 | .88 | 7 | TMC125-5 | 1.87 |
| 2"-6 | | | 516ACMETM028/072... | 2 | .83 | 5 | TMC100-5 | 1.83 |
| 2"-5 | | | 515ACMETM028/071... | 2 | .80 | 4 | TMC100-5 | 1.80 |
| 2 1/4"-6 | | | 516ACMETM028/072... | 2 | .83 | 5 | TMC125-5 | 2.08 |
| 2 1/4"-5 | | | 515ACMETM028/073... | 2 | .80 | 4 | TMC100-5 | 2.05 |
| 2 1/2"-5 | | | 515ACMETM028/073... | 2 | .80 | 4 | TMC125-5 | 2.30 |


For toolholder information, see page 282.


Trapez

Internal



Defined by: Trapez DIN 103
Tolerance class: 7e/7H





Coarse Pitch TM



Coarse Pitch TM

| Thread | Insert Size | | Ordering Code | Cutting Edge | Le | Teeth | Toolholder | Bore Dia. Range |
|------------|---------------------|--------|---------------------|--------------|----------|-------------|------------------|-----------------|
| mm | IC | L Inch | Internal | | Inch | | | Inch |
| TR 16X2.0 | 1/4" | .43 | 2I2.0TRTM028/028... | 1 | .39 | 5 | TMC075-2-124/206 | .55 |
| TR 18X2.0 | | | 2I2.0TRTM028/029... | 1 | .39 | 5 | TMC075-2-124/206 | .63 - .71 |
| TR 20X2.0 | | | 2I2.0TRTM028/029... | 1 | .39 | 5 | TMC075-2-124/206 | .63 - .71 |
| TR 24X3.0 | 1/2" | .87 | 4I3.0TRTM028/030... | 1 | .71 | 6 | TMC100-4-124/202 | .83 |
| TR 26X3.0 | | | 4I3.0TRTM028/031... | 1 | .71 | 6 | TMC100-4-124/202 | .91 - 1.06 |
| TR 28X3.0 | | | 4I3.0TRTM028/031... | 1 | .71 | 6 | TMC100-4-124/202 | .91 - 1.06 |
| TR 30X3.0 | | | 4I3.0TRTM028/031... | 1 | .71 | 6 | TMC100-4-124/202 | .91 - 1.06 |
| TR 32X3.0 | | | 4I3.0TRTM028/032... | 1 | .71 | 6 | TMC100-4-124/207 | 1.14 - 1.30 |
| TR 34X3.0 | | | 4I3.0TRTM028/032... | 1 | .71 | 6 | TMC100-4-124/207 | 1.14 - 1.30 |
| TR 36X3.0 | 5/8" | 1.06 | 4I3.0TRTM028/032... | 1 | .71 | 6 | TMC100-4-124/207 | 1.14 - 1.30 |
| TR 38X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5-124/204 | 1.38 - 1.54 |
| TR 40X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5-124/204 | 1.38 - 1.54 |
| TR 42X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5-124/204 | 1.38 - 1.54 |
| TR 44X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5 | 1.61 - 1.77 |
| TR 46X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5 | 1.61 - 1.77 |
| TR 48X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC100-5 | 1.61 - 1.77 |
| TR 50X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC125-5 | 1.85 - 2.24 |
| TR 52X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC125-5 | 1.85 - 2.24 |
| TR 55X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC125-5 | 1.85 - 2.24 |
| TR 60X3.0 | | | 5I3.0TRTM028/033... | 2 | .94 | 8 | TMC125-5 | 1.85 - 2.24 |
| TR 65X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 70X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 75X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 80X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 85X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 90X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 95X4.0 | | | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 |
| TR 100X4.0 | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 | | |
| TR 105X4.0 | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 | | |
| TR 110X4.0 | 5I4.0TRTM028/034... | 2 | .94 | 6 | TMC125-5 | 2.40 - 4.17 | | |

TM Standard

For toolholder information, see page 282.

External and Internal Toolholders



TM Standard

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | |  |  |
|-------------|---------------|---------|-----------------|------|------|------|------|---|---|
| IC | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key |
| 6.0mm | TMMC050-6.0 | 67635 | 2.72 | .57 | .50 | .27 | .35 | SN7T | K7T |
| | TMMC075-6.0 | 67636 | 3.50 | .67 | .75 | .27 | .35 | | |
| 1/4" | TMC050-2 | 67612 | 2.75 | .47 | .50 | .35 | .45 | SN2TM | K2T |
| | TMC075-2 | 67614 | 3.50 | .79 | .75 | .35 | .45 | | |
| | TMC075-2LH | 66712 | 3.50 | .79 | .75 | .35 | .45 | | |
| 3/8" | TMC0625-3 | 67613 | 3.56 | .87 | .625 | .54 | .67 | SN3TM | K3T |
| | TMC075-3 | 67615 | 3.75 | 1.69 | .75 | .65 | .79 | | |
| 3/8"B | BTMC0625-3B | 67600 | 3.15 | 1.14 | .625 | .53 | .67 | SN3T | K3T |
| | BTMC075-3B | 67601 | 3.27 | 1.14 | .75 | .61 | .75 | | |
| | BTMC100-3B | 67602 | 3.68 | 1.18 | 1.00 | .61 | .75 | | |
| | BTMWC100-3B | 67609 | 3.62 | 1.18 | 1.00 | .73 | .87 | | |
| 5/8" | TMC100-5 | 67616 | 4.38 | 2.05 | 1.00 | .94 | 1.18 | SN5TM | K5T |
| | TMC100-5LH | 67617 | 4.38 | 2.05 | 1.00 | .94 | 1.18 | | |
| | TMC125-5 | 67618 | 4.75 | 2.28 | 1.25 | 1.22 | 1.46 | | |
| 3/4"B | TMC125-6B | 67619 | 4.45 | 2.16 | 1.25 | 1.06 | 1.38 | SM7T | K30T |
| | TMC150-6B | 67708 | 5.25 | 2.56 | 1.50 | 1.50 | 1.81 | | |

TM Standard



Internal Thread Application for Standard Toolholder

| Toolholder | | Min. Thread Dia. | | | | |
|------------------------------------|------|------------------|---|-------------------|---|---|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ |
| TMMC050-6.0 TMMC075-6.0 | .35 | | M10x0.75; M12x1.0; M14x1.25; M14x1.5 | | 7/16-32UN; 7/16-28UNEF; 1/2-24UNS; 7/16-20UNF; 9/16-18UNF; 9/16-16UNF | 9/16-24UNJEF; 1/2-20UNJF; 9/16- 18UNJF; 9/16-16UNJF |
| TMC050-2 TMC075-2 TMC075-2LH | .45 | | M15x1.0; M16x1.5 | | 9/16-32UN; 9/16-28UN; 9/16-24UNEF; 5/8-20UN; 9/16-18UNF; 9/16-16UNF; 7/8-14UNF | 9/16-24UNJEF; 3/4-20UNJEF; 5/8- 18UNJF; 5/8-16UNJF; 7/8-14UNJF |
| TMC0625-3 | .67 | | M20x1.0; M22x1.5; M24x2.0 | | 3/4-32UN; 13/16-28UN; 7/8-24UNS; 7/8-20UNEF; 7/8-18UNS 7/8-16UNS; 1-14UNS; 1 1/16-12UN | 15/8-24UNJ; 7/8-20UNJEF; 1 1/16-18UNJEF; 7/8-16UNJ; 1 5/8-14UNJ; 1 1/16-12UNJ |
| TMC075-3 | .79 | | M24x1.0; M25x1.5; M27x2.0 | | 7/8-32UN; 15/16-28UN; 1-24UNS; 15/16-20UNEF; 1-18UNS; 1-16 UNS; 1 1/8-14UNS; 1 1/16-12UN | 1 5/8-24 UNJ; 15/16-20UNJEF; 1 1/16-18UNJEF; 1-16UNJ; 1 5/8-14UNJ; 1 1/16-12UNJ |
| BTMC0625-3B | .67 | | M20x1.0; M22x1.5; M24x2.0 | | 7/8-24UNS; 7/8-20UNEF; 7/8-18UNS; 7/8-16UNS; 1-14UNS; 1 1/16-12UN | |
| BTMC075-3B BTMC100-3B | .75 | | M22x1.0; M24x1.5; M25x2.0 | | 7/8-24UNS; 15/16-20UNEF; 1-18UNS; 1-16UNS; 1-14UNS; 1-12UNF | |
| BTMWC100-3B | .87 | M27x1.5 | M25x1.0; M30x2 | | 1-24UNS; 1 1/16-20UN; 1 1/16-18UNEF; 1 1/16-16UNEF; 1 1/8-14UNS; 1 1/8-12UNF | |
| TMC100-5 TMC100-5LH | 1.18 | | M35x1.5; M39x2.0; M36x3.0; M36x4.0; M42x4.5; M48x5.0 | 1 3/4-5 | 1 3/8-24UNS; 1 3/8-20UN; 1 7/16-18UNEF; 1 7/16-16UNEF; 1 1/2-14UNS; 1 1/2-12UNF; 1 5/8-10UNS; 1 7/16-8UN; 1 5/8-6UN | 1 7/16-16UNJ; 1 1/2-12UNJF |
| TMC125-5 | 1.46 | | M45x1.5; M45x2.0; M50x3.0; M56x4.0 | | 1 5/8-24UNS; 1 11/16-20UN; 1 11/16-18UNEF; 1 11/16-16UNEF; 1 3/4-14UNS; 1 3/4-12 UN; 1 7/8-10UNS; 2-8 UN; 2 1/4-6UN | 1 11/16-16UNJ; 1 3/4-12UNJ |
| TMC125-6B | 1.38 | M64x6.0 | M42x1.5; M42x2.0; M48x3.0; M55x4.0; M48x5.0; M56x5.5 | 2-4.5; 2 1/2-4 | 2 1/4-6UN | |
| TMC150-6B | 1.81 | M64x6.0 | M52x1.5; M55x2.0; M60x3.0; M60x4.0; M60x5.5 | 2 1/2-4 | 2 3/8-6UN | |

| | D2 | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS | Trapez | ACME |
|------------------------------------|------|---|---------------------|----------|------------|------------|-----------------|------------------------|-----------------------|------------------------------------|
| TMMC050-6.0 TMMC075-6.0 | .35 | 7/16-26BSF; 1/2-20BSW; 7/16-18BSF; | 1/4-19 | | | | PG7 | | | 1/2-16 |
| TMC050-2 TMC075-2 TMC075-2LH | .45 | 5/8-26BSF; 5/8-20BSW; 9/16-16BSF; 1 1/16-14BSF | 3/8-19; 1/2-14 | 3/8-19 | | | PG9; PG21 | | | 5/8-16; |
| TMC0625-3 | .67 | 13/16-26BSF; 7/8-20BSW; 7/8-16BSW; 13/16-12BSW | 5/8-14; 1 1/4-11 | | | | PG13.5; PG21 | 1/2-14; 1-11.5 | | 1-14; 1 1/8-12 |
| TMC075-3 | .79 | 15/16-26BSF; 1-20BSW; 1 11/16-16BSW; 15/16-12BSW; | 3/4-14; 1-11 | | | | PG16; PG21 | 3/4-14; 1-11.5 | | 1 1/4-12 |
| BTMC0625-3B | .67 | 7/8-20BSW; 7/8-16BSW; 13/16-12BSW | 5/8-14; 1-11 | | | | | 1-11.5 | | |
| BTMC075-3B BTMC100-3B | .75 | 15/16-20BSW; 1-16BSW; 1 1/16-12BSW | 3/4-14; 1-11 | | | | | 1-11.5 | | |
| BTMWC100-3B | .87 | 1 1/16-20BSW; 1 1/8-16BSW | 7/8-14; 1-11 | | | | | 1-11.5 | | |
| TMC100-5 TMC100-5LH | 1.18 | 1.4-16BSW; 1 3/8-12BSW; 1 7/16-8BSW; 1 3/4-7BSF; 1.6-6BSW | 1 1/8-11 | 1 1/4-11 | 1 1/4-11.5 | 1 1/4-11.5 | PG29 | 1 1/4-11.5; 2 1/2-8 | TR44-3.0 | 1 1/2-10; 1 3/4-8; 1 3/4-6; 2-5 |
| TMC125-5 | 1.46 | 1 3/4-16BSW; 1 7/8-12BSW; 2.1-8BSW; 1 7/8-6BSW; | 1 1/2-11 | 1 1/2-11 | 1 1/2-11.5 | 1 1/2-11.5 | PG36 | 1 1/2-11.5; 2 1/2-8 | TR50-3.0; TR65-4.0 | 1 3/4-10; 2-8; 2 1/4-6; 2 1/2-5 |
| TMC125-6B | 1.38 | 2 1/4-6 BSF; 3-5BSF; 3 1/2-4.5BSF; | 1 1/2-11 | | 2 1/2-8 | 2 1/2-8 | | | | |
| TMC150-6B | 1.81 | 2 5/8-6BSW; 3-5BSF; 3 1/2-4.5BSF | 2-11 | | 3-8 | 3-8 | | | | |

TM Standard

External and Internal Toolholders



TML Long Tools

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | |
|-------------|---------------|---------|-----------------|------|------|------|------|--------------|----------|
| | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key |
| 1/4" | TMLC100-2 | 67719 | 4.95 | .67 | 1.00 | .35 | .45 | SN2TM | K2T |
| 3/8" | TMLC100-3 | 67624 | 5.00 | .98 | 1.00 | .73 | .87 | | |
| 3/8"B | BTMLC100-3 | 67737 | 4.95 | 2.50 | 1.00 | .73 | .87 | SN3T | K3T |
| | BTMLC075-3B | 67603 | 3.86 | 1.73 | .75 | .61 | .75 | | |
| 5/8" | TMLC100-5 | 67625 | 5.88 | 3.62 | 1.00 | .94 | 1.18 | SN5TM | K5T |
| | TMLC125-5 | 67628 | 6.33 | 3.86 | 1.25 | 1.22 | 1.46 | | |
| 3/4"B | TMLC150-6B | 67720 | 6.55 | 3.74 | 1.50 | 1.50 | 1.81 | SM7T | K30T |




Internal Thread Application for TML Toolholder

| Toolholder | Min. Thread Dia. | | | | | |
|-------------------------|------------------|------------|---|---------|---|--|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ |
| TMLC100-2 | .45 | | M15x1.0; M16x1.5 | | 9/16-32UN; 9/16-28UN; 9/16-24UNEF; 5/8-20UN; 9/16-18UNF; 9/16-16UNF; 7/8-14UNF | 9/16-24UNJEF; 3/4-20UNJEF; 5/8-18UNJF; 5/8-16UNJF; 7/8-14UNJF |
| TMLC100-3 BTMLC100-3 | .87 | M27x1.5 | M25x1.0; M30x2.0 | | 1-32UN; 1-28UN; 1-24UNS; 1 1/16-20UN; 1 1/16-18UNEF; 1 1/16-16UNEF; 1 1/8-14UNS; 1 1/8-12 | 1 5/8-24 UNJ; 1 1/16-20UNJ; 1 1/16-18UNJEF; 1 1/16-16; 1 1/8-12UNJF |
| BTMLC075-3B | .75 | | M22x1.0; M24x1.5; M25x2.0 | | 7/8-24UNS; 15/16-20UNEF; 1-18UNS; 1-16UNS; 1-14UNS; 1-12UNF | |
| BTMLC100-3B | .87 | M27x1.5 | M25x1.0; M30x2.0 | | 1-24UNS; 1 1/16-20UN; 1 1/16-18UNEF; 1 1/16-16UNEF; 1 1/8-14UNS; 1 1/8-12UNF | |
| TMLC100-5 | 1.18 | | M35x1.5; M39x2.0; M36x3.0; M36x4.0; M42x4.5; M48x5.0 | 1 3/4-5 | 1 3/8-24UNS; 1 3/8-20UN; 1 7/16-18UNEF; 1 7/16-16UNEF; 1 1/2-14UNS; 1 1/2-12UNF; 1 5/8-10UNS; 1 7/16-8UN; 1 5/8-6UN | 1 7/16-16UNJ; 1 1/2-12UNJF |
| TMLC125-5 | 1.46 | | M45x1.5; M45x2.0; M50x3.0; M56x4.0 | | 1 5/8-24UNS; 1 11/16-20UN; 1 11/16-18UNEF; 1 11/16-16UNEF; 1 3/4-14UNS; 1 3/4-12UN; 1 7/8-10UNS; 2-8 UN; 2 1/4-6UN | 1 11/16-16UNJ; 1 3/4-12UNJ |
| TMLC150-6B | 1.81 | M64x6.0 | M52x1.5; M55x2.0; M60x3.0; M60x4.0; M60x5.5 | 2 1/2-4 | 2 3/8-6UN | |

| Toolholder | D2 | Thread Standards | | | | | | | | | |
|-------------------------|------|--|----------------|----------|------------|------------|-----------|------------------------|-----------------------|------------------------------------|--|
| | | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS | Trapez | ACME | |
| TMLC100-2 | .45 | 5/8-26BSF; 5/8-20BSW; 1 1/16-14BSF | 3/8-19; 1/2-14 | 3/8-19 | | | PG9; PG21 | | | | |
| TMLC100-3 BTMLC100-3 | .87 | 1 1/16-26BSF; 1 1/16-20BSW; 1 1/8-16BSW | 7/8-14; 1-11 | | | | PG21 | 1-11.5 | | | |
| BTMLC075-3B | .75 | 15/16-20BSW; 1-16BSW; 1 1/16-12BSW | 3/4-14; 1-11 | | | | | 1-11.5 | | | |
| BTMLC100-3B | .87 | 1 1/16-20BSW; 1 1/8-16BSW | 7/8-14; 1-11 | | | | PG21 | 1-11.5 | | | |
| TMLC100-5 | 1.18 | 1 3/4-7BSF; 1 7/8-6BSW | 1 1/4-11 | 1 1/4-11 | 1 1/4-11.5 | 1 1/4-11.5 | PG29 | 1 1/4-11.5; 2 1/2-8 | TR44-3.0 | 1 1/2-10; 1 3/4-8; 1 3/4-6; 2-5 | |
| TMLC125-5 | 1.46 | 1 7/8-6BSW | 1 1/2-11 | 1 1/2-11 | 1 1/2-11.5 | 1 1/2-11.5 | PG36 | 1 1/2-11.5; 2 1/2-8 | TR50-3.0; TR65-4.0 | 1 3/4-10; 2-8; 2 1/4-6; 2 1/2-5 | |
| TMLC150-6B | 1.81 | 3-5BSF; 3 1/2-4.5BSF | 2-11 | | 2 1/2-8 | 2 1/2-8 | | | | | |

TM Standard

External and Internal Toolholders



124/... - For Coarse Pitch Threads

Spare Parts



| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | |
|-------------|-------------------|---------|-----------------|------|------|-----|-----|--------------|----------|
| | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key |
| 6.0mm | TMMC075-6-124/203 | 67700 | 3.50 | .59 | .75 | .26 | .35 | SN7T | K7T |
| | TMC075-2-124/205 | 67702 | 3.12 | .61 | .75 | .29 | .39 | | |
| 1/4" | TMC075-2-124/206 | 67703 | 3.12 | .61 | .75 | .35 | .47 | SN2TM | K2T |
| | TMC075-2-124/209 | 67706 | 3.12 | .61 | .75 | .29 | .39 | | |
| 3/8" | TMC075-3-124/201 | 67698 | 3.75 | .81 | .75 | .48 | .61 | SN3TM | K3T |
| 1/2" | TMC100-4-124/202 | 67699 | 3.58 | 1.18 | 1.00 | .53 | .71 | SN4TM | K4T |
| | TMC100-4-124/207 | 67704 | 3.97 | 1.57 | 1.00 | .63 | .79 | SA4TM | |
| 5/8" | TMC100-5-124/204 | 67701 | 3.98 | 1.57 | 1.00 | .75 | .98 | SA5TM | K5T |
| | TMC100-5-124/208 | 67705 | 3.98 | 1.57 | 1.00 | .65 | .87 | SN5TM | |

Internal Thread Application for 124/... Coarse Pitch Toolholder

| Toolholder | | Min. Thread Dia. | | | | |
|-------------------|-----|---------------------|------------------------------------|----------------|--|---|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ |
| TMMC075-6 124/203 | .35 | M12x1.75 | M12x1.0; M22x1.5; M12x1.75 | 7/16-14 | 1 1/16-32UN; 1/2-24UNS; 9/16-18UNF; 9/16-16UNF | 9/16-24UNJEF; 1/2-20UNJF; 9/16-18UNJF; 9/16-16UNJF |
| TMC075-2 124/205 | .39 | | | 1/2-13 | 5/8-12UN | |
| TMC075-2 124/206 | .47 | | | 5/8-11 | | |
| TMC075-2 124/209 | .39 | | | | | |
| TMC075-3 124/201 | .61 | M20x2.5 | M20x1.0; M22x1.5; M22x2.0 | 3/4-10 | 1 1/16-32UN; 3/4-28UN; 3/4-24UNS; 13/16-20UNEF; 7/8-18UNS; 7/8-16UNS; 7/8-14UNF; 7/8-12UN | 15/8-24UNJ; 13/16-20UNJEF; 1 1/16-18UNJEF; 13/16-16UNJ; 7/8-14UNJF; 7/8-12UNJ |
| TMC100-4 124/202 | .71 | M22x2.5; M24x3.0 | | 7/8-9; 1 1/8-7 | | |
| TMC100-4 124/207 | .79 | | | 1-8 | | |
| TMC100-5 124/204 | .98 | M30x3.5 | M30x1.5; M33x2.0; M39x3.0; M56x4.0 | 1 3/8-6 | 1 1/8-24UNS; 1 3/16-20UN; 1 3/16-18UNEF; 1 3/16-16UNEF; 1 1/4-14UNS; 1 1/4-12UNF; 1 1/2-10UNS; 1 1/4-8UN | 1 3/16-16UNJ; 1 1/4-12UNJF |
| TMC100-5 124/208 | .87 | | | | | |

| | D2 | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS | Trapez | ACME |
|-------------------|-----|---|--------|--------------|------------------------|------------------------|-----------------|------------------------|----------|--|
| TMMC075-6 124/203 | .35 | 7/16-26BSF; 7/16-18BSF; | 1/4-19 | | | | PG7 | 1/2-14; 1-11.5 | | |
| TMC075-2 124/205 | .39 | 1/2-16BSF | | | | | | | | 5/8-14 |
| TMC075-2 124/206 | .47 | 5/8-14BSF | | | | | | | TR16-2 | 3/4-14; 3/4-12 |
| TMC075-2 124/209 | .39 | | | | 1/4-18 | 1/4-18 | | | | |
| TMC075-3 124/201 | .61 | 3/4-12BSF | 1/2-14 | 3/4-14; 1-11 | 3/4-14; 1-11.5 | 3/4-14; 1-11.5 | PG13.5; PG21 | 1-11.5 | | |
| TMC100-4 124/202 | .71 | 7/8-11BSF; 1-10BSF; 7/8-9BSW; 1-8BSW | | | | | | | TR24-3.0 | 1-10; 1-8 |
| TMC100-4 124/207 | .79 | | | | | | | | TR32-3.0 | 1 1/8-10 |
| TMC100-5 124/204 | .98 | 1 3/16-8BSW; 1 1/4-7BSW; 1 3/16-6BSW | 1-11 | 1-11 | 1 1/4-11.5; 2 1/2-8 | 1 1/4-11.5; 2 1/2-8 | PG21 | 1 1/4-11.5; 2 1/2-8 | TR38-3.0 | 1 1/4-10; 1 3/8-8; 1 1/2-6; 1 3/4-5 |
| TMC100-5 124/208 | .87 | 1 1/8-7BSW | | | | | | | | 1 3/8-6 |

External and Internal Toolholders




TMN - For Conical Threads (NPT, NPTF, BSPT)

Spare Parts

| Insert Size | Ordering Code | EDP No. | Ordering Code | EDP No. | Dimensions Inch | | | | |  |  |
|-------------|---------------|---------|----------------|---------|-----------------|------|------|------|------|---|---|
| IC | RH | | *LH | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key |
| 3/8" | TMNC0625-3 | 67638 | TMNC0625-3LH | 67639 | 3.56 | .87 | .625 | .49 | .61 | SN3TM | K3T |
| | TMNC075-3 | 67640 | TMNC075-3LH | 67641 | 3.38 | .91 | .75 | .59 | .75 | | |
| 3/8"B | BTMNC0625-3B | 67605 | BTMNC0625-3BLH | 67606 | 3.15 | 1.14 | .625 | .53 | .67 | SN3TM | K3T |
| | BTMNC075-3B | 67607 | BTMNC075-3BLH | 67730 | 3.27 | 1.14 | .75 | .61 | .75 | | |
| 5/8" | TMNC125-5 | 67644 | TMNC125-5LH | 67645 | 4.75 | 2.28 | 1.25 | 1.22 | 1.46 | SN5TM | K5T |

TM Standard






Internal Thread Application for TMN Toolholder

| Toolholder | | Min. Thread Dia. | | | |
|--------------------------------|------|---------------------------------------|-----|---|--|
| | D2 | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ |
| TMNCO625-3 TMNCO625-3LH | .61 | M20x1.0; M22x1.5; M22x2.0 | | 1 ¹ / ₁₆ -32UN; 3 ⁴ / ₄ -28UN; 3 ⁴ / ₄ -24UNS; 1 ³ / ₁₆ -20UNEF; 7 ⁸ / ₈ -18UNS; 7 ⁸ / ₈ -16UNS; 7 ⁸ / ₈ -14UNF; 3 ⁴ / ₄ -12UN | 1 ⁵ / ₈ -24UNJ; 1 ³ / ₁₆ -20UNJEF; 1 ¹ / ₁₆ -18UNJEF; 1 ³ / ₁₆ -16 UNJ; 7 ⁸ / ₈ -14UNJF; 7 ⁸ / ₈ -12UNJ |
| TMNCO75-3 TMNCO75-3LH | .75 | M22x1.0; M24x1.5; M25x2.0 | | 7 ⁸ / ₈ -32UN; 7 ⁸ / ₈ -28UN; 7 ⁸ / ₈ -24UNS; 1 ⁵ / ₁₆ -20UNEF; 1-18UNS; 1-16UNS; 1-14UNS; 1-12UNF | 1 ⁵ / ₈ -24UNJ; 1 ⁵ / ₁₆ -20UNJEF; 1 ¹ / ₁₆ -18UNJEF; 1 ⁵ / ₁₆ -16UNJ; 1 5 ⁸ / ₈ -14UNJ; 1-12UNJF |
| BTMNC0625-3B BTMNC0625-3BLH | .67 | M20x1.0; M22x1.5; M24x2.0 | | 7 ⁸ / ₈ -24UNS; 7 ⁸ / ₈ -20UNEF; 7 ⁸ / ₈ -18UNS; 7 ⁸ / ₈ -16UNS; 1-14UNS; 1 ³ / ₁₆ -12UN | |
| BTMNC075-3B BTMNC075-3BLH | .75 | M22x1.0; M24x1.5; M25x2.0 | | 7 ⁸ / ₈ -24UNS; 1 ⁵ / ₁₆ -20UNEF; 1-18UNS; 1-16UNS; 1-14UNS; 1-12UNF | |
| TMNCO125-5 TMNCO125-5LH | 1.46 | M45x1.5; M45x2.0; M50x3.0; M56x4.0 | | 1 ⁵ / ₈ -24UNS; 1 ¹¹ / ₁₆ -20UN; 1 ¹¹ / ₁₆ -18UNEF; 1 ¹¹ / ₁₆ -16UNEF; 1 ³ / ₄ -14UNS; 1 ³ / ₄ -12UN; 1 ⁷ / ₈ -10UNS; 2-8UN; 2 ¹ / ₄ -6UN | |

| | D2 | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS | Trapez | ACME |
|--------------------------------|------|--|---|---|--|--|---------------|--|--------|---|
| TMNCO625-3 TMNCO625-3LH | .61 | 1 ³ / ₁₆ -16BSW | 1 ¹ / ₂ -14 | 1 ¹ / ₂ -14; 1-11 | 1 ¹ / ₂ -14; 1-11.5 | 1 ¹ / ₂ -14; 1-11.5 | PG11; PG21 | 1 ¹ / ₂ -14; 1-11.5 | | 7 ⁸ / ₈ -14; 1-12 |
| TMNCO75-3 TMNCO75-3LH | .75 | 1 ⁵ / ₁₆ -26BSW; 1 ⁵ / ₁₆ -20BSW; 1-16BSW; 1 ¹ / ₁₆ -12BSW | 3 ⁴ / ₄ -14; 1-11 | 3 ⁴ / ₄ -14; 1-11 | 3 ⁴ / ₄ -14; 1-11.5 | 3 ⁴ / ₄ -14; 1-11.5 | PG21 | 3 ⁴ / ₄ -14; 1-11.5 | | |
| BTMNC0625-3B BTMNC0625-3BLH | .67 | 7 ⁸ / ₈ -20BSW; 7 ⁸ / ₈ -16BSW; 1 ³ / ₁₆ -12BSW | 5 ⁸ / ₈ -14; 1-11 | | 3 ⁴ / ₄ -14; 1-11.5 | 3 ⁴ / ₄ -14; 1-11.5 | | 1-11.5 | | |
| BTMNC075-3B BTMNC075-3BLH | .75 | 1 ⁵ / ₁₆ -20BSW; 1-16BSW; 1 ¹ / ₁₆ -12BSW | 3 ⁴ / ₄ -14; 1-11 | | 3 ⁴ / ₄ -14; 1-11.5 | 3 ⁴ / ₄ -14; 1-11.5 | | 1-11.5 | | |
| TMNCO125-5 TMNCO125-5LH | 1.46 | 1 ⁷ / ₈ -6BSW | 1 ¹ / ₂ -11 | 1 ¹ / ₂ -11 | 1 ¹ / ₂ -11.5; 2 ¹ / ₂ -8 | 1 ¹ / ₂ -11.5; 2 ¹ / ₂ -8 | PG36 | 1 ¹ / ₂ -11.5; 2 ¹ / ₂ -8 | | |

TM Standard

External and Internal Toolholders




TM2 - Twin Flutes

Spare Parts


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | |  |  |
|-------------|---------------|---------|-----------------|------|------|------|------|---|---|
| IC | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key |
| 1/4" | TM2C075-2 | 67685 | 3.42 | .79 | .75 | .57 | .67 | SN2TM | K2T |
| 3/8" | TM2C100-3 | 67686 | 4.02 | 1.69 | 1.00 | .89 | 1.02 | SN3T | K3T |
| 3/8"B | BTM2C100-3B | 67718 | 4.13 | 1.81 | 1.00 | .89 | 1.02 | | |
| 5/8" | TM2C125-5 | 67687 | 4.65 | 1.77 | 1.25 | 1.42 | 1.65 | SN5TM | K5T |
| 3/4"B | TM2C150-6B | 67688 | 5.33 | 2.56 | 1.50 | 1.73 | 2.05 | SM7T | K30T |

Internal Thread Application for TM2 Toolholder

| Toolholder | Min. Thread Dia. | | | | | | | | | | | |
|--------------------------|------------------|---|---------|--|---|---|----------|------|--------|---------|---------------|--------------------|
| | D2 | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS |
| TM2C075-2 | .67 | M22x1.5 | | 3/4-32UN; 13/16-28UN; 7/8-24UNS; 7/8-20UNEF; 7/8-18UNS; 7/8-16UNS; 1-14UNS | 15/8-24UNJ; 7/8-20UNJEF; 1 1/16-18UNJEF; 7/8-16UNJ; 1 5/8-14UNJ | | 5/8-14 | | | | PG16; PG21 | |
| TM2C100-3 BTM2C100-3B | 1.02 | M32x1.5; M33x2.0 | | 1 1/4-24UNS; 1 3/16-20UN; 1 1/4-18UNEF; 1 1/4-16UNEF; 1 3/8-14UNS; 1 5/16-12UN | 1 5/8-24UNJ; 1 3/16-20UNJ; 1 1/4-18UNJEF; 1 1/4-16UNJ; 1 5/16-12UNJ | 1 3/16-26BSF; 1 1/4-20BSW; 1 5/16-16BSW | 1 1/8-11 | | | | PG36 | 1 1/4-11.5 |
| TM2C125-5 | 1.65 | M48x1.5; M50x2.0; M55x3.0; M64x4.0 | | 1 7/8-20UN; 2-18UNS; 2-16UNS; 2-14UNS; 2-12UN; 2 1/4-10UNS; 2 1/4-8UN; 2 1/2-6UN | 1 5/16-16UNJ; 2-12UNJ | 2-16BSW; 2-12BSW; 2 1/4-8BSW | 2-11 | 2-11 | 2-11.5 | 2-11.5 | PG36 | 2-11.5; 2 1/2-8 |
| TM2C150-6B | 2.05 | M58x1.5; M68x4.0; M70x6.0 | 2 3/4-4 | 2 5/8-6UN | | 2 7/8-6BSW; 2 7/8-5BSW; 3 3/4-4.5BSF | 2 1/4-11 | | | 2 1/2-8 | | |



External and Internal Toolholders




TMO - Twin Flute Offset

Spare Parts

| Insert Size | Ordering Code EDP No. | | Applicable Threads | | | Dimensions Inch | | | | | Spare Parts | |
|-------------|-----------------------|----------|---------------------|------------------------|---------------------------|-----------------|------|------|-----|--------------|-------------|-----|
| | IC | External | Internal | External & Internal | L | L1 | D | D1 | D2 | Insert Screw | Torx Key | |
| 1/4" | TMOC075-2-1 | 67655 | 16UN | 48/32/16UN | | | | | | | | |
| | TMOC075-2-2 | 67657 | 24/18UN | 48/24/18UN | 24W | | | | | | | |
| | TMOC075-2-3 | 67658 | 28/14UN | 28/14UN | 28/14W | | | | | | | |
| | TMOC075-2-4 | 67659 | 20UN | 20UN | | | | | | | | |
| | TMOC075-2-5 | 67693 | | | 26W | 3.50 | .98 | .75 | .47 | .57 | SN2TM | K2T |
| | TMOC075-2-6 | 67727 | | | 20W | | | | | | | |
| | TMOC075-2-7 | 67660 | | | 19W | | | | | | | |
| | TMOC075-2-8 | 67713 | 1.0/1.5ISO | 0.5/1.0/1.5ISO | | | | | | | | |
| | TMOC075-2-9 | 67762 | 0.75ISO | 48UN, 0.75ISO | | | | | | | | |
| | TMOC075-2-10 | 67656 | 1.25ISO | 1.25ISO | | | | | | | | |
| 3/8" | TMOC075-3-1 | 67661 | 1.5ISO | 0.5/1.5ISO | | | | | | | | |
| | TMOC075-3-2 | 67763 | 13UN | 13UN | 26W | | | | | | | |
| | TMOC075-3-3 | 67663 | 28UN | 32/28UN | | | | | | | | |
| | TMOC075-3-4 | 67674 | 27UN | 27UN | | | | | | | | |
| | TMOC075-3-5 | 67664 | | 11.5UN | 11.5NPS | | | | | | | |
| | TMOC075-3-6 | 67665 | 24/20/18/16/14/12UN | 24/20/18/16/14/12UN | 26/20/18/16/14/12W, 14NPS | 3.75 | 1.69 | .75 | .65 | .79 | SN3T | K3T |
| | TMOC075-3-7 | 67764 | 1.25ISO | 1.25ISO | 24W | | | | | | | |
| | TMOC075-3-8 | 67765 | | | 19W | | | | | | | |
| | TMOC075-3-9 | 67716 | | | 11W | | | | | | | |
| | TMOC075-3-10 | 67662 | 1.0/2.0ISO | 0.5/1.0/2.0ISO | | | | | | | | |
| | TMOC075-3-11 | 67766 | 0.75ISO | 32UN, 0.75ISO | | | | | | | | |
| | TMOC075-3-12 | 67767 | 1.75ISO | 1.75ISO | | | | | | | | |
| 5/8" | TMOC100-5-1 | 67666 | 24/20/18/14/13/12UN | 24/20/18/14/13/11UN | 14W | | | | | | | |
| | TMOC100-5-2 | 67667 | 24/18/12UN | 24/18/12/6UN | 12W | | | | | | | |
| | TMOC100-5-3 | 67668 | 16UN | 16UN | 16W, 8NPS | | | | | | | |
| | TMOC100-5-4 | 67669 | 14/7UN | 14UN | 14/7W | | | | | | | |
| | TMOC100-5-5 | 67726 | | 11.5UN | 11.5NPS | | | | | | | |
| | TMOC100-5-6 | 67707 | 11UN | 11UN | 11W | | | | | | | |
| | TMOC100-5-7 | 67670 | 10UN | 10/5UN | 10W | | | | | | | |
| | TMOC100-5-8 | 67714 | 9UN | 9UN | 9W | 4.38 | 2.05 | 1.00 | .94 | 1.18 | SN5TM | K5T |
| | TMOC100-5-9 | 67671 | 8UN | 8UN | 8W | | | | | | | |
| | TMOC100-5-10 | 67678 | | 7UN | | | | | | | | |
| | TMOC100-5-11 | 67768 | 6UN | | 6W | | | | | | | |
| | TMOC100-5-12 | 67712 | 1.0/2.0/2.5/4.0ISO | 1.0/2.0/2.5/4.0/5.0ISO | | | | | | | | |
| | TMOC100-5-13 | 67769 | 1.25ISO | 1.25ISO | | | | | | | | |
| | TMOC100-5-14 | 67770 | 1.5/2.5/4.5ISO | 1.5/2.5/4.5/ISO | | | | | | | | |
| | TMOC100-5-15 | 67771 | 1.75ISO | 1.75ISO | | | | | | | | |
| | TMOC100-5-16 | 67760 | 1.0/1.5/3.0/3.5ISO | 1.0/1.5/3.0/3.5ISO | | | | | | | | |

TM Standard

External and Internal Toolholders



TM Shell Mill

Spare Parts




| Insert Size | Ordering Code | EDP No. | No. of inserts | Dimensions Inch | | | Spare Parts | | |
|-------------|------------------|---------|----------------|-----------------|-------|------|--------------|----------|--------------|
| | | | | D2 | d(H7) | H | Insert Screw | Torx Key | Holder Screw |
| 1/4" | TMSH-D150-050-2 | 67100 | 6 | 1.50 | 1/2 | 1.58 | SN2T | HK2T | 1/4 X 28 |
| 1/4" | TMSH-D200-075-2 | 67101 | 8 | 1.97 | 3/4 | 1.58 | | | 3/8 X 24 |
| 3/8" | TMSH-D200-075-3 | 67102 | 6 | 1.97 | 3/4 | 1.58 | SN3TM | HK3T | 3/8 X 24 |
| 3/8B" | TMSH-D250-075-3B | 67103 | 6 | 2.48 | 3/4 | 1.58 | | | |
| 5/8" | TMSH-D250-075-5 | 67104 | 4 | 2.48 | 3/4 | 1.77 | SN5TM | HK5T | 3/8 X 24 |
| 3/4B" | TMSH-D250-075-6B | 67112 | 4 | 2.48 | 3/4 | 1.97 | SM7T | HK7T | 3/8 X 24 |
| 5/8" | TMSH-D300-100-5 | 67105 | 6 | 3.15 | 1 | 2.00 | SN5TM | HK5T | 1/2 X 20 |
| 3/4B" | TMSH-D300-100-6B | 67106 | 5 | 3.15 | 1 | 2.00 | SM7T | HK7T | 1/2 X 20 |
| 5/8" | TMSH-D400-125-5 | 67107 | 7 | 3.94 | 1 1/4 | 2.16 | SN5TM | HK5T | 5/8 X 18 |
| 3/4B" | TMSH-D400-125-6B | 67772 | 6 | 3.94 | 1 1/4 | 2.16 | SM7T | HK7T | 5/8 X 18 |
| 5/8" | TMSH-D500-150-5 | 67109 | 9 | 4.92 | 1 1/2 | 2.50 | SN5TM | HK5T | 3/4 X 16 |
| 3/4B" | TMSH-D500-150-6B | 67110 | 8 | 4.92 | 1 1/2 | 2.50 | SM7T | HK7T | 3/4 X 16 |

Internal Thread Application for Shell Mill Toolholder

| Toolholder | | Min. Thread Dia. | | | | | | | | | | |
|------------------|------|------------------------------------|----------------------------------|---|--|--|-----------------------------------|------|----------------------------------|----------------------------------|------|----------------------------------|
| | D2 | ISO Fine | UNC | UN/UNF/UNEF/UNS | UNJ | BSW/BSF | BSP | BSPT | NPT | NPTF | PG | NPS |
| TMSH-D150-050-2 | 1.50 | M45x1.5 | | 1 ¹¹ / ₁₆ -20UN; 1 ³ / ₄ -18UNS; 1 ³ / ₄ -16UNS; 1 ⁷ / ₈ -14UNS | 1 ⁵ / ₈ -24UNJ; 1 ¹¹ / ₁₆ -20UNJ; 1 ³ / ₄ -16UNJ | 1 ³ / ₄ -26BSF; 1 ³ / ₄ -20BSW | | | | | PG36 | |
| TMSH-D200-075-2 | 1.97 | M56x1.5 | | 2 ¹ / ₄ -20UN; 2 ¹ / ₄ -18UNS; 2 ¹ / ₄ -16UNS; 2 ¹ / ₄ -14UNS | 2 ¹ / ₄ -20UNJ; 2 ¹ / ₄ -16UNJ | | | | | | | |
| TMSH-D200-075-3 | 1.97 | M56x1.5; M58x2.0 | | 2 ¹ / ₄ -20UN; 3 ¹ / ₄ -18UNS; 3 ¹ / ₄ -16UNS; 3 ¹ / ₄ -14UNS; 2 ³ / ₈ -12UN | 2 ¹ / ₄ -20UNJ; 2 ¹ / ₄ -16UNJ; 2 ³ / ₈ -12UNJ | 2 ¹ / ₄ -20BSW; 2 ³ / ₈ -16BSW; 2 ³ / ₈ -12BSW | 2 ¹ / ₄ -11 | | | | PG42 | 2-11.5 |
| TMSH-D250-075-3B | 2.48 | M70x1.5; M70x2.0 | | 2 ³ / ₄ -20UN; 2 ³ / ₄ -18UNS; 2 ³ / ₄ -16UNS; 2 ³ / ₄ -14UNS; 2 ⁷ / ₈ -12UN | | | 2 ¹ / ₂ -11 | | | | | |
| TMSH-D250-075-5 | 2.48 | M70x1.5; M70x2.0; M75x3.0; M80x4.0 | | 2 ³ / ₄ -20UN; 3 ³ / ₄ -18UNS; 3 ³ / ₄ -16UNS; 3 ³ / ₄ -14UNS; 2 ⁷ / ₈ -12UN; 3-10UNS; 3-8UN | 2 ³ / ₄ -16UNJ; 2 ⁷ / ₈ -12UNJ | 2 ⁷ / ₈ -16BSW; 2 ⁷ / ₈ -12BSW; 3 ¹ / ₈ -8BSW | 2 ¹ / ₂ -11 | 3-11 | | | | 3-8 |
| TMSH-D250-075-6B | 2.48 | M70x2.0; M80x4.0; M85x6.0 | 3 ¹ / ₄ -4 | 3 ¹ / ₄ -6UN | | 3 ³ / ₈ -6BSW; 3 ¹ / ₂ -4.5BSF | 2 ¹ / ₂ -11 | | 3-8 | 3-8 | | |
| TMSH-D300-100-5 | 3.15 | M90x2.0; M95x3.0; M95x4.0 | | 3 ¹ / ₂ -18UNS; 3 ¹ / ₂ -16UNS; 3 ¹ / ₂ -14UNS; 3 ¹ / ₂ -12UN; 3 ³ / ₄ -10UNS; 3 ³ / ₄ -8UN | 3 ³ / ₈ -16UNJ; 3 ¹ / ₂ -12UNJ | 3 ¹ / ₂ -16BSW; 3 ¹ / ₂ -12BSW; 3 ³ / ₄ -8BSW | 3 ¹ / ₄ -11 | 4-11 | | | | 3 ¹ / ₂ -8 |
| TMSH-D300-100-6B | 3.15 | M90x2.0; M95x4.0; M105x6.0 | | 3 ⁷ / ₈ -6UN | | 4-6BSW | 3 ¹ / ₄ -11 | | 3 ¹ / ₂ -8 | 3 ¹ / ₂ -8 | | |
| TMSH-D400-125-5 | 3.94 | M110x2.0; M115x3.0; M115x4.0 | | | 4 ¹ / ₄ -16UNJ; 4 ³ / ₈ -12UNJ | 4 ¹ / ₄ -16BSW; 4 ¹ / ₄ -12BSW; 4 ⁵ / ₈ -8BSW | 4-11 | 4-11 | | | | |
| TMSH-D400-125-6B | 3.94 | M110x2.0; M115x4.0; M125x6.0 | | | | 4 ⁷ / ₈ -6BSW | 4-11 | | 5-8 | 5-8 | | |
| TMSH-D500-150-5 | 4.92 | M135x2.0; M140x3.0; M140x4.0 | | | 5 ¹ / ₄ -16UNJ; 5 ³ / ₈ -12UNJ | 5 ¹ / ₄ -16BSW; 5 ¹ / ₄ -12BSW; 5 ⁵ / ₈ -8BSW | 5-11 | 5-11 | | | | |
| TMSH-D500-150-6B | 4.92 | M135x2.0; M140x4.0; M150x6.0 | | | | 5 ⁷ / ₈ -6BSW | 5-11 | | 5-8 | 5-8 | | |

TM Standard

External and Internal Toolholders



TMS - Single Point (Standard Inserts)




Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Spare Parts | |
|-------------|---------------|---------|-----------------|-----|------|-----|-----|--------------|-------------|--|
| IC | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key | |
| 1/4" | TMSC0375-2 | 67673 | 2.50 | .98 | .375 | .37 | .49 | SN2TK | K2T | |

Use Standard laydown thread turning inserts. See Thread Turning Inserts section - Page 21.
Use external LH inserts for external thread and internal RH inserts for internal thread.

TM Standard

External and Internal Toolholders



TMV - Single Point (Vertical Insert)

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | Spare Parts | |
|-------------|---------------|---------|-----------------|------|------|------|------|--------------|-------------|--|
| IC | | | L | L1 | D | D1 | D2 | Insert Screw | Torx Key | |
| 5/8"V | TMVC125-5 | 67677 | 4.65 | 2.36 | 1.25 | 1.41 | 1.81 | SN6T | K6T | |

Requires IC 5/8" Vertical thread turning inserts (width T=6). Use external LH inserts for external threads and internal RH inserts for internal threads.
See Thread Turning Inserts section - Page 21.

Recommended Grades, Cutting Speeds Vc [ft/min] and Feed f [inch/tooth]

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | | Feed f [inch/tooth] | |
|-------------------------------------|-----------------------------|--|------------------------------------|-------------|-----------|------------|---------------------|-------------|
| | | | | Coated | | Uncoated | | |
| | | | | VBX | VTX | VK2 | | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 328-689 | 295-591 | .002-.0118 | |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 328-591 | 295-558 | .002-.0098 | |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 328-558 | 295-525 | .002-.0079 | |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 295-525 | 295-509 | .002-.0098 | |
| | 5 | | Hardened | 275 | 262-591 | 262-525 | .002-.0079 | |
| | 6 | | Hardened | 350 | 230-459 | 230-492 | .002-.0059 | |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 197-427 | 230-377 | .002-.0079 | |
| | 8 | | Hardened | 325 | 230-361 | 197-328 | .002-.0039 | |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 328-558 | 328-558 | 328-492 | .002-.0059 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 230-394 | 230-427 | 197-427 | .002-.0039 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 328-558 | 394-591 | .002-.0059 | |
| | 12 | | Hardened | 330 | 328-558 | 394-591 | .002-.0039 | |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 230-459 | 328-459 | .002-.0059 | |
| | 14 | | Super Austenitic | 200 | 230-459 | 328-459 | .002-.0039 | |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 230-459 | 328-459 | .002-.0059 | |
| | 16 | Stainless Steel Cast Austenitic | Hardened | 330 | 230-459 | 328-459 | .002-.0039 | |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 230-394 | 328-394 | .002-.0059 | |
| | 18 | | Hardened | 330 | 230-394 | 328-394 | .002-.0039 | |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 197-427 | 328-394 | .0008-.0315 | |
| | 29 | | Pearlitic (long chips) | 230 | 197-394 | 262-328 | .0008-.002 | |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 197-427 | 262-328 | .002-.0059 | |
| | 31 | | High Tensile Strength | 260 | 197-328 | 262-328 | .002-.0039 | |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 197-410 | 262-328 | .002-.0059 | |
| 33 | Pearlitic | | 260 | 164-295 | 197-295 | .002-.0039 | | |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-820 | | 656-984 | .0039-.0157 |
| | 35 | | Aged | 100 | 328-591 | | 197-361 | .0039-.0118 |
| | 36 | Aluminium Alloys | Cast | 75 | 492-1,312 | | 197-394 | .0039-.0118 |
| | 37 | | Cast & Aged | 90 | 492-919 | | 197-328 | .002-.0098 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 262-492 | | 66-164 | .0039-.0118 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 394-689 | 328-656 | 164-230 | .0039-.0118 |
| 40 | Bronze And Non Leded Copper | | 100 | 394-689 | 328-656 | 164-230 | .002-.0098 | |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 66-148 | 66-131 | 66-98 | .002-.0039 |
| | 20 | | Aged (iron based) | 280 | 66-98 | 66-98 | 49-82 | .0008-.002 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 66-164 | 49-66 | 49-66 | .0008-.002 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 33-49 | 33-49 | 33-49 | .0008-.002 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 230-459 | 230-394 | 131-197 | .0008-.002 |
| 24 | α+β Alloys | | 1050Rm | 66-164 | 66-164 | 66-131 | .0008-.002 | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 66-148 | 66-148 | | .0004-.0012 |
| | 26 | | | 51-55HRc | 66-148 | 66-148 | | .0004-.0008 |

TM Standard

Grades

| Grade | Application | Sample |
|------------|--|---|
| VBX | First choice for steel and cast iron A tough sub-micron substrate with TiCN coating |  |
| VTX | First choice for stainless steel A tough sub-micron substrate with TiAlN coating |  |
| VK2 | Uncoated grade for machining cast iron & nonferrous metals |  |



TMSD


Thread Milling for Deep Holes

Inserts | Toolholders

Vardex Ordering Code System

TMSD Inserts

| | | | | | | |
|----------|----------|----------|-----------|-----------|-----------|------------|
| 2 | U | I | DB | 60 | TM | VBX |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |

| | | | | |
|---|--|---|--|---|
| 1 - Insert Size 5 - IC5.0 mm 2 - IC1/4" 3 - IC3/8" 4 - IC1/2" 7 - IC6.8 mm 9 - IC8.5 mm 11 - IC10.7 mm  | 2 - Insert Style U -  A -  L -  V - Vertical Style 7, 9, 11 V - V Style 5/8"  | 3 - Type of Insert I - Internal EI - External + Internal | 4 - Pitch Full Profile - Pitch Range mm TPI 1.0-8.0 18-2.5 Partial Profile - U, A, L Styles Partial Profile - Vertical Style mm TPI mm TPI DA 0.5-1.5 48-16 VA 0.5-1.0 28-27 DB 1.5-2.0 16-12 VB - 11-9 DC 2.5-4.0 10-6 VC - 16-10 DD 2.0-2.5 9-12 VD 1.0-2.0 24-12 DE 2.5-3.5 10-7 VE 2.0-3.0 12-8 DH 4.0-6.0 6-4 VF 1.0-1.5 24-16 DK 6.0-8.0 4-3 VG 1.5-2.0 16-12 DL - 11-7 VH - 16-14 DM 2.5 10 VK 2.0-2.5 12-10 DN 1.0-2.0 24-11 VJ - 26-19 DP 1.5-3.0 16-8 VM - 8-7 DR - 26-14 VN 1.5-2.5 16-11 DT 2.0-4.0 12-6 | 5 - Standard 60 - Partial Profile 60° 55 - Partial Profile 55° ISO - ISO Metric UN - American UN NPT - NPT TR - Trapez DIN 103 ACME - ACME STACME - Stub ACME ABUT - American Buttress APIRD - API Round Casing & Tubing 6 - System TM - TMSD (U, A, L Styles) TM3 - TMSD Vertical 7 - Carbide Grade VBX, VTX |
|---|--|---|--|---|

TMSD Toolholders (U, A, L Styles)

| | | | | | | | | | | | | |
|----------|-----------|----------|----------|----------|------------|----------|------------|----------|------------|----------|-----------|-----------|
| C | TM | 2 | S | C | 056 | C | 068 | - | 235 | - | 2 | U |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | | 9 | | 10 | 11 |

| | | | | | | | |
|---|---|---|--|-----------------------------------|---------------------------------------|--|---------------------------------------|
| 1 - Shank Style None - Steel C - Carbide Shank | 2 - System TM | 3 - No. of Flutes 1-4 | 4 - Insert Type S - Single Point | 5 - Cooling C - Coolant | 6 - Shank Dia. .3125 - 1.50 | 7 - Shank Type W - Weldon C - Cylindrical | 8 - Cutting Dia. .51 - 1.65 |
| 9 - Max. Tool Overhang 5.67 | 10 - Insert Size 5 - IC5.0 mm 2 - IC1/4" 3 - IC3/8" 4 - IC1/2" | 11 - Insert Style U A L | 12 - Tool Application ABUT - For American Buttress | | | | |

TMSD Toolholders (Vertical Style)

| | | | | | | | | | | | |
|----------|-----------|----------|----------|----------|-----------|----------|-----------|----------|----------|----------|----------|
| C | GM | C | 9 | C | 13 | - | 45 | - | 7 | - | 3 |
| 1 | 2 | 3 | 4 | 5 | 6 | | 7 | | 8 | | 9 |

| | | | | | | | |
|---|---|-----------------------------------|-------------------------------------|---|------------------------------------|--------------------------------------|--|
| 1 - Holder Type None - Steel Shank C - Carbide Shank | 2 - System GM - Groove Milling and Thread Milling | 3 - Cooling C - Coolant | 4 - Shank Dia. .75 - 2.56 | 5 - Shank Style C - Cylindrical W - Weldon | 6 - Cutting Dia. .41-.87 | 7 - Tool Overhang .98-2.56 | 8 - Insert Size 7 - IC6.8 mm 9 - IC8.5 mm 11 - IC10.7 mm |
| 9 - Number of Flutes 3 | | | | | | | |

TMSD Shell Mill (U, L, V Styles)

| | | | | | | | | | | | |
|-----------|----------|----------|----------|--|-------------|----------|------------|----------|----------|----------|----------|
| TM | 4 | S | C | | D169 | - | 050 | - | 3 | U | |
| 1 | 2 | 3 | 4 | | 5 | | 6 | | 7 | 8 | 9 |

| | | | | | | | |
|---|---------------------------------|--|-----------------------------------|--------------------------------------|--|--|------------------------------------|
| 1 - System TM | 2 - No. of Flutes 4-7 | 3 - Insert Type S - Single Point | 4 - Cooling C - Coolant | 5 - Cutting Dia. 1.69-4.35 | 6 - Drive Hole Dia. .50, .75, 1.00, 1.50 | 7 - Insert Size 3 - IC3/8" 4 - IC1/2" 5 - IC5/8" | 8 - Insert Style U, L, V |
| 9 - Tool Application ABUT - American Buttress | | | | | | | |


TMSD

Thread Milling for Deep Holes

A multi-flute, highly productive and economical solution for milling threads in deep holes



Full Profile Inserts



ISO, American UN, NPT, API RD

American Buttress


U Style For Large Pitches

Weldon Shank



Tool Overhang (L1) 1.57-4.72
Cutting Dia. (D2) .58-1.66
No. of Flutes (Z) 1-4

Carbide Cylindrical Shank



Tool Overhang (L1) max 5.3
Cutting Dia. (D2) .58-1.24
No. of Flutes (Z) 1-4

Steel Cylindrical Shank



Tool Overhang (L1) max 5.65
Cutting Dia. (D2) .91-1.46
No. of Flutes (Z) 2-4

Shell Mill



Tool Overhang (L1) max 7.87
Cutting Dia. (D2) 1.69-4.35
No. of Flutes (Z) 4-8

L Style (Mini L) For Small Bores

Weldon Shank



Tool Overhang (L1) 1.14-1.80
Cutting Dia. (D2) .51-.72
No. of Flutes (Z) 1-3

Carbide Cylindrical Shank



Tool Overhang (L1) max 2.56
Cutting Dia. (D2) .51-.72
No. of Flutes (Z) 1-3

Vertical Style (7V, 9V, 11V)

Weldon Shank



Tool Overhang (L1) .98-1.77
Cutting Dia. (D2) .41-.82
No. of Flutes (Z) 3

Carbide Cylindrical Shank



Tool Overhang (L1) max 2.56
Cutting Dia. (D2) .41-.82
No. of Flutes (Z) 3

L Style (3/8" L) For Large Trapezoid Profiles and ABUT

Weldon Shank



Tool Overhang (L1) 2.0-4.13
Cutting Dia. (D2) .85-1.4
No. of Flutes (Z) 1-3

Carbide Cylindrical Shank



Tool Overhang (L1) max 4.43
Cutting Dia. (D2) .85-1.32
No. of Flutes (Z) 1-3

Shell Mill



Tool Overhang (L1) max 7.87
Cutting Dia. (D2) 2.28-3.15
No. of Flutes (Z) 5-7

A Style For Shorter L2


Steel Cylindrical Shank



Tool Overhang (L1) max 5.12
Cutting Dia. (D2) 1.02-1.39
No. of Flutes (Z) 3


TMSD

Partial Profile 60°



Vertical Style


| Insert Style | Pitch | | Ordering Code | EDP No. | | Dimensions Inch | | | Application (Min. Thread Size) | | | | Toolholder |
|--------------|---------|-------|----------------|----------|-------|-----------------|-----|------|--------------------------------|---|-------------------|--|---|
| | mm | TPI | | Internal | VTX | VBX | D2 | T | L2 | ISO Coarse | ISO Fine | UNC | |
| 7V | 0.5-1.0 | 28-27 | 7VIVA60TM3... | 59605 | 59606 | .413 | .11 | .024 | - | M11.5x0.5; M11.5x0.75; M12x1.0 | - | 1/2-28UNEF; 1/2-27UNS | CGMC5/16C13-40-7-3 GMC075W050-100-7-3 CGMC9C13-45-7-3 |
| | 1.0-1.5 | 24-16 | 7VIVF60TM3... | 59607 | 59608 | .437 | .11 | .031 | - | M12.5x1; M13x1.5 | - | 1/2-24UNS; 1/2-20UNF; 5/16-18UNF; 5/16-16UN | |
| | 1.5-2.0 | 16-12 | 7VIVG60TM3... | 59611 | 59612 | .465 | .11 | .039 | M14x2.0 | M14x1.5 | - | 5/16-16UN; 5/16-14UNS; 5/16-12UN | |
| | 1.5-2.5 | 16-11 | 7VIVN60TM3... | 30156 | 30157 | .488 | .11 | .043 | - | M15x1.5 M16x2 M18x2.5 | 5/8-11; 5/8-12 | 5/8-14UNS; 5/8-16UN | |
| 9V | 0.5-1.0 | 28-27 | 9VIVA60TM3... | 59613 | 59614 | .516 | .17 | .024 | - | M14x0.5; M14x0.75; M15x1 | - | 5/16-28UN; 5/16-27UNS | CGMC 7/16C17-45-9-3 GMC075W066-118-9-3 CGMC11.5C17-50-9-3 |
| | 1.0-1.5 | 24-16 | 9VIVF60TM3... | 59615 | 59616 | .539 | .17 | .031 | - | M15x1; M15.5x1.5 | - | 5/8-24UNEF; 5/8-20UN; 5/8-18UNF; 5/8-16UN | |
| | 1.5-2.0 | 16-12 | 9VIVG60TM3... | 59617 | 59618 | .567 | .17 | .039 | - | M16.5x1.5; M17x2 | - | 11/16-16UN; 3/4-14UNS; 11/16-12UN | |
| | 2.0-2.5 | 12-10 | 9VIVK60TM3... | 59619 | 59620 | .594 | .17 | .055 | - | M17.5x2; M18x2.5 | 3/4-10 | 11/16-12UN; | |
| 11V | 1.0-2.0 | 24-12 | 11VVD60TM3... | 59621 | 59622 | .705 | .22 | .039 | - | M19x1, M19.5x1.25; M19.5x1.5; M20x1.75; M20x2 | - | 3/4-24UNS; 13/16-20UNEF; 7/8-18UNS; 13/16-16UN; 7/8-14UNF; 13/16-12UN | CGMC5/8C22-65-11-3 GMC100W085-175-11-3 CGMC15C22-65-11-3 |
| | 2.0-3.0 | 12-8 | 11VIVE60TM3... | 59623 | 59624 | .768 | .22 | .059 | M22x2.5 M24x3 | M23x2 | 1-8 | 7/8-10UNS; 7/8-12UN | |



Vertical Style

TMSD


Partial Profile 55°



Vertical Style



| Insert Style | Pitch | Ordering Code | EDP No. | | Dimensions Inch | | | | Application (Min. Thread Size) | | |
|--------------|-------|----------------|---------|-------|-----------------|-----|------|------|--------------------------------|----------------------------------|--|
| | | | VTX | VBX | D2 | T | L2 | r | BSP (G) | Partial 55° | Toolholder |
| 7V | 26-19 | 7VIVJ55TM3... | 59625 | 59626 | .447 | .11 | .031 | .003 | ¼-19; ⅜-19 | - | CGMC5/16C13-40-7-3 GMC075W050-100-7-3 CGMC9C13-45-7-3 |
| | 16-14 | 7VIVH55TM3... | 59627 | 59628 | .472 | | .039 | .005 | ½-14; ⅝-14; ¾-14; 7/8-14; | 9/16-16; ⅝-14 | |
| 9V | 26-19 | 9VIVJ55TM3... | 59629 | 59630 | .526 | .17 | .031 | .004 | ⅜-19 | ⅝-26; ⅜-16 | CGMC7/16C17-45-9-3 GMC075W066-118-9-3 CGMC11.5C17-50-9-3 |
| | 16-10 | 9VIVC55TM3... | 59631 | 59632 | .606 | | .047 | .006 | ½-14 | ¾-16; 1½-14; ¾-12; ⅞-11; ¾-10 | |
| 11V | 16-12 | 11VIVG55TM3... | 59633 | 59634 | .701 | .22 | .035 | .006 | ½-14 | 1⅜-16; 1⅝-12 | CGMC5/8C22-65-11-3 GMC100W085-175-11-3 CGMC15C22-65-11-3 |
| | 11-9 | 11VIVB55TM3... | 59635 | 59636 | .752 | | .051 | .008 | 1-11 | ⅞-11; 1-10; 1⅝-9 | |
| | 8-7 | 11VIVM55TM3... | 59637 | 59638 | .772 | | .059 | .014 | - | 1-8; 1⅝-7; | |




Vertical Style


TMSD

Trapez

Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Vertical Style

Vertical Style


| Insert Style | Pitch mm | Ordering Code Internal | EDP No. | | Dimensions Inch | | | Application | |
|--------------|-------------|---------------------------|---------|-------|-----------------|-----|------|-------------|--|
| | | | VTX | VBX | D2 | T | L2 | Trapez | Toolholder |
| 7V | 2.0 | 7VI2.0TR-1TM3... | 59639 | 59640 | .484 | .11 | .051 | TR16x2 | CGMC5/16C13-40-7-3 GMC075W050-100-7-3 CGMC9C13-45-7-3 |
| | | 7VI2.0TR-2TM3... | 59641 | 59642 | | | | TR18x2 | |
| | | 7VI2.0TR-3TM3... | 59643 | 59644 | | | | TR20x2 | |
| 9V | 3.0 | 9VI3.0TR-1TM3... | 59645 | 59646 | .606 | .17 | .077 | TR22x3 | CGMC7/16C17-45-9-3 GMC075W066-118-9-3 CGMC11.5C17-50-9-3 |
| | | 9VI3.0TR-2TM3... | 59647 | 59648 | | | | TR24x3 | |




TMSD

Stub ACME

Internal



Defined by: ANSI B1.8: 1988
Tolerance class: 2G




Vertical Style

Vertical Style

| Insert Style | Pitch TPI | Ordering Code Internal | EDP No. | | Dimensions Inch | | | Application | |
|--------------|--------------|---------------------------|---------|-------|-----------------|-----|------|-------------|--|
| | | | VTX | VBX | D2 | T | L2 | Stub ACME | Toolholder |
| 7V | 8 | 7VI8STACMETM3... | 59649 | 59650 | .484 | .11 | .051 | 5/8-8 | CGMC5/16C13-40-7-3 GMC075W050-100-7-3 CGMC9C13-45-7-3 |
| | | 7VI6STACME-1TM3... | 59651 | 59652 | | | | 3/4-6 | |
| | | 7VI6STACME-2TM3... | 59653 | 59654 | | | | 7/8-6 | |
| 9V | 5 | 9VI5STACME-1TM3... | 59655 | 59656 | .657 | .17 | .077 | 1-5 | CGMC7/16C17-45-9-3 GMC075W066-118-9-3 CGMC11.5C17-50-9-3 |
| | | 9VI5STACME-2TM3... | 59657 | 59658 | | | | 1 1/8-5 | |
| | | 9VI5STACME-3TM3... | 59659 | 59660 | | | | 1 1/4-5 | |
| 11V | 4 | 11VI4STACME-1TM3... | 59661 | 59662 | .819 | .22 | .102 | 1 3/8-4 | CGMC5/8C22-65-11-3 GMC100W085-175-11-3 CGMC15C22-65-11-3 |
| | | 11VI4STACME-2TM3... | 59663 | 59664 | | | | 1 1/2-4 | |
| | | 11VI4STACME-3TM3... | 59665 | 59666 | | | | 1 3/4-4 | |
| | | 11VI4STACME-4TM3... | 59667 | 59668 | | | | 2-4 | |




Vertical Toolholders - Weldon Shank



| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | |
|--------------|---------------------|---------|-----------------|------|-----|-----|---------|---------------------------------------|----------------|-----------------------------|----------------------------------|
| | | | L | L1 | D | D1 | D2* | Insert Screw | Torx Key | Blade | Handle |
| 7V | GMC075W050-100-7-3 | 67146 | 3.78 | .98 | .75 | .35 | .41-.50 | SN2T8-M1 (M3.0x0.5x9) (70266) | K2T (70020) | - | - |
| 9V | GMC075W066-118-9-3 | 67147 | 4.13 | 1.18 | .75 | .45 | .51-.65 | SN3T15-M2 (M4x0.7x13.5) (70267) | - | Blade T15-1/4 (72009) | Smart Handle 1/4x2 (72010) |
| 11V | GMC100W085-175-11-3 | 67148 | 4.53 | 1.77 | 1.0 | .63 | .70-.82 | SN4T20-M3 (M5x0.8x15.5) (70268) | - | Blade T20-1/4 (72008) | Smart Handle 1/4x2 (72010) |

* The tool cutting diameter (D2) is defined by the insert (See pages 298-300).



For Correct Clamping:



Always mount insert with the identification mark between the two curved surfaces on the toolholder.

TMSD

Vertical Toolholders - Carbide Cylindrical Shank




TMSD

| Insert Style | Ordering Code | EDP No. | Dimensions Inch | | | | | | Spare Parts | | | |
|--------------|--------------------|---------|-----------------|------|----------|------|-----|---------|---------------------------------------|----------------|-----------------------------|----------------------------------|
| | | | L | L1 | L3 (min) | D | D1 | D2* | Insert Screw | Torx Key | Blade | Handle |
| 7V | CGMC9C13-45-7-3 | 67140 | 4.53 | 1.77 | .79 | .354 | .35 | .41-.50 | SN2T8-M1 (M3.0x0.5x9) (70266) | K2T (70020) | - | - |
| | CGMC5/16C13-40-7-3 | 67141 | | 1.57 | .71 | 5/16 | | | | | | |
| 9V | CGMC11.5C17-50-9-3 | 67142 | 4.92 | 1.97 | .98 | .453 | .45 | .51-.65 | SN3T15-M2 (M4x0.7x13.5) (70267) | - | Blade T15-1/4 (72009) | Smart Handle 1/4x2 (72010) |
| | CGMC7/16C17-45-9-3 | 67143 | | 1.77 | .98 | 7/16 | | | | | | |
| 11V | CGMC15C22-65-11-3 | 67144 | 5.31 | 2.56 | 1.26 | .591 | .59 | .70-.82 | SN4T20-M3 (M5x0.8x15.5) (70268) | - | Blade T20-1/4 (72008) | Smart Handle 1/4x2 (72010) |
| | CGMC5/8C22-65-11-3 | 67145 | | 2.56 | 1.34 | 5/8 | | | | | | |


* The tool cutting diameter (D2) is defined by the insert (See pages 298-300).

For Correct Clamping:



Always mount insert with the identification mark between the two curved surfaces on the toolholder.

Partial Profile 60°



L Style



| Insert Size | | Pitch | | Ordering Code | EDP No. | | Dimensions Inch | | Toolholder |
|------------------|---|---------|-------|---------------|---------|-------|-----------------|--------------|------------|
| IC | L | mm | TPI | Internal | VTX | VBX | r* | | |
| 5.0L (Mini L) | - | 0.5-1.5 | 48-16 | 5LIDA60TM... | 50264 | 50263 | .002 | TM.SC...5L | |
| | | 1.0-2.0 | 24-11 | 5LIDN60TM... | 50267 | 50266 | .002 | CTM. SC...5L | |

U Style



2UIDM60 TM...
2UIDD60 TM...




| Insert Size | | Pitch | | Ordering Code | EDP No. | | Dimensions Inch | | Toolholder |
|-------------|-----|---------|-------|---------------|---------|-------|-----------------|----------------------------|------------|
| IC | L | mm | TPI | Internal | VTX | VBX | r* | | |
| 1/4"U | .43 | 0.5-1.5 | 48-16 | 2UIDA60TM... | 50305 | 50299 | .002 | TM.SC...2U CTM. SC...2U | |
| | | 1.5-2.0 | 16-12 | 2UIDB60TM... | 50018 | 50008 | .002 | | |
| | | 2.0-2.5 | 9-12 | 2UIDD60TM... | 50355 | 50352 | .004 | CTM2SC 056C068-235-2U | |
| | | 2.5 | 10 | 2UIDM60TM... | 50296 | 50291 | .004 | | |
| 3/8"U | .63 | 1.5-2.0 | 16-12 | 3UIDB60TM... | 50040 | 50034 | .002 | TM.SC...2U CTM. SC...2U | |
| | | 2.5-3.5 | 10-7 | 3UIDE60TM... | 50044 | 50041 | .006 | TM.SC...3U | |
| | | 4.0-6.0 | 6-4 | 3UIDH60TM... | 50048 | 50045 | .001 | | |
| 1/2"U | .87 | 6.0-8.0 | 4-3 | 4UIDK60TM... | 50052 | 50049 | .012 | TM.SC D...4U | |


A Style




| Insert Size | | Pitch | | Ordering Code | EDP No. | | Dimensions Inch | | Toolholder |
|-------------|-----|---------|------|---------------|---------|-------|-----------------|------------|------------|
| IC | L | mm | TPI | Internal | VTX | VBX | r* | | |
| 1/4"A | .43 | 1.5-3.0 | 16-8 | 2AIDP60TM... | 50219 | 50200 | .002 | TM.SC...2A | |
| 3/8"A | .63 | 2.0-4.0 | 12-6 | 3AIDT60TM... | 50227 | 50226 | .003 | TM.SC...3A | |



U Style
For Large Pitches



A Style
For Shorter L2





Mini-L Style
For Small Bores and Short L2


* The indicated radius (r) refers to the insert nose radius only.

Partial Profile 55°

Internal



Mini L Style



U Style

L Style




| Insert Size | Pitch | Ordering Code | EDP No. | | Dimensions Inch | |
|---------------|-------|---------------|---------|-------|-----------------|----------------------------|
| | | | VTX | VBX | *r | Toolholder |
| IC | TPI | Internal | | | | |
| 5.0L (Mini L) | 26-14 | 5LIDR55TM... | 50269 | 50269 | .004 | TM.SC...5L CTM. SC...5L |


U Style



| Insert Size | | Pitch | Ordering Code | EDP No. | | Dimensions Inch | |
|-------------|------|-------|---------------|---------|-------|-----------------|----------------------------|
| IC | L mm | | | VTX | VBX | *r | Toolholder |
| 1/4"U | .43 | 48-16 | 2UIDA55TM... | 50317 | 50309 | .004 | TM.SC...2U CTM. SC...2U |
| | | 16-12 | 2UIDB55TM... | 50055 | 50053 | .003 | |
| | | 11-7 | 2UIDL55TM... | 50061 | 50056 | .010 | |
| 3/8"U | .63 | 16-12 | 3UIDB55TM... | 50067 | 50062 | .003 | TM.SC...3U |
| | | 11-7 | 3UIDL55TM... | 50091 | 50068 | .009 | |
| | | 6-4 | 3UIDH55TM... | 50148 | 50233 | .011 | |
| 1/2"U | .87 | 4-3 | 4UIDK55TM... | 50190 | 50189 | .020 | TM.SC D...4U |



U Style
For Large Pitches



Mini-L Style
For Small Bores and Short L2

* The indicated radius (r) refers to the insert nose radius only.

ISO Metric

Internal

Defined by: R262 (DIN 13)
Tolerance class: 6g/6H

Mini L Style
5LI2.0ISOTM...

Mini L Style

U Style


L Style

| Insert Size IC | Pitch mm | Ordering Code Internal | EDP No. | | Toolholder | Toolholder Cutting Diameter D2 (Inch) |
|-------------------|-------------|---------------------------|---------|-------|---------------------------|---------------------------------------|
| | | | VTX | VBX | | Adjusted D2 |
| 5.0L (Mini L) | 1.0 | 5LI1.0ISOTM... | 59726 | 59725 | TM.SC...5L CTM.SC...5L | - |
| | 1.5 | 5LI1.5ISOTM... | 59780 | 59779 | | - |
| | 2.0 | 5LI2.0ISOTM... | 59782 | 59781 | | - |


U Style

| Insert Size IC | L mm | Pitch mm | Ordering Code Internal | EDP No. | | Toolholder | Toolholder Cutting Diameter D2 (Inch) |
|-------------------|------|-------------|---------------------------|---------|-------|--|---------------------------------------|
| | | | | VTX | VBX | | * Adjusted D2 |
| 1/4"U | 0.43 | 1.5 | 2UI1.5ISOTM... | 50419 | 50418 | TM2SC 100W090-275-2U; TM3SC 100W102-315-2U; TM4SC 125W122-374-2U; TM2SC062C090-300-2U; TM3SC075C102-415-2U; TM4SC 100C122-452-2U; CTM3SC075C102-433-2U; CTM4SC 100C124-530-2U | For 1.5ISO change D2 to D2-.039 |
| | | 2.0 | 2UI2.0ISOTM... | 50435 | 50427 | | For 2.0ISO change D2 to D2-.045 |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.



U Style
For Large Pitches



Mini-L Style
For Small Bores and Short L2

American UN - UNC; UNF; UNEF; UNS

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2A/2B

Mini L Style
5LI14UNTM...
5LI12UNTM...

Mini L Style

U Style


L Style

| Insert Size | Pitch | Ordering Code | EDP No. | | Toolholder | Toolholder Cutting Diameter D2 (Inch) |
|------------------|-------|---------------|---------|-------|---------------------------|---------------------------------------|
| IC | TPI | Internal | VTX | VBX | | Adjusted D2 |
| 5.0L (Mini L) | 18 | 5LI18UNTM... | 59722 | 59721 | TM.SC...5L CTM.SC...5L | - |
| | 16 | 5LI16UNTM... | 59788 | 59787 | | |
| | 14 | 5LI14UNTM... | 59786 | 59785 | | |
| | 12 | 5LI12UNTM... | 59784 | 59783 | | |


U Style

| Insert Size | | Pitch | Ordering Code | EDP No. | | Toolholder | Toolholder Cutting Diameter D2 (Inch) |
|-------------|-----|-------|---------------|---------|-------|---|---------------------------------------|
| IC | L | TPI | Internal | VTX | VBX | | * Adjusted D2 |
| 1/4"U | .43 | 14 | 2UI14UNTM... | 50448 | 50447 | TM2SC100W090-275-2U; TM3SC100W102-315-2U; TM4SC125W122-374-2U; TM2SC062C090-300-2U; TM3SC075C102-415-2U; TM4SC100C122-452-2U; CTM3SC075C102-433-2U; CTM4SC100C124-530-2U | For 14UN change D2 to D2-.042 |
| | | 12 | 2UI12UNTM... | 50441 | 50436 | | For 12UN change D2 to D2-.045 |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.




U Style
For Large Pitches




Mini-L Style
For Small Bores and Short L2

NPT


External / Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT



Mini L Style



U Style

L Style




| Insert Size | Pitch | Ordering Code | EDP No. | | Toolholder Cutting Diameter D2 (Inch) | |
|------------------|-------|-------------------|---------|-------|---------------------------------------|-------------|
| IC | TPI | External/Internal | | | Toolholder | Adjusted D2 |
| 5.0L (Mini L) | 18 | 5LEI18NPT-TM... | 59724 | 59723 | TM.SC...5L CTM.SC...5L | - |

U Style




| Insert Size | | Pitch | Ordering Code | | | Toolholder Cutting Diameter D2 (Inch) | |
|----------------------|---|------------------|-------------------|-------|----------------------|---|---------------|
| IC | L | TPI | Internal/External | VTX | VBX | Toolholder | * Adjusted D2 |
| 1/4"U | 0.43 | 14 | 2UEI14NPT-TM... | 50408 | 50404 | TM1SC062W059-157-2U | .574 |
| | | | | | | CTM1SC031C059-157-2U | .574 |
| | | | | | | CTM1SC043C061-235-2U | .590 |
| | | 11.5 | 2UEI11.5NPT-TM... | 50397 | 50391 | TM2SC100W082-236-2U; CTM2SC056C082-256-2U; CTM2SC062C082-315-2U | .807 |
| | | | | | | TM2SC100W090-275-2U; TM2SC062C090-300-2U | .891 |
| | | | | | | TM3SC100W102-315-2U; TM3SC075C102-415-2U; CTM3SC075C102-433-2U | 1.009 |
| | TM4SC125W122-374-2U; TM4SC100C122-452-2U | | | | | 1.206 | |
| | CTM4SC100C124-530-2U | | | | | 1.225 | |
| | TM3SC125W143-374-3U; TM3SC125W144-570-3U; TM3SC100C143-512-3U | | | | | 1.404 | |
| | 0.63 | 3UEI11.5NPTTM... | 50461 | 50457 | TM3SC112C146-565-3U | 1.429 | |
| | | | | | TM4SC 150W165-472-3U | 1.620 | |
| | | | | | TM4SC D169-050-3U | 1.659 | |
| TM5SC D208-075-3U | | | | | 2.053 | | |
| TM3SC125W143-374-3U | | | | | 1.404 | | |
| TM3SC125W144-570-3U | | | | | | | |
| TM3SC 100C143-512-3U | | | | | | | |
| 3/8"U | 0.63 | 8 | 3UEI8NPTTM... | 50454 | 50449 | TM3SC 112C146-565-3U | 1.429 |
| | | | | | | TM4SC 150W165-472-3U | 1.620 |
| | | | | | | TM4SC D169-050-3U | 1.659 |
| | | | | | | TM5SC D208-075-3U | 2.053 |
| | | | | | | TM6SCD346-100-4U | 3.467 |
| | | | | | | TM7SCD435-150-4U | |
| 1/2"U | 0.86 | 8 | 4UEI8NPT-TM... | 50468 | 50467 | | |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.




U Style
For Large Pitches




Mini-L Style
For Small Bores and Short L2

Trapez

Internal



Defined by: DIN 103
Tolerance class: 7e/7H



Mini L Style

3/8" L

U Style

L Style



| Insert Size | Pitch | Ordering Code | EDP No. | | Application | |
|------------------|-------|-----------------|---------|-------|----------------|---|
| | | | VTX | VBX | Internal | Toolholder |
| 5.0L (Mini L) | 2.0 | 5LI2.0TR-1TM... | 50359 | 50207 | TR16x2, TR20x2 | TM.SC...5L CTM.SC...5L |
| | 2.0 | 5LI2.0TR-2TM... | 50367 | 50361 | TR18x2 | |
| 3/8" L | 6.0 | 3LI6.0TR-1TM... | 59509 | 59503 | (TR30-36)x6 | TM1SC100W085-200-3L CTM1SC050C085-295-3L |
| | 6.0 | 3LI6.0TR-2TM... | 59516 | 59515 | (TR115-130)x6 | TM7SCD315-100-3L |
| | 7.0 | 3LI7.0TRTM... | 59518 | 59517 | (TR38-44)x7 | TM2SC100W112-275-3L CTM2SC062C112-330-3L |
| | 8.0 | 3LI8.0TR-1TM... | 59571 | 59519 | (TR46-52)x8 | TM3SC125W132-350-3L CTM3SC075C132-443-3L |
| | 8.0 | 3LI8.0TR-2TM... | 59573 | 59572 | (TR175-240)x8 | TM7SCD315-100-3L |


U Style




| Insert Size | | Pitch | Ordering Code | EDP No. | | Application | |
|-------------|-----|-------|-----------------|---------|-------|----------------|-------------------|
| IC | L | | | VTX | VBX | Internal | Toolholder |
| 1/4" U | .43 | 3.0 | 2UI3.0TR-1TM... | 50383 | 50372 | (TR22-TR30)x3 | See pages 310-316 |
| | | | 2UI3.0TR-2TM... | 50389 | 50386 | (TR32-TR60)x3 | |
| | | 4.0 | 2UI4.0TR-1TM... | 50396 | 50394 | (TR20-TR28)x4 | |
| | | | 2UI4.0TR-2TM... | 50415 | 50399 | (TR65-TR110)x4 | |
| | | 5.0 | 2UI5.0TR-1TM... | 50428 | 50417 | TR22x5; TR28x5 | |
| | | | 2UI5.0TR-2TM... | 50438 | 50431 | TR24x5; TR26x5 | |

American ACME

Internal



Defined by: ANSI B1.5: 1988
Tolerance class: 3G



3/8" L

L Style




3/8" L


| Insert Size | Pitch | Ordering Code | EDP No. | | Application | |
|-------------|-------|-----------------|---------|-------|-------------|--|
| | | | VTX | VBX | Internal | Toolholder |
| 3/8" L | 5 | 3LI5ACMETM... | 59575 | 59574 | 1¼-5ACME | TM1SC100W085-200-3L CTM1SC 050C085-295-3L |
| | | 3LI4ACME-1TM... | 59577 | 59576 | 1⅜-4ACME | |
| | | 3LI4ACME-2TM... | 59579 | 59578 | 1½-4ACME | |
| | 4 | 3LI4ACME-3TM... | 59581 | 59580 | 1¾-4ACME | TM2SC100W112-275-3L CTM2SC062C112-330-3L |
| | | 3LI4ACME-4TM... | 59583 | 59582 | 2-4ACME | |
| | | 3LI3ACME-1TM... | 59585 | 59584 | 2¼-3ACME | |
| | 3 | 3LI3ACME-2TM... | 59587 | 59586 | 2½-3ACME | TM3SC125W132-350-3L CTM3SC075C132-443-3L |
| | | 3LI3ACME-3TM... | 59589 | 59588 | 2¾-3ACME | |

Stub ACME

Internal



Defined by: ANSI B1.8: 1988
Tolerance class: 2G



3/8" L

L Style




3/8" L


| Insert Size | Pitch | Ordering Code | EDP No. | | Application | |
|-------------|-------|-------------------|---------|-------|-------------|---|
| | | | VTX | VBX | Internal | Toolholder |
| 3/8" L | 5 | 3LI5STACMETM... | 59591 | 59590 | 1¼-5STACME | TM1SC100W085-200-3L CTM1SC050C085-295-3L |
| | | 3LI4STACME-1TM... | 59593 | 59592 | 1⅜-4STACME | |
| | | 3LI4STACME-2TM... | 59595 | 59594 | 1½-4STACME | |
| | 4 | 3LI4STACME-3TM... | 59597 | 59596 | 2-4STACME | TM3SC125W132-350-3L CTM3SC075C132-443-3L |
| | | 3LI3STACME-1TM... | 59599 | 59598 | 2¼-3STACME | |
| | | 3LI3STACME-2TM... | 59601 | 59600 | 2½-3STACME | |
| | 3 | 3LI3STACME-3TM... | 59603 | 59602 | 2¾-3STACME | |

American Buttress


Internal




Defined by: ANSI B1.9.1973
Tolerance class: Class 2



Mini L Style



3/8" L




5/8 V

L Style

| Insert Size | Pitch | Ordering Code | EDP No. | | Application | | |
|---|------------------|---------------|-----------------|-----------------|--|------------------|---|
| | | | IC | TPI | Internal | VTX | VBX |
|  | 5.0L (Mini L) | 16 | 5LI16ABUT-TM... | 59671 | 59670 | .875"-4.0" ABUT | TM2SC 062W055-140-5L-ABUT CTM2SC 037C055-200-5L-ABUT |
| | | | | | | 1.25"-4.0" ABUT | TM3SC 075W072-180-5L-ABUT CTM3SC 055C072-256-5L-ABUT |
| | | 12 | 5LI12ABUT-TM... | 59673 | 59672 | .875"-6.0" ABUT | TM2SC 062W055-140-5L-ABUT CTM2SC 037C055-200-5L-ABUT |
| | | | | | | 1.25"-6.0" ABUT | TM3SC 075W072-180-5L-ABUT CTM3SC 055C072-256-5L-ABUT |
| | | 10 | 5LI10ABUT-TM... | 59675 | 59674 | .875"-16.0" ABUT | TM2SC 062W055-140-5L-ABUT CTM2SC 037C055-200-5L-ABUT |
| | | | | | | 1.25"-16.0" ABUT | TM3SC 075W072-180-5L-ABUT CTM3SC 055C072-256-5L-ABUT |
| | 3/8" L | 16 | 3LI16ABUT-TM... | 59677 | 59676 | 1.75"-4.0" ABUT | TM2SC 100W104-315-3L-ABUT CTM2SC 075C104-450-3L-ABUT |
| | | | | | | 2.5"-4.0" ABUT | TM3SC 125W140-413-3L-ABUT |
| | | 12 | 3LI12ABUT-TM... | 59679 | 59678 | 1.75"-6.0" ABUT | TM2SC 100W104-315-3L-ABUT CTM2SC 075C104-450-3L-ABUT |
| | | | | | | 2.5"-6.0" ABUT | TM3SC 125W140-413-3L-ABUT |
| | | 10 | 3LI10ABUT-TM... | 59681 | 59680 | 1.75"-6.0" ABUT | TM2SC 100W104-315-3L-ABUT CTM2SC 075C104-450-3L-ABUT |
| | | | | | | 2.5"-6.0" ABUT | TM3SC 125W140-413-3L-ABUT |
| 8 | 3LI8ABUT-TM... | 59683 | 59682 | 1.75"-6.0" ABUT | TM2SC 100W104-315-3L-ABUT CTM2SC 075C104-450-3L-ABUT" | | |
| | | | | 2.5"-6.0" ABUT | TM3SC 125W140-413-3L-ABUT | | |
| 6 | 3LI6ABUT-TM... | 59685 | 59684 | 1.75"-6.0" ABUT | TM2SC 100W104-315-3L-ABUT CTM2SC 075C104-450-3L-ABUT | | |
| | | | | 2.5"-6.0" ABUT | TM3SC 125W140-413-3L-ABUT | | |
| | | | | | | 4.0"-6.0" ABUT | TM6SC D228-075-3L-ABUT |


V Style




| Insert Size | Pitch | Ordering Code | EDP No. | | Application | | |
|-------------|-------|------------------|---------|-------|-------------|-----------------|-------------------------|
| | | | IC | TPI | Internal | VTX | VBX |
| 5/8" V | 4 | 5VI4ABUT-TM... | 59687 | 59686 | .24 | 5.5"-24.0" ABUT | TM6SC D346-125-5V6-ABUT |
| | 3 | 5VI3ABUT-TM... | 59689 | 59688 | .31 | 6.0"-24.0" ABUT | TM6SC D346-125-5V8-ABUT |
| | 2.5 | 5VI2.5ABUT-TM... | 59691 | 59690 | .39 | 7.0"-24.0" ABUT | |

API Round Casing & Tubing

Internal



Defined by: API STD. 5B:1979
Tolerance class: Standard API RD




U Style



| IC | Insert Size | | Pitch | Ordering Code | EDP No. | | Toolholder | Toolholder Cutting Diameter D2 (Inch) |
|---------------------|-------------|-----|-----------------|---------------|----------|---------------------|------------|---------------------------------------|
| | L Inch | TPI | | | Internal | VTX | | VBX |
| 1/4"U | .43 | 10 | 2UI10APIRDTM... | 30158 | 30159 | TM2SC100W090-275-2U | .844 | |
| | | | | | | TM2SC062C090-300-2U | | |
| | | | | | | TM3SC100W102-315-2U | .962 | |
| 3/8"U | .63 | 8 | 3UI8APIRDTM... | 30160 | 30161 | TM3SC075C102-415-2U | | |
| | | | | | | TM4SC125W122-374-2U | 1.159 | |
| | | | | | | TM4SC100C122-452-2U | | |
| | | | | | | TM3SC125W143-374-3U | 1.366 | |
| | | | | | | TM3SC125W144-570-3U | | |
| | | | | | | TM3SC100C143-512-3U | | |
| | | | | | | TM3SC112C146-565-3U | 1.389 | |
| TM4SC150W165-472-3U | 1.583 | | | | | | | |
| TM4SCD169-050-3U | 1.622 | | | | | | | |
| TM5SCD208-075-3U | 2.016 | | | | | | | |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.

Standard Toolholders - Weldon Shank (U Style)



| Weldon Shank for U Style Inserts | | | | | | | | | | Spare Parts | | |
|----------------------------------|---------------------|---------|-----------------|------|-----|------|------|------|---|-----------------|-----------------|--|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | No. of Flutes | | |
| IC | | | L | L1 | L2 | D | D1 | D2 | Z | Insert Screw | Torx Key | |
| 1/4"U | TM1SC062W059-157-2U | 67116 | 3.76 | 1.57 | | .625 | .42 | .58* | 1 | SN2T (70036) | HK2T (70227) | |
| | TM2SC100W082-236-2U | 67117 | 4.92 | 2.36 | | 1.00 | .63 | .81* | 2 | | | |
| | TM2SC100W090-275-2U | 67722 | 5.38 | 2.75 | .21 | 1.00 | .70 | .91 | 2 | | | |
| | TM3SC100W102-315-2U | 67724 | 5.79 | 3.15 | | 1.00 | .80 | 1.02 | 3 | | | |
| 3/8"U | TM4SC125W122-374-2U | 67725 | 6.37 | 3.74 | | 1.25 | 1.01 | 1.22 | 4 | SA3T (70028) | HK3T (70228) | |
| | TM3SC125W143-374-3U | 67742 | 6.45 | 3.74 | | 1.25 | 1.14 | 1.44 | 3 | | | |
| | TM3SC125W144-570-3U | 67763 | 8.80 | 5.70 | .32 | 1.25 | 1.10 | 1.44 | 3 | | | |
| | TM4SC150W165-472-3U | 67743 | 7.82 | 4.72 | | 1.50 | 1.35 | 1.66 | 4 | SN3T (70038) | | |

Weldon Shank (U Style) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | Min. Thread Dia. | | | | | | | |
|--|------------------|---|---|-------------------------------|--|----------------------------|---|-------------------|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° | Trapez |
| TM1SC062W059-157-2U | .58* | M18x2.5; M24x3.0 | M16x0.5; M16x0.75; M16x1.0; M17x1.25; M17x1.5; M17x2.0 | 3/4-10 | 5/8-32UN; 5/8-28UN; 5/8-27UNS; 11/16-24UN; 11/16-20UN; 11/16-16UN; 3/4-14UNS; 3/4-12UN | 3/8-19; 1/2-14; 1-11 | 11/16-14; 3/4-12; 7/8-11; 3/4-10; 7/8-9; 1-8; 1 1/8-7 | TR22x3; TR24x3 |
| TM2SC100W082-236-2U | .81* | M24x3.0; M30x3.5 | M22x0.5; M22x0.75; M22x1.0; M23x1.25; M23x1.5; M23x2.0 | 1-8; 1 1/8-7; 1 3/8-6 | 7/8-32UN; 7/8-28UN; 7/8-27UNS; 7/8-24UNS; 7/8-20UNEF; 1-18UNS; 1 1/16-16UN; 1-14UNS; 1 1/16-12UN; 1-10UNS | 3/4-14; 1-11 | 1-26; 1-20; 1-16; 1-12; 1-10; 1 1/8-9; 1-8; 1 1/8-7 | (TR26- TR60)x3 |
| TM2SC100W090-275-2U | .91 | M27x3.0; M30x3.5; M36x4.0 | M24x0.5; M24x0.75; M25x1.0; M25x1.25; M26x1.5; M26x2.0; M27x2.5 | 1 1/8-7 | 1-32UN; 1-28UN; 1-27UNS; 1-24UNS; 1-20UNEF; 1-18UNS; 1-16UN; 1-14UNS; 1-12UNF; 1 1/8-10UNS; 1 1/8-8UN | 3/4-14; 1-11 | 1-26; 1-20; 1-16; 1 1/16-12; 1 1/8-9; 1 1/8-7 | - |
| TM3SC100W102-315-2U | 1.02 | M30x3.5; M36x4.0 | M27x0.5; M27x0.75; M28x1.0; M28x1.25; M28x1.5; M29x2.0; M30x2.5; M30x3.0 | 1 1/4-7; 1 3/8-6 | 1 1/8-28UN; 1 1/8-24UNS; 1 1/8-20UN; 1 1/8-18UNEF; 1 1/8-16UN; 1 1/8-14UNS; 1 1/8-12UNF; 1 1/4-10UNS; 1 3/16-8UN | 7/8-14; 1-11 | 1 1/8-26; 1 1/8-20; 1 3/8-16; 1 3/8-12; 1 3/16-8; 1 1/4-7 | - |
| TM4SC125W122-374-2U | 1.22 | M36x4.0 | M32x0.5; M32x0.75; M33x1.0; M33x1.25; M33x1.5; M34x2.0; M34x2.5; M35x3.0; M36x3.5 | 1 1/2-6 | 1 3/16-28UN; 1 3/16-24UNS; 1 3/16-20UN; 1 3/16-18UNEF; 1 3/16-16UN; 1 3/16-14UNS; 1 3/16-12UNF; 1 3/8-10UNS; 1 3/8-8UN | 1 1/8-11 | 1 3/8-26; 1 3/8-20; 1 3/8-16; 1 3/8-12; 1 7/16-8 | - |
| TM3SC125W143-374-3U TM3SC125W144-570-3U | 1.44 | M42x4.5; M48x5.0; M56x5.5; M64x6.0 | M39x1.5; M39x2.0; M40x2.5; M41x3.0; M42x3.5; M42x4.0 | 1 3/4-5; 2-4.5; 2 1/2-4 | 1 1/8-16UN; 1 1/8-14UNS; 1 1/8-12UN; 1 1/8-10UNS; 1 1/8-8UN; 1 1/8-6UN | 1 1/4-11 | 1 5/8-16; 1 5/8-12; 1 5/8-8; 1 5/8-6; 1 3/4-5 | - |
| TM4SC150W165-472-3U | 1.66 | M48x5.0; M56x5.5; M64x6.0 | M45x1.5; M45x2.0; M46x2.5; M48x3.0; M48x3.5; M48x4.0 | 2-4.5; 2 1/2-4 | 1 3/4-16UN; 1 3/4-14UNS; 1 3/16-12UN; 1 3/16-8UN; 1 1/16-6UN | 1 1/2-11 | 1 7/8-16; 1 7/8-12; 1 7/8-8; 2 1/4-6; 2-4.5 | - |

* For TR inserts use the CNC program (D2+.01").

Weldon Shank (U Style) Applications (con't)

Thread Applications for Full Profile Inserts (ISO & UN)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | | Pitch | | Min. Thread Dia. | |
|---------------------|---------------------------------------|-----|-------|----------|------------------|--|
| | * Adjusted D2 | mm | TPI | ISO Fine | UN/UNF/UNEF/UNS | |
| TM2SC100W090-275-2U | .866 | 1.5 | - | M26x1.5 | - | |
| | .860 | 2.0 | - | M26x2.0 | - | |
| | .864 | - | 14 | - | 1-14UNS | |
| | .860 | - | 12 | - | 1-12UNF | |
| TM3SC100W102-315-2U | .984 | 1.5 | - | M28x1.5 | - | |
| | .978 | 2.0 | - | M29x2.0 | - | |
| | .982 | - | 14 | - | 1 1/8-14UNF | |
| | .978 | - | 12 | - | 1 1/8-12UNF | |
| TM4SC125W122-374-2U | 1.181 | 1.5 | - | M33x1.5 | - | |
| | 1.175 | 2.0 | - | M34x2.0 | - | |
| | 1.179 | - | 14 | - | 1 3/8-14UNS | |
| | 1.175 | - | 12 | - | 1 3/8-12UNF | |

Thread Applications for Full Profile Inserts (NPT)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | | Pitch | Cylindrical or Conical Pre-Drilled Hole | Cylindrical Pre-Drilled Hole |
|---------------------|---------------------------------------|------|-------|--|--|
| | * Adjusted D2 | TPI | | NPT Threading by 1 Radial Pass | **NPT Threading by 2 Radial Passes (50% / 50%) |
| TM1SC062W059-157-2U | .574 | 14 | | 1/2-14NPT; 3/4-14NPT | - |
| TM2SC100W082-236-2U | .807 | 14 | | 3/4-14NPT | - |
| TM2SC100W090-275-2U | .891 | 11.5 | | 1-11.5NPT; 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC100W102-315-2U | 1.009 | 11.5 | | 1-11.5NPT; 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM4SC125W122-374-2U | 1.206 | 11.5 | | 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC125W143-374-3U | 1.404 | 11.5 | | 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC125W144-570-3U | | | | | |
| TM3SC125W143-374-3U | 1.404 | 8 | | - | 2 1/2...10-8NPT |
| TM3SC125W144-570-3U | | | | | |
| TM4SC150W165-472-3U | 1.620 | 11.5 | | 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM4SC150W165-472-3U | 1.620 | 8 | | - | 2 1/2...10-8NPT |


** When the pre-drilled hole for 8NPT is conical, the thread can be machined in one pass.

Thread Applications for Full Profile Inserts (API Round)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | | Pitch | Cylindrical or Conical Pre-Drilled Hole (for cylindrical 2 radial passes 50%/50%; for conical one radial pass) | Conical Pre-Drilled Hole only (one pass) | |
|---------------------|---------------------------------------|-----|-------|---|---|------------------------------|
| | * Adjusted D2 | TPI | | Thread Dia. | | |
| TM2SC100W090-275-2U | .844 | 10 | | 1.05x10APIRD (for UP TBG; UP TBG Long); 1.315...1.66x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | - | |
| TM3SC100W102-315-2U | .962 | | | 1.66...2.875x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | | |
| TM4SC125W122-374-2U | 1.159 | | | 1.66...3.5x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | | |
| TM3SC125W143-374-3U | 1.366 | 8 | | 2.375...13.375x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...5.5x8APIRD (for LCSG) | - | |
| TM3SC125W144-570-3U | | | | | 2.375...20x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...7.625x8APIRD (for LCSG) | 8.625...20x8APIRD (for LCSG) |
| TM4SC150W165-472-3U | | | 1.583 | | 2.875...20x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...7.625x8APIRD (for LCSG) | 8.625x8APIRD (for LCSG) |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.

Standard Toolholders - Carbide Cylindrical Shank (U Style)




Carbide Cylindrical Shank for U Style Inserts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | No. of Flutes | Spare Parts | |
|-------------|----------------------|---------|-----------------|----------|------|----------|-------|-------|---|-----------------|-----------------|----------|
| | | | L | L1 (max) | L2 | L3 (min) | D | D2 | Z | | Insert Screw | Torx Key |
| IC | | | | | | | | | | | | |
| 1/4"U | CTM1SC031C059-157-2U | 67121 | 4.30 | 1.57 | .21 | .65 | .3125 | .58* | 1 | SN2T (70036) | HK2T (70227) | |
| | CTM1SC043C061-235-2U | 67123 | 4.72 | 2.35 | | .90 | .4375 | .60* | 1 | | | |
| | CTM2SC056C068-235-2U | 67125 | 5.35 | 2.35 | .13 | 1.15 | .5625 | .68** | 2 | | | |
| | CTM2SC056C082-256-2U | 67122 | 5.38 | 2.56 | | 1.15 | .5625 | .81* | 2 | | | |
| | CTM2SC062C082-315-2U | 67124 | 5.30 | 3.15 | .21 | 1.28 | .625 | .81* | 2 | | | |
| | CTM3SC075C102-433-2U | 67129 | 6.50 | 4.33 | | 1.57 | .75 | 1.02* | 3 | | | |
| | CTM4SC100C124-530-2U | 67128 | 7.60 | 5.30 | 1.81 | 1.00 | 1.24* | 4 | | | | |

* For TR inserts use the CNC program (D2+.010").
 ** To be used only with inserts 2UIDD60TM... or 2UIDM60TM...
 For insert 2UIDD60 TM... use the CNC program (D2+.028").

TMSD



Carbide Cylindrical Shank (U Style) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | Min. Thread Dia. | | | | | | | |
|----------------------|------------------|---|---|--|---|---------------|---|---|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° | Trapez |
| CTM1SC031C059-157-2U | .58* | M18x2.5; M24x3.0; M30x3.5; M36x4.0 | M16x0.5; M16x0.75; M16x1.0; M17x1.25; M17x1.5; M17x2.0 | ¾-10; ¾-9; 1-8; 1½-7; 1¾-6 | ⅝-32UN; ⅝-28UN; ⅝-27UNS; 1½-24UNEF; 1½-20UN; 1½-16UN; ¾-14UNS; 1½-12UN | ½-14; 1-11 | 1½-26; 1½-20; 1½-16; 1½-14; ¾-12; ⅝-11; ¾-10; ⅞-9; 1-8; 1½-7 | TR22x3; TR24x3; TR20x4; TR22x5; TR24x5; TR26x5; TR28x5 |
| CTM1SC043C061-235-2U | .60* | M18x2.5; M24x3.0 | M16x0.5; M16x0.75; M16x1.0; M17x1.25; M17x1.5; M17x2.0 | ¾-10; ¾-9; 1-8 | ⅝-32UN; ⅝-28UN; ⅝-27UNS; 1½-24UNEF; 1½-20UN; 1½-16UN; ¾-14UNS; 1½-12UN | ½-14; 1-11 | 1½-26; 1½-20; 1½-16; 1½-14; ¾-12; ⅝-11; ¾-10; ⅞-9 | TR22x3; TR24x3 |
| CTM2SC056C068-235-2U | .68** | M20x2.5; M22x2.5 | M21x2.0 | ⅞-9 | ⅞-10UNS; 1½-12UN | - | - | - |
| CTM2SC056C082-256-2U | .81* | M24x3.0; M30x3.5; M36x4.0 | M22x0.5; M22x0.75; M22x1.0; M23x1.25; M23x1.5; M23x2.0 | 1-8; 1½-7; 1¾-6 | ⅞-32UN; ⅞-28UN; ⅞-27UNS; ⅞-24UNS; ⅞-20UNEF; 1-18UNS; 1½-16UN; 1-14UNS; 1½-12UN; 1-10UNS | ¾-14; 1-11 | 1-26; 1-20; 1-16; 1-12; 1-10; 1½-9; 1-8; 1½-7 | (TR26-TR60)x3; TR28x4; (TR65-TR110)x4; TR28x5 |
| CTM2SC062C082-315-2U | .81* | M24x3.0; M30x3.5 | M22x0.5; M22x0.75; M22x1.0; M23x1.25; M23x1.5; M23x2.0 | 1-8; 1½-7; 1¾-6 | ⅞-32UN; ⅞-28UN; ⅞-27UNS; ⅞-24UNS; ⅞-20UNEF; 1-18UNS; 1½-16UN; 1-14UNS; 1½-12UN; 1-10UNS | ¾-14; 1-11 | 1-26; 1-20; 1-16; 1-12; 1-10; 1½-9; 1-8; 1½-7 | (TR26-TR60)x3 |
| CTM3SC075C102-433-2U | 1.02* | M30x3.5; M36x4.0 | M27x0.5; M27x0.75; M28x1.0; M28x1.25; M28x1.5; M29x2.0; M30x2.5; M30x3.0 | 1¼-7; 1¾-6 | 1½-28UN; 1½-24UNS; 1½-20UN; 1½-18UNEF; 1½-16UN; 1½-14UNS; 1½-12UNF; 1¾-10UNS; 1½-8UN | ⅞-14; 1-11 | 1½-26; 1½-20; 1¾-16; 1¾-12; 1¾-8; 1¼-7 | (TR40-TR60)x3 (TR65-TR110)x4 |
| CTM4SC100C124-530-2U | 1.24* | M36x4.0 | M32x0.5; M32x0.75; M33x1.0; M33x1.25; M33x1.5; M34x2.0; M34x2.5; M35x3.0; M36x3.5 | 1½-6 | 1½-28UN; 1½-24UNS; 1½-20UN; 1½-18UNEF; 1¾-16UN; 1¾-14UNS; 1¾-12UNF; 1¾-10UNS; 1½-8UN | 1½-11 | 1¾-26; 1¾-20; 1¾-16; 1¾-12; 1¾-8 | (TR50-TR60)x3 (TR65-TR110)x4 |

* For TR inserts use the CNC program (D2+.10").

** To be used only with inserts 2UIDD60TM... or 2UIDM60TM...

For insert 2UIDD60 TM... use the CNC program (D2+.028").

Thread Applications for Full Profile Inserts (ISO & UN)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | | | Min. Thread Dia. | |
|----------------------|---------------------------------------|---------------|-----|-----|------------------|-----------------|
| | | * Adjusted D2 | mm | TPI | ISO Fine | UN/UNF/UNEF/UNS |
| CTM3SC075C102-433-2U | .984 | | 1.5 | - | M28x1.5 | - |
| | .978 | | 2.0 | - | M29x2.0 | - |
| | .982 | | - | 14 | - | 1 1/8-14UNS |
| | .978 | | - | 12 | - | 1 1/8-12UNF |
| CTM4SC100C124-530-2U | 1.181 | | 1.5 | - | M33x1.5 | - |
| | 1.175 | | 2.0 | - | M34x2.0 | - |
| | 1.179 | | - | 14 | - | 1 3/8-14UNS |
| | 1.175 | | - | 12 | - | 1 3/8-12UNF |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.


Thread Applications for Full Profile Inserts (NPT)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | Cylindrical or Conical Pre-Drilled Hole | |
|----------------------|---------------------------------------|-------|--|-----|
| | | | * Adjusted D2 | TPI |
| CTM1SC031C059-157-2U | .574 | 14 | NPT Threading by 1 Radial Pass | |
| CTM1SC043C061-235-2U | | | NPT Threading by 2 Radial Passes (50% / 50%) | |
| CTM2SC056C082-256-2U | .807 | 14 | 1/2-14NPT; 3/4-14NPT | |
| CTM2SC062C082-315-2U | | | 3/4-14NPT | |
| CTM3SC075C102-433-2U | 1.009 | 11.5 | 1-11.5NPT; 1¼-11.5NPT; 1½-11.5NPT; 2-11.5NPT | |
| CTM4SC100C124-530-2U | 1.206 | 11.5 | 1¼-11.5NPT; 1½-11.5NPT; 2-11.5NPT | |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.

TMSD

Standard Toolholders - Steel Cylindrical Shank (U Style)




| Steel Cylindrical Shank for U Style Inserts | | | | | | | | | | | | Spare Parts | | |
|---|---------------------|---------|-----------------|----------|-----|----------|------|-------|------|------|---|-----------------|-----------------|--|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | | No. of Flutes | | |
| IC | | | L | L1 (max) | L2 | L3 (min) | L4 | D | D1 | D2 | Z | Insert Screw | Torx Key | |
| 1/4"U | TM2SC062C090-300-2U | 67744 | 5.60 | 3.00 | .21 | 1.35 | 2.16 | .625 | .70 | .91 | 2 | SN2T (70036) | HK2T (70227) | |
| | TM3SC075C102-415-2U | 67745 | 7.20 | 4.15 | .21 | 1.57 | - | .75 | .75 | 1.02 | 3 | | | |
| | TM4SC100C122-452-2U | 67746 | 7.70 | 4.52 | .21 | 1.80 | - | 1.00 | 1.00 | 1.22 | 4 | | | |
| 3/8"U | TM3SC100C143-512-3U | 67747 | 8.35 | 5.12 | .31 | 1.80 | 3.08 | 1.00 | 1.14 | 1.44 | 3 | SA3T (70028) | HK3T (70228) | |
| | TM3SC112C146-565-3U | 67762 | 8.75 | 5.65 | .31 | 2.35 | 3.08 | 1.125 | 1.14 | 1.46 | 3 | | | |

Steel Cylindrical Shank (U Style) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | Min. Thread Dia. | | | | | | |
|---------------------|------------------|--------------------------------------|---|---------------------|--|--------------|--|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° |
| TM2SC062C090-300-2U | .91 | M27x3.0; M30x3.5; M36x4.0 | M24x0.5; M25x0.75; M25x1.0; M25x1.25; M26x1.5; M26x2.0; M27x2.5 | 1/8-7 | 1-32UN; 1-28UN; 1-27UN; 1-24UNS; 1-20UNEF; 1-18UNS; 1-16UN; 1-14UNS; 1/16-12UN; 1/8-10UNS; 1/8-8UN | 3/4-14; 1-11 | 1-26; 1-20; 1/8-16; 1/8-12; 1/8-9; 1/8-7 |
| TM3SC075C102-415-2U | 1.02 | M30x3.5; M36x4.0 | M27x0.5; M27x0.75; M28x1.0; M28x1.25; M28x1.5; M29x2.0; M30x2.5; M30x3.0 | 1/4-7; 1/8-6 | 1/8-28UN; 1/8-24UNS; 1/8-20UN; 1/8-18UNEF; 1/8-16UN; 1/8-14UNS; 1/8-12UNF; 1/8-10UNS; 1/8-8UN | 7/8-14; 1-11 | 1/8-26; 1/8-20; 1/8-16; 1/8-12; 1/8-8; 1/4-7 |
| TM4SC100C122-452-2U | 1.22 | M36x4.0 | M32x0.5; M32x0.75; M33x1.0; M33x1.25; M33x1.5; M34x2.0; M34x2.5; M35x3.0; M36x3.5 | 1/2-6 | 1/8-28UN; 1/8-24UNS; 1/2-20UN; 1/2-18UNEF; 1/8-16UN; 1/8-14UNS; 1/8-12UNF; 1/8-10UNS; 1/8-8UN | 1/8-11 | 1/8-26; 1/8-20; 1/8-16; 1/8-12; 1/8-8 |
| TM3SC100C143-512-3U | 1.44 | M42.5x4.5; M48x5.0; M56x5.5; M64x6.0 | M39x1.5; M40x2.5; M41x3.0; M42x3.5; M42x4.0 | 1/4-5; 2-4.5; 2/2-4 | 1/16-16UN; 1/8-14UNS; 1/16-12UN; 1/8-10UNS; 1/8-8UN; 1/8-6UN | 1/4-11 | 1/8-16; 1/8-12; 1/8-8; 1/8-6; 1/4-5 |
| TM3SC112C146-565-3U | 1.46 | M42.5x4.5; M48x5.0; M56x5.5; M64x6.0 | M39x1.5; M40x2.5; M41x3.0; M42x3.5; M42x4.0 | 1/4-5; 2-4.5; 2/2-4 | 1/16-16UN; 1/8-14UNS; 1/16-12UN; 1/8-10UNS; 1/8-8UN; 1/8-6UN | 1/4-11 | 1/8-16; 1/8-12; 1/8-8; 1/8-6; 1/4-5 |



Steel Cylindrical Shank (U Style) Applications (con't)

Thread Applications for Full Profile Inserts (ISO & UN)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | | Min. Thread Dia. | |
|---------------------|---------------------------------------|-------|-----|------------------|-----------------|
| | * Adjusted D2 | mm | TPI | ISO Fine | UN/UNF/UNEF/UNS |
| TM2SC062C090-300-2U | .866 | 1.5 | - | M26x1.5 | - |
| | .860 | 2.0 | - | M26x2.0 | - |
| | .864 | - | 14 | - | 1-14UNS |
| | .860 | - | 12 | - | 1-12UNF |
| TM3SC075C102-415-2U | .984 | 1.5 | - | M28x1.5 | - |
| | .978 | 2.0 | - | M29x2.0 | - |
| | .982 | - | 14 | - | 1 1/8-14UNS |
| | .978 | - | 12 | - | 1 1/8-12UNF |
| TM4SC100C122-452-2U | 1.181 | 1.5 | - | M33x1.5 | - |
| | 1.175 | 2.0 | - | M34x2.0 | - |
| | 1.179 | - | 14 | - | 1 3/8-14UNS |
| | 1.175 | - | 12 | - | 1 3/8-12UNF |

Thread Applications for Full Profile Inserts (NPT)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | Cylindrical or Conical Pre-Drilled Hole | Cylindrical Pre-Drilled Hole |
|---------------------|---------------------------------------|-------|--|--|
| | * Adjusted D2 | TPI | NPT Threading by 1 Radial Pass | **NPT Threading by 2 Radial Passes (50% / 50%) |
| TM2SC062C090-300-2U | .891 | 11.5 | 1-11.5NPT; 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC075C102-415-2U | 1.009 | 11.5 | 1-11.5NPT; 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM4SC100C122-452-2U | 1.206 | 11.5 | 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC100C143-512-3U | 1.404 | 11.5 | 1 1/4-11.5NPT; 1 1/2-11.5NPT; 2-11.5NPT | - |
| TM3SC112C146-565-3U | | | | |
| TM3SC100C143-512-3U | 1.404 | 8 | - | 2 1/2...10-8NPT |
| TM3SC112C146-565-3U | | | | |


** When the pre-drilled hole for 8NPT is conical, the thread can be machined in one pass.

Thread Applications for Full Profile Inserts (API Round)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | Cylindrical or Conical Pre-Drilled Hole (for cylindrical 2 radial passes 50%/50%; for conical one radial pass) | Conical Pre-Drilled Hole only (one pass) |
|---------------------|---------------------------------------|-------|--|--|
| | * Adjusted D2 | TPI | Thread Dia. | |
| TM2SC062C090-300-2U | .844 | 10 | 1.05x10APIRD (for UP TBG; UP TBG Long); 1.315...1.66x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | - |
| TM3SC075C102-415-2U | .962 | | 1.66...2.875x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | |
| TM4SC100C122-452-2U | 1.159 | | 1.66...3.5x10APIRD (for TBG; UP TBG; UP TBG Long; Integral-Joint TBG) | |
| TM3SC100C143-512-3U | 1.366 | 8 | 2.375...20x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...7.625x8APIRD (for LCSG) | 8.625...9.625x8APIRD (for LCSG) |
| TM3SC112C146-565-3U | 1.389 | | | 8.625...20x8APIRD (for LCSG) |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.

Shell Mill (U Style)



Shell Mill for U Style Inserts

Spare Parts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes |  |  |  |
|-------------|-------------------|---------|-----------------|------|-------|------|-----|---------------|---|---|---|
| IC | | | D1 | D2 | d(H7) | H | L2 | Z | Insert Screw | Torx Key | Holder Screw |
| 3/8"U | TM4SC-D169-050-3U | 67750 | 1.38 | 1.69 | .50 | 1.58 | .31 | 4 | SN3T (70038) | HK3T (70228) | 1/4-28x1.25 (70222) |
| | TM5SC-D208-075-3U | 67751 | 1.77 | 2.09 | .75 | 1.58 | .31 | 5 | | | 3/8-24x1.25 (70223) |
| 1/2"U | TM6SC-D346-100-4U | 67752 | 2.99 | 3.47 | 1.0 | 2.00 | .39 | 6 | SA4T (70032) | HK4T (70241) | 1/2-20x1.5 (70224) |
| | TM8SC-D435-150-4U | 67761 | 3.83 | 4.35 | 1.5 | 2.17 | .39 | 8 | | | 3/4-16x1.75 (70226) |

Shell Mill (U Style) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | Min. Thread Dia. | | | | | | |
|-------------------|------------------|--------------------|---------------------------------------|------------------|--|---------|---|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° |
| TM4SC-D169-050-3U | 1.69 | M56x5.5 M64x6.0 | M45x1.5; M48x2.0 M48x3.0; M48x4.0 | 2-4.5; 2½ - 4 | 1 ¹³ / ₁₆ -16UN; 1 ⁷ / ₈ -14UNS; 1 ¹³ / ₁₆ -12UN; 1 ⁷ / ₈ -10UNS; 1 ⁷ / ₈ -8UN; 1 ¹⁵ / ₁₆ -6UN | 1½ - 11 | 1 ⁷ / ₈ -16; 1 ⁷ / ₈ -12; 1 ⁷ / ₈ -8; 2 ¹ / ₈ -6; 2- 4.5; 2¼ - 4 |
| TM5SC-D208-075-3U | 2.09 | M64x6.0 | M55x1.5; M56x2.0; M58x3.0; M58x4.0 | 2½ - 4 | 2¼-16UN; 2¼-14UNS; 2¼-12UN; 2¼-10UNS; 2¼-8UN; 2 ³ / ₈ -6UN | 2 - 11 | 2¼-16; 2¼-12; 2 ³ / ₈ -8; 2 ³ / ₈ -6; 3-5; 3½-4.5 |
| TM6SC-D346-100-4U | 3.47 | - | M95x6; M125x8 | 4 - 4 | 4¼-4UN | 3½ - 11 | 4¼-4; 4-3 |
| TM8SC-D435-150-4U | 4.35 | - | M120x6; M125x8 | - | 4 ³ / ₄ -4UN | - | - |

Shell Mill (U Style) Applications (con't)

Thread Applications for Full Profile Inserts (NPT)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | Cylindrical or Conical Pre-Drilled Hole | Cylindrical Pre-Drilled Hole |
|-------------------|---------------------------------------|-------|---|--|
| | * Adjusted D2 | TPI | NPT Threading by 1 Radial Pass | **NPT Threading by 2 Radial Passes (50% / 50%) |
| TM4SC-D169-050-3U | 1.659 | 11.5 | 1½-11.5NPT; 2-11.5NPT | - |
| TM4SC-D169-050-3U | 1.659 | 8 | - | 2½...10-8NPT |
| TM5SC-D208-075-3U | 2.053 | 11.5 | 2-11.5NPT | - |
| TM5SC-D208-075-3U | 2.053 | 8 | - | 2½...10-8NPT |
| TM6SC-D346-100-4U | 3.467 | 8 | 3½"...160D-8NPT | 160D...240D-8NPT |
| TM7SC-D435-150-4U | 4.353 | 8 | 4"...160D-8NPT | 160D...240D-8NPT |


** When the pre-drilled hole for 8NPT is conical, the thread can be machined in one pass.

Thread Applications for Full Profile Inserts (API Round)

| Toolholder | Toolholder Cutting Diameter D2 (Inch) | Pitch | Cylindrical or Conical Pre-Drilled Hole (for cylindrical 2 radial passes 50%/50%; for conical one radial pass) | Conical Pre-Drilled Hole only (one pass) |
|-------------------|---------------------------------------|-------|--|---|
| | * Adjusted D2 | TPI | Thread Dia. | |
| TM4SC-D169-050-3U | 1.622 | 8 | 2.875...20x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...7.625x8APIRD (for LCSG) | 8.625...20x8APIRD (for LCSG) |
| TM5SC-D208-075-3U | 2.016 | | 3.5...20x8APIRD (for CSG; TBG; UP TBG; UP TBG Long); 4.5...7.625x8APIRD (for LCSG) | |

* Correct the toolholder cutting diameter D2 according to adjustment, as indicated in the above table.

Standard Toolholders - Weldon Shank (L Style - Mini L)



Weldon Shank for Mini-L Style Inserts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | No. of Flutes | Spare Parts | |
|------------------|--------------------------|---------|-----------------|------|------|------|-----|-----|---|---------------|--------------|----------|
| | | | L | L1 | L2 | D | D1 | D2 | Z | | Insert Screw | Torx Key |
| IC mm | | | | | | | | | | | | |
| 5.0L (Mini L) | TM1SC062W051-114-5L | 67111 | 3.20 | 1.14 | | .625 | .38 | .51 | 1 | SN5LTR | K7T | |
| | TM2SC062W054-130-5L | 67114 | 3.40 | 1.30 | .04 | .625 | .41 | .53 | 2 | | | |
| | TM3SC075W069-165-5L | 67115 | 3.80 | 1.65 | | .75 | .56 | .70 | 3 | | | |
| | TM2SC062W055-140-5L-ABUT | 67780 | 3.50 | 1.40 | | .625 | .41 | .55 | 2 | | | |
| | TM3SC075W072-180-5L-ABUT | 67781 | 4.00 | 1.80 | .074 | .75 | .56 | .72 | 3 | | | |

Weldon Shank (L Style - Mini L) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | | Min. Thread Dia. | | | | | | |
|---------------------|-----|------------------|--|--------|--|---------|-------------|----------------|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° | Trapez |
| TM1SC062W051-114-5L | .51 | M16x2 | M14x0.5; M14x0.75; M14.5x1.0; M15x1.5; M17x2.0 | 5/8-11 | 5/16-32UN; 5/16-28UN; 9/16-27UNS; 5/16-24UNEF; 5/8-20UN; 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 5/8-12UN | 3/8-19 | 5/8-14 | TR16X2; TR18X2 |
| TM2SC062W054-130-5L | .53 | M16x2 | M15x0.5; M15x0.75; M15x1.0; M16x1.5; M17x2.0 | - | 5/8-32UN; 5/8-28UN; 5/8-27UNS; 5/8-24UNEF; 5/8-20UN; 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 11/16-12UN | 3/8-19 | 11/16-14 | TR16X2; TR18X2 |
| TM3SC075W069-165-5L | .70 | - | M19x0.5; M19x0.75; M19x1.0; M20x1.5; M20x2.0 | - | 3/4-32UN; 3/4-28UN; 7/8-27UNS; 3/4-24UNS; 13/16-20UNEF; 7/8-18UNS; 13/16-16UN; 7/8-14UNF; 13/16-12UN | 1/2-14 | - | TR20X2 |

Thread Applications for Full Profile Inserts (ISO, UN, NPT)


| Toolholder | | Min. Thread Dia. | | |
|---------------------|-----|-----------------------------|--|-----------|
| | D2 | ISO Fine | UN/UNF/UNEF/UNS | NPT |
| TM1SC062W051-114-5L | .51 | M14.5x1.0; M15x1.5; M17x2.0 | 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 5/8-12UN | 3/8-18NPT |
| TM2SC062W054-130-5L | .53 | M15x1.0; M16x1.5; M17x2.0 | 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 11/16-12UN | 3/8-18NPT |
| TM3SC075W069-165-5L | .70 | M19x1.0; M20x1.5; M20x2.0 | 7/8-18UNS; 13/16-16UN; 7/8-14UNF; 13/16-12UN | - |

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | | Thread Dia. | |
|--------------------------|-----|---|--|
| | D2 | American Buttress | |
| TM2SC062W055-140-5L-ABUT | .55 | (0.875"-4")-16; (0.875"-6")-12; (0.875"-16")-10 | |
| TM3SC075W072-180-5L-ABUT | .72 | (1.25"-4")-16; (1.25"-6")-12; (1.25"-16")-10 | |


TMSD

Standard Toolholders - Carbide Cylindrical Shank (L Style - Mini L)



Carbide Cylindrical Shank for Mini-L Style Inserts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | No. of Flutes | Spare Parts | |
|------------------|---------------------------|---------|-----------------|----------|------|----------|------|-----|---|-------------------|--------------------------------|----------|
| | | | L | L1 (max) | L2 | L3 (min) | D | D2 | Z | | Insert Screw | Torx Key |
| IC | | | | | | | | | | | | |
| 5.0L (Mini L) | CTM1SC037C051-169-5L | 67118 | 4.30 | 1.69 | | .80 | .375 | .51 | 1 | SN5LTR (72007) | Torx Key K7T (70026) | |
| | CTM2SC037C053-197-5L | 67119 | 4.30 | 1.97 | .04 | .80 | .375 | .53 | 2 | | | |
| | CTM3SC056C069-255-5L | 67120 | 5.20 | 2.55 | | 1.15 | .562 | .70 | 3 | | | |
| | CTM2SC037C055-200-5L-ABUT | 67784 | 4.30 | 2.00 | | .87 | .375 | .55 | 2 | | | |
| | CTM3SC055C072-256-5L-ABUT | 67785 | 5.20 | 2.56 | .074 | 1.18 | .550 | .72 | 3 | | | |



Carbide Cylindrical Shank (L Style - Mini L) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | | Min. Thread Dia. | | | | | | | |
|----------------------|-----|------------------|--|--------|--|---------|-------------|----------------|--|
| | D2 | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) | Partial 55° | Trapez | |
| CTM1SC037C051-169-5L | .51 | M16x2 | M14x0.5; M14x0.75; M14.5x1.0; M15x1.5; M17x2.0 | 5/8-11 | 5/16-32UN; 3/16-28UN; 3/16-27UNS; 5/16-24UNEF; 5/16-20UN; 5/16-18UNF; 5/16-16UN; 5/16-14UNS; 5/16-12UN | 3/8-19 | 5/8-14 | TR16X2; TR18X2 | |
| CTM2SC037C053-197-5L | .53 | M16x2 | M15x0.5; M15x0.75; M15x1.0; M16x1.5; M17x2.0 | - | 5/8-32UN; 5/8-28UN; 5/8-27UNS; 5/8-24UNEF; 5/8-20UN; 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 11/16-12UN | 3/8-19 | 11/16-14 | TR16X2; TR18X2 | |
| CTM3SC056C069-255-5L | .70 | - | M19x0.5; M19x0.75; M19x1.0; M20x1.5; M20x2.0 | - | 3/4-32UN; 3/4-28UN; 7/8-27UNS; 3/4-24UNEF; 13/16-20UNEF; 7/8-18UNF; 13/16-16UN; 7/8-14UNF; 13/16-12UN | 1/2-14 | - | TR20X2 | |

Thread Applications for Full Profile Inserts (ISO, UN, NPT)


| Toolholder | | Min. Thread Dia. | | |
|----------------------|-----|-----------------------------|--|-----------|
| | D2 | ISO Fine | UN/UNF/UNEF/UNS | NPT |
| CTM1SC037C051-169-5L | .51 | M14.5x1.0; M15x1.5; M17x2.0 | 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 5/8-12UN | 3/8-18NPT |
| CTM2SC037C053-197-5L | .53 | M15x1.0; M16x1.5; M17x2.0 | 5/8-18UNF; 5/8-16UN; 5/8-14UNS; 11/16-12UN | 3/8-18NPT |
| CTM3SC056C069-255-5L | .70 | M19x1.0; M20x1.5; M20x2.0 | 7/8-18UNS; 13/16-16UN; 7/8-14UNF; 13/16-12UN | - |

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | | Thread Dia. | |
|---------------------------|-----|---|--|
| | D2 | American Buttress | |
| CTM2SC037C055-200-5L-ABUT | .55 | (0.875"-4")-16; (0.875"-6")-12; (0.875"-16")-10 | |
| CTM3SC055C072-256-5L-ABUT | .72 | (1.25"-4")-16; (1.25"-6")-12; (1.25"-16")-10 | |

TMSD

Standard Toolholders - Weldon Shank (L Style - 3/8" L)



Weldon Shank for 3/8" L Style Inserts

| Weldon Shank for 3/8" L Style Inserts | | | | | | | | | | Spare Parts | |
|---------------------------------------|--------------------------|---------|-----------------|------|------|------|---------------|---|---|--------------|--------------|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes |  |  | | |
| IC | Toolholder | | L | L1 | L2 | D | D1 | D2 | Z | Insert Screw | Torx Key |
| 3/8" L | TM1SC100W085-200-3L | 67135 | 4.60 | 2.00 | .276 | 1.00 | .50 | .85 | 1 | SN3T (70038) | HK3T (70228) |
| | TM2SC100W112-275-3L | 67136 | 5.32 | 2.75 | | 1.00 | .71 | 1.12 | 2 | SA3T (70028) | |
| | TM3SC125W132-350-3L | 67137 | 6.22 | 3.50 | | 1.25 | .87 | 1.32 | 3 | SN3T (70038) | |
| | TM2SC100W104-315-3L-ABUT | 67782 | 5.70 | 3.15 | .185 | 1.00 | .79 | 1.04 | 2 | SA3T (70028) | |
| | TM3SC125W140-413-3L-ABUT | 67783 | 6.75 | 4.13 | | 1.25 | 1.10 | 1.40 | 3 | | |

Weldon Shank (L Style - 3/8" L) Applications

Thread Applications for Partial Profile Inserts


| Toolholder | Min. Thread Dia. | | |
|---------------------|------------------|--------------------------------|--------------------------------|
| D2 | Trapez | American ACME | Stub ACME |
| TM1SC100W085-200-3L | .85 (TR30-36)x6 | 1 1/4-5; 1 3/8-4; 1 1/2-4 | 1 1/4-5; 1 3/8-4; 1 1/2-4 |
| TM2SC100W112-275-3L | 1.12 (TR38-44)x7 | 1 3/4-4 | - |
| TM3SC125W132-350-3L | 1.32 (TR46-52)x8 | 2-4; 2 1/4-3; 2 1/2-3; 2 3/4-3 | 2-4; 2 1/4-3; 2 1/2-3; 2 3/4-3 |

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | Thread Dia. | |
|---------------------------|-------------------|---|
| D2 | American Buttress | |
| TM2SC 100W104-315-3L-ABUT | 1.04 | (1.75"-4")-16; (1.75"-6")-12; (1.75"-6")-10; (1.75"-6")-8; (1.75"-6")-6 |
| TM3SC 125W140-413-3L-ABUT | 1.40 | (2.5"-4")-16; (2.5"-6")-12; (2.5"-6")-10; (2.5"-6")-8; (2.5"-6")-6 |

TMSD

Standard Toolholders - Carbide Cylindrical Shank (L Style - 3/8" L)



Carbide Cylindrical Shank for 3/8" L Style Inserts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | No. of Flutes | Spare Parts | |
|-------------|---------------------------|---------|-----------------|---------|-----|---------|------|------|---|---------------|--------------|----------|
| | | | L | L1(max) | L2 | L3(min) | D | D2 | Z | | Insert Screw | Torx Key |
| 3/8" L | CTM1SC050C085-295-3L | 67132 | 4.53 | 2.95 | | 1.58 | .50 | .85 | 1 | SN3T (70038) | HK3T (70228) | |
| | CTM2SC062C112-330-3L | 67133 | 6.10 | 3.30 | .28 | 1.81 | .625 | 1.12 | 2 | SA3T (70028) | | |
| | CTM3SC075C132-443-3L | 67134 | 6.60 | 4.43 | | 1.81 | .75 | 1.32 | 3 | SN3T (70038) | | |
| | CTM2SC075C104-450-3L-ABUT | 67786 | 6.75 | 4.35 | .19 | 1.57 | .75 | 1.04 | 2 | SA3T (70028) | | |


Carbide Cylindrical Shank (L Style - 3/8" L) Applications

Thread Applications for Partial Profile Inserts


| Toolholder | Min. Thread Dia. | | | |
|----------------------|------------------|-------------|-----------------------|-----------------------|
| | D2 | Trapez | American ACME | Stub ACME |
| CTM1SC050C085-295-3L | .85 | (TR30-36)x6 | 1¼-5; 1⅜-4; 1½-4 | 1¼-5; 1⅜-4; 1½-4 |
| CTM2SC062C112-330-3L | 1.12 | (TR38-44)x7 | 1¾-4 | - |
| CTM3SC075C132-443-3L | 1.32 | (TR46-52)x8 | 2-4; 2¼-3; 2½-3; 2¾-3 | 2-4; 2¼-3; 2½-3; 2¾-3 |

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | Thread Dia. | |
|---------------------------|-------------|---|
| | D2 | American Buttress |
| CTM2SC075C104-450-3L-ABUT | 1.04 | (1.75"-4")-16; (1.75"-6")-12; (1.75"-6")-10; (1.75"-6")-8; (1.75"-6")-6 |



Shell Mill (L Style - 3/8" L)



Shell Mill for 3/8" L Style Inserts

| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | No. of Flutes | Spare Parts | | |
|-------------|------------------------|---------|-----------------|------|-------|------|------|---|-----------------|-----------------|---------------------------|--------------|
| | | | D1 | D2 | d(H7) | H | L2 | Z | | Insert Screw | Torx Key | Holder Screw |
| 3/8" L | TM7SC-D315-125-3L | 67775 | 2.72 | 3.15 | 1.25 | 2.16 | .276 | 7 | SA3T (70028) | HK3T (70228) | 5/8-18UNx1 1/2 (70037) | |
| | TM6SC-D228-075-3L-ABUT | 67788 | 2.01 | 2.28 | .75 | 1.58 | .185 | 6 | | | 3/8-24x1.25 (70223) | |

TMSD

Shell Mill (L Style - 3/8" L) Applications


Thread Applications for Partial Profile Inserts

| Toolholder | Min. Thread Dia. | | | |
|-------------------|------------------|----------------------------------|---------------|-----------|
| | D2 | Trapez | American ACME | Stub ACME |
| TM7SC-D315-125-3L | 3.15 | (TR115-TR130)x6; (TR175-TR240)x8 | - | - |

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | Thread Dia. | |
|------------------------|-------------|--|
| | D2 | American Buttress |
| TM6SC-D228-075-3L-ABUT | 2.28 | (4.0"-6")-12; (4.0"-6")-10; (4.0"-6")-8; (4.0"-6")-6 |

Shell Mill (5/8" V Style)



Shell Mill for 5/8" V Style Inserts

| Shell Mill for 5/8" V Style Inserts | | | | | | | | | Spare Parts | | | |
|-------------------------------------|-------------------------|---------|-----------------|------|-------|------|-----|---------------|------------------|---|---|---|
| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | No. of Flutes | |  |  |  |
| IC | Toolholder | | D1 | D2 | d(H7) | H | L2 | Z | Insert | Insert Screw | Torx Key | Holder Screw |
| 5/8"V | TM6SC-D346-125-5V6-ABUT | 67768 | 2.85 | 3.46 | 1.25 | 1.92 | .21 | 6 | 5V14ABUT-TM... | SA5 (70033) | HK5T (70011) | 5/8-18UNx1 1/2 (70037) |
| | TM6SC-D346-125-5V8-ABUT | 67789 | 2.85 | 3.46 | 1.25 | 2.07 | .33 | 6 | 5V12.5ABUT-TM... | | | |
| | | | | | | 2.00 | .28 | | 5V13ABUT-TM... | | | |


Shell Mill (5/8" V Style) Applications

Thread Applications for Full Profile American Buttress Inserts

| Toolholder | D2 | Thread Dia. |
|-------------------------|------|------------------------------|
| | | American Buttress |
| TM6SC-D346-125-5V6-ABUT | 3.46 | (5.0"-24")-4 |
| TM6SC-D346-125-5V8-ABUT | 3.46 | (6.0"-24")-3; (7.0"-24")-2.5 |

TMSD

Standard Toolholders - Steel Cylindrical Shank (A Style)



Steel Cylindrical Shank for A-Style Inserts


| Insert Size | Ordering Code | EDP No. | Dimensions Inch | | | | | | | | No. of Flutes | Spare Parts | |
|-------------|---------------------|---------|-----------------|---------|-----|----------|------|------|------|------|---------------|--------------|--------------|
| | | | L | L1(max) | L2 | L3 (min) | L4 | D | D1 | D2 | | Z | Insert Screw |
| 1/4"A | TM3SC075C102-415-2A | 67748 | 7.20 | 4.15 | .12 | 1.57 | - | .75 | .75 | 1.02 | 3 | SN2T (70036) | HK2T (70227) |
| 3/8"A | TM3SC100C138-512-3A | 67749 | 8.35 | 5.12 | .16 | 1.80 | 3.08 | 1.00 | 1.11 | 1.39 | 3 | SA3T (70028) | HK3T (70228) |

TMSD

Steel Cylindrical Shank (A Style) Applications

Thread Applications for Partial Profile Inserts

| Toolholder | D2 | Min. Thread Dia. | | | | |
|---------------------|------|------------------|------------------------------------|-----|---|---------|
| | | ISO Coarse | ISO Fine | UNC | UN/UNF/UNEF/UNS | BSP (G) |
| TM3SC075C102-415-2A | 1.02 | - | M28x1.5; M29x2.0; M30x2.5; M30x3.0 | - | 1 1/8-16UN; 1 1/8-14UNS; 1 3/16-12UN; 1 1/4-10UNS; 1 3/16-8UN | - |
| TM3SC100C138-512-3A | 1.39 | - | M38x2.0; M39x2.5; M39x3.0; M40x4.0 | - | 1 1/2-12UN; 1 1/2-10UNS; 1 1/8-8UN; 1 1/8-6UN | - |



Recommended Grades, Cutting Speeds Vc [ft/min] and Feed f [inch/tooth]

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | Feed* f [inch/tooth] by Cutting Dia. (D2) | | | |
|-------------------------------------|------------------------------|--|------------------------------------|-------------|----------|---|-------------|-------------|-------------|
| | | | | VBX | VTX | .51-.91 | .94-1.65 | Shell Mill | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 328-689 | 295-590 | .0079-.0126 | .0118-.0197 | .0118-.0295 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 328-590 | 295-558 | .0079-.0126 | .0118-.0197 | .0118-.0295 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 328-558 | 295-525 | .0059-.0091 | .0098-.0138 | .0098-.0205 |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 197-295 | 295-508 | .0067-.011 | .011-.0177 | .011-.0264 |
| | 5 | | Hardened | 275 | 262-492 | 262-525 | .0059-.011 | .0098-.0177 | .0098-.0264 |
| | 6 | | Hardened | 350 | 230-459 | 230-492 | .0059-.0098 | .0098-.0157 | .0098-.0236 |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 197-426 | 230-377 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| | 8 | | Hardened | 325 | 230-361 | 197-328 | .0051-.0083 | .0071-.0118 | .0071-.0177 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 328-558 | 328-558 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 230-394 | 230-426 | .0047-.0087 | .0067-.0118 | .0067-.0177 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 328-558 | 394-590 | .0059-.0087 | .0087-.0134 | .0087-.0197 |
| | 12 | | Hardened | 330 | 328-558 | 394-590 | .0063-.0091 | .0083-.0126 | .0083-.0189 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 230-459 | 328-459 | .0059-.0098 | .0098-.0157 | .0098-.0236 |
| | 14 | | Super Austenitic | 200 | 230-459 | 328-459 | .0047-.0079 | .0067-.0102 | .0067-.0154 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 230-459 | 328-459 | .0063-.0094 | .0098-.0146 | .0098-.0217 |
| | 16 | | Hardened | 330 | 230-459 | 328-459 | .0047-.0079 | .0067-.0102 | .0067-.0154 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 230-394 | 328-394 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| | 18 | | Hardened | 330 | 230-394 | 328-394 | .0047-.0079 | .0067-.0102 | .0067-.0154 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 197-426 | 328-394 | .0063-.0094 | .0098-.0146 | .0098-.0217 |
| | 29 | | Pearlitic (long chips) | 230 | 197-394 | 262-328 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 197-426 | 262-328 | .0059-.0087 | .0087-.0134 | .0087-.0197 |
| | 31 | | High Tensile Strength | 260 | 197-328 | 262-328 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 197-410 | 262-328 | .0039-.0079 | .0059-.0098 | .0059-.0146 |
| | 33 | | Pearlitic | 260 | 164-295 | 197-295 | .0059-.0087 | .0079-.0118 | .0079-.0177 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-820 | | .0118-.0197 | .0236-.0394 | .0236-.0591 |
| | 35 | | Aged | 100 | 328-590 | | .011-.0197 | .0197-.0354 | .0197-.0472 |
| | 36 | Aluminium Alloys | Cast | 75 | 492-1312 | | .011-.0197 | .0197-.0354 | .0197-.0472 |
| | 37 | | Cast & Aged | 90 | 492-918 | | .0098-.0157 | .0157-.0236 | .0157-.0354 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 262-492 | | .011-.0197 | .0197-.0354 | .0197-.0472 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 394-689 | 328-656 | .0118-.0197 | .0236-.0394 | .0236-.0591 |
| 40 | Bronze and Non Leaded Copper | | 100 | 394-689 | 328-656 | .011-.0197 | .0197-.0354 | .0197-.0472 | |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 66-148 | 66-131 | .0035-.0059 | .0047-.0087 | .0047-.013 |
| | 20 | | Aged (iron based) | 280 | 66-98 | 66-98 | .0028-.0051 | .0039-.0079 | .0039-.0118 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 49-66 | 49-66 | .0031-.0059 | .0031-.0079 | .0031-.0118 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 33-49 | 33-49 | .0031-.0059 | .0031-.0079 | .0031-.0118 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 230-459 | 230-394 | .0028-.0051 | .0039-.0079 | .0039-.0118 |
| 24 | α+β alloys | | 1050Rm | 66-164 | 66-164 | .0028-.0051 | .0039-.0079 | .0039-.0118 | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 49-148 | 49-148 | .002-.0047 | .002-.0071 | .002-.0106 |
| | 26 | | | 51-55HRc | 49-131 | 49-131 | .002-.0047 | .002-.0071 | .002-.0106 |

* When using a Shell Mill toolholder, the feed can be increased by 50%.
 * For 3/8"L it is recommended to machine in two passes and decrease the feed by 40%.

Grades

| Grade | Application |
|------------|--|
| VBX | TiCN coated carbide grade. Excellent grade for Steels and General Use. |
| VTX | TiAlN coated carbide grade. Ideal for Stainless Steels. |



TMSD



TM Solid

Solid Carbide Thread Milling Tools

Vardex Ordering Code System

TM Solid Carbide

| | | | | | | | | | | | |
|-----------|----------|-----------|------------|------------|----------|----------|-----------|------------|-----------|-----------|------------|
| HC | | 19 | 141 | L03 | - | I | 24 | UNC | TM | | VTH |
| 1 | 2 | 3 | 4 | 5 | | 6 | 7 | 8 | 9 | 10 | 11 |

| 1 - Line | 2 - No. of Teeth | 3 - Shank Dia. | 4 - Cutting Dia. | 5 - Tool Cutting Length | 6 - Type of Tool |
|---|--|--|------------------|-------------------------|--|
| HC - Helicool HCR - Helicool R HCC - Helicool C H - Helical S - Straight Flutes D - Deep Threading or MilliPro | 1T - 1 Tooth 3T - 3 Teeth (MilliPro) 2L - 2 Teeth LH (MilliPro HD) | 12 - 1/8" 19 - 3/16" 25 - 1/4" 31 - 5/16" 37 - 3/8" 50 - 1/2" 63 - 5/8" 75 - 3/4" | .028-.746 | Up to 3Do | E - External I - Internal EI - External + Internal |

| 7 - Pitch | 8 - Standard | 9 - System | 10 - No. of Flutes | 11 - Carbide Grade | | | | | | | | | | | | | | | | | | | | | | |
|---|--------------|------------|--------------------|--------------------|--|----|-----|----|---------|-------|----|---------|-------|----|----------|-------|----|----------|-------|----|----------|-------|---|------------------------|---|------------|
| Full Profile - Pitch Range <table border="1"> <tr> <th>mm</th> <th>TPI</th> </tr> <tr> <td>0.25-6.0</td> <td>80 - 4.5</td> </tr> </table> Partial Profile - Pitch Range <table border="1"> <tr> <th></th> <th>mm</th> <th>TPI</th> </tr> <tr> <td>TA</td> <td>0.5-0.8</td> <td>32-56</td> </tr> <tr> <td>TB</td> <td>0.5-1.0</td> <td>24-56</td> </tr> <tr> <td>TC</td> <td>1.0-1.50</td> <td>16-24</td> </tr> <tr> <td>TD</td> <td>1.0-1.75</td> <td>14-24</td> </tr> <tr> <td>TF</td> <td>0.5-1.25</td> <td>20-48</td> </tr> </table> | mm | TPI | 0.25-6.0 | 80 - 4.5 | | mm | TPI | TA | 0.5-0.8 | 32-56 | TB | 0.5-1.0 | 24-56 | TC | 1.0-1.50 | 16-24 | TD | 1.0-1.75 | 14-24 | TF | 0.5-1.25 | 20-48 | 60 - Partial Profile 60° ISO - ISO Metric UN - American UN UNC - UN Coarse UNF - UN Fine UNEF - UN Extra Fine UNJ - UNJ MJ - MJ BSW - Whitworth Coarse BSP - BSP BSF - Whitworth Fine BSPT - BSPT NPT - NPT ANPT - ANPT NPTF - NPTF NPS - NPS PG - PG TP60 - Taper 60° TP55 - Taper 55° | TM TML - Extra Long | 3 - 3 Flutes 5 - 5 Flutes * For straight flutes only. | VTS VTH |
| mm | TPI | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.25-6.0 | 80 - 4.5 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | mm | TPI | | | | | | | | | | | | | | | | | | | | | | | | |
| TA | 0.5-0.8 | 32-56 | | | | | | | | | | | | | | | | | | | | | | | | |
| TB | 0.5-1.0 | 24-56 | | | | | | | | | | | | | | | | | | | | | | | | |
| TC | 1.0-1.50 | 16-24 | | | | | | | | | | | | | | | | | | | | | | | | |
| TD | 1.0-1.75 | 14-24 | | | | | | | | | | | | | | | | | | | | | | | | |
| TF | 0.5-1.25 | 20-48 | | | | | | | | | | | | | | | | | | | | | | | | |

HTC Thriller

| | | | | |
|------------|-----------|------------|-----------|------------|
| HTC | M6 | 1.0 | 2D | VTN |
| 1 | 2 | 3 | 4 | 5 |

| 1 - Line | 2 - Thread Diameter | 3 - Pitch | 4 - Thread Length | 5 - Carbide Grade |
|----------------|---------------------|------------|-------------------|-------------------|
| HTC - Thriller | M6 - M12 | 1 - 1.75mm | 2D 2.5D | VTN VTS |

Miniature Threads MilliPro

MilliPro &
MilliPro EL
From 1-72UNF (M1.6x0.35)



MilliPro HD
Up to 62 HRC

MilliPro Dental
From 0-80UNF (M1.0x0.25)

Long Thread Deep Threading

Full Profile



Partial Profile

Up to 3XDo

Normal Use Straight Flutes

Taper
For Bone Plate Applications
From Pitch 0.3-0.6mm



From No.8-36UNF (M4.5x0.75)

Heavy Duty Helicool



From No.10-32UNF (M3x0.5)

Radial Coolant Helicool-R (HCR)



From No.10-32UNF (M6x1.0)

Helicool and Chamfer Helicool-C (HCC)



From No.10-32UNF (M6x1.0)

Economical Tool He-Lex

Taper
For Bone Plate Applications
From Pitch 0.3-0.6mm




From No.10-32UNF (M3x0.5)

Drill, Thread and Chamfer HTC



From M6x1.0



Defined by: R262 (DIN 13)
Tolerance class: 6H

Helical Flutes with Thru-Hole Coolant

1.5 x Do (Le ≤ 1.5 x Thread Diameter)


| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------|--------------|-------|--------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | HC19094L01-I0.50ISOTM... | 80337 | 3/16 | .094 | 1.772 | .187 | 3 | 9 | .098 |
| M4x0.7 | | 0.7 | HC19124L02-I0.70ISOTM... | 80355 | 3/16 | .124 | 1.772 | .262 | 3 | 9 | .129 |
| M5x0.8 | | 0.8 | HC19159L02-I0.80ISOTM... | 80356 | 3/16 | .159 | 2.244 | .299 | 3 | 9 | .165 |
| M6x1.0 | M8-M40x1.0 | 1.0 | HC25189L03-I1.00ISOTM... | 80343 | 1/4 | .189 | 2.244 | .374 | 3 | 9 | .197 |
| M8x1.25 | | 1.25 | HC31256L05-I1.25ISOTM... | 80357 | 5/16 | .256 | 2.402 | .524 | 3 | 10 | .268 |
| M10x1.5 | M12-M48x1.5 | 1.5 | HC37323L06-I1.50ISOTM... | 80346 | 3/8 | .323 | 2.874 | .620 | 3 | 10 | .335 |
| M12x1.75 | | 1.75 | HC37370L07-I1.75ISOTM... | 80358 | 3/8 | .370 | 2.874 | .724 | 4 | 10 | .405 |
| M14x2.0 | M17-M80x2.0 | 2.0 | HC50457L08-I2.00ISOTM... | 80351 | 1/2 | .457 | 2.874 | .827 | 4 | 10 | .472 |
| M16x2.0 | M17-M80x2.0 | 2.0 | HC63535L09-I2.00ISOTM... | 80353 | 5/8 | .535 | 3.622 | .984 | 4 | 12 | .551 |

Helical Flutes with Thru-Hole Coolant

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------|--------------|-------|--------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | HC19094L02-I0.50ISOTM... | 80336 | 3/16 | .094 | 1.772 | .246 | 3 | 12 | .098 |
| | M4x0.5 | 0.5 | HC19126L03-I0.50ISOTM... | 80338 | 3/16 | .126 | 1.772 | .325 | 3 | 16 | .138 |
| | M5x0.5 | 0.5 | HC25165L04-I0.50ISOTM... | 80339 | 1/4 | .165 | 2.244 | .404 | 3 | 20 | .177 |
| M4x0.7 | | 0.7 | HC19124L03-I0.70ISOTM... | 80284 | 3/16 | .124 | 1.772 | .344 | 3 | 12 | .129 |
| | M6x0.75 | 0.75 | HC25197L04-I0.75ISOTM... | 80340 | 1/4 | .197 | 2.244 | .487 | 3 | 16 | .209 |
| M5x0.8 | | 0.8 | HC19159L04-I0.80ISOTM... | 80341 | 3/16 | .159 | 2.244 | .425 | 3 | 13 | .165 |
| M6x1.0 | M8-M40x1.0 | 1.0 | HC25189L04-I1.00ISOTM... | 80342 | 1/4 | .189 | 2.244 | .492 | 3 | 12 | .197 |
| | M8x1.0 | 1.0 | HC31264L06-I1.00ISOTM... | 80344 | 5/16 | .264 | 2.402 | .650 | 3 | 16 | .276 |
| | M10x1.0 | 1.0 | HC37343L08-I1.00ISOTM... | 80285 | 3/8 | .343 | 2.874 | .807 | 3 | 20 | .354 |
| | M12x1.0 | 1.0 | HC50421L09-I1.00ISOTM... | 80286 | 1/2 | .421 | 2.874 | .965 | 4 | 24 | .433 |
| M8x1.25 | | 1.25 | HC31256L06-I1.25ISOTM... | 80287 | 5/16 | .256 | 2.402 | .664 | 3 | 13 | .268 |
| | M10x1.25 | 1.25 | HC37335L08-I1.25ISOTM... | 80345 | 3/8 | .335 | 2.874 | .812 | 3 | 16 | .346 |
| M10x1.5 | M12-M48x1.5 | 1.5 | HC37323L07-I1.50ISOTM... | 80288 | 3/8 | .323 | 2.874 | .797 | 3 | 13 | .335 |
| | M12x1.5 | 1.5 | HC37370L09-I1.50ISOTM... | 80347 | 3/8 | .370 | 2.874 | .974 | 4 | 16 | .413 |
| | M14x1.5 | 1.5 | HC50469L11-I1.50ISOTM... | 80348 | 1/2 | .469 | 3.150 | 1.152 | 4 | 19 | .492 |
| | M16x1.5 | 1.5 | HC63547L12-I1.50ISOTM... | 80349 | 5/8 | .547 | 3.150 | 1.270 | 4 | 21 | .571 |
| M12x1.75 | | 1.75 | HC37370L09-I1.75ISOTM... | 80350 | 3/8 | .370 | 2.874 | .999 | 4 | 14 | .405 |
| M14x2.0 | M17-M80x2.0 | 2.0 | HC50457L11-I2.00ISOTM... | 80289 | 1/2 | .457 | 3.150 | 1.142 | 4 | 14 | .472 |
| M16x2.0 | M17-M80x2.0 | 2.0 | HC63535L12-I2.00ISOTM... | 80352 | 5/8 | .535 | 3.622 | 1.299 | 4 | 16 | .551 |
| M18x2.5 | | 2.5 | HC63583L14-I2.50ISOTM... | 80354 | 5/8 | .583 | 3.622 | 1.427 | 4 | 14 | .598 |
| M20x2.5 | | 2.5 | HC75673L16-I2.50ISOTM... | 80290 | 3/4 | .673 | 4.016 | 1.624 | 4 | 16 | .687 |
| M24x3.0 | | 3.0 | HC75746L19-I3.00ISOTM... | 80359 | 3/4 | .746 | 4.016 | 1.949 | 4 | 16 | .827 |

*Bore diameter applies to smallest thread dia.



Helical Flutes with Thru-Hole Coolant

1.5 x Do (Le ≤ 1.5 x Thread Diameter)


| Thread | | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------|----------------|--------------------|-------|------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| UNC | UNF | UNEF | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| No.10-24 | 5/16"; 3/8"x24 | 9/16"-11/16"x24 | 24 | HC19141L03-I24UNCTM... | 80360 | 3/16 | .141 | 1.772 | .312 | 3 | 7 | .150 |
| No.12-24 | 5/16"; 3/8"x24 | 9/16"-11/16"x24 | 24 | HC25163L03-I24UNCTM... | 80361 | 1/4 | .163 | 2.244 | .354 | 3 | 8 | .177 |
| 1/4"x20 | 7/16"; 1/2"x20 | 3/4"-1"x20 | 20 | HC25192L03-I20UNCTM... | 80362 | 1/4 | .192 | 2.244 | .375 | 3 | 7 | .201 |
| 5/16"x18 | 9/16"; 5/8"x18 | 11/16"-1 11/16"x18 | 18 | HC31242L04-I18UNCTM... | 80363 | 5/16 | .242 | 2.402 | .472 | 3 | 8 | .260 |
| 3/8"x16 | 3/4"x16 | | 16 | HC31301L05-I16UNCTM... | 80364 | 5/16 | .301 | 2.402 | .594 | 3 | 9 | .315 |
| 7/16"x14 | 7/8"x14 | | 14 | HC37354L06-I14UNCTM... | 80365 | 3/8 | .354 | 2.874 | .678 | 3 | 9 | .370 |
| 1/2"x13 | | | 13 | HC50407L08-I13UNCTM... | 80366 | 1/2 | .407 | 3.150 | .808 | 4 | 10 | .429 |
| 9/16"x12 | 1"-1 1/2"x12 | | 12 | HC50465L08-I12UNCTM... | 80367 | 1/2 | .465 | 3.150 | .875 | 4 | 10 | .484 |

Helical Flutes with Thru-Hole Coolant

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------|----------------|--------------------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| UNC | UNF | UNEF | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| | No.10-32 | No.12-3/8"x32 | 32 | HC19150L03-I32UNFTM... | 80291 | 3/16 | .150 | 1.772 | .391 | 3 | 12 | .157 |
| | | No.12-3/8"x32 | 32 | HC25173L04-I32UNEFTM... | 80292 | 1/4 | .173 | 2.244 | .453 | 3 | 14 | .185 |
| | No.12; 1/4"x28 | 7/16"; 1/2"x28 | 28 | HC25169L04-I28UNFTM... | 80293 | 1/4 | .169 | 2.244 | .446 | 3 | 12 | .181 |
| | 1/4"x28 | 7/16"; 1/2"x28 | 28 | HC25203L05-I28UNFTM... | 80294 | 1/4 | .203 | 2.244 | .518 | 3 | 14 | .216 |
| | | 7/16"; 1/2"x28 | 28 | HC37371L08-I28UNEFTM... | 80295 | 3/8 | .371 | 2.874 | .875 | 3 | 24 | .401 |
| No.10-24 | 5/16"; 3/8"x24 | 9/16"-11/16"x24 | 24 | HC19141L04-I24UNCTM... | 80296 | 3/16 | .141 | 1.772 | .396 | 3 | 9 | .150 |
| No.12-24 | 5/16"; 3/8"x24 | 9/16"-11/16"x24 | 24 | HC25163L04-I24UNCTM... | 80297 | 1/4 | .163 | 2.244 | .437 | 3 | 10 | .177 |
| | 5/16"; 3/8"x24 | 9/16"-11/16"x24 | 24 | HC31263L06-I24UNFTM... | 80298 | 5/16 | .263 | 2.402 | .646 | 3 | 15 | .272 |
| | 3/8"x24 | 9/16"-11/16"x24 | 24 | HC37323L07-I24UNFTM... | 80299 | 3/8 | .323 | 2.874 | .771 | 3 | 18 | .335 |
| | | 9/16"-11/16"x24 | 24 | HC50496L11-I24UNEFTM... | 80300 | 1/2 | .496 | 3.150 | 1.145 | 4 | 27 | .520 |
| 1/4"x20 | 7/16"; 1/2"x20 | 3/4"-1"x20 | 20 | HC25192L05-I20UNCTM... | 80301 | 1/4 | .192 | 2.244 | .525 | 3 | 10 | .201 |
| | 7/16"; 1/2"x20 | 3/4"-1"x20 | 20 | HC37362L08-I20UNFTM... | 80302 | 3/8 | .362 | 2.874 | .875 | 3 | 17 | .390 |
| | 1/2"x20 | 3/4"-1"x20 | 20 | HC50437L10-I20UNFTM... | 80303 | 1/2 | .437 | 3.150 | 1.025 | 4 | 20 | .453 |
| | | 3/4"-1"x20 | 20 | HC75685L15-I20UNEFTM... | 80304 | 3/4 | .685 | 4.016 | 1.525 | 4 | 30 | .701 |
| 5/16"x18 | 9/16"; 5/8"x18 | 11/16"-1 11/16"x18 | 18 | HC31242L06-I18UNCTM... | 80305 | 5/16 | .242 | 2.402 | .639 | 3 | 11 | .260 |
| | 9/16"; 5/8"x18 | 11/16"-1 11/16"x18 | 18 | HC50492L11-I18UNFTM... | 80306 | 1/2 | .492 | 3.150 | 1.139 | 4 | 20 | .512 |
| | 5/8"x18 | 11/16"-1 11/16"x18 | 18 | HC63555L12-I18UNFTM... | 80307 | 5/8 | .555 | 3.622 | 1.250 | 4 | 22 | .575 |
| 3/8"x16 | 3/4"x16 | | 16 | HC31301L07-I16UNCTM... | 80308 | 5/16 | .301 | 2.402 | .781 | 3 | 12 | .315 |
| | 3/4"x16 | | 16 | HC75669L15-I16UNFTM... | 80309 | 3/4 | .669 | 4.016 | 1.528 | 4 | 24 | .689 |
| 7/16"x14 | 7/8"x14 | | 14 | HC37354L08-I14UNCTM... | 80310 | 3/8 | .354 | 2.874 | .893 | 3 | 12 | .370 |
| | 7/8"x14 | | 14 | HC75746L17-I14UNFTM... | 80311 | 3/4 | .746 | 4.016 | 1.750 | 4 | 24 | .807 |
| 1/2"x13 | | | 13 | HC50407L10-I13UNCTM... | 80312 | 1/2 | .407 | 3.150 | 1.039 | 4 | 13 | .430 |
| 9/16"x12 | 1"-1 1/2"x12 | | 12 | HC50465L11-I12UNCTM... | 80313 | 1/2 | .465 | 3.150 | 1.125 | 4 | 13 | .484 |
| | 1"-1 1/2"x12 | | 12 | HC75746L20-I12UNFTM... | 80314 | 3/4 | .746 | 4.016 | 2.042 | 4 | 24 | .925 |
| 5/8"x11 | | | 11 | HC63516L13-I11UNCTM... | 80315 | 5/8 | .516 | 3.622 | 1.318 | 4 | 14 | .539 |
| 3/4"x10 | | | 10 | HC63622L15-I10UNCTM... | 80316 | 5/8 | .622 | 3.622 | 1.550 | 4 | 15 | .657 |
| 7/8"x9 | | | 9 | HC75746L18-I9UNCTM... | 80317 | 3/4 | .746 | 4.016 | 1.833 | 4 | 16 | .768 |
| 1"x8 | | | 8 | HC75746L20-I8UNCTM... | 80318 | 3/4 | .746 | 4.016 | 2.063 | 4 | 16 | .866 |

* Bore diameter applies to smallest thread dia.




Defined by: B.S.84:1956,
DIN 259, ISO228/1:1982
Tolerance class: Medium class A

Helical Flutes with Thru-Hole Coolant

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------|-----------------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| BSW | BSF | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| | 1/4"x26 | 26 | HC25197L05-EI26BSFTM... | 80368 | 1/4 | .197 | 2.244 | .519 | 3 | 13 | .209 |
| | 5/16"x22 | 22 | HC31250L06-EI22BSFTM... | 80369 | 5/16 | .250 | 2.402 | .659 | 3 | 14 | .264 |
| 1/4"x20 | 3/8"x20 | 20 | HC25175L05-EI20BSWTM... | 80370 | 1/4 | .175 | 2.244 | .525 | 3 | 10 | .197 |
| | 3/8"x20 | 20 | HC31301L07-EI20BSFTM... | 80371 | 5/16 | .301 | 2.402 | .775 | 3 | 15 | .323 |
| 5/16"x18 | 7/16"x18 | 18 | HC25230L06-EI18BSWTM... | 80372 | 1/4 | .230 | 2.244 | .639 | 3 | 11 | .256 |
| | 7/16"x18 | 18 | HC37362L09-EI18BSFTM... | 80373 | 3/8 | .362 | 2.874 | .917 | 3 | 16 | .382 |
| 3/8"x16 | 1/2", 9/16"x16 | 16 | HC31283L07-EI16BSWTM... | 80374 | 5/16 | .283 | 2.402 | .781 | 3 | 12 | .311 |
| | 1/2", 9/16"x16 | 16 | HC50413L10-EI16BSFTM... | 80375 | 1/2 | .413 | 2.874 | 1.031 | 4 | 16 | .437 |
| | 9/16"x16 | 16 | HC50478L11-EI16BSFTM... | 80376 | 1/2 | .478 | 3.150 | 1.156 | 4 | 18 | .496 |
| 7/16"x14 | 5/8", 11/16"x14 | 14 | HC37335L08-EI14BSWTM... | 80377 | 3/8 | .335 | 2.874 | .893 | 3 | 12 | .362 |
| | 5/8", 11/16"x14 | 14 | HC63528L12-EI14BSFTM... | 80378 | 5/8 | .528 | 3.150 | 1.250 | 4 | 17 | .551 |
| | 11/16"x14 | 14 | HC63591L13-EI14BSFTM... | 80379 | 5/8 | .591 | 3.622 | 1.393 | 4 | 19 | .614 |
| 1/2"x12 | 3/4"x12 | 12 | HC37362L10-EI12BSWTM... | 80380 | 3/8 | .362 | 2.874 | 1.042 | 3 | 12 | .413 |
| 9/16"x12 | 3/4"x12 | 12 | HC50444L11-EI12BSWTM... | 80381 | 1/2 | .444 | 3.150 | 1.125 | 4 | 13 | .476 |
| | 3/4"x12 | 12 | HC63622L15-EI12BSFTM... | 80382 | 5/8 | .622 | 3.622 | 1.542 | 4 | 18 | .661 |
| 5/8"x11 | 7/8"x11 | 11 | HC50496L13-EI11BSWTM... | 80383 | 1/2 | .496 | 3.150 | 1.318 | 4 | 14 | .528 |
| | 11/16"x11 | 11 | HC63559L14-EI11BSWTM... | 80384 | 5/8 | .559 | 3.622 | 1.409 | 4 | 15 | .591 |

* Bore diameter applies to smallest thread dia.



Helical Flutes with Thru-Hole Coolant

1.5 x Do (Le ≤ 1.5 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16", 1/8"x28 | 28 | HC31252L04-EI28BSPTM... | 80386 | 5/16 | .252 | 2.402 | .480 | 3 | 13 | .264 |
| 1/8"x28 | 28 | HC37323L05-EI28BSPTM... | 80388 | 3/8 | .323 | 2.874 | .591 | 3 | 16 | .324 |
| 1/4", 3/8"x19 | 19 | HC50433L08-EI19BSPTM... | 80389 | 1/2 | .433 | 2.874 | .815 | 4 | 15 | .465 |
| 3/8"x19 | 19 | HC63571L10-EI19BSPTM... | 80391 | 5/8 | .571 | 3.622 | 1.028 | 4 | 19 | .602 |
| 1"-4"x11 | 11 | HC75746L16-EI11BSPTM... | 80393 | 3/4 | .746 | 4.016 | 1.681 | 4 | 18 | 1.208 |

Helical Flutes with Thru-Hole Coolant

2 x Do (Le ≤ 2 x Thread Diameter)


| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|----------------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16", 1/8"x28 | 28 | HC31252L06-EI28BSPTM... | 80385 | 5/16 | .252 | 2.402 | .625 | 3 | 17 | .264 |
| 1/8"x28 | 28 | HC37323L07-EI28BSPTM... | 80387 | 3/8 | .323 | 2.874 | .768 | 3 | 21 | .324 |
| 1/4", 3/8"x19 | 19 | HC50433L10-EI19BSPTM... | 80319 | 1/2 | .433 | 3.150 | 1.079 | 4 | 20 | .465 |
| 3/8"x19 | 19 | HC63571L13-EI19BSPTM... | 80390 | 5/8 | .571 | 3.622 | 1.342 | 4 | 25 | .602 |
| 1/2"-7/8"x14 | 14 | HC75705L16-EI14BSPTM... | 80392 | 3/4 | .705 | 4.016 | 1.678 | 4 | 23 | .752 |

* Bore diameter applies to smallest thread dia.


NPT

Helicool

External / Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT




Helical Flutes with Thru-Hole Coolant

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------------------------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|----------------------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x27 | 27 | HC25232L03-EI27NPT-TM... | 80321 | 1/4 | .232 | 2.244 | .389 | 3 | 10 | .244 |
| 1/8"x27 | 27 | HC31301L03-EI27NPT-TM... | 80322 | 5/16 | .301 | 2.402 | .389 | 3 | 10 | .330 |
| 1/4"x18 | 18 | HC37370L05-EI18NPT-TM... | 80323 | 3/8 | .370 | 2.874 | .583 | 3 | 10 | .437 |
| 3/8"x18 | 18 | HC50439L05-EI18NPT-TM... | 80324 | 1/2 | .439 | 2.874 | .583 | 4 | 10 | .562 |
| 1/2", 3/4"x14 | 14 | HC63561L07-EI14NPT-TM... | 80325 | 5/8 | .561 | 3.150 | .750 | 4 | 10 | .704, .905 |
| 1", 1 1/4", 1 1/2", 2"x11.5 | 11.5 | HC75746L09-EI11.5NPT-TM... | 80326 | 3/4 | .746 | 4.016 | .913 | 4 | 10 | 1.411, 1.484, 1.732, 2.204 |
| 2 1/2", 3"x8 | 8 | HC75746L13-EI8NPT-TM... | 80327 | 3/4 | .746 | 4.016 | 1.313 | 4 | 10 | 2.625, 3.232 |


ANPT

Helicool

External / Internal



Defined by: MIL-P-7105B
Tolerance class: Standard ANPT




Helical Flutes with Thru-Hole Coolant

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|---------------|-------|---------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/4"x18 | 18 | HC37370L05-EI18ANPT-TM... | 81054 | 3/8 | .370 | 2.874 | .583 | 3 | 10 | .437 |
| 1/2", 3/4"x14 | 14 | HC63561L07-EI14ANPT-TM... | 81055 | 5/8 | .561 | 3.150 | .750 | 4 | 10 | .704, .905 |

* Bore diameter applies to smallest thread dia.

NPTF

Helicool




Helical Flutes with Thru-Hole Coolant

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------------------------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|----------------------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x27 | 27 | HC25232L03-EI27NPTFTM... | 80328 | 1/4 | .232 | 2.244 | .389 | 3 | 10 | .240 |
| 1/8"x27 | 27 | HC31301L03-EI27NPTFTM... | 80329 | 5/16 | .301 | 2.402 | .389 | 3 | 10 | .330 |
| 1/4"x18 | 18 | HC37370L05-EI18NPTFTM... | 80330 | 3/8 | .370 | 2.874 | .583 | 3 | 10 | .437 |
| 3/8"x18 | 18 | HC50439L05-EI18NPTFTM... | 80331 | 1/2 | .439 | 2.874 | .583 | 4 | 10 | .562 |
| 1/2", 3/4"x14 | 14 | HC63561L07-EI14NPTFTM... | 80332 | 5/8 | .561 | 3.150 | .750 | 4 | 10 | .704, .905 |
| 1", 1 1/4", 1 1/2", 2"x11.5 | 11.5 | HC75746L09-EI11.5NPTFTM... | 80333 | 3/4 | .746 | 4.016 | .913 | 4 | 10 | 1.411, 1.484, 1.720, 2.188 |
| 2 1/2"x8; 3"x8 | 8 | HC75746L13-EI8NPTFTM... | 80334 | 3/4 | .746 | 4.016 | 1.313 | 4 | 10 | 2.610, 3.232 |

BSPT


Helicool



Helical Flutes with Thru-Hole Coolant

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|---------------------------|-------|---------------------------|---------|-----------------|------|-------|-------|---------------|-------|------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x28 | 28 | HC25232L03-EI28BSPT-TM... | 80394 | 1/4 | .232 | 2.402 | .401 | 3 | 11 | .264 |
| 1/8"x28 | 28 | HC31301L03-EI28BSPT-TM... | 80320 | 5/16 | .301 | 2.402 | .401 | 3 | 11 | .342 |
| 1/4"x19 | 19 | HC50400L05-EI19BSPT-TM... | 80395 | 1/2 | .400 | 2.874 | .605 | 3 | 11 | .464 |
| 3/8"x19 | 19 | HC50439L05-EI19BSPT-TM... | 80396 | 1/2 | .439 | 2.874 | .605 | 4 | 11 | .598 |
| 1/2, 3/4"x14 | 14 | HC63561L08-EI14BSPT-TM... | 80397 | 5/8 | .561 | 3.150 | .893 | 4 | 12 | .748 |
| 1", 1 1/2", 2", 2 1/2"x11 | 11 | HC75746L10-EI11BSPT-TM... | 80398 | 3/4 | .746 | 4.016 | 1.136 | 4 | 12 | 1.209 |

* Bore diameter applies to smallest thread dia.




Defined by: MIL-S-8879C
Tolerance class: 3B

Helical Flutes with Thru-Hole Coolant

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | No. of Flutes | Teeth | Bore Dia.* | | | |
|-----------------|-----------------|-------------------|-----------------|---------|------------------------|-------|------|---------------|-------|------------|---|----|------|
| UNJC | UNJF | UNJEF | UNJ | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | mm |
| 0.138" (#6) | 0.190" (#10) | 0.216" (#12) | 0.4375" (7/16") | 32 | HC19106L02-I32UNJTM... | 80106 | 3/16 | .106 | 1.772 | .297 | 3 | 9 | .110 |
| - | 0.250" (1/4") | 0.4375" (7/16") | 0.5625" (9/16") | 28 | HC25213L05-I28UNJTM... | 81110 | 1/4 | .213 | 2.244 | .518 | 3 | 14 | .220 |
| 0.190" (#10) | 0.3125" (5/16") | 0.5625" (9/16") | - | 24 | HC19146L03-I24UNJTM... | 80108 | 3/16 | .146 | 1.772 | .396 | 3 | 9 | .157 |
| - | 0.3125" (5/16") | 0.5625" (9/16") | - | 24 | HC31264L06-I24UNJTM... | 80109 | 5/16 | .264 | 2.402 | .646 | 3 | 15 | .276 |
| 0.250" (1/4") | 0.4375" (7/16") | 0.750" (3/4") | 0.3125" (5/16") | 20 | HC25197L05-I20UNJTM... | 80110 | 1/4 | .197 | 2.244 | .525 | 3 | 10 | .209 |
| - | 0.4375" (7/16") | 0.750" (3/4") | 0.5625" (9/16") | 20 | HC37371L08-I20UNJTM... | 80111 | 3/8 | .371 | 2.874 | .875 | 4 | 17 | .394 |
| 0.3125" (5/16") | 0.5625" (9/16") | 1.0625" (1 1/16") | - | 18 | HC31252L06-I18UNJTM... | 80112 | 5/16 | .252 | 2.402 | .639 | 3 | 11 | .266 |
| 0.375" (3/8") | 0.750" (3/4") | - | 0.4375" (7/16") | 16 | HC31303L07-I16UNJTM... | 80113 | 5/16 | .303 | 2.402 | .781 | 3 | 12 | .319 |
| 0.4375" (7/16") | 0.875" (7/8") | - | - | 14 | HC37362L08-I14UNJTM... | 80114 | 3/8 | .362 | 2.874 | .893 | 4 | 12 | .374 |
| 0.500" (1/2") | - | - | - | 13 | HC37371L10-I13UNJTM... | 80115 | 3/8 | .371 | 2.874 | 1.039 | 4 | 13 | .433 |

* Bore diameter applies to smallest thread dia.




Helical Flutes with Thru-Hole Coolant

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|------------|-------|---------------------------|---------|-----------------|------|-------|------|---------------|-------|--------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/8" | 27 | HC31301L03-EI27NPSTM... | 80116 | 5/16 | .301 | 2.402 | .389 | 3 | 10 | .330 |
| 1/4" | 18 | HC37370L05-EI18NPSTM... | 80117 | 3/8 | .370 | 2.874 | .583 | 3 | 10 | .437 |
| 3/8" | 18 | HC50439L05-EI18NPSTM... | 80118 | 1/2 | .439 | 2.874 | .583 | 4 | 10 | .562 |
| 1/2", 3/4" | 14 | HC63561L07-EI14NPSTM... | 80119 | 5/8 | .561 | 3.150 | .750 | 4 | 10 | .704, .905 |
| 1", 2" | 11.5 | HC75746L08-EI11.5NPSTM... | 80120 | 3/4 | .746 | 4.016 | .913 | 4 | 10 | 1.411, 2.204 |

American UN

Helicool-R (HCR)



HeliCool-R (HCR)

Helical Flutes with Radial Cooling

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* | |
|----------|----------------|-------------------|---------------|-------------------------|-----------------|------|------|-------|---------------|-------|------------|------|
| UNC | UNF | UNEF | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| No.10-32 | No.12-3/8"x32 | | 32 | HCR19150L03-I32UNFTM... | 80458 | 3/16 | .150 | 1.772 | .391 | 3 | 12 | .157 |
| 1/4"x28 | 7/16", 1/2"x28 | | 28 | HCR25203L05-I28UNFTM... | 80459 | 1/4 | .203 | 2.244 | .518 | 3 | 14 | .216 |
| No.10-24 | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCR19141L04-I24UNCTM... | 80460 | 3/16 | .141 | 1.772 | .396 | 3 | 9 | .150 |
| No.12-24 | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCR19163L04-I24UNCTM... | 80461 | 3/16 | .163 | 1.772 | .437 | 3 | 10 | .177 |
| | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCR31263L06-I24UNFTM... | 80462 | 5/16 | .263 | 2.402 | .646 | 3 | 15 | .272 |
| | 3/8"x24 | 9/16"-11/16"x24 | 24 | HCR37323L07-I24UNFTM... | 80463 | 3/8 | .323 | 2.874 | .771 | 3 | 18 | .335 |
| 1/4"x20 | 7/16", 1/2"x20 | 3/4"-1"x20 | 20 | HCR25192L05-I20UNCTM... | 80464 | 1/4 | .192 | 2.244 | .525 | 3 | 10 | .201 |
| | 1/2"x20 | 3/4"-1"x20 | 20 | HCR50437L10-I20UNFTM... | 80465 | 1/2 | .437 | 3.150 | 1.025 | 4 | 20 | .453 |
| 5/16"x18 | 9/16", 5/8"x18 | 11/16"-1 1/16"x18 | 18 | HCR31242L06-I18UNCTM... | 80466 | 5/16 | .242 | 2.402 | .639 | 3 | 11 | .260 |
| 3/8"x16 | 3/4"x16 | | 16 | HCR31301L07-I16UNCTM... | 80467 | 5/16 | .301 | 2.402 | .781 | 3 | 12 | .315 |
| 7/16"x14 | 7/8"x14 | | 14 | HCR37354L08-I14UNCTM... | 80468 | 3/8 | .354 | 2.874 | .893 | 3 | 12 | .370 |
| 1/2"x13 | | | 13 | HCR50407L10-I13UNCTM... | 80469 | 1/2 | .407 | 3.150 | 1.039 | 4 | 13 | .430 |
| 9/16"x12 | 1"-1 1/2"x12 | | 12 | HCR50465L11-I12UNCTM... | 80470 | 1/2 | .465 | 3.150 | 1.125 | 4 | 13 | .484 |

* Bore diameter applies to smallest thread dia.

NPT

Helicoil-R (HCR)

External / Internal

Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

Helicoil-R (HCR)

Helical Flutes with Radial Cooling

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | Flutes | Teeth | Bore Dia.* |
|-----------------------------|-------|-----------------------------|---------|-----------------|------|-------|-------|--------|-------|----------------------------|
| Standard | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x27 | 27 | HCR25232L03-EI27NPT-TM... | 80573 | 1/4 | .232 | 2.244 | .389 | 3 | 10 | .244 |
| 1/8"x27 | 27 | HCR31301L03-EI27NPT-TM... | 80574 | 5/16 | .301 | 2.402 | .389 | 3 | 10 | .330 |
| 1/4"x18 | 18 | HCR37370L05-EI18NPT-TM... | 80575 | 3/8 | .370 | 2.874 | .583 | 3 | 10 | .437 |
| 3/8"x18 | 18 | HCR50439L05-EI18NPT-TM... | 80576 | 1/2 | .439 | 2.874 | .583 | 4 | 10 | .562 |
| 1/2", 3/4"x14 | 14 | HCR63561L07-EI14NPT-TM... | 80577 | 5/8 | .561 | 3.150 | .750 | 4 | 10 | .704, .905 |
| 1", 1 1/4", 1 1/2", 2"x11.5 | 11.5 | HCR75746L09-EI11.5NPT-TM... | 80578 | 3/4 | .746 | 4.016 | .913 | 4 | 10 | 1.411, 1.484, 1.732, 2.204 |
| 2 1/2", 3"x8 | 8 | HCR75746L13-EI8NPT-TM... | 80579 | 3/4 | .746 | 4.016 | 1.313 | 4 | 10 | 2.625, 3.232 |

American UN

Helicoil-C (HCC)

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2B

Dc = Minimum recommended chamfer diameter


Helicoil-C (HCC)

Helical Flutes with Axial Coolant - Thru & Chamfer

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* | | | |
|----------|----------------|-------------------|---------------|-------------------------|-----------------|------|------|------|---------------|-------|------------|---|----|------|
| UNC | UNF | UNEF | TPI | Internal | VTH | D | D2 | Dc | L | Le | Lc | Z | Zt | inch |
| | No.10-32 | No.12-3/8"x32 | 32 | HCC25150L03-I32UNFTM... | 80449 | 1/4 | .150 | .202 | 2.244 | .391 | .417 | 3 | 12 | .157 |
| | 1/4"x28 | 7/16", 1/2"x28 | 28 | HCC31203L05-I28UNFTM... | 80450 | 5/16 | .203 | .262 | 2.402 | .518 | .549 | 3 | 14 | .216 |
| No.10-24 | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCC25141L04-I24UNCTM... | 80451 | 1/4 | .141 | .202 | 2.244 | .396 | .425 | 3 | 9 | .150 |
| No.12-24 | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCC25163L04-I24UNCTM... | 80452 | 1/4 | .163 | .228 | 2.244 | .437 | .468 | 3 | 10 | .177 |
| | 5/16", 3/8"x24 | 9/16"-11/16"x24 | 24 | HCC37263L06-I24UNFTM... | 80453 | 3/8 | .263 | .324 | 2.874 | .646 | .678 | 3 | 15 | .272 |
| | 3/8"x24 | 9/16"-11/16"x24 | 24 | HCC50323L07-I24UNFTM... | 80454 | 1/2 | .323 | .387 | 3.150 | .771 | .804 | 3 | 18 | .335 |
| 1/4"x20 | 7/16", 1/2"x20 | 3/4"-1"x20 | 20 | HCC31192L05-I20UNCTM... | 80455 | 5/16 | .192 | .262 | 2.402 | .525 | .558 | 3 | 10 | .201 |
| | 1/2"x20 | 3/4"-1"x20 | 20 | HCC63437L10-I20UNFTM... | 80456 | 5/8 | .437 | .512 | 3.622 | 1.025 | 1.065 | 3 | 20 | .453 |
| 5/16"x18 | 9/16", 5/8"x18 | 11/16"-1 1/16"x18 | 18 | HCC37242L16-I18UNCTM... | 80457 | 3/8 | .242 | .324 | 2.874 | .639 | .676 | 3 | 11 | .260 |
| 3/8"x16 | 3/4"x16 | | 16 | HCC50301L07-I16UNCTM... | 80528 | 1/2 | .301 | .387 | 3.150 | .781 | .814 | 3 | 12 | .315 |
| 7/16"x14 | 7/8"x14 | | 14 | HCC50354L08-I14UNCTM... | 80529 | 1/2 | .354 | .449 | 3.150 | .893 | .937 | 3 | 12 | .370 |
| 1/2"x13 | | | 13 | HCC63407L10-I13UNCTM... | 80530 | 5/8 | .407 | .512 | 3.622 | 1.039 | 1.087 | 4 | 13 | .430 |
| 9/16"x12 | 1"-1 1/2"x12 | | 12 | HCC63465L11-I12UNCTM... | 80531 | 5/8 | .465 | .574 | 3.622 | 1.125 | 1.178 | 4 | 13 | .484 |

* Bore diameter applies to smallest thread dia.




HTC (Thriller)

Drill, Chamfer & Thread with Coolant-Thru

| Thread | Ordering Code | EDP No. | Pitch | Dimensions Inch | | | | | | | | | | | No. of Flutes | Teeth | |
|-------------------------------|--------------------|---------|-------|-----------------|-------|-------|-------|-------|------|------|------|-------|------|------|---------------|-------|----|
| ISO 2xD _o Coarse | Internal | VTS | VTN | mm | L | L4 | L2 | L3 | W | Le | D3 | D(mm) | D1 | Dc | D2 | Z | Zt |
| M6x1.0 | HTCM6x1.0x2D... | 80687 | 80680 | 1.00 | 2.441 | .571 | .539 | 1.417 | .039 | .500 | .197 | 8 | .260 | .248 | .191 | 2 | 11 |
| M8x1.25 | HTCM8x1.25x2D... | 80688 | 80681 | 1.25 | 2.913 | .717 | .673 | 1.575 | .051 | .622 | .268 | 10 | .354 | .327 | .254 | 2 | 11 |
| M10x1.5 | HTCM10x1.5x2D... | 80689 | 80682 | 1.50 | 3.110 | .921 | .870 | 1.772 | .059 | .811 | .335 | 12 | .433 | .406 | .318 | 2 | 12 |
| M12x1.75 | HTCM12x1.75x2D... | 80690 | 80683 | 1.75 | 3.504 | 1.067 | 1.004 | 1.772 | .059 | .945 | .406 | 14 | .531 | .484 | .383 | 2 | 12 |
| ISO 2.5xD _o Coarse | | | | | | | | | | | | | | | | | |
| M6x1.0 | HTCM6x1.0x2.5D... | 80691 | 80684 | 1.00 | 2.441 | .650 | .618 | 1.417 | .039 | .579 | .197 | 8 | .260 | .248 | .191 | 2 | 13 |
| M8x1.25 | HTCM8x1.25x2.5D... | 80692 | 80685 | 1.25 | 2.913 | .913 | .870 | 1.575 | .051 | .819 | .268 | 10 | .354 | .327 | .254 | 2 | 15 |
| M10x1.5 | HTCM10x1.5x2.5D... | 80693 | 80686 | 1.50 | 3.110 | 1.098 | 1.047 | 1.772 | .059 | .988 | .335 | 12 | .433 | .406 | .318 | 2 | 15 |


HTC - Thriller Operating Cycle



TM Solid

HTC line is suitable for Aluminium and Cast Iron machining only.

External / Internal



Defined by: R262 (DIN 13)
Tolerance class: 6g/6H



Helical Flutes - External (D-mm shank)

2 x Do (Le ≤ 2 x Thread Diameter)


| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | No. of Flutes | Teeth | |
|-----------|-------|-------------------------|---------|-----------------|------|-------|---------------|-------|----|
| M Coarse | mm | External | VTH | D(mm) | D2 | L | Le | Z | Zt |
| M3x0.5 | 0.5 | H04039L06-E0.5ISOTM... | 80891 | 4 | .154 | 1.772 | .236 | 3 | 12 |
| M4.5x0.75 | 0.75 | H04039L09-E0.75ISOTM... | 80892 | 4 | .154 | 1.772 | .354 | 3 | 12 |
| M6x1.0 | 1.0 | H04039L12-E1.0ISOTM... | 80893 | 4 | .154 | 1.772 | .472 | 3 | 12 |
| M8x1.25 | 1.25 | H06059L16-E1.25ISOTM... | 80894 | 6 | .232 | 2.244 | .640 | 3 | 13 |
| M10x1.5 | 1.5 | H08079L21-E1.5ISOTM... | 80895 | 8 | .311 | 2.480 | .827 | 3 | 14 |
| M14x2.0 | 2.0 | H10099L28-E2.0ISOTM... | 80896 | 10 | .390 | 2.874 | 1.102 | 4 | 14 |

Helical Flutes - Internal (D-mm shank)

2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | No. of Flutes | Teeth | Bore Dia.* | |
|-------------|--------------|-------------------------|---------|-----------------|------|-------|---------------|-------|------------|------|
| M Coarse | M Fine | Internal | VTH | D(mm) | D2 | L | Le | Z | Zt | Inch |
| M3x0.5 | M3.5-M16x0.5 | H04022L06-I0.5ISOTM... | 80897 | 4 | .087 | 1.772 | .236 | 3 | 12 | .098 |
| | M4x0.5 | H04030L08-I0.5ISOTM... | 80898 | 4 | .118 | 1.772 | .315 | 3 | 16 | .138 |
| | M5x0.5 | H04039L10-I0.5ISOTM... | 80899 | 4 | .154 | 1.772 | .394 | 3 | 20 | .177 |
| M4x0.7 | | H04028L08-I0.7ISOTM... | 80900 | 4 | .110 | 1.772 | .331 | 3 | 12 | .130 |
| | M6x0.75 | H04039L12-I0.75ISOTM... | 80901 | 4 | .154 | 1.772 | .472 | 3 | 16 | .209 |
| M5x0.8 | | H04035L10-I0.8ISOTM... | 80902 | 4 | .138 | 1.772 | .409 | 3 | 13 | .165 |
| M6x1.0 | M8-M40x1.0 | H04039L12-I1.0ISOTM... | 80903 | 4 | .154 | 1.772 | .472 | 3 | 12 | .197 |
| | M8x1.0 | H06059L16-I1.0ISOTM... | 80904 | 6 | .232 | 2.244 | .630 | 3 | 16 | .276 |
| | M10x1.0 | H08079L20-I1.0ISOTM... | 80905 | 8 | .311 | 2.480 | .787 | 3 | 20 | .354 |
| | M12x1.0 | H10099L24-I1.0ISOTM... | 80801 | 10 | .390 | 2.874 | .945 | 4 | 24 | .433 |
| M8x1.25 | | H06058L16-I1.25ISOTM... | 80907 | 6 | .228 | 2.244 | .640 | 3 | 13 | .268 |
| | M10x1.25 | H08077L20-I1.25ISOTM... | 80908 | 8 | .303 | 2.480 | .787 | 3 | 16 | .346 |
| M10x1.5 | M12-M48x1.5 | H08077L21-I1.5ISOTM... | 80909 | 8 | .303 | 2.480 | .827 | 3 | 14 | .335 |
| | M12x1.5 | H10094L24-I1.5ISOTM... | 80910 | 10 | .370 | 2.874 | .945 | 4 | 16 | .413 |
| | M14x1.5 | H12112L28-I1.5ISOTM... | 80911 | 12 | .441 | 3.268 | 1.122 | 4 | 19 | .492 |
| | M16x1.5 | H12119L33-I1.5ISOTM... | 80912 | 12 | .469 | 3.268 | 1.299 | 4 | 22 | .571 |
| M12x1.75 | | H10087L24-I1.75ISOTM... | 80913 | 10 | .343 | 2.874 | .965 | 4 | 14 | .402 |
| M14x2.0 | M17-M80x2.0 | H10099L28-I2.0ISOTM... | 80914 | 10 | .390 | 2.874 | 1.102 | 4 | 14 | .472 |
| M16x2.0 | M17-M80x2.0 | H12119L32-I2.0ISOTM... | 80915 | 12 | .469 | 3.268 | 1.260 | 4 | 16 | .551 |
| M18-M22x2.5 | | H16139L40-I2.5ISOTM... | 80916 | 16 | .547 | 3.622 | 1.575 | 5 | 16 | .610 |
| M24x3.0 | | H16159L42-I3.0ISOTM... | 80917 | 16 | .626 | 3.622 | 1.654 | 4 | 14 | .827 |

* Bore diameter applies to smallest thread dia.



Defined by: ANSI B1.1.74
Tolerance class: 2A/2B

Helical Flutes - Internal


2 x Do (Le ≤ 2 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* | |
|----------|-------|--------------------------|----------|-----------------|------|-----|-------|---------------|-------|------------|------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| No.10-32 | 32 | HX1/8".121"-I32UNFTM... | 80534 | 1/8 | .121 | 2.0 | .312 | 3 | 10 | .157 | |
| No.10-28 | 28 | HX1/8".121"-I28UNFTM... | 80535 | 1/8 | .121 | 2.0 | .321 | 3 | 9 | .155 | |
| No.12-28 | 28 | HX3/16".150"-I28UNFTM... | 80536 | 3/16 | .150 | 2.5 | .464 | 3 | 13 | .181 | |
| 1/4"x28 | 28 | HX3/16".181"-I28UNFTM... | 80537 | 3/16 | .181 | 2.5 | .500 | 3 | 14 | .217 | |
| No.10-24 | 24 | HX1/8".120"-I24UNCTM... | 80538 | 1/8 | .120 | 2.0 | .333 | 3 | 8 | .150 | |
| No.12-24 | 24 | HX3/16".138"-I24UNCTM... | 80539 | 3/16 | .138 | 2.5 | .458 | 3 | 11 | .177 | |
| 5/16"x24 | 24 | HX1/4".232"-I24UNFTM... | 80540 | 1/4 | .232 | 2.5 | .625 | 3 | 15 | .268 | |
| 3/8"x24 | 24 | HX5/16".291"-I24UNFTM... | 80541 | 5/16 | .291 | 3.0 | .750 | 4 | 18 | .335 | |
| 1/4"x20 | 20 | HX3/16".181"-I20UNCTM... | 80542 | 3/16 | .181 | 2.5 | .500 | 3 | 10 | .205 | |
| 1/2"x20 | 20 | HX3/8".371"-I20UNFTM... | 80543 | 3/8 | .371 | 3.5 | 1.000 | 4 | 20 | .453 | |
| 7/16"x20 | 20 | HX3/8".335"-I20UNFTM... | 80544 | 3/8 | .335 | 3.5 | .900 | 4 | 18 | .386 | |
| 5/16"x18 | 18 | HX1/4".232"-I18UNCTM... | 80545 | 1/4 | .232 | 2.5 | .667 | 3 | 12 | .256 | |
| 9/16"x18 | 18 | HX3/8".371"-I18UNFTM... | 80546 | 3/8 | .371 | 3.5 | .889 | 4 | 16 | .504 | |
| 5/8"x18 | 18 | HX1/2".496"-I18UNFTM... | 80547 | 1/2 | .496 | 3.5 | 1.278 | 4 | 23 | .571 | |
| 3/8"x16 | 16 | HX5/16".285"-I16UNCTM... | 80548 | 5/16 | .285 | 3.0 | .750 | 4 | 12 | .315 | |
| 3/4"x16 | 16 | HX1/2".496"-I16UNFTM... | 80549 | 1/2 | .496 | 3.5 | 1.250 | 4 | 20 | .689 | |
| 7/16"x14 | 14 | HX5/16".305"-I14UNCTM... | 80550 | 5/16 | .305 | 3.0 | .786 | 4 | 11 | .366 | |
| 1/2"x13 | 13 | HX3/8".350"-I13UNCTM... | 80551 | 3/8 | .350 | 3.5 | .923 | 4 | 12 | .425 | |
| 9/16"x12 | 12 | HX3/8".371"-I12UNCTM... | 80552 | 3/8 | .371 | 3.5 | .917 | 4 | 11 | .484 | |
| 5/8"x11 | 11 | HX1/2".469"-I11UNCTM... | 80553 | 1/2 | .469 | 3.5 | 1.273 | 4 | 14 | .531 | |
| 3/4"x10 | 10 | HX1/2".496"-I10UNCTM... | 80554 | 1/2 | .496 | 3.5 | 1.300 | 4 | 13 | .650 | |
| 7/8"x9 | 9 | HX5/8".621"-I9UNCTM... | 80555 | 5/8 | .621 | 4.0 | 1.444 | 4 | 13 | .768 | |
| 1"x8 | 8 | HX5/8".621"-I8UNC TM... | 80556 | 5/8 | .621 | 4.0 | 1.375 | 4 | 11 | .878 | |

TM Solid

* Bore diameter applies to smallest thread dia.

External / Internal





Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

Helical Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-------------------|-------|-----------------------------|---------|-----------------|------|-----|-------|---------------|-------|-------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x27, 1/8"x27 | 27 | HX1/4".209"-EI27NPT-TM... | 80562 | 1/4 | .209 | 2.5 | .407 | 3 | 11 | .248, .335 |
| 1/4"x18, 3/8"x18 | 18 | HX5/16".305"-EI18NPT-TM... | 80563 | 5/16 | .305 | 3.0 | .611 | 4 | 11 | .437, .571 |
| 1/2"x14, 3/4"x14 | 14 | HX1/2".496"-EI14NPT-TM... | 80564 | 1/2 | .496 | 3.5 | .929 | 4 | 13 | .697, .906 |
| 1"-2"x11.5 | 11.5 | HX5/8".621"-EI11.5NPT-TM... | 80565 | 5/8 | .621 | 4.0 | 1.130 | 4 | 13 | 1.142-2.205 |
| 2 1/2"-6"x8 | 8 | HX3/4".746"-EI8NPT-TM... | 80566 | 3/4 | .746 | 5.0 | 1.500 | 4 | 12 | from 2.618 |

External / Internal




Defined by: ANSI 1.20.3-1976
Tolerance class: Standard NPTF

Helical Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-------------------|-------|-----------------------------|---------|-----------------|------|-----|-------|---------------|-------|-------------|
| Standard | TPI | External / Internal | VTH | D | D2 | L | Le | Z | Zt | Inch |
| 1/16"x27, 1/8"x27 | 27 | HX1/4".209"-EI27NPTFTM... | 80557 | 1/4 | .209 | 2.5 | .407 | 3 | 11 | .248, .331 |
| 1/4"x18, 3/8"x18 | 18 | HX5/16".305"-EI18NPTFTM... | 80558 | 5/16 | .305 | 3.0 | .611 | 4 | 11 | .437, .579 |
| 1/2"x14, 3/4"x14 | 14 | HX1/2".496"-EI14NPTFTM... | 80559 | 1/2 | .496 | 3.5 | .929 | 4 | 13 | .705, .921 |
| 1"-2"x11.5 | 11.5 | HX5/8".621"-EI11.5NPTFTM... | 80560 | 5/8 | .621 | 4.0 | 1.130 | 4 | 13 | 1.158-2.213 |
| 2 1/2"-6"x8 | 8 | HX3/4".746"-EI8NPTFTM... | 80561 | 3/4 | .746 | 5.0 | 1.500 | 4 | 12 | from 2.638 |

* Bore diameter applies to smallest thread dia.



Helical Flutes - Taper 60°
TM Solid Helical Flutes for Bone Plate Applications

| Pitch | Ordering Code | Taper | Thread Angle | Profile Height | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-------|---------------------------|-------|--------------|----------------|-----------------|------|------|-------|---------------|-------|----|
| mm | Internal | | α | h | D (mm) | D2 | D1 | L | Le | Z | Zt |
| 0.4 | H06059L080-10.4TAP60TM... | 20° | 60° | .008 | 6 | .232 | .126 | 2.244 | .315 | 3 | 20 |
| 0.5 | H06059L090-10.5TAP60TM... | 20° | 60° | .010 | 6 | .232 | .114 | 2.244 | .354 | 3 | 18 |


Helical Flutes - Taper 55°
TM Solid Helical Flutes for Bone Plate Applications

| Pitch | Ordering Code | Taper | Thread Angle | Profile Height | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-------|----------------------------|-------|--------------|----------------|-----------------|------|------|-------|---------------|-------|----|
| mm | Internal | | α | h | D (mm) | D2 | D1 | L | Le | Z | Zt |
| 0.3 | H03028L039-10.3TAP55TM... | 20° | 55° | .007 | 3 | .110 | .059 | 1.496 | .154 | 3 | 13 |
| 0.35 | H04039L063-10.35TAP55TM... | 20° | 55° | .008 | 4 | .154 | .071 | 1.772 | .248 | 3 | 18 |
| 0.4 | H06059L100-10.4TAP55TM... | 20° | 55° | .011 | 6 | .232 | .098 | 2.244 | .394 | 3 | 25 |
| 0.5 | H06059L090-10.5TAP55TM... | 20° | 55° | .013 | 6 | .232 | .114 | 2.244 | .354 | 3 | 18 |
| 0.6 | H06059L066-10.6TAP55TM... | 20° | 55° | .019 | 6 | .232 | .150 | 2.244 | .260 | 3 | 11 |

TM Solid

American UN

Deep Threading




Deep Threading - Long Tools for Deep Holes

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | No. of Flutes | Teeth | Bore Dia. | | |
|----------|----------|---------------|---------------------------|-----------------|------|------|---------------|-------|-----------|----|------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | inch |
| 1/4"x20 | | 20 | D1T5/16".157"-I20UNCTM... | 80220 | 5/16 | .157 | 2.480 | .787 | 3 | 1 | .205 |
| | 1/4"x28 | 28 | D1T5/16".181"-I28UNFTM... | 80271 | 5/16 | .181 | 2.480 | .787 | 3 | 1 | .217 |
| 5/16"x18 | | 18 | D1T3/8".205"-I18UNCTM... | 80221 | 3/8 | .205 | 2.874 | .984 | 3 | 1 | .256 |
| | 5/16"x24 | 24 | D1T3/8".224"-I24UNFTM... | 80272 | 3/8 | .224 | 2.874 | .984 | 3 | 1 | .268 |
| 3/8"x16 | | 16 | D1T3/8".264"-I16UNCTM... | 80222 | 3/8 | .264 | 2.874 | 1.181 | 3 | 1 | .315 |
| | 3/8"x24 | 24 | D1T3/8".291"-I24UNFTM... | 80273 | 3/8 | .291 | 2.874 | 1.181 | 3 | 1 | .335 |
| 7/16"x14 | | 14 | D1T1/2".299"-I14UNCTM... | 80274 | 1/2 | .299 | 3.268 | 1.378 | 4 | 1 | .366 |
| | 7/16"x20 | 20 | D1T1/2".335"-I20UNFTM... | 80275 | 1/2 | .335 | 3.268 | 1.378 | 4 | 1 | .386 |
| 1/2"x13 | | 13 | D1T1/2".350"-I13UNCTM... | 80223 | 1/2 | .350 | 3.268 | 1.575 | 4 | 1 | .425 |
| | 1/2"x20 | 20 | D1T1/2".398"-I20UNFTM... | 80276 | 1/2 | .398 | 3.268 | 1.575 | 4 | 1 | .453 |
| 9/16"x12 | | 12 | D1T5/8".406"-I12UNCTM... | 80224 | 5/8 | .406 | 3.780 | 1.772 | 4 | 1 | .484 |
| | 9/16"x18 | 18 | D1T5/8".445"-I18UNFTM... | 80277 | 5/8 | .445 | 3.780 | 1.772 | 4 | 1 | .504 |
| 5/8"x11 | | 11 | D1T5/8".433"-I11UNCTM... | 80225 | 5/8 | .433 | 3.976 | 1.969 | 4 | 1 | .531 |
| | 5/8"x18 | 18 | D1T5/8".504"-I18UNFTM... | 80278 | 5/8 | .504 | 3.976 | 1.969 | 4 | 1 | .571 |
| 3/4"x10 | | 10 | D1T5/8".531"-I10UNCTM... | 80226 | 5/8 | .531 | 4.370 | 2.362 | 5 | 1 | .650 |
| | 3/4"x16 | 16 | D1T5/8".610"-I16UNFTM... | 80227 | 5/8 | .610 | 4.370 | 2.362 | 5 | 1 | .689 |

American ACME (2G)




Deep Threading - Long Tools for Deep Holes

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | No. of Flutes | Teeth | Bore Dia. | |
|---------|-------|-----------------------------|---------|-----------------|------|-------|---------------|-------|-----------|------|
| UNC | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | inch |
| 3/8"-12 | 12 | S1LC25024L075-I12ACME-2G... | 81058 | 1/4 | .240 | 2.520 | .811 | 3 | 1 | .354 |
| 1/2"-10 | 10 | S1LC37032L100-I10ACME-2G... | 81059 | 3/8 | .327 | 2.990 | 1.071 | 3 | 1 | .400 |
| 5/8"-8 | 8 | S1LC50042L125-I8ACME-2G... | 81060 | 1/2 | .425 | 3.500 | 1.330 | 4 | 1 | .500 |
| 3/4"-6 | 6 | S1LC50049L150-I6ACME-2G... | 81061 | 1/2 | .488 | 3.500 | 1.600 | 5 | 1 | .583 |
| 1"-5 | 5 | S1LC63057L200-I5ACME-2G... | 81062 | 5/8 | .571 | 4.015 | 2.110 | 5 | 1 | .800 |

Partial Profile 60°


Deep Threading



Deep Threading - Long Tools for Deep Holes

| Thread | | Min. Thread | Pitch | | Ordering Code | EDP No. | Dimensions Inch | | | | | |
|----------|------------------------------------|---|----------|-------|-------------------------|---------|-----------------|------|-------|------|---|----|
| M Coarse | M Fine | UN, UNS, UNF, UNEF | mm | TPI | Internal | | D | D2 | L | L1 | Z | Zt |
| M5x0.8 | M5x0.5, M5X0.75 | No.10-56UNS, No.10-48UNS, No.10-40UNS, No.10-36UNS, No.10-32UNF | 0.5-0.8 | 32-56 | D1T19154L063-ITA60TM... | 80414 | 3/16 | .154 | 1.750 | .63 | 4 | 1 |
| M6x1.0 | M6x0.5, M6X0.75 | No.12-56UNS, No.12-48UNS, 1/4-40UNS, 1/4-36UNS, 1/4-32UNEF, 1/4-28UNF, 1/4-27UNS, 1/4-24UNS | 0.5-1.0 | 24-56 | D1T25191L079-ITB60TM... | 80415 | 1/4 | .191 | 2.000 | .79 | 5 | 1 |
| M8x1.25 | M7x0.5, M7x0.75, M7.5x1.0 | 5/16-48UNS, 5/16-40UNS, 5/16-36UNS, 5/16-32UNEF, 5/16-28UN, 5/16-27UNS, 5/16-24UNS, 5/16-20UN | 0.5-1.25 | 20-48 | D1T25232L100-ITF60TM... | 80416 | 1/4 | .232 | 2.500 | 1.00 | 5 | 1 |
| - | M10.5x0.5, M11x0.75, M11x1.0 | 7/16-32UN, 7/16-28UNEF, 7/16-27UNS, 7/16-24UNS | 0.5-1.0 | 24-56 | D1T37370L138-ITB60TM... | 80417 | 3/8 | .370 | 3.000 | 1.38 | 6 | 1 |
| M10x1.5 | M10x1.0, M10X1.25 | 3/8-24UNF, 3/8-20UN, 7/16-18UNS, 7/16-16UN | 1.0-1.50 | 16-24 | D1T31307L126-ITC60TM... | 80423 | 5/16 | .307 | 2.500 | 1.26 | 6 | 1 |
| M12x1.75 | M12x1.0, M12X1.25, M12x1.5 | 1/2-24UNS, 1/2-20UNS, 1/2-18UNS, 1/2-16UNS, 1/2-14UNS | 1.0-1.75 | 14-24 | D1T37370L150-ITD60TM... | 80424 | 3/8 | .370 | 3.000 | 1.50 | 6 | 1 |
| - | M13.5x1.0, M14x1.25, M14x1.5 | 9/16-24UNEF | 1.0-1.75 | 14-24 | D1T50469L177-ITD60TM... | 80425 | 1/2 | .469 | 3.250 | 1.77 | 6 | 1 |

TM Solid



MilliPro
Miniature Thread Mills

2 x Do (L1 ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | mm |
| M1.6x0.35 | | 0.35 | D3T12047L134-I0.35ISOTM... | 80660 | 1/8 | .047 | 1.181 | .134 | 3 | 3 | .049 |
| M2x0.4 | | 0.4 | D3T25061L165-I0.4ISOTM... | 80661 | 1/4 | .061 | 2.244 | .165 | 3 | 3 | .063 |
| M2.2x0.45 | | 0.45 | D3T25065L181-I0.45ISOTM... | 80662 | 1/4 | .065 | 2.244 | .181 | 3 | 3 | .069 |
| M2.5x0.45 | | 0.45 | D3T25077L205-I0.45ISOTM... | 80663 | 1/4 | .077 | 2.244 | .205 | 3 | 3 | .081 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T25094L244-I0.5ISOTM... | 80664 | 1/4 | .094 | 2.244 | .244 | 3 | 3 | .098 |
| M3.5x0.6 | | 0.6 | D3T25108L287-I0.6ISOTM... | 80665 | 1/4 | .108 | 2.244 | .287 | 3 | 3 | .114 |
| M4x0.7 | | 0.7 | D3T25124L327-I0.7ISOTM... | 80666 | 1/4 | .124 | 2.244 | .327 | 3 | 3 | .130 |
| M5x0.8 | | 0.8 | D3T25159L409-I0.8ISOTM... | 80667 | 1/4 | .159 | 2.244 | .409 | 3 | 3 | .165 |
| M6x1.0 | M8-M40x1.0 | 1.0 | D3T25189L492-I1.0ISOTM... | 80668 | 1/4 | .189 | 2.244 | .492 | 3 | 3 | .197 |
| M8x1.25 | | 1.25 | D3T31256L654-I1.25ISOTM... | 80669 | 5/16 | .256 | 2.480 | .654 | 3 | 3 | .268 |
| M10x1.5 | M12-M48x1.50 | 1.50 | D3T37323L819-I1.50ISOTM... | 80670 | 3/8 | .323 | 2.874 | .819 | 3 | 3 | .335 |
| M12x1.75 | | 1.75 | D3T37371L984-I1.75ISOTM... | 80671 | 3/8 | .371 | 2.874 | .984 | 3 | 3 | .406 |


TM Solid

MilliPro
Miniature Thread Mills

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| M1.6x0.35 | | 0.35 | D3T12047L197-I0.35ISOTM... | 80672 | 1/8 | .047 | 1.181 | .197 | 3 | 3 | .049 |
| M2x0.4 | | 0.4 | D3T25061L244-I0.4ISOTM... | 80673 | 1/4 | .061 | 2.244 | .244 | 3 | 3 | .063 |
| M2.5x0.45 | | 0.45 | D3T25077L276-I0.45ISOTM... | 80674 | 1/4 | .077 | 2.244 | .276 | 3 | 3 | .081 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T25094L362-I0.5ISOTM... | 80675 | 1/4 | .094 | 2.244 | .362 | 3 | 3 | .098 |
| M4x0.7 | | 0.7 | D3T25124L484-I0.7ISOTM... | 80676 | 1/4 | .124 | 2.244 | .484 | 3 | 3 | .130 |
| M5x0.8 | | 0.8 | D3T25159L606-I0.8ISOTM... | 80677 | 1/4 | .159 | 2.244 | .606 | 3 | 3 | .165 |
| M6x1.0 | M8-M40 x1.0 | 1.0 | D3T25189L728-I1.0ISOTM... | 80678 | 1/4 | .189 | 2.244 | .728 | 3 | 3 | .197 |
| M8x1.25 | | 1.25 | D3T31256L969-I1.25ISOTM... | 80679 | 5/16 | .256 | 2.480 | .969 | 3 | 3 | .268 |

* Bore diameter applies to smallest thread dia.



MilliPro (D-mm shank)
Miniature Thread Mills

2 x Do (L1 ≤ 2 x Thread Diameter)


| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|-----------------|-----|------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D(mm) | D2 | L | L1 | Z | Zt | Inch |
| M1.6x0.35 | | 0.35 | D3T03012L034-I0.35ISOTM... | 80420 | 3 | .05 | 1.18 | .13 | 3 | 3 | .05 |
| M2x0.4 | | 0.4 | D3T06015L042-I0.4ISOTM... | 80254 | 6 | .06 | 2.24 | .17 | 3 | 3 | .06 |
| M2.2x0.45 | | 0.45 | D3T06016L046-I0.45ISOTM... | 80255 | 6 | .06 | 2.24 | .18 | 3 | 3 | .07 |
| M2.5x0.45 | | 0.45 | D3T06019L052-I0.45ISOTM... | 80256 | 6 | .08 | 2.24 | .20 | 3 | 3 | .08 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T06024L062-I0.5ISOTM... | 80257 | 6 | .09 | 2.24 | .24 | 3 | 3 | .10 |
| M3.5x0.6 | | 0.6 | D3T06027L073-I0.6ISOTM... | 80258 | 6 | .11 | 2.24 | .29 | 3 | 3 | .11 |
| M4x0.7 | | 0.7 | D3T06031L083-I0.7ISOTM... | 80259 | 6 | .12 | 2.24 | .33 | 3 | 3 | .13 |
| M5x0.8 | | 0.8 | D3T06040L104-I0.8ISOTM... | 80260 | 6 | .16 | 2.24 | .41 | 3 | 3 | .17 |
| M6x1.0 | M8-M40x1.0 | 1.0 | D3T06048L125-I1.0ISOTM... | 80261 | 6 | .19 | 2.24 | .49 | 3 | 3 | .20 |
| M8x1.25 | | 1.25 | D3T08065L166-I1.25ISOTM... | 80262 | 8 | .26 | 2.48 | .65 | 3 | 3 | .27 |
| M10x1.5 | M12-M48x1.50 | 1.50 | D3T10082L208-I1.50ISOTM... | 80418 | 10 | .32 | 2.87 | .82 | 3 | 3 | .33 |
| M12x1.75 | | 1.75 | D3T10099L250-I1.75ISOTM... | 80419 | 10 | .39 | 2.87 | .98 | 3 | 3 | .41 |
| M16x2.0 | | 2.0 | D3T12119L330-I2.0ISOTM... | 80963 | 12 | .47 | 3.27 | 1.30 | 3 | 3 | .55 |
| M20x2.5 | | 2.50 | D3T16159L413-I2.5ISOTM... | 80962 | 16 | .63 | 3.62 | 1.63 | 3 | 3 | .69 |

MilliPro (D-mm shank)
Miniature Thread Mills

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|-----------------|-----|------|-----|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D(mm) | D2 | L | L1 | Z | Zt | Inch |
| M1.6x0.35 | | 0.35 | D3T03012L050-I0.35ISOTM... | 80421 | 3 | .05 | 1.18 | .20 | 3 | 3 | .05 |
| M2x0.4 | | 0.4 | D3T03015L062-I0.4ISOTM... | 80966 | 3 | .06 | 1.18 | .24 | 3 | 3 | .06 |
| M2x0.4 | | 0.4 | D3T06015L062-I0.4ISOTM... | 80422 | 6 | .06 | 2.24 | .24 | 3 | 3 | .06 |
| M2.5x0.45 | | 0.45 | D3T03019L077-I0.45ISOTM... | 80964 | 3 | .08 | 1.18 | .30 | 3 | 3 | .08 |
| M2.5x0.45 | | 0.45 | D3T06019L077-I0.45ISOTM... | 80265 | 6 | .08 | 2.24 | .30 | 3 | 3 | .08 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T03024L092-I0.5ISOTM... | 80965 | 3 | .09 | 1.18 | .36 | 3 | 3 | .10 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T06024L092-I0.5ISOTM... | 80266 | 6 | .09 | 2.24 | .36 | 3 | 3 | .10 |
| M4x0.7 | | 0.7 | D3T06031L123-I0.7ISOTM... | 80267 | 6 | .12 | 2.24 | .48 | 3 | 3 | .13 |
| M5x0.8 | | 0.8 | D3T06040L154-I0.8ISOTM... | 80268 | 6 | .16 | 2.24 | .61 | 3 | 3 | .17 |
| M6x1.0 | M8-M40x1.0 | 1.00 | D3T06048L185-I1.0ISOTM... | 80269 | 6 | .19 | 2.24 | .73 | 3 | 3 | .20 |
| M8x1.25 | | 1.25 | D3T08065L246-I1.25ISOTM... | 80270 | 8 | .26 | 2.48 | .97 | 3 | 3 | .27 |

* Bore diameter applies to smallest thread dia.



MilliPro
Miniature Thread Mills

2 x Do (L1 ≤ 2 x Thread Diameter)


| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|---------------|----------|-------|-------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| | No.1-72 | 72 | D3T25057L154-I72UNTM... | 80215 | 1/4 | .057 | 2.244 | .154 | 3 | 3 | .059 |
| No.1-64 | No.2-64 | 64 | D3T25055L165-I64UNTM... | 80214 | 1/4 | .055 | 2.244 | .165 | 3 | 3 | .059 |
| No.2-56 | No.3-56 | 56 | D3T25065L197-I56UNTM... | 80216 | 1/4 | .065 | 2.244 | .197 | 3 | 3 | .071 |
| No.3-48 | No.4-48 | 48 | D3T25075L236-I48UNTM... | 80217 | 1/4 | .075 | 2.244 | .236 | 3 | 3 | .079 |
| No.4, No.5-40 | No.6-40 | 40 | D3T25083L236-I40UNTM... | 80218 | 1/4 | .083 | 2.244 | .236 | 3 | 3 | .090 |
| No.5-40 | No.6-40 | 40 | D3T25096L283-I40UNTM... | 80219 | 1/4 | .096 | 2.244 | .283 | 3 | 3 | .102 |
| | No.8-36 | 36 | D3T25130L343-I36UNTM... | 80240 | 1/4 | .130 | 2.244 | .343 | 3 | 3 | .138 |
| No.6, No.8-32 | No.10-32 | 32 | D3T25100L292-I32UNTM... | 80241 | 1/4 | .100 | 2.244 | .292 | 3 | 3 | .110 |
| No.8-32 | No.10-32 | 32 | D3T25126L394-I32UNTM... | 80242 | 1/4 | .126 | 2.244 | .394 | 3 | 3 | .134 |
| | No.10-32 | 32 | D3T25150L406-I32UNTM... | 80694 | 1/4 | .150 | 2.244 | .406 | 3 | 3 | .157 |
| | 1/4"x28 | 28 | D3T25207L520-I28UNTM... | 80243 | 1/4 | .207 | 2.244 | .520 | 3 | 3 | .216 |
| No.10-24 | 5/16"x24 | 24 | D3T25141L402-I24UNTM... | 80244 | 1/4 | .141 | 2.244 | .402 | 3 | 3 | .150 |
| | 5/16"x24 | 24 | D3T31263L650-I24UNTM... | 80245 | 5/16 | .263 | 2.480 | .650 | 3 | 3 | .272 |
| 1/4"x20 | 7/16"x20 | 20 | D3T25192L528-I20UNTM... | 80246 | 1/4 | .192 | 2.244 | .528 | 3 | 3 | .201 |
| | 7/16"x20 | 20 | D3T37375L906-I20UNTM... | 80247 | 3/8 | .375 | 2.874 | .906 | 3 | 3 | .390 |
| 5/16"x18 | | 18 | D3T31242L650-I18UNTM... | 80121 | 5/16 | .242 | 2.480 | .650 | 3 | 3 | .256 |
| 3/8"x16 | | 16 | D3T31264L752-I16UNTM... | 80279 | 3/8 | .264 | 2.480 | .752 | 3 | 3 | .315 |
| 7/16"x14 | | 14 | D3T37354L917-I14UNTM... | 80248 | 3/8 | .354 | 2.874 | .917 | 3 | 3 | .370 |

MilliPro
Miniature Thread Mills

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|---------------|----------|-------|-------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | mm |
| | No.1-72 | 72 | D3T25057L226-I72UNTM... | 80443 | 1/4 | .057 | 2.244 | .226 | 3 | 3 | .059 |
| No.4, No.5-40 | No.6-40 | 40 | D3T25083L354-I40UNTM... | 80263 | 1/4 | .083 | 2.244 | .354 | 3 | 3 | .091 |
| No.5-40 | No.6-40 | 40 | D3T25096L394-I40UNTM... | 80249 | 1/4 | .096 | 2.244 | .394 | 3 | 3 | .102 |
| No.6, No.8-32 | No.10-32 | 32 | D3T25100L433-I32UNTM... | 80264 | 1/4 | .100 | 2.244 | .433 | 3 | 3 | .110 |
| No.8-32 | No.10-32 | 32 | D3T25126L512-I32UNTM... | 80250 | 1/4 | .126 | 2.244 | .512 | 3 | 3 | .134 |
| | No.10-32 | 32 | D3T25150L594-I32UNTM... | 80695 | 1/4 | .150 | 2.244 | .594 | 3 | 3 | .157 |
| | 1/4"x28 | 28 | D3T25207L772-I28UNTM... | 80251 | 1/4 | .207 | 2.244 | .772 | 3 | 3 | .216 |
| | 5/16"x24 | 24 | D3T31263L965-I24UNTM... | 80252 | 5/16 | .263 | 2.480 | .965 | 3 | 3 | .272 |
| 1/4"x20 | 7/16"x20 | 20 | D3T25192L780-I20UNTM... | 80253 | 1/4 | .192 | 2.244 | .780 | 3 | 3 | .201 |
| 5/16"x18 | | 18 | D3T31242L944-I18UNTM... | 80122 | 5/16 | .242 | 2.480 | .944 | 3 | 3 | .256 |

* Bore diameter applies to smallest thread dia.




MilliPro - Miniature Thread Mills

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* | |
|-----------------|-----------------|---------------|--------------------------|-----------------|------|------|-------|---------------|-------|------------|------|
| UNJC | UNJF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| 0.138" (#6) | 0.190" (#10) | 32 | D3T25106L043-I32UNJTM... | 80436 | 1/4 | .106 | 2.244 | .433 | 3 | 3 | .110 |
| | 0.250" (1/4") | 28 | D3T25213L076-I28UNJTM... | 80437 | 1/4 | .213 | 2.244 | .768 | 3 | 3 | .220 |
| 0.190" (#10) | 0.3125" (5/16") | 24 | D3T25146L058-I24UNJTM... | 80438 | 1/4 | .146 | 2.244 | .587 | 3 | 3 | .157 |
| | 0.3125" (5/16") | 24 | D3T31264L094-I24UNJTM... | 80439 | 5/16 | .264 | 2.480 | .949 | 3 | 3 | .276 |
| 0.250" (1/4") | 0.4375" (7/16") | 20 | D3T25197L076-I20UNJTM... | 80445 | 1/4 | .197 | 2.244 | .768 | 3 | 3 | .209 |
| | 0.4375" (7/16") | 20 | D3T37371L131-I20UNJTM... | 80446 | 3/8 | .371 | 2.874 | 1.319 | 3 | 3 | .394 |
| 0.3125" (5/16") | 0.5625" (9/16") | 18 | D3T31252L094-I18UNJTM... | 80961 | 5/16 | .252 | 2.480 | .949 | 3 | 3 | .266 |
| 0.375" (3/8") | 0.750" (3/4") | 16 | D3T31303L114-I16UNJTM... | 80879 | 5/16 | .303 | 2.480 | 1.142 | 3 | 3 | .319 |
| 0.4375" (7/16") | 0.875" (7/8") | 14 | D3T37362L131-I14UNJTM... | 80880 | 3/8 | .362 | 2.874 | 1.319 | 3 | 3 | .374 |
| 0.500" (1/2") | | 13 | D3T37371L151-I13UNJTM... | 80881 | 3/8 | .371 | 2.874 | 1.516 | 3 | 3 | .433 |

MJ



MilliPro - Miniature Thread Mills

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia. |
|-----------|-------|---------------------------|---------|-----------------|------|-------|-------|---------------|-------|-----------|
| MJ | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| MJ3x0.5 | 0.5 | D3T25094L036-I0.5MJTM... | 80882 | 1/4 | .094 | 2.244 | .362 | 3 | 3 | .102 |
| MJ3.5x0.6 | 0.6 | D3T25112L043-I0.6MJTM... | 80883 | 1/4 | .112 | 2.244 | .433 | 3 | 3 | .118 |
| MJ4x0.7 | 0.7 | D3T25124L048-I0.7MJTM... | 80884 | 1/4 | .124 | 2.244 | .484 | 3 | 3 | .134 |
| MJ5x0.8 | 0.8 | D3T25159L060-I0.8MJTM... | 80885 | 1/4 | .159 | 2.244 | .606 | 3 | 3 | .169 |
| MJ6x1.0 | 1.0 | D3T25189L072-I1.0MJTM... | 80886 | 1/4 | .189 | 2.244 | .728 | 3 | 3 | .201 |
| MJ8x1.25 | 1.25 | D3T31256L096-I1.25MJTM... | 80887 | 5/16 | .256 | 2.480 | .969 | 3 | 3 | .272 |
| MJ10x1.5 | 1.50 | D3T37323L121-I1.50MJTM... | 80888 | 3/8 | .323 | 2.874 | 1.213 | 3 | 3 | .343 |
| MJ12x1.75 | 1.75 | D3T37371L145-I1.75MJTM... | 80889 | 3/8 | .371 | 2.874 | 1.457 | 3 | 3 | .409 |
| MJ14x2 | 2.0 | D3T50469L167-I2.0MJTM... | 80890 | 1/2 | .469 | 3.268 | 1.673 | 3 | 3 | .482 |

* Bore diameter applies to smallest thread dia.

TM Solid

Internal

Defined by: R262 (DIN 13)
Tolerance class: 6H

Recommended Overhang

3 Flutes

MilliPro Dental

Miniature Thread Mills for Dental Implants

3xDo (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia. |
|-----------|-----------|-------|----------------------------|---------|-----------------|------|-------|------|---------------|-------|-----------|
| M Coarse | M Fine | mm | Internal | VTH | D(mm) | D2 | L | L1 | Z | Zt | Inch |
| M1.0x0.25 | M1.4x0.25 | 0.25 | D1T03007L031-I0.25ISOTM... | 80210 | 3 | .028 | 1.220 | .122 | 3 | 1 | .030 |
| M1.2x0.25 | M1.4x0.25 | 0.25 | D1T03009L038-I0.25ISOTM... | 80211 | 3 | .035 | 1.220 | .150 | 3 | 1 | .037 |
| M1.4x0.3 | - | 0.30 | D1T03011L044-I0.30ISOTM... | 80212 | 3 | .041 | 1.220 | .173 | 3 | 1 | .045 |
| M1.6x0.35 | - | 0.35 | D1T03012L050-I0.35ISOTM... | 80213 | 3 | .047 | 1.220 | .197 | 3 | 1 | .051 |
| M1.8x0.35 | M2.0x0.35 | 0.35 | D1T03014L056-I0.35ISOTM... | 80280 | 3 | .055 | 1.220 | .220 | 3 | 1 | .059 |
| M2.0x0.4 | - | 0.40 | D1T03015L062-I0.40ISOTM... | 80281 | 3 | .059 | 1.220 | .244 | 3 | 1 | .065 |
| M2.5x0.45 | - | 0.45 | D1T03019L077-I0.45ISOTM... | 80282 | 3 | .077 | 1.220 | .303 | 3 | 1 | .083 |

American UN

MilliPro Dental

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2B

Recommended Overhang

3 Flutes

MilliPro Dental

Miniature Thread Mills for Dental Implants


3xDo (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia. |
|--------|-----|-------|-------------------------|---------|-----------------|------|-------|------|---------------|-------|-----------|
| UNF | TPI | | Internal | VTH | D(mm) | D2 | L | L1 | Z | Zt | Inch |
| 0-80 | 80 | | D1T03011L046-I80UNTM... | 80283 | 3 | .045 | 1.220 | .181 | 3 | 1 | .051 |
| 1-72 | 72 | | D1T03014L065-I72UNTM... | 80413 | 3 | .057 | 1.220 | .256 | 3 | 1 | .063 |

The MilliPro Dental line was specially designed for machining Titanium and Stainless Steel in high RPM. MilliPro Dental DIT tools are also suitable for general use applications.

ISO Metric

MilliPro EL




MilliPro EL Miniature Thread Mills , Extra Long Tools

2 x Do (L1 ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|-----------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| M2x0.4 | | 0.4 | D3T25061L165-I0.4ISOTML... | 80426 | 1/4 | .061 | 3.937 | .165 | 3 | 3 | .063 |
| M2.5x0.45 | | 0.45 | D3T25077L205-I0.45ISOTML... | 80428 | 1/4 | .077 | 3.937 | .205 | 3 | 3 | .081 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | D3T25094L244-I0.5ISOTML... | 80429 | 1/4 | .094 | 3.937 | .244 | 3 | 3 | .098 |

American UN

MilliPro EL



MilliPro EL Miniature Thread Mills, Extra Long Tools


2 x Do (L1 ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|---------------|----------|-------|--------------------------|---------|-----------------|------|-------|------|---------------|-------|------------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| No.2-56 | No.3-56 | 56 | D3T25065L197-I56UNTML... | 80430 | 1/4 | .065 | 3.937 | .197 | 3 | 3 | .071 |
| No.4, No.5-40 | No.6-40 | 40 | D3T25083L236-I40UNTML... | 80431 | 1/4 | .083 | 3.937 | .236 | 3 | 3 | .091 |
| No.6, No.8-32 | No.10-32 | 32 | D3T25100L291-I32UNTML... | 80432 | 1/4 | .100 | 3.937 | .291 | 3 | 3 | .110 |
| No.8-32 | No.10-32 | 32 | D3T25126L394-I32UNTML... | 80433 | 1/4 | .126 | 3.937 | .394 | 3 | 3 | .134 |


* Bore diameter applies to smallest thread dia.

TM Solid

Internal



Defined by: R262 (DIN 13)
Tolerance class: 6H



Left Hand Tool

MilliPro HD

Miniature Thread Mills for Hard Materials Up to 62HRC

2 x Do (L1 ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|-----------------|------|------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| M2x0.4 | | 0.4 | S2L25061L165-I0.4ISOTM... | 80918 | 1/4 | .061 | 2.99 | .18 | 4 | 2 | .063 |
| M2.2x0.45 | | 0.45 | S2L25065L181-I0.45ISOTM... | 80919 | 1/4 | .065 | 2.99 | .20 | 4 | 2 | .071 |
| M2.5x0.45 | | 0.45 | S2L25077L204-I0.45ISOTM... | 80920 | 1/4 | .077 | 2.99 | .22 | 4 | 2 | .081 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | S2L25094L244-I0.5ISOTM... | 80921 | 1/4 | .094 | 2.99 | .27 | 4 | 2 | .101 |
| M3.5x0.6 | | 0.6 | S2L25108L287-I0.6ISOTM... | 80922 | 1/4 | .108 | 2.99 | .31 | 4 | 2 | .116 |
| M4x0.7 | | 0.7 | S2L25124L326-I0.7ISOTM... | 80923 | 1/4 | .124 | 2.99 | .36 | 4 | 2 | .132 |
| M5x0.8 | | 0.8 | S2L25159L409-I0.8ISOTM... | 80924 | 1/4 | .159 | 2.99 | .44 | 4 | 2 | .169 |
| M6x1.0 | M8-M40x1.0 | 1.0 | S2L25189L492-I1.0ISOTM... | 80925 | 1/4 | .189 | 2.99 | .53 | 5 | 2 | .201 |
| M8x1.25 | | 1.25 | S2L31256L653-I1.25ISOTM... | 80926 | 5/16 | .256 | 3.15 | .70 | 5 | 2 | .268 |
| M10x1.5 | M12-M48x1.50 | 1.50 | S2L31308L818-I1.50ISOTM... | 80927 | 5/16 | .308 | 3.15 | .88 | 6 | 2 | .339 |
| M12x1.75 | | 1.75 | S2L37371L984-I1.75ISOTM... | 80928 | 3/8 | .371 | 3.98 | 1.05 | 6 | 2 | .409 |

MilliPro HD

Miniature Thread Mills for Hard Materials Up to 62HRC

3 x Do (L1 ≤ 3 x Thread Diameter)



| Thread | | Pitch | Ordering Code | EDP No. | Dimensions mm | | | | No. of Flutes | Teeth | Bore Dia.* |
|-----------|--------------|-------|----------------------------|---------|---------------|------|------|------|---------------|-------|------------|
| M Coarse | M Fine | mm | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| M2x0.4 | | 0.4 | S2L25061L244-I0.4ISOTM... | 80929 | 1/4 | .061 | 2.99 | .26 | 4 | 2 | .063 |
| M2.5x0.45 | | 0.45 | S2L25077L303-I0.45ISOTM... | 80930 | 1/4 | .077 | 2.99 | .32 | 4 | 2 | .081 |
| M3x0.5 | M3.5-M16x0.5 | 0.5 | S2L25094L362-I0.5ISOTM... | 80931 | 1/4 | .094 | 2.99 | .38 | 4 | 2 | .101 |
| M4x0.7 | | 0.7 | S2L25124L484-I0.7ISOTM... | 80932 | 1/4 | .124 | 2.99 | .51 | 4 | 2 | .132 |
| M5x0.8 | | 0.8 | S2L25159L606-I0.8ISOTM... | 80933 | 1/4 | .159 | 2.99 | .64 | 4 | 2 | .169 |
| M6x1.0 | M8-M40x1.0 | 1.0 | S2L25189L728-I1.0ISOTM... | 80934 | 1/4 | .189 | 2.99 | .77 | 5 | 2 | .201 |
| M8x1.25 | | 1.25 | S2L31256L968-I1.25ISOTM... | 80935 | 5/16 | .256 | 3.15 | 1.02 | 5 | 2 | .268 |

Roughing (Partial Profile)

Finish (Full Profile)

Two cutting teeth: Partial Profile for leading tooth followed by Full Profile for finishing.

The work direction should be from the top to the bottom (Climb Milling).



MilliPro HD Tools are left handed. For CNC use M04 code.

* Bore diameter applies to smallest thread dia.

Internal

Defined by: ANSI B1.1:74
Tolerance class: 2B

Recommended Overhang

4-6 Flutes

Left Hand Tool

MilliPro HD

Miniature Thread Mills for Hard Materials Up to 62HRc

2 x Do (L1 ≤ 2 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|------------------|----------|-------|-------------------------|---------|-----------------|------|------|-------|---------------|-------|------------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| No.2-56 | No.3-56 | 56 | S2L25065L197-I56UNTM... | 80936 | 1/4" | .065 | 3.00 | .210 | 4 | 2 | .071 |
| No.3-48 | No.4-48 | 48 | S2L25075L236-I48UNTM... | 80937 | 1/4" | .075 | 3.00 | .260 | 4 | 2 | .083 |
| No.4-40, No.5-40 | No.6-40 | 40 | S2L25083L236-I40UNTM... | 80938 | 1/4" | .083 | 3.00 | .260 | 4 | 2 | .093 |
| No.5-40 | No.6-40 | 40 | S2L25096L283-I40UNTM... | 80939 | 1/4" | .096 | 3.00 | .310 | 4 | 2 | .104 |
| | No.8-36 | 36 | S2L25130L343-I36UNTM... | 80940 | 1/4" | .130 | 3.00 | .370 | 4 | 2 | .140 |
| No.6-32, No.8-32 | No.10-32 | 32 | S2L25100L292-I32UNTM... | 80941 | 1/4" | .100 | 3.00 | .320 | 4 | 2 | .112 |
| No.8-32 | No.10-32 | 32 | S2L25126L394-I32UNTM... | 80942 | 1/4" | .126 | 3.00 | .420 | 4 | 2 | .138 |
| | No.10-32 | 32 | S2L25146L394-I32UNTM... | 80943 | 1/4" | .146 | 3.00 | .430 | 4 | 2 | .164 |
| | 1/4"x28 | 28 | S2L25207L520-I28UNTM... | 80944 | 1/4" | .207 | 3.00 | .560 | 5 | 2 | .219 |
| No.10-24 | 5/16"x24 | 24 | S2L25141L402-I24UNTM... | 80945 | 1/4" | .141 | 3.00 | .440 | 4 | 2 | .154 |
| | 5/16"x24 | 24 | S2L31263L650-I24UNTM... | 80946 | 5/16" | .263 | 3.15 | .690 | 5 | 2 | .276 |
| 1/4"-20 | 7/16"x20 | 20 | S2L25192L528-I20UNTM... | 80947 | 1/4" | .192 | 3.00 | .580 | 5 | 2 | .205 |
| | 7/16"x20 | 20 | S2L37372L906-I20UNTM... | 80948 | 3/8" | .372 | 4.00 | .960 | 6 | 2 | .390 |
| 5/16"x18 | | 18 | S2L25242L630-I18UNTM... | 80123 | 1/4" | .242 | 3.00 | .715 | 4 | 2 | .256 |
| 3/8"x16 | | 16 | S2L31301L776-I16UNTM... | 80949 | 5/16" | .301 | 3.15 | .840 | 5 | 2 | .315 |
| 7/16"x14 | | 14 | S2L37354L917-I14UNTM... | 80950 | 3/8" | .354 | 4.00 | .990 | 6 | 2 | .374 |
| 1/2"x13 | | 13 | S2L37372L101-I13UNTM... | 80951 | 3/8" | .362 | 4.00 | 1.080 | 6 | 2 | .429 |

MilliPro HD

Miniature Thread Mills for Hard Materials Up to 62HRc

3 x Do (L1 ≤ 3 x Thread Diameter)

| Thread | | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | Bore Dia.* |
|------------------|----------|-------|-------------------------|---------|-----------------|------|------|-------|---------------|-------|------------|
| UNC | UNF | TPI | Internal | VTH | D | D2 | L | L1 | Z | Zt | Inch |
| No.4-40, No.5-40 | No.6-40 | 40 | S2L25083L354-I40UNTM... | 80952 | 1/4" | .083 | 3.00 | .380 | 4 | 2 | .093 |
| No.5-40 | No.6-40 | 40 | S2L25096L394-I40UNTM... | 80953 | 1/4" | .096 | 3.00 | .410 | 4 | 2 | .104 |
| No.6-32, No.8-32 | No.10-32 | 32 | S2L25100L433-I32UNTM... | 80954 | 1/4" | .100 | 3.00 | .460 | 4 | 2 | .111 |
| No.8-32 | No.10-32 | 32 | S2L25126L512-I32UNTM... | 80955 | 1/4" | .126 | 3.00 | .540 | 4 | 2 | .136 |
| | 1/4"x28 | 28 | S2L25207L772-I28UNTM... | 80956 | 1/4" | .207 | 3.00 | .810 | 5 | 2 | .219 |
| | 5/16"x24 | 24 | S2L31263L965-I24UNTM... | 80957 | 5/16" | .263 | 3.15 | 1.010 | 5 | 2 | .272 |
| 1/4"x20 | 7/16"x20 | 20 | S2L25192L780-I20UNTM... | 80958 | 1/4" | .192 | 3.00 | .830 | 5 | 2 | .204 |
| 5/16"x18 | | 18 | S2L25242L945-I18UNTM... | 80124 | 1/4" | .242 | 3.00 | 1.030 | 4 | 2 | .256 |
| 7/16"x14 | | 14 | S2L37354L131-I14UNTM... | 80959 | 3/8" | .354 | 4.00 | 1.390 | 6 | 2 | .375 |

Roughing (Partial Profile) **Finish (Full Profile)**

Two cutting teeth: Partial Profile for leading tooth followed by Full Profile for finishing.

The work direction should be from the top to the bottom (Climb Milling).


1 Pitch

MilliPro HD Tools are left handed. For CNC use M04 code.

* Bore diameter applies to smallest thread dia.

Tap 60°, Tap 55°

Straight



Straight Flutes - Taper 60° TM Solid Straight Flutes for Bone Plate Applications

| Pitch | Ordering Code | EDP No. | Taper | Thread Angle | Profile Height | Dimensions Inch | | | | | No. of Flutes | Teeth |
|-------|-------------------------------|---------|-------|--------------|----------------|-----------------|------|------|-------|------|---------------|-------|
| mm | Internal | VTS | | α | h | D | D2 | D1 | L | Le | Z | Zt |
| 0.4 | S1/4".232"L315-I0.4TAP60TM... | 80975 | 20° | 60° | .008 | 1/4 | .232 | .126 | 2.244 | .315 | 3 | 20 |
| 0.5 | S1/4".232"L354-I0.5TAP60TM... | 80976 | 20° | 60° | .010 | 1/4 | .232 | .114 | 2.244 | .354 | 3 | 18 |

Straight Flutes - Taper 55° TM Solid Straight Flutes for Bone Plate Applications

| Pitch | Ordering Code | EDP No. | Taper | Thread Angle | Profile Height | Dimensions Inch | | | | | No. of Flutes | Teeth |
|-------|---------------------------------|---------|-------|--------------|----------------|-----------------|------|------|-------|------|---------------|-------|
| mm | Internal | VTS | | α | h | D | D2 | D1 | L | Le | Z | Zt |
| 0.3 | S1/8".110"L154-I0.3TAP55TM... | 80977 | 20° | 55° | .007 | 1/8 | .110 | .059 | 1.496 | .154 | 3 | 13 |
| 0.35 | S3/16".154"L248-I0.35TAP55TM... | 80978 | 20° | 55° | .008 | 3/16 | .154 | .071 | 1.772 | .248 | 3 | 18 |
| 0.4 | S1/4".232"L394-I0.4TAP55TM... | 80979 | 20° | 55° | .011 | 1/4 | .232 | .098 | 2.244 | .394 | 3 | 25 |
| 0.5 | S1/4".232"L354-I0.5TAP55TM... | 80980 | 20° | 55° | .013 | 1/4 | .232 | .114 | 2.244 | .354 | 3 | 18 |
| 0.6 | S1/4".232"L260-I0.6TAP55TM... | 80981 | 20° | 55° | .019 | 1/4 | .232 | .150 | 2.244 | .260 | 3 | 11 |

External / Internal

Defined by: R262 (DIN 13)
Tolerance class: 6g/6H

Straight Flutes - External



| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | mm | External | VTS | D | D2 | L | Le | Z | Zt | h |
| M3 | 0.50 | S1/4".240"-E0.5ISOTM... | 80000 | 1/4 | .240 | 2.244 | .591 | 3 | 30 | .012 |
| M4.5 | 0.75 | S5/16".310"-E0.75ISOTM3... | 80001 | 5/16 | .310 | 2.480 | .610 | 3 | 26 | .019 |
| M4.5 | 0.75 | S5/16".310"-E0.75ISOTM5... | 80444 | 5/16 | .310 | 2.480 | .610 | 5 | 26 | .019 |
| M6 | 1.00 | S3/8".370"-E1.0ISOTM... | 80002 | 3/8 | .370 | 2.835 | .945 | 5 | 24 | .025 |
| M10 | 1.50 | S1/2".470"-E1.5ISOTM... | 80003 | 1/2 | .470 | 3.268 | 1.181 | 5 | 20 | .037 |
| M14 | 2.00 | S1/2".470"-E2.0ISOTM... | 80004 | 1/2 | .470 | 3.268 | 1.181 | 5 | 15 | .050 |
| M24 | 3.00 | S5/8".620"-E3.0ISOTM... | 80005 | 5/8 | .620 | 3.622 | 1.417 | 5 | 12 | .075 |
| M36 | 4.00 | S5/8".620"-E4.0ISOTM... | 80006 | 5/8 | .620 | 3.622 | 1.575 | 5 | 10 | .100 |
| M64 | 6.00 | S3/4".745"-E6.0ISOTM... | 80007 | 3/4 | .745 | 4.095 | 1.417 | 5 | 6 | .149 |

Straight Flutes - Internal

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | mm | Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| M4.5 | 0.75 | S1/8".120"-I0.75ISOTM... | 80008 | 1/8 | .120 | 1.496 | .270 | 3 | 9 | .017 |
| M8 | 0.75 | S1/4".240"-I0.75ISOTM... | 80009 | 1/4 | .240 | 2.244 | .591 | 3 | 20 | .017 |
| M5 | 0.80 | S3/16".145"-I0.8ISOTM... | 80010 | 3/16 | .145 | 1.654 | .315 | 3 | 10 | .018 |
| M6 | 1.00 | S3/16".160"-I1.0ISOTM... | 80011 | 3/16 | .160 | 1.654 | .354 | 3 | 9 | .023 |
| M12 | 1.00 | S5/16".310"-I1.0ISOTM3... | 80012 | 5/16 | .310 | 2.480 | .787 | 3 | 20 | .023 |
| M12 | 1.00 | S5/16".310"-I1.0ISOTM5... | 80239 | 5/16 | .310 | 2.480 | .787 | 5 | 20 | .023 |
| M8 | 1.25 | S1/4".200"-I1.25ISOTM... | 80013 | 1/4 | .200 | 2.244 | .492 | 3 | 10 | .029 |
| M10 | 1.50 | S1/4".240"-I1.5ISOTM... | 80014 | 1/4 | .240 | 2.244 | .591 | 3 | 10 | .035 |
| M14 | 1.50 | S3/8".370"-I1.5ISOTM... | 80015 | 3/8 | .370 | 2.835 | .945 | 5 | 16 | .035 |
| M18 | 1.50 | S1/2".470"-I1.5ISOTM... | 80016 | 1/2 | .470 | 3.268 | 1.181 | 5 | 20 | .035 |
| M12 | 1.75 | S5/16".310"-I1.75ISOTM3... | 80017 | 5/16 | .310 | 2.480 | .758 | 3 | 11 | .040 |
| M12 | 1.75 | S5/16".310"-I1.75ISOTM5... | 80236 | 5/16 | .310 | 2.480 | .758 | 5 | 11 | .040 |
| M16 | 2.00 | S3/8".370"-I2.0ISOTM... | 80018 | 3/8 | .370 | 2.835 | .944 | 5 | 12 | .046 |
| M18 | 2.00 | S1/2".470"-I2.0ISOTM... | 80019 | 1/2 | .470 | 3.268 | 1.181 | 5 | 15 | .046 |
| M20 | 2.50 | S1/2".470"-I2.5ISOTM... | 80020 | 1/2 | .470 | 3.268 | 1.181 | 5 | 12 | .058 |
| M24 | 3.00 | S5/8".620"-I3.0ISOTM... | 80021 | 5/8 | .620 | 3.622 | 1.417 | 5 | 12 | .069 |
| M30 | 3.50 | S5/8".620"-I3.5ISOTM... | 80022 | 5/8 | .620 | 3.622 | 1.516 | 5 | 11 | .081 |
| M36 | 4.00 | S5/8".620"-I4.0ISOTM... | 80023 | 5/8 | .620 | 3.622 | 1.575 | 5 | 10 | .092 |
| M48 | 5.00 | S3/4".745"-I5.0ISOTM... | 80024 | 3/4 | .745 | 4.095 | 1.575 | 5 | 8 | .116 |
| M64 | 6.00 | S3/4".745"-I6.0ISOTM... | 80025 | 3/4 | .745 | 4.095 | 1.417 | 5 | 6 | .139 |

TM Solid

External / Internal



Defined by: ANSI B1.1:74
Tolerance class: 2A/2B



Straight Flutes - External

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External | VTS | D | D2 | L | Le | Z | Zt | h |
| No.6 | 32 | S1/4".240"-E32UNTM... | 80026 | 1/4 | .240 | 2.244 | .562 | 3 | 18 | .019 |
| No.12 | 28 | S5/16".310"-E28UNTM3... | 80027 | 5/16 | .310 | 2.480 | .786 | 3 | 22 | .022 |
| No.12 | 28 | S5/16".310"-E28UNTM5... | 80408 | 5/16 | .310 | 2.480 | .786 | 5 | 22 | .022 |
| 1/4" | 20 | S3/8".370"-E20UNTM... | 80028 | 3/8 | .370 | 2.835 | .900 | 5 | 18 | .031 |
| 5/16" | 18 | S3/8".370"-E18UNTM... | 80029 | 3/8 | .370 | 2.835 | .944 | 5 | 17 | .034 |
| 3/8" | 16 | S1/2".470"-E16UNTM... | 80030 | 1/2 | .470 | 3.268 | 1.125 | 5 | 18 | .038 |
| 9/16" | 12 | S1/2".470"-E12UNTM... | 80031 | 1/2 | .470 | 3.268 | 1.167 | 5 | 14 | .051 |
| 1" | 8 | S5/8".620"-E8UNTM... | 80032 | 5/8 | .620 | 3.622 | 1.500 | 5 | 12 | .077 |
| 1 3/8" | 6 | S5/8".620"-E6UNTM... | 80033 | 5/8 | .620 | 3.622 | 1.500 | 5 | 9 | .102 |

Straight Flutes - Internal

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|-------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| No.8 | 36 | S1/8".120"-I36UNTM... | 80034 | 1/8 | .120 | 1.654 | .250 | 3 | 9 | .016 |
| No.8 | 32 | S1/8".120"-I32UNTM... | 80035 | 1/8 | .120 | 1.654 | .250 | 3 | 8 | .018 |
| 5/16" | 32 | S1/4".240"-I32UNTM... | 80036 | 1/4 | .240 | 2.244 | .562 | 3 | 18 | .018 |
| No.12 | 28 | S3/16".145"-I28UNTM... | 80037 | 3/16 | .145 | 1.654 | .321 | 3 | 9 | .021 |
| 7/16" | 28 | S5/16".310"-I28UNTM3... | 80038 | 5/16 | .310 | 2.480 | .786 | 3 | 22 | .021 |
| 7/16" | 28 | S5/16".310"-I28UNTM5... | 80441 | 5/16 | .310 | 2.480 | .786 | 5 | 22 | .021 |
| No.12 | 24 | S3/16".160"-I24UNTM... | 80039 | 3/16 | .160 | 2.244 | .333 | 3 | 8 | .024 |
| 1/4" | 20 | S3/16".160"-I20UNTM... | 80040 | 3/16 | .160 | 2.244 | .400 | 3 | 8 | .029 |
| 9/16" | 20 | S3/8".370"-I20UNTM... | 80041 | 3/8 | .370 | 2.835 | .900 | 5 | 18 | .029 |
| 5/16" | 18 | S1/4".200"-I18UNTM... | 80440 | 1/4 | .200 | 2.244 | .500 | 3 | 9 | .033 |
| 9/16" | 18 | S3/8".370"-I18UNTM... | 80043 | 3/8 | .370 | 2.835 | .944 | 5 | 17 | .033 |
| 3/8" | 16 | S1/4".240"-I16UNTM... | 80044 | 1/4 | .240 | 2.244 | .562 | 3 | 9 | .037 |
| 13/16" | 16 | S1/2".470"-I16UNTM... | 80045 | 1/2 | .470 | 3.268 | 1.125 | 5 | 18 | .037 |
| 7/16" | 14 | S5/16".310"-I14UNTM3... | 80046 | 5/16 | .310 | 2.480 | .714 | 3 | 10 | .042 |
| 7/16" | 14 | S5/16".310"-I14UNTM5... | 80238 | 5/16 | .310 | 2.480 | .714 | 5 | 10 | .042 |
| 1/2" | 13 | S5/16".310"-I13UNTM3... | 80047 | 5/16 | .310 | 2.480 | .769 | 3 | 10 | .045 |
| 1/2" | 13 | S5/16".310"-I13UNTM5... | 80237 | 5/16 | .310 | 2.480 | .769 | 5 | 10 | .045 |
| 9/16" | 12 | S3/8".370"-I12UNTM... | 80048 | 3/8 | .370 | 2.835 | .917 | 5 | 11 | .049 |
| 1" | 12 | S1/2".470"-I12UNTM... | 80049 | 1/2 | .470 | 3.268 | 1.167 | 5 | 14 | .049 |
| 5/8" | 11 | S3/8".370"-I11UNTM... | 80050 | 3/8 | .370 | 2.835 | .909 | 5 | 10 | .053 |
| 3/4" | 10 | S1/2".470"-I10UNTM... | 80051 | 1/2 | .470 | 3.268 | 1.100 | 5 | 11 | .059 |
| 7/8" | 9 | S5/8".620"-I9UNTM... | 80442 | 5/8 | .620 | 3.622 | 1.333 | 5 | 12 | .065 |
| 1" | 8 | S5/8".620"-I8UNTM... | 80053 | 5/8 | .620 | 3.622 | 1.500 | 5 | 12 | .073 |
| 1 1/8" | 7 | S5/8".620"-I7UNTM... | 80054 | 5/8 | .620 | 3.622 | 1.429 | 5 | 10 | .084 |
| 1 3/8" | 6 | S3/4".745"-I6UNTM... | 80055 | 3/4 | .745 | 4.095 | 1.500 | 5 | 9 | .098 |
| 1 3/4" | 5 | S3/4".745"-I5UNTM... | 80057 | 3/4 | .745 | 4.095 | 1.600 | 5 | 8 | .117 |
| 2" | 4.5 | S3/4".745"-I4.5UNTM... | 80058 | 3/4 | .745 | 4.095 | 1.555 | 5 | 7 | .130 |

External / Internal





Defined by: B.S.84:1956, DIN 259, ISO228/1:1982
Tolerance class: Medium class A

Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|---------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| 1/4" | 20 | S3/16".160"-EI20BSWTM... | 80059 | 3/16 | .160 | 1.654 | .400 | 3 | 8 | .032 |
| 5/16" | 18 | S1/4".200"-EI18BSWTM... | 80060 | 1/4 | .200 | 2.244 | .444 | 3 | 8 | .035 |
| 3/8" | 16 | S1/4".240"-EI16BSWTM... | 80061 | 1/4 | .240 | 2.244 | .562 | 3 | 9 | .040 |
| 7/16" | 14 | S5/16".310"-EI14BSWTM3... | 80062 | 5/16 | .310 | 2.480 | .714 | 3 | 10 | .046 |
| 7/16" | 14 | S5/16".310"-EI14BSWTM5... | 80232 | 5/16 | .310 | 2.480 | .714 | 5 | 10 | .046 |
| 1/2" | 12 | S5/16".310"-EI12BSWTM3... | 80063 | 5/16 | .310 | 2.480 | .750 | 3 | 9 | .053 |
| 1/2" | 12 | S5/16".310"-EI12BSWTM5... | 80447 | 5/16 | .310 | 2.480 | .750 | 5 | 9 | .053 |
| 5/8" | 11 | S3/8".370"-EI11BSWTM... | 80064 | 3/8 | .370 | 2.835 | .909 | 5 | 10 | .058 |
| 3/4" | 10 | S1/2".470"-EI10BSWTM... | 80065 | 1/2 | .470 | 3.268 | 1.100 | 5 | 11 | .064 |
| 7/8" | 9 | S1/2".470"-EI9BSWTM... | 80066 | 1/2 | .470 | 3.268 | 1.111 | 5 | 10 | .071 |
| 1" | 8 | S5/8".620"-EI8BSWTM... | 80067 | 5/8 | .620 | 3.622 | 1.500 | 5 | 12 | .080 |
| 1 1/8" | 7 | S5/8".620"-EI7BSWTM... | 80068 | 5/8 | .620 | 3.622 | 1.429 | 5 | 10 | .091 |
| 1 3/8" | 6 | S5/8".620"-EI6BSWTM... | 80069 | 5/8 | .620 | 3.622 | 1.500 | 5 | 9 | .107 |
| 1 5/8" | 5 | S3/4".745"-EI5BSWTM... | 80070 | 3/4 | .745 | 4.095 | 1.600 | 5 | 8 | .128 |
| 1 7/8" | 4.5 | S3/4".745"-EI4.5BSWTM... | 80071 | 3/4 | .745 | 4.095 | 1.555 | 5 | 7 | .142 |

External / Internal



Defined by: B.S.2779:1956
Tolerance class: Medium class

Straight Flutes



| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|---------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| 1/16" | 28 | S1/4".240"-EI28BSPTM... | 80076 | 1/4 | .240 | 2.244 | .571 | 3 | 16 | .023 |
| 1/4" | 19 | S5/16".310"-EI19BSPTM3... | 80073 | 5/16 | .310 | 2.480 | .737 | 3 | 14 | .034 |
| 1/4" | 19 | S5/16".310"-EI19BSPTM5... | 80234 | 5/16 | .310 | 2.480 | .737 | 5 | 14 | .034 |
| 1/2" | 14 | S1/2".470"-EI14BSPTM... | 80074 | 1/2 | .470 | 3.268 | 1.143 | 5 | 16 | .046 |
| 1" | 11 | S5/8".620"-EI11BSPTM... | 80075 | 5/8 | .620 | 3.622 | 1.364 | 5 | 15 | .058 |

TM Solid

BSPT

Straight

External / Internal



Defined by: B.S.21:1985
Tolerance class: Standard BSPT



Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|-----------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| 1/16" | 28 | S1/4".240"-EI28BSPT-TM... | 80072 | 1/4 | .240 | 2.244 | .393 | 3 | 11 | .023 |
| 1/4" | 19 | S5/16".310"-EI19BSPT-TM3... | 80077 | 5/16 | .310 | 2.480 | .579 | 3 | 11 | .034 |
| 1/4" | 19 | S5/16".310"-EI19BSPT-TM5... | 80235 | 5/16 | .310 | 2.480 | .579 | 5 | 11 | .034 |
| 1/2" | 14 | S1/2".470"-EI14BSPT-TM... | 80078 | 1/2 | .470 | 3.268 | .786 | 5 | 11 | .046 |
| 1" | 11 | S5/8".620"-EI11BSPT-TM... | 80079 | 5/8 | .620 | 3.622 | 1.545 | 5 | 17 | .058 |

NPT

Straight

External / Internal



Defined by: USAS B2.1:1968
Tolerance class: Standard NPT

Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| 1/16" | 27 | S1/4".240"-EI27NPT-TM... | 80080 | 1/4 | .240 | 2.244 | .370 | 3 | 10 | .030 |
| 1/4" | 18 | S5/16".310"-EI18NPT-TM3... | 80081 | 5/16 | .310 | 2.480 | .555 | 3 | 10 | .044 |
| 1/4" | 18 | S5/16".310"-EI18NPT-TM5... | 80190 | 5/16 | .310 | 2.480 | .555 | 5 | 10 | .044 |
| 1/2" | 14 | S1/2".470"-EI14NPT-TM... | 80082 | 1/2 | .470 | 3.268 | .786 | 5 | 11 | .057 |
| 1" | 11.5 | S5/8".620"-EI11.5NPT-TM... | 80083 | 5/8 | .620 | 3.622 | 1.043 | 5 | 12 | .070 |
| 2 1/2" | 8 | S5/8".620"-EI8NPT-TM... | 80084 | 5/8 | .620 | 3.622 | 1.500 | 5 | 12 | .100 |

External / Internal

Defined by: MIL-P-7105B
Tolerance class: Standard ANPT



Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|-----------------------------|---------|-----------------|------|-------|------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | | D | D2 | L | Le | Z | Zt | h |
| 1/4" | 18 | S5/16".310"-EI18ANPT-TM5... | 81056 | 5/16 | .310 | 2.480 | .555 | 5 | 10 | .044 |
| 1/2" | 14 | S1/2".470"-EI14ANPT-TM... | 81057 | 1/2 | .470 | 3.268 | .786 | 5 | 11 | .057 |

NPTF

Straight

External / Internal



Defined by: ANSI 1.20.3-1976
Tolerance class: Standard NPTF



Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|-----------|-------|----------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| Min. Dia. | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| 1/16" | 27 | S1/4".240"-EI27NPTFTM... | 80085 | 1/4 | .240 | 2.244 | .370 | 3 | 10 | .030 |
| 1/4" | 18 | S5/16".310"-EI18NPTFTM3... | 80086 | 5/16 | .310 | 2.480 | .555 | 3 | 10 | .044 |
| 1/4" | 18 | S5/16".310"-EI18NPTFTM5... | 80233 | 5/16 | .310 | 2.480 | .555 | 5 | 10 | .044 |
| 1/2" | 14 | S1/2".470"-EI14NPTFTM... | 80087 | 1/2 | .470 | 3.268 | .786 | 5 | 11 | .057 |
| 1" | 11.5 | S5/8".620"-EI11.5NPTFTM... | 80088 | 5/8 | .620 | 3.622 | 1.043 | 5 | 12 | .070 |
| 2 1/2" | 8 | S5/8".620"-EI8NPTFTM... | 80089 | 5/8 | .620 | 3.622 | 1.500 | 5 | 12 | .100 |

Pg

Straight

External / Internal



Defined by: DIN 40430
Tolerance class: Standard

Straight Flutes

| Thread | Pitch | Ordering Code | EDP No. | Dimensions Inch | | | | No. of Flutes | Teeth | |
|----------------------|-------|--------------------------|---------|-----------------|------|-------|-------|---------------|-------|------|
| | TPI | External / Internal | VTS | D | D2 | L | Le | Z | Zt | h |
| Pg7 | 20 | S5/16".310"-EI20PGTM3... | 80090 | 5/16 | .310 | 2.480 | .750 | 3 | 15 | .024 |
| Pg7 | 20 | S5/16".310"-EI20PGTM5... | 80448 | 5/16 | .310 | 2.480 | .750 | 5 | 15 | .024 |
| Pg9, 11, 13.5, 16 | 18 | S3/8".370"-EI18PGTM... | 80091 | 3/8 | .370 | 2.835 | .944 | 5 | 17 | .026 |
| Pg21, 29, 36, 42, 48 | 16 | S1/2".470"-EI16PGTM... | 80092 | 1/2 | .470 | 3.268 | 1.125 | 5 | 18 | .030 |

Grades and Their Applications

VTH

Helicool HCR HCC

MilliPro MilliPro Dental MilliPro HD

MilliPro EL Deep Threading Helical

- A general-purpose, heavy duty thread milling grade
- TiCN coated for high resistance to wear

VTS

Straight

- A general-purpose grade, specially designed for TM Solid Straight Flute cutters
- TiAlN coated for high resistance to wear

VTS

HTC (Thriller)

- TiAlN coated grade
- First choice for Cast Iron and general use

VTN

HTC (Thriller)

- Uncoated grade
- First choice for Aluminium and general use




TM Solid

Recommended Cutting Speeds Vc [ft/min] and Feed f [inch/tooth] (Not Including HTC & MilliPro HD)

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | | Feed [inch/tooth] | | | | | |
|--------------------------------|-------------------------------------|--|------------------------------------|---|---------|----------|-------------------|-------------|----------------|------------------|-------------|-------------|
| | | | | Helicool, HCR, HCC, Helical, Straight, Deep Threading | | MilliPro | He-Lex | Straight | Deep Threading | Helicool HCC HCR | MilliPro | |
| | | | | VTH | VTS | VTH | | | | | | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 262-820 | 164-590 | 197-393 | .0012-.0031 | .0012-.0031 | .0039-.0138 | .0012-.0031 | .0008-.0063 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 262-754 | 164-459 | 197-393 | .0012-.0031 | .0012-.0031 | .0031-.0118 | .0012-.0031 | .0008-.0063 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 262-656 | 164-393 | 197-295 | .0012-.0031 | .0012-.0024 | .0031-.0118 | .0012-.0031 | .0008-.0063 |
| | 4 | Low Alloy Steel (alloying elements ≤5%) | Non Hardened | 180 | 197-590 | 197-557 | 197-295 | .0012-.0031 | .0012-.0028 | .0031-.0118 | .0012-.0031 | .0008-.0063 |
| | 5 | | Hardened | 275 | 197-557 | 197-525 | 164-262 | .0012-.0028 | .0012-.0028 | .0031-.0118 | .0012-.0028 | .0008-.0028 |
| | 6 | | Hardened | 350 | 197-525 | 197-492 | 164-262 | .0008-.002 | .0008-.0016 | .002-.0059 | .0008-.0024 | .0008-.0012 |
| | 7 | High Alloy Steel (alloying elements >5%) | Annealed | 200 | 131-328 | 131-295 | 164-262 | .0012-.0028 | .0012-.0028 | .0039-.0094 | .0012-.0028 | .0008-.0035 |
| | 8 | | Hardened | 325 | 98-262 | 98-230 | 164-262 | .0008-.0016 | .0008-.002 | .002-.0059 | .0012-.0024 | .0008-.0012 |
| | 9 | Cast Steel | Low Alloy (alloying elements <5%) | 200 | 262-820 | 230-656 | 230-295 | .0012-.0031 | .0012-.0024 | .0031-.0118 | .0012-.0028 | .0008-.0063 |
| | 10 | | High Alloy (alloying elements >5%) | 225 | 197-557 | 197-492 | 197-262 | .0012-.002 | .0012-.0024 | .002-.0059 | .0012-.0028 | .0008-.0012 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 197-492 | 164-459 | 197-295 | .0016-.0028 | .0008-.002 | .0043-.0138 | .0012-.0031 | .0008-.0063 |
| | 12 | | Hardened | 330 | 197-393 | 164-361 | 164-262 | .0008-.0024 | .0004-.0012 | .002-.0094 | .0012-.0024 | .0008-.0012 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 197-459 | 197-426 | 197-295 | .0012-.0031 | .0008-.002 | .0043-.0138 | .0012-.0031 | .0008-.0063 |
| | 14 | | Super Austenitic | 200 | 197-426 | 164-393 | 164-262 | .0012-.0031 | .0008-.002 | .0043-.0138 | .0012-.0024 | .0008-.0063 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 197-525 | 164-492 | 197-295 | .0012-.0031 | .0008-.002 | .0043-.0138 | .0012-.0024 | .0008-.0063 |
| | 16 | | Hardened | 330 | 197-361 | 164-328 | 164-262 | .0008-.002 | .0008-.0012 | .0039-.0094 | .0008-.002 | .0008-.0012 |
| | 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 197-492 | 164-459 | 197-295 | .0012-.0031 | .0008-.0024 | .0043-.0138 | .0008-.002 | .0008-.0063 |
| | 18 | | Hardened | 330 | 197-328 | 164-295 | 164-262 | .0008-.002 | .0004-.0012 | .0039-.0094 | .0008-.0016 | .0008-.0012 |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 197-230 | 197-492 | 164-262 | .0012-.0031 | .0012-.0031 | .002-.0059 | .0012-.0031 | .0008-.0012 |
| | 29 | | Pearlitic (long chips) | 230 | 197-492 | 262-328 | 197-295 | .0012-.0031 | .0012-.0024 | .0039-.0094 | .0012-.0028 | .0008-.0047 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 230-525 | 164-459 | 230-328 | .0012-.0031 | .0012-.0024 | .0035-.0098 | .0012-.0028 | .0008-.0063 |
| | 31 | | High Tensile Strength | 260 | 131-393 | 131-361 | 197-295 | .0008-.0024 | .0008-.002 | .0039-.0094 | .0012-.0028 | .0008-.0047 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 131-361 | 131-328 | 230-328 | .0012-.0031 | .0012-.0028 | .0035-.0098 | .0012-.0031 | .0008-.0063 |
| | 33 | | Pearlitic | 260 | 131-328 | 131-295 | 197-295 | .0008-.0024 | .0008-.002 | .0039-.0094 | .0012-.0028 | .0008-.0047 |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 656-984 | 492-820 | 197-820 | .002-.0047 | .002-.0059 | .0047-.0157 | .0016-.0039 | .0012-.0059 |
| | 35 | | Aged | 100 | 492-820 | 328-721 | 197-492 | .002-.0047 | .0012-.0039 | .0039-.0126 | .0012-.0039 | .0012-.0063 |
| | 36 | Aluminium Alloys | Cast | 75 | 328-656 | 262-492 | 197-820 | .002-.0047 | .002-.0059 | .0039-.0126 | .0012-.0039 | .0012-.0063 |
| | 37 | | Cast & Aged | 90 | 393-721 | 295-525 | 197-492 | .002-.0047 | .0012-.0039 | .0039-.0118 | .0024-.0047 | .0008-.0063 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 656-984 | 492-820 | 820 | .002-.0047 | .002-.0059 | .0039-.0126 | .002-.0047 | .0012-.0059 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 656-984 | 492-820 | 197-820 | .0024-.0051 | .002-.0059 | .0047-.0157 | .002-.0047 | .0012-.0063 |
| | 40 | | Bronze And Non Leaded Copper | 100 | 492-820 | 328-721 | 197-492 | .002-.0047 | .0012-.0039 | .0039-.0126 | .002-.0047 | .0012-.0059 |
| | S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 98-197 | 98-164 | 197 | .0012-.0028 | .0008-.0016 | .0043-.0138 | .0012-.0276 |
| 20 | | Aged (iron based) | | 280 | 66-164 | 66-131 | 164 | .0008-.0016 | .0004-.0012 | .002-.0059 | .0012-.0024 | .0008-.0012 |
| 21 | | Annealed (nickel or cobalt based) | | 250 | 49-115 | 49-98 | 115 | .0008-.0016 | .0004-.0012 | .002-.0059 | .0012-.0024 | .0008-.0012 |
| 22 | | Aged (nickel or cobalt based) | | 350 | 49-98 | 49-82 | 98 | .0008-.0016 | .0004-.0012 | .002-.0059 | .0008-.002 | .0008-.0012 |
| 23 | | Titanium Alloys | Pure 99.5 Ti | 400Rm | 131-262 | 98-230 | 98-164 | .0008-.0016 | .0004-.0012 | .0039-.0094 | .0008-.002 | .0008-.0028 |
| 24 | α+β Alloys | | 1050Rm | 66-164 | 66-148 | 82-115 | .0008-.0016 | .0004-.0008 | .0039-.0094 | .0008-.0016 | .0008-.0028 | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50Hrc | 49-148 | 49-115 | 148 | .0008-.0012 | .0008 | .0012-.0024 | .0008-.0012 | - |
| | 26 | | | 51-55Hrc | 49-131 | 49-98 | 98 | .0008-.0012 | .0004 | .0012-.0024 | .0008-.0012 | - |

Recommendation:
At tool entry, set the Feed f [inch/tooth] to 70% lower than the threading Feed.

Example:
Threading Feed: .012[inch/tooth]
Tool entry Feed: .0035[inch/tooth]



MilliPro HD Cutting Speeds Vc [ft/min] and Feed f [inch/tooth]

| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] Feed f [inch/tooth] by Cutting Dia.=D2 | | | | | | |
|-------------------------------------|------------|---|-----------------------------------|--|---------|---------|---------|---------|---------|-------|
| | | | | VTH | .06-.10 | .10-.20 | .20-.30 | .30-.35 | .35-.45 | |
| P Steel | 6 | Low Alloy Steel (alloying elements≤5%) Hardened | 350 | 82-525 | .0016 | .0020 | .0024 | .0028 | .0031 | |
| | 8 | High Alloy Steel (alloying elements>5%) Hardened | 325 | 82-591 | | | | | | |
| M Stainless Steel | 12 | Stainless Steel Ferritic Hardened | 330 | 82-394 | .0016 | .0020 | .0024 | .0028 | .0031 | |
| | 16 | Stainless Steel Cast Ferritic Hardened | 330 | 82-361 | | | | | | |
| | 18 | Stainless Steel Cast Austenitic Hardened | 330 | 82-328 | | | | | | |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 82-525 | .0020 | .0024 | .0028 | .0031 | .0039 |
| | 29 | | Pearlitic (long chips) | 230 | 82-492 | .0016 | .0020 | .0024 | .0028 | .0031 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 82-427 | .0020 | .0024 | .0028 | .0031 | .0039 |
| | 31 | | High Tensile Strength | 260 | 82-328 | .0016 | .0020 | .0024 | .0028 | .0031 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 82-410 | .0016 | .0020 | .0024 | .0028 | .0035 |
| | 33 | | Pearlitic | 260 | 82-295 | .0012 | .0016 | .0020 | .0024 | .0028 |
| S Heat Resistant Material | 21 | High Temperature Alloys | Annealed (nickel or cobalt based) | 250 | 49-115 | .0012 | .0016 | .0020 | .0024 | .0028 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 49-98 | | | | | |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 82-230 | | | | | |
| | 24 | | α+β alloys | 1050Rm | 82-164 | | | | | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRC | 82-230 | .0016 | .0020 | .0024 | .0028 | .0031 |
| | 26 | | | 51-55HRC | 82-197 | .0012 | .0016 | .0020 | .0024 | .0028 |
| | 27 | | | 56-62HRC | 82-164 | .0008 | .0012 | .0016 | .0020 | .0024 |


HTC Recommended Grades, Cutting Speed and Feed

| Material Group | Material | Hardness Brinell HB | Strength (N-mm ²) | Vc[ft/min] | | fb[Inch/rev] | | fz[inch/tooth] | | |
|--------------------------------|---------------------|--|-------------------------------|------------|-----------|--------------|-----------|----------------|-----------|-----------|
| | | | | VTN | VTS | ≤.24 inch | ≤.47 inch | ≤.24 inch | ≤.47 inch | |
| K Cast Iron | Cast Iron | Grey Cast Iron | ≤150 | ≤500 | 164-262 | 262-394 | .004-.006 | .006-.009 | .001-.002 | .002-.004 |
| | | Grey Cast Iron, Heat Treated | 150-300 | 500-1000 | 164-262 | 262-394 | .004-.006 | .006-.009 | .001-.002 | .002-.004 |
| | | Spher. Graph. Cast Iron | ≤200 | ≤700 | 164-262 | 262-394 | .004-.006 | .006-.009 | .001-.002 | .002-.004 |
| N Non-Ferrous Metals | Aluminium/Magnesium | Copper | ≤200 | ≤700 | 328-984 | — | .002-.004 | .004-.012 | .001-.002 | .002-.004 |
| | | Aluminium, Magnesium Non-Alloy | ≤100 | ≤350 | 328-1,312 | 328-1,312 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| | | Aluminium, Wrought Alloy, Breaking Strain (A5) < 14% | ≤180 | ≤600 | 328-1,312 | 328-1,312 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| | | Aluminium, Wrought Alloy, Breaking Strain (A5) ≥ 14% | ≤180 | ≤600 | 328-1,312 | 328-1,312 | .001-.002 | .002-.005 | .001-.002 | .002-.004 |
| | | Aluminium, Cast Alloy, Si<10% | ≤180 | ≤600 | 328-984 | 328-1,312 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| | | Aluminium, Cast Alloy, Si≥10% | ≤180 | ≤600 | — | 328-984 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| K Plastic | Plastic | Thermo Plastics | — | — | 197-394 | 197-394 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| | | Thermosetting Plastic | — | — | 197-328 | 197-328 | .004-.010 | .010-.012 | .001-.002 | .002-.004 |
| | | Fiber Reinforced Plastic | — | — | 131-197 | 197-262 | .004-.006 | .006-.009 | .001-.002 | .002-.004 |

Vc - Cutting Speed [ft/min]

fb - (Drilling) - Feed per Revolution [inch/rev]

fz - (Threading) - Feed per Tooth [inch/tooth]



VARGUS
GENIUS™
Tool Selector and CNC
Program Generator

Thread Milling Technical Data

About Thread Milling

To perform a thread milling operation, a milling machine with three-axis control capable of helical interpolation is required. Helical interpolation is a CNC function producing tool movement along a helical path. This helical motion combines circular movement in one plane with a simultaneous linear motion in a plane perpendicular to the first. For example, the path from point A to point B (Fig. A) on the envelope of the cylinder combines a circular movement in the xy plane with a linear displacement in the z direction.

On most CNC systems this function can be executed in two different ways:

G02: Helical interpolation in a clockwise direction

G03: Helical interpolation in a counter-clockwise direction




Fig. A




Fig. B

The thread milling operation (Fig. B) consists of circular rotation of the tool around its own axis together with an orbiting motion along the bore or workpiece circumference.

During one such orbit, the tool will shift vertically one pitch length. These movements combined with the insert geometry create the required thread form.


There are three acceptable ways of approaching the workpiece with the tool to initiate production of the thread:

- 1 **Tangential Arc Approach**
- 2 **Radial Approach**
- 3 **Tangential Line Approach**

1 Tangential Arc Approach

With this method, the tool enters and exits the workpiece smoothly. No marks are left on the workpiece and there is no vibration, even with harder materials.

Although it requires slightly more complex programming than the radial approach (see below), this is the method recommended for machining the highest quality threads.



1-2: Rapid approach

2-3: Tool entry along tangential arc, with simultaneous feed along z-axis

3-4: Helical movement during one full orbit (360°)

4-5: Tool exit along tangential arc, with continuing feed along z-axis

5-6: Rapid return


2 Radial Approach

This is the simplest method. There are two characteristics worth noting about the radial approach:

1. A small vertical mark may be left at the entry (and exit) point. This is of no significance to the thread itself.

2. When using this method with very hard materials, there may be a tendency of the tool to vibrate as it approaches the full cutting depth.

Note: Radial feed during entry to the full profile depth should only be $\frac{1}{3}$ of the subsequent circular feed.




1-2: Radial entry

2-3: Helical movement during one full orbit (360°)

3-4: Radial exit

3 Tangential Line Approach

This method is very simple, and has all of the advantages of the tangential arc method. However, it is applicable only with external threads.



Preparing for the Thread Milling Operation


1 Calculation of Rotational Velocity and Feed at the Cutting Edge

$$N = \frac{12 \times V}{\pi \times D_2}$$



$$V = \frac{N \times \pi \times D_2}{12}$$

$$F_1 = N \times z \times f$$

N - Rotational Velocity [R.P.M.]
 V - Cutting Speed [ft/min]
 D₂ - Toolholder Cutting Dia. [Inch]
 F₁ - Tool Feed Rate at the Cutting Edge [Inch/min]
 z - No. of Cutting Edges
 f - Feed per Tooth per Rotation [inch/tooth]



2 Calculation of Feed Rates at the Tool Center Line



The equations define the relationship between feed rates at the cutting edge and at the tool center line. On most CNC machines the feed rate required for programming is that of the center-line of the tool. When dealing with linear tool movement the feed rate at the cutting edge and the center line are identical. This is not the case with circular tool movement.

List of "G" Codes (ISO) for CNC Program

| Code | Description | Code | Description |
|------|---|------|---|
| % | Recognition code (ISO or EIA) + End of tape | H | Tool length compensation number |
| G00 | Fast feed linear positioning | D | Tool radius compensation number |
| G01 | Linear interpolation | X | X coordinate |
| G02 | Circular/Helical interpolation CW | Y | Y coordinate |
| G03 | Circular/Helical interpolation CCW | Z | Z coordinate |
| G40 | Cutter radius compensation cancel | R | Radius of travel |
| G41 | Cutter radius compensation left | I | X coordinate to center of starting arc travel |
| G42 | Cutter radius compensation right | J | Y coordinate to center of starting arc travel |
| G43 | Tool length compensation + | M3 | Spindle forward rotation |
| G49 | Tool length compensation cancel | M5 | Spindle stop |
| G57 | Work coordinate system selection | M30 | Program end & rewind |
| G90 | Absolute command relative to work coordinate origin | O | Program number |
| G91 | Incremental command relative to tool position | N | Block number (can be avoided) |
| F | Feed Inch/min | (| Start of comment |
| S | Spindle speed RPM |) | End of comment |

CNC Program Sample (Thread: M60 x 1.5 x 20)

```


%
O0001 (TMINRH CLIMB CYCLES = 1)..... Program no.
(Fanuc 11M Controller.) ..... Remark
G90 G00 G57 X0 Y0..... Home (origin) set
G43 H10 Z0 M3 S946 ..... Tool length compensation-on and RPM set
G91 G00 X0 Y0 Z-0.7981 ..... Go down in Z-axis
G41 D60 X0.3724 Y-0.8108 Z0..... Tool diameter compensation-on
G91 G03 X0.8108 Y0.8108 Z0.0107 R0.8108 F1.4173 ..... Entrance by tangential arc
G91 G03 X0 Y0 Z0.0591 I-1.1832 J0 ..... Thread machining-HELICAL interpolation movement
G91 G03 X-0.8108 Y0.8108 Z0.0107 R0.8108 ..... Exit by tangential arc
G00 G40 X-0.3724 Y-0.8108 Z0 ..... Tool diameter compensation-off
G90 G49 G57 G00 Z7.874 M5 ..... Tool length compensation-off and RPM close
M30 ..... End of program
%
    
```

Recommendation:

At tool entry, set the Feed f [inch/tooth] to 70% lower than the threading Feed.

Example:

Threading Feed: .0012[inch/tooth]
 Tool entry Feed: .0036[inch/tooth]



Minimum Bore Diameters for TM Standard line

| Pitch mm | | 0.5 | 0.6 | 0.7 | 0.75 0.80 | 0.9 | 1.0 | 1.25 | 1.5 | 1.75 | 2.0 | | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 | | 6.0 | | |
|-----------------------------|------|-------------------------------|------|------|--------------|------|----------|----------|----------|------|----------|------------|------|--------|------|------|------|------|------|------|------|------|--|
| Pitch TPI | | 48 | 44 | 36 | 32 | 28 | 26 24 | 20 19 | 18 16 | 14 | 13 12 | 11.5 11 | 10 | 9 8 | 7 | 6 | | 5 | | 4.5 | | 4 | |
| Toolholder Ordering Code | D2 | Minimum Bore Diameter Di Inch | | | | | | | | | | | | | | | | | | | | | |
| TMMC050-6.0 | .35 | .37 | .38 | .39 | .39 | .41 | .42 | .45 | .47 | | | | | | | | | | | | | | |
| TMMC075-6.0 | .35 | .37 | .38 | .39 | .39 | .41 | .42 | .45 | .47 | | | | | | | | | | | | | | |
| TMMC075-6.0124/203 | .35 | .37 | .38 | .39 | .39 | .41 | .42 | .45 | .47 | | | | | | | | | | | | | | |
| TMC050-2 | .45 | .47 | .48 | .49 | .49 | .51 | .52 | .55 | .57 | .59 | | | | | | | | | | | | | |
| TMC075-2 | .45 | .47 | .48 | .49 | .49 | .51 | .52 | .55 | .57 | .59 | | | | | | | | | | | | | |
| TMLC100-2 | .45 | .47 | .48 | .49 | .49 | .51 | .52 | .55 | .57 | .59 | | | | | | | | | | | | | |
| TMSC0375-2 | .49 | .51 | .50 | .54 | .53 | .55 | .56 | .59 | .61 | .63 | | | | | | | | | | | | | |
| TMOC075-2 | .57 | .59 | .60 | .6 | .61 | .63 | .65 | .67 | .70 | .73 | | | | | | | | | | | | | |
| TMNC0625-3 | .61 | .63 | .64 | .65 | .65 | .67 | .68 | .70 | .73 | .75 | .77 | .79 | | | | | | | | | | | |
| TMC075-3124/201 | .61 | .63 | .64 | .65 | .65 | .67 | .68 | .70 | .73 | .75 | .77 | .79 | | | | | | | | | | | |
| TMC0625-3 | .67 | .69 | .70 | .71 | .72 | .74 | .75 | .77 | .79 | .81 | .83 | .85 | | | | | | | | | | | |
| BTMC0625-3B | .67 | .69 | .70 | .71 | .72 | .74 | .75 | .77 | .79 | .81 | .83 | .85 | | | | | | | | | | | |
| TM2C075-2 | .67 | .69 | .70 | .71 | .72 | .74 | .75 | .77 | .79 | .81 | | | | | | | | | | | | | |
| BTMC075-3B | .75 | .78 | .79 | .80 | .80 | .82 | .83 | .85 | .87 | .89 | .91 | .93 | | | | | | | | | | | |
| TMNC075-3 | .75 | .78 | .79 | .80 | .80 | .82 | .83 | .85 | .87 | .89 | .91 | .93 | | | | | | | | | | | |
| TMC075-3 | .79 | .81 | .83 | .83 | .84 | .86 | .87 | .89 | .91 | .93 | .94 | .96 | | | | | | | | | | | |
| TMOC075-3 | .79 | .81 | .83 | .83 | .84 | .86 | .87 | .89 | .91 | .93 | .94 | .96 | | | | | | | | | | | |
| BTMWC100-3B | .87 | .89 | .91 | .91 | .92 | .94 | .94 | .97 | .98 | 1.00 | 1.02 | 1.04 | | | | | | | | | | | |
| BTMLC100-3B | .87 | .89 | .91 | .91 | .92 | .94 | .94 | .97 | .98 | 1.00 | 1.02 | 1.04 | | | | | | | | | | | |
| TMLC100-3 | .87 | .89 | .91 | .91 | .92 | .94 | .94 | .97 | .98 | 1.00 | 1.02 | 1.04 | | | | | | | | | | | |
| TMC100-5124/204 | .98 | 1.01 | 1.02 | 1.03 | 1.04 | 1.06 | 1.06 | 1.09 | 1.11 | 1.13 | 1.15 | 1.17 | 1.23 | 1.33 | 1.44 | 1.56 | 1.68 | | | | | | |
| TM2C100-3 | 1.02 | 1.05 | 1.06 | 1.07 | 1.08 | 1.09 | 1.10 | 1.13 | 1.15 | 1.17 | 1.19 | 1.21 | | | | | | | | | | | |
| BTM2C100-3B | 1.02 | 1.05 | 1.06 | 1.07 | 1.08 | 1.09 | 1.10 | 1.13 | 1.15 | 1.17 | 1.19 | 1.21 | | | | | | | | | | | |
| TMC100-5 | 1.18 | 1.21 | 1.22 | 1.23 | 1.24 | 1.25 | 1.26 | 1.29 | 1.32 | 1.34 | 1.36 | 1.40 | 1.44 | 1.54 | 1.65 | 1.77 | 1.89 | | | | | | |
| TMLC100-5 | 1.18 | 1.21 | 1.22 | 1.23 | 1.24 | 1.25 | 1.26 | 1.29 | 1.32 | 1.34 | 1.36 | 1.40 | 1.44 | 1.54 | 1.65 | 1.77 | 1.89 | | | | | | |
| TMOC100-5 | 1.18 | 1.21 | 1.22 | 1.23 | 1.24 | 1.25 | 1.26 | 1.29 | 1.32 | 1.34 | 1.36 | 1.40 | 1.44 | 1.54 | 1.65 | 1.77 | 1.89 | | | | | | |
| TMC125-6B | 1.38 | | | | | | | | 1.52 | 1.54 | 1.56 | 1.60 | 1.65 | 1.73 | 1.85 | 1.97 | 2.10 | 1.67 | 1.97 | 1.76 | 2.26 | 2.23 | |
| TMC125-5 | 1.46 | 1.50 | 1.50 | 1.51 | 1.52 | 1.54 | 1.56 | 1.59 | 1.61 | 1.63 | 1.65 | 1.69 | 1.73 | 1.83 | 1.93 | 2.05 | 2.19 | | | | | | |
| TMLC125-5 | 1.46 | 1.50 | 1.50 | 1.51 | 1.52 | 1.54 | 1.56 | 1.59 | 1.61 | 1.63 | 1.65 | 1.69 | 1.73 | 1.83 | 1.93 | 2.05 | 2.19 | | | | | | |
| TMNC125-5 | 1.46 | 1.50 | 1.50 | 1.51 | 1.52 | 1.54 | 1.56 | 1.57 | 1.61 | 1.63 | 1.65 | 1.69 | 1.73 | 1.83 | 1.93 | 2.05 | 2.19 | | | | | | |
| TMSHD150-050-2 | 1.50 | 1.52 | 1.52 | 1.53 | 1.54 | 1.56 | 1.57 | 1.61 | 1.65 | 1.69 | | | | | | | | | | | | | |
| TM2C125-5 | 1.65 | 1.70 | 1.71 | 1.72 | 1.72 | 1.75 | 1.77 | 1.81 | 1.83 | 1.85 | 1.87 | 1.90 | 1.93 | 2.05 | 2.15 | 2.26 | 2.40 | | | | | | |
| TMVC125-5 | 1.81 | | | | | | | | | | | | | | | | | | | | | 2.46 | |
| TMC150-6B | 1.81 | | | | | | | | 1.95 | 1.97 | 1.99 | 2.03 | 2.09 | 2.17 | 2.17 | 2.19 | 2.17 | 2.07 | 2.13 | 2.15 | 2.26 | 2.23 | |
| TMLC150-6B | 1.81 | | | | | | | | 1.95 | 1.97 | 1.99 | 2.03 | 2.09 | 2.17 | 2.17 | 2.19 | 2.17 | 2.07 | 2.13 | 2.15 | 2.26 | 2.23 | |
| TMSHD200-075-2 | 1.97 | 1.99 | 2.00 | 2.00 | 2.01 | 2.03 | 2.05 | 2.09 | 2.13 | 2.15 | | | | | | | | | | | | | |
| TMSHD200-075-3 | 1.97 | 1.99 | 2.00 | 2.00 | 2.01 | 2.03 | 2.05 | 2.09 | 2.13 | 2.15 | 2.17 | 2.19 | | | | | | | | | | | |

Thread Milling
Technical Data

Minimum Bore Diameters for TM Standard line (con't)


| Pitch mm | 0.5 | 0.6 | 0.7 | 0.75 0.80 | 0.9 | 1.0 | 1.25 | 1.5 | 1.75 | 2.0 | | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 | | 6.0 | | | | | | | | | | |
|-----------------------------|------|------|------|--------------|------|----------|----------|----------|------|-------------------------------|------------|------|--------|------|------|------|------|------|------|------|------|------|--|--|--|--|--|--|--|--|
| Pitch TPI | 48 | 44 | 36 | 32 | 28 | 26 24 | 20 19 | 18 16 | 14 | 13 12 | 11.5 11 | 10 | 9 8 | 7 | 6 | | 5 | | | 4.5 | | 4 | | | | | | | | |
| Toolholder Ordering Code | D2 | | | | | | | | | Minimum Bore Diameter Di Inch | | | | | | | | | | | | | | | | | | | | |
| TM2C150-6B | 2.05 | | | | | | | | 2.20 | 2.21 | 2.22 | 2.24 | 2.32 | 2.42 | | 2.48 | 2.52 | 2.60 | 2.64 | 2.66 | 2.72 | 2.76 | | | | | | | | |
| TMSHD250-075-3B | 2.48 | 2.5 | 2.51 | 2.52 | 2.52 | 2.54 | 2.56 | 2.6 | 2.64 | 2.66 | 2.68 | 2.72 | | | | | | | | | | | | | | | | | | |
| TMSHD250-075-5 | 2.48 | 2.5 | 2.51 | 2.52 | 2.52 | 2.54 | 2.56 | 2.6 | 2.64 | 2.66 | 2.68 | 2.72 | 2.76 | 2.83 | 2.87 | 2.91 | 2.95 | | | | | | | | | | | | | |
| TMSHD250-075-6B | 2.48 | | | | | | | | 2.64 | 2.66 | 2.68 | 2.72 | 2.76 | 2.83 | 2.87 | 2.91 | 2.95 | 3.03 | 3.07 | 3.09 | 3.15 | 3.19 | | | | | | | | |
| TMSHD300-100-5 | 3.15 | 3.17 | 3.18 | 3.19 | 3.19 | 3.21 | 3.23 | 3.27 | 3.31 | 3.33 | 3.35 | 3.39 | 3.43 | 3.50 | 3.54 | 3.58 | 3.62 | | | | | | | | | | | | | |
| TMSHD300-100-6B | 3.15 | | | | | | | | 3.31 | 3.33 | 3.35 | 3.39 | 3.43 | 3.50 | 3.54 | 3.58 | 3.62 | 3.70 | 3.74 | 3.76 | 3.82 | 3.86 | | | | | | | | |
| TMSHD400-125-5 | 3.94 | 3.96 | 3.96 | 3.97 | 3.98 | 4.00 | 4.02 | 4.06 | 4.09 | 4.11 | 4.13 | 4.17 | 4.21 | 4.29 | 4.33 | 4.37 | 4.41 | | | | | | | | | | | | | |
| TMSHD400-125-6B | 3.94 | | | | | | | | 4.09 | 4.11 | 4.13 | 4.17 | 4.21 | 4.29 | 4.33 | 4.37 | 4.41 | 4.49 | 4.53 | 4.55 | 4.61 | 4.65 | | | | | | | | |
| TMSHD500-150-5 | 4.92 | 4.94 | 4.95 | 4.96 | 4.96 | 4.98 | 5.00 | 5.04 | 5.08 | 5.10 | 5.12 | 5.16 | 5.20 | 5.28 | 5.31 | 5.35 | 5.39 | | | | | | | | | | | | | |
| TMSHD500-50-6B | 4.92 | | | | | | | | 5.08 | 5.10 | 5.12 | 5.16 | 5.20 | 5.28 | 5.31 | 5.35 | 5.39 | 5.47 | 5.51 | 5.54 | 5.59 | 5.63 | | | | | | | | |

Coarse Pitch Tooling:

This table is not applicable to the Coarse Pitch system, which can thread mill bores smaller than those listed above.

See the Coarse Pitch section of the various thread standards.

Spare Parts for TM Standard Line



Insert Screw



| IC | Holder | Holder Screw | Designation | Thread | Torx Key | Torx Size |
|-------|-----------------------------|--------------|--------------|-------------------|----------|-----------|
| 6.0mm | TMMC...-6.0 | | SN7T | M2.2x0.45x5.0 | K7T | T7 |
| 1/4" | TM.C...-2 | | SN2TM | M2.6x0.45x5.9 | K2T | T8 |
| 3/8" | TM.C...-3, TMC...-3 124/... | | SN3T, SN3TM | 5-40UNCx8.8, 7.3 | K3T | T10 |
| 3/8"B | BTM.C...-3B | | SN3T | 5-40UNCx8.8 | K3T | T10 |
| 1/2" | TMC...-4 124/... | | SN4TM, SA4TM | 8-32UNCx9.8, 10.7 | K4T | T20 |
| 5/8" | TM.C...-5, TMC...-5 124/... | | SN5TM, SA5TM | M5x0.8x15.0 | K5T | T25 |
| 3/4"B | TM.C...-6B | | SM7T | M7x1.0x15.0 | K30T | T30 |
| 1/4" | TMSH-D150-050-2 | 1/4 X 28 | SN2T | M2.6x0.45x6.5 | HK2T | T8 |
| 1/4" | TMSH-D200-075-2 | | SN2T | M2.6x0.45x6.5 | HK2T | T8 |
| 3/8" | TMSH-D200-075-3 | | SN3TM | 5-40UNCx7.3 | HK3T | T10 |
| 3/8"B | TMSH-D250-075-3B | 3/8 X 24 | SN3TM | 5-40UNCx7.3 | HK3T | T10 |
| 5/8" | TMSH-D250-075-5 | | SN5TM | M5x0.8x15.0 | HK5T | T25 |
| 3/4"B | TMSH-D250-075-6B | | SM7T | M7x1.0x15.0 | HK7T | T30 |
| 5/8" | TMSH-D300-100-5 | 1/2 X 20 | SN5TM | M5x0.8x15.0 | HK5T | T25 |
| 3/4"B | TMSH-D300-100-6B | | SM7T | M7x1.0x15.0 | HK7T | T30 |
| 5/8" | TMSH-D400-125-5 | 5/8 X 18 | SN5TM | M5x0.8x15.0 | HK5T | T25 |
| 3/4"B | TMSH-D400-125-6B | | SM7T | M7x1.0x15.0 | HK7T | T30 |
| 5/8" | TMSH-D500-150-5 | 3/4 X 16 | SN5TM | M5x0.8x15.0 | HK5T | T25 |
| 3/4"B | TMSH-D500-150-6B | | SM7T | M7x1.0x15.0 | HK7T | T30 |
| 1/4" | TMSC0375-2 | | SN2TK | M2.6x0.45x5.9 | K2T | T8 |
| 5/8"V | TMVC125-5 | | SN6T | M6x1.0x29.0 | K6T | T20 |

Spare Parts for MiTM Line



Insert Screw








| Insert Size | Holder | Holder Screw | Designation | Thread | Torx Key | Torx Size |
|-------------|------------------------|--------------|---------------------|--------|----------|-----------|
| 19 | RTMC...A | | SLD3IP6 | M3x0.5 | KIP6 | Torx+6 |
| 24 | RTMC...M | | SLD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| 25 | RTMC...S RTMC-D...S | | SLD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| 40 | RTMC...L RTMC-D...L | | SLD4IP8A SCD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| 41 | RTMC...B RTMC-D...B | | SLD4IP8A SCD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| 25 | RTMC-D150-050-25S5 | 1/4"-28x1.25 | SLD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| | RTMC-D190-075-25S7 | 3/8"-24x1.25 | | | | |
| | RTMC-D230-100-25S9 | 1/2"-20x1.50 | | | | |
| | RTMNC-D150-050-25S5 | 1/4"-28x1.25 | | | | |
| 40 | RTMCD190-075-40L7 | 3/8"-24x1.25 | SLD4IP8A SCD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| | RTMCD230-100-40L9 | 1/2"-20x1.50 | | | | |
| | RTMNCD190-075-40L7 | 3/8"-24x1.25 | | | | |
| 41 | RTMCD209-075-41B5 | 3/8"-24x1.5 | SLD4IP8A SCD4IP8 | M4x0.7 | KIP8 | Torx+8 |
| | RTMCD248-100-41B6 | 1/2"-20x1.5 | | | | |

Spare Parts for TMSD Line



| IC | Holder | Holder Screw | Designation | Thread | Torx Key | Blade | Handle | Torx Size |
|--------------|-----------------------------------|---------------|--------------|-----------------------------|----------|---------------|--------------------|-----------|
| 7V | GMC...-7-3 CGMC...-7-3 | | SN2T8-M1 | M3.0x0.5x9 | K2T | | | T8 |
| 9V | GMC...-9-3 CGMC...-9-3 | | SN2T15-M2 | M4x0.7x13.5 | - | Blade T15-1/4 | Smart Handle 1/4x2 | T15 |
| 11V | GMC...-11-3 CGMC...-11-3 | | SN4T20-M3 | M55x0.8x15.5 | - | Blade T20-1/4 | Smart Handle 1/4x2 | T20 |
| 1/4"U, 1/4"A | TM.C....-2U CTMC....-2U or 2A | | SN2T | M2.6x0.45x6.5 | HK2T | | | T8 |
| 3/8"U, 3/8"A | TM.C....-3U TM.C-D...-3U or 3A | | SN3T | 5-40UNCx8.8 | HK3T | | | T10 |
| 1/2"U | TM.C....-4U TM.C-D...-4U | | SA4T | 8-32UNCx14.0 | HK4T | | | T20 |
| 5.0L | TM.C....-5L CTMC....-5L | | SN5LTR | M2.2X0.45X5.0 | K7T | | | T7 |
| 3/8"L | TM.C....-3 CTMC....-3L | | SN3T SA3T | 5-40UNCx8.8 5-40UNCx11.3 | HK3T | | | T10 |
| 5/8"V | TM.SC-D...-5V.. | | SA5T | M5x0.8x22.0 | HK5T | | | T25 |
| 3/8"U | TM4SC D169-050-3U | 1/4-28x1.25 | SN3T | 5-40UNCx8.8 | HK3T | | | T10 |
| | TM5SC D208-075-3U | 3/8-24x1.25 | | | | | | |
| 1/2"U | TM6SC D346-100-4U | 1/2-20x1.5 | SA4T | 8-32UNCx14.0 | HK4T | | | T20 |
| | TM8SC D435-150-4U | 3/4-16x1.75 | | | | | | |
| 3/8"L | TM7SC-D315-125-3L | 5/8-18UNx11/2 | SA3T | 5-40UNCx11.3 | HK3T | | | T10 |
| | TM6SC-D228-075-3L-ABUT | 3/8-24x1.25 | | | | | | |
| 5/8"V | TM6SC D346-125-5V6-ABUT | 5/8-18UNx11/2 | SA5T | M5x0.8x22.0 | HK5T | | | T25 |
| | TM6SC D346-125-5V8-ABUT | | | | | | | |

Troubleshooting


| Image | Problem | Possible Cause | Solution |
|---|--|--|--|
|  | Increased insert flank wear | Cutting speed too high -----> Chip is too thin -----> Insufficient coolant -----> | Reduce cutting speed/use coated insert Increase feed rate Increase coolant flow rate |
|  | Chipping of cutting edge | Chip is too thick -----> Vibration -----> | Reduce feed rate Use the tangential arc method Increase RPM Check stability |
|  | Material build up on the cutting edge | Incorrect cutting speed -----> Unsuitable carbide grade -----> | Change cutting speed Use a coated carbide grade |
|  | Chatter / Vibration | Feed rate is too high -----> Profile is too deep -----> Thread length is too long -----> | Reduce the feed Execute two passes, each with increased cutting depth Execute two passes, each cutting only half the thread length Execute two passes, each cutting only half the thread length |
|  | Insufficient thread accuracy | Tool deflection -----> | Reduce feed rate Execute a "zero" cut |



The Thread Milling Handbook

The Thread Milling Handbook:

Your everyday guide to the theory and implementation of the thread milling system.

Download at www.vargususa.com





MINIPRO

| | | |
|---|---|-----|
| ■ | PowerBore Inserts | 381 |
| ■ | Micro (Boring & Grooving) Inserts | 383 |
| ■ | Toolholders (PowerBore & Micro) | 395 |
| ■ | Technical Data | 403 |

Vardex Ordering Code System

■ PowerBore Inserts

| | | | | | | |
|---|--|---|---------------|--|----------------|-----------------|
| T 1 | D 2 | 0 3 | W 4 | 41 5 | 14 6 | VTX 7 |
| 1 - Insert Shape C - Diamond 80 deg. T - Triangle W - Trigon 80 deg. | 2 - Clearance Angle C - 7 deg. D - 15 deg. | 3 - Tolerance Class 0 - Special Tolerance Class | | 4 - Insert Type W - Hole + Countersink | | |
| 5 - Insert Dimension 40 - IC .156" - Thickness-.040" 41 - IC .160" - Thickness-.047" 42 - IC .156" - Thickness-.062" 50 - IC .187" - Thickness-.096" | 6 - Corner Radius 11 - R.002 12 - R.007 13 - R.008 14 - R.015 | 7 - Carbide Grade VTX | | | | |



■ Micro Boring Inserts - Double Ended

| | | | | | | | | | | |
|---|---|---------------|---|--|--|---------------------------------|--------------------------------------|---|---------------|-----------------|
| 6.0 1 | S 2 | I 3 | R 4 | 0.2 5 | M 6 | - | Bore 7 | - | 1 8 | VMX 9 |
| 1 - Insert Dia. 3.0 - 3.0mm 4.0 - 4.0mm 6.0 - 6.0mm 8.0 - 8.0mm 10.0 - 10.0mm | 2 - Insert Style S - Micro Insert | | 3 - Type of Insert I - Internal | | 4 - RH or LH R - Right Hand Insert L - Left Hand Insert | | 5 - Corner Radius (mm) 0.2 | | | |
| 6 - Tool Length U - Ultra Short S - Short M - Medium L - Long | 7 - Tool Application Bore - Boring Copy - Boring Copy Chamfer - Boring Chamfer Back - Back Edge 3527, 3537, 3547 - Long Nose BD - Bore Drill | | | 8 - Front Relief 1 - With Relief 0 - Without Relief | | 9 - Carbide Grade VMX | | | | |

■ Micro Grooving Inserts - Double Ended


| | | | | | | | | | | |
|--|---|---------------|---|--|--|---------------------------------|--|---|-----------------|-----------------|
| 4.0 1 | S 2 | I 3 | R 4 | 090 5 | S 6 | - | D472 7 | - | 1.1 8 | VMX 9 |
| 1 - Insert Dia. 3.0 - 3.0 mm 4.0 - 4.0 mm 6.0 - 6.0 mm 8.0 - 8.0 mm 10.0 - 10.0 mm | 2 - Insert Style S - Micro Insert | | 3 - Type of Insert I - Internal | | 4 - RH / LH Insert R - Right Hand Insert L - Left Hand Insert | | 5 - Groove Std. Width .027 - .078 (inch) 0.90 - 2.15 (mm) | | | |
| 6 - Insert Length A - Axially S - Short M - Medium L - Long | 7 - Groove Standard DIN 471 DIN 472 CIRCLIP DIN 7993 DIN 765H, DIN 765T DIN 3770S, DIN 3770D SNAP RING CIRCLIP - Face Grooving | | | 8 - Groove Depth .02" - .06" | | 9 - Carbide Grade VMX | | | | |

Internal



CD0W

CD0W Inserts



| Insert Size | Ordering Code | Dimensions Inch | |
|-------------|---------------|-----------------|------|
| | | R | T |
| .156" | CD0W4011... | .002 | .040 |
| | CD0W4012... | .007 | .040 |
| | CD0W4014... | .015 | .040 |



Spare Parts

Insert Screw




VS01

Internal



TD0W

TD0W Inserts



| Insert Size | Ordering Code | Dimensions Inch | |
|-------------|---------------|-----------------|------|
| | | R | T |
| .160" | TD0W4111... | .002 | .047 |
| | TD0W4112... | .007 | .047 |
| | TD0W4114... | .015 | .047 |

Spare Parts

Insert Screw



VS01, VS40


Boring

Internal



WCOW 4213, 4214

WCOW Inserts




| Insert Size | Ordering Code | Dimensions Inch | | Spare Parts |
|-------------|---------------|-----------------|------|--|
| | | R | T | |
| .156" | WCOW4213... | .008 | .062 | Insert Screw  VS40 |
| | WCOW4214... | .015 | .062 | |

Internal




WCOW 5013, 5014

WCOW Inserts



| Insert Size | Ordering Code | Dimensions Inch | | Spare Parts |
|-------------|---------------|-----------------|------|--|
| | | R | T | |
| .187" | WCOW5013... | .008 | .096 | Insert Screw  VS41 |
| | WCOW5014... | .015 | .096 | |



Micro Boring - Boring



Micro - Double Ended

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-----------------------|-----------------|------|-------|------|------|----------------|------------|
| d mm | RH | R | L1 | L | S | F | Inch | |
| 3.0 | 3.0SIR0.1U-Bore-1... | .004 | .24 | 1.417 | .022 | .054 | .126 | SMC..-3.0 |
| | 3.0SIR0.1S-Bore-1... | .004 | .35 | 1.417 | .022 | .054 | | |
| | 3.0SIR0.2S-Bore-1... | .008 | .35 | 1.417 | .026 | .056 | | |
| | 3.0SIR0.2M-Bore-1... | .008 | .63 | 1.969 | .026 | .056 | | |
| 4.0 | 4.0SIR0.2S-Bore-1... | .008 | .35 | 1.417 | .026 | .076 | .165 | SMC..-4.0 |
| | 4.0SIR0.2M-Bore-1... | .008 | .63 | 1.969 | .026 | .076 | | |
| | 4.0SIR0.2L-Bore-1... | .008 | .83 | 2.362 | .026 | .076 | | |
| 6.0 | 6.0SIR0.2S-Bore-1... | .008 | .35 | 1.417 | .030 | .115 | .244 | SMC..-6.0 |
| | 6.0SIR0.2M-Bore-1... | .008 | .63 | 1.969 | .030 | .115 | | |
| | 6.0SIR0.2L-Bore-1... | .008 | .83 | 2.362 | .030 | .115 | | |
| 8.0 | 8.0SIR0.2S-Bore-1... | .008 | .47 | 2.126 | .032 | .154 | .323 | SMC..-8.0 |
| | 8.0SIR0.2M-Bore-1... | .008 | .79 | 2.756 | .032 | .154 | | |
| | 8.0SIR0.2L-Bore-1... | .008 | 1.10 | 3.386 | .032 | .154 | | |
| 10.0 | 10.0SIR0.2S-Bore-1... | .008 | .59 | 2.362 | .039 | .194 | .402 | SMC..-10.0 |
| | 10.0SIR0.2M-Bore-1... | .008 | .98 | 3.150 | .039 | .194 | | |
| | 10.0SIR0.2L-Bore-1... | .008 | 1.38 | 3.937 | .039 | .194 | | |

Internal







RH-Double Ended

Micro - Double Ended

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|----------------------|-----------------|-----|-------|------|------|----------------|------------|
| d mm | RH | R | L1 | L | S | F | Inch | |
| 4.0 | 4.0SIR0.2S-Copy-1... | .008 | .35 | 1.417 | .039 | .076 | .165 | SMC...-4.0 |
| | 4.0SIR0.2M-Copy-1... | .008 | .63 | 1.969 | .039 | .076 | | |
| | 4.0SIR0.2L-Copy-1... | .008 | .83 | 2.362 | .039 | .076 | | |
| 6.0 | 6.0SIR0.2S-Copy-1... | .008 | .35 | 1.417 | .051 | .115 | .276 | SMC...-6.0 |
| | 6.0SIR0.2M-Copy-1... | .008 | .63 | 1.969 | .051 | .115 | | |
| | 6.0SIR0.2L-Copy-1... | .008 | .83 | 2.362 | .051 | .115 | | |

Micro Boring - Chamfer

Internal




RH-Double Ended

Micro - Double Ended

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder | |
|-------------|-------------------------|-----------------|-----|-------|------|------|----------------|------------|------------|
| d mm | RH | R | L1 | L | F | S1 | S | mm | |
| 4.0 | 4.0SIR0.2S-Chamfer-0... | .008 | .35 | 1.417 | .076 | .039 | .016 | .165 | SMC...-4.0 |
| | 4.0SIR0.2M-Chamfer-0... | .008 | .63 | 1.969 | .076 | .039 | .016 | | |
| | 4.0SIR0.2L-Chamfer-0... | .008 | .83 | 2.362 | .076 | .039 | .016 | | |
| 6.0 | 6.0SIR0.2S-Chamfer-0... | .008 | .35 | 1.417 | .115 | .047 | .028 | .244 | SMC...-6.0 |
| | 6.0SIR0.2M-Chamfer-0... | .008 | .63 | 1.969 | .115 | .047 | .028 | | |
| | 6.0SIR0.2L-Chamfer-0... | .008 | .83 | 2.362 | .115 | .047 | .028 | | |

Boring & Grooving Inserts




Micro - Double Ended

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder |
|-------------|-----------------------|-----------------|------|-------|------|------|----------------|-------------|
| d mm | RH | R | L1 | L | S | F | Inch | |
| 6.0 | 6.0SIR0.2S-3527-1... | .008 | .35 | 1.417 | .106 | .115 | .272 | SMC...-6.0 |
| | 6.0SIR0.2M-3527-1... | .008 | .63 | 1.969 | .106 | .115 | | |
| | 6.0SIR0.2L-3527-1... | .008 | .83 | 2.362 | .106 | .115 | | |
| 8.0 | 8.0SIR0.2S-3537-1... | .008 | .47 | 2.126 | .146 | .154 | .350 | SMC...-8.0 |
| | 8.0SIR0.2M-3537-1... | .008 | .79 | 2.756 | .146 | .154 | | |
| | 8.0SIR0.2L-3537-1... | .008 | 1.10 | 3.386 | .146 | .154 | | |
| 10.0 | 10.0SIR0.2S-3547-1... | .008 | .59 | 2.362 | .185 | .194 | .425 | SMC...-10.0 |
| | 10.0SIR0.2M-3547-1... | .008 | .98 | 3.150 | .185 | .194 | | |
| | 10.0SIR0.2L-3547-1... | .008 | 1.38 | 3.937 | .185 | .194 | | |

Micro Boring - Back Boring


MINIPRO



Micro - Double Ended

| Insert Dia. d mm | Ordering Code | Dimensions Inch | | | | | | | | | | Min. Bore Dia. Inch | Toolholder |
|---------------------|----------------------|-----------------|-----|-------|------|------|------|------|------|------|------|------------------------|------------|
| | | RH | R | L1 | L | A | W | W1 | S | S1 | F | | |
| 3.0 | 3.0SIR0.2S-Back-1... | .002 | .35 | 1.417 | .135 | .059 | .071 | .031 | .024 | .056 | .126 | SMC...-3.0 | |
| | 3.0SIR0.2M-Back-1... | .002 | .63 | 1.969 | | | | | | | | | |
| 4.0 | 4.0SIR0.2S-Back-1... | .002 | .35 | 1.417 | .175 | .079 | .092 | .051 | .039 | .076 | .165 | SMC...-4.0 | |
| | 4.0SIR0.2M-Back-1... | .002 | .63 | 1.969 | | | | | | | | | |
| | 4.0SIR0.2L-Back-1... | .002 | .83 | 2.362 | | | | | | | | | |
| 6.0 | 6.0SIR0.2S-Back-1... | .002 | .35 | 1.417 | .254 | .079 | .097 | .075 | .063 | .115 | .244 | SMC...-6.0 | |
| | 6.0SIR0.2M-Back-1... | .002 | .63 | 1.969 | | | | | | | | | |
| | 6.0SIR0.2L-Back-1... | .002 | .83 | 2.362 | | | | | | | | | |

Micro Boring - Bore Drill






Micro - Double Ended

| Insert Dia. d mm | Ordering Code | Dimensions Inch | | | | Min. Bore Dia. Inch | Toolholder |
|---------------------|--------------------|-----------------|------|-------|------|------------------------|------------|
| | | RH | L1 | L | A | | |
| 4.0 | 4.0SIR0.2M-BD-1... | | .63 | 1.969 | .139 | .147 | SMC...-4.0 |
| 6.0 | 6.0SIR0.2M-BD-1... | | .63 | 1.969 | .205 | .228 | SMC...-6.0 |
| | 6.0SIR0.2L-BD-1... | | .83 | 2.362 | | | |
| 8.0 | 8.0SIR0.2S-BD-1... | | .47 | 2.126 | .272 | .307 | SMC...-8.0 |
| | 8.0SIR0.2M-BD-1... | | .79 | 2.756 | | | |
| | 8.0SIR0.2L-BD-1... | | 1.10 | 3.386 | | | |

Boring & Grooving Inserts

Internal






RH-Double Ended

Micro - Double Ended

| Insert Dia. | Ordering Code | Groove Std. | Dimensions Inch | | | | | | Min. Bore Dia. | Toolholder |
|-------------|-------------------------|-------------|-----------------|-----|-------|------|------|------|----------------|------------|
| d mm | RH | m (H13) | W | L1 | L | B | t | F | Inch | |
| 3.0 | 3.0SIR0.90S-D472-0.5... | .035 | .039 | .35 | 1.417 | .031 | .02 | .055 | .126 | SMC...-3.0 |
| | 3.0SIR0.90M-D472-0.5... | .035 | .039 | .63 | 1.969 | | | | | |
| | 3.0SIR1.10S-D472-0.5... | .043 | .047 | .35 | 1.417 | | | | | |
| | 3.0SIR1.10M-D472-0.5... | .043 | .047 | .63 | 1.969 | | | | | |
| 4.0 | 4.0SIR0.90S-D472-1.1... | .035 | .039 | .35 | 1.417 | .055 | .043 | .075 | .161 | SMC...-4.0 |
| | 4.0SIR0.90M-D472-1.1... | .035 | .039 | .63 | 1.969 | | | | | |
| | 4.0SIR0.90L-D472-1.1... | .035 | .039 | .83 | 2.362 | | | | | |
| | 4.0SIR1.10S-D472-1.1... | .043 | .047 | .35 | 1.417 | | | | | |
| | 4.0SIR1.10M-D472-1.1... | .043 | .047 | .63 | 1.969 | | | | | |
| | 4.0SIR1.10L-D472-1.1... | .043 | .047 | .83 | 2.362 | | | | | |
| | 4.0SIR1.30S-D472-1.1... | .051 | .055 | .35 | 1.417 | | | | | |
| | 4.0SIR1.30M-D472-1.1... | .051 | .055 | .63 | 1.969 | | | | | |
| | 4.0SIR1.30L-D472-1.1... | .051 | .055 | .83 | 2.362 | | | | | |
| | 4.0SIR1.60S-D472-1.1... | .063 | .067 | .35 | 1.417 | | | | | |
| | 4.0SIR1.60M-D472-1.1... | .063 | .067 | .63 | 1.969 | | | | | |
| | 4.0SIR1.60L-D472-1.1... | .063 | .067 | .83 | 2.362 | | | | | |
| 6.0 | 6.0SIR0.90S-D472-1.5... | .035 | .039 | .35 | 1.417 | .071 | .059 | .114 | .240 | SMC...-6.0 |
| | 6.0SIR0.90M-D472-1.5... | .035 | .039 | .63 | 1.969 | | | | | |
| | 6.0SIR0.90L-D472-1.5... | .035 | .039 | .83 | 2.362 | | | | | |
| | 6.0SIR1.10S-D472-1.5... | .043 | .047 | .35 | 1.417 | | | | | |
| | 6.0SIR1.10M-D472-1.5... | .043 | .047 | .63 | 1.969 | | | | | |
| | 6.0SIR1.10L-D472-1.5... | .043 | .047 | .83 | 2.362 | | | | | |
| | 6.0SIR1.30S-D472-1.5... | .051 | .055 | .35 | 1.417 | | | | | |
| | 6.0SIR1.30M-D472-1.5... | .051 | .055 | .63 | 1.969 | | | | | |
| | 6.0SIR1.30L-D472-1.5... | .051 | .055 | .83 | 2.362 | | | | | |
| | 6.0SIR1.60S-D472-1.5... | .063 | .067 | .35 | 1.417 | | | | | |
| | 6.0SIR1.60M-D472-1.5... | .063 | .067 | .63 | 1.969 | | | | | |
| | 6.0SIR1.60L-D472-1.5... | .063 | .067 | .83 | 2.362 | | | | | |
| | 6.0SIR1.85S-D472-1.5... | .073 | .076 | .35 | 1.417 | | | | | |
| | 6.0SIR1.85M-D472-1.5... | .073 | .076 | .63 | 1.969 | | | | | |
| | 6.0SIR1.85L-D472-1.5... | .073 | .076 | .83 | 2.362 | | | | | |
| | 6.0SIR2.15S-D472-1.5... | .085 | .088 | .35 | 1.417 | | | | | |
| | 6.0SIR2.15M-D472-1.5... | .085 | .088 | .63 | 1.969 | | | | | |
| | 6.0SIR2.15L-D472-1.5... | .085 | .088 | .83 | 2.362 | | | | | |

Internal






RH-Double Ended

Micro - Double Ended

| Insert Dia. | Ordering Code | Groove Std. | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder | |
|--------------------------|--------------------------|-------------|-----------------|------|------|------|------|----------------|------------|------------|
| d mm | RH | m (H13) | W | L1 | L | B | t | F | Inch | |
| 8.0 | 8.0SIR1.10M-D472-2.0... | .043 | .047 | .79 | 2.76 | .098 | .079 | .154 | .331 | SMC..-8.0 |
| | 8.0SIR1.30M-D472-2.0... | .051 | .055 | .79 | 2.76 | .098 | .079 | | | |
| | 8.0SIR1.60M-D472-2.5... | .063 | .067 | .79 | 2.76 | .118 | .098 | | | |
| | 8.0SIR1.85M-D472-2.5... | .073 | .076 | .79 | 2.76 | .118 | .098 | | | |
| | 8.0SIR2.15M-D472-3.0... | .085 | .088 | .79 | 2.76 | .138 | .118 | | | |
| | 8.0SIR2.65M-D472-3.5... | .104 | .108 | .79 | 2.76 | .157 | .138 | | | |
| | 8.0SIR3.15M-D472-3.5... | .124 | .129 | .79 | 2.76 | .157 | .138 | | | |
| 10.0 | 10.0SIR1.30M-D472-3.5... | .051 | .055 | .98 | 3.15 | .157 | .138 | .193 | .409 | SMC..-10.0 |
| | 10.0SIR1.60M-D472-3.5... | .063 | .067 | .98 | 3.15 | | | | | |
| | 10.0SIR1.85M-D472-3.5... | .073 | .076 | .98 | 3.15 | | | | | |
| | 10.0SIR2.15M-D472-3.5... | .085 | .088 | .98 | 3.15 | | | | | |
| | 10.0SIR2.65M-D472-3.5... | .104 | .108 | .98 | 3.15 | | | | | |
| | 10.0SIR3.15M-D472-3.5... | .124 | .129 | .98 | 3.15 | | | | | |
| | 10.0SIR4.15M-D472-3.5... | .163 | .169 | .98 | 3.15 | | | | | |
| 10.0SIR5.15M-D472-3.5... | .203 | .208 | .98 | 3.15 | | | | | | |

Internal






RH-Double Ended

Micro (Partial Profile)

| Insert Dia. d mm | Ordering Code RH | Dimensions Inch | | | | | Min. Bore Dia. Inch | Toolholder | | | |
|-------------------------|-------------------------|-----------------|------|------|------|------|------------------------|------------|------------|------|------|
| | | W | L1 | L | B | t | | | | | |
| 3.0 | 3.0SIR.027S-CIRC-.02... | .027 | .35 | 1.42 | .035 | .023 | .055 | .126 | SMC...-3.0 | | |
| | 3.0SIR.027M-CIRC-.02... | .027 | .63 | 1.97 | | | | | | | |
| | 3.0SIR.031S-CIRC-.02... | .031 | .35 | 1.42 | | | | | | | |
| | 3.0SIR.031M-CIRC-.02... | .031 | .63 | 1.97 | | | | | | | |
| | 3.0SIR.041S-CIRC-.02... | .041 | .35 | 1.42 | | | | | | | |
| | 3.0SIR.041M-CIRC-.02... | .041 | .63 | 1.97 | | | | | | | |
| | 3.0SIR.046S-CIRC-.04... | .046 | .35 | 1.42 | | | | | | .055 | .043 |
| | 3.0SIR.046M-CIRC-.04... | .046 | .63 | 1.97 | | | | | | | |
| 4.0 | 4.0SIR.027S-CIRC-.04... | .027 | .35 | 1.42 | .055 | .043 | .074 | .165 | SMC...-4.0 | | |
| | 4.0SIR.027M-CIRC-.04... | .027 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.027L-CIRC-.04... | .027 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.031S-CIRC-.04... | .031 | .35 | 1.42 | | | | | | | |
| | 4.0SIR.031M-CIRC-.04... | .031 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.031L-CIRC-.04... | .031 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.041S-CIRC-.04... | .041 | .35 | 1.42 | | | | | | | |
| | 4.0SIR.041M-CIRC-.04... | .041 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.041L-CIRC-.04... | .041 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.047S-CIRC-.04... | .046 | .35 | 1.42 | | | | | | | |
| | 4.0SIR.047M-CIRC-.04... | .046 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.047L-CIRC-.04... | .046 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.058S-CIRC-.04... | .058 | .35 | 1.42 | | | | | | | |
| | 4.0SIR.058M-CIRC-.04... | .058 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.058L-CIRC-.04... | .058 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.062S-CIRC-.06... | .062 | .35 | 1.42 | | | | | | .071 | .059 |
| | 4.0SIR.062M-CIRC-.06... | .062 | .63 | 1.97 | | | | | | | |
| | 4.0SIR.062L-CIRC-.06... | .062 | .83 | 2.36 | | | | | | | |
| | 4.0SIR.078S-CIRC-.06... | .078 | .35 | 1.42 | | | | | | | |
| | 4.0SIR.078M-CIRC-.06... | .078 | .63 | 1.97 | | | | | | | |
| 4.0SIR.078L-CIRC-.06... | .078 | .83 | 2.36 | | | | | | | | |

Internal




RH-Double Ended

Micro (Partial Profile)

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Min. Bore Dia. | Toolholder | |
|-------------------------|-------------------------|-----------------|------|------|------|------|----------------|------------|------------|
| d mm | RH | W | L1 | L | B | t | F | Inch | |
| 6.0 | 6.0SIR.046S-CIRC-.06... | .046 | .35 | 1.42 | .071 | .059 | .114 | .244 | SMC...-6.0 |
| | 6.0SIR.046M-CIRC-.06... | .046 | .63 | 1.97 | | | | | |
| | 6.0SIR.046L-CIRC-.06... | .046 | .83 | 2.36 | | | | | |
| | 6.0SIR.058S-CIRC-.06... | .058 | .35 | 1.42 | | | | | |
| | 6.0SIR.058M-CIRC-.06... | .058 | .63 | 1.97 | | | | | |
| | 6.0SIR.058L-CIRC-.06... | .058 | .83 | 2.36 | | | | | |
| | 6.0SIR.062S-CIRC-.06... | .062 | .35 | 1.42 | | | | | |
| | 6.0SIR.062M-CIRC-.06... | .062 | .63 | 1.97 | | | | | |
| | 6.0SIR.062L-CIRC-.06... | .062 | .83 | 2.36 | | | | | |
| | 6.0SIR.072S-CIRC-.06... | .072 | .35 | 1.42 | | | | | |
| | 6.0SIR.072M-CIRC-.06... | .072 | .63 | 1.97 | | | | | |
| | 6.0SIR.072L-CIRC-.06... | .072 | .83 | 2.36 | | | | | |
| | 6.0SIR.078S-CIRC-.06... | .078 | .35 | 1.42 | | | | | |
| | 6.0SIR.078M-CIRC-.06... | .078 | .63 | 1.97 | | | | | |
| | 6.0SIR.078L-CIRC-.06... | .078 | .83 | 2.36 | | | | | |
| | 6.0SIR.088S-CIRC-.06... | .088 | .35 | 1.42 | | | | | |
| | 6.0SIR.088M-CIRC-.06... | .088 | .63 | 1.97 | | | | | |
| | 6.0SIR.088L-CIRC-.06... | .088 | .83 | 2.36 | | | | | |
| | 6.0SIR.094S-CIRC-.07... | .094 | .35 | 1.42 | | | | | |
| | 6.0SIR.094M-CIRC-.07... | .094 | .63 | 1.97 | | | | | |
| 6.0SIR.094L-CIRC-.07... | .094 | .83 | 2.36 | | | | | | |
| 6.0SIR.097S-CIRC-.07... | .097 | .35 | 1.42 | | | | | | |
| 6.0SIR.097M-CIRC-.07... | .097 | .63 | 1.97 | | | | | | |
| 6.0SIR.097L-CIRC-.07... | .097 | .83 | 2.36 | | | | | | |
| 6.0SIR.105S-CIRC-.07... | .105 | .35 | 1.42 | | | | | | |
| 6.0SIR.105M-CIRC-.07... | .105 | .63 | 1.97 | | | | | | |
| 6.0SIR.105L-CIRC-.07... | .105 | .83 | 2.36 | | | | | | |
| | | | | | .079 | .069 | | | |

Boring & Grooving Inserts






Micro (Partial Profile) - Double Ended

| Insert Dia. d mm | Ordering Code RH | Groove Std. m (H13) | Dimensions Inch | | | | | | Min. Bore Dia. Inch | Toolholder |
|-------------------------|--------------------------|------------------------|-----------------|------|------|------|------|------|------------------------|-------------|
| | | | W | L1 | L | B | t | F | | |
| 3.0 | 3.0SIR0.4S-D7993-0.6... | .016 | .031 | .36 | 1.42 | .031 | .024 | .055 | .126 | SMC...-3.0 |
| | 3.0SIR0.4M-D7993-0.6... | .016 | .031 | .64 | 1.97 | | | | | |
| 4.0 | 4.0SIR0.4S-D7993-0.6... | .016 | .031 | .36 | 1.42 | .035 | .024 | .075 | .161 | SMC...-4.0 |
| | 4.0SIR0.4M-D7993-0.6... | .016 | .031 | .64 | 1.97 | | | | | |
| | 4.0SIR0.4L-D7993-0.8... | .016 | .031 | .84 | 2.36 | | | | | |
| | 4.0SIR0.6S-D7993-0.8... | .024 | .047 | .36 | 1.42 | | | | | |
| | 4.0SIR0.6M-D7993-0.8... | .024 | .047 | .64 | 1.97 | .043 | .031 | | | |
| | 4.0SIR0.6L-D7993-0.8... | .024 | .047 | .84 | 2.36 | | | | | |
| | 4.0SIR0.9S-D7993-1.1... | .035 | .071 | .36 | 1.42 | | | | | |
| | 4.0SIR0.9M-D7993-1.1... | .035 | .071 | .64 | 1.97 | | | | | |
| 4.0SIR0.9L-D7993-1.1... | .035 | .071 | .84 | 2.36 | | | | | | |
| 6.0 | 6.0SIR0.9S-D7993-1.1... | .035 | .071 | .36 | 1.42 | .055 | .043 | .114 | .24 | SMC...-6.0 |
| | 6.0SIR0.9M-D7993-1.1... | .035 | .071 | .64 | 1.97 | | | | | |
| | 6.0SIR0.9L-D7993-1.1... | .035 | .071 | .84 | 2.36 | | | | | |
| | 6.0SIR1.0S-D7993-1.2... | .039 | .079 | .36 | 1.42 | | | | | |
| | 6.0SIR1.0M-D7993-1.2... | .039 | .079 | .64 | 1.97 | .059 | .047 | | | |
| | 6.0SIR1.0L-D7993-1.2... | .039 | .079 | .84 | 2.36 | | | | | |
| | 6.0SIR1.1S-D7993-1.3... | .043 | .087 | .36 | 1.42 | | | | | |
| | 6.0SIR1.1M-D7993-1.3... | .043 | .087 | .64 | 1.97 | | | | | |
| 6.0SIR1.1L-D7993-1.3... | .043 | .087 | .84 | 2.36 | | | | | | |
| 8.0 | 8.0SIR0.9M-D7993-2.0... | .035 | .071 | .79 | 2.76 | .098 | .079 | .154 | .331 | SMC...-8.0 |
| | 8.0SIR1.1M-D7993-2.0... | .043 | .087 | .79 | 2.76 | | | | | |
| | 8.0SIR1.4M-D7993-2.0... | .055 | .110 | .79 | 2.76 | | | | | |
| 10.0 | 10.0SIR1.4M-D7993-2.9... | .055 | .110 | .99 | 3.15 | .134 | .114 | .193 | .409 | SMC...-10.0 |
| | 10.0SIR1.8M-D7993-2.9... | .071 | .142 | .99 | 3.15 | | | | | |

Snap Ring Grooves Inch Standard



Internal




RH-Double Ended

Micro (Partial Profile) - Double Ended

| Insert Dia. d mm | Ordering Code RH | Groove Std. | | | Dimensions Inch | | | | Min. Bore Dia. Inch | Toolholder |
|-------------------------|-------------------------|-------------|------|------|-----------------|------|------|------|------------------------|------------|
| | | R | W | L1 | L | B | t | F | | |
| 3.0 | 3.OSIR.015S-SNAP-.02... | .015 | .030 | .35 | 1.42 | .035 | .024 | .055 | .126 | SMC...-3.0 |
| | 3.OSIR.015M-SNAP-.02... | .015 | .030 | .63 | 1.97 | | | | | |
| 4.0 | 4.OSIR.015S-SNAP-.02... | .015 | .030 | .35 | 1.42 | .035 | .024 | .075 | .161 | SMC...-4.0 |
| | 4.OSIR.015M-SNAP-.02... | .015 | .030 | .63 | 1.97 | | | | | |
| | 4.OSIR.015L-SNAP-.02... | .015 | .030 | .83 | 2.36 | | | | | |
| | 4.OSIR.023S-SNAP-.03... | .023 | .047 | .35 | 1.42 | | | | | |
| | 4.OSIR.023M-SNAP-.03... | .023 | .047 | .63 | 1.97 | .047 | .035 | | | |
| | 4.OSIR.023L-SNAP-.03... | .023 | .047 | .83 | 2.36 | | | | | |
| | 4.OSIR.031S-SNAP-.05... | .031 | .062 | .35 | 1.42 | | | | | |
| | 4.OSIR.031M-SNAP-.05... | .031 | .062 | .63 | 1.97 | | | | | |
| 6.0 | 4.OSIR.031L-SNAP-.05... | .031 | .062 | .83 | 2.36 | .063 | .051 | .114 | .240 | SMC...-6.0 |
| | 6.OSIR.031S-SNAP-.05... | .031 | .062 | .35 | 1.42 | | | | | |
| | 6.OSIR.031M-SNAP-.05... | .031 | .062 | .63 | 1.97 | | | | | |
| | 6.OSIR.031L-SNAP-.05... | .031 | .062 | .83 | 2.36 | | | | | |
| | 6.OSIR.036S-SNAP-.05... | .036 | .072 | .35 | 1.42 | | | | | |
| | 6.OSIR.036M-SNAP-.05... | .036 | .072 | .63 | 1.97 | | | | | |
| | 6.OSIR.036L-SNAP-.05... | .036 | .072 | .83 | 2.36 | | | | | |
| | 6.OSIR.039S-SNAP-.05... | .039 | .078 | .35 | 1.42 | | | | | |
| | 6.OSIR.039M-SNAP-.05... | .039 | .078 | .63 | 1.97 | | | | | |
| | 6.OSIR.039L-SNAP-.05... | .039 | .078 | .83 | 2.36 | | | | | |
| | 6.OSIR.047S-SNAP-.05... | .047 | .094 | .35 | 1.42 | | | | | |
| | 6.OSIR.047M-SNAP-.05... | .047 | .094 | .63 | 1.97 | | | | | |
| 6.OSIR.047L-SNAP-.05... | .047 | .094 | .83 | 2.36 | | | | | | |
| 6.OSIR.062S-SNAP-.07... | .062 | .125 | .35 | 1.42 | .079 | .067 | | | | |
| 6.OSIR.062M-SNAP-.07... | .062 | .125 | .63 | 1.97 | | | | | | |
| 6.OSIR.062L-SNAP-.07... | .062 | .125 | .83 | 2.36 | | | | | | |


Boring & Grooving Inserts



Micro - Double Ended

| Insert Dia. | Ordering Code | Groove Std. | Dimensions Inch | | | | | | Min. Bore Dia. | Toolholder |
|-------------|--------------------------|-------------|-----------------|-----|------|------|------|------|----------------|------------|
| d mm | RH | m (H13) | W | L1 | L | B | t | F | Inch | |
| 6.0 | 6.0SIR1.6S-D3770S-1.5... | .063 | .078 | .35 | 1.42 | .071 | .059 | .114 | .24 | SMC...-6.0 |
| | 6.0SIR1.6M-D3770S-1.5... | .063 | .078 | .63 | 1.97 | | | | | |
| | 6.0SIR1.6L-D3770S-1.5... | .063 | .078 | .83 | 2.36 | | | | | |
| | 6.0SIR2.0S-D3770D-1.8... | .079 | .094 | .35 | 1.42 | .079 | .071 | .114 | | |
| | 6.0SIR2.0M-D3770D-1.8... | .079 | .094 | .63 | 1.97 | | | | | |
| | 6.0SIR2.0L-D3770D-1.8... | .079 | .094 | .83 | 2.36 | | | | | |

CIRCLIP - Face Grooves



Micro (Partial Profile) - Double Ended

| Insert Dia. | Ordering Code | Dimensions Inch | | | | | Inner Groove Ø | Outer Groove Ø |
|-------------|--------------------------|-----------------|------|-------|------|------------|----------------|----------------|
| d mm | RH | W | t | L | F | Sleeve | | |
| 4.0 | 4.0SIR.031A-CIRC-.055... | .031 | .043 | 1.969 | .076 | SMC...-4.0 | .138 | .198 |
| | 4.0SIR.041A-CIRC-.063... | .041 | .051 | | | | .130 | .212 |
| | 4.0SIR.047A-CIRC-.071... | .047 | .059 | | | | .122 | .216 |
| | 4.0SIR.058A-CIRC-.082... | .058 | .075 | | | | .110 | .226 |
| | 4.0SIR.062A-CIRC-.086... | .062 | .083 | | | | .106 | .230 |
| 6.0 | 6.0SIR.031A-CIRC-.055... | .031 | .043 | 1.969 | .126 | SMC...-6.0 | .216 | .276 |
| | 6.0SIR.041A-CIRC-.063... | .041 | .051 | | | | .209 | .291 |
| | 6.0SIR.047A-CIRC-.071... | .047 | .059 | | | | .200 | .294 |
| | 6.0SIR.058A-CIRC-.082... | .058 | .075 | | | | .189 | .305 |
| | 6.0SIR.062A-CIRC-.086... | .062 | .083 | | | | .185 | .309 |
| | 6.0SIR.072A-CIRC-.094... | .072 | .087 | | | | .177 | .321 |
| | 6.0SIR.078A-CIRC-.088... | .078 | .087 | | | | .169 | .325 |
| | 6.0SIR.088A-CIRC-.110... | .088 | .088 | | | | .161 | .337 |

Boring & Grooving Inserts



For Grooving and Turning Solutions
visit

GROOVEX
Innovative Grooving & Turning Solutions
www.vargususa.com

MINIPRO

MiniPro Toolholders

PowerBore Toolholders | Micro Toolholders


Vardex Ordering Code System

PowerBore Toolholders

| | | | | | | |
|--|--|---|---|---|----------------|--|
| C 1 | 06 2 | - | 23 3 | C 4 | 40 5 | 5 6 |
| 1 - Shank Style C - Carbide S - Steel | 2 - Shank Dia. 05 - 5/32" - .156 06 - 3/16" - .187 08 - 1/4" - .250 10 - 5/16" - .312 12 - 3/8" - .375 16 - 1/2" - .500 | 3 - Bar Dia. [D₁] 21 - .165 23 - .180 24 - .187 26 - .203 32 - .250 40 - .312 | 4 - Insert Shape C - Diamond 80 Deg.  T - Triangle  W - Trigon 80 Deg.  | 5 - Holder Length [L₂] 23 - 2.25 25 - 2.50 27 - 2.75 30 - 3.00 35 - 3.50 40 - 4.00 45 - 4.50 50 - 5.00 60 - 6.00 | | 6 - Front Relief Angle 0, 5, 7 |

Micro Toolholders (Sleeves)

| | | | | | |
|--|--|---|---|---|---------------|
| S 1 | M 2 | C 3 | 0625 4 | - | 3 5 |
| 1 - Holder Shape S - Sleeve (Double Ended) | 2 - Holder Type M - Micro (Double Ended) | 3 - Cooling C - Coolant Channel | 4 - Holder Dia. 050 - 1/2" 0625 - 5/8" 075 - 3/4" | 5 - Bore Size Micro Size (mm) 3, 4, 6, 8, 10 | |



Alloy Steel Shanks - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|-------------|-------------|-------|----------|
| | | | A | D | D1 | M | L2 | L1 | Insert Type | Screw | Torx Key |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | | | |
| 3/16" | S06-21C257 | 41546 | 7° | .187 | .165 | .180 | 2.500 | .500 | CD0W | VS01 | VT51 |
| | S06-23C255 | 41547 | 5° | .187 | .180 | .208 | 2.500 | | | | |
| | S06-24C255 | 41548 | 5° | .187 | .187 | .230 | 2.500 | | | | |
| | S06-24C250 | 41543 | 0° | .187 | .187 | .244 | 2.500 | | | | |
| 1/4" | S08-32C305 | 41550 | 5° | .250 | .250 | .290 | 3.000 | D1=D | | | |
| | S08-32C300 | 41551 | 0° | .250 | .250 | .300 | 3.000 | | | | |


Solid Carbide Shank - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|-------------|-------------|-------|----------|
| | | | A | D | D1 | M | L2 | L1 | Insert Type | Screw | Torx Key |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | | | |
| 5/32" | C05-21C607 | 41552 | 7° | .156 | .165 | .180 | 6.000 | .500 | CD0W | VS01 | VT51 |
| | C06-23C405 | 41553 | 5° | .187 | .180 | .208 | 4.000 | | | | |
| 3/16" | C06-24C405 | 41554 | 5° | .187 | .187 | .230 | 4.000 | D1=D | | | |
| | C06-24C400 | 41555 | 0° | .187 | .187 | .244 | 4.000 | | | | |
| 1/4" | C08-32C405 | 41556 | 5° | .250 | .250 | .290 | 4.000 | D1=D | | | |
| | C08-32C400 | 41557 | 0° | .250 | .250 | .300 | 4.000 | | | | |

Alloy Steel Shanks - Oversize

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | Spare Parts | | | |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|-------------|-------------|-------|----------|
| | | | A | D | D1 | M | L2 | L1 | Insert Type | Screw | Torx Key |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | | | |
| 3/8" | S12-23C235 | 41558 | 5° | .375 | .180 | .208 | 2.250 | 1.000 | CD0W | VS01 | VT51 |
| | S12-26C235 | 41559 | 5° | .375 | .203 | .230 | 2.250 | | | | |
| | S12-26C230 | 41560 | 0° | .375 | .203 | .244 | 2.250 | | | | |
| | S12-32C255 | 41561 | 5° | .375 | .250 | .290 | 2.500 | 1.250 | | | |
| | S12-32C250 | 41562 | 0° | .375 | .250 | .300 | 2.500 | | | | |

* 5° angle for facing and thru-hole boring.
 * 0° angle for thru-hole boring and boring to a shoulder.



Alloy Steel Shanks - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Spare Parts | | |
|-------|---------------|---------|-----------------|----------|-----------|----------------|-------------|--------------|----------|
| | | | A | D=D1 | M | L2 | Insert Type | Screw | Torx Key |
| | | | Angle | Bar Dia. | Min. Bore | Overall Length | TD0W | VS01 VS40 | VT51 |
| 3/16" | S06-24T355 | 41563 | 5° | .187 | .270 | 3.500 | | | |
| | S06-24T350 | 41564 | 0° | .187 | .270 | 3.500 | | | |
| 1/4" | S08-32T405 | 41565 | 5° | .250 | .300 | 4.000 | | | |
| | S08-32T400 | 41566 | 0° | .250 | .300 | 4.000 | | | |
| 5/16" | S10-40T405 | 41567 | 5° | .312 | .360 | 4.000 | | | |
| | S10-40T400 | 41568 | 0° | .312 | .360 | 4.000 | | | |


Solid Carbide Shank - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Spare Parts | | |
|-------|---------------|---------|-----------------|----------|-----------|----------------|-------------|--------------|----------|
| | | | A | D=D1 | M | L2 | Insert Type | Screw | Torx Key |
| | | | Angle | Bar Dia. | Min. Bore | Overall Length | TD0W | VS01 VS40 | VT51 |
| 3/16" | C06-24T405 | 41569 | 5° | .187 | .270 | 4.000 | | | |
| | C06-24T400 | 41570 | 0° | .187 | .270 | 4.000 | | | |
| 1/4" | C08-32T405 | 41571 | 5° | .250 | .300 | 4.000 | | | |
| | C08-32T400 | 41572 | 0° | .250 | .300 | 4.000 | | | |
| 5/16" | C10-40T405 | 41573 | 5° | .312 | .360 | 4.000 | | | |
| | C10-40T400 | 41574 | 0° | .312 | .360 | 4.000 | | | |

Alloy Steel Shanks - Oversize

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | | Spare Parts | | |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|------------|-------------|--------------|----------|
| | | | A | D | D1 | M | L2 | L1 | Insert Type | Screw | Torx Key |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | TD0W | VS01 VS40 | VT51 |
| 3/8" | S12-26T255 | 41575 | 5° | .375 | .203 | .270 | 2.500 | 1.000 | | | |
| | S12-26T250 | 41576 | 0° | .375 | .203 | .270 | 2.500 | | | | |
| | S12-32T275 | 41577 | 5° | .375 | .250 | .300 | 2.750 | 1.250 | | | |
| | S12-32T270 | 41578 | 0° | .375 | .250 | .300 | 2.750 | | | | |
| | S12-40T305 | 41579 | 5° | .375 | .312 | .360 | 3.000 | 1.500 | | | |
| | S12-40T300 | 41580 | 0° | .375 | .312 | .360 | 3.000 | | | | |

* 5° angle for facing and thru-hole boring.
 * 0° angle for thru-hole boring and boring to a shoulder.



Alloy Steel Shanks - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Spare Parts | | | | | |
|-------|---------------|---------|-----------------|----------|-----------|------------|----------------------|-------|----------|--|--|--|
| | | | A | D=D1 | M | L | Insert Type | Screw | Torx Key | | | |
| | | | Angle | Bar Dia. | Min. Bore | Bar Length | | | | | | |
| 3/16" | S06-24W255 | 41581 | 5° | .187 | .230 | 2.500 | WCOW4213 WCOW4214 | VS40 | VT51 | | | |
| | S06-24W250 | 41582 | 0° | .187 | .244 | | | | | | | |
| 1/4" | S08-32W405 | 41583 | 5° | .250 | .300 | 4.000 | | | | | | |
| | S08-32W400 | 41584 | 0° | .250 | .300 | | | | | | | |


Solid Carbide Shank - Standard Size

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Spare Parts | | | | | |
|-------|---------------|---------|-----------------|----------|-----------|------------|----------------------|-------|----------|--|--|--|
| | | | A | D=D1 | M | L | Insert Type | Screw | Torx Key | | | |
| | | | Angle | Bar Dia. | Min. Bore | Bar Length | | | | | | |
| 3/16" | C06-24W405 | 41585 | 5° | .187 | .230 | 4.000 | WCOW4213 WCOW4214 | VS40 | VT51 | | | |
| | C06-24W400 | 41586 | 0° | .187 | .244 | | | | | | | |
| 1/4" | C08-32W405 | 41587 | 5° | .250 | .290 | 4.000 | | | | | | |
| | C08-32W400 | 41588 | 0° | .250 | .300 | | | | | | | |

Alloy Steel Shanks - Oversize

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | | Spare Parts | | | | | |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|------------|----------------------|-------|----------|--|--|--|
| | | | A | D | D1 | M | L2 | L1 | Insert Type | Screw | Torx Key | | | |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | | | | | | |
| 3/8" | S12-26W235 | 41589 | 5° | .375 | .203 | .230 | 2.250 | .500 | WCOW4213 WCOW4214 | VS40 | VT51 | | | |
| | S12-26W230 | 41590 | 0° | .375 | .203 | .244 | 2.250 | | | | | | | |
| | S12-32W255 | 41591 | 5° | .375 | .250 | .290 | 2.500 | .750 | | | | | | |
| | S12-32W250 | 41592 | 0° | .375 | .250 | .300 | 2.500 | | | | | | | |

* 5° angle for facing and thru-hole boring.
 * 0° angle for thru-hole boring and boring to a shoulder.



Alloy Steel Shanks - Standard Size

Spare Parts

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Insert Type | Screw | Torx Key |
|-------|---------------|---------|-----------------|----------|-----------|------------|----------------------|-------|----------|
| | | | A | D=D1 | M | L | | | |
| | | | Angle | Bar Dia. | Min. Bore | Bar Length | | | |
| 5/16" | S10-40W405 | 41593 | 5° | .312 | .360 | 4.000 | WC0W5013 WC0W5014 | VS41 | VT51 |
| | S10-40W400 | 41594 | 0° | .312 | .360 | | | | |



Solid Carbide Shank - Standard Size

Spare Parts

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | Insert Type | Screw | Torx Key |
|-------|---------------|---------|-----------------|----------|-----------|------------|----------------------|-------|----------|
| | | | A | D=D1 | M | L | | | |
| | | | Angle | Bar Dia. | Min. Bore | Bar Length | | | |
| 5/16" | C10-40W405 | 41597 | 5° | .312 | .360 | 4.000 | WC0W5013 WC0W5014 | VS41 | VT51 |
| | C10-40W400 | 41598 | 0° | .312 | .360 | | | | |




Alloy Steel Shanks - Oversize

Spare Parts

| Shank | Ordering Code | EDP No. | Dimensions Inch | | | | | | Insert Type | Screw | Torx Key |
|-------|---------------|---------|-----------------|------------|----------|-----------|----------------|------------|----------------------|-------|----------|
| | | | A | D | D1 | M | L2 | L1 | | | |
| | | | Angle | Shank Dia. | Bar Dia. | Min. Bore | Overall Length | Bar Length | | | |
| 3/8" | S12-40W305 | 41599 | 5° | .375 | .312 | .360 | 3.000 | 1.500 | WC0W5013 WC0W5014 | VS41 | VT51 |
| | S12-40W300 | 41600 | 0° | .375 | .312 | .360 | 3.000 | | | | |



* 5° angle for facing and thru-hole boring.
 * 0° angle for thru-hole boring and boring to a shoulder.



Spare Parts



Micro - Double Ended

| Micro Insert Dia. d mm | Shank Dia. D | Ordering Code | EDP No. | Dimensions Inch | | | Location Screw* | | | Clamping Screw x 3 | |
|---------------------------|-----------------|---------------|---------|-----------------|--------------|-----------|-----------------|------|------|--------------------|------|
| | | | | L | L1 | L0 | Screw | M | Key | Screw | Key |
| 3 | .50 | SMC050-3.0 | 41075 | 3.15 | .35 - Short | 3.50 | 4GISM8X28 | 1.10 | K4.0 | M4X.7X4.0 | K2.0 |
| | | SMC0625-3.0 | 40210 | | .63 - Medium | 3.78 | 4GISM8X21 | .83 | | | |
| | SMC075-3.0 | 41080 | 3.74 | .35 - Short | 4.09 | 4GISM8X49 | 1.93 | | | | |
| .63 - Medium | 4.37 | 4GISM8X42 | | 1.65 | | | | | | | |
| .75 - Long | 4.57 | 4GISM8X37 | | 1.46 | | | | | | | |
| 4 | .50 | SMC050-4.0 | 41092 | 3.15 | .35 - Short | 3.50 | 4GISM8X28 | 1.10 | | | |
| | | .63 - Medium | 3.78 | | 4GISM8X21 | .83 | | | | | |
| | | .83 - Long | 3.98 | | 4GISM8X16 | .63 | | | | | |
| | .63 | SMC0625-4.0 | 40212 | 3.74 | .35 - Short | 4.09 | 4GISM8X49 | 1.93 | | | |
| | | .63 - Medium | 4.37 | | 4GISM8X42 | 1.65 | | | | | |
| | | .75 - Long | 4.57 | | 4GISM8X37 | 1.46 | | | | | |
| 6 | .50 | SMC050-6.0 | 41517 | 3.15 | .35 - Short | 3.50 | 4GISM8X28 | 1.10 | | | |
| | | .63 - Medium | 3.78 | | 4GISM8X21 | .83 | | | | | |
| | | .83 - Long | 3.98 | | 4GISM8X16 | .63 | | | | | |
| | .63 | SMC0625-6.0 | 40214 | 3.74 | .35 - Short | 4.09 | 4GISM8X49 | 1.93 | | | |
| | | .63 - Medium | 4.37 | | 4GISM8X42 | 1.65 | | | | | |
| | | .75 - Long | 4.57 | | 4GISM8X37 | 1.46 | | | | | |
| 8 | .63 | SMC0625-8.0 | 40248 | 3.74 | .47 - Short | 4.21 | 4GISM8X33 | 1.30 | | | |
| | | .79 - Medium | 4.53 | | 4GISM8X25 | .98 | | | | | |
| | | 1.10 - Long | 4.84 | | 4GISM8X17 | .67 | | | | | |
| 10 | .63 | SMC0625-10.0 | 41093 | 3.74 | .59 - Short | 4.33 | 4GISM8X30 | 1.18 | | | |
| | | .98 - Medium | 4.72 | | 4GISM8X20 | .79 | | | | | |
| | | 1.38 - Long | 5.12 | | 4GISM8X10 | .39 | | | | | |
| | | SMC075-10.0 | 41083 | | | | | | | | |

* Every toolholder package contains the full range of location screws needed.

40184
41093
41083



For Grooving and Turning Solutions
visit
GROOVEX
Innovative Grooving & Turning Solutions
www.vargususa.com

MINIPRO

MiniPro Technical Data

Recommended Grades, Cutting Speeds Vc [ft/min], Feed f [Inch/rev] and Max Depth [Inch]



| Material Group | Vargus No. | Material | Hardness Brinell HB | Vc [ft/min] | | Feed [Inch/rev] | | | Max Depth [Inch] | | | |
|-------------------------------------|---------------------------------|---|-----------------------------------|-----------------|-------------|-----------------|--------------|----------------|------------------|------|--------------|------|
| | | | | Coated | | Power Bore | Micro Boring | Micro Grooving | PowerBore | | Micro Boring | |
| | | | | VTX (PowerBore) | VMX (Micro) | | | | TDOW CDOW | WDOW | | |
| P Steel | 1 | Unalloyed Steel | Low Carbon (C=0.1-0.25%) | 125 | 377-623 | 164-394 | .0098 | .0020 | .0012 | .018 | .024 | .016 |
| | 2 | | Medium Carbon (C=0.25-0.55%) | 150 | 328-574 | 131-328 | .0079 | .0016 | .0008 | .018 | .024 | .016 |
| | 3 | | High Carbon (C=0.55-0.85%) | 170 | 295-541 | 98-262 | .0059 | .0012 | .0004 | .018 | .024 | .016 |
| | 4 | Low Alloy Steel (alloying elements≤5%) | Non Hardened | 180 | 279-476 | 164-230 | .0079 | .0016 | .0008 | .014 | .020 | .012 |
| | 5 | | Hardened | 275 | 246-459 | 131-197 | .0059 | .0016 | .0004 | .014 | .020 | .012 |
| | 6 | | Hardened | 350 | 230-443 | 98-164 | .0039 | .0012 | .0004 | .014 | .020 | .012 |
| | 7 | High Alloy Steel (alloying elements>5%) | Annealed | 200 | 230-361 | 98-164 | .0039 | .0016 | .0008 | .007 | .016 | .006 |
| | 8 | | Hardened | 325 | 164-328 | 82-131 | .0020 | .0012 | .0004 | .007 | .016 | .006 |
| | 9 | Cast Steel | Low Alloy (alloying elements<5%) | 200 | 246-459 | 98-164 | .0098 | .0016 | .0008 | .007 | .016 | .006 |
| | 10 | | High Alloy (alloying elements>5%) | 225 | 197-394 | 82-131 | .0039 | .0016 | .0008 | .007 | .016 | .006 |
| M Stainless Steel | 11 | Stainless Steel Ferritic | Non Hardened | 200 | 230-427 | 197-328 | .0079 | .0016 | .0004 | .009 | .020 | .008 |
| | 12 | | Hardened | 330 | 197-377 | 131-197 | .0031 | .0012 | .0004 | .007 | .016 | .006 |
| | 13 | Stainless Steel Austenitic | Austenitic | 180 | 295-459 | 164-295 | .0079 | .0016 | .0004 | .009 | .020 | .008 |
| | 14 | | Super Austenitic | 200 | 131-361 | 131-197 | .0031 | .0016 | .0004 | .007 | .016 | .006 |
| | 15 | Stainless Steel Cast Ferritic | Non Hardened | 200 | 295-394 | 131-197 | .0079 | .0016 | .0008 | .009 | .020 | .008 |
| | 16 | | Hardened | 330 | 213-361 | 98-164 | .0031 | .0012 | .0004 | .007 | .016 | .006 |
| 17 | Stainless Steel Cast Austenitic | Austenitic | 200 | 279-361 | 131-197 | .0079 | .0016 | .0008 | .009 | .020 | .008 | |
| 18 | | Hardened | 330 | 197-328 | 98-164 | .0031 | .0012 | .0004 | .007 | .016 | .006 | |
| K Cast Iron | 28 | Malleable Cast Iron | Ferritic (short chips) | 130 | 230-525 | 164-230 | .0059 | .0008 | .0008 | .012 | .016 | .010 |
| | 29 | | Pearlitic (long chips) | 230 | 197-476 | 164-230 | .0039 | .0004 | .0004 | .012 | .016 | .010 |
| | 30 | Grey Cast Iron | Low Tensile Strength | 180 | 230-427 | 164-230 | .0059 | .0008 | .0008 | .018 | .024 | .016 |
| | 31 | | High Tensile Strength | 260 | 197-377 | 131-197 | .0039 | .0004 | .0059 | .018 | .024 | .016 |
| | 32 | Nodular Sg Iron | Ferritic | 160 | 410-525 | 164-230 | .0059 | .0008 | .0008 | .018 | .024 | .016 |
| 33 | Pearlitic | | 260 | 295-394 | 197-262 | .0039 | .0004 | .0004 | .018 | .024 | .016 | |
| N Non-Ferrous Metals | 34 | Aluminium Alloys Wrought | Non Aging | 60 | 328-1,198 | 328-984 | .0118 | .0012 | .0012 | .025 | .039 | .020 |
| | 35 | | Aged | 100 | 262-722 | 328-492 | .0079 | .0012 | .0012 | .025 | .039 | .020 |
| | 36 | Aluminium Alloys | Cast | 75 | 656-1,312 | 328-492 | .0118 | .0012 | .0012 | .025 | .039 | .020 |
| | 37 | | Cast & Aged | 90 | 656-919 | 197-328 | .0079 | .0012 | .0012 | .025 | .039 | .020 |
| | 38 | Aluminium Alloys | Cast Si 13-22% | 130 | 197-591 | 328-492 | .0118 | .0008 | .0008 | .025 | .039 | .020 |
| | 39 | Copper and Copper Alloys | Brass | 90 | 262-738 | 197-328 | .0118 | .0012 | .0012 | .025 | .039 | .020 |
| 40 | Bronze And Non Leaded Copper | | 100 | 262-837 | 197-328 | .0079 | .0012 | .0012 | .025 | .039 | .020 | |
| S Heat Resistant Material | 19 | High Temperature Alloys | Annealed (iron based) | 200 | 148-197 | 82-148 | .0079 | .0016 | .0004 | .009 | .020 | .008 |
| | 20 | | Aged (iron based) | 280 | 98-164 | 66-98 | .0031 | .0012 | .0004 | .007 | .016 | .006 |
| | 21 | | Annealed (nickel or cobalt based) | 250 | 66-98 | 49-66 | .0031 | .0004 | .0004 | .007 | .016 | .006 |
| | 22 | | Aged (nickel or cobalt based) | 350 | 49-82 | 33-49 | .0020 | .0004 | .0004 | .007 | .016 | .006 |
| | 23 | Titanium Alloys | Pure 99.5 Ti | 400Rm | 459-558 | 197-328 | .0020 | .0008 | .0008 | .007 | .016 | .006 |
| 24 | α+β Alloys | | 1050Rm | 164-230 | 131-164 | .0020 | .0008 | .0008 | .007 | .016 | .006 | |
| H Hardened Material | 25 | Extra Hard Steel | Hardened & Tempered | 45-50HRc | 148-213 | 66-148 | .0008 | .0004 | .0004 | .002 | .008 | .002 |
| | 26 | | | 51-55HRc | 148-197 | 66-131 | .0004 | .0004 | .0004 | .002 | .004 | .002 |

Grades

VTX

General use carbide grade. TiAlN coated.

VMX

General use carbide grade for Micro inserts. TiN coated.

| Spare Parts for PowerBore line | | |  |  | | |
|---|------------|-------------------------------------|--|---|----------|-----------|
| Insert | Boring Bar | Insert | Torx Screw | Screw Description | Torx Key | Torx Size |
|  | A | CD0W | VS01 | 1-72 Oval X .109LG. | VT51 | T6 |
|  | B | TD0W Min. Bore .28 > Bore .28 | VS01 VS40 | 1-72 Oval X .109LG. M2 X 0.4 X .152LG. | | |
|  | E | WC0W4213, WC0W4214 | VS40 | M2 X 0.4 X .152LG. | | |
| | F | WC0W5013, WC0W5014 | VS41 | M2 X 0.4 X .193LG. | | |




SHAVIV
Leading Deburring Solutions

The Finishing Touch



SHAVIV hand deburring tools offer a range of cost-effective and efficient solutions to companies across all industry sectors that need to remove burrs from different materials. The tools are renowned for providing “the finishing touch” in a host of applications, such as hole edges, straight edges, flat surfaces, keyways and corners.





GROOVEX
Innovative Grooving & Turning Solutions

The increasingly popular and rapidly growing **GROOVEX** line, established in 2011, provides a comprehensive line of products for grooving, boring, turning and micro-machining solutions across all industry sectors.



VG-Cut



microSCOPE



Mini-V



GrooVical

With a network of 13 international companies and hundreds of distributors, warehouses and certified ISO 9001 manufacturing facilities, VARGUS Ltd. serves customers in more than 100 countries around the globe. A customer-focused organization, VARGUS Ltd. is committed to providing innovative products and solutions of the highest quality and excellent value, and is renowned for its technical expertise and uncompromising service.



VARGUS Ltd. - Global Headquarters +972 4 9855 101 | mrktg@vargus.com

 **VARGUS USA** +1 800 828 8765 / 608 756 4930 | sales@vargususa.com

EUROPE

 **DENMARK**
VARGUS Scandinavia
+45 8794 4100
vargus@vargus.dk

 **FRANCE**
VARGUS France
+33 1 4601 7060
commercial@vargus.fr

 **GERMANY**
VARGUS Germany
+49 7043 36 161
info@vargus.de

 **ISRAEL**
NEUMO-VARGUS
+972 3 537 3275
neumo@neumo-vargus.co.il

 **POLAND**
VARGUS Poland
+48 46 834 9904 / 46 831 5140
vargus@neumo.pl

 **SPAIN**
VARGUS Ibérica
+34 977 52 49 00
sales@vargus.es

 **SWITZERLAND**
VARGUS Switzerland
+41 41784 2121
info@vargus.ch

 **TURKEY**
VARGUS Turkey
+90 212 875 01 41
info@vargusturkey.com

 **UNITED KINGDOM**
VARGUS Tooling UK
+44 1952 583 222
tooling.uk@vargustooling.co.uk

ASIA

 **CHINA**
VARGUS China
+86 21 516 88300
info@varguschina.net

 **INDIA**
VARGUS India
+91 2135 654748
info@vargusindia.com

LATIN AMERICA

 **BRAZIL**
VARGUS Brazil
+55 47 3084 8001
info@vargus.com.br



VARGUS GENiUS™ | Tool Selector and CNC Program Generator



The most popular and advanced thread turning and thread milling software on the market today.

Available in 4 versions at www.vargus.com

