



## Product Data Sheet

### 3.0 mil Carton Sealing Tape



Effective 04/2019

#### Product Description:

High-performance grade acrylic packaging tape for heavy duty manual and automated industrial sealing of cartons exposed to rough handling and load stress. With excellent quick stick and superior clarity in a wide range of applications, environments, and temperatures

#### Item ID Numbers:

30CST255C , 30CST355C

#### Nominal Values:

Film thickness:	1.97 mil
Adhesive:	Acrylic
Adhesive thickness:	1.02 mil
Color:	Clear
Total Thickness:	2.99 MIL
Adhesion to Steel: (min.)	28.22 oz/in (ASTM D3330)
Breaking Strength: (Max, Min 10%)	35.27 lb./in (ASTM D3759)
Elongation: (Max, Min 10%)	190% (ASTM D3759)
Shear strength (on paper)	3.33 hr. (min.) (ASTM D3654)
Rolling ball tack (Max.)	551 Mils PSTC-6

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

#### Wrap Tite, Inc.

6200 Cochran Rd.  
Solon, Ohio 44139

**Toll Free:** 888-WRAP TITE (972-7848)

**Fax:** 440-349-5432

[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

