



Product Data Sheet

Filament Tape



Effective 01/2017

Product Description:

A high tensile strength, high adhesion, rubber based, uni-directional, glass reinforced pressure sensitive tape designed for many demanding packaging applications.

Item ID Numbers:

FT3909, FT3912, FT3918, FT3924, FT3936, FT3948

Nominal Values:

Backing:	1.0 mil(25 mic.)Biaxial-Oriented PP Film
Adhesive:	Synthetic Rubber/Resin
Color:	Clear
Total Thickness: (PSTC-133)	4 MIL
Adhesion to Steel(at 90° peel angle)	60 oz/in (PSTC-101)
Tensile Strength:	100 lb/in (PSTC-131)
Elongation:	3 % (PSTC-131)
Quick Stick To Kraft To Steel	7 oz / in 31 oz/ in
Shear to Kraft Paper (hours)(1"x1"x1000g)	>96

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
 6200 Cochran Rd.
 Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

