



PRODUCT SPECIFICATION REPORT



ZEP FAST GASKET CLEAR™

DESCRIPTION

A clear silicone rubber bonding and sealing compound in a convenient pressurized package.

FEATURES

BENEFITS

- | | |
|--|--|
| <ul style="list-style-type: none"> • Durable • Wide Temperature Range • Easy To Use • Convenient | <ul style="list-style-type: none"> • 100% silicone provides permanent flexibility and adhesion. • Effective temperature range is -60°F to 450°F. • Produces a fine bead, at the touch of a finger, for neater jobs and less waste. • No caulking gun or squeeze tube needed. |
|--|--|

APPLICATIONS

Use to seal joints and cracks in the roof and sides of school buses, construction and farm equipment. Create formed-in-place gaskets for gear boxes, compressors and pumps.

Note: DO NOT USE ON: Intake/exhaust manifold
Head Gasket
Carburetor Base Gasket

COMPANION PRODUCTS

Zepunch, Zepteen, Zeprotreat, Zep P.L.S., Zepride, Zep Orange Split, Big Orange, Big Orange E, Orange Gel

SPECIFICATIONS

Physical form Pressurized Container	Shelf Life 1 year minimum
Can size 9 fl. oz.	Flammability Non-flammable
Net weight 7.25 oz. avdp. (205 g)	D.O.T. Shipping Label Consumer commodity
Storage Temperature 120°F maximum	

PACKAGING

Tube



PRODUCT LABEL

PROD. #1430
1104

ZEP FAST GASKET CLEAR™

clear

FAST GASKET™
ADHESIVE/SEALANT

SPECIMEN

Certified to Federal Specification TT-S-001543A, TT-S-00230C, Mil-A-46106


FAST GASKET BONDS, CAULKS, SEALS, FASTENS, INSULATES, WEATHERPROOFS AND REPAIRS MANY TYPES OF MATERIALS (See rear panel for additional uses)

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG.

KEEP OUT OF REACH OF CHILDREN
NET WT. 7.25 oz. (205 grams)

PROD. #1430 704A

POWER CAN DISPENSING INSTRUCTIONS



1. Make sure the surface is clean and dry. Snap off the tamper proof tab from nozzle and remove cap before dispensing.



2. Turn nozzle counterclockwise for a quarter turn to open. This will open the valve and open the lever. Depress lever to dispense. Turn nozzle clockwise to close lever to original position. Replace cap.



3. Relocate nozzle back over valve, with the two thick plastic fins pointing to the back hinge and front of lever. Swing lever back over nozzle to original position, slightly press the nozzle backwards towards the hinge. Use lever to firmly "click" nozzle back in position.



4. To remove dried sealant from nozzle leave the nozzle in the closed position and swing the lever over the nozzle as shown. Pull nozzle forward to remove, clean nozzle tip with a paper clip or compressed air line.

- Permanently Flexible
- 100% silicone rubber
- Ideal for Maintenance & "Form-in-Place Gasket"
- -60°F (-51°C) to 450°F (232°C)

Fast Gasket Clear Adhesive/Sealant meets a variety of your sealing needs. This multi-surface adhesive/sealant adheres to glass, non-oily woods, metal, porcelain, ceramic, painted surfaces as well as many plastics and rubbers.

Uses: 1. Seals Windows, Doors and Pipe Joints 2. Caulks Duct Work and Equipment Housings 3. Bonds Appliance Parts and Sign Letters 4. Fastens Glass to Metal in Electronic Assemblies 5. Insulates and Seals Holes in Walls where Housings Telephone Cables, Refrigerant Lines have entered 6. Weatherproofs Truck Cabs, Cable Connectors, Motors and Switches 7. Oils Pans 8. Oil Pumps 9. Water Pumps 10. Valve Covers

DO NOT USE ON: 1. Intake/exhaust manifold 2. Head Gasket 3. Carburetor Base Gasket.

When fully cured and washed, the product meets the requirements of FDA regulation NO. 21CFR 177.2600. Fast Gasket will bond, caulk, seal, fasten, insulate, protect and repair many types of materials. Fast Gasket offers unmatched performance even under the most severe operating conditions, such as weather, temperature extremes, chemicals and aging. Paints do not adhere well to this sealant. Complete painting before applying. This product also does not adhere well to oily woods such as cedar, teak and cypress. Not recommended for exterior, below-waterline marine applications.

DIRECTIONS:

1. Clean and dry surface. Remove any soap, oil or grease with appropriate Zep cleaner.
2. For a smooth seal, hold at 45° angle and apply.
3. If further cooling is needed, complete within 5 minutes. Remove excess sealant immediately with dry paper towel.
4. Normally sealant "skins" in 5 minutes, dries to touch in 1 hour, fully cures and bonds in 24 hours. Optimum strength.
5. After application to food processing equipment, allow Fast Gasket to cure completely, then wash thoroughly before using. Excess cured material can be removed by trimming with a sharp blade. Avoid undercutting the seal.
6. After use, leave small amount of silicone extending out of nozzle so silicone remaining in nozzle will cure and provide a protective plug. To reuse, remove plug or cured material and proceed as before.
7. Wipe hands with dry cloth and clean with heavy duty hand cleaner, such as Zep-O-Me, Zep-Clch or Zep Reach. Clean tools and clothing with non-flammable cleaning fluid.

CAUTION: Avoid contact with eyes and skin. Contact lens wearers should wash hands before installing or removing lenses. Sealant releases acetic acid (vinegar-like odor) during cure. Contents under pressure. Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F (48°C).

IN CASE OF CONTACT, immediately flush eyes with plenty of water for 15 minutes. Call a physician. Remove from skin with a dry cloth or paper towel.

CONTAINS: Dimethylsiloxane CAS 70131-67-8, Amorphous Silica CAS 7631-86-9, Ethyl Triacetoxysilane CAS 17689-77-9, Methyl Triacetoxysilane CAS 4253-34-3, Poly dimethylsiloxane CAS 63148-62-9

Proudly American Made
ZEP MANUFACTURING COMPANY
A division of Acuity Specialty Products Group, Inc.
ATLANTA, GEORGIA 30301
CLEAN ACROSS AMERICA AND THROUGHOUT THE WORLD™

AcuityBrands.

ZEP MANUFACTURING COMPANY

Your One Source for Cleaning and Maintenance Products

1-877-I BUY ZEP
(1-877-428-9937)